DK1 battery trading: methods

github.com/jacobazu/dk1-battery-trade · October 2026

A 2 MWh / 1 MW battery planned every day on my DK1 price forecast, with its risk, costs and P&L. Python, checked against the R version.

Plan	Mixed-integer linear program on the price forecast: 90% round trip, one cycle a day (Bradbury et al., 2014). Solved with SciPy.
Risk	EWMA-filtered historical simulation of the forecast errors (Hull and White, 1998; J.P. Morgan/Reuters, 1996), a 5% floor and the average below it, the Kupiec test (Kupiec, 1995), and four stress tests.
Loss limit	A limit on the worst 5% of scenarios (Rockafellar and Uryasev, 2000). Tested and not used.
Costs	Nord Pool fee and an assumed wear cost in the plan; Energinet's tariffs as a side case.
Tests	Daily differences tested with a Newey–West variance (Newey and West, 1987).
Rules	The plan only uses the forecast saved before the auction. Limits, cost cases and tests are set before running.

References

Bradbury, K., Pratson, L. and Patiño-Echeverri, D. (2014). Economic viability of energy storage systems based on price arbitrage potential in real-time U.S. electricity markets. *Applied Energy*.

Hull, J. and White, A. (1998). Incorporating volatility updating into the historical simulation method for value-at-risk. *Journal of Risk*.

J.P. Morgan/Reuters (1996). *RiskMetrics Technical Document*.

Kupiec, P. (1995). Techniques for verifying the accuracy of risk measurement models. *Journal of Derivatives*.

Newey, W. K. and West, K. D. (1987). A simple, positive semi-definite, heteroskedasticity and autocorrelation consistent covariance matrix. *Econometrica*.

Rockafellar, R. T. and Uryasev, S. (2000). Optimization of conditional value-at-risk. *Journal of Risk*.