



# Importance of Normalization

School of Information Studies  
Syracuse University

# Importance of Normalization

Different examples/vectors might differ greatly in length.

Example: For text documents, the vector lengths of long documents are much greater than short documents.

# An Example of Normalization in Information Retrieval

		a	against	but	camera	gallery	hit	husband	images	imagined
music.1	13	0	3	0	0	0	0	0	0	0
music.2	18	0	7	0	0	2	0	0	0	0
music.3	33	0	2	0	3	1	0	0	0	0
music.4	28	0	11	0	0	1	0	0	0	0
music.5	10	0	0	0	1	0	0	0	0	0
art.1	20	0	3	2	0	0	1	0	0	0
art.2	51	0	9	1	4	0	0	2	1	1
art.3	55	1	6	11	1	0	2	8	0	0
art.4	64	2	7	0	0	0	0	0	2	2
art.5	11	1	1	0	0	0	0	2	0	0

		instruments	melody	new	old	photographs	photography	songs	wife
music.1		3	1	0	0	0	0	0	0
music.2		0	0	1	1	0	0	0	0
music.3		0	0	2	1	0	0	3	0
music.4		0	0	2	0	0	0	0	1
music.5		0	1	2	1	0	0	1	0
art.1		0	0	1	0	0	1	0	1
art.2		0	0	3	3	1	4	0	1
art.3		1	0	5	2	0	3	0	2
art.4		0	0	1	0	0	0	0	2
art.5		0	0	0	0	1	1	0	0

Table 2: Bag-of-words vectors for five randomly selected stories classified as “music”, and five classified as “art” (but not music), from the *Times* corpus. The table shows a selection of the 700 features.

<http://www.stat.cmu.edu/~cshalizi/350/lectures/01/lecture-01.pdf>



# Longer Documents Tend to Be Far Away From Short Ones Based on Raw Euclidean Distance

		a	against	but	camera	gallery	hit	husband	images	imagined
music.1	13	0	3	0	0	0	0	0	0	0
music.2	18	0	7	0	0	2	0	0	0	0
music.3	33	0	2	0	3	1	0	0	0	0
music.4	28	0	11	0	0	1	0	0	0	0
music.5	10	0	0	0	1	0	0	0	0	0
art.1	20	0	3	2	0	0	1	0	0	0
art.2	51	0	9	1	4	0	0	2	2	1
art.3	55	1	6	11	1	0	2	8	0	0
art.4	64	2	7	0	0	0	0	0	0	2
art.5	11	1	1	0	0	0	0	2	0	0

  

		instruments	melody	new	old	photographs	photography	songs	wife
music.1		3	1	0	0	0	0	0	0
music.2		0	0	1	1	0	0	0	0
music.3		0	0	2	1	0	0	3	0
music.4		0	0	2	0	0	0	0	1
music.5		0	1	2	1	0	0	1	0
art.1		0	0	1	0	0	1	0	1
art.2		0	0	3	3	1	4	0	1
art.3		1	0	5	2	0	3	0	2
art.4		0	0	1	0	0	0	0	2
art.5		0	0	0	0	1	1	0	0

Table 2: Bag-of-words vectors for five randomly selected stories classified as “music”, and five classified as “art” (but not music), from the *Times* corpus. The table shows a selection of the 700 features.

<http://www.stat.cmu.edu/~cshalizi/350/lectures/01/lecture-01.pdf>

# Normalization by Document Length (L-1)

## 2.1 Normalization

Just looking at the Euclidean distances between document vectors doesn't work, at least if the documents are at all different in size. Instead, we need to **normalize** by document size, so that we can fairly compare short texts with long ones. There are (at least) two ways of doing this.

**Document length normalization** Divide the word counts by the total number of words in the document. In symbols,

$$\vec{x} \mapsto \frac{\vec{x}}{\sum_{i=1}^p x_i}$$

Notice that all the entries in the normalized vector are non-negative fractions, which sum to 1. The  $i^{\text{th}}$  component is thus the probability that if we pick a word out of the bag at random, it's the  $i^{\text{th}}$  entry in the lexicon.

# Normalization by Euclidean Length (L-2)

**Euclidean length normalization** Divide the word counts by the Euclidean length of the document vector:

$$\vec{x} \mapsto \frac{\vec{x}}{\|\vec{x}\|}$$

For search, normalization by Euclidean length tends to work a bit better than normalization by word-count, apparently because the former de-emphasizes words which are rare in the document.

**Cosine “distance”** is actually a similarity measure, not a distance:

$$d_{\cos} \vec{x}, \vec{y} = \frac{\sum_i x_i y_i}{\|\vec{x}\| \|\vec{y}\|}$$

It's the cosine of the angle between the vectors  $\vec{x}$  and  $\vec{y}$ .

# Compare Results With/Without Normalization

L 1

	Best match by similarity measure		
	Euclidean	Euclidean + word-count	Euclidean + length
music.1	art.5	art.4	art.4
music.2	art.1	music.4	music.4
music.3	music.4	music.4	art.3
music.4	music.2	art.1	art.3
music.5	art.5	music.3	music.3
art.1	music.1	art.4	art.3
art.2	music.4	art.4	art.4
art.3	art.4	art.4	art.4
art.4	art.3	art.3	art.3
art.5	music.1	art.3	art.3
error count	6	2	3

L 2

Table 3: Closest matches for the ten documents, as measured by the distances between bag-of-words vectors, and the total error count (number of documents whose nearest neighbor is in the other class).