

MATH 512 - Project 2

**Wasif Ahmed, Haoxiang Deng, Jacob Fein-Ashley,
Kanav Malhotra**

Question 1 (a)


We use the Kolmogorov-Smirnov test to test for the uniformity of the random numbers generated by the LCG. The test statistic is given by

$$D_n = \max_{1 \leq i \leq n} \left(\frac{i}{n} - U_{(i)} \right) \vee \max_{1 \leq i \leq n} \left(U_{(i)} - \frac{i-1}{n} \right)$$

where $U_{(i)}$ is the i -th order statistic of the U_i 's.

- Our null hypothesis is that the random numbers are uniformly distributed.
- We find that $D_n = 0.0105$ and a p-value of 0.208. This means that we fail to reject the null hypothesis at the 5% significance level, and conclude that the random numbers are uniformly distributed.

Question 1 (a)



Question 1 (b)

Parameters: $a = 6, m = 11, x_0 = 3, c = 1$


- The sequence is $[3, 7, 9, 10, 5, 8, 4, 2, 1, 6]$
- The period is 1

Parameters: $a = 6, m = 10, x_0 = 3, c = 1$



- The sequence is $[3, 8, 8, 8, 8, 8, 8, 8, 8, 8]$
- The period is 2

Question 1 (c)

Histogram of random numbers using `numpy.random.rand()`




Question 1 (d)



- The two histograms look relatively similar, meaning both look relatively uniform.

Question 1 (e)




- I'm not seeing much of a pattern...

Question 1 (f)

Disadvantages of LCG:

- It can appear to be random with the right set of parameters, but as we saw, it can get “stuck” in a loop.
- The randomness depends on the bit position of the seed.
- The randomness depends on the choice of parameters.



In combination with *plain*,
it makes a nice thank-you slide!



<https://github.com/piazzai/arguelles>
<https://ctan.org/pkg/beamertheme-arguelles>