


Evaluating a Phonotactic Learner for MITSL₂ Languages



Jacob Johnson

Aniello De Santo

MeLo Lab, Department of Linguistics, University of Utah ✉: jacob.k.johnson@utah.edu ✉: aniello.desanto@utah.edu



Key Findings

- MITSL2IA (De Santo & Aksënova, 2021) is successful on several subregular patterns, despite low data
- Aksënova (2020)'s evaluation pipeline is valuable for testing subregular learning algorithms
- Transparent learners could be used to inspect the quality of the data in samples available to learners




Figure: ITSL₂ analysis of Yaka nasal harmony from De Santo & Aksënova (2021), illustrating a 2-local projection and 2-local tier constraints. (a) is ill-formed because of tier-adjacent * [nd], but [n,d,g,N] are projected on the tier only when not in a nasal-stop cluster in the input (cf. (b), (c)).; data from Walker (2000)





Figure: Subsumption of subregular classes, with the TSL extensions as of De Santo & Graf (2019).




Introduction

- Formal Language Theory provides insights into properties underlying typologically attested patterns (Heinz, 2018)
- MITSL handles **multiple** interactions of **local and non-local phonotactic** constraints (De Santo & Graf, 2019)
- MITSL₂ can be learned efficiently from positive data (De Santo & Aksënova, 2021)
- Here:** An implementation and extensive evaluation of (De Santo & Aksënova, 2021)

Learning MITSL₂ Patterns

- De Santo & Aksënova extend McMullin et al. (2019)'s MTSL₂ algorithm to MITSL₂
- MITSL2IA builds on the intuition that if a bigram $\rho_1\rho_2$ is banned on some tier, then it will never appear in string-adjacent contexts
- We can determine which segments are freely distributed with respect to a bigram $\rho_1\rho_2$ which is not attested and thus assumed to be banned on some tier
- MITSL2IA is guaranteed to learn target grammars efficiently if the input sample is characteristic, but does this align with how phenomena of interest are represented in naturalistic data sets?
- Our implementation of MITSL2IA is available at <https://github.com/jacobkj314/MITSL2IA>
- By inspecting the output, it is possible to infer whether/why the input data was insufficient for the learner to converge on the target grammar in some cases

The Evaluation Pipeline (Aksënova, 2020)



- We implemented MITSL2IA in Python 3 following requirements of SigmaPie
- We evaluated it on artificial and simplified natural language phenomena in different subregular classes
- Artificial datasets contained 1000 randomly sampled strings, and up to 130K words for the simplified natural language corpora
- The learned grammars were then given to string generators, and we computed the proportion of strings in the newly generated sample that were well-formed according to the target grammar
- We defined an injection procedure process to explain strings generated by the learned grammar that were not accepted by the target grammar and form new strings to augment the input sample
- Re-running the learner on the data augmented with the “missing” samples resulted in a 100% performance in all cases

References

Aksënova, A. (2020). Tool-assisted induction of subregular languages and mappings (Doctoral dissertation, State University of New York at Stony Brook). · De Santo, A., Aksënova, A. (2021, February). Learning Interactions of Local and Non-Local Phonotactic Constraints from Positive Input. In Proceedings of the Society for Computation in Linguistics 2021 (pp. 167-176). · De Santo, A., Graf, T. (2019). Structure sensitive tier projection: Applications and formal properties. In Formal Grammar: 24th International Conference, FG 2019, Riga, Latvia, August 11, 2019, Proceedings 24 (pp. 35-50). Springer Berlin Heidelberg. · Heinz, J.: The computational nature of phonological generalizations. In: Hyman, L., Plank, F. (eds.) Phonological Typology, chap. 5, pp. 126-195. Phonetics and Phonology, Mouton De Gruyter (2018) · McMullin, K., Aksënova, A., De Santo, A. (2019). Learning phonotactic restrictions on multiple tiers. Proceedings of the Society for Computation in Linguistics, 2(1), 377-378. · Walker, R. (2000, September). Yaka nasal harmony: Spreading or segmental correspondence?. In Annual meeting of the berkeley linguistics society (Vol. 26, No. 1, pp. 321-332).

Acknowledgement. This project was supported by a Research Incentive Seed Grant from the University of Utah awarded to Aniello De Santo (Project #: 51900472).

	Aksënova (2020)				This Paper
	SP	SL	TSL	MTSL	MITSL
Word-final devoicing					
T	✗	✓	✓	✓	✓
A	68%	100%	100%	100%	100%
N _G	58%	100%	100%	100%	100%
Single vowel harmony without blocking					
T	✓	✗	✓	✓	✓
A	100%	83%	100%	100%	100%
N _F	100%	72%	100%	100%	100%
Single vowel harmony with blocking					
T	✗	✗	✓	✓	✓
A	84%	89%	100%	100%	99%
Several vowel harmonies without blocking					
T	✓	✗	✓	✓	✓
A	100%	69%	100%	100%	100%
Several vowel harmonies with blocking					
T	✗	✗	✓	✓	✓
A	76%	59%	100%	100%	99%
N _T	76%	70%	67%	95%	99%
Vowel harmony and consonant harmony without blocking					
T	✓	✗	✗	✓	✓
A	100%	64%	74%	100%	100%
Vowel harmony and consonant harmony with blocking					
T	✗	✗	✗	✓	✓
A	83%	64%	69%	100%	100%
Unbounded tone plateauing					
T	✓	✗	✗	✗	✓
A	100%	85%	90%		100%
Two locally-driven long-distance assimilations (ITSL restrictions)					
T	✗	✗	✗	✗	✓
A					100%

Table: (T)heoretical expectations and performance of 5 subregular learners on (A)rtificial and simplified (N)atural language input data-sets. MITSL corresponds to this work. N_G: German; N_F: Finnish; N_T: Turkish.