NOCO + T12 / CONVERTER CARRIER / MECHANICAL & ELECTRICAL REVIEW

Converter carrier circuit r09



File: Carrier.kicad_sch

Sheet: /
File: UnderBot.kicad_sch

Title:

Size: A3	Date:	**Rev:**
KiCad E.D.A. 10.0.6		Id: 1/2


CONVERTER CARRIER r09 | DESIGN REVIEW / UNROUTED

NOCO12V accessory output only. External main protection/disconnect and manual-reset stop still require final design.

J1
Protected12V input + / GND



J2
Stop contact SEND+ / RETURN+ (NO GND)



A1
52PI EP-0225 mounted on standoffs



F1
MINI current rating HOLD



J3
Short DC cable to mounted EP-0225



F2
MINI current rating HOLD



J4
DDR input: +Vin5 / -Vin6



A2
Mean Well DDR-60G-12 / rail mounting



F3
MINI current rating HOLD



J5
DDR output return: +Vo3 / -Vo1



DDR terminals2 and4 duplicate output -/+; unused.
Output negative intentionally joins system ground here.
This assembly does not preserve galvanic isolation.
Set output12.0V and verify before plugging in Kinect.

F4
MINI current rating HOLD



J6
Regulated12V to Kinect v2 adapter



J7
Stopped nominal12V to Adeept VIN



U3
Pololu D24V50F5 #2851



H1
M3

H2
M3

H3
M3

H4
M3

J8
Stopped regulated5V AUX output



A1/A2 use short harnesses within the assembly; no invented PCB electrical pin footprint. U3 is a soldered daughterboard.

J pin numbers are proposed harness assignments, not OEM connector pinouts
PROVISIONAL CIRCUIT / HARNESS DESIGN — NOT FOR FABRICATION
UnderBot

Sheet: /Converter carrier circuit r09/
File: Carrier.kicad_sch

Title: NOCO converter carrier r09 — module integration

Size: A3	Date: 2026-10-02	**Rev: 0.9 CARRIER**
KiCad E.D.A. 10.0.6		Id: 2/2