


Sep.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
2	DIS-C-000490	T.H.E.K		07.01.31					



- NOTES
- 1 TOTAL LENGTH BECOMES 29.8±1 WHEN 8 IS SCREWED INTO 1 COMPLETELY.
  - 2 TABLE FOR ASSEMBLY AND SOLDERING IS AVAILABLE HR30-6P-6S-T01.
  - 3 THE RECOMMENDED CLAMP TORQUE OF REF. NO.8 TO BE 0.5N·m.  
LOCTITE 271, LOCPRIMER 7649, HENKEL JAPAN IS RECOMMENDED TO PREVENT REF. NO.8 FROM LOOSENING.  
SPACER FOR ASSEMBLY IS AVAILABLE HR30-6P-T02.
  - 4 SURFACE PLATING: GOLD PLATING 0.2μm min.  
UNDER PLATING: NICKEL PLATING 2μm min.
  - 5 THE CABLE PULL AND TWISTING STRENGTH AND OTHER CHARACTERISTICS MAY DIFFER,  
DEPENDING ON THE CABLE STRUCTURE.  
PLEASE CONFIRM BEFORE THE USE.

4	PBT	(BLACK)	UL94V-0	8	PBT	(BLACK)	UL94V-0
3	SIR	(RED)		7	POLYACETAL	(NATURAL)	
2	BRONZE ALLOY	4		6	CR	(BLACK)	
1	PPS	(BLACK)	UL94V-0	5	STAINLESS STEEL		
NO.	MATERIAL	FINISH, REMARKS		NO.	MATERIAL	FINISH, REMARKS	

CODE NO. (OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
	M.HANYU	H.NAGANO	E.KUNII	M.SATO	
	'05. 8. 8	'05. 8. 8	'05. 8. 10	'05. 8. 10	

SCALE	DRAWING NO.	PART NO.
5 : 1	EDC3-112512-71	HR30-6PA-6S(71)
UNITS	HIROSE ELECTRIC CO., LTD	CODE NO.
mm		CL130-0019-9-71

TO
R