Hubbard-Holstein Mathematical Notes (Symbolic-Only Edition)

Jake Skyler Strobel

March 20, 2026

Contents

1. Parameter Manifest and Reader Contract **5**
1.1 Required parameter manifest . . . 5
1.2 Reader contract . . . 5
1.2.1 Quick notation glossary for adaptive and continuation sections . . . 5
1.2.2 Quick parameter glossary for adaptive and continuation sections . . . 6
1.3 Non-negotiable representational conventions . . . 7
1.3.1 Internal Pauli alphabet . . . 7
1.3.2 Pauli-word and qubit ordering . . . 7
1.3.3 Canonical algebra sources . . . 7
1.3.4 Surface-specific defaults . . . 7
1.4 Canonical mathematical anchors . . . 7

2. Ordering, Indexing, and Register Layout **7**
2.1 Site, spin, and mode indices . . . 7
2.1.1 Interleaved ordering . . . 8
2.1.2 Blocked ordering . . . 8
2.2 Pauli-word placement and basis-index extraction . . . 8
2.3 Full HH register layout . . . 8

3. Fermionic Primitives and Direct Substitution **9**
3.1 Jordan-Wigner ladder primitives . . . 9
3.2 Number primitive . . . 9
3.3 Site densities and doublon operator . . . 9
3.4 Worked ordering substitutions . . . 9
3.4.1 Interleaved . . . 9
3.4.2 Blocked . . . 9

4. Boson Primitives and Encodings **10**
4.1 Local boson Hilbert space . . . 10
4.2 Binary encoding . . . 10
4.3 Unary encoding . . . 10
4.4 Phonon vacuum . . . 10
4.4.1 Binary vacuum . . . 10
4.4.2 Unary vacuum . . . 10

5. Hubbard Hamiltonian by Explicit Substitution **10**
5.1 Kinetic term . . . 11
5.2 Onsite interaction . . . 11
5.3 Static potential term . . . 11
5.4 Fully substituted Hubbard Hamiltonian . . . 11

6. Hubbard-Holstein Hamiltonian by Explicit Substitution **11**
6.1 Phonon energy . . . 11

6.1.1 Unary explicit form . . . 11
6.1.2 Binary explicit form . . . 12
6.2 Electron-phonon coupling . . . 12
6.2.1 Unary explicit form . . . 12
6.2.2 Binary explicit form . . . 12
6.2.3 Worked Holstein-only reduction after Jordan-Wigner fermions and unary phonons . . . 12
6.2.3.1 Qubit indexing used . . . 12
6.2.3.2 Jordan-Wigner fermionic number operators . . . 13
6.2.3.3 Unary phonon ladder operators in Pauli form . . . 13
6.2.3.4 Explicit Holstein Hamiltonian in the qubit basis . . . 13
6.3 Time-dependent density drive . . . 14
6.3.1 Generic density-drive waveform surface . . . 14
6.4 Two HH assembly surfaces . . . 14
6.4.1 Exact Hamiltonian surface . . . 14
6.4.2 Variational HH ansatz surface . . . 14
6.5 Fully substituted HH master form . . . 15

7. Reference States and Exact Sector ED **15**
7.1 Fermionic Hartree-Fock determinant . . . 15
7.2 Hubbard-Holstein reference state . . . 15
7.3 Exact HH sector basis . . . 15
7.3.1 Binary index map . . . 15
7.3.2 Unary index map . . . 15
7.4 Exact HH matrix elements . . . 15
7.4.1 Diagonal elements . . . 15
7.4.2 Hopping matrix elements . . . 15
7.4.3 Electron-phonon matrix elements . . . 16

8. Statevector Action, Expectation, and Exponential Primitives **16**
8.1 Basis-state primitive . . . 16
8.2 Explicit Pauli-word action . . . 16
8.3 Expectation values . . . 16
8.4 Pauli rotations . . . 16
8.5 Exponential of a Pauli polynomial . . . 16
8.6 Exact sector energy target . . . 17

9. Fixed VQE Ansatz Families **17**
9.1 Hubbard layerwise ansatz . . . 17
9.2 Hubbard excitation-based surface . . . 17
9.3 HH layerwise ansatz . . . 17
9.4 HH physical-termwise ansatz . . . 17
9.5 Reference-state and ansatz pairing principle . . . 18

10. Polaronic Operator Families **18**
10.1 Primitive polaronic ingredients . . . 18
10.1.1 Shifted density . . . 18
10.1.2 Phonon primitives P_i and x_i . . . 18
10.1.3 Local squeeze primitive . . . 18
10.1.4 Doublon primitive . . . 18
10.1.5 Even hopping channel . . . 18
10.1.6 Odd current channel . . . 18
10.2 Representative dressed channels . . . 18
10.2.1 Conditional displacement . . . 18
10.2.2 Doublon dressing . . . 19
10.2.3 Dressed hopping drag . . . 19
10.2.4 Odd-channel drag . . . 19
10.2.5 Second-order even channel . . . 19

10.2.6 Third-order odd current channel . . . 19
10.2.7 Fourth-order even hopping channel . . . 19
10.2.8 Bond-conditioned displacement and squeeze channels . . . 19
10.2.9 Local squeeze channels . . . 19
10.2.10 Extended cloud channels . . . 19
10.2.11 Doublon-translation and doublon-squeeze channels . . . 19
10.3 Pool-family map . . . 19
10.3.1 Compact displacement/squeeze macro families . . . 19

11. Adaptive Selection and Staged Continuation **20**
11.1 Cumulative phase construction for adaptive selection . . . 20
11.2 Phase 1 broad fallback selector surface . . . 20
11.2.1 Core signal, append position, and refit window . . . 20
11.2.2 Gates, burdens, and feature ingredients . . . 20
11.2.3 Cheap score . . . 20
11.2.4 Position probing, trough detection, and effective selector . . . 20
11.2.5 Full-pool limiting case . . . 21
11.3 Phase 2 relaxed selector surface . . . 21
11.3.1 Core signal, append position, refit window, and cheap screen . . . 21
11.3.2 Shortlist rule . . . 21
11.3.3 Reduced-path geometry, novelty, curvature, and trust-region drop . . . 21
11.3.4 Full rerank score and effective selector . . . 22
11.4 Phase 3 primary selector surface . . . 22
11.4.1 Core signal, append position, refit window, and cheap screen . . . 22
11.4.2 Shortlist, reduced-path geometry, novelty, full rerank score, and split-aware augmentation . . . 24
11.4.3 Beam-adapt over scaffold alternatives: branch state, pruning, and effective selector . . . 26
11.5 Active HH pool surface and selected scaffold . . . 31
11.6 Stage controller . . . 32

12. SPSA and Optimizer Semantics **32**
12.1 SPSA schedules . . . 32
12.2 Two-point stochastic gradient . . . 32
12.3 Update and projection . . . 32
12.4 Repeat aggregation . . . 32
12.5 Return policy . . . 33
12.6 Surface note . . . 33

13. Drive, Exact Propagation, and Propagator Semantics **33**
13.1 Static drive labels and time-dependent coefficients . . . 33
13.2 Reference coefficient map . . . 33
13.3 Propagator surfaces . . . 33
13.4 Reference propagator versus reported trajectory propagator . . . 33
13.4.1 Static reference branch . . . 33
13.4.2 Drive-enabled reference branch . . . 34
13.5 CFQM macro-step mathematics . . . 34
13.6 Filtered exact manifold and subspace fidelity . . . 34
13.7 Branch-resolved observable contracts . . . 34
13.8 State import and handoff contract . . . 34
13.9 Highest-tier continuation surfaces . . . 34

14. Continuation and Handoff Contract **34**
14.1 Handoff state bundle . . . 34
14.2 Continuation block . . . 35
14.3 General handoff map . . . 35
14.4 Symmetry and tier-three payload note . . . 35
14.5 Historical warm/refine chain note . . . 35

15. Cross-Checks and Exact-Benchmark Contracts **35**
15.1 Trial matrix by problem family . . . 35
15.2 Auto-scaled parameter resolution . . . 36
15.3 Exact target and shared reference-state construction . . . 36
15.4 Per-trial energy and trajectory semantics . . . 36
15.5 Artifact contracts . . . 36
15.6 HH seed-surface preset and resource proxies . . . 36

16. Noise Validation, Symmetry-Mitigation, and Parity Contracts **36**
16.1 Filtered versus full exact targets . . . 36
16.2 Noisy-minus-ideal observable deltas . . . 36
16.3 Anchor parity gate . . . 37
16.4 Same-anchor paired comparison semantics . . . 37
16.5 Symmetry-mitigation mode surface . . . 37
16.6 Parameter manifest and provenance digest . . . 37

17. Projective McLachlan Real-Time Geometry and Piecewise Beam-Adaptive Control **37**
17.1 What problem is being solved? . . . 37
17.2 Why projective Hilbert space is the right setting . . . 38
17.3 The current manifold and its allowed velocities . . . 38
17.4 The fixed-structure McLachlan step . . . 38
17.5 What regularization means . . . 39
17.6 Why the residual is the right local error quantity . . . 39
17.7 The geometric projector behind the formulas . . . 39
17.8 What a candidate generator really is . . . 40
17.9 The exact local gain formula . . . 40
17.10 What S and w mean . . . 40
17.11 The unregularized geometric meaning . . . 41
17.12 When should the ansatz adapt? . . . 41
17.13 Which candidates should be admissible? . . . 41
17.14 Two different residuals should be tracked . . . 42
17.15 Why integrated residual is the right branch-pruning quantity . . . 42
17.16 The branch objective . . . 42
17.17 The full process, in one coherent sequence . . . 43
17.18 One concise interpretation . . . 43
17.19 Explicit symbolic–mathematical differences between the clean story and the current implementation 43

18. Final Primitive-Closed Summary **45**

19. Data **45**
19.1 Matched novelty ablation . . . 45
19.2 Interpretation of the novelty ablation . . . 46
19.3 Pool-family redundancy . . . 46
19.4 Relation to live pruning . . . 47
19.5 Data provenance note . . . 48

Appendix A. Spec-only or not-yet-formalized surfaces kept out of the main body **48**
A.1 Broader continuation-theory items . . . 48
A.2 Obsolete historical warm-start → refine → ADAPT → replay path . . . 48
A.3 Drive-amplitude comparison path . . . 48
A.4 Appendix rule . . . 49

References **49**

Canonical naming note: `MATH/Math.md` is the symbolic manuscript and corresponds to `MATH/Math.pdf`. The archival repo-oriented manuscript is `MATH/archaic_repo_math.md`.

1. Parameter Manifest and Reader Contract

This duplicate is intentionally symbolic-first. It keeps the same broad manuscript shape as the existing mathematical notes,

1. primitives first,
2. composite operators second,
3. explicit substitutions third,
4. reduced master forms last,

but it suppresses almost all implementation labels, file names, mode strings, and executable-surface commentary. The goal is to make the document readable as mathematics rather than as a repository audit.

1.1 Required parameter manifest

A complete symbolic run or derivation should specify at least the following data.

- Model family: Hubbard or Hubbard-Holstein.
- Lattice size: L.
- Ordering map: interleaved or blocked, i.e. a choice of $p(i, \sigma)$.
- Boundary condition: open or periodic.
- Fermionic parameters: hopping t, onsite interaction U, and static site potentials v_i.
- Bosonic parameters: phonon frequency ω_0, electron-phonon coupling g, and cutoff $n_{\mathrm{ph,max}}$.
- Boson encoding choice: binary or unary.
- Variational family, when relevant: layerwise, physical-termwise, excitation-based, or adaptive.
- Control parameters, when relevant: optimizer family, propagation rule, drive waveform parameters, and benchmark grid.

1.2 Reader contract

This manuscript favors explicit substitution over compressed abstraction.

- If a primitive operator exists, it is written first.
- If a composite object is built from primitives, the primitive form is shown.
- If a later equation can be simplified by inserting an earlier primitive explicitly, that insertion is made.
- If multiple mathematical surfaces exist, such as different index orderings or boson encodings, the surface is named locally rather than hidden behind an unnamed default.

1.2.1 Quick notation glossary for adaptive and continuation sections

This subsection is a compact map for the symbols that recur in the adaptive-selection, split-aware, replay, and beam-style sections.

- g, m: generic candidate generators. The manuscript uses both letters in different sections; they play the same role.
- p: candidate insertion position in the ordered scaffold.
- $r = (m, p)$: a candidate-position record, i.e. a generator together with a chosen insertion position.
- $\mathcal{G}$: the full master generator pool.
- $\mathcal{G}^{(1)}, \mathcal{G}^{(2)}, \mathcal{G}^{(3)}$: progressively more restricted candidate universes, with

$$\mathcal{G}^{(3)} \subseteq \mathcal{G}^{(2)} \subseteq \mathcal{G}^{(1)} \subseteq \mathcal{G}.$$

- $\mathcal{P}_g$ or $\mathcal{P}_m$: admissible insertion positions for candidate g or m.
- $W(p)$: inherited refit window used if a candidate is inserted at position p.
- $W_{\mathrm{new}}(p)$: the newest-parameter portion of the refit window.
- $W_{|\theta|}(p)$: the older large-amplitude carry subset of the refit window.
- $\mathcal{P}^{(3)}_{\mathrm{avail}}$: the full available set of Phase-3 candidate-position records.
- $\mathcal{C}_{\mathrm{cheap}}$: the cheap-pass capped candidate set retained after the first Phase-3 gradient screen.
- $\mathcal{S}_2, \mathcal{S}_3$: the Phase-2 and Phase-3 shortlists that survive cheap screening before full reranking.
- $\mathcal{C}_{\mathrm{split}}(m)$: the family of split children generated from macro generator m.

- $\mathcal{O}_*$: the finally selected adaptive scaffold, i.e. the ordered generator sequence admitted by the adaptive stage.
- $\mathcal{M}_{\text{warm}}, \mathcal{M}_{\text{refine}}, \mathcal{M}_{\text{replay}}$: archival appendix-only warm-start, optional refine, and replay manifolds.
- $\mathcal{B}$: a portable handoff/state bundle carrying manifest, amplitudes, energies, and continuation metadata.
- $\mathcal{C}$: continuation payload / provenance payload attached to a handoff bundle.
- Γ_{stage}: stage-admissibility gate.
- Γ_{sym}: symmetry-admissibility gate.
- $\mathfrak{b}$: a beam branch state. In §11 it indexes alternative ADAPT scaffolds; in §17 it indexes projected-dynamics branches over checkpoint segments.
- $\mathcal{H}_b$: admitted-record history carried by scaffold branch b.
- $\mathcal{A}_b$: branch-local admissible admission set retained for scaffold-beam expansion.
- $\mathcal{Q}(b)$: scaffold-beam proposal family, usually $\{\text{stop}\} \cup \mathcal{A}_b$.
- η_b: branch-local stage label for the scaffold beam, e.g. core/seed versus residual.
- $W_{\text{act}}(\mathfrak{b})$: the currently active position-probe window on branch b.
- $\mathfrak{F}_c$: live frontier at beam round c.
- $\mathfrak{T}_c$: terminal-branch pool at beam round c.
- $\mathfrak{W}_{\text{final}}$: final union of surviving frontier and terminal branches.
- J_b: cumulative branch objective tuple used to rank or prune branch b; its coordinates are section-specific.

1.2.2 Quick parameter glossary for adaptive and continuation sections

The symbols below are the main scalar controls that appear in the adaptive-selection, split-aware, and beam-style formulas.

- $\lambda_{2\text{q}}$: weight on two-qubit proxy burden.
- λ_d: weight on depth-style proxy burden.
- λ_θ: weight on marginal parameter-count burden.
- λ_F: cheap-stage normalization weight multiplying the tangent metric term.
- λ_H: regularization strength for inherited-window Hessian blocks.
- ρ: trust-region radius scale used in one-dimensional local improvement models.
- $N_{\text{cheap}}^{\max}$: maximum cheap-pass size before shortlist construction.
- $N_{\max}$: maximum shortlist size.
- f_{short}: shortlist fraction used in Phase 3.
- w_R: weight on remaining-depth or remaining-evaluations burden.
- w_D: weight on lifetime depth/compile burden.
- w_G: weight on newly introduced grouped-measurement burden.
- w_C: weight on newly introduced compile or circuit burden.
- w_c: weight on any extra cheap-path correction burden.
- γ_N: exponent applied to novelty factors in full rerank scores.
- ε: small positive stabilizer used in denominators and tie-safe quotients.
- ε_{nov}: novelty regularizer used when inverting or stabilizing tangent-overlap matrices.
- z_α: confidence multiplier used to convert a raw gradient estimate into a lower-confidence gradient.
- $\sigma(g,p)$ or σ_r: uncertainty estimate attached to the candidate-position gradient signal.
- τ_1: Phase-2 shortlist threshold.
- τ_{split}: split-replacement margin required before a split child or child-set beats its parent.
- τ_{drop}: minimum per-depth absolute-error improvement regarded as meaningful by the stage controller.
- M: patience window used when counting repeated small-drop depths.
- τ_{miss}: projected-miss threshold used in manifold-growth logic.
- B_{child}: beam child cap per parent branch-expansion round.
- B_{live}: live-frontier beam width retained after pruning.
- B_{term}: cap on stored terminal branches.
- M_{probe}: cap on distinct probed insertion positions retained in order.
- Δk_{cp}: checkpoint advance used in the projected-dynamics beam of §17, not in the scaffold beam of §11.
- Δk_{probe}: probe advance used in the projected-dynamics beam of §17, not in the scaffold beam of §11.
- C: final beam round index / number of retained beam-update rounds.

1.3 Non-negotiable representational conventions

1.3.1 Internal Pauli alphabet

In formulas below we use the standard alphabet

$$\{I, X, Y, Z\}.$$

If one prefers the lower-case alphabet $\{e, x, y, z\}$, the identification is simply

$$e \leftrightarrow I, \qquad x \leftrightarrow X, \qquad y \leftrightarrow Y, \qquad z \leftrightarrow Z.$$

1.3.2 Pauli-word and qubit ordering

Pauli words and computational-basis labels are written left-to-right as

$$q_{N_q-1} \cdots q_1 q_0,$$

with qubit q_0 the rightmost symbol and also the least-significant bit in basis-index arithmetic.

1.3.3 Canonical algebra sources

The canonical mathematical primitives are:

- Jordan-Wigner ladder operators $\hat{c}_p^\dagger$ and $\hat{c}_p$,
- fermion number operators $\hat{n}_p$,
- boson ladder operators $\hat{b}_i^\dagger$ and $\hat{b}_i$,
- Hermitian Pauli words and Pauli polynomials,
- ordered exponentials generated from those primitives.

1.3.4 Surface-specific defaults

This symbolic version does not pretend there is a single universal surface. The mathematics admits several equally valid choices:

- interleaved or blocked fermion ordering,
- open or periodic boundary conditions,
- binary or unary boson encoding,
- static or driven Hamiltonians,
- fixed-structure or adaptive variational manifolds.

Whenever a formula depends on the choice of surface, that dependence is shown locally.

1.4 Canonical mathematical anchors

The main objects carried through the manuscript are:

- the ordering map $p(i, \sigma)$,
- the ladder primitives $\hat{c}_p^\dagger$, $\hat{c}_p$, $\hat{b}_i^\dagger$, $\hat{b}_i$,
- the density operators $\hat{n}_{i\sigma}$, $\hat{n}_i$, and $\hat{D}_i$,
- the Hubbard and Hubbard-Holstein Hamiltonians,
- the reference state $|\psi_{\mathrm{ref}}\rangle$,
- the variational manifold $\mathcal{M}$ and its ansatz map $\theta \mapsto |\psi(\theta)\rangle$,
- the propagation rule $U(t)$,
- the continuation or handoff bundle $\mathcal{B}$.

2. Ordering, Indexing, and Register Layout

2.1 Site, spin, and mode indices

The site index is

$$i \in \{0, 1, \ldots, L-1\},$$

and the spin label is stored as

$$\sigma \in \{\uparrow, \downarrow\} \equiv \{0, 1\}.$$

The fermion mode index is the Jordan-Wigner qubit index.

2.1.1 Interleaved ordering

The interleaved map is

$$p(i, \sigma) = 2i + \sigma,$$

so that

$$p(i, \uparrow) = 2i, \qquad p(i, \downarrow) = 2i + 1.$$

2.1.2 Blocked ordering

The blocked map is

$$p(i, \uparrow) = i, \qquad p(i, \downarrow) = L + i.$$

2.2 Pauli-word placement and basis-index extraction

If a Pauli letter acts on qubit q, then in a printed word of length N_q it sits at string position

$$\mathrm{pos}(q) = N_q - 1 - q.$$

If the computational-basis index is k, then the occupation bit on qubit q is

$$b_q(k) = \left\lfloor \frac{k}{2^q} \right\rfloor \bmod 2.$$

Thus the printed bitstring and integer basis index obey the same rightmost-q_0 convention.

2.3 Full HH register layout

The fermion register uses

$$N_{\mathrm{ferm}} = 2L$$

qubits.

If the local phonon cutoff is $n_{\mathrm{ph,max}}$, then the local phonon Hilbert dimension is

$$d = n_{\mathrm{ph,max}} + 1.$$

The number of phonon qubits per site is

$$q_{\mathrm{pb}} = \begin{cases} \max\{1, \lceil \log_2 d \rceil\}, & \text{binary}, \\ d, & \text{unary}. \end{cases}$$

Therefore the total HH qubit count is

$$N_q = 2L + Lq_{\mathrm{pb}}.$$

In qubit-index order, the register is naturally partitioned as

$$[\text{fermions} \mid \text{site-0 phonons} \mid \cdots \mid \text{site-(L-1) phonons}].$$

In printed order $q_{N_q-1} \cdots q_0$, the high-index phonon blocks appear on the left.

3. Fermionic Primitives and Direct Substitution

3.1 Jordan-Wigner ladder primitives

For mode p, the creation operator is

$$\hat{c}_p^\dagger = \frac{1}{2}(X_p - iY_p)\prod_{r=0}^{p-1} Z_r,$$

and the annihilation operator is

$$\hat{c}_p = \frac{1}{2}(X_p + iY_p)\prod_{r=0}^{p-1} Z_r.$$

In fully expanded printed-word form, the operator acts on the word ordered as $q_{N_q-1}\cdots q_0$ with the Jordan-Wigner Z-string extending through all modes below p.

3.2 Number primitive

The fermion number operator is

$$\hat{n}_p = \hat{c}_p^\dagger \hat{c}_p = \frac{I - Z_p}{2}.$$

3.3 Site densities and doublon operator

At site i, define

$$\hat{n}_i = \hat{n}_{i\uparrow} + \hat{n}_{i\downarrow},$$

and the doublon operator

$$\hat{D}_i = \hat{n}_{i\uparrow}\hat{n}_{i\downarrow}.$$

By direct substitution,

$$\hat{D}_i = \frac{1}{4}(I - Z_{p(i,\uparrow)})(I - Z_{p(i,\downarrow)}).$$

3.4 Worked ordering substitutions

3.4.1 Interleaved

Under interleaved ordering,

$$\hat{n}_i = I - \frac{1}{2}(Z_{2i} + Z_{2i+1}),$$

and

$$\hat{D}_i = \frac{1}{4}(I - Z_{2i})(I - Z_{2i+1}).$$

For nearest-neighbor spin-up hopping in a one-dimensional chain,

$$\hat{c}_{i\uparrow}^\dagger \hat{c}_{i+1,\uparrow} + \hat{c}_{i+1,\uparrow}^\dagger \hat{c}_{i\uparrow} = \frac{1}{2}\Big(X_{2i}Z_{2i+1}X_{2i+2} + Y_{2i}Z_{2i+1}Y_{2i+2}\Big).$$

3.4.2 Blocked

Under blocked ordering,

$$\hat{n}_i = I - \frac{1}{2}(Z_i + Z_{L+i}),$$

and

$$\hat{D}_i = \frac{1}{4}(I - Z_i)(I - Z_{L+i}).$$

For spin-up nearest-neighbor hopping, the Jordan-Wigner string is empty because the two blocked spin-up modes are adjacent, so

$$\hat{c}_{i\uparrow}^\dagger \hat{c}_{i+1,\uparrow} + \hat{c}_{i+1,\uparrow}^\dagger \hat{c}_{i\uparrow} = \frac{1}{2}\Big(X_iX_{i+1} + Y_iY_{i+1}\Big).$$

The general blocked-ordering formula uses the same Jordan-Wigner interval rule as before, with an empty product for adjacent modes.

4. Boson Primitives and Encodings

4.1 Local boson Hilbert space

For each site i, the truncated boson Hilbert space is

$$\mathcal{H}_{b,i} = \mathrm{span}\{|n_i\rangle : 0 \le n_i \le n_{\mathrm{ph,max}}\}.$$

The ladder operators satisfy

$$\hat{b}_i^\dagger |n\rangle = \sqrt{n+1}\,|n+1\rangle, \qquad \hat{b}_i |n\rangle = \sqrt{n}\,|n-1\rangle,$$

with

$$\hat{n}_{b,i} = \hat{b}_i^\dagger \hat{b}_i, \qquad \hat{x}_i = \hat{b}_i + \hat{b}_i^\dagger, \qquad \hat{P}_i = i(\hat{b}_i^\dagger - \hat{b}_i).$$

4.2 Binary encoding

In binary encoding, each local occupation number $n \in \{0, \dots, d-1\}$ is mapped to a binary word on $q_{\mathrm{pb}} = \lceil \log_2 d \rceil$ qubits:

$$|n\rangle \longmapsto |\,\mathrm{bin}(n)\rangle.$$

The truncated number operator is then

$$\hat{n}_{b,i} = \sum_{n=0}^{d-1} n\,|n\rangle\langle n|,$$

understood as an operator on the binary-encoded subspace.

4.3 Unary encoding

In unary encoding, each local occupation n is represented by a one-hot basis state on d qubits:

$$|n\rangle \longmapsto |0\cdots010\cdots0\rangle,$$

with the single 1 marking the occupied unary slot. The number operator remains

$$\hat{n}_{b,i} = \sum_{n=0}^{d-1} n\,|n\rangle\langle n|,$$

but now the basis states are embedded in a one-hot code space.

4.4 Phonon vacuum

4.4.1 Binary vacuum

The local binary vacuum is

$$|0\rangle_{b,i} \longmapsto |00\cdots0\rangle.$$

4.4.2 Unary vacuum

The local unary vacuum is the one-hot state carrying occupancy zero,

$$|0\rangle_{b,i} \longmapsto |10\cdots0\rangle,$$

or whichever one-hot convention is chosen consistently for the lowest occupation.

5. Hubbard Hamiltonian by Explicit Substitution

Write the static Hubbard Hamiltonian as

$$\hat{H}_{\mathrm{Hub}} = \hat{H}_t + \hat{H}_U + \hat{H}_v.$$

5.1 Kinetic term

The kinetic term is

$$\hat{H}_t = -t \sum_{\langle i,j\rangle,\sigma} \left(\hat{c}^\dagger_{i\sigma}\hat{c}_{j\sigma} + \hat{c}^\dagger_{j\sigma}\hat{c}_{i\sigma}\right).$$

For two fermion modes $p < q$, direct Jordan-Wigner substitution gives

$$\hat{c}^\dagger_p\hat{c}_q + \hat{c}^\dagger_q\hat{c}_p = \frac{1}{2}\left(X_p Z_{p+1} \cdots Z_{q-1} X_q + Y_p Z_{p+1} \cdots Z_{q-1} Y_q\right).$$

5.2 Onsite interaction

The onsite interaction term is

$$\hat{H}_U = U \sum_i \hat{n}_{i\uparrow}\hat{n}_{i\downarrow} = U \sum_i \hat{D}_i.$$

Substituting the number primitive,

$$\hat{H}_U = \frac{U}{4} \sum_i (I - Z_{p(i,\uparrow)})(I - Z_{p(i,\downarrow)}).$$

5.3 Static potential term

The static potential term is

$$\hat{H}_v = \sum_{i,\sigma} v_i \hat{n}_{i\sigma}.$$

After substitution,

$$\hat{H}_v = \sum_i v_i \left(I - \frac{1}{2}(Z_{p(i,\uparrow)} + Z_{p(i,\downarrow)})\right).$$

5.4 Fully substituted Hubbard Hamiltonian

Combining the pieces,

$$\hat{H}_{\text{Hub}} = -t \sum_{\langle i,j\rangle,\sigma} \left(\hat{c}^\dagger_{i\sigma}\hat{c}_{j\sigma} + \hat{c}^\dagger_{j\sigma}\hat{c}_{i\sigma}\right) + \frac{U}{4} \sum_i (I - Z_{p(i,\uparrow)})(I - Z_{p(i,\downarrow)}) + \sum_i v_i \left(I - \frac{1}{2}(Z_{p(i,\uparrow)} + Z_{p(i,\downarrow)})\right),$$

with the kinetic term expanded further into Pauli strings as needed.

6. Hubbard-Holstein Hamiltonian by Explicit Substitution

The driven Hubbard-Holstein Hamiltonian is

$$\hat{H}_{\text{HH}}(t) = \hat{H}_t + \hat{H}_U + \hat{H}_v + \hat{H}_{\text{ph}} + \hat{H}_g + \hat{H}_{\text{drive}}(t).$$

6.1 Phonon energy

The phonon energy is

$$\hat{H}_{\text{ph}} = \omega_0 \sum_i \left(\hat{n}_{b,i} + \frac{1}{2}I\right).$$

6.1.1 Unary explicit form

In unary form, $\hat{n}_{b,i}$ is diagonal on the one-hot occupation basis:

$$\hat{n}_{b,i} = \sum_{n=0}^{d-1} n\, |n\rangle_i\langle n|.$$

For the full qubit-level Pauli reduction in the spin-block JW + unary setting, including the explicit I/Z form of $\hat{H}_{\text{ph}}$, see Section 6.2.3.4(a).

6.1.2 Binary explicit form

In binary form,

$$\hat{n}_{b,i} = \sum_{n=0}^{d-1} n \,|\, \mathrm{bin}(n)\rangle_i \langle \mathrm{bin}(n)|,$$

understood as an operator on the truncated binary code space.

6.2 Electron-phonon coupling

A natural density-shifted coupling is

$$\hat{H}_g = g \sum_i \hat{x}_i (\hat{n}_i - \bar{n} I),$$

where $\bar{n} = N_e/L$ is the reference density, often $\bar{n} = 1$ at half filling.

6.2.1 Unary explicit form

In unary encoding, $\hat{x}_i$ acts as nearest-neighbor hopping on the truncated local occupation chain:

$$\hat{x}_i = \sum_{n=0}^{d-2} \sqrt{n+1} \Big(|n+1\rangle_i \langle n| + |n\rangle_i \langle n+1| \Big).$$

Thus

$$\hat{H}_g = g \sum_i \hat{x}_i (\hat{n}_i - \bar{n} I)$$

with $\hat{x}_i$ understood in that unary basis. For the detailed spin-block JW + unary Pauli reduction of the Holstein sector, including the explicit ZXX/ZYY expansion, see Sections 6.2.3.2–6.2.3.4.

6.2.2 Binary explicit form

In binary encoding, the same operator is written on the binary code space:

$$\hat{x}_i = \sum_{n=0}^{d-2} \sqrt{n+1} \Big(|\,\mathrm{bin}(n+1)\rangle_i \langle \mathrm{bin}(n)| + |\,\mathrm{bin}(n)\rangle_i \langle \mathrm{bin}(n+1)| \Big),$$

with the same density factor $(\hat{n}_i - \bar{n} I)$.

6.2.3 Worked Holstein-only reduction after Jordan-Wigner fermions and unary phonons

Set

$$N_b = n_{\mathrm{ph,max}}.$$

In this worked subsection, isolate the Holstein part of the Hubbard-Holstein Hamiltonian:

$$\hat{H}_{\mathrm{Hol}} = \omega_0 \sum_{i=0}^{L-1} \hat{b}_i^\dagger \hat{b}_i \;+\; g \sum_{i=0}^{L-1} (\hat{b}_i^\dagger + \hat{b}_i)(\hat{n}_i - 1), \qquad \hat{n}_i = \hat{n}_{i\uparrow} + \hat{n}_{i\downarrow}.$$

6.2.3.1 Qubit indexing used

For fermions, use spin-block Jordan-Wigner ordering:

$$q(i,\sigma) = i + \sigma L, \qquad \sigma = 0 \equiv \uparrow, \quad \sigma = 1 \equiv \downarrow .$$

Thus

$$q_{i\uparrow} = i, \qquad q_{i\downarrow} = i + L, \qquad i = 0, \dots, L-1.$$

For phonons, use a unary register with cutoff N_b. Per site i, allocate $N_b + 1$ qubits labelled by $n = 0, \dots, N_b$, and place all fermions first and phonons second:

$$q_{i,n}^{(b)} = 2L + i(N_b + 1) + n, \qquad n = 0, \dots, N_b.$$

Let X_q, Y_q, and Z_q denote the Pauli operators on qubit q.

6.2.3.2 Jordan-Wigner fermionic number operators

Jordan-Wigner gives

$$\hat{n}_{i\sigma} = \frac{I - Z_{q_{i\sigma}}}{2},$$

so

$$\hat{n}_i - 1 = \left(\frac{I - Z_{q_{i\uparrow}}}{2} + \frac{I - Z_{q_{i\downarrow}}}{2} \right) - 1 = -\frac{Z_{q_{i\uparrow}} + Z_{q_{i\downarrow}}}{2}.$$

6.2.3.3 Unary phonon ladder operators in Pauli form

Define the single-qubit combinations

$$(+)_q = \frac{X_q + iY_q}{2}, \qquad (-)_q = \frac{X_q - iY_q}{2}.$$

Then the unary truncated ladder operators are

$$\hat{b}_i^\dagger = \sum_{n=0}^{N_b-1} \sqrt{n+1}\, (+)_{q_{i,n}^{(b)}} (-)_{q_{i,n+1}^{(b)}},$$

$$\hat{b}_i = \sum_{n=1}^{N_b} \sqrt{n}\, (-)_{q_{i,n-1}^{(b)}} (+)_{q_{i,n}^{(b)}}.$$

A convenient real Pauli expansion is

$$\hat{b}_i^\dagger + \hat{b}_i = \frac{1}{2} \sum_{n=0}^{N_b-1} \sqrt{n+1} \Big(X_{q_{i,n}^{(b)}} X_{q_{i,n+1}^{(b)}} + Y_{q_{i,n}^{(b)}} Y_{q_{i,n+1}^{(b)}} \Big).$$

6.2.3.4 Explicit Holstein Hamiltonian in the qubit basis

(a) Phonon energy term On the unary one-hot code space, the phonon number operator is diagonal and may be written as

$$\hat{b}_i^\dagger \hat{b}_i \equiv \hat{n}_i^{(b)} = \sum_{n=0}^{N_b} n \, \frac{I - Z_{q_{i,n}^{(b)}}}{2} \qquad \text{(exact on the one-hot subspace).}$$

Therefore

$$\boxed{\hat{H}_{\text{ph}} = \omega_0 \sum_{i=0}^{L-1} \sum_{n=0}^{N_b} n \, \frac{I - Z_{q_{i,n}^{(b)}}}{2}}.$$

Equivalently, as constant plus Pauli-Z,

$$\hat{H}_{\text{ph}} = \underbrace{\omega_0 \frac{1}{2} \sum_i \sum_{n=0}^{N_b} n}_{\omega_0 L \frac{N_b(N_b+1)}{4}} \; I - \frac{\omega_0}{2} \sum_{i=0}^{L-1} \sum_{n=0}^{N_b} n \, Z_{q_{i,n}^{(b)}}.$$

The global constant shift may be dropped if desired.

(b) Electron-phonon coupling term Using

$$\hat{n}_i - 1 = -\frac{Z_{q_{i\uparrow}} + Z_{q_{i\downarrow}}}{2}$$

and the unary expansion of $\hat{b}_i^\dagger + \hat{b}_i$, one obtains

$$\boxed{\hat{H}_{e\text{-}ph} = -\frac{g}{4}\sum_{i=0}^{L-1}\sum_{n=0}^{N_b-1}\sqrt{n+1}(Z_{q_{i\uparrow}} + Z_{q_{i\downarrow}})\Big(X_{q_{i,n}^{(b)}}X_{q_{i,n+1}^{(b)}} + Y_{q_{i,n}^{(b)}}Y_{q_{i,n+1}^{(b)}}\Big)}.$$

The fully expanded Pauli-string sum is

$$\hat{H}_{e\text{-}ph} = -\frac{g}{4}\sum_{i=0}^{L-1}\sum_{n=0}^{N_b-1}\sqrt{n+1}\Big[Z_{q_{i\uparrow}}X_{q_{i,n}^{(b)}}X_{q_{i,n+1}^{(b)}} + Z_{q_{i\uparrow}}Y_{q_{i,n}^{(b)}}Y_{q_{i,n+1}^{(b)}} + Z_{q_{i\downarrow}}X_{q_{i,n}^{(b)}}X_{q_{i,n+1}^{(b)}} + Z_{q_{i\downarrow}}Y_{q_{i,n}^{(b)}}Y_{q_{i,n+1}^{(b)}}\Big].$$

Each summand is three-local.

Final Holstein Hamiltonian in JW + unary form Collecting the phonon-energy and electron-phonon pieces,

$$\boxed{\hat{H}_{\text{Hol}}^{(\text{JW+unary})} = \omega_0\sum_{i=0}^{L-1}\sum_{n=0}^{N_b} n\,\frac{I - Z_{q_{i,n}^{(b)}}}{2} - \frac{g}{4}\sum_{i=0}^{L-1}\sum_{n=0}^{N_b-1}\sqrt{n+1}(Z_{q_{i\uparrow}} + Z_{q_{i\downarrow}})\Big(X_{q_{i,n}^{(b)}}X_{q_{i,n+1}^{(b)}} + Y_{q_{i,n}^{(b)}}Y_{q_{i,n+1}^{(b)}}\Big)}.$$

6.3 Time-dependent density drive

A general density drive may be written as

$$\hat{H}_{\text{drive}}(t) = \sum_i v_i(t)\hat{n}_i.$$

A useful waveform class is

$$v_i(t) = As_i\sin(\omega t + \phi)\exp\left[-\frac{(t-t_0)^2}{2\bar{t}^2}\right],$$

where A is the amplitude, s_i is a static spatial pattern, ω is the drive frequency, ϕ is the phase, and $\bar{t}$ is the envelope width.

6.3.1 Generic density-drive waveform surface

After inserting $\hat{n}_i = I - \frac{1}{2}(Z_{p(i,\uparrow)} + Z_{p(i,\downarrow)})$, the drive separates into an identity offset and a sum of time-dependent Z-coefficients. Thus the time dependence resides in the coefficients rather than in the operator labels.

6.4 Two HH assembly surfaces

6.4.1 Exact Hamiltonian surface

The exact surface treats $\hat{H}_{\text{HH}}(t)$ as an operator to be diagonalized, exponentiated, projected, or applied directly to statevectors.

6.4.2 Variational HH ansatz surface

The variational surface treats the same physical pieces as generator families from which one builds a structured manifold

$$|\psi(\theta)\rangle = U(\theta)|\psi_{\text{ref}}\rangle.$$

6.5 Fully substituted HH master form

The full symbolic master form is therefore

$$\hat{H}_{\mathrm{HH}}(t) = \hat{H}_{\mathrm{Hub}} + \omega_0 \sum_i \left(\hat{n}_{b,i} + \frac{1}{2}I\right) + g \sum_i \hat{x}_i(\hat{n}_i - \bar{n}I) + \sum_i v_i(t)\hat{n}_i,$$

with $\hat{n}_i$, $\hat{n}_{b,i}$, and $\hat{x}_i$ expanded according to the chosen fermion ordering and boson encoding.

7. Reference States and Exact Sector ED

7.1 Fermionic Hartree-Fock determinant

Let $\mathcal{O}$ denote the occupied spin-orbital set in a Slater determinant reference. Then

$$|\Phi_{\mathrm{HF}}\rangle = \prod_{p\in\mathcal{O}} \hat{c}_p^\dagger |\mathrm{vac}_f\rangle.$$

7.2 Hubbard-Holstein reference state

The natural HH reference is the tensor product of the phonon vacuum and fermionic Hartree-Fock state:

$$|\psi_{\mathrm{ref}}^{\mathrm{HH}}\rangle = |\mathrm{vac}_{\mathrm{ph}}\rangle \otimes |\Phi_{\mathrm{HF}}\rangle.$$

7.3 Exact HH sector basis

Fixing the fermion particle numbers $(N_\uparrow, N_\downarrow)$, the exact sector basis is

$$\mathcal{H}_{\mathrm{sector}} = \mathrm{span}\{|f\rangle \otimes |\mathbf{n}_b\rangle : |f\rangle \in \mathcal{H}_{N_\uparrow,N_\downarrow},\ 0 \le n_{b,i} \le n_{\mathrm{ph,max}}\}.$$

7.3.1 Binary index map

For binary boson encoding, one may order basis states by the pair

$$(f, \mathbf{n}_b),$$

where f is the fermionic bit pattern and $\mathbf{n}_b = (n_{b,0}, \dots, n_{b,L-1})$ is the vector of local phonon occupations, each encoded in binary.

7.3.2 Unary index map

For unary boson encoding, the same sector is indexed by

$$(f, \mathbf{e}_{n_{b,0}}, \dots, \mathbf{e}_{n_{b,L-1}}),$$

where $\mathbf{e}_n$ denotes the unary one-hot representation of occupation n.

7.4 Exact HH matrix elements

7.4.1 Diagonal elements

For basis state $|f\rangle \otimes |\mathbf{n}_b\rangle$, the diagonal contribution is

$$U \sum_i n_{i\uparrow}(f) n_{i\downarrow}(f) + \sum_i v_i\, n_i(f) + \omega_0 \sum_i \left(n_{b,i} + \frac{1}{2}\right).$$

7.4.2 Hopping matrix elements

If $|f'\rangle$ differs from $|f\rangle$ by a single allowed nearest-neighbor hop with the same phonon occupations, then

$$\langle f', \mathbf{n}_b | \hat{H}_t | f, \mathbf{n}_b\rangle = -t\,(-1)^{\chi(f;p,q)},$$

where $\chi(f;p,q)$ is the Jordan-Wigner parity count between the two fermion modes p and q.

7.4.3 Electron-phonon matrix elements

At fixed fermion configuration, the electron-phonon term changes the local phonon number by one. For site i,

$$\langle n_{b,i}+1|\hat{x}_i|n_{b,i}\rangle = \sqrt{n_{b,i}+1}, \qquad \langle n_{b,i}-1|\hat{x}_i|n_{b,i}\rangle = \sqrt{n_{b,i}}.$$

Hence the off-diagonal electron-phonon matrix elements are proportional to

$$g\,(n_i(f)-\bar{n})\sqrt{n_{b,i}+1} \quad \text{or} \quad g\,(n_i(f)-\bar{n})\sqrt{n_{b,i}},$$

according to whether the phonon occupation increases or decreases.

8. Statevector Action, Expectation, and Exponential Primitives

8.1 Basis-state primitive

A statevector on N_q qubits is written as

$$|\psi\rangle = \sum_{k=0}^{2^{N_q}-1} a_k|k\rangle = \sum_{b\in\{0,1\}^{N_q}} a_b|b\rangle.$$

8.2 Explicit Pauli-word action

Let P be a Pauli word. Then its action on a computational basis state can be written in the form

$$P|b\rangle = \omega_P(b)\,|b\oplus\chi_P\rangle,$$

where χ_P records which qubits are flipped by X or Y, and $\omega_P(b)$ is the phase determined by the Y and Z letters acting on the bitstring b.

8.3 Expectation values

If

$$\hat{H} = \sum_\alpha h_\alpha P_\alpha,$$

then the expectation value is

$$E(\psi) = \langle\psi|\hat{H}|\psi\rangle = \sum_\alpha h_\alpha\langle\psi|P_\alpha|\psi\rangle.$$

8.4 Pauli rotations

For any Hermitian Pauli word with $P^2 = I$,

$$e^{-i\theta P} = \cos\theta\, I - i\sin\theta\, P.$$

This identity is the primitive behind fast statevector application of Pauli exponentials.

8.5 Exponential of a Pauli polynomial

For a Pauli polynomial

$$A = \sum_\alpha a_\alpha P_\alpha,$$

one has

$$U_A(\theta) = e^{-i\theta A}.$$

If the P_α commute pairwise, then

$$U_A(\theta) = \prod_\alpha e^{-i\theta a_\alpha P_\alpha}.$$

If they do not commute, one may use either exact exponentiation on the working subspace or an ordered product formula.

8.6 Exact sector energy target

The natural exact comparison target in a fixed fermion sector is

$$E_{\text{exact,sector}} = \min_{\psi \in \mathcal{H}_{\text{sector}}} \langle \psi | \hat{H} | \psi \rangle.$$

This is distinct from the unrestricted full-Hilbert minimum when a sector constraint is imposed.

9. Fixed VQE Ansatz Families

This section records the main symbolic manifold families without tying them to any implementation names.

9.1 Hubbard layerwise ansatz

For the static Hubbard model, write

$$\hat{H}_{\text{Hub}} = \hat{H}_t + \hat{H}_U + \hat{H}_v.$$

A layerwise ansatz uses one parameter per physical group per layer:

$$U^{(\ell)}_{\text{Hub}} = \exp(-i\theta^{(\ell)}_t \hat{H}_t) \exp(-i\theta^{(\ell)}_U \hat{H}_U) \exp(-i\theta^{(\ell)}_v \hat{H}_v),$$

with the understanding that each grouped generator may itself be split into Pauli exponentials internally while sharing the same scalar parameter within the group.

9.2 Hubbard excitation-based surface

Relative to a Hartree-Fock occupied/virtual partition, single- and double-excitation generators take the form

$$G^{(\sigma)}_{i \to a} = i \left(\hat{c}^\dagger_{a\sigma} \hat{c}_{i\sigma} - \hat{c}^\dagger_{i\sigma} \hat{c}_{a\sigma} \right),$$

and

$$G^{(\sigma,\sigma')}_{ij \to ab} = i \left(\hat{c}^\dagger_{a\sigma} \hat{c}^\dagger_{b\sigma'} \hat{c}_{j\sigma'} \hat{c}_{i\sigma} - \text{h.c.} \right).$$

A layered excitation manifold is then

$$U_{\text{exc}}(\theta) = \prod_r e^{-i\theta_r G_r}.$$

9.3 HH layerwise ansatz

For the HH model, define grouped generators

$$G_t,\ G_U,\ G_v,\ G_{\text{ph}},\ G_g,\ G_{\text{drive}}.$$

One layer is

$$U^{(\ell)}_{\text{HH,lw}} = \exp(-i\theta_{t,\ell} G_t) \exp(-i\theta_{U,\ell} G_U) \exp(-i\theta_{v,\ell} G_v) \exp(-i\theta_{\text{ph},\ell} G_{\text{ph}}) \exp(-i\theta_{g,\ell} G_g) \exp(-i\theta_{\text{drive},\ell} G_{\text{drive}}),$$

with inactive groups omitted.

9.4 HH physical-termwise ansatz

A physical-termwise layer sits between the grouped and fully split extremes. Let

$$\mathcal{A}_{\text{phys}} = \{A_m\}$$

be the collection of unsplit physical HH generators such as bond hopping terms, onsite interactions, local phonon energies, local couplings, and local drive terms. Then

$$U^{(\ell)}_{\text{HH,phys}} = \prod_{A_m \in \mathcal{A}_{\text{phys}}} e^{-i\phi_{m,\ell} A_m}.$$

Because the generators remain grouped at the physical-operator level, this fixed-family surface stays aligned with the same conserved-sector story as the HH layerwise surface. In this symbolic HH manuscript, the canonical fixed-family surface is intentionally restricted to the sector-preserving HH layerwise and HH physical-termwise families.

9.5 Reference-state and ansatz pairing principle

The reference state and variational family should be paired by three criteria:

1. the conserved sector they preserve,
2. the expressive scale needed by the target Hamiltonian,
3. the conditioning and optimization burden induced by the chosen parameterization.

10. Polaronic Operator Families

10.1 Primitive polaronic ingredients

10.1.1 Shifted density

If the total electron number is N_e, define the mean density

$$\bar{n} = \frac{N_e}{L},$$

and the shifted density

$$\tilde{n}_i = \hat{n}_i - \bar{n}I.$$

At half filling $N_e = L$, this reduces to

$$\tilde{n}_i = -\frac{1}{2}(Z_{p(i,\uparrow)} + Z_{p(i,\downarrow)}).$$

10.1.2 Phonon primitives P_i and x_i

Define

$$P_i = i(\hat{b}_i^\dagger - \hat{b}_i), \qquad x_i = \hat{b}_i + \hat{b}_i^\dagger.$$

10.1.3 Local squeeze primitive

A natural local squeeze generator is

$$S_i = i\left((\hat{b}_i^\dagger)^2 - \hat{b}_i^2\right).$$

10.1.4 Doublon primitive

The doublon projector is

$$D_i = \hat{n}_{i\uparrow}\hat{n}_{i\downarrow}.$$

10.1.5 Even hopping channel

A bond-even hopping operator is

$$T_{ij}^{(+)} = \sum_\sigma \left(\hat{c}_{i\sigma}^\dagger \hat{c}_{j\sigma} + \hat{c}_{j\sigma}^\dagger \hat{c}_{i\sigma}\right).$$

10.1.6 Odd current channel

A bond-odd current operator is

$$J_{ij}^{(-)} = i\sum_\sigma \left(\hat{c}_{i\sigma}^\dagger \hat{c}_{j\sigma} - \hat{c}_{j\sigma}^\dagger \hat{c}_{i\sigma}\right).$$

10.2 Representative dressed channels

The exact family boundaries can vary, but the symbolic equivalents of the common channels can be written as follows.

10.2.1 Conditional displacement

$$G_i^{(\mathrm{cd})} = \tilde{n}_i P_i.$$

10.2.2 Doublon dressing

$$G_i^{(\mathrm{dd})} = D_i P_i.$$

10.2.3 Dressed hopping drag

$$G_{ij}^{(\mathrm{hd})} = T_{ij}^{(+)}(P_i - P_j).$$

10.2.4 Odd-channel drag

$$G_{ij}^{(\mathrm{od})} = J_{ij}^{(-)}(x_i - x_j).$$

10.2.5 Second-order even channel

$$G_{ij}^{(2)} = T_{ij}^{(+)}(x_i - x_j)^2.$$

10.2.6 Third-order odd current channel

$$G_{ij}^{(3)} = J_{ij}^{(-)}(x_i - x_j)^3.$$

10.2.7 Fourth-order even hopping channel

$$G_{ij}^{(4)} = T_{ij}^{(+)}(x_i - x_j)^4.$$

10.2.8 Bond-conditioned displacement and squeeze channels

With a bond-sensitive scalar observable B_{ij}, one may write

$$G_{ij}^{(\mathrm{bd})} = B_{ij} P_i, \qquad G_{ij}^{(\mathrm{bs})} = B_{ij} S_i.$$

A simple choice is $B_{ij} = \hat{n}_i - \hat{n}_j$.

10.2.9 Local squeeze channels

$$G_i^{(\mathrm{sq})} = S_i, \qquad \tilde{G}_i^{(\mathrm{sq})} = \tilde{n}_i S_i.$$

10.2.10 Extended cloud channels

A symbolic extended cloud family is

$$G_i^{(\mathrm{cloud})} = \tilde{n}_i \sum_{r \in \mathcal{N}(i)} \alpha_{ir} P_r,$$

with coefficients α_{ir} controlling cloud shape.

10.2.11 Doublon-translation and doublon-squeeze channels

$$G_{ij}^{(\mathrm{DT})} = D_i T_{ij}^{(+)}, \qquad G_i^{(\mathrm{DS})} = D_i S_i.$$

10.3 Pool-family map

A useful abstract partition is

$$\mathcal{G} = \mathcal{G}_{\mathrm{local}} \cup \mathcal{G}_{\mathrm{bond}} \cup \mathcal{G}_{\mathrm{squeeze}} \cup \mathcal{G}_{\mathrm{cloud}} \cup \mathcal{G}_{\mathrm{doublon}}.$$

These families can be opened gradually rather than all at once.

10.3.1 Compact displacement/squeeze macro families

Two especially compact subfamilies are

$$\mathcal{G}_{\mathrm{VLF}} = \{\tilde{n}_i P_i\}_i, \qquad \mathcal{G}_{\mathrm{SQ}} = \{S_i, \tilde{n}_i S_i\}_i.$$

They act as coarse polaronic and squeeze envelopes.

11. Adaptive Selection and Staged Continuation

11.1 Cumulative phase construction for adaptive selection

Rather than treating Phase 1, Phase 2, and Phase 3 as three unrelated selector passes tried in reverse order, the current HH continuation logic is best read cumulatively. We write

$$\mathcal{G}^{(3)} \subseteq \mathcal{G}^{(2)} \subseteq \mathcal{G}^{(1)} \subseteq \mathcal{G},$$

where $\mathcal{G}$ is the full expensive master pool, but the later phases reuse the earlier scoring and refinement machinery rather than replacing it with an unrelated fallback pass.

In that cumulative reading:

- **Phase 1** provides the broad cheap-screen surface over candidate-position records,
- **Phase 2** reuses the Phase-1 records and adds shortlist-and-full-rerank refinement,
- **Phase 3** reuses the Phase-1 and Phase-2 machinery and adds the highest-level augmentations used in current HH mainline.

Separately, the runtime controller may broaden the currently exposed candidate family through controller-stage transitions such as `seed/core $\to$ residual`; that controller-stage evolution should not be confused with the Phase-1/2/3 sophistication labels.

So the exposition below is written in the same constructive order **Phase 1** $\to$ **Phase 2** $\to$ **Phase 3** that the cumulative selector surface itself follows.

11.2 Phase 1 broad fallback selector surface

11.2.1 Core signal, append position, and refit window

Let $g \in \mathcal{G}^{(1)}$ be a candidate generator and p a candidate insertion position. Let $W(p)$ denote the parameter window that is allowed to refit after insertion at p. The local post-refit drop is abstractly

$$\delta E(g,p) = E(\theta) - \min_{\vartheta \in W(p)} E\big(\theta \oplus_p (g,\vartheta)\big).$$

ie the old scaffold energy - energy-imporvement caused by reoptimizing generators within a window inserted about position p

11.2.2 Gates, burdens, and feature ingredients

Each candidate-position pair is filtered by admissibility gates and assigned a burden

$$B(g,p) = \lambda_{2\mathrm{q}} C_{2\mathrm{q}}(g,p) + \lambda_d D(g,p) + \lambda_\theta \Delta K(g,p),$$

where $C_{2\mathrm{q}}$ is a two-qubit proxy cost, D is a depth proxy, and ΔK is the marginal parameter count.

11.2.3 Cheap score

A Phase-1 broad score closes immediately to

$$\begin{aligned} S_1(g,p) &= \frac{\underline{\delta E}(g,p)}{B(g,p)+\varepsilon} \\ &= \frac{\underline{\delta E}(g,p)}{\lambda_{2\mathrm{q}} C_{2\mathrm{q}}(g,p) + \lambda_d D(g,p) + \lambda_\theta \Delta K(g,p) + \varepsilon}, \end{aligned}$$

where $\underline{\delta E}$ is a lower-bound or surrogate estimate of useful post-refit energy drop.

11.2.4 Position probing, trough detection, and effective selector

Rather than selecting only by generator identity, one probes positions p and computes

$$(g_1, p_1) = \arg\max_{(g,p)} S_1(g,p).$$

If the best score remains below threshold across all positions, that can be treated as a plateau or trough signal.

11.2.5 Full-pool limiting case

If one removes the structured shortlist machinery and keeps only the final full-pool backstop, the limiting Phase-1 rule becomes: choose the admissible generator with largest gradient magnitude,

$$g_* = \arg \max_{g \in \mathcal{G}^{(1)}_{\text{admissible}}} |\partial_\epsilon E(\epsilon; g)|_{\epsilon=0}|,$$

subject to symmetry and cost gates.

11.3 Phase 2 relaxed selector surface

Phase 2 should be read as an extension of the Phase-1 cheap screen: it keeps the same candidate-position language, but adds shortlist formation and a richer reranking model on top of the earlier score. More precisely, Phase 1 does not hand Phase 2 only the single best record from §11.2.4; it hands forward a retained family of candidate-position records, and the explicit retained set is the shortlist $\mathcal{S}_2$ defined below by threshold or Top-K on S_1.

11.3.1 Core signal, append position, refit window, and cheap screen

The Phase-2 selector works over candidate-position pairs with

$$g \in \mathcal{G}^{(2)}, \qquad p \in \mathcal{P}_g,$$

and the cheap screening surface closes as

$$\begin{aligned}
\delta E(g,p) &= E(\theta) - \min_{\vartheta \in W(p)} E(\theta \oplus_p (g,\vartheta)),\\
B(g,p) &= \lambda_{2\mathrm{q}} C_{2\mathrm{q}}(g,p) + \lambda_d D(g,p) + \lambda_\theta \Delta K(g,p),\\
S_1(g,p) &= \frac{\underline{\delta E}(g,p)}{B(g,p)+\varepsilon} = \frac{\underline{\delta E}(g,p)}{\lambda_{2\mathrm{q}} C_{2\mathrm{q}}(g,p) + \lambda_d D(g,p) + \lambda_\theta \Delta K(g,p) + \varepsilon}.
\end{aligned}$$

11.3.2 Shortlist rule

Define the shortlist by threshold or cap:

$$\begin{aligned}
\mathcal{S}_2 &= \{(g,p) : S_1(g,p) \geq \tau_1\} \quad \text{or} \quad \mathrm{Top}_K\{(g,p) \text{ by } S_1(g,p)\}\\
&= \big\{(g,p) : \underline{\delta E}(g,p) \geq \tau_1 \big[\lambda_{2\mathrm{q}} C_{2\mathrm{q}}(g,p) + \lambda_d D(g,p) + \lambda_\theta \Delta K(g,p) + \varepsilon\big]\big\}\\
&\qquad \text{or} \quad \mathrm{Top}_K \left\{(g,p) \text{ by } \frac{\underline{\delta E}(g,p)}{\lambda_{2\mathrm{q}} C_{2\mathrm{q}}(g,p) + \lambda_d D(g,p) + \lambda_\theta \Delta K(g,p) + \varepsilon}\right\}.
\end{aligned}$$

If $\pi_g(g,p) = g$ denotes projection onto generator identity, then the generators actually carried forward by the shortlist are $\pi_g(\mathcal{S}_2)$. We therefore do not write $\mathcal{G}^{(2)} = \mathcal{S}_2$: $\mathcal{G}^{(2)}$ lives in generator space, whereas $\mathcal{S}_2$ is a state-dependent shortlist of candidate-position records.

11.3.3 Reduced-path geometry, novelty, curvature, and trust-region drop

For a shortlisted record (g,p), let

$$|\psi\rangle = U_{>p}\, U_{\leq p}\, |\psi_0\rangle, \qquad |\psi_{(m,p)}(\alpha)\rangle = U_{>p}\, e^{-i\alpha A_m}\, U_{\leq p}\, |\psi_0\rangle,$$

$$\widetilde{A}_{(m,p)} := U_{>p}\, A_m\, U_{>p}^\dagger, \qquad U_{>p} := U_K(\theta_K) \cdots U_{p+1}(\theta_{p+1}),$$

$$|\psi_{(m,p)}(\alpha)\rangle = e^{-i\alpha \widetilde{A}_{(m,p)}} |\psi\rangle, \qquad \partial_\alpha |\psi_{(m,p)}(\alpha)\rangle\big|_{\alpha=0} = -i\, \widetilde{A}_{(m,p)} |\psi\rangle.$$

$$
\begin{aligned}
U_{g,p}(\alpha) &= e^{-i\alpha \widetilde{A}_{g,p}}, \qquad |\psi_{g,p}(\alpha)\rangle = U_{g,p}(\alpha)|\psi\rangle, \qquad Q_\psi = I - |\psi\rangle\langle\psi|,\\
|d_{g,p}\rangle &= \partial_\alpha |\psi_{g,p}(\alpha)\rangle\big|_{\alpha=0} = -i\widetilde{A}_{g,p}|\psi\rangle, \qquad |d^{(2)}_{g,p}\rangle = \partial^2_\alpha |\psi_{g,p}(\alpha)\rangle\big|_{\alpha=0} = -\widetilde{A}^2_{g,p}|\psi\rangle,\\
\tau_{g,p} &= Q_\psi |d_{g,p}\rangle = Q_\psi\, \partial_\alpha |\psi_{g,p}(\alpha)\rangle\big|_{\alpha=0} = -iQ_\psi \widetilde{A}_{g,p}|\psi\rangle,\\
g(g,p) &= \partial_\alpha \langle\psi_{g,p}(\alpha)|H|\psi_{g,p}(\alpha)\rangle\big|_{\alpha=0} = 2\Re\langle\psi|H|d_{g,p}\rangle,\\
g_{\mathrm{lcb}}(g,p) &= \max\{|g(g,p)| - z_\alpha \sigma(g,p), 0\}.
\end{aligned}
$$

If $\{\tau_j\}_{j\in W(p)}$ are the current horizontal tangents in the inherited window, then

$$
\begin{aligned}
F(g,p) &= \|\tau_{g,p}\|^2 = \langle \tau_{g,p}, \tau_{g,p}\rangle = \langle d_{g,p}|Q_\psi|d_{g,p}\rangle,\\
\mathcal{N}(g,p) &= 1 - \max_{j\in W(p)} \frac{|\langle \tau_{g,p}, \tau_j\rangle|}{\|\tau_{g,p}\|\,\|\tau_j\|} = 1 - \max_{j\in W(p)} \frac{|\langle d_{g,p}|Q_\psi|\partial_{\theta_j}\psi\rangle|}{\sqrt{\langle d_{g,p}|Q_\psi|d_{g,p}\rangle}\sqrt{\langle \partial_{\theta_j}\psi|Q_\psi|\partial_{\theta_j}\psi\rangle}},\\
\kappa(g,p) &= h_{g,p} = \partial^2_\alpha \langle\psi_{g,p}(\alpha)|H|\psi_{g,p}(\alpha)\rangle\big|_{\alpha=0} = 2\Re\Big(\langle d_{g,p}|H|d_{g,p}\rangle + \langle\psi|H|d^{(2)}_{g,p}\rangle\Big),\\
\delta E_{\mathrm{TR}}(g,p) &= \max_{|\alpha|\le \rho/\sqrt{F(g,p)}} \left[g_{\mathrm{lcb}}(g,p)|\alpha| - \frac{1}{2}\max(h_{g,p},0)\alpha^2 \right],\\
\delta E_{\mathrm{quad}}(g,p) &= \frac{g_{\mathrm{lcb}}(g,p)^2}{2h_{g,p}} \qquad \text{when } h_{g,p} > 0 \text{ and the unconstrained minimizer lies inside the trust region.}
\end{aligned}
$$

11.3.4 Full rerank score and effective selector

The Phase-2 rerank score is not just symbolically

$$
S_2(g,p) = \frac{\delta E_{\mathrm{TR}}(g,p)\,\mathcal{N}(g,p)}{B(g,p)(1+\kappa(g,p)) + \varepsilon},
$$

but, after substitution of the local burden, miss, curvature, and tangent geometry,

$$
\begin{aligned}
S_2(g,p) &= \frac{\delta E_{\mathrm{TR}}(g,p)\,\mathcal{N}(g,p)}{[\lambda_{2\mathrm{q}} C_{2\mathrm{q}}(g,p) + \lambda_d D(g,p) + \lambda_\theta \Delta K(g,p)](1+h_{g,p}) + \varepsilon}\\
&= \frac{\max\limits_{|\alpha|\le\rho/\sqrt{\langle d_{g,p}|Q_\psi|d_{g,p}\rangle}} \left[\max\{|2\Re\langle\psi|H|d_{g,p}\rangle| - z_\alpha\sigma(g,p),0\}|\alpha| - \frac{1}{2}\max\Big(2\Re(\langle d_{g,p}|H|d_{g,p}\rangle + \langle\psi|H|d^{(2)}_{g,p}\rangle),0\Big)\alpha^2 \right]}{[\lambda_{2\mathrm{q}} C_{2\mathrm{q}}(g,p) + \lambda_d D(g,p) + \lambda_\theta \Delta K(g,p)]\Big(1 + 2\Re(\langle d_{g,p}|H|d_{g,p}\rangle + \langle\psi|H|d^{(2)}_{g,p}\rangle)\Big) + \varepsilon}\\
&\quad \times \left(1 - \max_{j\in W(p)} \frac{|\langle d_{g,p}|Q_\psi|\partial_{\theta_j}\psi\rangle|}{\sqrt{\langle d_{g,p}|Q_\psi|d_{g,p}\rangle}\sqrt{\langle \partial_{\theta_j}\psi|Q_\psi|\partial_{\theta_j}\psi\rangle}} \right).
\end{aligned}
$$

The selected candidate is then

$$
(g_2, p_2) = \arg\max_{(g,p)\in\mathcal{S}_2} S_2(g,p).
$$

11.4 Phase 3 primary selector surface

This section describes the full symbolic Phase-3 selector surface: position-aware candidate records, inherited refit windows, and split-aware reranking. In current HH mainline, Phase 3 is not a separate reverse-order fallback pass; it reuses the Phase-1 cheap screen and the Phase-2 shortlist/full-rerank machinery, then adds the highest-level augmentations used in runtime policy.

11.4.1 Core signal, append position, refit window, and cheap screen

The cumulative Phase-3 selector is most naturally written over candidate-position pairs

$$
r = (m,p), \qquad m \in \mathcal{G}^{(3)}_{\mathrm{avail}}, \quad p \in \mathcal{P}_m.
$$

Here m is a candidate generator, p is a candidate insertion position, and $\mathcal{P}_m$ is the set of admissible positions for m.

The inherited refit window attached to position p is denoted $W(p)$. A useful decomposition is

$$W(p) = W_{\text{new}}(p) \cup W_{|\theta|}(p),$$

where W_{new} keeps the newest coordinates and $W_{|\theta|}$ optionally preserves a small set of older large-amplitude coordinates.

The raw candidate-position universe entering the cumulative Phase-3 selector is

$$\mathcal{P}^{(3)}_{\text{avail}} = \left\{ r = (m,p) : m \in \mathcal{G}^{(3)}_{\text{avail}},\ p \in \mathcal{P}_m \right\}.$$

Let

$$N_{\text{cheap}} = \min\left\{ N^{\max}_{\text{cheap}}, \left|\mathcal{P}^{(3)}_{\text{avail}}\right| \right\}$$

be the active cheap-pass size, where $N^{\max}_{\text{cheap}}$ is the Phase-3 cheap-pass cap. Then the cheap universe is the gradient-ranked capped subset

$$\mathcal{C}_{\text{cheap}} = \text{Top}_{N_{\text{cheap}}}\left(\mathcal{P}^{(3)}_{\text{avail}}; g_{\text{lcb}}\right),$$

that is, the set of the top N_{cheap} records in $\mathcal{P}^{(3)}_{\text{avail}}$ ranked by the lower-confidence gradient signal $g_{\text{lcb}}(r)$ defined below.

For $r = (m,p)$, let

$$\begin{aligned}
U_r(\alpha) &= e^{-i\alpha \widetilde{A}_r}, \\
|\psi_r(\alpha)\rangle &= U_r(\alpha)|\psi\rangle, \\
Q_\psi &= I - |\psi\rangle\langle\psi|, \\
|d_r\rangle &= \partial_\alpha |\psi_r(\alpha)\rangle|_{\alpha=0} = -i\widetilde{A}_r|\psi\rangle, \\
t_r &= Q_\psi |d_r\rangle, \\
F_{\text{raw}}(r) &= \|t_r\|^2 = \langle d_r|Q_\psi|d_r\rangle, \\
g_r &= \partial_\alpha \langle\psi_r(\alpha)|H|\psi_r(\alpha)\rangle|_{\alpha=0} = 2\Re\langle\psi|H|d_r\rangle, \\
g_{\text{lcb}}(r) &= \max\{|g_r| - z_\alpha \sigma_r, 0\}, \\
\Gamma_{\text{stage}}(r) &:= \Gamma_{\text{stage}}(m), \\
\Gamma_{\text{sym}}(r) &:= \Gamma_{\text{sym}}(m,p), \\
K_{\text{cheap}}(r) &= 1 + w_R \bar{R}_{\text{rem}}(r) + w_D \bar{D}_{\text{life}}(r) \\
&\quad + w_G \bar{G}_{\text{new}}(r) + w_C \bar{C}_{\text{new}}(r) + w_c \bar{c}(r).
\end{aligned}$$

Yes—here is the full term expansion you asked for, in symbolic form:

$$K_{\text{cheap}}(r) = 1 + w_R \bar{R}_{\text{rem}}(r) + w_D \bar{D}_{\text{life}}(r) + w_G \bar{G}_{\text{new}}(r) + w_C \bar{C}_{\text{new}}(r) + w_c \bar{c}(r)$$

with

$$\bar{D}_{\text{life}}(r) = \frac{D_{\text{raw}}(r)}{\text{depth_ref}}, \quad D_{\text{raw}}(r) = \sum_{\ell \in \mathcal{L}_r} \left[2\max(\text{wt}(\ell) - 1, 0) + \frac{1}{2}(2\,\#_{X,Y}(\ell) + 1) \right] + |p_{\text{app}} - p|,$$

where $\mathcal{L}_r$ is the active Pauli-label set for the candidate term (fallback is $\max(1, \text{candidate_term_count}) + |p_{\text{app}} - p|$).

$$\bar{G}_{\text{new}}(r) = \frac{G_{\text{new}}(r)}{\text{group_ref}}, \quad G_{\text{new}}(r) = |\mathcal{G}_{\text{new}}(r)|,$$

$$\bar{C}_{\text{new}}(r) = \frac{C_{\text{new}}(r)}{\text{shot_ref}}, \quad C_{\text{new}}(r) = G_{\text{new}}(r) \cdot n_{\text{shots/group}},$$

$$\bar{c}(r) = \frac{c(r)}{\text{reuse_ref}}, \quad c(r) = \text{groups_new}(r),$$

$$\bar{R}_{\text{rem}}(r) = N_{\text{rem}}\big(\bar{D}_{\text{life}} + \bar{G}_{\text{new}} + \bar{C}_{\text{new}} + \bar{c} + \bar{P}_{\text{opt}}\big)\,\mathbf{1}_{\text{lifetime mode}}, \quad N_{\text{rem}} = \max(1, d_{\max} - d + 1), \quad \bar{P}_{\text{opt}} = \frac{|W(p)|}{\text{optdim_ref}}.$$

Qualitatively: $\bar{D}_{\text{life}}$ is circuit/compile burden at the candidate record, $\bar{G}_{\text{new}}$ and $\bar{C}_{\text{new}}$ are measurement-group and shot burden of the new term, $\bar{c}$ is the reuse penalty, and $\bar{R}_{\text{rem}}$ is the remaining-depth lifetime discount/multiplier applied only when lifetime-cost mode is on. So the Phase-1-style cheap screen reused inside the cumulative Phase-3 selector is not only symbolically but explicitly

$$\begin{aligned} S_{3,\text{cheap}}(r) &= \Gamma_{\text{stage}}(r)\Gamma_{\text{sym}}(r)\frac{g_{\text{lcb}}(r)^2}{2\lambda_F F_{\text{raw}}(r)}\frac{1}{K_{\text{cheap}}(r)+\varepsilon} \\ &= \Gamma_{\text{stage}}(r)\Gamma_{\text{sym}}(r)\frac{\max\{|2\Re\langle\psi|H|d_r\rangle| - z_\alpha\sigma_r, 0\}^2}{2\lambda_F\langle d_r|Q_\psi|d_r\rangle\,(K_{\text{cheap}}(r)+\varepsilon)}. \end{aligned}$$

This cheap screen is meant to be wide relative to the final shortlist but still inexpensive relative to a full local-model rebuild: it keeps only the strongest cheap gradient proposals before the later shortlist, local geometry, novelty, and rerank machinery is applied.

Math

$$K_{\text{cheap}}(r) = 1 + w_R\,\bar{R}_{\text{rem}}(r) + w_D\,\bar{D}_{\text{life}}(r) + w_G\,\bar{G}_{\text{new}}(r) + w_C\,\bar{C}_{\text{new}}(r) + w_c\,\bar{c}(r), \qquad r = (m,p).$$

$$\bar{D}_{\text{life}}(r) = \frac{D_{\text{raw}}(r)}{\text{depth}_{\text{ref}}}, \qquad D_{\text{raw}}(r) = \sum_{\ell\in\mathcal{L}_r}\Big[2\max(\text{wt}(\ell)-1,0) + \frac{1}{2}\big(2\,\#_{X,Y}(\ell)+1\big)\Big] + |p_{\text{app}} - p|,$$

$$\bar{G}_{\text{new}}(r) = \frac{G_{\text{new}}(r)}{\text{group}_{\text{ref}}}, \qquad \bar{C}_{\text{new}}(r) = \frac{C_{\text{new}}(r)}{\text{shot}_{\text{ref}}}, \qquad \bar{c}(r) = \frac{c(r)}{\text{reuse}_{\text{ref}}}, \qquad C_{\text{new}}(r) = G_{\text{new}}(r)\,n_{\text{shots/group}}, \qquad c(r) = \text{groups}_{\text{new}}(r),$$

$$\bar{R}_{\text{rem}}(r) = N_{\text{rem}}\,\big(\bar{D}_{\text{life}} + \bar{G}_{\text{new}} + \bar{C}_{\text{new}} + \bar{c} + \bar{P}_{\text{opt}}\big)\,\mathbf{1}_{\text{lifetime}}, \qquad N_{\text{rem}} = \max(1, d_{\max} - d + 1), \qquad \bar{P}_{\text{opt}} = \frac{|W(p)|}{\text{optdim}_{\text{ref}}}.$$

From first principles, $K_{\text{cheap}}(r)$ is a dimensionless burden functional: the numerator of $S_{3,\text{cheap}}(r)$ estimates local benefit, and $K_{\text{cheap}}(r)$ discounts that benefit by how expensive it is to admit r now and, through $\bar{R}_{\text{rem}}$, how expensive that decision is likely to remain over the rest of the run. The $2\max(\text{wt}(\ell)-1,0)$ piece is a two-qubit-style burden proxy, the $\frac{1}{2}(2\,\#_{X,Y}(\ell)+1)$ piece is a basis-change / one-qubit rotation proxy, and $|p_{\text{app}} - p|$ penalizes inserting far from the current append location.

11.4.2 Shortlist, reduced-path geometry, novelty, full rerank score, and split-aware augmentation

The shortlist size is

$$N_{\text{short}} = \min\left\{|\mathcal{C}_{\text{cheap}}|, N_{\max}, \lceil f_{\text{short}}|\mathcal{C}_{\text{cheap}}|\rceil\right\}, \qquad \mathcal{S}_3 \subseteq \mathcal{C}_{\text{cheap}}.$$

So the flow is

$$\mathcal{P}^{(3)}_{\text{avail}} \longrightarrow \mathcal{C}_{\text{cheap}} \longrightarrow \mathcal{S}_3 \longrightarrow \arg\max_{r\in\mathcal{S}_3} S_{3,\text{base}}(r) \text{ or } \arg\max_{r\in\mathcal{S}_3} S_{3,\text{aug}}(r),$$

where the first arrow is the reused Phase-1 cheap screen, the middle arrow forms the internal shortlist, and the later arrows perform the richer reranking and Phase-3 augmentation built on top of the earlier surfaces.

For each shortlisted record $r = (m, p)$, let $W_r = W(m, p)$ be the inherited window that would actually be refit if m were admitted at position p, and let $\{t_j\}_{j \in W_r}$ be the current horizontal tangents in that inherited window. Then

$$
\begin{aligned}
F_{\text{raw}}(r) &= \langle t_r, t_r \rangle, \\
(Q_r)_{jk} &= \Re\langle t_j, t_k \rangle, \\
(q_r)_j &= \Re\langle t_j, t_r \rangle, \\
E(\alpha, \delta\theta_{W_r}; r) &\approx E_0 + g_r \alpha + \tfrac{1}{2} h_r \alpha^2 \\
&\quad + \alpha b_r^\top \delta\theta_{W_r} + \tfrac{1}{2} \delta\theta_{W_r}^\top H_{W_r} \delta\theta_{W_r}, \\
M_r &= \tfrac{1}{2}(H_{W_r} + H_{W_r}^\top) + \lambda_H I, \\
\tilde{h}_r &= h_r - b_r^\top M_r^{-1} b_r, \\
F_r^{\text{red}} &= F_{\text{raw}}(r) - 2 q_r^\top M_r^{-1} b_r + b_r^\top M_r^{-1} Q_r M_r^{-1} b_r, \\
q_r^{\text{red}} &= q_r - Q_r M_r^{-1} b_r, \\
\nu_r &= \text{clip}_{[0,1]}\left(1 - \frac{(q_r^{\text{red}})^\top (Q_r + \varepsilon_{\text{nov}} I)^{-1} q_r^{\text{red}}}{F_r^{\text{red}}}\right), \\
\Delta E_{\text{TR}}(r) &= \max_{|\alpha| \le \rho/\sqrt{F_r^{\text{red}}}} \left[g_{\text{lcb}}(r)|\alpha| - \tfrac{1}{2} \max(\tilde{h}_r, 0)\alpha^2 \right], \\
K_{\text{full}}(r) &= 1 + w_R \bar{R}_{\text{rem}}(r) + w_D \bar{D}_{\text{life}}(r) \\
&\quad + w_G \bar{G}_{\text{new}}(r) + w_C \bar{C}_{\text{new}}(r) + w_c \bar{c}(r).
\end{aligned}
$$

So the base rerank score closes to

$$
\begin{aligned}
S_{3,\text{base}}(r) &= \Gamma_{\text{stage}}(m) \Gamma_{\text{sym}}(r)\, \nu_r^{\gamma_N} \frac{\Delta E_{\text{TR}}(r)}{K_{\text{full}}(r) + \varepsilon} \\
&= \Gamma_{\text{stage}}(m) \Gamma_{\text{sym}}(r) \left[\text{clip}_{[0,1]}\left(1 - \frac{(q_r^{\text{red}})^\top (Q_r + \varepsilon_{\text{nov}} I)^{-1} q_r^{\text{red}}}{F_r^{\text{red}}}\right) \right]^{\gamma_N} \frac{\Delta E_{\text{TR}}(r)}{K_{\text{full}}(r) + \varepsilon}.
\end{aligned}
$$

The augmented selector score is therefore

$$
\begin{aligned}
S_{3,\text{aug}}(r) &= S_{3,\text{base}}(r) + \beta_{\text{split}} \Sigma(r) + \beta_{\text{motif}} M(r) + \beta_{\text{sym}} Y(r) - \beta_{\text{dup}} D_{\text{dup}}(r) \\
&= \Gamma_{\text{stage}}(m) \Gamma_{\text{sym}}(r) \left[\text{clip}_{[0,1]}\left(1 - \frac{(q_r^{\text{red}})^\top (Q_r + \varepsilon_{\text{nov}} I)^{-1} q_r^{\text{red}}}{F_r^{\text{red}}}\right) \right]^{\gamma_N} \frac{\Delta E_{\text{TR}}(r)}{K_{\text{full}}(r) + \varepsilon} \\
&\quad + \beta_{\text{split}} \Sigma(r) + \beta_{\text{motif}} M(r) + \beta_{\text{sym}} Y(r) - \beta_{\text{dup}} D_{\text{dup}}(r).
\end{aligned}
$$

Here Σ measures the gain available from selective macro-splitting, M measures motif compatibility or transferable local pattern alignment, Y measures symmetry quality or mitigation value, and D_{dup} penalizes near-duplicate continuation directions.[1] If a shortlisted macro generator m admits a split family

$$
\mathcal{C}_{\text{split}}(m) = \{m_1, \dots, m_{K_m}\},
$$

then each split child inherits the same position p and therefore defines a child record $r_j = (m_j, p)$, with replacement rule

$$
r \rightsquigarrow r_j^* \quad \text{if} \quad \max_j S_{3,\text{aug}}(r_j) > S_{3,\text{aug}}(r) + \tau_{\text{split}}.
$$

$$
\mathcal{S}_3 = \{r_1, \dots, r_N\}, \qquad s(r) = S_{3,\text{aug}}(r) \text{ or } S_{3,\text{base}}(r),
$$

and let the shortlist be sorted so that

$$
s(r_1) \ge s(r_2) \ge \cdots \ge s(r_N).
$$

A batch selector does not choose a single winner; it chooses a set

$$
\mathcal{B}_{\text{batch}} \subseteq \mathcal{S}_3, \qquad 1 \le |\mathcal{B}_{\text{batch}}| \le B_{\text{cap}},
$$

[1] These four addends are intentionally higher-level selector covariates. They should be read as implementation-facing heuristic modifiers layered on top of the primitive geometric score $S_{3,\text{base}}$, not as unique primitive invariants with a single repo-independent closed form.

by starting from the top record and then greedily adding near-degenerate compatible records.

$$r \in \mathcal{B}_{\text{batch}} \quad \Longrightarrow \quad s(r) \geq \eta_{\text{nd}}\, s(r_{\max}),$$

where $r_{\max}$ is the top shortlisted record and $0 < \eta_{\text{nd}} \leq 1$ is the near-degeneracy ratio. In other words, only candidates whose score is sufficiently close to the best score are even allowed to compete for the same batch.

Then define a pairwise incompatibility penalty

$$\Pi(r, r') = w_{\text{ov}}\, \Omega(r, r') + w_{\text{comm}}\, \Xi(r, r') + w_{\text{curv}}\, \mathcal{K}(r, r') + w_{\text{sched}}\, \mathcal{A}(r, r') + w_{\text{meas}}\, \mathcal{M}(r, r'),$$

with

$$\Omega(r, r') = \frac{|\operatorname{supp}(r) \cap \operatorname{supp}(r')|}{|\operatorname{supp}(r) \cup \operatorname{supp}(r')|}, \qquad \Xi(r, r') = \begin{cases} 0, & \text{if the candidate generators commute,} \\ 1, & \text{otherwise,} \end{cases}$$

$$\mathcal{K}(r, r') = \text{cross-curvature / tangent-overlap proxy}, \qquad \mathcal{A}(r, r') = \frac{|W_r \cap W_{r'}|}{|W_r \cup W_{r'}|}, \qquad \mathcal{M}(r, r') = 1 - \text{measurement-overlap}(r, r').$$

[2]

The greedy admission rule is then

$$r \text{ is appended to } \mathcal{B}_{\text{batch}} \quad \Longrightarrow \quad s(r) - \sum_{r' \in \mathcal{B}_{\text{batch}}} \Pi(r, r') > 0,$$

together with

$$|\mathcal{B}_{\text{batch}}| < B_{\text{target}} \quad \text{or at worst} \quad |\mathcal{B}_{\text{batch}}| < B_{\text{cap}}.$$

So batch selection is a greedy set-building rule:

$$\mathcal{B}_{\text{batch},0} = \emptyset, \qquad \mathcal{B}_{\text{batch},k+1} = \mathcal{B}_{\text{batch},k} \cup \{r\} \text{ only if } r \text{ is near-degenerate and still has positive net value after penalties.}$$

Qualitatively, batch means "several shortlisted candidates are so similarly good that we admit more than one at the same ADAPT depth, provided they do not clash too much." It is not beam: beam keeps multiple alternative scaffolds alive, while batch commits multiple compatible admissions into one scaffold immediately. It is also not a joint global optimizer over subsets; it is a greedy compatibility-filtered multi-admission rule.

11.4.3 Beam-adapt over scaffold alternatives: branch state, pruning, and effective selector

In this section beam-adapt is **purely structural**: each branch carries an alternative ADAPT scaffold together with its locally refit amplitudes. There is no time checkpoint, probe rollout, or projected-dynamics integral in this section. Those belong to the separate time-dynamics beam surface developed in §17.

The cleanest way to read a live scaffold branch is

$$\mathfrak{b} = (\text{identity/history;}\ \text{current scaffold and amplitudes;}\ \text{current energy/depth;}\ \text{cumulative selector totals/status}).$$

More explicitly, write

$$\begin{aligned} \mathfrak{b} &= (\mathrm{id}_b, \pi_b, \mathcal{H}_b, \mathcal{O}_b, \theta_b, E_b, d_b, S_b^{\text{cum}}, K_b^{\text{cum}}, \sigma_b, \tau_b), \\ \mathcal{H}_b &= (r_{b,1}, \dots, r_{b,d_b}), \qquad r_{b,j} = (m_{b,j}^{\text{adm}}, p_{b,j}^{\text{adm}}), \\ \mathcal{O}_b &= (m_{b,1}, \dots, m_{b,|\mathcal{O}_b|}), \qquad E_b = E(\theta_b; \mathcal{O}_b), \\ S_b^{\text{cum}} &= \sum_{j=1}^{d_b} s_{b,j}, \qquad K_b^{\text{cum}} = \sum_{j=1}^{d_b} \kappa_{b,j}. \end{aligned}$$

Here id_b and π_b are the branch and parent identifiers, $\mathcal{H}_b$ is the ordered history of admitted records, $\mathcal{O}_b$ is the scaffold currently carried by branch b, θ_b is the refit parameter vector on that scaffold, E_b is the current variational energy, d_b is the branch ADAPT depth, $s_{b,j}$ and $\kappa_{b,j}$ are the selector score and burden increment contributed by the jth admitted record in $\mathcal{H}_b$, and (σ_b, τ_b) record live/terminal status and termination label.

[2] Batch note: $\mathcal{K}$ and $\mathcal{M}$ are proxy penalties rather than primitive-closed observables. On paper they are best interpreted as controller-supplied overlap costs used to discourage mutually awkward co-admissions.

If beam search is entered from an incumbent scaffold $(\mathcal{O}^{(0)}, \theta^{(0)})$, the root branch is

$$\mathfrak{b}_{\text{root}} = (\text{id}_0, \emptyset, \mathcal{H}^{(0)}, \mathcal{O}^{(0)}, \theta^{(0)}, E(\theta^{(0)}; \mathcal{O}^{(0)}), d_0, S^{\text{cum}}_{\text{root}}, K^{\text{cum}}_{\text{root}}, \text{frontier}, \emptyset),$$

with

$$d_0 = |\mathcal{H}^{(0)}|, \qquad S^{\text{cum}}_{\text{root}} = \sum_{j=1}^{d_0} s_j^{(0)}, \qquad K^{\text{cum}}_{\text{root}} = \sum_{j=1}^{d_0} \kappa_j^{(0)}.$$

If the beam is started from a fresh scaffold, then $\mathcal{H}^{(0)} = \emptyset$, $d_0 = 0$, and both cumulative sums vanish.

One beam round is best read as four structural steps.

(i) Recompute the branch-local cumulative Phase-3 screening chain.
Each live branch $\mathfrak{b} \in \mathfrak{F}_c$ induces its own raw candidate-position surface. Let

$$\eta_b \in \{\text{core/seed}, \text{residual}\}$$

be the branch-local stage label, and let the branch-local enabled generator family be

$$\mathcal{G}^{(3)}_{\eta_b}(\mathfrak{b}) = \begin{cases} \mathcal{G}^{(3)}_{\text{core/seed}}(\mathfrak{b}), & \eta_b = \text{core/seed}, \\ \mathcal{G}^{(3)}_{\text{residual}}(\mathfrak{b}), & \eta_b = \text{residual}. \end{cases}$$

Let $\mathcal{P}_{\text{residual}}(\mathfrak{b}) \subseteq \mathcal{G}^{(3)}$ denote the residual-only generator family on branch b.[3] Then the controller-stage gate and the branch-local available Phase-3 generator family are

$$\Gamma_{\text{stage},b}(m) = \begin{cases} 1, & \eta_b = \text{residual}, \\ 1, & \eta_b = \text{core/seed and } m \notin \mathcal{P}_{\text{residual}}(\mathfrak{b}), \\ 0, & \eta_b = \text{core/seed and } m \in \mathcal{P}_{\text{residual}}(\mathfrak{b}), \end{cases} \qquad \mathcal{G}^{(3)}_{\text{avail}}(\mathfrak{b}) = \{\, m \in \mathcal{G}^{(3)} : \Gamma_{\text{stage},b}(m) = 1 \,\}.$$

In the branch-local beam surface, the optional transient `seed` stage is absorbed into the label core/seed and resolves immediately before persistent beam branching. A convenient closed stage-label transition rule consistent with the stage-controller surface of §11.6 is[4]

$$\eta_{\text{root}} \in \{\text{core/seed}, \text{residual}\}, \qquad \eta_{b'} = \begin{cases} \text{residual}, & \eta_b = \text{residual}, \\ \text{residual}, & \eta_b = \text{core/seed},\ d_{b'} \geq d_{\min},\ n^{\text{small}}_{d_{b'}} = M,\ \chi^{\text{trough}}_{b'} = 0, \\ \text{core/seed}, & \text{otherwise}, \end{cases}$$

where $\chi^{\text{trough}}_{b'} \in \{0, 1\}$ is the branch-local trough indicator. Thus η_{root} is inherited from the incoming controller state, once a branch reaches residual stage it remains there, and the core/seed $\to$ residual transition occurs only after a branch-local plateau-patience hit without trough detection. Now let

$$n_b = |\mathcal{O}_b|, \qquad p_{\text{app}}(\mathfrak{b}) = n_b, \qquad W_{\text{act}}(\mathfrak{b}) \subseteq \{0, \dots, n_b - 1\}$$

be the current scaffold length, append slot, and active position-probe window on branch b. The ordered probe list is

$$\mathcal{L}_{\text{probe}}(\mathfrak{b}) := (p_{\text{app}}(\mathfrak{b}),\ 0,\ W_{\text{act}}(\mathfrak{b})),$$

where the entries of $W_{\text{act}}(\mathfrak{b})$ are read in their native order. The distinct retained probe positions are[5]

$$\mathcal{P}_{\text{probe}}(\mathfrak{b}) = \text{Head}_{M_{\text{probe}}}\Big(\text{Dedup}_{\text{ord}}(\mathcal{L}_{\text{probe}}(\mathfrak{b}))\Big) \subseteq \{0, \dots, n_b\}.$$

[3] Implementation note: this is a controller-defined subset of the Phase-3 pool rather than a primitive Hamiltonian object. In practice it is decided from the branch's current stage/state and can depend on runtime policy rather than only on algebraic data.

[4] Reader note: η_b, n^{small}_d, $d_{\min}$, M, τ_{drop}, and χ^{trough}_b are best read as controller-state quantities. The manuscript gives a mathematically usable surface for them, but they are still runtime decision variables/signals rather than primitive observables derived directly from the Hamiltonian.

[5] Algorithmic note: $\text{Dedup}_{\text{ord}}$ means stable order-preserving deduplication of the probe list, and $\text{Head}_{M_{\text{probe}}}$ means truncation to the first M_{probe} surviving entries. These are algorithmic selection operators rather than primitive algebraic maps.

For each candidate-position record $r = (m, p)$, let the branch-local symmetry gate be

$$\Gamma_{\mathrm{sym},b}(m,p) = \begin{cases} 0, & \text{the symmetry audit for } (m,p;\mathcal{O}_b) \text{ returns a hard violation,} \\ 1, & \text{otherwise.} \end{cases}$$

Hence the branch-local admissible insertion-position set for generator m is

$$\mathcal{P}_m(\mathfrak{b}) = \{\, p \in \mathcal{P}_{\mathrm{probe}}(\mathfrak{b}) : \Gamma_{\mathrm{sym},b}(m,p) = 1 \,\},$$

and the resulting raw candidate-position surface is

$$\mathcal{R}_b^{\mathrm{raw}} = \{\, r = (m,p) : m \in \mathcal{G}^{(3)}_{\mathrm{avail}}(\mathfrak{b}),\ p \in \mathcal{P}_m(\mathfrak{b}) \,\},$$

so the generator stage gate and the position-level symmetry gate are already absorbed into $\mathcal{R}_b^{\mathrm{raw}}$. In the maximally wide limit,

$$W_{\mathrm{act}}(\mathfrak{b}) = \{0, \dots, n_b - 1\}, \qquad M_{\mathrm{probe}} \geq n_b + 1 \quad \Longrightarrow \quad \mathcal{P}_{\mathrm{probe}}(\mathfrak{b}) = \{0, \dots, n_b\},$$

and the branch can test every insertion position on its current scaffold. The local screening flow is then

$$\begin{aligned} N_{\mathrm{cheap}}(\mathfrak{b}) &= \min\Big\{ N^{\max}_{\mathrm{cheap}}, |\mathcal{R}_b^{\mathrm{raw}}| \Big\}, \\ \mathcal{C}_{\mathrm{cheap}}(\mathfrak{b}) &= \mathrm{Top}_{N_{\mathrm{cheap}}(\mathfrak{b})}\big(\mathcal{R}_b^{\mathrm{raw}}; S_{3,\mathrm{cheap}}\big), \\ N_{\mathrm{short}}(\mathfrak{b}) &= \min\Big\{ |\mathcal{C}_{\mathrm{cheap}}(\mathfrak{b})|, N_{\max}, \lceil f_{\mathrm{short}} |\mathcal{C}_{\mathrm{cheap}}(\mathfrak{b})| \rceil \Big\}, \\ \mathcal{S}_3(\mathfrak{b}) &= \mathrm{Top}_{N_{\mathrm{short}}(\mathfrak{b})}\big(\mathcal{C}_{\mathrm{cheap}}(\mathfrak{b}); S_{3,\mathrm{cheap}}\big). \end{aligned}$$

using the same cumulative chain from §§11.4.1–11.4.2 — first the reused cheap screen, then the shortlist/full rerank, and finally the Phase-3 augmentations — but now evaluated on the current branch state $(\mathcal{O}_b, \theta_b)$ with

$$\Gamma_{\mathrm{stage}}(m) = \Gamma_{\mathrm{stage},b}(m), \qquad \Gamma_{\mathrm{sym}}(r) = \Gamma_{\mathrm{sym},b}(m,p) \quad \text{for } r = (m,p).$$

Also set

$$S_{3,\mathrm{cheap}}(r;\mathfrak{b}) := s_{b,\mathrm{cheap}}(r), \qquad S_{3,\mathrm{base}}(r;\mathfrak{b}) := s_{b,\mathrm{base}}(r),$$

so the branch-local shortlist operators are using the same score names as §§11.4.1–11.4.2. Denote the resulting local selector by

$$s_b(r) = S_{3,\mathrm{aug}}(r;\mathfrak{b}) \quad \text{or} \quad s_b(r) = S_{3,\mathrm{base}}(r;\mathfrak{b}).$$

More explicitly, the branch-local score flow is

$$\begin{aligned} s_{b,\mathrm{cheap}}(r) &= \Gamma_{\mathrm{stage},b}(m)\Gamma_{\mathrm{sym},b}(m,p) \frac{\max\Big\{ \big| 2\Re\langle \psi_b | H | d_r^{(b)} \rangle \big| - z_\alpha \sigma_r(\mathfrak{b}), 0 \Big\}^2}{2\lambda_F \langle d_r^{(b)} | Q_{\psi_b} | d_r^{(b)} \rangle \, (K_{\mathrm{cheap}}(r;\mathfrak{b}) + \varepsilon)}, \\ |\psi_b\rangle &= U(\theta_b; \mathcal{O}_b)|\phi_0\rangle, \qquad Q_{\psi_b} = I - |\psi_b\rangle\langle\psi_b|, \\ |d_r^{(b)}\rangle &= -i\widetilde{A}_r^{(b)}|\psi_b\rangle, \qquad t_r^{(b)} = Q_{\psi_b}|d_r^{(b)}\rangle, \qquad F_{\mathrm{raw}}(r;\mathfrak{b}) = \langle d_r^{(b)} | Q_{\psi_b} | d_r^{(b)} \rangle, \\ t_j^{(b)} &= Q_{\psi_b}\partial_{\theta_j}|\psi_b\rangle, \qquad (Q_r(\mathfrak{b}))_{jk} = \Re\langle t_j^{(b)}, t_k^{(b)}\rangle, \qquad (q_r(\mathfrak{b}))_j = \Re\langle t_j^{(b)}, t_r^{(b)}\rangle, \\ \tilde{h}_r(\mathfrak{b}) &= h_r(\mathfrak{b}) - b_r(\mathfrak{b})^\top M_r(\mathfrak{b})^{-1} b_r(\mathfrak{b}), \\ F_r^{\mathrm{red}}(\mathfrak{b}) &= F_{\mathrm{raw}}(r;\mathfrak{b}) - 2q_r(\mathfrak{b})^\top M_r(\mathfrak{b})^{-1} b_r(\mathfrak{b}) + b_r(\mathfrak{b})^\top M_r(\mathfrak{b})^{-1} Q_r(\mathfrak{b}) M_r(\mathfrak{b})^{-1} b_r(\mathfrak{b}), \\ q_r^{\mathrm{red}}(\mathfrak{b}) &= q_r(\mathfrak{b}) - Q_r(\mathfrak{b}) M_r(\mathfrak{b})^{-1} b_r(\mathfrak{b}), \\ \nu_r(\mathfrak{b}) &= \mathrm{clip}_{[0,1]}\left(1 - \frac{(q_r^{\mathrm{red}}(\mathfrak{b}))^\top (Q_r(\mathfrak{b}) + \varepsilon_{\mathrm{nov}} I)^{-1} q_r^{\mathrm{red}}(\mathfrak{b})}{F_r^{\mathrm{red}}(\mathfrak{b})} \right), \\ \Delta E_{\mathrm{TR}}(r;\mathfrak{b}) &= \max_{|\alpha| \leq \rho/\sqrt{F_r^{\mathrm{red}}(\mathfrak{b})}} \left[g_{\mathrm{lcb}}(r;\mathfrak{b})|\alpha| - \frac{1}{2}\max(\tilde{h}_r(\mathfrak{b}), 0)\alpha^2 \right], \\ s_{b,\mathrm{base}}(r) &= \Gamma_{\mathrm{stage},b}(m)\Gamma_{\mathrm{sym},b}(m,p) \left[\mathrm{clip}_{[0,1]}\left(1 - \frac{(q_r^{\mathrm{red}}(\mathfrak{b}))^\top (Q_r(\mathfrak{b}) + \varepsilon_{\mathrm{nov}} I)^{-1} q_r^{\mathrm{red}}(\mathfrak{b})}{F_r^{\mathrm{red}}(\mathfrak{b})} \right) \right]^{\gamma_N} \\ &\qquad \times \frac{\max_{|\alpha| \leq \rho/\sqrt{F_r^{\mathrm{red}}(\mathfrak{b})}} \left[\max\Big\{ \big| 2\Re\langle \psi_b | H | d_r^{(b)} \rangle \big| - z_\alpha \sigma_r(\mathfrak{b}), 0 \Big\} |\alpha| - \frac{1}{2}\max(\tilde{h}_r(\mathfrak{b}), 0)\alpha^2 \right]}{K_{\mathrm{full}}(r;\mathfrak{b}) + \varepsilon}, \\ s_b(r) &= s_{b,\mathrm{base}}(r) + \beta_{\mathrm{split}}\Sigma(r;\mathfrak{b}) + \beta_{\mathrm{motif}} M(r;\mathfrak{b}) + \beta_{\mathrm{sym}} Y(r;\mathfrak{b}) - \beta_{\mathrm{dup}} D_{\mathrm{dup}}(r;\mathfrak{b}). \end{aligned}$$

So the branch-local screening/rerank chain closes as

$$\mathcal{R}_b^{\text{raw}} \xrightarrow{s_{b,\text{cheap}}} \mathcal{C}_{\text{cheap}}(\mathfrak{b}) \xrightarrow{s_{b,\text{cheap}}} \mathcal{S}_3(\mathfrak{b}) \xrightarrow{s_b} \mathcal{A}_b^{\text{raw}} \xrightarrow{\text{Top}_{K_b}} \mathcal{A}_b.$$

For $r = (m, p) \in \mathcal{S}_3(\mathfrak{b})$, let the runtime-split child family be

$$\mathcal{C}_{\text{split}}(m) = \{m_1, \dots, m_{K_m}\}.$$

For a child subset $S \subseteq \mathcal{C}_{\text{split}}(m)$, define the combined child-set polynomial

$$m_S := \sum_{u \in S} u.$$

For any real-coefficient Pauli polynomial

$$m = \sum_w c_w P_w$$

written in the internal $e/x/y/z$ word alphabet, define the canonical polynomial signature

$$\text{Sig}_{\text{poly}}(m; \tau_{\text{sig}}) := \text{sort}\left\{(w, \text{rnd}_{12}(c_w)) : |c_w| > \tau_{\text{sig}}\right\}, \qquad \text{rnd}_{12}(x) := 10^{-12}\,\text{round}(10^{12}x).$$

Thus $\text{Dedup}_{\text{sig}}$ retains one representative from each common value of $\text{Sig}_{\text{poly}}(\cdot; \tau_{\text{sig}})$ after collecting like terms. Each singleton child is re-audited at the same insertion position p, and the symmetry-safe combined child-set family is

$$\mathcal{A}_{\text{split}}(m, p; \mathfrak{b}) = \text{Dedup}_{\text{sig}}\Big[\{\, S \subseteq \mathcal{C}_{\text{split}}(m) : \Gamma_{\text{sym},b}(m_S, p) = 1,\ m_S \not\equiv m \,\}\Big].$$

Write

$$r_j = (m_j, p), \qquad r_S = (m_S, p) \quad (|S| \geq 2),$$

for the singleton and child-set representatives, where r_S denotes the combined child-set polynomial placed at the same position p. Then the full split-aware promotion universe of the parent record is

$$\mathcal{U}_b(r) = \{r\} \cup \{\, r_j : \Gamma_{\text{sym},b}(m_j, p) = 1 \,\} \cup \{\, r_S : S \in \mathcal{A}_{\text{split}}(m, p; \mathfrak{b}),\ |S| \geq 2 \,\}.$$

Unsafe child atoms and unsafe child sets are excluded from $\mathcal{U}_b(r)$ by the symmetry gate and therefore may remain in provenance only, not in the admissible promotion surface. Now define

$$r_b^\star(r) = \arg\max_{u \in \mathcal{U}_b(r)} s_b(u),$$

and then the split-aware promoted representative is

$$\hat{r}_b(r) = \begin{cases} r_b^\star(r), & \text{if } s_b(r_b^\star(r)) > s_b(r) + \tau_{\text{split}}, \\ r, & \text{otherwise.} \end{cases}$$

The actual raw admission set passed to the beam is therefore

$$\mathcal{A}_b^{\text{raw}} = \{\, \hat{r}_b(r) : r \in \mathcal{S}_3(\mathfrak{b}),\ s_b(\hat{r}_b(r)) > 0 \,\},$$

and the retained candidate-admission set is

$$\mathcal{A}_b = \text{Top}_{K_b}(\mathcal{A}_b^{\text{raw}}; s_b), \qquad K_b \leq B_{\text{child}} - 1.$$

[6]

(ii) Materialize either stop or one new admission.
The proposal family is

$$\mathcal{Q}(b) = \{\text{stop}\} \cup \mathcal{A}_b.$$

[6]Beam-width note: Top_{K_b} is the score-ordered child selector on branch b. The inequality fixes only an admissible cap; the exact runtime choice of K_b remains a controller policy decision unless specified separately.

The symbol stop means "terminate this scaffold as-is," while each $r = (m, p) \in \mathcal{A}_b$ means "insert one new generator into this branch and refit." If

$$\mathcal{O}_b = (m_{b,1}, \dots, m_{b,n_b}), \qquad 0 \le p \le n_b,$$

then the scaffold insertion map is

$$\mathrm{Insert}(\mathcal{O}_b, m, p) = (m_{b,1}, \dots, m_{b,p}, m, m_{b,p+1}, \dots, m_{b,n_b}),$$

and the insertion index transport is

$$I_p(j) = \begin{cases} j, & 1 \le j \le p, \\ j+1, & p < j \le n_b. \end{cases}$$

The zero-lifted parameter vector is therefore

$$\theta_b^{\uparrow(r)} = (\theta_{b,1}, \dots, \theta_{b,p}, 0, \theta_{b,p+1}, \dots, \theta_{b,n_b}).$$

Equivalently,

$$(\theta_b^{\uparrow(r)})_{I_p(j)} = \theta_{b,j}, \qquad (\theta_b^{\uparrow(r)})_{p+1} = 0.$$

For newest-window cap w_{new} and amplitude-carry cap $k_{|\theta|}$, let

$$w_{\mathrm{eff}}^{(p)} = \min\{w_{\mathrm{new}}, n_b + 1\}, \qquad W_{\mathrm{new}}^{(p)} = \{n_b + 2 - w_{\mathrm{eff}}^{(p)}, \dots, n_b + 1\},$$

$$W_{|\theta|}^{(p)} = \mathrm{Top}_{k_{|\theta|}}\Big(\{1, \dots, n_b + 1\} \backslash W_{\mathrm{new}}^{(p)}; \big|(\theta_b^{\uparrow(r)})_j\big|\Big).$$

Hence the inherited refit window on the inserted scaffold is

$$W_r = W(m, p) = W_{\mathrm{new}}^{(p)} \cup W_{|\theta|}^{(p)}.$$

Then the branch-local refit map is

$$\mathrm{Refit}_{W_r}(\theta_b; r) := \arg\min_{\vartheta} \Big\{ E(\vartheta; \mathrm{Insert}(\mathcal{O}_b, m, p)) : \ \vartheta_j = (\theta_b^{\uparrow(r)})_j \ \forall j \notin W_r \Big\}.$$

The transfer map is

$$\mathcal{T}(\mathfrak{b}, \mathrm{stop}) = \mathfrak{b}' \quad \text{with} \quad \mathcal{H}_{b'} = \mathcal{H}_b,\ \mathcal{O}_{b'} = \mathcal{O}_b,\ \theta_{b'} = \theta_b,\ E_{b'} = E_b,\ d_{b'} = d_b,\ S_{b'}^{\mathrm{cum}} = S_b^{\mathrm{cum}},\ K_{b'}^{\mathrm{cum}} = K_b^{\mathrm{cum}},\ \sigma_{b'} = \mathrm{terminal},$$

and for $r = (m, p)$,

$$\mathcal{T}(\mathfrak{b}, r) = \mathfrak{b}' \quad \text{with} \quad \mathcal{O}_{b'} = \mathrm{Insert}(\mathcal{O}_b, m, p), \qquad \theta_{b'} = \mathrm{Refit}_{W_r}(\theta_b; r),$$

$$\mathcal{H}_{b'} = (\mathcal{H}_b, r), \qquad E_{b'} = E(\theta_{b'}; \mathcal{O}_{b'}), \qquad d_{b'} = d_b + 1, \qquad S_{b'}^{\mathrm{cum}} = S_b^{\mathrm{cum}} + s_b(r), \qquad K_{b'}^{\mathrm{cum}} = K_b^{\mathrm{cum}} + K_{\mathrm{full}}(r), \qquad \sigma_{b'} = \begin{cases} \text{termin} \\ \text{frontie} \end{cases}$$

where $\mathcal{A}_{b'}$ is recomputed from step (i) on the child branch itself. So a non-stop child is exactly one more ADAPT admission applied to the parent scaffold, followed by the inherited-window refit already defined above. If $\mathcal{A}_b = \emptyset$, then $\mathcal{Q}(b) = \{\mathrm{stop}\}$ and the branch contributes only a terminal child.

(iii) Classify, deduplicate, and prune the scaffold children.
The frontier and terminal descendants of branch b are

$$\mathfrak{C}_b^{\mathrm{front}} = \{\mathfrak{b}' : \mathfrak{b}' = \mathcal{T}(\mathfrak{b}, r),\ r \in \mathcal{A}_b,\ \sigma_{b'} = \mathrm{frontier}\},$$

$$\mathfrak{C}_b^{\mathrm{term}} = \{\mathfrak{b}' : \mathfrak{b}' = \mathcal{T}(\mathfrak{b}, q),\ q \in \mathcal{Q}(b),\ \sigma_{b'} = \mathrm{terminal}\}.$$

Two branches are treated as duplicates when they represent the same scaffold and essentially the same refit point, for example under the fingerprint

$$\mathrm{rnd}_{10}(x) := 10^{-10}\,\mathrm{round}(10^{10}x), \qquad \mathrm{round}_{10}(\theta_b) := (\mathrm{rnd}_{10}(\theta_{b,1}), \dots, \mathrm{rnd}_{10}(\theta_{b,n_b})),$$

$$\mathrm{fp}(\mathfrak{b}) = (d_b, \mathrm{labels}(\mathcal{O}_b), \mathrm{round}_{10}(\theta_b)).$$

Among near-equivalent branches, keep the one with best lexicographic prune key

$$\kappa_{\mathrm{prune}}(\mathfrak{b}) = (E_b, -S_b^{\mathrm{cum}}, K_b^{\mathrm{cum}}, |\mathcal{O}_b|, \mathrm{labels}(\mathcal{O}_b), \mathrm{round}_{10}(\theta_b), \mathrm{id}_b).$$

This means that, within the symbolic scaffold beam, lower current energy is primary; stronger cumulative admitted selector value is secondary; lower accumulated burden and then smaller/simpler equivalent scaffolds break the remaining ties.

The beam operators are therefore

$$\mathrm{Dedup}(\mathcal{X}) = \{\text{best branch per fingerprint under } \kappa_{\mathrm{prune}}\}, \qquad \mathrm{Prune}(\mathcal{X}; B) = \text{lowest-}B \text{ branches in } \mathrm{Dedup}(\mathcal{X}) \text{ by } \kappa_{\mathrm{prune}}.$$

Hence the live and terminal pools update by

$$\mathfrak{F}_{c+1} = \mathrm{Prune}\left(\bigcup_{b\in\mathfrak{F}_c} \mathfrak{C}_b^{\mathrm{front}}; B_{\mathrm{live}}\right), \qquad \mathfrak{T}_{c+1} = \mathrm{Prune}\left(\mathfrak{T}_c \cup \bigcup_{b\in\mathfrak{F}_c} \mathfrak{C}_b^{\mathrm{term}}; B_{\mathrm{term}}\right).$$

(iv) Choose the final scaffold branch.
After C scaffold-beam rounds, the surviving candidate set is

$$\mathfrak{W}_{\mathrm{final}} = \mathfrak{F}_C \cup \mathfrak{T}_C,$$

and the effective beam selector is

$$\mathfrak{b}_* = \arg\min_{\mathfrak{b}\in\mathfrak{W}_{\mathrm{final}}} \kappa_{\mathrm{prune}}(\mathfrak{b}).$$

Equivalently,

$$\mathfrak{b}_* = \arg\min_{\mathfrak{b}\in\mathfrak{F}_C\cup\mathfrak{T}_C} (E_b, -S_b^{\mathrm{cum}}, K_b^{\mathrm{cum}}, |\mathcal{O}_b|, \mathrm{labels}(\mathcal{O}_b), \mathrm{round}_{10}(\theta_b), \mathrm{id}_b).$$

A compact scaffold-beam algorithm block is therefore

$$\begin{aligned}
&\text{A: } \mathfrak{F}_0 = \{\mathfrak{b}_{\mathrm{root}}\}, \qquad \mathfrak{T}_0 = \emptyset,\\
&\text{B: } \mathcal{R}_b^{\mathrm{raw}} \to \mathcal{C}_{\mathrm{cheap}}(\mathfrak{b}) \to \mathcal{S}_3(\mathfrak{b}) \to \mathcal{A}_b \qquad (\mathfrak{b}\in\mathfrak{F}_c),\\
&\text{C: } \mathcal{Q}(b) = \{\mathrm{stop}\} \cup \mathcal{A}_b, \qquad \mathfrak{C}_b = \{\mathcal{T}(\mathfrak{b}, q) : q \in \mathcal{Q}(b)\},\\
&\text{D: } \mathfrak{C}_b^{\mathrm{front}} = \{\mathfrak{b}' \in \mathfrak{C}_b : \sigma_{b'} = \mathrm{frontier}\}, \qquad \mathfrak{C}_b^{\mathrm{term}} = \{\mathfrak{b}' \in \mathfrak{C}_b : \sigma_{b'} = \mathrm{terminal}\},\\
&\text{E: } \mathfrak{F}_{c+1} = \mathrm{Prune}\left(\bigcup_{b\in\mathfrak{F}_c} \mathfrak{C}_b^{\mathrm{front}}; B_{\mathrm{live}}\right), \qquad \mathfrak{T}_{c+1} = \mathrm{Prune}\left(\mathfrak{T}_c \cup \bigcup_{b\in\mathfrak{F}_c} \mathfrak{C}_b^{\mathrm{term}}; B_{\mathrm{term}}\right),\\
&\text{F: } \mathfrak{W}_{\mathrm{final}} = \mathfrak{F}_C \cup \mathfrak{T}_C, \qquad \mathfrak{b}_* = \arg\min_{\mathfrak{b}\in\mathfrak{W}_{\mathrm{final}}} \kappa_{\mathrm{prune}}(\mathfrak{b}).
\end{aligned}$$

In words: each round keeps several scaffold alternatives alive, recomputes the local cumulative Phase-3 screening chain on each surviving scaffold, branches by admitting one additional generator or stopping, deduplicates nearly equivalent descendants, prunes back to the beam budgets, and finally returns the best surviving scaffold under the lexicographic selector key.

The separate time-dynamics / projected-dynamics beam surface, with checkpoint advances, probe rollouts, and integrated residual objectives, is developed later in §17.

11.5 Active HH pool surface and selected scaffold

The active HH adaptive surface is carried by the nested pool family

$$\Omega_{\mathrm{HH}}^{(3)} \subseteq \Omega_{\mathrm{HH}}^{(2)} \subseteq \Omega_{\mathrm{HH}}^{(1)}, \qquad \mathcal{G}_{\mathrm{adapt}}^{(k)} = \{\tau_m\}_{m\in\Omega_{\mathrm{HH}}^{(k)}}.$$

The adaptive output is the selected scaffold

$$\mathcal{O}_* = (\tau_{m_1}, \dots, \tau_{m_d}), \qquad \tau_{m_j} \in \mathcal{G}_{\mathrm{adapt}}^{(3)},$$

together with its fitted amplitude vector and resulting state,

$$(\mathcal{O}_*, \theta_*^{\text{adapt}}, |\psi_*\rangle), \qquad |\psi_*\rangle = U(\theta_*^{\text{adapt}}; \mathcal{O}_*)|\phi_0\rangle.$$

Thus the active HH scaffold manifold selected by ADAPT may be written as

$$\mathcal{M}_{\text{scaf}}(\mathcal{O}_*) = \{\, U(\vartheta; \mathcal{O}_*)|\phi_0\rangle : \vartheta \in \mathbb{R}^{|\mathcal{O}_*|} \,\}.$$

The obsolete historical warm-start → refine → ADAPT → replay chain is no longer part of the mainline symbolic flow and is recorded only in Appendix A.2.

11.6 Stage controller

Let the absolute error and its depth-to-depth improvement be

$$\begin{aligned} \Delta_d^{\text{abs}} &= |E_d - E_{\text{exact}}|, \\ \rho_d &= \Delta_{d-1}^{\text{abs}} - \Delta_d^{\text{abs}} = |E_{d-1} - E_{\text{exact}}| - |E_d - E_{\text{exact}}|. \end{aligned}$$

A compact stage-controller surface is then

$$\begin{aligned} n_d^{\text{small}} &= \sum_{\ell=\max\{1,d-M+1\}}^{d} \mathbf{1}(\rho_\ell \le \tau_{\text{drop}}), \\ \text{continue} &\iff d < d_{\min} \text{ or } n_d^{\text{small}} < M, \\ \text{handoff/stop} &\iff d \ge d_{\min} \text{ and } n_d^{\text{small}} = M. \end{aligned}$$

Gradient floors remain secondary diagnostics rather than the primary stop signal.

12. SPSA and Optimizer Semantics

12.1 SPSA schedules

The standard SPSA schedules are

$$c_k = \frac{c}{(k+1)^\gamma}, \qquad a_k = \frac{a}{(A+k+1)^\alpha}.$$

12.2 Two-point stochastic gradient

At iteration k, with Rademacher direction Δ_k, evaluate

$$y_+ = f(x_k + c_k\Delta_k), \qquad y_- = f(x_k - c_k\Delta_k),$$

and form the gradient estimate

$$\hat{g}_k = \frac{y_+ - y_-}{2c_k}\,\Delta_k.$$

12.3 Update and projection

The update is

$$x_{k+1} = x_k - a_k\hat{g}_k.$$

If projection or clipping is imposed, it is applied to both the perturbed points and the updated iterate.

12.4 Repeat aggregation

If the same point is sampled multiple times, the repeated evaluations may be aggregated by

$$\text{mean} \qquad \text{or} \qquad \text{median}\,.$$

12.5 Return policy

Two standard return policies are:

- return an averaged late-trajectory iterate,
- return the best sampled point observed during the run.

12.6 Surface note

Stochastic inner optimizers are especially natural for large, noisy, or nondifferentiable effective surfaces, while deterministic optimizers are often effective on smaller and smoother fixed-structure manifolds.

13. Drive, Exact Propagation, and Propagator Semantics

13.1 Static drive labels and time-dependent coefficients

Let $\mathcal{L}_{\text{drive}}$ denote the fixed set of density operators appearing in the drive. Then the drive always has the form

$$\hat{H}_{\text{drive}}(t) = \sum_{\lambda \in \mathcal{L}_{\text{drive}}} c_\lambda(t) P_\lambda,$$

with fixed labels P_λ and time-dependent coefficients $c_\lambda(t)$.

13.2 Reference coefficient map

For a site-density drive,

$$\Delta c[Z_{p(i,\uparrow)}](t) = \Delta c[Z_{p(i,\downarrow)}](t) = -\frac{1}{2} v_i(t),$$

and the identity shift is

$$\Delta c[I](t) = \sum_i v_i(t)$$

if one chooses to retain the scalar offset explicitly.

13.3 Propagator surfaces

A common propagator menu is:

- second-order Suzuki,
- piecewise exact propagation,
- fourth-order CFQM,
- sixth-order CFQM.

For CFQM methods, the key mathematical point is that the stage times are fixed scheme nodes c_j, so a macro-step from t_n to $t_{n+1} = t_n + \Delta t$ samples the Hamiltonian at

$$t_n + c_j \Delta t,$$

not at a left, midpoint, or right rule chosen independently.

13.4 Reference propagator versus reported trajectory propagator

Write the reported propagator as $U_{\text{traj}}(t)$ and the high-accuracy reference propagator as $U_{\text{ref}}(t)$. These need not be the same approximation.

13.4.1 Static reference branch

In the static case, one may take

$$U_{\text{ref}}(t) = e^{-it\hat{H}}.$$

13.4.2 Drive-enabled reference branch

For time-dependent $\hat{H}(t)$, a refined piecewise-constant reference is

$$U_{\mathrm{ref}}(t_{n+1}, t_n) \approx e^{-i\Delta t \hat{H}(t_n^*)},$$

with t_n^* sampled on a refined grid and the full reference obtained as an ordered product over the refined slices.

13.5 CFQM macro-step mathematics

A generic commutator-free quasi-Magnus macro-step takes the form

$$U_{n+1,n}^{\mathrm{CFQM}} = \prod_{r=1}^{s} \exp\left[-ia_r \Delta t\, \hat{H}(t_n + c_r \Delta t)\right],$$

with method-specific coefficients a_r and nodes c_r. The formal order is achieved when the stage exponentials are themselves treated at the intended accuracy.

13.6 Filtered exact manifold and subspace fidelity

Let Π_{sector} denote the projector onto the target symmetry sector. Then the filtered exact energy is

$$E_{\mathrm{exact,filtered}} = \min_{\psi \in \Pi_{\mathrm{sector}}\mathcal{H}} \langle \psi | \hat{H} | \psi \rangle,$$

and a sector-aware fidelity may be defined by

$$F_{\mathrm{sector}}(t) = \frac{|\langle \psi_{\mathrm{exact}}(t) | \Pi_{\mathrm{sector}} | \psi(t) \rangle|^2}{\langle \psi(t) | \Pi_{\mathrm{sector}} | \psi(t) \rangle}.$$

13.7 Branch-resolved observable contracts

If several trajectory branches are carried simultaneously, each observable should be indexed by branch label b:

$$\mathcal{O}_b(t), \qquad b \in \{\mathrm{var}, \mathrm{traj}, \mathrm{ref}, \mathrm{noisy}, \mathrm{ideal}\}.$$

Typical observables are energy, density, doublon density, and fidelity.

13.8 State import and handoff contract

A portable state bundle can be written abstractly as

$$\mathcal{B} = (\Lambda, \theta, a, E, \mathcal{C}),$$

where Λ is the physical manifest, θ are variational parameters when available, a is an amplitude map for the working state, E stores energy summaries, and $\mathcal{C}$ is continuation metadata.

13.9 Highest-tier continuation surfaces

At the highest continuation tier, $\mathcal{C}$ may include split-event summaries, motif data, symmetry diagnostics, replay policy data, and limited branch histories. These are naturally viewed as auxiliary mathematical metadata rather than as part of the operator algebra itself.

14. Continuation and Handoff Contract

14.1 Handoff state bundle

A handoff bundle may contain:

- the parameter manifest Λ,

- the current energy summary,
- the normalized statevector amplitudes,
- an exact comparison target,
- optional continuation metadata.

One convenient symbolic amplitude map is

$$\{b_{N_q-1} \cdots b_0 \mapsto (\mathfrak{R}a_b, \mathfrak{I}a_b)\}.$$

14.2 Continuation block

The continuation payload can be treated abstractly as

$$\mathcal{C} = (m, \mathcal{S}, \mathcal{M}_{\text{opt}}, \Gamma, \Sigma, \mathcal{L}, \mathcal{U}, \Xi, \mathcal{R}, \mathcal{P}),$$

where:

- m is the continuation mode,
- $\mathcal{S}$ is inherited manifold-structure data,
- $\mathcal{M}_{\text{opt}}$ is auxiliary optimizer state,
- Γ is selected-generator metadata,
- Σ is split-event data,
- $\mathcal{L}$ is a motif library,
- $\mathcal{U}$ is motif usage,
- Ξ is symmetry information,
- $\mathcal{R}$ is rescue or recovery history,
- $\mathcal{P}$ is optional historical replay-policy metadata when such provenance is still being carried.

14.3 General handoff map

Let $\mathcal{H}_{A\to B}$ be a handoff map from source manifold $\mathcal{M}_A$ to target manifold $\mathcal{M}_B$:

$$\mathcal{H}_{A\to B} : (|\psi_A\rangle, \theta_A, \mathcal{C}_A) \mapsto (|\psi_B^{(0)}\rangle, \theta_B^{(0)}, \mathcal{C}_B).$$

The map is intentionally abstract here: it records state, coordinates, and continuation payload transfer between manifolds without committing the main body to any obsolete replay-specific burn-in policy.

14.4 Symmetry and tier-three payload note

Symmetry information belongs in the handoff if later stages will use it for validation, postselection, or projector-renormalized estimation. Mathematically, the carried object is a projector or a list of commuting symmetry generators.

14.5 Historical warm/refine chain note

The obsolete warm-start → refine → ADAPT → replay path is kept only in Appendix A.2 and is not part of the active main-body symbolic contract.

15. Cross-Checks and Exact-Benchmark Contracts

15.1 Trial matrix by problem family

For the Hubbard model, a natural benchmark trial set is

$$\mathcal{T}_{\text{Hub}} = \{\text{layerwise, excitation-based, adaptive(exc), adaptive(full-H)}\}.$$

For the HH model, the canonical sector-preserving core set is

$$\mathcal{T}_{\text{HH}} = \{\text{HH-layerwise, HH-physical-termwise, adaptive(full-H)}\}.$$

A seed-surface extension can enlarge $\mathcal{T}_{\text{HH}}$ by adding polaronic refinements built on the same sector-preserving fixed-family surface.

15.2 Auto-scaled parameter resolution

Let

$$S_{\mathrm{trot}}(L, n_{\mathrm{ph,max}}), \quad R_{\mathrm{restart}}(L, n_{\mathrm{ph,max}}), \quad I_{\mathrm{max}}(L, n_{\mathrm{ph,max}})$$

be monotone nondecreasing control maps for Trotter steps, restart count, and optimizer effort. The key contract is monotonicity with problem size, not a single universal constant setting.

15.3 Exact target and shared reference-state construction

Within a benchmark matrix, all trial families should be compared against the same exact target and the same conserved-sector reference construction. Thus every trial is judged against the same $E_{\mathrm{exact,sector}}$ and the same physical Hamiltonian instance.

15.4 Per-trial energy and trajectory semantics

Each trial should at minimum record:

- the variational ground-state energy,
- the exact comparison target,
- trajectory observables on a shared time grid when dynamics are studied,
- fidelity or overlap relative to a common reference branch.

15.5 Artifact contracts

Every report artifact should begin with a concise parameter manifest listing:

- model family,
- ansatz family,
- drive enabled or disabled,
- t, U, ω_0, g, and $n_{\mathrm{ph,max}}$,
- any propagation parameters needed to reproduce the result.

15.6 HH seed-surface preset and resource proxies

A seed-surface comparison is naturally evaluated not only by energy but also by simple resource proxies such as

$$C_{2\mathrm{q}}, \qquad D_{\mathrm{proxy}}, \qquad C_{1\mathrm{q}}.$$

One can then compare improvement per marginal resource,

$$\frac{\Delta E}{C_{2\mathrm{q}}}, \qquad \frac{\Delta E}{D_{\mathrm{proxy}}}.$$

16. Noise Validation, Symmetry-Mitigation, and Parity Contracts

16.1 Filtered versus full exact targets

The filtered target is

$$E_{\mathrm{exact,filtered}} = \min_{\psi \in \mathcal{H}_{\mathrm{sector}}} \langle \psi | \hat{H} | \psi \rangle,$$

while the unrestricted target is

$$E_{\mathrm{exact,full}} = \min \mathrm{spec}(\hat{H}).$$

The two coincide only if the physical and computational sectors match exactly.

16.2 Noisy-minus-ideal observable deltas

For any observable $\mathcal{O}(t)$, define

$$\Delta\mathcal{O}(t) = \mathcal{O}_{\mathrm{noisy}}(t) - \mathcal{O}_{\mathrm{ideal}}(t).$$

In particular,

$$\Delta E(t) = E_{\mathrm{noisy}}(t) - E_{\mathrm{ideal}}(t), \qquad \Delta D(t) = D_{\mathrm{noisy}}(t) - D_{\mathrm{ideal}}(t).$$

16.3 Anchor parity gate

If a new idealized path is compared against a fixed anchor trajectory, a strict parity gate takes the form

$$\max_{t\in\mathcal{T}} |\mathcal{O}_{\text{new}}(t) - \mathcal{O}_{\text{anchor}}(t)| \le \varepsilon_{\text{parity}}.$$

This is an anchor-based equality test, not merely a qualitative agreement statement.

16.4 Same-anchor paired comparison semantics

Two noisy methods should be compared against the same ideal anchor, on the same time grid, with the same initial state, so that differences can be attributed to the noise or mitigation model rather than to different starting conditions.

16.5 Symmetry-mitigation mode surface

Three increasingly strong symmetry surfaces are:

1. verify-only sector diagnostics,
2. bitstring postselection,
3. projector-renormalized estimators.

If Π is the projector onto the target symmetry sector, the renormalized estimator is

$$\langle O\rangle_{\Pi} = \frac{\langle\psi|\Pi O\Pi|\psi\rangle}{\langle\psi|\Pi|\psi\rangle}.$$

16.6 Parameter manifest and provenance digest

Even in a symbolic setting, it is useful to view each artifact as carrying a manifest $\mathfrak{M}$ and a provenance digest $h(\mathfrak{M})$. The purpose is not algebraic; it is to guarantee that the reported mathematics can be traced back to a unique physical parameter set.

17. Projective McLachlan Real-Time Geometry and Piecewise Beam-Adaptive Control

Below is the cleanest mathematical story for what the projected real-time implementation is doing. It is most naturally written as a **piecewise-smooth control problem on a family of variational manifolds**, with $\hbar = 1$, normalized pure states, and real parameters. The two geometric facts underneath everything are:

1. the McLachlan principle projects the exact Schrödinger velocity onto a **real-linear** tangent space using the real inner product $g(u, v) = \Re\langle u, v\rangle$, and
2. physical pure states are rays, so the natural state space is **projective Hilbert space**, which means global-phase directions should be removed from the local scoring geometry.

17.1 What problem is being solved?

Fix a Hilbert space $\mathcal{H} \cong \mathbb{C}^d$, a Hamiltonian $H(t)$, and a current ansatz structure $\mathcal{S}$. That structure defines a parameterized family of states

$$|\psi(\theta; \mathcal{S})\rangle, \qquad \theta \in \mathbb{R}^m.$$

At time t, the exact Schrödinger equation asks for the state velocity

$$\frac{d}{dt}|\psi_{\text{ex}}(t)\rangle = -iH(t)|\psi_{\text{ex}}(t)\rangle.$$

The local projected-dynamics question is therefore:

> **At the current state, how closely can the current ansatz manifold reproduce the exact instantaneous quantum velocity?**

This is the local question answered by real-time McLachlan dynamics. It is also the quantity that drives adaptive manifold growth: enlarge the ansatz when the instantaneous projected defect becomes too large.

17.2 Why projective Hilbert space is the right setting

A normalized ket $|\psi\rangle$ and $e^{i\phi}|\psi\rangle$ represent the same physical state. So the physical state space is projective Hilbert space $\mathbb{P}(\mathcal{H})$ rather than the unit sphere itself. At a normalized state $|\psi\rangle$, define the horizontal projector

$$Q_\psi := I - |\psi\rangle\langle\psi|.$$

For each parameter θ_j, the raw tangent vector is

$$\tau_j := \partial_{\theta_j}|\psi(\theta;\mathcal{S})\rangle,$$

and the horizontal tangent is

$$\bar{\tau}_j := Q_\psi \tau_j.$$

Collect the horizontal tangents as columns:

$$\bar{T} := [\bar{\tau}_1, \dots, \bar{\tau}_m] \in \mathbb{C}^{d\times m}.$$

The exact Schrödinger drift is

$$b := -iH\psi,$$

but the physically relevant local velocity is its horizontal part

$$\bar{b} := Q_\psi b = -i(H - E_\psi)\psi, \qquad E_\psi := \langle\psi|H|\psi\rangle.$$

Its squared norm is

$$\|\bar{b}\|^2 = \langle\psi|(H - E_\psi)^2|\psi\rangle = \mathrm{Var}_\psi(H).$$

So the squared norm of the exact projective Schrödinger velocity is the energy variance. This is why $\mathrm{Var}_\psi(H)$ is the natural normalization scale for projected McLachlan defects.

17.3 The current manifold and its allowed velocities

Because the parameters are real, the attainable instantaneous velocities form the **real-linear** tangent cone

$$T_\psi\mathcal{M}_\mathcal{S} = \left\{\bar{T}\dot{\theta} : \dot{\theta} \in \mathbb{R}^m\right\}.$$

This is not a complex-linear subspace in general. So the correct local geometry is built from the real inner product

$$g(u,v) := \Re\langle u, v\rangle.$$

The variational velocity associated with parameter rates $\dot{\theta}$ is

$$v(\dot{\theta}) = \bar{T}\dot{\theta}.$$

17.4 The fixed-structure McLachlan step

The fixed-structure local problem is

$$\dot{\theta}_0 = \arg\min_{\dot{\theta}\in\mathbb{R}^m} \|\bar{T}\dot{\theta} - \bar{b}\|^2.$$

Its quadratic form, projective metric, force vector, and solved stationarity system close to

$$\begin{aligned}
\|\bar{T}\dot{\theta} - \bar{b}\|^2 &= \|\bar{b}\|^2 - 2\Re\langle\bar{T}\dot{\theta}, \bar{b}\rangle + \dot{\theta}^\top\Re(\bar{T}^\dagger\bar{T})\dot{\theta},\\
(\bar{G})_{ij} &= \Re\langle\bar{\tau}_i, \bar{\tau}_j\rangle = \Re\langle\partial_{\theta_i}\psi|Q_\psi|\partial_{\theta_j}\psi\rangle,\\
\bar{f}_i &= \Re\langle\bar{\tau}_i, \bar{b}\rangle = \Re\langle Q_\psi\partial_{\theta_i}\psi, -i(H - E_\psi)|\psi\rangle,\\
\mathcal{L}_0(\dot{\theta}) &= \|\bar{b}\|^2 - 2\bar{f}^\top\dot{\theta} + \dot{\theta}^\top\bar{G}\dot{\theta},\\
\bar{G}\dot{\theta}_0 &= \bar{f},\\
\dot{\theta}_0 &= \bar{G}^+\bar{f} \qquad \text{if } \bar{G} \text{ is singular or rank-deficient},\\
0 &= \Re\langle\bar{\tau}_i, \bar{T}\dot{\theta}_0 - \bar{b}\rangle \qquad \forall i.
\end{aligned}$$

17.5 What regularization means

A stabilized runtime step solves

$$\dot{\theta}_\lambda = \arg\min_{\dot{\theta}\in\mathbb{R}^m} \left(\|\bar{T}\dot{\theta} - \bar{b}\|^2 + \dot{\theta}^\top \Lambda \dot{\theta} \right), \qquad \Lambda \succeq 0.$$

With

$$K := \bar{G} + \Lambda,$$

the regularized geometry closes to

$$\begin{aligned}
K\dot{\theta}_\lambda &= \bar{f}, \\
\epsilon^2_{\text{proj}} &:= \min_{\dot{\theta}} \|\bar{T}\dot{\theta} - \bar{b}\|^2 = \|\bar{b}\|^2 - \bar{f}^\top \bar{G}^+ \bar{f}, \\
\epsilon^2_{\text{step}} &:= \|\bar{T}\dot{\theta}_\lambda - \bar{b}\|^2, \\
\mathcal{L}^\star_\lambda &:= \min_{\dot{\theta}} \left(\|\bar{T}\dot{\theta} - \bar{b}\|^2 + \dot{\theta}^\top \Lambda \dot{\theta} \right) = \|\bar{b}\|^2 - \bar{f}^\top K^{-1} \bar{f} \qquad (K \text{ invertible}), \\
\mathcal{L}^\star_\lambda &= \epsilon^2_{\text{step}} + \dot{\theta}_\lambda^\top \Lambda \dot{\theta}_\lambda.
\end{aligned}$$

So ϵ^2_{proj} measures intrinsic model inadequacy, ϵ^2_{step} measures the actual mismatch of the damped runtime step, and $\mathcal{L}^\star_\lambda$ is the stabilized solver objective.

17.6 Why the residual is the right local error quantity

Choose a local gauge in which the representatives are horizontal at the current time. Then the exact and variational projective velocities are

$$\bar{b} \qquad \text{and} \qquad \bar{T}\dot{\theta}.$$

Define the horizontal residual

$$\bar{r} := \bar{T}\dot{\theta} - \bar{b}.$$

Then, for a short step h,

$$\begin{aligned}
|\psi_{\text{ex}}(t+h)\rangle &= |\psi\rangle + h\,\bar{b} + O(h^2), \\
|\psi_{\text{var}}(t+h)\rangle &= |\psi\rangle + h\,\bar{T}\dot{\theta} + O(h^2),
\end{aligned}$$

so

$$|\psi_{\text{var}}(t+h)\rangle - |\psi_{\text{ex}}(t+h)\rangle = h\,\bar{r} + O(h^2).$$

So the correct local score is an **instantaneous derivative-mismatch score**. Static energy scores or novelty scores can help in secondary ranking, but they are not the primary real-time control quantity.

17.7 The geometric projector behind the formulas

Because the tangent space is real-linear, the correct projector is

$$P^{\mathbb{R}}_{\bar{T}} v = \bar{T}\,\bar{G}^+\,\mathfrak{R}(\bar{T}^\dagger v).$$

The unregularized optimal residual is therefore

$$\bar{r}_0 = \bar{T}\dot{\theta}_0 - \bar{b} = \left(P^{\mathbb{R}}_{\bar{T}} - I \right) \bar{b}.$$

So the ansatz follows the component of the exact projective Schrödinger vector field that lies in the current real tangent plane, and the residual is the orthogonal complement.

17.8 What a candidate generator really is

Suppose the current structure is an ordered product ansatz

$$|\psi(\theta;\mathcal{S})\rangle = e^{-i\theta_m A_m} \cdots e^{-i\theta_1 A_1}|\phi_0\rangle.$$

Now insert a candidate block A_c at position p, with new parameter η, initialized at zero:

$$|\psi'(\theta,\eta)\rangle = e^{-i\theta_m A_m} \cdots e^{-i\theta_p A_p} e^{-i\eta A_c} e^{-i\theta_{p-1} A_{p-1}} \cdots e^{-i\theta_1 A_1}|\phi_0\rangle.$$

At $\eta = 0$,

$$|\psi'(\theta,0)\rangle = |\psi(\theta)\rangle.$$

So the state is continuous, but the tangent space changes immediately. The new tangent column is

$$u_c := \partial_\eta |\psi'(\theta,\eta)\rangle\big|_{\eta=0}, \qquad \bar{u}_c := Q_\psi \nu_c.$$

So a candidate is not merely "a promising operator." It is a **new tangent direction that becomes available at the current state without moving the state**. For a block candidate carrying q new real parameters, collect the new columns into

$$\bar{U} \in \mathbb{C}^{d\times q}.$$

17.9 The exact local gain formula

Now augment the local problem:

$$\min_{\dot\theta,\eta} \Big(\|\bar{T}\dot\theta + \bar{U}\eta - \bar{b}\|^2 + \dot\theta^\top \Lambda \dot\theta + \eta^\top \Lambda_c \eta \Big), \qquad \Lambda_c \succeq 0.$$

With the mixed overlaps

$$\begin{aligned} B_{ia} &= \Re\langle \bar{\tau}_i, \bar{u}_a\rangle, & B &= \Re(\bar{T}^\dagger \bar{U}) \in \mathbb{R}^{m\times q}, \\ C_{ab} &= \Re\langle \bar{u}_a, \bar{u}_b\rangle, & C &= \Re(\bar{U}^\dagger \bar{U}) \in \mathbb{R}^{q\times q}, \\ q_a &= \Re\langle \bar{u}_a, \bar{b}\rangle, & q &= \Re(\bar{U}^\dagger \bar{b}) \in \mathbb{R}^{q}, \end{aligned}$$

the augmented normal equations, Schur complement, and gain reduce to

$$\begin{aligned} \begin{bmatrix} K & B \\ B^\top & C+\Lambda_c \end{bmatrix} \begin{bmatrix} \dot\theta \\ \eta \end{bmatrix} &= \begin{bmatrix} \bar{f} \\ q \end{bmatrix}, \\ \dot\theta(\eta) &= K^{-1}(\bar{f} - B\eta), \\ \mathcal{L}^\star_{\mathrm{aug},\lambda}(\eta) &= \mathcal{L}^\star_\lambda - 2\eta^\top w + \eta^\top S \eta, \\ S &= C + \Lambda_c - B^\top K^{-1} B, \\ w &= q - B^\top K^{-1}\bar{f}, \\ \eta_\star &= S^+ w, \\ \Delta_\lambda &:= \mathcal{L}^\star_\lambda - \mathcal{L}^\star_{\mathrm{aug},\lambda} = w^\top S^+ w \\ &= (q - B^\top K^{-1}\bar{f})^\top (C + \Lambda_c - B^\top K^{-1} B)^+ (q - B^\top K^{-1}\bar{f}). \end{aligned}$$

For a single real candidate direction ($q = 1$), this reduces to

$$\Delta_\lambda = \frac{w^2}{S}.$$

17.10 What S and w mean

The Schur-complement pair and resulting score may be read in one chain:

$$\begin{aligned} S &= C + \Lambda_c - B^\top K^{-1} B, \\ w &= q - B^\top K^{-1}\bar{f}, \\ \Delta_\lambda &= w^\top S^+ w \\ &= (q - B^\top K^{-1}\bar{f})^\top (C + \Lambda_c - B^\top K^{-1} B)^+ (q - B^\top K^{-1}\bar{f}). \end{aligned}$$

So S is the metric of the new block after removing the part already explainable by the old tangent space, w is the residualized overlap with the exact projective drift, and Δ_λ is residualized force squared divided by residualized norm.

17.11 The unregularized geometric meaning

Set $\Lambda = \Lambda_c = 0$. For a single real candidate direction $\bar{u}$, define

$$\bar{u}_\perp := (I - P_{\bar{T}}^{\mathbb{R}})\bar{u}, \qquad \bar{r}_0 := (I - P_{\bar{T}}^{\mathbb{R}})\bar{b}.$$

Then the exact one-direction gain closes to

$$\begin{aligned}\Delta_0 &= \frac{\left(\Re\langle \bar{u}_\perp, \bar{r}_0\rangle\right)^2}{\|\bar{u}_\perp\|^2} \\ &= \frac{\left(\Re\langle (I - P_{\bar{T}}^{\mathbb{R}})\bar{u}, (I - P_{\bar{T}}^{\mathbb{R}})\bar{b}\rangle\right)^2}{\|(I - P_{\bar{T}}^{\mathbb{R}})\bar{u}\|^2}.\end{aligned}$$

The numerator uses $\Re\langle \bar{u}_\perp, \bar{r}_0\rangle$ rather than $|\langle \bar{u}_\perp, \bar{r}_0\rangle|$ because one is adding **one real parameter**, not an arbitrary complex tangent line.

17.12 When should the ansatz adapt?

The intrinsic normalized miss closes to

$$\begin{aligned}\rho_{\text{miss}} &:= \frac{\epsilon_{\text{proj}}^2}{\|\bar{b}\|^2 + \varepsilon} = \frac{\|\bar{b}\|^2 - \bar{f}^\top \bar{G}^+ \bar{f}}{\|\bar{b}\|^2 + \varepsilon} \\ &= \frac{\mathrm{Var}_\psi(H) - \bar{f}^\top \bar{G}^+ \bar{f}}{\mathrm{Var}_\psi(H) + \varepsilon} = \frac{\langle \psi | (H - E_\psi)^2 | \psi\rangle - \bar{f}^\top \bar{G}^+ \bar{f}}{\langle \psi | (H - E_\psi)^2 | \psi\rangle + \varepsilon}.\end{aligned}$$

Interpretation:

- $\rho_{\text{miss}} \approx 0$: the current manifold already captures the projective velocity well,
- ρ_{miss} large: the manifold is missing important directions.

A clean rule is therefore

$$\text{adapt if } \rho_{\text{miss}} > \tau_{\text{miss}}.$$

One may also adapt for numerical unreliability or after a maximum interval without any structural update.

17.13 Which candidates should be admissible?

A candidate may have nonzero gain and still be numerically poor because it is nearly redundant. So before ranking by Δ_λ, one should inspect the residualized geometry:

- compute singular values of S, or of the corresponding whitened residualized block,
- reject candidates whose retained support is too ill-conditioned.

An invariant way to do this is to whiten the old tangent metric. If

$$\bar{G} \approx V \Sigma^2 V^\top$$

on its numerical support, define whitened coordinates

$$z := \Sigma V^\top \dot{\theta}.$$

Then penalizing $\|z\|^2$ is a penalty on **physical tangent speed** rather than coordinate speed. This is the least chart-dependent way to stabilize an overparameterized manifold.

17.14 Two different residuals should be tracked

The projective residual is

$$\bar{r} := \bar{T}\dot{\theta}_\lambda - \bar{b}.$$

This is the correct gauge-invariant quantity for local candidate scoring and local manifold-growth decisions.

The raw Hilbert-space residual is

$$r_{\text{raw}} := T\dot{\theta}_\lambda - (-iH\psi) = T\dot{\theta}_\lambda + iH\psi.$$

These are related by

$$\bar{r} = Q_\psi r_{\text{raw}}.$$

So:

- use $\bar{r}$ for **local structure growth**,
- use r_{raw} when a rigorous Hilbert-space accumulated-error bound is desired.

17.15 Why integrated residual is the right branch-pruning quantity

Let a branch be propagated on a fixed structure over a segment $[t_a, t_b]$. Let $|\psi_{\text{ex}}\rangle$ be the exact state and $|\psi_{\text{var}}\rangle$ the variational state with the same initial condition at t_a, and define

$$e(t) := |\psi_{\text{var}}(t)\rangle - |\psi_{\text{ex}}(t)\rangle.$$

Then the error evolution, Duhamel representation, norm bound, and segment cost close to

$$\begin{aligned}
\dot{\psi}_{\text{ex}} &= -iH\psi_{\text{ex}}, \qquad\qquad \dot{\psi}_{\text{var}} = T\dot{\theta}_\lambda, \quad r_{\text{raw}} = T\dot{\theta}_\lambda + iH\psi,\\
\dot{e} &= -iHe + r_{\text{raw}},\\
e(t) &= \int_{t_a}^{t} U(t,s)\, r_{\text{raw}}(s)\, ds,\\
\|e(t)\| &\le \int_{t_a}^{t} \|r_{\text{raw}}(s)\|\, ds \le \sqrt{t-t_a}\left(\int_{t_a}^{t} \|r_{\text{raw}}(s)\|^2\, ds\right)^{1/2},\\
J_{\text{seg}}^{\text{raw}} &:= \int_{t_a}^{t_b} \|r_{\text{raw}}(t)\|^2\, dt = \int_{t_a}^{t_b} \|T\dot{\theta}_\lambda(t) + iH(t)\psi(t)\|^2\, dt.
\end{aligned}$$

So $J_{\text{seg}}^{\text{raw}}$ is a natural upper-bound surrogate for accumulated state-vector error. If one wants a fully gauge-invariant pruning metric instead, replace $\|r_{\text{raw}}(t)\|^2$ by $\|\bar{r}(t)\|^2 = \|Q_\psi r_{\text{raw}}(t)\|^2$ and interpret the result as a ray/projective error surrogate.

17.16 The branch objective

A branch is a sequence of structures $\mathcal{S}_0, \mathcal{S}_1, \dots, \mathcal{S}_J$ used over consecutive checkpoint segments, and the cumulative objective closes as

$$\begin{aligned}
J_{\text{branch}} &= \sum_{j=0}^{J-1} J_{\text{seg},j} + \beta\, C_{\text{hw}} + \gamma\, N_{\text{adapt}} + \mu_E \sum_{j=0}^{J-1} \int_{t_j}^{t_{j+1}} \left| \frac{d}{dt}\langle H(t)\rangle_j - \langle \partial_t H(t)\rangle_j \right|^2 dt\\
&= \sum_{j=0}^{J-1} \int_{t_j}^{t_{j+1}} \|r_{\text{raw}}^{(j)}(t)\|^2\, dt + \beta\, C_{\text{hw}} + \gamma\, N_{\text{adapt}} + \mu_E \sum_{j=0}^{J-1} \int_{t_j}^{t_{j+1}} \left| \frac{d}{dt}\langle H(t)\rangle_j - \langle \partial_t H(t)\rangle_j \right|^2 dt\\
&= \sum_{j=0}^{J-1} \int_{t_j}^{t_{j+1}} \left\| T^{(j)}(t)\dot{\theta}_\lambda^{(j)}(t) + iH(t)\psi^{(j)}(t) \right\|^2 dt + \beta\, C_{\text{hw}} + \gamma\, N_{\text{adapt}} + \mu_E \sum_{j=0}^{J-1} \int_{t_j}^{t_{j+1}} \left| \frac{d}{dt}\langle H(t)\rangle_j - \langle \partial_t H(t)\rangle_j \right|^2 dt.
\end{aligned}$$

If one wants a fully gauge-invariant branch surrogate instead, replace $\|r_{\text{raw}}^{(j)}(t)\|^2$ by $\|\bar{r}^{(j)}(t)\|^2 = \|Q_{\psi^{(j)}} r_{\text{raw}}^{(j)}(t)\|^2$.

17.17 The full process, in one coherent sequence

At each time t, with current structure $\mathcal{S}$, the full loop can be written compactly as

$$\begin{aligned}
&\text{A: } |\psi\rangle = |\psi(\theta;\mathcal{S})\rangle, \qquad Q_\psi = I - |\psi\rangle\langle\psi|, \qquad \bar{T} = Q_\psi T, \qquad \bar{b} = Q_\psi(-iH\psi) = -i(H - E_\psi)\psi,\\
&\text{B: } \bar{G} = \mathfrak{R}(\bar{T}^\dagger \bar{T}), \qquad \bar{f} = \mathfrak{R}(\bar{T}^\dagger \bar{b}), \qquad K = \bar{G} + \Lambda, \qquad \dot{\theta}_\lambda = K^+ \bar{f},\\
&\quad \epsilon^2_{\text{proj}} = \|\bar{b}\|^2 - \bar{f}^\top \bar{G}^+ \bar{f}, \qquad \epsilon^2_{\text{step}} = \|\bar{T}\dot{\theta}_\lambda - \bar{b}\|^2, \qquad \bar{r} = \bar{T}\dot{\theta}_\lambda - \bar{b}, \qquad r_{\text{raw}} = T\dot{\theta}_\lambda + iH\psi,\\
&\text{C: } \rho_{\text{miss}} = \frac{\epsilon^2_{\text{proj}}}{\|\bar{b}\|^2 + \varepsilon} = \frac{\epsilon^2_{\text{proj}}}{\mathrm{Var}_\psi(H) + \varepsilon}, \qquad \text{adapt iff } \rho_{\text{miss}} > \tau_{\text{miss}},\\
&\text{D: } B_c = \mathfrak{R}(\bar{T}^\dagger \bar{U}_c), \qquad C_c = \mathfrak{R}(\bar{U}_c^\dagger \bar{U}_c), \qquad q_c = \mathfrak{R}(\bar{U}_c^\dagger \bar{b}),\\
&\quad S_c = C_c + \Lambda_c - B_c^\top K^+ B_c, \qquad w_c = q_c - B_c^\top K^+ \bar{f}, \qquad \Delta_{\lambda,c} = w_c^\top S_c^+ w_c.
\end{aligned}$$

For each shortlisted admissible candidate c, one then creates a zero-initialized child, propagates it over the next probe segment, and prunes on the accumulated branch objective:

$$\begin{aligned}
&\text{E: } \mathcal{S} \mapsto \mathcal{S}_c^+, \qquad |\psi(\theta, 0; \mathcal{S}_c^+)\rangle = |\psi(\theta;\mathcal{S})\rangle,\\
&\text{F: } J^{\text{raw}}_{\text{seg},c} = \int_{t_a}^{t_b} \|r_{\text{raw},c}(t)\|^2\, dt = \int_{t_a}^{t_b} \left\|T_c(t)\dot{\theta}_{\lambda,c}(t) + iH(t)\psi_c(t)\right\|^2 dt,\\
&\text{G: } J^{\text{new}}_{\text{branch},c} = J^{\text{old}}_{\text{branch}} + J^{\text{raw}}_{\text{seg},c} + \beta\, C_{\text{hw},c} + \gamma\, N_{\text{adapt},c}, \qquad \mathfrak{B}_{\text{next}} = \mathrm{Prune}\Big(\{(\mathcal{S}_c^+, J^{\text{new}}_{\text{branch},c})\}_c\Big).
\end{aligned}$$

That is the whole piecewise-manifold control loop.

17.18 One concise interpretation

The method is doing this:

The exact quantum dynamics asks for a projective velocity $\bar{b}$.
The current ansatz only provides a real tangent plane.
McLachlan chooses the closest available tangent velocity.
If the miss is too large, the algorithm enlarges the tangent plane by adding zero-initialized candidate directions.
The local gain formula tells us which candidate most reduces the current miss.
Short probe rollouts then decide which structural choices remain best after actual propagation.

17.19 Explicit symbolic–mathematical differences between the clean story and the current implementation

The clean story above is the right mathematical idealization. The current implementation differs from that idealization in a few explicit ways:

1. **Sign convention.** The clean story uses

$$\bar{b} = -iQ_\psi H\psi, \qquad \bar{r} = \bar{T}\dot{\theta} - \bar{b}.$$

   The implementation instead uses

$$r = \bar{T}\dot{\theta} + iQ_\psi H\psi, \qquad f_i = \mathfrak{I}\langle\bar{\tau}_i|H|\psi\rangle, \qquad \mathfrak{R}\langle\bar{\tau}_i, -iH\psi\rangle = \mathfrak{I}\langle\bar{\tau}_i, H\psi\rangle.$$

2. **Regularization surface.** Rather than a general positive-semidefinite penalty Λ or Λ_c, the implementation uses a scalar $\lambda \geq 0$ on either chart coordinates or whitened metric coordinates:

$$\begin{aligned}
&K_{\text{chart}} = \bar{G} + \lambda I,\\
&\quad \bar{G} \approx V\Sigma^2 V^\top, \qquad z = \Sigma V^\top \dot{\theta}, \qquad (I + \lambda I)z = \Sigma^{-1} V^\top \bar{f}, \qquad \dot{\theta} = V\Sigma^{-1} z.
\end{aligned}$$

3. **Propagation solve versus policy solve.** The clean story presents one stabilized local solve, whereas the implementation may separate the propagated step from the policy/telemetry step:

$$(\dot{\theta}_{\text{prop}}, \epsilon^{2,\text{prop}}_{\text{step}}) \neq (\dot{\theta}_{\text{policy}}, \epsilon^{2,\text{policy}}_{\text{step}}) \quad \text{in general,}$$

   even when both are derived from the same local geometry.

4. **Variance normalization and guards.** The clean story writes

$$\rho_{\text{miss}} = \frac{\epsilon^2_{\text{proj}}}{\text{Var}_\psi(H) + \varepsilon}.$$

The implemented ratio surface is closer to

$$\rho_{\text{miss}} = \begin{cases} \epsilon^2_{\text{proj}}/(\text{Var}_\psi(H) + \varepsilon), & \text{Var}_\psi(H) \geq \nu_{\min}, \\ \text{suppressed}, & \text{Var}_\psi(H) < \nu_{\min}, \end{cases}$$

with an auxiliary guard flag recording the suppressed regime.

5. **Active-parameter windows.** The clean story is written on the full tangent space, but the implementation may restrict to an active suffix or oracle-supplied index set:

$$T \mapsto T_{W_{\text{act}}}, \qquad \dot{\theta} \mapsto (\dot{\theta}_{W_{\text{act}}}, 0), \qquad \bar{G} \mapsto \bar{G}_{W_{\text{act}} W_{\text{act}}},$$

so inactive coordinates are frozen.

6. **Candidate gain evaluation.** The clean story scores candidates by the Schur-complement gain

$$\Delta_\lambda = w^\top S^+ w.$$

The implementation instead zero-initializes one append candidate, rebuilds the augmented local geometry, and scores by direct defect drops

$$\Delta_0 = \epsilon^2_{\text{proj,current}} - \epsilon^2_{\text{proj,aug}}, \qquad \Delta_\lambda = \epsilon^2_{\text{step,current}} - \epsilon^2_{\text{step,aug}}.$$

7. **Position-aware current branch growth.** The clean story allows arbitrary insertion positions and multi-parameter blocks. The helper layer now supports position-aware insertion and position-centered post-insert refit windows,

$$\mathcal{T}(\mathfrak{b}, m, p) = \mathfrak{b}', \qquad \mathcal{O}_{b'} = \mathcal{O}_b \oplus_p m, \qquad \theta_{b'} = \theta_b \oplus_p 0,$$

and the active probe set is built from the append slot, the left boundary, and the active reoptimization window. Hence, when the active window is made maximally large and the probe-position cap is also made large enough, the implementation can evaluate the full insertion set $p \in \{0, \dots, |\theta|\}$ rather than append only. The live surface still remains zero-initialized **single-parameter** growth, but not append-only growth.

8. **Checkpoint-trigger logic.** The clean story says "adapt when ρ_{miss} is too large." The implemented trigger surface is richer:

$$\mathbf{1}_{\text{checkpoint}} = \mathbf{1}_{\text{cadence}} \vee \mathbf{1}(\epsilon^2_{\text{proj}} > \tau_{\text{proj}}) \vee \mathbf{1}(\epsilon^2_{\text{step}} > \tau_{\text{step}}) \vee \mathbf{1}(\rho_{\text{miss}} > \tau_{\text{miss}} \text{ when defined}),$$

together with a model-versus-damping failure classification.

9. **Branch objective surface.** The clean story uses a scalar objective such as

$$J_{\text{scalar}} = \sum J_{\text{seg}} + \beta C_{\text{hw}} + \gamma N_{\text{adapt}}.$$

The implementation instead prunes by the lexicographic key

$$\kappa_{\text{prune}} = (J^{\text{rt}}, J^{\text{res}}, J^{\text{model}}, J^{\text{damp}}, J^{\text{cons}}, |\mathcal{O}|, k, \text{labels}(\mathcal{O}), \text{round}_{10}(\theta), \text{id}),$$

after deduplicating by time index, selected-operator labels, and rounded parameter values.

10. **Projective versus raw residual accumulation.** The clean story distinguishes a projective residual $\bar{r}$ from a raw Hilbert-space residual r_{raw}. The implemented rollout telemetry is closer to

$$(\Delta J^\epsilon, \Delta J^{\text{model}}, \Delta J^{\text{damp}}) = \left(\int \epsilon^2_{\text{step}}, \int \epsilon^2_{\text{proj}}, \int \max(\epsilon^2_{\text{step}} - \epsilon^2_{\text{proj}}, 0) \right),$$

rather than a separately stored raw Hilbert-space residual bound.

11. **Geometry source.** The clean story is written as if the tangent vectors and $H\psi$ are assembled directly every time. The implementation may instead start from externally supplied local data:

$$(\bar{G}, \bar{f}, \mathrm{Var}_\psi(H)) = \mathcal{O}_{\mathrm{geom}}(\psi, H, \mathcal{S}),$$

after which the host solves the McLachlan system on that returned geometry.

So the mathematical backbone is the same, but the implemented restricted surface closes schematically to

projective policy geometry + scalar chart/whitened damping + append-only zero-init growth
+ checkpointed short-horizon rollout + lexicographic prune key + optional oracle-supplied local ge

18. Final Primitive-Closed Summary

The symbolic substitution chain is linear and closed:

1. choose the fermion ordering $p(i, \sigma)$,
2. write the Jordan-Wigner ladder primitives $\hat{c}_p^\dagger$ and $\hat{c}_p$,
3. reduce number operators to $(I - Z_p)/2$,
4. substitute them into $\hat{H}_t$, $\hat{H}_U$, and $\hat{H}_v$,
5. write $\hat{b}_i$, $\hat{b}_i^\dagger$, $\hat{n}_{b,i}$, $\hat{x}_i$, and $\hat{P}_i$,
6. substitute them into $\hat{H}_{\mathrm{ph}}$ and $\hat{H}_g$,
7. reduce the drive term to explicit identity-plus-Z coefficients,
8. propagate those operators into statevector primitives,
9. build fixed and adaptive variational manifolds from the same operators,
10. define projective McLachlan tangent geometry on those manifolds,
11. define branch growth, probe rollout, and beam pruning on top of the local defect geometry,
12. define continuation and handoff on top of those manifolds, with historical replay paths kept in the appendix,
13. define benchmark and noise-validation contracts relative to the same exact targets.

This is the point of the symbolic duplicate: the same mathematical skeleton remains, but implementation labels are stripped away so the document can serve as a clean theory-facing reference.

19. Data

This final chapter records empirical evidence for the selector and pruning claims developed in the main body. The goal is not to replace the symbolic formulas above, but to show that the live Phase-3 HH selector surfaces described in §§11 and 17 materially change the observed outcomes on matched runs.

19.1 Matched novelty ablation

The freshest clean ablation available is a matched four-run HH study with

$$L = 2, \qquad t = 1, \qquad U = 4, \qquad \omega_0 = 1, \qquad g = 0.5, \qquad n_{\mathrm{ph,max}} = 1,$$

using binary bosons, blocked ordering, open boundaries, the same seed, the same compiled backend path, the same windowed reoptimization policy, the same live pruning machinery, and the same rescue/symmetry/lifetime settings. The only changes are:

1. operator pool: `pareto_lean_l2` versus `full_meta`,
2. novelty exponent: $\gamma_N = 1$ versus $\gamma_N = 0$.

Writing the final filtered-energy error as

$$|\Delta E| = \left|E_{\mathrm{final}} - E_{\mathrm{exact,filtered}}\right|,$$

the matched runs give:

Pool	γ_N	E_{final}	$\lvert\Delta E\rvert$	Depth	Parameters	Stop reason	Prune kept
`pareto_lean_l2`	1.0	0.158724082365	0.371078234644 \times 10^{-5}	14	25	`drop_plateau`	4 / 5
`pareto_lean_l2`	0.0	0.486960214364	4.628649231024 \times 10^{-1}	14	23	`drop_plateau`	4 / 5
`full_meta`	1.0	0.158724082365	0.371078234644 \times 10^{-5}	13	28	`drop_plateau`	5 / 5
`full_meta`	0.0	0.486990909513	3.282552300539 \times 10^{-1}	13	22	`drop_plateau`	5 / 5

If

$$R_{\text{nov}}(\mathcal{G}) = \frac{|\Delta E|_{\gamma_N=0,\mathcal{G}}}{|\Delta E|_{\gamma_N=1,\mathcal{G}}},$$

then the two matched pool ratios are

$$R_{\text{nov}}(\texttt{pareto_lean_l2}) \approx 5.84376 \times 10^3, \qquad R_{\text{nov}}(\texttt{full_meta}) \approx 5.84431 \times 10^3.$$

So, on this matched HH benchmark, turning novelty weighting off worsens the final filtered-energy error by roughly a factor of 5.8×10^3 in both a lean pool and a heavy pool.

19.2 Interpretation of the novelty ablation

Several points survive this comparison cleanly.

1. **Novelty-on recovers the low-error line.** In both pools, $\gamma_N = 1$ reaches the same final error scale,

$$|\Delta E| \approx 5.62 \times 10^{-5}.$$

2. **Novelty-off collapses to a much worse terminal scaffold.** In both pools, $\gamma_N = 0$ ends near

$$E_{\text{final}} \approx 0.487, \qquad |\Delta E| \approx 3.28 \times 10^{-1},$$

   far above the filtered exact target near 0.158668.

3. **This is not merely a depth effect.** The on/off pairs stop at the same logical depth within each pool, so the dominant difference is the operator-ranking trajectory rather than a simple "more steps" explanation.

4. **This is not merely a pruning-on versus pruning-off effect.** Pruning stays active in all four runs. What changes is the upstream ranking rule. In particular, novelty telemetry is still assembled when $\gamma_N = 0$; what is ablated is the multiplicative use of novelty inside the selector score, not the underlying geometric information itself.

These runs therefore support the claim that the reduced-tangent-space novelty factor is doing real work inside the ADAPT ranking rule rather than serving as passive telemetry.

19.3 Pool-family redundancy

The same data story also sharpens the pool-reduction claim. For the studied HH regime

$$L = 2, \qquad n_{\text{ph,max}} = 1,$$

the heavy `full_meta` pool has size 46, while the lean `pareto_lean_l2` pool has size 11. Hence the pool-reduction fraction is

$$\eta_{\text{pool}} = 1 - \frac{11}{46} = \frac{35}{46} \approx 0.7609.$$

Equivalently, the lean pool removes about 76% of the heavy-pool candidates while still retaining the same practical final energy scale,

$$E_{\text{final}} \approx 0.15872408, \qquad |\Delta E| \approx 5.62 \times 10^{-5},$$

on the current-code lean rerun.

The generator classes discussed in this L=2 comparison may be represented symbolically by

$$\begin{aligned}
A^{\text{sing}}_{ia,\sigma} &= i\left(\hat{c}^\dagger_{a\sigma}\hat{c}_{i\sigma} - \hat{c}^\dagger_{i\sigma}\hat{c}_{a\sigma}\right), \\
A^{\text{dbl}}_{ijab} &= i\left(\hat{c}^\dagger_a\hat{c}^\dagger_b\hat{c}_j\hat{c}_i - \text{h.c.}\right), \\
G^{(\text{cloud})}_i &= \tilde{n}_i \sum_{r\in\mathcal{N}(i)} \alpha_{ir} P_r, \\
G^{(\text{hd})}_{ij} &= T^{(+)}_{ij}(P_i - P_j), \\
G^{(\text{dd})}_i &= D_i P_i, \\
G^{(\text{od})}_{ij} &= J^{(-)}_{ij}(x_i - x_j), \\
G^{(2)}_{ij} &= T^{(+)}_{ij}(x_i - x_j)^2, \\
x_i &= \hat{b}_i + \hat{b}^\dagger_i, \qquad P_i = i(\hat{b}^\dagger_i - \hat{b}_i).
\end{aligned}$$

On this $L = 2$ benchmark, the retained/useful classes were A^{sing}, the P-type polaronic classes $G^{(\text{cloud})}_i$, $G^{(\text{hd})}_{ij}$, and $G^{(\text{dd})}_i$, together with the quadrature seeds. By contrast, A^{dbl}, HVA, and the x-type / higher-order channels $G^{(\text{od})}_{ij}$ and $G^{(2)}_{ij}$ were not needed to preserve the achieved error scale.

Empirically, the following heavy-pool families are absent from the lean pool yet are not needed to retain that achieved accuracy scale on this benchmark:

- lifted UCCSD doubles,
- HH unit terms,
- HVA layers,
- `paop_cloud_x`,
- `paop_disp`,
- `paop_dbl`,
- `paop_dbl_x`,
- `paop_curdrag`,
- `paop_hop2`.

This should be read as a scoped data claim, not as a universal proof: for the present HH $L = 2$, $n_{\text{ph,max}} = 1$ target problem, the heavy pool carries substantial operator-family redundancy relative to the observed energy objective.

19.4 Relation to live pruning

The redundancy story above is consistent with the live pruning machinery, but it should not be conflated with it. The implemented scaffold-pruning pass is active and ranks removal candidates primarily by small amplitude, then by weaker prior proxy benefit. Schematically, the ordering is lexicographic in

$$(|\theta_j|,\ \text{prior proxy benefit}_j).$$

A candidate removal is then accepted only after a local refit if the post-removal regression remains below the allowed prune threshold; otherwise it is rejected, and later symmetry or energy failure can trigger a rollback. So pruning is a live remove-refit-verify mechanism, not a static heuristic deletion list.

It is also important that estimated remaining depth is **not** part of the prune accept/reject rule itself. Remaining-depth information enters the lifetime-burden term of the selector score, whereas pruning uses the small-$|\theta|$ plus local-regression logic above.

19.5 Data provenance note

The novelty-ablation numbers in this chapter come from the fresh direct `adapt_pipeline` artifacts `pi_ablate_pareto_lean_l2_n` `pi_ablate_pareto_lean_l2_novelty_off.json`, `pi_ablate_full_meta_novelty_on.json`, and `pi_ablate_full_meta_novel` all dated `2026-03-24`. The heavy-versus-lean pool-family comparison is anchored by the `2026-03-21` comparison bundle summarized in `pareto_lean_l2_vs_heavy_L2_ecut1_comparison.md` together with the corresponding lean rerun artifact. The data are therefore matched and current enough for PI-facing evidence.

The honesty caveat is the same one stated in the reporting notes: these matched ablations share the same physics, seed, and selector family, but they are not claimed to be byte-for-byte reproductions of every earlier March 21/22 runtime-resolved default. That caveat does not weaken the on/off comparisons above, because the resolved settings were shared inside each matched pair.

Appendix A. Spec-only or not-yet-formalized surfaces kept out of the main body

A.1 Broader continuation-theory items

Several topics belong naturally in a later symbolic pass rather than in the present core manuscript:

- multi-source motif transfer and motif tiling,
- richer split-event formalism,
- more detailed rescue dynamics,
- exact handoff-policy closure beyond the present abstract maps,
- measured-geometry and backend-specific closure beyond the exact symbolic statevector surface.

A.2 Obsolete historical warm-start → refine → ADAPT → replay path

The historical staged path can be written symbolically as

$$\begin{aligned}
\mathcal{M}_{\text{warm}} &= \{\, U_{\text{warm}}(\theta_{\text{w}})|\phi_0\rangle : \theta_{\text{w}} \in \mathbb{R}^{m_{\text{w}}} \,\}, \\
\mathcal{M}_{\text{refine}} &= \{\, U_{\text{refine}}(\theta_{\text{r}}) U_{\text{warm}}(\theta_{\text{w}}^*)|\phi_0\rangle : \theta_{\text{r}} \in \mathbb{R}^{m_{\text{r}}} \,\}, \\
\mathcal{M}_{\text{replay}}(\mathcal{O}_*) &= \{\, U_{\text{replay}}(\varphi; \mathcal{O}_*)|\phi_0\rangle : \varphi \in \mathbb{R}^{m_{\text{rep}}} \,\}.
\end{aligned}$$

The corresponding historical handoff chain is

$$\begin{aligned}
(\theta_{\text{w}}^*, |\psi_{\text{warm}}\rangle) \in \mathcal{M}_{\text{warm}} &\mapsto (\theta_{\text{r}}^*, |\psi_{\text{refine}}\rangle) \in \mathcal{M}_{\text{refine}} \\
&\mapsto (\mathcal{O}_*, \theta_*^{\text{adapt}}, |\psi_*\rangle) \\
&\mapsto (\varphi^{(0)}, |\psi_{\text{replay}}^{(0)}\rangle) = \mathcal{H}_{\text{replay}}(|\psi_*\rangle, \theta_*^{\text{adapt}}, \mathcal{O}_*, \mathcal{C}_*) \in \mathcal{M}_{\text{replay}}(\mathcal{O}_*).
\end{aligned}$$

A typical replay-style historical policy is:

1. preserve inherited scaffold parameters,
2. initialize residual parameters at zero,
3. optionally freeze inherited coordinates for a burn-in stage,
4. then unfreeze and refit in a controlled window.

This path is kept for archival provenance only and is not part of the active main-body symbolic contract.

A.3 Drive-amplitude comparison path

A drive-amplitude comparison path can be expressed symbolically by comparing several amplitudes $A_0, A_1, \ldots$ at fixed Hamiltonian parameters and examining

$$\Delta E_A(t), \qquad \Delta D_A(t), \qquad F_A(t)$$

across the amplitude family. The formal structure is clear even if the exact report layout is deferred.

A.4 Appendix rule

The rule of this symbolic manuscript is therefore:

1. main body = closed mathematical definitions and comparison contracts,
2. appendix = promising but not yet fully formalized extensions.

References

1. Grimsley, Economou, Barnes, and Mayhall, An adaptive variational algorithm for exact molecular simulations on a quantum computer, Nature Communications 10, 3007 (2019), DOI: 10.1038/s41467-019-10988-2.
2. Provost and Vallée, Riemannian structure on manifolds of quantum states, Communications in Mathematical Physics 76, 289-301 (1980), DOI: 10.1007/BF02193559.
3. Stokes, Izaac, Killoran, and Carleo, Quantum Natural Gradient, Quantum 4, 269 (2020), DOI: 10.22331/q-2020-05-25-269.
4. Nocedal and Wright, Trust-Region Methods, in Numerical Optimization, Springer, DOI: 10.1007/0-387-22742-3_4.
5. Ramôa, Santos, Mayhall, Barnes, and Economou, Reducing measurement costs by recycling the Hessian in adaptive variational quantum algorithms, Quantum Science and Technology 10, 015031 (2025), DOI: 10.1088/2058-9565/ad904e.
6. Ramôa, Anastasiou, Santos, Mayhall, Barnes, and Economou, Reducing the resources required by ADAPT-VQE using coupled exchange operators and improved subroutines, npj Quantum Information (2025), DOI: 10.1038/s41534-025-01039-4.
7. Verteletskyi, Yen, and Izmaylov, Measurement optimization in the variational quantum eigensolver using a minimum clique cover, The Journal of Chemical Physics 152, 124114 (2020), DOI: 10.1063/1.5141458.
8. Yen, Verteletskyi, and Izmaylov, Measuring All Compatible Operators in One Series of Single-Qubit Measurements Using Unitary Transformations, Journal of Chemical Theory and Computation (2020), DOI: 10.1021/acs.jctc.0c00008.
9. Ikhtiarudin, Sunnardianto, Fathurrahman, Agusta, and Dipojono, Shot-Efficient ADAPT-VQE via Reused Pauli Measurements and Variance-Based Shot Allocation, arXiv:2507.16879 (2025).
10. Stadelmann, Übelher, Ramôa, Sambasivam, Barnes, and Economou, Strategies for Overcoming Gradient Troughs in the ADAPT-VQE Algorithm, arXiv:2512.25004 (2025).