

MusicFormats maintainance guide

<https://github.com/jacques-menu/musicformats>

v0.9.65 – August 23, 2022

Jacques Menu

This document presents the internal working of MusicFormats. It is part of the MusicFormats documentation, to be found at <https://github.com/jacques-menu/musicformats/tree/dev/documentation>.

```
1 void msrSegment::browseData (basevisitor* v)
2 {
3     // ... ..
4
5     for (
6         list<S_msrMeasure>::const_iterator i = fSegmentElementsList.begin ();
7         i != fSegmentElementsList.end ();
8         ++i
9     ) {
10        // browse the element
11        msrBrowser<msrMeasure> browser (v);
12        browser.browse (*(i));
13    } // for
14
15    // ... ..
16 }
```

```
1 void msr2msrTranslator::visitStart (S_msrClef& elt)
2 {
3     #ifdef TRACING_IS_ENABLED
4         if (gGlobalMsrOahGroup->getTraceMsrvVisitors ()) {
5             gLogStream <<
6                 "--> Start visiting msrClef" <<
7                 ", line " << elt->getInputLineNumber () <<
8                 endl;
9         }
10    #endif
11
12    fCurrentVoiceClone->
13        appendClefToVoice (elt);
14 }
```

List of Figures

1.1	The MusicFormats architecture	18
16.1	The OAH classes hierarchy	123
19.1	The solo rests problem.	168
19.2	Humdrum-Scot keys	179
19.3	The MSR classes hierarchy.	181
19.4	Three segments in a voice	193
30.1	Zoltán Kodály's Mikrokosmos III Wandering	233
30.2	The LilyPondIssue34 score.	234
70.1	Braille for HelloWorld.xml with interpretation	382
70.2	Un Petit Air, par Jean Abou-Samra	385

Listings

13.1	<code>libmusicxml/samples/countnotes.cpp</code> <code>Main</code> <code>countnotes.cpp</code> <code>Files</code> <code>libmusicxml/samples!</code> <code>countnotes.cpp</code> 62	
13.2	<code>Visiting <scaling/>Main</code> <code><scaling />MusicXML</code> <code>scaling </></code>	63
13.3	<code>msrDoubleTremolo::browseData</code> <code>(basevisitor* v)</code>	64

Contents

I	Overview of MusicFormats	15
1	Introduction	16
1.1	Acknowledgements	16
1.2	Prerequisites	16
1.3	Chronology	17
1.4	The GitHub repository	17
2	Documentation.	19
2.1	L ^A T _E X macros	21
2.2	About this document	23
2.3	The MusicFormats architecture	23
2.4	User guide	23
2.5	API guide	23
2.6	Maintainance guide	23
3	Building MusicFormats	24
3.1	Cloning the repository.	24
3.2	One-shot partial <code>make</code> runs	24
3.3	<code>cmake</code> configuration	25
3.4	Library <code>Makefile</code>	25
3.5	CLI amplies <code>Makefile</code>	25
3.6	Building MusicFormats in practise	25
4	Code base structure	27
4.1	The <code>libmusicxml</code> folder	27
4.1.1	Embedding <code>libmusicxml</code> in MusicFormats	28
4.1.2	Upgrading the supported MusicXML version	28
4.2	The <code>doc</code> folder	30
4.3	The <code>schemas</code> folder	31
4.4	The <code>src</code> folder	31
4.5	The <code>validation</code> folder	35
5	Components	36
5.1	Components terminology	36
5.2	Formats	38
5.3	Representations	38
5.4	Passes	39
5.5	Generators	40
5.6	Converters	41
5.7	Running a service	41
6	Command line samples	45
7	Warning and errors (WAE)	46
8	The trace facility.	47
8.1	Activating the trace	47
8.2	Trace categories	48
8.3	Using traces in practise	48
8.4	Debugging traces handling.	48

9	Multi-lingual support	49
10	Textual input and output	50
10.1	Indented output streams	50
10.2	Creating indented output streams	51
10.3	Indenting the output	52
10.4	Printing descriptions	53
11	Binary data output	56
12	CPU measurements	57
II	The two-phase visitors pattern	59
13	The two-phase visitors pattern	60
13.1	Basic mechanism	60
13.2	Browser template classes	61
13.3	A first example: counting notes in MusicXML data	62
13.4	A more complex example	62
13.5	Data browsing order	64
13.6	Selectively inhibiting data browsing	64
13.7	Adapting visitors to data browsing order with booleans	67
13.8	Adapting visitors to data browsing order with stacks	69
13.9	Avoiding the visiting pattern by cascading	70
III	Programming style and conventions	71
14	Programming style and conventions	72
14.1	Files naming conventions	72
14.2	Adding C++ files	74
14.3	Renaming C++ files	75
14.4	Source code layout	75
14.5	Defensive programming	76
14.6	Sanity checks	77
14.7	JMI comments	77
14.8	Exported symbols	78
14.9	Smart pointers	78
14.10	Files contents layout	79
14.11	#define DEBUG* code sections	80
14.12	Identifiers naming conventions	81
14.13	Exceptions and warnings/errors reporting	82
14.14	Exporting symbols for Windows DLLs	84
14.15	Dynamic type checking	85
14.16	Input line numbers	85
14.17	Static declarations	86
14.18	Avoiding MusicFormats multiple initializations	86
14.19	Enumeration types	87
14.20	yes/no enumerations types	89
14.21	Boolean values anyway	89
14.22	On/off values	90
14.23	Iterating over numeration types	91
14.24	Rational numbers	93
14.25	Default values	93
14.26	create* methods	94
14.27	get*(), set*() and fetch*() methods	95
14.28	initialize*() and finalize*() methods	96
14.29	*asString() and *fromString() functions	97
14.30	translate*() methods and convert*() functions	98
14.31	context arguments	99
14.32	Sorting and compare*() methods	100

IV	MusicFormats components	102
15	MusicFormats components (MFC)	103
15.1	Versions numbers	103
15.2	Versions descriptions	104
15.3	Versions histories	104
15.4	Components descriptions	105
15.5	Multi-components	106
15.6	Versions history creation	108
15.6.1	Representations and passes components creation	108
15.6.2	Generators and converters components creation	109
15.6.3	MusicFormats library component creation	110
15.6.4	Version and history options handling	113
15.7	Accessing versions in regular handlers	114
15.8	Getting current version numbers	114
15.8.1	Current version numbers in options	115
15.8.2	Current version numbers in formats	117
15.8.3	Current version numbers in passes	118
V	Options and help	120
16	Options and help (OAH)	121
16.1	OAH basics	121
16.2	Features	122
16.3	OAH classes inheritance	122
16.4	Atoms expecting a value	124
16.4.1	The <code>oahAtomStoringAValue</code> class	124
16.4.2	The <code>oahBooleanAtom</code> special case	125
16.4.3	Checking whether an option has been selected	126
16.4.4	The <code>oahAtomStoringAValue</code> subclasses	127
16.5	Pure help atoms	128
16.5.1	Pure help atoms without a value	128
16.5.2	Pure help atoms expecting a value	128
16.6	Options implicitly storing a value	129
16.7	Options and help handling	130
16.8	Basic OAH types	131
16.9	Prefixes handling	131
16.10	<code>argc/argv</code> versus <code>oahOptionsVector</code>	131
16.11	Applying options	132
16.12	A OAH atoms collection	133
16.13	An option and help example	133
16.14	Options and help introspection	134
16.15	Insider versus regular handlers	135
16.16	Deciphering the options and arguments	136
16.16.1	Options and arguments multi-pass analysis	136
16.16.2	Pure help runs	138
16.16.3	Applying options	138
16.16.4	Early handling of some options	140
16.17	Implementing the <code>-find</code> option	142
16.18	Checking options consistency	144
16.19	Adding new options	144
16.19.1	Representations' vs. passes' options	145
16.19.2	Using an existing OAH atom class	145
16.19.3	Creating a new OAH atom class without a value	147
16.19.4	Creating a new OAH atom class expecting a value	149
16.20	Extra options	152
16.21	<code>man</code> pages generation	153
16.22	Specific global OAH groups	153
16.23	Visiting OAH groups	154

VI	Representations	155
17	Representations general principles	156
17.1	Trees vs graphs	156
17.2	Denormalization	156
17.3	Newborn clones	156
17.4	Deep clones	158
17.5	Inheritance	158
17.5.1	Single inheritance	158
17.5.2	Single inheritance for smart pointers	159
17.5.3	Multiple inheritance for visitors.	160
17.5.4	Multiple inheritance in other classes	161
17.5.5	Reversibility	162
18	Displaying formats	163
18.1	Display categories	163
18.2	Displaying in practise	163
19	Music Scores Representation (MSR).	164
19.1	MSR basic types	165
19.2	Data matching across formats	166
19.3	Lengths.	167
19.4	Positions in measures and moments	167
19.5	Rests and skips	167
19.6	Solo notes and rests	167
19.7	Linear versus time-oriented representation	168
19.8	Spanners	169
19.9	Uplinks and sidelinks	169
19.10	Sounding and displayed durations	169
19.11	Printing descriptions	170
19.12	Pitches	171
19.13	Octaves.	173
19.14	Durations.	173
19.15	Alterations	174
19.16	Accidentals	174
19.17	Durations.	174
19.18	Tempos	175
19.18.1	Tempos notes	175
19.18.2	Tempos tuplets	176
19.18.3	Tempos description	177

19.19	Clefs	178
19.20	Keys	179
19.21	Time signatures	179
19.22	MSR classes inheritance	180
19.23	Books	183
19.24	Scores	183
19.25	Part groups	184
19.26	Parts	184
19.27	Staves	184
19.28	Voice elements	185
19.29	Voices	186
19.30	Measures	187
19.31	Repeats patterns and replicas	188
19.32	Beat repeats	189
19.33	Measure repeats	190
19.34	Multiple full-bar rests	191
19.35	Barlines	191
19.36	Repeats	191
19.37	Segments	193
19.38	Notes and rests	194
19.39	Articulations	195
19.40	Ornaments	195
19.41	Ties	195
19.42	Dynamics	195
19.43	Beams	195
19.44	Slurs	195
19.45	Grace notes groups	195
19.46	Chords	195
19.47	Tuplets	195
19.48	Harmonies and figured bass similarities	196
19.49	Harmonies	198
19.50	Figured bass elements	198
19.51	Lyrics	198
19.52	MIDI	199
20	MSR time-oriented representation	200
20.1	Note events	200
20.2	Simultaneous notes chunks	201
20.3	Measures slices	201
20.4	Measures slices sequences	201
20.5	Building the measures slices	202
20.5.1	Part measures slices	202
20.5.2	Staff measures slices	203
20.6	Solo notes and rests	203
20.7	A measures slices example	204
21	Path to voice	205
22	LilyPond Scores Representation (LPSR)	206
22.1	LPSR basic types	206
22.2	Adapting LilyPond code generation to the target version number	207
23	Braille Scores Representation (BSR)	208
23.1	BSR basic types	208
23.2	Representing cells	208

24	MusicXML Scores Representation (MXSR)	211
24.1	MusicXML elements and attributes	211
24.2	The <code>xmlelement</code> and <code>xmlattribute</code> types	212
24.3	Enumeration types for <code>xmlelement</code> 's <code>fType</code>	213
24.4	Classes for the <code>xmlements</code>	214
24.5	<code>xmlelement</code> trees	215
24.5.1	Creating <code>xmlelement</code> trees from textual data	216
24.5.2	Printing <code>xmlelement</code> trees	216
24.6	The <code>SXMLFile</code> type	216
VII	Passes	218
25	The passes	219
25.1	Translating MusicXML data to an MXSR format	219
25.1.1	MusicXML coverage	219
25.2	Translating an MXSR to an MSR	219
25.3	Translating an MSR to an MXSR	219
25.4	Translating an MSR to another MSR	219
25.5	Translating an MSR to an LPSR	219
25.6	Translating an LPSR to LilyPond code	220
25.7	Translating an MSR to an BSR	220
25.8	Translating a BSR to another BSR	220
25.9	Translating an MXSR to Guido	220
26	LilyPond code generation	221
26.1	Basic principle	221
26.2	Generating Scheme functions in the LilyPond output	222
27	Braille generation	223
27.1	Basic principle	223
27.2	Output files name and contents options	224
27.3	Braille generators	224
27.4	Writing braille cells	225
28	MusicXMLMain]MusicXML generation	227
28.1	Basic principle	227
28.2	Creating an <code>xmlelement</code>	227
28.3	Creating an <code>xmlelement</code> tree	228
28.4	Browsing the visited MSR score	229
28.5	Ancillary functions to create MXSR data	230
29	Guido code generation	231
29.1	Basic principle	231
VIII	Generators	232
30	The generators	233
30.1	<code>MusicAndHarmonies</code>	233
30.2	<code>Mikrokosmos3Wandering</code>	233
30.3	<code>LilyPondIssue34</code>	234
IX	Converters	235
31	The converters	236
31.1	<code>xml2ly</code>	236
31.2	<code>xml2brl</code>	236
31.3	<code>xml2xml</code>	237
31.4	<code>xml2gmn</code>	237
31.5	<code>msdlconverter</code>	237

X	Interfaces	238
32	Library interfaces	239
33	Representations interfaces	240
33.1	MSR interfaces	240
33.2	LPSR interfaces	240
33.3	MSDL interfaces	240
34	Passes interfaces	241
34.1	Translating MusicXML data to an MXSR	242
34.2	Translating an MXSR to an MSR	242
34.3	Translating an MSR to an MXSR	242
34.4	Translating an MSR to another MSR	242
34.5	Translating an MSR to an LPSR	242
34.6	Translating an LPSR to LilyPond code	242
34.7	Translating an MSR to an BSR	242
34.8	Translating a BSR to another BSR	242
34.9	Translating an MXSR to Guido	242
35	Converters interfaces	243
XI	Distributions and versions	245
36	MusicFormats distributions	246
36.1	GitHub actions	246
36.1.1	Creating the distributions	251
36.1.2	Security issue in recent MacOS™ versions	252
37	MusicFormats branches and versions	254
XII	Selected topics	260
38	Initializations	261
38.1	Options and help initializations	261
38.2	Representations initializations	262
38.2.1	MSR initialization	262
38.2.2	LPSR initialization	263
38.2.3	BSR initialization	263
38.3	Passes initializations	263
38.4	Converters initializations	263
39	The OAH atoms collection	266
39.1	OAH macro atoms	266
39.2	A OAH macro atom example	268
39.3	LilyPond octave entry	269
40	Measures handling	271
40.1	Voices contents	271
40.2	Voice elements	271
40.3	Measure elements	272
40.4	Appending measure elements to a measure	272
40.5	Appending measures to a segment	274
40.6	Appending measures to a voice	276
40.7	Translating from MXSR to MSR	278
40.8	Translating from MXSR to MSR	279
40.9	Translating from MSR to MSR	280
40.10	Translating from MSR to LPSR	280
40.11	Translating from LPSR to LilyPond	280
41	Positions in measures	281
41.1	Determining positions in measures	281

42	Finalizations	282
42.1	Clones vs non-clones finalization	282
42.2	The finalization methods	283
42.3	Finalizing parts	286
42.4	Finalizing staves	287
42.5	Finalizing voices	287
42.6	Finalizing repeats	289
42.7	Finalizing measures	289
42.7.1	Finalizing regular measures	290
42.7.2	Finalizing harmonies measures	293
42.7.3	Finalizing figured bass measures	294
42.8	Determining positions in measures	296
43	Tempos handling	297
43.1	Translating from MXSR to MSR (src/passes/mxsr2msr/)	297
43.2	Translating from MXSR to MSR (src/passes/mxsr2msr/)	297
43.3	Translating from MSR to MSR (src/passes/msr2msr/)	297
43.4	Translating from MSR to LPSR (src/passes/msr2lpsr/)	297
43.5	Translating from LPSR to LilyPond (src/passes/lpsr2lilypond/)	297
44	Positions in measures	298
44.1	Determining positions in measures	298
45	Notes handling	299
45.1	Translating from MXSR to MSR (src/passes/mxsr2msr/)	299
45.2	Translating from MXSR to MSR (src/passes/mxsr2msr/)	299
45.3	Translating from MSR to MSR (src/passes/msr2msr/)	299
45.4	Translating from MSR to LPSR (src/passes/msr2lpsr/)	299
45.5	Translating from LPSR to LilyPond (src/passes/lpsr2lilypond/)	299
46	Segments handling	300
46.1	Segments creation	300
46.1.1	Creating a new last segment for a voice	301
46.1.2	Creating a new last segment for a voice from its first measure	302
46.2	Appending measures to a segment	303
46.3	Translating from MXSR to MSR	304
46.4	Translating from MXSR to MSR	304
46.5	Translating from MSR to MSR	304
46.6	Translating from MSR to LPSR	304
46.7	Translating from LPSR to LilyPond	304
47	Beat repeats handling	305
47.1	Translating from MXSR to MSR (src/passes/mxsr2msr/)	305
47.2	Translating from MXSR to MSR (src/passes/mxsr2msr/)	305
47.3	Translating from MSR to MSR (src/passes/msr2msr/)	305
47.4	Translating from MSR to LPSR (src/passes/msr2lpsr/)	305
47.5	Translating from LPSR to LilyPond (src/passes/lpsr2lilypond/)	305
48	Measure repeats handling	306
48.1	Translating from MXSR to MSR (src/passes/mxsr2msr/)	306
48.2	Translating from MXSR to MSR (src/passes/mxsr2msr/)	306
48.3	Translating from MSR to MSR (src/passes/msr2msr/)	306
48.4	Translating from MSR to LPSR (src/passes/msr2lpsr/)	306
48.5	Translating from LPSR to LilyPond (src/passes/lpsr2lilypond/)	306
49	Multiple full-bar rests handling	307
50	Repeats handling	308
50.1	Translating repeats from MXSR to MSR	308
50.2	Translating repeats from MXSR to MSR	313
50.3	Translating repeats from MSR to MSR	313
50.4	Translating repeats from MSR to LPSR	313
50.5	Translating repeats from LPSR to LilyPond	313

51	Voices handling	314
51.1	Translating from MXSR to MSR (src/passes/mxsr2msr/)	314
51.2	Translating from MXSR to MSR (src/passes/mxsr2msr/)	314
51.3	Translating from MSR to MSR (src/passes/msr2msr/)	314
51.4	Translating from MSR to LPSR (src/passes/msr2lpsr/)	314
51.5	Translating from LPSR to LilyPond (src/passes/lpsr2lilypond/)	314
52	Staves handling	315
52.1	Translating from MXSR to MSR (src/passes/mxsr2msr/)	315
52.2	Translating from MXSR to MSR (src/passes/mxsr2msr/)	315
52.3	Translating from MSR to MSR (src/passes/msr2msr/)	315
52.4	Translating from MSR to LPSR (src/passes/msr2lpsr/)	315
52.5	Translating from LPSR to LilyPond (src/passes/lpsr2lilypond/)	315
53	Parts handling	316
53.1	Parts browsing	316
53.2	Translating from MXSR to MSR (src/passes/mxsr2msr/)	317
53.3	Translating from MXSR to MSR (src/passes/mxsr2msr/)	317
53.4	Translating from MSR to MSR (src/passes/msr2msr/)	317
53.5	Translating from MSR to LPSR (src/passes/msr2lpsr/)	317
53.6	Translating from LPSR to LilyPond (src/passes/lpsr2lilypond/)	317
54	Part groups handling	318
55	Scores handling	320
55.1	Translating from MXSR to MSR (src/passes/mxsr2msr/)	320
55.2	Translating from MXSR to MSR (src/passes/mxsr2msr/)	320
55.3	Translating from MSR to MSR (src/passes/msr2msr/)	320
55.4	Translating from MSR to LPSR (src/passes/msr2lpsr/)	320
55.5	Translating from LPSR to LilyPond (src/passes/lpsr2lilypond/)	320
56	Books handling	321
56.1	Translating from MXSR to MSR (src/passes/mxsr2msr/)	321
56.2	Translating from MXSR to MSR (src/passes/mxsr2msr/)	321
56.3	Translating from MSR to MSR (src/passes/msr2msr/)	321
56.4	Translating from MSR to LPSR (src/passes/msr2lpsr/)	321
56.5	Translating from LPSR to LilyPond (src/passes/lpsr2lilypond/)	321
57	Ornaments handling	322
57.1	Translating from MXSR to MSR (src/passes/mxsr2msr/)	322
57.2	Translating from MXSR to MSR (src/passes/mxsr2msr/)	322
57.3	Translating from MSR to MSR (src/passes/msr2msr/)	322
57.4	Translating from MSR to LPSR (src/passes/msr2lpsr/)	322
57.5	Translating from LPSR to LilyPond (src/passes/lpsr2lilypond/)	322
58	Ties handling	323
58.1	Translating from MXSR to MSR (src/passes/mxsr2msr/)	323
58.2	Translating from MXSR to MSR (src/passes/mxsr2msr/)	323
58.3	Translating from MSR to MSR (src/passes/msr2msr/)	323
58.4	Translating from MSR to LPSR (src/passes/msr2lpsr/)	323
58.5	Translating from LPSR to LilyPond (src/passes/lpsr2lilypond/)	323
59	Dynamics handling	324
59.1	Translating from MXSR to MSR (src/passes/mxsr2msr/)	324
59.2	Translating from MXSR to MSR (src/passes/mxsr2msr/)	324
59.3	Translating from MSR to MSR (src/passes/msr2msr/)	324
59.4	Translating from MSR to LPSR (src/passes/msr2lpsr/)	324
59.5	Translating from LPSR to LilyPond (src/passes/lpsr2lilypond/)	324
60	Beams handling	325
60.1	Translating from MXSR to MSR (src/passes/mxsr2msr/)	325
60.2	Translating from MXSR to MSR (src/passes/mxsr2msr/)	325
60.3	Translating from MSR to MSR (src/passes/msr2msr/)	325
60.4	Translating from MSR to LPSR (src/passes/msr2lpsr/)	325
60.5	Translating from LPSR to LilyPond (src/passes/lpsr2lilypond/)	325

61	Slurs handling	326
61.1	Translating from MXSR to MSR (src/passes/mxsr2msr/)	326
61.2	Translating from MXSR to MSR (src/passes/mxsr2msr/)	326
61.3	Translating from MSR to MSR (src/passes/msr2msr/)	326
61.4	Translating from MSR to LPSR (src/passes/msr2lpsr/)	326
61.5	Translating from LPSR to LilyPond (src/passes/lpsr2lilypond/)	326
62	Grace notes groups handling	327
62.1	Translating from MXSR to MSR (src/passes/mxsr2msr/)	327
62.2	Translating from MXSR to MSR (src/passes/mxsr2msr/)	327
62.3	Translating from MSR to MSR (src/passes/msr2msr/)	327
62.4	Translating from MSR to LPSR (src/passes/msr2lpsr/)	327
62.5	Translating from LPSR to LilyPond (src/passes/lpsr2lilypond/)	327
63	Chords handling	328
63.1	Translating from MXSR to MSR (src/passes/mxsr2msr/)	328
63.2	Translating from MXSR to MSR (src/passes/mxsr2msr/)	328
63.3	Translating from MSR to MSR (src/passes/msr2msr/)	328
63.4	Translating from MSR to LPSR (src/passes/msr2lpsr/)	328
63.5	Translating from LPSR to LilyPond (src/passes/lpsr2lilypond/)	328
64	Tuplets handling	329
64.1	Translating from MXSR to MSR (src/passes/mxsr2msr/)	329
64.2	Translating from MXSR to MSR (src/passes/mxsr2msr/)	329
64.3	Translating from MSR to MSR (src/passes/msr2msr/)	329
64.4	Translating from MSR to LPSR (src/passes/msr2lpsr/)	329
64.5	Translating from LPSR to LilyPond (src/passes/lpsr2lilypond/)	329
65	Harmonies handling	330
65.1	Harmonies staves and voices	331
65.2	Harmonies staves creation	331
65.3	Harmonies creation	332
65.4	Translating harmonies from MXSR to MSR	333
65.5	Translating harmonies from MXSR to MSR	334
65.5.1	First <code>S_harmony</code> visit.	334
65.5.2	Second <code>S_harmony</code> visit	335
65.5.3	Attaching <code>msrHarmony</code> instances to notes	336
65.5.4	Populating <code>msrHarmony</code> instances	337
65.5.5	First <code>S_harmony</code> visit.	338
65.5.6	Inserting <code>msrHarmony</code> instances in the part harmonies voice	339
65.6	Translating harmonies from MSR to MSR	340
65.7	Translating harmonies from MSR to LPSR	342
65.8	Translating harmonies from LPSR to LilyPond	344
66	Figured bass elements handling	346
66.1	Figured bass staves and voices	347
66.2	Figured bass staves creation	347
66.3	Figured bass elements creation.	348
66.4	Translating figured bass elements from MXSR to MSR	349
66.4.1	First <code>S_figured_bass</code> visit.	350
66.4.2	Second <code>S_figured_bass</code> visit.	351
66.4.3	Attaching <code>msrFiguredBassElement</code> instances to notes	352
66.4.4	Populating <code>msrFiguredBassElement</code> instances	353
66.4.5	Inserting <code>S_msFiguredBassElement</code> instances in the part figured bass voice	355
66.5	Translating figured bass elements from MSR to MSR	355
66.6	Translating figured bass elements from MSR to LPSR	357
66.7	Translating figured bass elements from LPSR to LilyPond	358

67	Lyrics handling	360
67.1	Translating from MXSR to MSR (src/passes/mxsr2msr/)	360
67.2	Translating from MXSR to MSR (src/passes/mxsr2msr/)	360
67.3	Translating from MSR to MSR (src/passes/msr2msr/)	360
67.4	Translating from MSR to LPSR (src/passes/msr2lpsr/)	360
67.5	Translating from LPSR to LilyPond (src/passes/lpsr2lilypond/)	360
68	MIDI handling	361
68.1	Translating from MXSR to MSR (src/passes/mxsr2msr/)	361
68.2	Translating from MXSR to MSR (src/passes/mxsr2msr/)	361
68.3	Translating from MSR to MSR (src/passes/msr2msr/)	361
68.4	Translating from MSR to LPSR (src/passes/msr2lpsr/)	361
68.5	Translating from LPSR to LilyPond (src/passes/lpsr2lilypond/)	361
XIII	MusicFormats Scripting Language (MFSL)	362
69	MFSL (MusicFormats Scripting Language)	363
69.1	A script example	363
69.2	Implementation principles	364
69.3	The contents of the MFSL folder	364
69.4	The MFSL basic types	365
69.5	The MFSL Makefile	365
69.6	Locations handling	366
69.7	Tokens description	366
69.8	The driver	367
69.9	Lexical analysis	369
69.9.1	Flex options	369
69.9.2	Flex regular expressions	370
69.10	Syntax and semantic analysis	372
69.10.1	Bison options for MFSL	372
69.10.2	The MFSL tokens	373
69.10.3	The MFSL non-terminals and axiom	373
69.11	Interface to the MFSL parser	374
69.12	Running the example MFSL script	375
69.12.1	Error recovery	376
XIV	Music Scores Description Language (MSDL)	377
70	MSDL (Music Scores Description Language)	378
70.1	Main features of MSDL	378
70.2	MSDL basic types	378
70.3	What the MSDL converter does	379
70.3.1	LilyPond generation	379
70.3.2	Braille generation	379
70.3.3	MusicXML generation	380
70.3.4	Guido generation	380
70.4	A first example	380
70.5	First example output from the MSDL converter	381
70.5.1	LilyPond output	381
70.5.2	Braille output	382
70.5.3	MusicXML output	382
70.5.4	Guido output	383
70.6	A more realistic example	384
70.7	Multi-language support	385
70.7.1	Multi-language messages handling	385
70.7.2	Multi-language keywords handling	385

Contents

70.8	Lexical analysis	385
70.9	Music Scores Descriptions Representation (MSDR)	385
70.10	Syntax and semantic analysis	385
70.10.1	Error recovery	385
XV	Debugging	386
71	Debugging	387
71.1	Useful options.	387
71.2	Removing the results of a build	388
71.3	Reverting to a previous MusicFormats version	388
72	Locating a bug with Git's bisection	389
72.1	Locating a bug at random in the Git log	390
72.2	Locating a bug in the commits with Git's bisection	391
72.3	Locating the bug in the code base	392
XVI	Indexes	394

Part I

Overview of MusicFormats

Chapter 1

Introduction

This document presents the design principles and architecture of MusicFormats, as well as information needed to maintain it. It is part of the MusicFormats documentation, to be found at <https://github.com/jacques-menu/musicformats/tree/master/doc>.

All the MusicXML examples mentioned can be downloaded from <https://github.com/jacques-menu/musicformats/tree/master/files/musicxml>.

They are grouped by subject in subdirectories, such as `basic/HelloWorld.xml`.

The MSDL examples can be found at <https://github.com/jacques-menu/musicformats/tree/master/files/msdl>.

1.1 Acknowledgements

Many thanks to Dominique Dominique Fober, the designer and maintainer of the `libmusicxml2` library!

1.2 Prerequisites

In order to maintain MusicFormats, one needs to do the following:

- obtain a working knowledge of C++ programming. The code base of MusicFormats uses classes, simple inheritance, and templates;
- study the architecture of MusicFormats, which can be seen in figure 1.1 [Architecture], page 18, and is presented in more detail at:
<https://github.com/jacques-menu/musicformats/blob/master/doc/musicformatsArchitecture/musicformatsArchitecture.pdf>

In this document, all paths to files are relative to the MusicFormats source code directory.

1.3 Chronology

Dominique Fober created `libmusicxml2` long before this author had the need for a library to read MusicXML data, in order to convert it to LilyPond. In the picture showing the architecture of MusicFormats in figure 1.1 [Architecture], page 18, Dom's work is essentially represented by the MusicXML, MXSR and Guido boxes at the top. He did more than this, of course, to provide `libmusicxml2` to users!

This author's work started with `xml2ly`, initially named `xml2lilypond`, whose goal was to:

- perform as least as well as `musicxml2ly`, provided by LilyPond;
- provide as many options as needed to meet the user's needs.

The `*.cpp` files in `samples` were examples of the use of the library. Among them, `xml2guido` has been used since in various contexts. The diagram in figure 1.1 [Architecture], page 18, was created afterwards, and it would then have consisted of only MusicXML, MXSR and Guido, with passes 1, 2 and 3.

When tackling the conversion of MusicXML to LilyPond, this author created MSR as the central internal representation for music score. It is meant to capture the musical contents of score in fine-grain detail, to meet the needs of creating LilyPond code first, and Braille later. The only change made to the existing MXSR format has been to add an input line number to `xmlElement`.

The conversion from MSR to BSR music was two-pass from the beginning, first creating a BSRformat with unlimited line and page lengths, and then constraining that in a second BSR would take the numbers of cell per line and lines per page into account. This was frozen in autumn 2019 due to the lack of interest from the numerous persons and bodies that this author contacted about `xml2brl`. The current status is the braille output is that the cells per line and lines per page values are ignored.

The creation of MusicXML code from MSR data was then added to close a loop with MusicXML2xml, with the idea that it would make MusicFormats a kind of swiss knife for textual formats of music scores.

Having implemented a number of computer languages in the past, this author was then tempted to design MSDL, which stands for Music Scores Description Language. The word *description* has been preferred to *programming*, because not all musicians have programming skills. The basic aim of MSDL is to provide a musician-oriented way to describe a score that can be converted to various target textual forms.

`src/clisamples/Mikrokosmos3Wandering.cpp` has been written to check that the MSR API was rich enough to go this way. The API was enriched along the way.

Having MSR, LPSR and BSR available, as well as the capability to generate MusicXML, LilyPond Guido and Braille, made writing a first draft of the MSDL converter, with version number 1.001, rather easy. The initial output target languages were MusicXML, LilyPond, MusicXML and Braille.


This document contains technical information about the internal working of the code added to MusicFormats by this author as their contribution to this great piece of software.

1.4 The GitHub repository

The GitHub repository, hosted at <https://github.com/jacques-menu/musicformats>, contains two branches types:

- the default master version, to be found at <https://github.com/jacques-menu/musicformats>, is where changes are pushed by the maintainers of MusicFormats. It is the most up to date;
- the `v. . . .` versions are the master versions frozen at some point in time.

Figure 1.1: The MusicFormats architecture



Chapter 2

Documentation

The MusicFormats documentation is written in L^AT_EX, the pictures being created with the TikZ/PGF package, see <https://www.bu.edu/math/files/2013/08/tikzpgfmanual.pdf>.

All the L^AT_EX files have an initial '`! TEX root`' comment. This is a TeXShop specific feature, allowing a documentation to be composed from any of the files that it imports, such as:

```
1 % !TEX root = MusicFormatsMaintenanceGuide.tex
```

The documentation/ directory contains:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev/documentation > ls -sal
2 total 48
3  0 drwxr-xr-x@ 10 jacquesmenu staff    320 Feb 28 07:42 .
4  0 drwxr-xr-x  38 jacquesmenu staff   1216 Feb 27 12:14 ..
5 48 -rw-r--r--@  1 jacquesmenu staff  22532 Feb 28 07:49 .DS_Store
6  0 drwxr-xr-x  18 jacquesmenu staff    576 Feb 28 08:27 CommonLaTeXFiles
7  0 drwxr-xr-x  38 jacquesmenu staff   1216 Feb 18 08:39 IntroductionToMusicXML
8  0 drwxr-xr-x  57 jacquesmenu staff   1824 Feb 28 10:08 MusicFormatsAPIGuide
9  0 drwxr-xr-x 116 jacquesmenu staff   3712 Feb 28 10:22 MusicFormatsMaintenanceGuide
10 0 drwxr-xr-x  53 jacquesmenu staff   1696 Feb 28 10:07 MusicFormatsUserGuide
11 0 drwxr-xr-x  27 jacquesmenu staff    864 Feb 14 08:54 graphics
12 0 drwxr-xr-x   5 jacquesmenu staff    160 Jan 23 16:33 presentation
```

The CommonLaTeXFiles/ directory contains L^AT_EX settings used by the various documentation files and the code for pictures:

```
1 jacquesmenu@macmini:~/musicformats-git-dev/documentation/CommonLaTeXFiles > ls -sal *.tex
2  8 -rwxr--r--@  1 jacquesmenu staff    241 Aug 17 14:21 CreateMSRScoreRepresentation.zsh
3  8 -rw-r--r--   1 jacquesmenu staff    507 Jun 28 20:52 LaTeXBoxes.tex
4 16 -rw-r--r--   1 jacquesmenu staff   6494 Jun 28 20:52 LaTeXCommonSettings.tex
5  8 -rw-r--r--   1 jacquesmenu staff   1907 Jun 28 20:52 LaTeXDivisionsCommands.tex
6  8 -rw-r--r--   1 jacquesmenu staff    957 Jun 28 20:52 LaTeXFontsAndColors.tex
7  8 -rw-r--r--   1 jacquesmenu staff    604 Jun 28 20:52 LaTeXGraphicsAndPictures.tex
8  8 -rw-r--r--   1 jacquesmenu staff   1128 Jun 28 20:52 LaTeXIndexing.tex
9 24 -rw-r--r--   1 jacquesmenu staff   10728 Jun 28 20:52 LaTeXListings.tex
10  8 -rw-r--r--   1 jacquesmenu staff   1527 Jun 28 20:52 LaTeXMusicFormatsCommands.tex
11 24 -rw-r--r--   1 jacquesmenu staff  11735 Aug 14 16:50 LaTeXMusicFormatsFilesAndFolders.
    tex
12  8 -rw-r--r--@  1 jacquesmenu staff   2151 Jun 28 20:52 LaTeXMusicFormatsNames.tex
13  8 -rw-r--r--   1 jacquesmenu staff    441 Jun 28 20:52 LaTeXMusicNotation.tex
14  8 -rw-r--r--   1 jacquesmenu staff   1535 Jun 28 20:52 LaTeXReferencing.tex
15 32 -rw-r--r--   1 jacquesmenu staff  15145 Aug 14 16:50 LaTeXShortcuts.tex
16  8 -rw-r--r--   1 jacquesmenu staff   2171 Jun 28 20:52 LaTeXTablesAndLists.tex
17 40 -rw-r--r--@  1 jacquesmenu staff  17746 Jun 28 20:52 MSRClassesHierarchyPicture.tex
18 40 -rw-r--r--@  1 jacquesmenu staff  16711 Aug 17 14:21 MSRScoreRepresentation.tex
19  8 -rw-r--r--   1 jacquesmenu staff    321 Jun 28 20:52 MusicFormats.ist
```

```

20 48 -rw-r--r--    1 jacquesmenu  staff   21749 Jun  28  20:52 MusicFormatsArchitecturePicture.
    tex
21  8 -rw-r--r--    1 jacquesmenu  staff    1558 Aug  15  23:36 OAHClassesHierarchyPicture.log
22 16 -rw-r--r--@   1 jacquesmenu  staff    5906 Aug  16  08:02 OAHClassesHierarchyPicture.tex

```

It is to be noted that `documentation/CommonLaTeXFiles/MSRScoreRepresentation.tex` is generated from `documentation/CommonLaTeXFiles/MSRClassesHierarchyPicture.tex` with this script, which should be run only if there is any change in the MSR classes hierarchy:

```

1  jacquesmenu@macmini-1:~/musicformats-git-dev/documentation/CommonLaTeXFiles > cat
    CreateMSRScoreRepresentation.zsh
2  #!/bin/zsh
3
4  # create a LaTeX file for the user guide from the maintainance one
5
6  sed 's/msr//g' MSRClassesHierarchyPicture.tex \
7  | \
8  sed 's/The MSR classes hierarchy/The MSR music score representation/g' \
9  > \
10 MSRScoreRepresentation.tex

```

Directory `graphics/` contains PNG files showing screenshots of the results of using the MusicFormats tools.

Directory `presentation/` contains a presentation of `libmusicxml2` written by Dominique Fober.

Directory `IntroductionToMusicxml/` contains a presentation done by this author at the 'MUSIC ENGRAVING IN THE 21ST CENTURY – DEVELOPMENTS AND PERSPECTIVES' conference at Mozarteum in Salzburg in January 2020 (<https://www.uni-mozarteum.at/en/kunst/music-engraving-conference.php>).

L^AT_EX needs to be run *three* times when the chapter/section/subsection hierarchy is modified. Check that the last page number, at the bottom of any page, is not less than the one before.

The following files contain the current MusicFormats version number and date:

- the `src/MusicFormatsVersionNumber.h` and `src/MusicFormatsVersionDate.h` files are used by the C++ code base;
- file `MusicFormatsVersionNumber.txt` and file `MusicFormatsVersionDate.txt` are used by the L^AT_EX source files

Those files should be re-generated when a new version of MusicFormats is created, for example:

```

1  jacquesmenu@macmini: ~/musicformats-git-dev > scripts/SetMusicFormatsVersionNumber.bash "
    0.9.61"
2  ==> PWD is:
3  /Users/jacquesmenu/musicformats-git-dev
4
5  ==> Writing MusicFormats version number 0.9.61 to MusicFormatsVersionNumber.txt
6
7  8 -rw-r--r--@ 1 jacquesmenu  staff    6 Mar  2 13:43:04 2022 MusicFormatsVersionNumber.txt
8  0.9.61
9  ==> PWD is:
10 /Users/jacquesmenu/musicformats-git-dev/src
11
12 ==> Writing MusicFormats version number 0.9.61 to MusicFormatsVersionNumber.h
13
14 8 -rw-r--r--@ 1 jacquesmenu  staff   45 Mar  2 13:43:04 2022 MusicFormatsVersionNumber.h
15 #define MUSICFORMATS_VERSION_NUMBER "0.9.61"

```

and:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev > scripts/SetMusicFormatsVersionDate.bash "
  March 2, 2022"
2 ==> PWD is:
3 /Users/jacquesmenu/musicformats-git-dev
4
5 ==> Writing MusicFormats version date March 2, 2022 to MusicFormatsVersionDate.txt
6
7 8 -rw-r--r--@ 1 jacquesmenu staff 14 Mar  2 13:43:32 2022 MusicFormatsVersionDate.txt
8 March 2, 2022
9
10 ==> PWD is:
11 /Users/jacquesmenu/musicformats-git-dev/src
12
13 ==> Writing MusicFormats version date March 2, 2022 to MusicFormatsVersionDate.h
14
15 8 -rw-r--r--@ 1 jacquesmenu staff 50 Mar  2 13:43:32 2022 MusicFormatsVersionDate.h
16 #define MUSICFORMATS_VERSION_DATE "March 2, 2022"

```

Avoid editing these files manually. In particular, `MusicFormatsVersionNumber.txt` should **NOT** be terminated by an end of line, since its contents is used in the name of library files generated in `build/lib`.

2.1 L^AT_EX macros

The MusicFormats documentation uses a number of macros both to simplify formatting of frequent texts and to feed the many indexes at the end. All of them are grouped in `documentation/CommonLaTeXFiles`:

```

1 jacquesmenu@mac-mini-de-jacques-1:~/musicformats-git-dev/documentation/CommonLaTeXFiles >
  ls -sal LaTeX*.tex
2  8 -rw-r--r--  1 jacquesmenu staff    507 Jun  28 20:52 LaTeXBoxes.tex
3 16 -rw-r--r--  1 jacquesmenu staff   6494 Jun  28 20:52 LaTeXCommonSettings.tex
4  8 -rw-r--r--  1 jacquesmenu staff   1907 Jun  28 20:52 LaTeXDivisionsCommands.tex
5  8 -rw-r--r--  1 jacquesmenu staff    957 Jun  28 20:52 LaTeXFontsAndColors.tex
6  8 -rw-r--r--  1 jacquesmenu staff    604 Jun  28 20:52 LaTeXGraphicsAndPictures.tex
7  8 -rw-r--r--  1 jacquesmenu staff   1128 Jun  28 20:52 LaTeXIndexing.tex
8 24 -rw-r--r--  1 jacquesmenu staff  10728 Jun  28 20:52 LaTeXListings.tex
9  8 -rw-r--r--  1 jacquesmenu staff   1527 Jun  28 20:52 LaTeXMusicFormatsCommands.tex
10 24 -rw-r--r--@ 1 jacquesmenu staff  11735 Jul  29 09:02 LaTeXMusicFormatsFilesAndFolders.
   tex
11  8 -rw-r--r--@ 1 jacquesmenu staff   2151 Jun  28 20:52 LaTeXMusicFormatsNames.tex
12  8 -rw-r--r--  1 jacquesmenu staff    441 Jun  28 20:52 LaTeXMusicNotation.tex
13  8 -rw-r--r--  1 jacquesmenu staff   1535 Jun  28 20:52 LaTeXReferencing.tex
14 32 -rw-r--r--@ 1 jacquesmenu staff  14665 Jun  28 20:52 LaTeXShortcuts.tex
15  8 -rw-r--r--  1 jacquesmenu staff   2171 Jun  28 20:52 LaTeXTablesAndLists.tex

```

For example:

```

1 \newcommand{\CLI}{command line\index[Main]{command line}}

```

```

1 \newcommand{\musicXmlMarkup}[1]{%
2 {\tt <#1/>}\index[Main]{\tt $<$#1 /$>$}\index[MusicXML]{\tt #1 $<$>$}%
3 }
4 \newcommand{\musicXmlAttribute}[1]{%
5 {\tt "#1"}\index[Main]{\tt $<$#1 /$>$}\index[MusicXML]{\tt #1 ""}%
6 }

```

```

1 \newcommand{\Main}[1]{%
2 #1\index[Main]{#1}%
3 }
4 \newcommand{\MainName}[1]{%
5 \index[Main]{#1}%
6 }

```

```

7
8 \newcommand{\code}[1]{%
9 {\tt #1}\index[Main]{\tt #1}}%
10 }

```

Some command exist in two forms, differing in the capitalization of the first character:

```

1 \newcommand{\enumType}{enumeration type\index[Main]{enumeration type}}
2 \newcommand{\EnumType}{Enumeration type\index[Main]{enumeration type}}

```

Some command names are of the form ***Both***:

```

1 \newcommand{\fileName}[1]{%
2 {\tt #1}\index[Main]{\tt #1}\index[Files]{\tt #1}}%
3 }
4 \newcommand{\fileNameBoth}[1]{%
5 {\textcolor{brown}{\tt *#1.h/.cpp}}\index[Main]{#1.h/.cpp@\tt *#1.h/.cpp}}\index[Files
6 ]{#1.h/.cpp@\tt *#1.h/.cpp}}%

```

```

1 \newcommand{\msrToMsr}[1]{%
2 {\textcolor{brown}{\tt src/passes/msr2msr/#1}}%
3 }
4 \newcommand{\msrToMsrBoth}[1]{%
5 {\textcolor{brown}{\tt src/passes/msr2msr/#1.h/.cpp}}%
6 }

```

Some command names are of the form **star***:

```

1 \newcommand{\methodName}[1]{%
2 {\tt #1~()}\index[Main]{\tt #1~()}\index[MethodsAndFields]{\tt #1~()}}%
3 }
4 \newcommand{\starMethodName}[1]{%
5 {\tt *#1~()}\index[Main]{#1~()@\tt *#1}}\index[MethodsAndFields]{*#1~()@\tt *#1~()}}%
6 }

```

Some commands have a variant of the form ***Name*** to produce only their arguments, with no additional text:

```

1 \newcommand{\file}[1]{%
2 file {\tt #1}\index[Main]{\tt #1}\index[Files]{\tt #1}}%
3 }
4 \newcommand{\File}[1]{%
5 File {\tt #1}\index[Main]{\tt #1}\index[Files]{\tt #1}}%
6 }
7
8 \newcommand{\fileName}[1]{%
9 {\tt #1}\index[Main]{\tt #1}\index[Files]{\tt #1}}%
10 }
11 \newcommand{\fileNameBoth}[1]{%
12 {\textcolor{brown}{\tt *#1.h/.cpp}}\index[Main]{#1.h/.cpp@\tt *#1.h/.cpp}}\index[Files
13 ]{#1.h/.cpp@\tt *#1.h/.cpp}}%

```

Some commands are in the form ***Repr** : the designate the name of a representation, such as:

```

1 \newcommand{\msrRepr}{MSR\index[Main]{MSR}}

```

2.2 About this document

This document provides cross views of the information needed for MusicFormats maintainance. It is organized in a number of parts:

- the first part provides an overview of the library, together with the concepts it uses;
- then the two-phase visitors pattern, which is central to MusicFormats, is presented;
- the third part is dedicated to the programming style and conventions used throughout the code base;
- the OAH (Options and help), a pervasive feature in MusicFormats, is detailed;
- the fifth part details the formats provided by the library;
- the following parts are dedicated to passes, generators and converters, respectively;
- the ninth part presents the interfaces to the formats, passes and converters;
- the tenth part provides a longitudinal view of the handling of selected music score contents elements, grouped by such elements such as staves, tuplets and harmonies;
- and finally, the last part is dedicated to the implementation of the MSDDL language.

2.3 The MusicFormats architecture

2.4 User guide

[documentation/MusicFormatsUserGuide/MusicFormatsUserGuide.pdf](#) is the usual user guide. It presents the use of MusicFormats with the command line for the time being.

2.5 API guide

[documentation/MusicFormatsAPIGuide/MusicFormatsAPIGuide.pdf](#) presents the use of MusicFormats through the APIs. The latter are used internally by the command line tools, and can be used from applications at will, such as in a Web site.

2.6 Maintainance guide

[documentation/MusicFormatsMaintainanceGuide/MusicFormatsMaintainanceGuide.pdf](#) describes the internals of MusicFormats from a maintainer's point of view. It contains a detailed presentation of the various types used, and a part dedicated to selected topics: this is to have a longitudinal view of how various music elements are handled in the various passes.

Chapter 3

Building MusicFormats

In order to build MusicFormats from source on your machine, you need:

- a C++17 compiler;
- the `cmake` tool.

The supported operating systems both to build the library and run the command line tools are Linux, Windows and MacOS. Other systems may be fine but have not been tested.

The C++17 language is needed because MusicFormats uses `<regex>` and the `auto` keyword. More recent versions should not be a problem.

3.1 Cloning the repository

Commands such as the following can be used to clone the master and version branches, respectively:

```
1 MUSIC_FORMATS_DIR=${HOME}/musicformats-git-dev
2 git clone https://github.com/jacques-menu/musicformats.git ${MUSIC_FORMATS_DIR}
3 cd ${MUSIC_FORMATS_DEV}
```

```
1 VERSION_BRANCH=v0.9.59
2 MUSIC_FORMATS_DIR=${HOME}/musicformats-git-${VERSION_BRANCH}
3 git clone -b ${VERSION_BRANCH} https://github.com/jacques-menu/musicformats.git ${MUSIC_FORMATS_DIR}
4 cd ${MUSIC_FORMATS_DIR}
```

3.2 One-shot partial make runs

Some parts of the source code base have to be created by their own `make` file once and for all. This is the case of:

- the constants and classes generated for MXSR from the MusicXML DTD by `libmusicxml/src/elements/templ`
- the MFSL scanner and parser in the `mfs1/` directory, generated by `flex` and `bison` respectively.

3.3 cmake configuration

This configuration is in `build/CMakeList.txt`.

3.4 Library Makefile

This Makefile is `build/Makefile`.

3.5 CLI amplex Makefile

This Makefile is `src/clisamples/Makefile`.

3.6 Building MusicFormats in practise

Once in the local repository clone, just execute:

```
1 cd build
2 make
```

The resulting executables are in `build/bin`:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev > ll build/bin
2 total 754368
3      0 drwxr-xr-x@ 26 jacquesmenu  staff      832 Sep 27 00:05:02 2021 ./
4      0 drwxr-xr-x  11 jacquesmenu  staff      352 Aug  1 18:32:54 2021 ../
5 72072 -rwxr-xr-x   1 jacquesmenu  staff 36899440 Sep 27 00:04:52 2021 LilyPondIssue34*
6 72080 -rwxr-xr-x   1 jacquesmenu  staff 36902528 Sep 27 00:04:54 2021
7      Mikrokosmos3Wandering*
8 8504 -rwxr-xr-x   1 jacquesmenu  staff 4350480 Sep 27 00:04:49 2021 MusicAndHarmonies*
9 8504 -rwxr-xr-x   1 jacquesmenu  staff 4350464 Sep 27 00:05:00 2021 RandomChords*
10 8504 -rwxr-xr-x   1 jacquesmenu  staff 4350448 Sep 27 00:05:01 2021 RandomMusic*
11 8696 -rwxr-xr-x   1 jacquesmenu  staff 4450928 Sep 27 00:04:56 2021 countnotes*
12 63904 -rwxr-xr-x   1 jacquesmenu  staff 32717248 Sep 27 00:04:57 2021
13      libMultipleInitsTest*
14 76696 -rwxr-xr-x   1 jacquesmenu  staff 39266928 Sep 27 00:05:01 2021 msdlconverter*
15 144 -rwxr-xr-x   1 jacquesmenu  staff    70480 Sep 27 00:04:55 2021 musicformatsversion
16      *
17 12616 -rwxr-xr-x   1 jacquesmenu  staff 6455376 Sep 27 00:04:59 2021 partsummary*
18 8920 -rwxr-xr-x   1 jacquesmenu  staff 4564864 Sep 27 00:04:59 2021 readunrolled*
19 81048 -rwxr-xr-x   1 jacquesmenu  staff 41496208 Sep 27 00:04:49 2021 xml2Any*
20 61232 -rwxr-xr-x   1 jacquesmenu  staff 31347456 Sep 27 00:04:53 2021 xml2brl*
21 63704 -rwxr-xr-x   1 jacquesmenu  staff 32615072 Sep 27 00:04:47 2021 xml2gmn*
22 17368 -rwxr-xr-x   1 jacquesmenu  staff 8891744 Sep 27 00:04:56 2021 xml2guido*
23 63896 -rwxr-xr-x   1 jacquesmenu  staff 32713936 Sep 27 00:04:50 2021 xml2ly*
24 12512 -rwxr-xr-x   1 jacquesmenu  staff 6403968 Sep 27 00:04:55 2021 xml2midi*
25 56384 -rwxr-xr-x   1 jacquesmenu  staff 28865024 Sep 27 00:04:59 2021 xml2xml*
26 9176 -rwxr-xr-x   1 jacquesmenu  staff 4695472 Sep 27 00:04:55 2021 xmlclone*
27 9320 -rwxr-xr-x   1 jacquesmenu  staff 4771024 Sep 27 00:05:00 2021 xmlfactory*
28 8912 -rwxr-xr-x   1 jacquesmenu  staff 4559072 Sep 27 00:04:57 2021 xmliter*
29 8752 -rwxr-xr-x   1 jacquesmenu  staff 4478336 Sep 27 00:04:55 2021 xmlread*
30 12104 -rwxr-xr-x   1 jacquesmenu  staff 6193216 Sep 27 00:04:54 2021 xmltranspose*
31 9320 -rwxr-xr-x   1 jacquesmenu  staff 4770128 Sep 27 00:05:02 2021 xmlversion*
```

The resulting libraries are in `build/bin`, here on MacOS:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev > ll build/lib
2 total 1888712
3      0 drwxr-xr-x  10 jacquesmenu  staff      320 Sep 27 00:04:46 2021 ./
4      0 drwxr-xr-x  11 jacquesmenu  staff      352 Aug  1 18:32:54 2021 ../
5 104904 -rwxr-xr-x   1 jacquesmenu  staff 53707712 Sep 27 00:04:46 2021 libmusicxml2
6      .3.2.0.dylib*
7      0 lrwxr-xr-x   1 jacquesmenu  staff      24 Sep 27 00:04:45 2021 libmusicxml2.3.
8      dylib@ -> libmusicxml2.3.2.0.dylib
9 1055040 -rw-r--r--   1 jacquesmenu  staff 532838416 Sep 27 00:04:41 2021 libmusicxml2.a
10 591776 -rw-r--r--   1 jacquesmenu  staff 302989312 Sep 21 09:05:55 2021 libmusicxml2.a.
11      A93i4n
12 57056 -rw-r--r--   1 jacquesmenu  staff 29212672 Sep 21 09:01:27 2021 libmusicxml2.a.
13      KHrJT0
14 39968 -rw-r--r--   1 jacquesmenu  staff 20463616 Sep 21 09:11:20 2021 libmusicxml2.a.
15      gZfmqe
16 39968 -rw-r--r--   1 jacquesmenu  staff 20463616 Sep 21 09:09:22 2021 libmusicxml2.a.
17      tndUAV
18      0 lrwxr-xr-x   1 jacquesmenu  staff      20 Sep 27 00:04:45 2021 libmusicxml2.
19      dylib@ -> libmusicxml2.3.dylib

```

Chapter 4

Code base structure

The code base of the MusicFormats library contains:

- `build` : a set of files to build the library in various environments with `make`
- `doc` : the documentation in L^AT_EX source and PDF formats
- `files` : a set of sample files for MusicXML and MSDL
- `javascript` : a set of files for the generation of Java Script, to allow the use of MusicFormats in Web sites
- `libmusicxml` : an embedded copy of the `libmusicxml2` code base
- `packages` : a set of files to create installable versions of the library, not yet operational
- `samples` : the main programs for examples supplied with MusicFormats, such as generators and converters
- `schemas` : a set of files defining the input languages, currently MusicXML, BMML and MEI, together with scripts to generate the set of classes definitions for analyzing them
- `src` the library code base, detailed below
- `validation` : a set of files including a `Makefile` for the validation of the library using the contents of files
- `win32` : Windows related support

4.1 The `libmusicxml` folder

This folder contains a version of Grame's `libmusicxml2` library, available at <https://github.com/grame-cncm/libmusicxml>. It is used by MusicFormats, to avoid the need for installing it separately.

The only possible annoyance when installing both libraries is that the executables in `libmusicxml/build/bin` such as `countnotes` and `xml2guido` are installed twice: choosing which one to use can be handled in the `PATH` and `LD_LIBRARY_PATH` environment variables or their equivalent.

4.1.1 Embedding libmusicxml in MusicFormats

libmusicxml2 was cloned initially like this:

```
1 jacquesmenu@mac-mini-de-jacques-1:~/musicformats-git-dev > git clone https://github.com/
   grame-cncm/libmusicxml -b dev
2 Cloning into 'libmusicxml'...
3 remote: Enumerating objects: 56386, done.
4 remote: Counting objects: 100% (4692/4692), done.
5 remote: Compressing objects: 100% (777/777), done.
6 remote: Total 56386 (delta 3917), reused 4671 (delta 3904), pack-reused 51694
7 Receiving objects: 100% (56386/56386), 105.98 MiB | 15.91 MiB/s, done.
8 Resolving deltas: 100% (46834/46834), done.
```

libmusicxml2 is quite stable, and it can be upgraded if needed with:

```
1 jacquesmenu@mac-mini-de-jacques-1:~/musicformats-git-dev/libmusicxml > git pull
2 Already up to date.
```

There is no need to build libmusicxml2 manually, since its code is taken into account by the MusicFormats Makefile.

4.1.2 Upgrading the supported MusicXML version

It may be necessary to upgrade the MusicXML DTD in `libmusicxml/elements` to keep up with evolutions if libmusicxml2 is not up to date yet.

To upgrade from MusicXML 3.1 to MusicXML 4.0, the following has been done. `Makefile_ORIGINAL` is a symbolic link to the `Makefile` provided by libmusicxml2 for 3.1 at the time of this writing:

```
1 jacquesmenu@mac-mini-de-jacques-1:~/musicformats-git-dev/libmusicxml/schema > ls -sal
2 total 208
3  0 drwxr-xr-x  14 jacquesmenu  staff    448 Jul 30 05:59 .
4  0 drwxr-xr-x  22 jacquesmenu  staff    704 Jul 29 07:19 ..
5  0 drwxr-xr-x   6 jacquesmenu  staff    192 Jul 29 07:19 2.0
6  0 drwxr-xr-x   6 jacquesmenu  staff    192 Jul 29 07:19 3.0
7  0 drwxr-xr-x   6 jacquesmenu  staff    192 Jul 29 07:19 3.1
8  0 drwxr-xr-x   8 jacquesmenu  staff    256 Jul 29 08:04 4.0
9  8 -rw-r--r--   1 jacquesmenu  staff   1215 Jul 29 07:19 Makefile
10 8 -rw-r--r--   1 jacquesmenu  staff   1215 Jul 29 07:19 Makefile_3.1
11 0 lrwxr-xr-x   1 jacquesmenu  staff     8 Jul 30 05:59 Makefile_ORIGINAL -> Makefile
```

First, create the `Makefile` for version 4.0:

```
1 jacquesmenu@mac-mini-de-jacques-1:~/musicformats-git-dev/libmusicxml/schema > sed 's
   /3.1/4.0/g' Makefile_3.1 > Makefile_4.0
```

Then use it to create the C++ files containing the constants and types to be used by MXSR, such as `k_accidental`, `S_accidental`:

```
1 jacquesmenu@mac-mini-de-jacques-1:~/musicformats-git-dev/libmusicxml/schema > make -f
   Makefile_4.0
2 grep "<xs:element" 4.0/musicxml.xsd | sed -e 's/^.*name="//' | sed -e 's/"..*//' | sort -u
   > elements.txt
3 ../src/elements/templates/elements.bash elements.txt ../src/elements/templates constants >
   elements.h || rm -f elements.h
4 ../src/elements/templates/elements.bash elements.txt ../src/elements/templates types >
   typedefs.h || rm -f typedefs.h
5 ../src/elements/templates/elements.bash elements.txt ../src/elements/templates map >
   factory.cpp || rm -f factory.cpp
```

The resulting files are the following, where `elements.txt` contains an alphabetic list of the MusicXML markups found in the DTD:

```

1 jacquesmenu@mac-mini-de-jacques-1:~/musicformats-git-dev/libmusicxml/schema > ls -sal
2 total 208
3  0 drwxr-xr-x  13 jacquesmenu  staff    416 Jul 29 08:27 .
4  0 drwxr-xr-x  22 jacquesmenu  staff    704 Jul 29 07:19 ..
5  0 drwxr-xr-x   6 jacquesmenu  staff    192 Jul 29 07:19 2.0
6  0 drwxr-xr-x   6 jacquesmenu  staff    192 Jul 29 07:19 3.0
7  0 drwxr-xr-x   6 jacquesmenu  staff    192 Jul 29 07:19 3.1
8  0 drwxr-xr-x   8 jacquesmenu  staff    256 Jul 29 08:04 4.0
9  8 -rw-r--r--   1 jacquesmenu  staff   1215 Jul 29 07:19 Makefile_3.1
10 8 -rw-r--r--@  1 jacquesmenu  staff   1215 Jul 29 08:26 Makefile_4.0
11 8 -rw-r--r--   1 jacquesmenu  staff   1215 Jul 29 07:19 Makefile_ORIGINAL
12 16 -rw-r--r--   1 jacquesmenu  staff   7130 Jul 29 08:27 elements.h
13 16 -rw-r--r--   1 jacquesmenu  staff   4561 Jul 29 08:27 elements.txt
14 96 -rw-r--r--   1 jacquesmenu  staff  46341 Jul 29 08:27 factory.cpp
15 56 -rw-r--r--   1 jacquesmenu  staff  24604 Jul 29 08:27 typedefs.h

```

The mapping between the makups text and the types that describes them is done with:

```

1 typedef SMARTP<musicxml<k_accidental> >    S_accidental;
2
3 fMap["accidental"] = new newElementFunctor<k_accidental>;

```

Finally, copy the new C++ files to the `libmusicxml/elements` folder:

```

1 jacquesmenu@mac-mini-de-jacques-1:~/musicformats-git-dev/libmusicxml/schema > cp -p
   elements.h factory.cpp typedefs.h ../src/elements

```

Now, rebuild MusicFormats, for it to use the new MusicXML DTD: `/libdir/CMakeCache.txt`

```

1 jacquesmenu@mac-mini-de-jacques-1:~/musicformats-git-dev/build > rm libdir/CMakeCache.txt
2 jacquesmenu@mac-mini-de-jacques-1:~/musicformats-git-dev/build > make

```

It may happen that error messages regarding the new markups are issued:

```

1 Undefined symbols for architecture x86_64:
2  "MusicFormats::mxsr2msrTranslator::visitStart(MusicXML2::SMARTP<MusicXML2::musicxml<241>
   >&)", referenced from:
3  "MusicFormats::mxsr2msrTranslator::visitStart(MusicXML2::SMARTP<MusicXML2::musicxml<266>
   >&)", referenced from:
4  "MusicFormats::mxsr2msrTranslator::visitStart(MusicXML2::SMARTP<MusicXML2::musicxml<284>
   >&)", referenced from:
5  "MusicFormats::mxsr2msrTranslator::visitStart(MusicXML2::SMARTP<MusicXML2::musicxml<29>
   >&)", referenced from:
6  "non-virtual thunk to MusicFormats::mxsr2msrTranslator::visitStart(MusicXML2::SMARTP<
   MusicXML2::musicxml<284> >&)", referenced from:
7  "non-virtual thunk to MusicFormats::mxsr2msrTranslator::visitStart(MusicXML2::SMARTP<
   MusicXML2::musicxml<29> >&)", referenced from:
8 clang: error: linker command failed with exit code 1 (use -v to see invocation)
9 ** BUILD FAILED **
10 make[1]: *** [macos] Error 65
11 make: *** [all] Error 2

```

In that case, the corresponding constants can be found in `elements.h`, at line `'26+numericalValue'`. For example, with MusicXML version 4.0, 241 is the numerical value of `k_notations`, describing markup `<"notations"/>`:

```

1 jacquesmenu@mac-mini-de-jacques-1:~/musicformats-git-dev/libmusicxml/src/elements > grep -
  n kNoElement elements.h
2 26: kNoElement,
3 jacquesmenu@mac-mini-de-jacques-1:~/musicformats-git-dev/libmusicxml/src/elements > grep -
  n k_notations elements.h
4 267: k_notations,
5 jacquesmenu@mac-mini-de-jacques-1:~/musicformats-git-dev/libmusicxml/src/elements > grep -
  n k_other_notation elements.h
6 292: k_other_notation,
7 jacquesmenu@mac-mini-de-jacques-1:~/musicformats-git-dev/libmusicxml/src/elements > grep -
  n k_part_name elements.h
8 310: k_part_name,
9 311: k_part_name_display,
10 jacquesmenu@mac-mini-de-jacques-1:~/musicformats-git-dev/libmusicxml/src/elements > grep -
  n k_bass elements.h
11 55: k_bass,
12 56: k_bass_alter,
13 57: k_bass_separator,
14 58: k_bass_step,

```

The incriminated MXSR elements are thus `k_notations`, `k_other_notation`, `k_part_name` and `k_bass`.

The first 4 error messages above mean that the corresponding `visitStart ()` methods are declared alright, but are not defined in `src/passes/mxsr2msr/mxsr2msrTranslator.cpp`.

The following methods definitions are thus missing:

- `method mxsr2msrTranslator::visitStart (S_notations& elt)`
- `method mxsr2msrTranslator::visitStart (S_other_notation& elt)`
- `method mxsr2msrTranslator::visitStart (S_part_name& elt)`
- `method mxsr2msrTranslator::visitStart (S_bass& elt)`

Type `S_part_name` is there by mistake (some typing was done before the upgrade to 4.0), since it is handled in class `mxsr2msrSkeletonBuilder`, and the other 3 are new in MusicXML 4.0.

4.2 The doc folder

This folder contains `LaTeXCommonSettings.tex`, included by the various \LaTeX documents whose code is in the respective folders, together with the PDF files:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/documentation > ll
2 total 56
3  0 drwxr-xr-x   9 jacquesmenu  staff    288 Jan  4 17:23:41 2022 ./
4  0 drwxr-xr-x  37 jacquesmenu  staff   1184 Dec 29 08:09:43 2021 ../
5 48 -rw-r--r--@   1 jacquesmenu  staff  22532 Jan  4 17:23:00 2022 .DS_Store
6  8 -rw-r--r--   1 jacquesmenu  staff    42 Apr 22 15:48:42 2021 .gitignore
7  0 drwxr-xr-x  38 jacquesmenu  staff   1216 Dec 26 08:49:24 2021 IntroductionToMusicXML/
8  0 drwxr-xr-x 119 jacquesmenu  staff   3808 Jan  4 17:19:38 2022
   MusicFormatsMaintenanceGuide/
9  0 drwxr-xr-x  49 jacquesmenu  staff   1568 Jan  4 17:04:10 2022 MusicFormatsUserGuide/
10 0 drwxr-xr-x   9 jacquesmenu  staff    288 Jan  4 17:23:41 2022 CommonLaTeXFiles/
11 0 drwxr-xr-x   6 jacquesmenu  staff    192 Apr 22 15:48:43 2021 presentation/

```

`common` contains a set of files used by the various documents and various stuff:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/documentation/common > ll
2 total 776
3  0 drwxr-xr-x  9 jacquesmenu  staff      288 Jan  4 17:23:41 2022 ./
4  0 drwxr-xr-x  9 jacquesmenu  staff      288 Jan  4 17:23:41 2022 ../
5 624 -rw-r--r--  1 jacquesmenu  staff    318497 Apr 22 15:48:40 2021 INSIDE.pdf
6   8 -rw-r--r--@ 1 jacquesmenu  staff      321 Sep  8 18:15:51 2021 MusicFormats.list
7  48 -rw-r--r--@ 1 jacquesmenu  staff    21751 Dec 28 18:45:25 2021
   MusicFormatsArchitecturePicture.tex
8  80 -rw-r--r--@ 1 jacquesmenu  staff    39133 Jan  4 17:18:28 2022 LaTeXCommonSettings.tex
9   8 -rwxr-xr-x@ 1 jacquesmenu  staff      157 Jan  4 09:43:30 2022
   createCurrentVersionNumberString.bash*
10  0 drwxr-xr-x 12 jacquesmenu  staff      384 Apr 22 15:48:41 2021 images_KEEP/
11  8 -rw-r--r--@ 1 jacquesmenu  staff        7 Jan  4 09:25:02 2022
   MusicFormatsVersionNumber.txt

```

The presentation sub-folder contains the documentation of the libmusicxml2 library, written by Dominique Fober:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/documentation/presentation > ll
2 total 504
3  0 drwxr-xr-x  6 jacquesmenu  staff      192 Apr 22 15:48:43 2021 ./
4  0 drwxr-xr-x  9 jacquesmenu  staff      288 Jan  4 17:23:41 2022 ../
5  0 drwxr-xr-x  6 jacquesmenu  staff      192 Apr 22 15:48:43 2021 imgs/
6  88 -rw-r--r--  1 jacquesmenu  staff    41534 Apr 22 15:48:43 2021 libmusicxml2.odg
7 392 -rw-r--r--  1 jacquesmenu  staff   200524 Apr 22 15:48:43 2021 libmusicxml2.pdf
8  24 -rw-r--r--@ 1 jacquesmenu  staff    11003 Oct 15 18:48:11 2021 libmusicxml2.tex

```

4.3 The schemas folder

This folder contains the definitions used to create the classes definitions to analyze textual data in the MusicXML, MEI and BMML formats.

In the scripts folder, `elements.bash` compiles the definitions of MusicXML markups into the C++ code files containing the corresponding C++ classes:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/schemas > ll
2 total 2576
3  0 drwxr-xr-x  9 jacquesmenu  staff      288 May 21 18:30:08 2021 ./
4  0 drwxr-xr-x 22 jacquesmenu  staff      704 May 25 17:19:16 2021 ../
5 16 -rw-r--r--  1 jacquesmenu  staff    6148 May 21 18:30:08 2021 .DS_Store
6  0 drwxr-xr-x  4 jacquesmenu  staff      128 Apr 22 15:49:14 2021 BMML/
7  0 drwxr-xr-x  5 jacquesmenu  staff      160 May 21 18:30:08 2021 MEI/
8   8 -rw-r--r--  1 jacquesmenu  staff    2502 Apr 22 15:49:15 2021 Makefile
9   0 drwxr-xr-x  6 jacquesmenu  staff      192 May 21 18:30:08 2021 MusicXML/
10 2552 -rw-r--r--  1 jacquesmenu  staff  1305905 Apr 22 15:49:13 2021 mei-CMN.rng
11  0 drwxr-xr-x  3 jacquesmenu  staff        96 Apr 22 15:49:08 2021 scripts/

```

4.4 The src folder

The src folder has the following structure:

- `clisamples` : the main () functions of the various command line executables provided by MusicFormats:


```

1 jacquesmenu@macmini: ~/musicformats-git-dev > ll clisamples/
2 total 320
3 0 drwxr-xr-x 16 jacquesmenu staff 512 May 24 10:58:19 2021 ./
4 0 drwxr-xr-x 22 jacquesmenu staff 704 May 25 17:19:16 2021 ../
5 16 -rw-r--r-- 1 jacquesmenu staff 6148 May 21 18:30:07 2021 .DS_Store
6 8 -rw-r--r-- 1 jacquesmenu staff 116 Apr 22 15:49:06 2021 .gitignore
7 40 -rw-r--r--@ 1 jacquesmenu staff 20239 May 24 11:17:46 2021 LilyPondIssue34.cpp
8 8 -rw-r--r-- 1 jacquesmenu staff 1615 Apr 22 15:49:15 2021 Makefile
9 40 -rw-r--r--@ 1 jacquesmenu staff 20239 May 24 11:07:21 2021
   Mikrokosmos3Wandering.cpp
10 24 -rw-r--r-- 1 jacquesmenu staff 9941 May 21 18:30:07 2021 MusicAndHarmonies.
   cpp
11 8 -rw-r--r-- 1 jacquesmenu staff 3114 Apr 22 15:49:15 2021 libMultipleInitsTest
   .cpp
12 48 -rw-r--r-- 1 jacquesmenu staff 23061 May 21 18:30:07 2021 msdl.cpp
13 8 -rw-r--r-- 1 jacquesmenu staff 895 May 21 18:30:07 2021 musicformatsversion.
   cpp
14 24 -rw-r--r-- 1 jacquesmenu staff 10492 Apr 22 15:49:14 2021 xml2Any.cpp
15 24 -rw-r--r-- 1 jacquesmenu staff 10076 May 21 18:30:07 2021 xml2brl.cpp
16 24 -rw-r--r-- 1 jacquesmenu staff 10515 May 21 18:30:07 2021 xml2gmn.cpp
17 24 -rw-r--r-- 1 jacquesmenu staff 10309 May 21 18:30:07 2021 xml2ly.cpp
18 24 -rw-r--r-- 1 jacquesmenu staff 10463 May 21 18:30:08 2021 xml2xml.cpp

```

- **converters** : the multi-pass converter combining those in passes

```

- msdl2braille
- msdl2guido
- msdl2lilypond
- msdl2musicxml
- msdlconverter

- msr2braille
- msr2guido
- msr2lilypond
- msr2musicxml

- musicxml2braille
- musicxml2guido
- musicxml2lilypond
- musicxml2musicxml

```

- **generators** :

```

- LilyPondIssue34
- Mikrokosmos3Wandering

```

- **components** : the MusicFormats components formats, including versions numbering and history:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src > ll components
2 total 168
3 0 drwxr-xr-x 7 jacquesmenu staff 224 Oct 22 08:53:06 2021 ./
4 0 drwxr-xr-x 19 jacquesmenu staff 608 Oct 22 05:29:29 2021 ../
5 8 -rw-r--r--@ 1 jacquesmenu staff 1106 Oct 22 09:16:21 2021 mfcComponents.h
6 96 -rw-r--r--@ 1 jacquesmenu staff 46691 Nov 8 12:59:57 2021 mfcBasicTypes.cpp
7 40 -rw-r--r--@ 1 jacquesmenu staff 20121 Nov 8 12:59:43 2021 mfcBasicTypes.h

```

```

8 16 -rw-r--r--@ 1 jacquesmenu staff 4950 Nov 8 12:59:08 2021 mfcLibraryComponent.
   cpp
9 8 -rw-r--r--@ 1 jacquesmenu staff 605 Oct 22 10:36:30 2021 mfcLibraryComponent.
   h

```

- **mfutilities** : various utilities, including indented text output streams, and version history support:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src > ll mfutilities/
2 total 200
3 0 drwxr-xr-x 15 jacquesmenu staff 480 Oct 22 06:25:57 2021 ./
4 0 drwxr-xr-x 19 jacquesmenu staff 608 Oct 22 05:29:29 2021 ../
5 8 -rw-r--r--@ 1 jacquesmenu staff 3255 Oct 18 20:22:16 2021 mfBool.cpp
6 16 -rw-r--r--@ 1 jacquesmenu staff 4917 Oct 18 19:56:51 2021 mfBool.h
7 8 -rw-r--r--@ 1 jacquesmenu staff 1336 Oct 15 18:48:10 2021 mfEnumAll.h
8 16 -rw-r--r--@ 1 jacquesmenu staff 7182 Nov 8 13:08:51 2021 mfIndentedTextOutput
   .cpp
9 16 -rw-r--r--@ 1 jacquesmenu staff 7715 Nov 8 13:08:40 2021 mfIndentedTextOutput
   .h
10 8 -rw-r--r--@ 1 jacquesmenu staff 889 Oct 15 20:34:47 2021 mfMusicformatsError.
   cpp
11 8 -rw-r--r--@ 1 jacquesmenu staff 629 Oct 15 20:34:47 2021 mfMusicformatsError.
   h
12 8 -rw-r--r--@ 1 jacquesmenu staff 2541 Nov 5 11:29:25 2021 oahOptionsVector.cpp
13 8 -rw-r--r--@ 1 jacquesmenu staff 972 Oct 15 20:16:51 2021 oahBasicTypes.h
14 64 -rw-r--r--@ 1 jacquesmenu staff 29773 Oct 15 18:48:10 2021 mfStringsHandling.
   cpp
15 16 -rw-r--r--@ 1 jacquesmenu staff 6269 Oct 15 18:55:46 2021 mfStringsHandling.h
16 16 -rw-r--r--@ 1 jacquesmenu staff 5028 Oct 7 20:03:27 2021 mfTiming.cpp
17 8 -rw-r--r--@ 1 jacquesmenu staff 3726 Oct 8 08:21:09 2021 mfTiming.h

```

- **oah** : object-oriented Options And Help support

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src > ll oah
2 total 1456
3 0 drwxr-xr-x 34 jacquesmenu staff 1088 Nov 16 08:12:11 2021 ./
4 0 drwxr-xr-x 20 jacquesmenu staff 640 Nov 16 08:12:03 2021 ../
5 48 -rw-r--r--@ 1 jacquesmenu staff 23743 Nov 16 08:16:55 2021 basicOah2manPage.
   cpp
6 16 -rw-r--r--@ 1 jacquesmenu staff 5202 Nov 15 12:56:16 2021 basicOah2manPage.h
7 8 -rw-r--r--@ 1 jacquesmenu staff 539 Jun 6 06:38:55 2021
   enableHarmoniesExtraOahIfDesired.h
8 8 -rw-r--r--@ 1 jacquesmenu staff 526 Oct 11 11:56:29 2021
   enableTracingIfDesired.h
9 72 -rw-r--r--@ 1 jacquesmenu staff 34280 Nov 16 08:16:55 2021 harmoniesExtraOah.
   cpp
10 24 -rw-r--r--@ 1 jacquesmenu staff 11848 Nov 15 12:56:16 2021 harmoniesExtraOah.
   h
11 16 -rw-r--r--@ 1 jacquesmenu staff 5154 Nov 16 08:16:55 2021
   harmoniesExtraOah2manPage.cpp
12 8 -rw-r--r--@ 1 jacquesmenu staff 1689 Nov 15 12:56:16 2021
   harmoniesExtraOah2manPage.h
13 8 -rw-r--r--@ 1 jacquesmenu staff 918 Nov 16 08:16:55 2021 oah2manPage.cpp
14 8 -rw-r--r--@ 1 jacquesmenu staff 912 Nov 15 12:56:16 2021 oah2manPage.h
15 344 -rw-r--r--@ 1 jacquesmenu staff 175094 Nov 16 08:16:55 2021 oahAtomsCollection
   .cpp
16 176 -rw-r--r--@ 1 jacquesmenu staff 87460 Nov 15 12:56:16 2021 oahAtomsCollection
   .h
17 336 -rw-r--r--@ 1 jacquesmenu staff 168969 Nov 16 08:16:55 2021 oahBasicTypes.cpp
18 96 -rw-r--r--@ 1 jacquesmenu staff 47228 Nov 15 12:56:16 2021 oahBasicTypes.h
19 8 -rw-r--r--@ 1 jacquesmenu staff 3258 Nov 16 08:16:55 2021 oahBrowsers.h
20 32 -rw-r--r--@ 1 jacquesmenu staff 14030 Nov 16 08:16:55 2021 oahElements.cpp
21 24 -rw-r--r--@ 1 jacquesmenu staff 10381 Nov 15 12:56:16 2021 oahElements.h
22 8 -rw-r--r--@ 1 jacquesmenu staff 2577 Nov 16 08:16:55 2021 oahInsiderHandlers
   .cpp
23 8 -rw-r--r--@ 1 jacquesmenu staff 2982 Nov 15 12:56:16 2021 oahInsiderHandlers
   .h

```

```

24 56 -rw-r--r--@ 1 jacquesmenu staff 25901 Nov 16 08:16:55 2021 oah0ah.cpp
25 32 -rw-r--r--@ 1 jacquesmenu staff 13849 Nov 16 08:16:55 2021 oah0ah.h
26 8 -rw-r--r--@ 1 jacquesmenu staff 1966 Nov 16 08:16:55 2021 oah0ah2manPage.cpp
27 8 -rw-r--r--@ 1 jacquesmenu staff 1021 Nov 15 12:56:16 2021 oah0ah2manPage.h
28 24 -rw-r--r--@ 1 jacquesmenu staff 8831 Nov 16 08:16:55 2021 oahRegularHandlers
   .cpp
29 8 -rw-r--r--@ 1 jacquesmenu staff 3855 Nov 15 12:56:16 2021 oahRegularHandlers
   .h
30 8 -rw-r--r--@ 1 jacquesmenu staff 568 Nov 15 12:56:16 2021 oahVisitor.cpp
31 8 -rw-r--r--@ 1 jacquesmenu staff 894 Nov 15 12:56:16 2021 oahVisitor.h
32 16 -rw-r--r--@ 1 jacquesmenu staff 5978 Nov 16 08:16:55 2021 outputFile0ah.cpp
33 8 -rw-r--r--@ 1 jacquesmenu staff 3593 Nov 15 12:56:16 2021 outputFile0ah.h
34 8 -rwxr--r--@ 1 jacquesmenu staff 236 Oct 23 12:02:12 2021 zsh_test.zsh*

```

- `formatsgeneration` : support for various output kinds

- `brailleGeneration`
- `guidoGeneration`
- `lilypondGeneration`
- `msrGeneration`
- `multiGeneration`
- `mxsrGeneration`

- `passes` : code for the individual passes

- `bsr2braille`
- `bsr2bsr`
- `lpsr2lilypond`
- `msr2bsr`
- `msr2lpsr`
- `msr2msr`
- `msr2mxsr`
- `mxsr2guido`
- `mxsr2msr`
- `mxsr2musicxml`

- `formats` : the various internal representations used by `MusicFormats`

- `bsr`
- `lpsr`
- `msdl`
- `msdr`
- `msr`
- `msrapi`
- `mxsr`

- `wae` : multilingual Warnings And Errors support, including exceptions handling

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src > ll wae/
2 total 104
3  0 drwxr-xr-x   9 jacquesmenu  staff    288 Oct 15 20:23:46 2021 ./
4  0 drwxr-xr-x  20 jacquesmenu  staff    640 Nov 16 08:12:03 2021 ../
5  8 -rw-r--r--@   1 jacquesmenu  staff    680 Jun  6 06:35:19 2021
   enableAbortToDebugErrors.h
6  8 -rw-r--r--@   1 jacquesmenu  staff    602 Nov 15 12:56:18 2021 waeExceptions.cpp
7 24 -rw-r--r--@   1 jacquesmenu  staff  11514 Nov 15 12:56:18 2021 waeExceptions.h
8  8 -rw-r--r--@   1 jacquesmenu  staff   1393 Nov 16 08:16:55 2021 waeHandlers.cpp
9  8 -rw-r--r--@   1 jacquesmenu  staff   1550 Nov 15 12:56:18 2021 waeHandlers.h
10 32 -rw-r--r--@   1 jacquesmenu  staff  16317 Nov 15 12:56:18 2021 wae.cpp
11 16 -rw-r--r--@   1 jacquesmenu  staff   5794 Nov 15 12:56:18 2021 wae.h

```

4.5 The validation folder

This folder contains a `Makefile` to compile all the files in the `files` folder. `musicformatsversion.txt` contains a validation version number, without a priori relation to the actual version number of the library, for example:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/validation > cat musicformatsversion.txt
2 1.0.0

```

In this example, `make` will create a folder named `1.0.0` containing the converted files, including PDF files produced by `lilypond`.

This validation version number allows for comparisons between version to ease regression tests.

There is no `clean` target in the `Makefile`. Removing the `1.0.0` folder in this case does the equivalent, then we can run `make` again.

Chapter 5

Components

5.1 Components terminology

In compiler writing terminology:

- an external format
- an internal representation is a data structure representing the program being compiled;
- there are often several internal representations, to simplify the compiler internal workings or for optimisation purposes;
- the output of the compiler, such as binary code for some physical or emulated processor, is a last 'representation' of the program;
- a pass converts an internal representation into another one, in a single step;
- a multi-pass converter is a chain of passes, reading the input, converting it into a first internal representation, then a pass to convert it into another internal representation, and so on until the compiler output is produced.

MusicFormats maps exactly to this model, providing the following components:

- internal representations (formats for short) of the music score: MSR, LSPR, BSR and MXSR;
- several passes are available to convert such formats into others;
- a set of multi-pass converters are supplied, such as `xml2lily` `xml2xml` and MSDL converter.

In the MusicFormats user documentation, the term 'converter' is used because it is more meaningful for musicians.

MusicFormats provides high-level interfaces to its components as functions in **Interface** files:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src > look Interface
2 ./formats/msr/msrInterface.cpp
3 ./formats/msr/msrInterface.h
4 ./formats/lpsr/lpsrInterface.cpp
5 ./formats/lpsr/lpsrInterface.h
6 ./formats/bsr/bsrInterface.cpp
7 ./formats/bsr/bsrInterface.h
8 ./passes/mxsr2musicxml/mxsr2musicxmlTranlatorInterface.h
9 ./passes/mxsr2musicxml/mxsr2musicxmlTranlatorInterface.cpp
10 ./passes/bsr2bsr/bsr2bsrFinalizerInterface.h
11 ./passes/bsr2bsr/bsr2bsrFinalizerInterface.cpp
12 ./passes/msr2mxsr/msr2mxsrInterface.cpp
13 ./passes/msr2mxsr/msr2mxsrInterface.h
14 ./passes/mxsr2msr/mxsr2msrSkeletonBuilderInterface.h
15 ./passes/mxsr2msr/mxsr2msrTranslatorInterface.cpp
16 ./passes/mxsr2msr/mxsr2msrTranslatorInterface.h
17 ./passes/mxsr2msr/mxsr2msrSkeletonBuilderInterface.cpp
18 ./passes/msr2msr/msr2msrInterface.h
19 ./passes/msr2msr/msr2msrInterface.cpp
20 ./passes/lpsr2lilypond/lpsr2lilypondInterface.h
21 ./passes/lpsr2lilypond/lpsr2lilypondInterface.cpp
22 ./passes/msr2lpsr/msr2lpsrInterface.cpp
23 ./passes/msr2lpsr/msr2lpsrInterface.h
24 ./passes/bsr2braille/bsr2brailleTranslatorInterface.h
25 ./passes/bsr2braille/bsr2brailleTranslatorInterface.cpp
26 ./passes/msr2bsr/msr2bsrInterface.h
27 ./passes/msr2bsr/msr2bsrInterface.cpp
28 ./passes/musicxml2mxsr/musicxml2mxsrInterface.h
29 ./passes/musicxml2mxsr/musicxml2mxsrInterface.cpp
30 ./passes/mxsr2guido/mxsr2guidoTranlatorInterface.h
31 ./passes/mxsr2guido/mxsr2guidoTranlatorInterface.cpp
32 ./converters/msr2guido/msr2guidoInterface.h
33 ./converters/msr2guido/msr2guidoInterface.cpp
34 ./converters/msr2braille/msr2brailleInterface.h
35 ./converters/msr2braille/msr2brailleInterface.cpp
36 ./converters/msdl2braille/msdl2brailleInterface.h
37 ./converters/msdl2braille/msdl2brailleInterface.cpp
38 ./converters/msdl2guido/msdl2guidoInterface.cpp
39 ./converters/msdl2guido/msdl2guidoInterface.h
40 ./converters/msdl2musicxml/msdl2musicxmlInterface.h
41 ./converters/msdl2musicxml/msdl2musicxmlInterface.cpp
42 ./converters/msdl2lilypond/msdl2lilypondInterface.h
43 ./converters/msdl2lilypond/msdl2lilypondInterface.cpp
44 ./converters/musicxml2braille/musicxml2brailleInterface.cpp
45 ./converters/musicxml2braille/musicxml2brailleInterface.h
46 ./converters/msr2lilypond/msr2lilypondInterface.cpp
47 ./converters/msr2lilypond/msr2lilypondInterface.h
48 ./converters/msr2musicxml/msr2musicxmlInterface.cpp
49 ./converters/msr2musicxml/msr2musicxmlInterface.h
50 ./converters/musicxml2musicxml/musicxml2musicxmlInterface.h
51 ./converters/musicxml2musicxml/musicxml2musicxmlInterface.cpp
52 ./converters/musicxml2lilypond/musicxml2lilypondInterface.h
53 ./converters/musicxml2lilypond/musicxml2lilypondInterface.cpp
54 ./converters/musicxml2guido/musicxml2guidoInterface.cpp
55 ./converters/musicxml2guido/musicxml2guidoInterface.h

```

The converters are implemented as functions as well as CLI tools that use the latter.

MusicFormats includes support for components versions numbering and history, see chapter ?? [MusicFormats components], page ??.

`src/components/mfcComponents.h` includes all the components's header files.

5.2 Formats

The formats are in `src/formats`:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src > ll formats/
2 total 32
3 0 drwxr-xr-x 10 jacquesmenu staff 320 Jun 25 05:39:49 2021 ./
4 0 drwxr-xr-x 13 jacquesmenu staff 416 Jun 17 17:16:37 2021 ../
5 24 -rw-r--r-- 1 jacquesmenu staff 10244 Jun 19 07:58:55 2021 .DS_Store
6 0 drwxr-xr-x 60 jacquesmenu staff 1920 Jun 18 07:32:14 2021 bsr/
7 0 drwxr-xr-x 42 jacquesmenu staff 1344 May 26 08:20:55 2021 lpsr/
8 0 drwxr-xr-x 12 jacquesmenu staff 384 Apr 22 15:49:23 2021 msdl/
9 0 drwxr-xr-x 10 jacquesmenu staff 320 May 26 08:20:55 2021 msdr/
10 0 drwxr-xr-x 151 jacquesmenu staff 4832 Jun 20 09:58:00 2021 msr/
11 0 drwxr-xr-x 6 jacquesmenu staff 192 May 26 08:20:55 2021 mxsr/

```

The formats interfaces are in files with the format's name:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src > ll formats/bsr/bsr.*
2 8 -rw-r--r--@ 1 jacquesmenu staff 700 Jun 6 06:35:19 2021 formats/bsr/bsr.cpp
3 8 -rw-r--r--@ 1 jacquesmenu staff 1206 Jun 18 10:04:45 2021 formats/bsr/bsr.h
4
5 jacquesmenu@macmini: ~/musicformats-git-dev/src > ll formats/lpsr/lpsr.*
6 8 -rw-r--r--@ 1 jacquesmenu staff 703 Jun 6 06:35:19 2021 formats/lpsr/lpsr.cpp
7 8 -rw-r--r--@ 1 jacquesmenu staff 1004 Jun 6 06:35:19 2021 formats/lpsr/lpsr.h
8
9 jacquesmenu@macmini: ~/musicformats-git-dev/src > ll formats/msdl/msdl.*
10 8 -rw-r--r--@ 1 jacquesmenu staff 736 Jun 6 06:35:19 2021 formats/msdl/msdl.cpp
11 8 -rw-r--r--@ 1 jacquesmenu staff 643 Jun 6 06:35:19 2021 formats/msdl/msdl.h
12
13 jacquesmenu@macmini: ~/musicformats-git-dev/src > ll formats/msdr/msdr.*
14 8 -rw-r--r--@ 1 jacquesmenu staff 709 Jun 6 06:35:19 2021 formats/msdr/msdr.cpp
15 8 -rw-r--r--@ 1 jacquesmenu staff 531 Jun 6 06:35:19 2021 formats/msdr/msdr.h
16
17 jacquesmenu@macmini: ~/musicformats-git-dev/src > ll formats/msr/msr.*
18 8 -rw-r--r--@ 1 jacquesmenu staff 700 Jun 6 06:35:19 2021 formats/msr/msr.cpp
19 8 -rw-r--r--@ 1 jacquesmenu staff 2410 Jun 20 09:58:38 2021 formats/msr/msr.h
20
21 jacquesmenu@macmini: ~/musicformats-git-dev/src > ll formats/mxsr/mxsr.*
22 8 -rw-r--r--@ 1 jacquesmenu staff 3292 Jun 6 06:35:19 2021 formats/mxsr/mxsr.cpp
23 8 -rw-r--r--@ 1 jacquesmenu staff 1555 Jun 6 06:35:19 2021 formats/mxsr/mxsrGeneration.
   h

```

5.3 Representations

The representations are in `src/representations`:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src > ll representations/
2 total 24
3 0 drwxr-xr-x 11 jacquesmenu staff 352 Dec 30 17:25:10 2021 ./
4 0 drwxr-xr-x 18 jacquesmenu staff 576 Jan 16 16:50:25 2022 ../
5 24 -rw-r--r--@ 1 jacquesmenu staff 10244 Jan 6 17:40:44 2022 .DS_Store
6 0 drwxr-xr-x 8 jacquesmenu staff 256 Dec 30 10:26:26 2021 braille/
7 0 drwxr-xr-x 69 jacquesmenu staff 2208 Jan 4 07:52:14 2022 bsr/
8 0 drwxr-xr-x 4 jacquesmenu staff 128 Dec 30 10:27:01 2021 guido/
9 0 drwxr-xr-x 51 jacquesmenu staff 1632 Jan 4 07:52:36 2022 lpsr/
10 0 drwxr-xr-x 16 jacquesmenu staff 512 Jan 4 07:52:55 2022 msdl/
11 0 drwxr-xr-x 12 jacquesmenu staff 384 Jan 4 07:53:13 2022 msdr/
12 0 drwxr-xr-x 165 jacquesmenu staff 5280 Jan 4 07:53:34 2022 msr/
13 0 drwxr-xr-x 10 jacquesmenu staff 320 Jan 4 07:53:54 2022 mxsr/

```

5.4 Passes

The passes are in `src/passes`:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src > ll passes
2 total 24
3  0 drwxr-xr-x  14 jacquesmenu  staff    448 Nov  24  16:29:20 2021 ./
4  0 drwxr-xr-x  20 jacquesmenu  staff    640 Nov  16  08:12:03 2021 ../
5 24 -rw-r--r--@  1 jacquesmenu  staff  10244 Nov  24  10:38:11 2021 .DS_Store
6  0 drwxr-xr-x   8 jacquesmenu  staff    256 Oct  22  07:19:11 2021 bsr2braille/
7  0 drwxr-xr-x   6 jacquesmenu  staff    192 Oct  22  07:20:34 2021 bsr2bsr/
8  0 drwxr-xr-x  10 jacquesmenu  staff    320 Nov  16  10:09:27 2021 lpsr2lilypond/
9  0 drwxr-xr-x  14 jacquesmenu  staff    448 Oct  22  07:22:09 2021 msdl2msr/
10 0 drwxr-xr-x   8 jacquesmenu  staff    256 Oct  22  07:24:35 2021 msr2bsr/
11 0 drwxr-xr-x   8 jacquesmenu  staff    256 Nov   1  16:31:34 2021 msr2lpsr/
12 0 drwxr-xr-x   8 jacquesmenu  staff    256 Nov   1  16:31:34 2021 msr2msr/
13 0 drwxr-xr-x   6 jacquesmenu  staff    192 Oct  22  07:27:46 2021 msr2mxsr/
14 0 drwxr-xr-x   4 jacquesmenu  staff    128 Oct  22  07:28:37 2021 mxsr2guido/
15 0 drwxr-xr-x  10 jacquesmenu  staff    320 Nov   1  16:31:34 2021 mxsr2msr/
16 0 drwxr-xr-x   4 jacquesmenu  staff    128 Oct  22  07:29:50 2021 mxsr2musicxml/

```

Some passes are named translators (converters could have been used), and others are not. In `src/passes/mxsr2msr/`, class `mxsr2msrSkeletonBuilder` does not translate MusicXML data to another full representation: it merely creates a skeleton containing voices, are are empty:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src > ll passes/mxsr2msr/
2 total 1808
3  0 drwxr-xr-x   8 jacquesmenu  staff    256 Jun  25  05:47:41 2021 ./
4  0 drwxr-xr-x  16 jacquesmenu  staff    512 May  26  08:20:55 2021 ../
5 96 -rw-r--r--@  1 jacquesmenu  staff  48389 Jun  21  07:43:20 2021 mxsr2msr0ah.cpp
6 40 -rw-r--r--@  1 jacquesmenu  staff  20327 Jun  16  10:41:37 2021 mxsr2msr0ah.h
7 192 -rw-r--r--@  1 jacquesmenu  staff  97896 Jun  25  08:58:38 2021
   mxsr2msrSkeletonBuilder.cpp
8 48 -rw-r--r--@  1 jacquesmenu  staff  20942 Jun  25  07:36:29 2021
   mxsr2msrSkeletonBuilder.h
9 1280 -rw-r--r--@  1 jacquesmenu  staff 651474 Jun  25  07:49:52 2021 mxsr2msrTranslator.cpp
10 152 -rw-r--r--@  1 jacquesmenu  staff  77039 Jun  21  07:43:20 2021 mxsr2msrTranslator.h

```

The passes functionality is available as functions in `*Interface.*`:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src > look Interface
2 ./representations/msr/msrInterface.cpp
3 ./representations/msr/msrInterface.h
4 ./representations/lpsr/lpsrInterface.cpp
5 ./representations/lpsr/lpsrInterface.h
6 ./representations/bsr/bsrInterface.h
7 ./representations/bsr/bsrInterface.cpp
8 ./passes/mxsr2musicxml/mxsr2musicxmlTranlatorInterface.h
9 ./passes/mxsr2musicxml/mxsr2musicxmlTranlatorInterface.cpp
10 ./passes/bsr2bsr/bsr2bsrFinalizerInterface.h
11 ./passes/bsr2bsr/bsr2bsrFinalizerInterface.cpp
12 ./passes/msr2mxsr/msr2mxsrInterface.cpp
13 ./passes/msr2mxsr/msr2mxsrInterface.h
14 ./passes/mxsr2msr/mxsr2msrSkeletonBuilderInterface.h
15 ./passes/mxsr2msr/mxsr2msrTranslatorInterface.cpp
16 ./passes/mxsr2msr/mxsr2msrTranslatorInterface.h
17 ./passes/mxsr2msr/mxsr2msrSkeletonBuilderInterface.cpp
18 ./passes/msr2msr/msr2msrInterface.h
19 ./passes/msr2msr/msr2msrInterface.cpp
20 ./passes/lpsr2lilypond/lpsr2lilypondInterface.h
21 ./passes/lpsr2lilypond/lpsr2lilypondInterface.cpp
22 ./passes/msr2lpsr/msr2lpsrInterface.cpp
23 ./passes/msr2lpsr/msr2lpsrInterface.h
24 ./passes/bsr2braille/bsr2brailleTranslatorInterface.h
25 ./passes/bsr2braille/bsr2brailleTranslatorInterface.cpp

```



```

26 ./passes/msr2bsr/msr2bsrInterface.h
27 ./passes/msr2bsr/msr2bsrInterface.cpp
28 ./passes/musicxml2mxsr/musicxml2mxsrInterface.h
29 ./passes/musicxml2mxsr/musicxml2mxsrInterface.cpp
30 ./passes/mxsr2guido/mxsr2guidoTranlatorInterface.h
31 ./passes/mxsr2guido/mxsr2guidoTranlatorInterface.cpp
32 ./converters/msr2guido/msr2guidoInterface.h
33 ./converters/msr2guido/msr2guidoInterface.cpp
34 ./converters/msr2braille/msr2brailleInterface.h
35 ./converters/msr2braille/msr2brailleInterface.cpp
36 ./converters/msdl2braille/msdl2brailleInterface.h
37 ./converters/msdl2braille/msdl2brailleInterface.cpp
38 ./converters/msdl2guido/msdl2guidoInterface.cpp
39 ./converters/msdl2guido/msdl2guidoInterface.h
40 ./converters/msdl2musicxml/msdl2musicxmlInterface.h
41 ./converters/msdl2musicxml/msdl2musicxmlInterface.cpp
42 ./converters/msdl2lilypond/msdl2lilypondInterface.h
43 ./converters/msdl2lilypond/msdl2lilypondInterface.cpp
44 ./converters/musicxml2braille/musicxml2brailleInterface.cpp
45 ./converters/musicxml2braille/musicxml2brailleInterface.h
46 ./converters/msr2lilypond/msr2lilypondInterface.cpp
47 ./converters/msr2lilypond/msr2lilypondInterface.h
48 ./converters/msr2musicxml/msr2musicxmlInterface.cpp
49 ./converters/msr2musicxml/msr2musicxmlInterface.h
50 ./converters/musicxml2musicxml/musicxml2musicxmlInterface.h
51 ./converters/musicxml2musicxml/musicxml2musicxmlInterface.cpp
52 ./converters/musicxml2lilypond/musicxml2lilypondInterface.h
53 ./converters/musicxml2lilypond/musicxml2lilypondInterface.cpp
54 ./converters/musicxml2guido/musicxml2guidoInterface.cpp
55 ./converters/musicxml2guido/musicxml2guidoInterface.h

```

5.5 Generators

A generator is a multi-pass command line tool that creates an output from scratch, without reading anything. All of them use `src/formatsgeneration/multiGeneration/multiGeneration.h/.cpp` to offer a set of output formats:

- `src/clisamples/Mikrokosmos3Wandering.cpp`
creates a score for this Bartok piece in various forms, depending on the options. It has been used to check the MSR API's:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src > ll formatsgeneration/
  multiGeneration/
2 total 56
3  0 drwxr-xr-x  4 jacquesmenu  staff    128 Apr 22 15:49:16 2021 ./
4  0 drwxr-xr-x 10 jacquesmenu  staff    320 May 26 08:20:55 2021 ../
5 40 -rw-r--r--@ 1 jacquesmenu  staff  16774 Jun  6 06:38:55 2021 multiGeneration0ah.
   cpp
6 16 -rw-r--r--@ 1 jacquesmenu  staff   6750 Jun  6 06:38:55 2021 mfMultiGeneration0ah
   .h

```

For example:

```

1 jacquesmenu@macmini: ~ > Mikrokosmos3Wandering -lilypond -a
2 What LilyPondIssue34 does:
3
4 This multi-pass generator creates a textual representation
5 of the LilyPondIssue34 score.
6 It basically performs 4 passes when generating LilyPond output output:
7
8 Pass 1: generate a first MSR for the LilyPondIssue34 score
9 Pass 2: converts the first MSR a second MSR;

```

```

10      Pass 3:  converts the second MSR into a
11              LilyPond Score Representation (LPSR);
12      Pass 4:  converts the LPSR to LilyPond code
13              and writes it to standard output.
14
15      Other passes are performed according to the options, such as
16      displaying views of the internal data or printing a summary of the score.
17
18      The activity log and warning/error messages go to standard error.

```

- `src/clisamples/LilyPondIssue34.cpp` creates a score for the LilyPond issue #34 issue, also in various forms;

```

1 jacquesmenu@macmini: ~ > LilyPondIssue34 -musicxml -a
2 What LilyPondIssue34 does:
3
4      This multi-pass generator creates a textual representation
5      of the LilyPondIssue34 score.
6      It basically performs 4 passes when generating MusicXML output output:
7
8      Pass 1:  generate a first MSR for the LilyPondIssue34 score
9      Pass 2:  converts the first MSR a second MSR, to apply options;
10     Pass 3:  converts the second MSR into an MusicXML tree;
11     Pass 4:  converts the MusicXML tree to MusicXML code
12             and writes it to standard output.
13
14     Other passes are performed according to the options, such as
15     displaying views of the internal data or printing a summary of the score.
16
17     The activity log and warning/error messages go to standard error.

```

5.6 Converters

The MusicFormats converters chain passes into a sequence, each pass reading the input or the format produced by the preceeding one:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src > ll converters/
2 total 32
3 0 drwxr-xr-x 17 jacquesmenu staff 544 May 26 08:20:55 2021 ./
4 0 drwxr-xr-x 13 jacquesmenu staff 416 Jun 17 17:16:37 2021 ../
5 24 -rw-r--r-- 1 jacquesmenu staff 10244 Jun 18 10:34:45 2021 .DS_Store
6 0 drwxr-xr-x 8 jacquesmenu staff 256 May 26 08:20:55 2021 msdl2braille/
7 0 drwxr-xr-x 8 jacquesmenu staff 256 May 26 08:20:55 2021 msdl2guido/
8 0 drwxr-xr-x 8 jacquesmenu staff 256 May 26 08:20:55 2021 msdl2lilypond/
9 0 drwxr-xr-x 8 jacquesmenu staff 256 May 26 08:20:55 2021 msdl2musicxml/
10 0 drwxr-xr-x 8 jacquesmenu staff 256 May 26 08:20:55 2021 msdlconverter/
11 0 drwxr-xr-x 8 jacquesmenu staff 256 May 26 08:20:55 2021 msr2braille/
12 0 drwxr-xr-x 8 jacquesmenu staff 256 May 26 08:20:55 2021 msr2guido/
13 0 drwxr-xr-x 8 jacquesmenu staff 256 May 26 08:20:55 2021 msr2lilypond/
14 0 drwxr-xr-x 8 jacquesmenu staff 256 May 26 08:20:55 2021 msr2musicxml/
15 0 drwxr-xr-x 4 jacquesmenu staff 128 May 26 08:20:55 2021 musicxml2braille/
16 0 drwxr-xr-x 4 jacquesmenu staff 128 May 26 08:20:55 2021 musicxml2guido/
17 0 drwxr-xr-x 4 jacquesmenu staff 128 May 26 08:20:55 2021 musicxml2lilypond/
18 0 drwxr-xr-x 4 jacquesmenu staff 128 May 26 08:20:55 2021 musicxml2musicxml/

```

5.7 Running a service

When a MusicFormats service is *run* from the command line or through an API function, an instance of class `mfServiceRunData` is created.

This class is defined in `src/mflibrary/mfServiceRunData.h/.cpp` to hold data specific to the run. They are global data, but don't belong to the regular, invariant data contained in the library, such as the notes pitches in various languages:

```

1 class EXP mfServiceRunData : public smartable
2 {
3     public:
4
5         // creation
6         // -----
7
8         static SMARTP<mfServiceRunData> create (const string& serviceName);
9
10        static SMARTP<mfServiceRunData> create (
11            const string& serviceName,
12            int          argc,
13            char*        argv[]);
14
15        static SMARTP<mfServiceRunData> create (
16            const string&          serviceName,
17            mfOptionsAndArguments& optionsAndArguments);
18
19    public:
20
21        // constructors/destructor
22        // -----
23
24        mfServiceRunData (const string& serviceName);
25
26        mfServiceRunData (
27            const string& serviceName,
28            int          argc,
29            char*        argv[]);
30
31        mfServiceRunData (
32            const string&          serviceName,
33            mfOptionsAndArguments& optionsAndArguments);
34
35        virtual ~mfServiceRunData ();
36
37        // .. .. .
38
39    private:
40
41        // private fields
42        // -----
43
44        // service name
45        string          fServiceName;
46
47        // conversion date
48        string          fRunDateFull;
49        string          fRunDateYYYYMMDD;
50
51        // conversion command
52        string          fCommandAsSupplied;
53
54        string          fCommandWithLongOptionsNames;
55        string          fCommandWithShortOptionsNames;
56
57        // options and arguments
58        mfOptionsAndArguments
59            fOptionsAndArguments;
60
61        // command line
62        string          fCommandLineAsSupplied;
63

```

```

64 // input source
65 string          fInputSourceName;
66 };

```

The various constructors are used depending on the way the service is run.

For example, if is created this way in `src/clisamples/xml2ly.cpp`:

```

1 int main (int argc, char* argv[])
2 {
3     // setup signals catching
4     // -----
5
6     // JMI catchSignals ();
7
8     // the service name
9     // -----
10
11     string serviceName = argv [0];
12
13     // create the global output and log indented streams
14     // -----
15
16     createTheGlobalIndentedOstreams (cout, cerr);
17
18     // create the global run data
19     // -----
20
21     gGlobalServiceRunData =
22         mfServiceRunData::create (serviceName);
23
24     // ... ..
25 }

```

Then the various run data can be accessed easily:

```

1 string
2     inputSourceName =
3     gGlobalServiceRunData->getInputSourceName ();

```

The run data is used for example in class `lpsrScore`, defined in `src/formats/lpsr//lpsrScores.h/.cpp`:

```

1 lpsrScore::lpsrScore (
2     int          inputLineNumber,
3     S_msrScore   theMsrScore,
4     S_mfcMultiComponent multiComponent)
5     : lpsrElement (inputLineNumber)
6 {
7     // ...
8
9     fMultiComponent = multiComponent;
10
11     // should the initial comments about the service and the options used
12     // be generated?
13     if (gGlobalLpsr2lilypondOahGroup->getXml2lyInfos ()) {
14         // create the 'generated by' comment
15         {
16             stringstream s;
17
18             s <<
19                 "Generated by " <<
20                 gGlobalOahOahGroup->getOahOahGroupServiceName () <<
21                 ' ' <<
22                 getGlobalMusicFormatsVersionNumberAndDate () <<
23                 endl <<
24

```

```
25     "% on " <<
26     gGlobalServiceRunData->getRunDateFull () <<
27     endl <<
28
29     "% from ";
30
31     string inputSourceName =
32         gGlobalServiceRunData->getInputSourceName ();
33
34     if (inputSourceName == "-") {
35         s << "standard input";
36     }
37     else {
38         s << "\"" << inputSourceName << "\"";
39     }
40
41     fInputSourceNameComment =
42         lpsrComment::create (
43             inputLineNumber,
44             s.str (),
45             lpsrComment::kGapAfterwardsYes);
46 }
47 }
48
49 // ...
50 }
```

Chapter 6

Command line samples

The `src/clisamples` folder contains example of the use of MusicFormats in CLI tools. They are out of the library proper, and built with a specific Makefile:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev > ll samples/
2 total 320
3 0 drwxr-xr-x 16 jacquesmenu staff 512 Jun 29 09:59:07 2021 ./
4 0 drwxr-xr-x 28 jacquesmenu staff 896 Jul 1 05:37:35 2021 ../
5 16 -rw-r--r-- 1 jacquesmenu staff 6148 May 26 08:20:55 2021 .DS_Store
6 8 -rw-r--r-- 1 jacquesmenu staff 116 Apr 22 15:49:06 2021 .gitignore
7 40 -rw-r--r--@ 1 jacquesmenu staff 18344 Jun 29 11:05:18 2021 LilyPondIssue34.cpp
8 8 -rw-r--r--@ 1 jacquesmenu staff 2101 Jun 29 10:00:56 2021 Makefile
9 40 -rw-r--r--@ 1 jacquesmenu staff 18362 Jun 29 11:05:10 2021 Mikrokosmos3Wandering.cpp
10 24 -rw-r--r--@ 1 jacquesmenu staff 10017 May 31 11:12:12 2021 MusicAndHarmonies.cpp
11 8 -rw-r--r--@ 1 jacquesmenu staff 3117 May 31 11:17:27 2021 libMultipleInitsTest.cpp
12 48 -rw-r--r--@ 1 jacquesmenu staff 21459 Jun 29 11:05:02 2021 msdlconverter.cpp
13 8 -rw-r--r--@ 1 jacquesmenu staff 898 May 31 11:15:59 2021 musicformatsversion.cpp
14 24 -rw-r--r--@ 1 jacquesmenu staff 8642 Jun 28 07:42:57 2021 xml2Any.cpp
15 24 -rw-r--r--@ 1 jacquesmenu staff 10085 Jul 1 06:22:13 2021 xml2brl.cpp
16 24 -rw-r--r--@ 1 jacquesmenu staff 10519 Jul 1 06:22:50 2021 xml2gmn.cpp
17 24 -rw-r--r--@ 1 jacquesmenu staff 10320 Jul 1 00:09:51 2021 xml2ly.cpp
18 24 -rw-r--r--@ 1 jacquesmenu staff 10473 Jul 1 06:21:10 2021 xml2xml.cpp
```

All the `*.cpp` files contain a `main ()` function using the interfaces for their purpose. Among them:

- `libMultipleInitsTest.cpp` is a maintenance tool to check that the MusicFormats library is not initialized more than once;
- `MusicAndHarmonies.cpp` creates a score at random with harmonies in it;
- `Mikrokosmos3Wandering.cpp` and `LilyPondIssue34.cpp` are generators;
- `xml2Any.cpp` uses the `oahOptionsVector` way to supply arguments instead of `arg/argv`;
- `xml2ly`, `xml2brl`, `xml2xml` and `xml2gmn` are converters from MusicXML to other formats;
- `msdlconverter.cpp` is the MSDL converter.

Chapter 7

Warning and errors (WAE)

Warning and errors in MusicFormats are handled with a set of functions defined in the `wae` folder.

Class `mfException` and context-specific exceptions are defined in `src/wae/waeExceptions`, such as:

```
1 // -----  
2 class EXP mf0ahException: public mfException  
3 {  
4     public:  
5         mf0ahException (string const& exceptionDescription) throw ()  
6             : mfException (exceptionDescription)  
7         {}  
8 };  
9 typedef SMARTP<mf0ahException> S_mf0ahException;
```

A typical use of exceptions in `src/passes/lpsr2lilypond/lpsr2lilypondInterface.cpp` is:

```
1 // convert the LPSR score to LilyPond code  
2 try {  
3     translateLpsrToLilypond (  
4         theLpsrScore,  
5         gGlobalMsr0ahGroup,  
6         gGlobalLpsr0ahGroup,  
7         passNumber,  
8         passDescription,  
9         lilypondStandardOutputStream);  
10 }  
11 catch (lpsr2lilypondException& e) {  
12     mfDisplayException (e, gOutputStream);  
13     return;  
14 }  
15 catch (std::exception& e) {  
16     mfDisplayException (e, gOutputStream);  
17     return;  
18 }
```

One finds in `src/wae/enableAbortToDebugErrors.h` the `ABORT_TO_DEBUG_ERRORS` macro to help debugging the code base:

```
1 // comment the following definition if abort on internal errors is desired  
2 // CAUTION: DON'T USE THIS IN PRODUCTION CODE,  
3 // since that could kill a session on a \Web\ server, for example  
4  
5 #ifndef ABORT_TO_DEBUG_ERRORS  
6     #define ABORT_TO_DEBUG_ERRORS  
7 #endif
```

Chapter 8

The trace facility

MusicFormats is instrumented with an optionnal, full-fledged trace facility, with numerous options to display what is going on when using the library. One can build the library with or without trace, which applies to the whole code base.

8.1 Activating the trace

Tracing is controlled by `TRACING_IS_ENABLED`, defined or nor in `src/oah/enableTracingIfDesired.h`:

```
1 #ifndef __enableTracingIfDesired__
2 #define __enableTracingIfDesired__
3
4 #ifndef TRACING_IS_ENABLED
5     // comment the following definition if no tracing is desired
6     #define TRACING_IS_ENABLED
7 #endif
8
9 #endif
```

This file should be included when the trace facility is used:

```
1 #include "enableTracingIfDesired.h"
2 #ifdef TRACING_IS_ENABLED
3     #include "tracingOah.h"
4 #endif
```

The files `src/oah/tracingOah.h/.cpp` contain the options to the trace facility itself.

Be sure to build MusicFormats with `TRACING_IS_ENABLED` both active and commented out before creating a new `v*` version branch, to check that variables scopes are fine.

For example, `xml2ly -insider -help-tracexml2lyoption -insider` produces:

```
1 menu@macbookprojm > xml2ly -insider -help-trace
2 --- Help for group "OAH Trace" ---
3 OAH Trace (-ht, -help-trace) (use this option to show this group)
4     There are trace options transversal to the successive passes,
5     showing what's going on in the various translation activities.
6     They're provided as a help for the maintenance of MusicFormats,
7     as well as for the curious.
8     The options in this group can be quite verbose, use them with small input data!
9     All of them imply '-trace-passes, -tpasses'.
10 -----
11 Options handling trace      (-htoh, -help-trace-options-handling):
12     -toah, -trace-oah
```



```

13         Write a trace of options and help handling to standard error.
14     -toahd, -trace-oah-details
15         Write a trace of options and help handling with more details to standard error
16     .
17     Score to voices          (-htstv, -help-trace-score-to-voices):
18     -t<SHORT_NAME>, -trace-<LONG_NAME>
19         Trace SHORT_NAME/LONG_NAME in books to voices.
20     The 10 known SHORT_NAMES are:
21         book, scores, pgroups, pgroupsd, parts, staves, st, schanges,
22     .
23     The 10 known LONG_NAMES are:
24         -books, -scores, -part-groups, -part-groups-details,
25         -parts, -staves, -staff-details, -staff-changes, -voices and
26         -voices-details.
27     ... ..

```

8.2 Trace categories

8.3 Using traces in practise

In `src/passes/lpsr2lilypond/lpsr2lilypondTranslator.cpp`, the trace for the generation of LilyPond code for a regular note in a measure is produced by:

```

1 void lpsr2lilypondTranslator::generateCodeForNoteRegularInMeasure (
2     S_msrNote note)
3 {
4     int inputLineNumber =
5         note->getInputLineNumber ();
6
7     #ifdef TRACING_IS_ENABLED
8         if (gGlobalTracingOahGroup->getTraceNotes ()) {
9             stringstream s;
10
11             s <<
12                 endl <<
13                 "% --> generating code for noteRegularInMeasure " <<
14                 note->asString () <<
15                 ", line " << inputLineNumber <<
16                 endl;
17
18             gLogStream          << s.str ();
19             fLilypondCodeStream << s.str ();
20         }
21     #endif

```

8.4 Debugging traces handling

If case there is a null pointer in a case such as:

```

1 gGlobalMsrOahGroup->getUseFilenameAsWorkTitle ()

```

the way to go is to:

- locate `gGlobalMxsr2msrOahGroup` in the `*.h` it is declared in;
- check that the creation method in the same, such as `createGlobalMxsr2msrOahGroup ()`, is called in the `*InsiderHandler.cpp` file for the tool that crashed, which may require including that `.h` header in `InsiderHandler.cpp`.

Chapter 9

Multi-lingual support

MusicFormats supports multiple languages in various areas:

- note pitches names in MSR, LPSR and generated LilyPond code;
- LilyPond chord names;
- reserved keywords in MSDL.

Chapter 10

Textual input and output

10.1 Indented output streams

To meet the need of indented output to produce , we got inspiration from <https://stackoverflow.com/questions/2212776/overload-handling-of-stdendl>.

This leads to class `mfIndentedOstream`, defined in `src/utilities/mfIndentedTextOutput.h/.cpp`:

```
1 class EXP mfIndentedOstream: public ostream, public smartable
```

The key to this lies in the overloaded method `mfIndentedStreamBuf::sync ()`:

```
1 // -----
2 int mfIndentedStreamBuf::sync ()
3 {
4     // When we sync the stream with fOutputStream:
5     // 1) output the indentation then the buffer
6     // 2) reset the buffer
7     // 3) flush the actual output stream we are using.
8
9     unsigned int strSize = str ().size ();
10
11     // fetch the last non-space character in the buffer
12     // caution: the '\n' is present as the last character!
13     size_t found = str ().find_last_not_of ( ' ', strSize - 2);
14
15     // this can be uncommented to see low level informations
16     // fOutputStream << "% strSize: " << strSize << ", found: " << found << '\n';
17
18     // output the indenter
19     fOutputStream << fOutputIndenter;
20
21     // output the buffer
22     if (found == strSize - 3) {
23         // don't output the trailing spaces, but output the end of line
24         fOutputStream << str ().substr (0, found + 1) << '\n';
25     }
26     else {
27         // output the whole buffer
28         fOutputStream << str ();
29     }
30
31     // reset the buffer
32     str ("");
33
34     // flush the output stream
35     fOutputStream.flush ();
36
```

```

37     return 0;
38 }

```

Such indented output streams are used for nearly all of the output produced by MusicFormats, except for Braille which follows its own rules for indentation of cell lines.

10.2 Creating indented output streams

Such indented output streams are passed by reference to various methods which only know of `ostream`, among them:

```

1 void print (ostream& os) const override;

```

All those methods manipulate `mfIndentedOstream` instances seamlessly, not knowing their actual type. This is needed for the use of MusicFormats by applications through the API and not as a service. In particular, Web sites also know only of regular output streams.

So when and where are `mfIndentedOstream` instances created?

Functions `translateLpsrToLilypondWithHandler ()`, in `src/passes/lpsr2lilypond/lpsr2lilypondInterface`, creates one depending on whether it writes the LilyPond code to standard output or to a file.

The parameters to this function are:

```

1 EXP void translateLpsrToLilypondWithHandler (
2     const S_lpsrScore theLpsrScore,
3     S_msrOahGroup      msrOpts,
4     S_lpsrOahGroup      lpsrOpts,
5     const string&       passNumber,
6     const string&       passDescription,
7     S_oahHandler        handler,
8     ostream&            out,
9     ostream&            err)

```

In order to have a global current indentation, MusicFormats uses global variable `gIndenter`, because it should otherwise be passed over to many methods throughout the code base. It is defined in `src/mfutilities/mfIndentedOstream`.

```

1 #define gIndenter mfOutputIndenter::gGlobalOStreamIndenter

```

When writing to standard output, the indented output stream is constructed above the caller-supplied `out`:

```

1 // create an indented output stream for the LilyPond code
2 // to be written to outputFileStream
3 mfIndentedOstream
4     lilypondStandardOutputStream (
5         out,
6         gIndenter);
7
8 // convert the LPSR score to LilyPond code
9 try {
10     translateLpsrToLilypond (
11         theLpsrScore,
12         gGlobalMsrOahGroup,
13         gGlobalLpsrOahGroup,
14         passNumber,
15         passDescription,
16         lilypondStandardOutputStream);
17 }

```

When writing to a file, an `ofstream` is instantiated to write to the file given by its name, and the indented output stream is constructed above the latter:

```

1      ofstream
2      outputFileStream (
3          outputFileName.c_str (),
4          ofstream::out);
5
6      // create an indented output stream for the LilyPond code
7      // to be written to outputFileStream
8      mfIndentedOstream
9      lilypondFileOutputStream (
10         outputFileStream,
11         gIndenter);
12
13     // convert the LPSR score to LilyPond code
14     try {
15         translateLpsrToLilypond (
16             theLpsrScore,
17             gGlobalMsrOahGroup,
18             gGlobalLpsrOahGroup,
19             passNumber,
20             passDescription,
21             lilypondFileOutputStream);
22     }
```

The code that uses `MusicFormats` thus does not have to care for indented streams instantiation: this is done behind the scene by the library.

10.3 Indenting the output

Indenting the output is handled with a single variable defined in `src/mfutilities/mfIndentedTextOutput.h`. This sharing of a global variable is needed to produce orderly output, since many parts of the `MusicFormats` library can contribute to it:

```

1  // useful shortcut macros
2  #define gIndenter mfOutputIndenter::gGlobalOStreamIndenter
3  #define gTab      mfOutputIndenter::gGlobalOStreamIndenter.getSpacer ()
```

A typical sequence to produce indented output is:

```

1  void msrTransposition::print (ostream& os) const
2  {
3      const int fieldWidth = 22;
4
5      os <<
6          "Transposition" <<
7          ", line " << fInputLineNumber <<
8          endl;
9
10     ++gIndenter;
11
12     os << left <<
13         setw (fieldWidth) <<
14         "fTranspositionDiatonic" << " = " << fTranspositionDiatonic <<
15         endl <<
16         setw (fieldWidth) <<
17         "fTranspositionChromatic" << " = " << fTranspositionChromatic <<
18         endl <<
19         setw (fieldWidth) <<
20         "fTranspositionOctaveChange" << " = " << fTranspositionOctaveChange <<
21         endl <<
22         setw (fieldWidth) <<
```

```

23     "fTranspositionDouble" << " = " << fTranspositionDouble <<
24     endl << endl;
25
26     --gIndenter;
27 }

```

There can be indentation issues, in which the user gets messages like:

```

1 % ### Indentation has become negative: -1

```

To debug this:

- activate the debugging for the indenter, uncommenting this definition in `src/components/mfIndentedTextOutput`

```

1 //-----
2 //define DEBUG_INDENTER

```

- activate abortion on errors in `src/wae/enableAbortToDebugErrors.h`:

```

1 // comment the following definition if abort on internal errors is desired
2 // CAUTION: DON'T USE THIS IN PRODUCTION CODE,
3 // since that could kill a session on a web server, for example
4
5 #ifndef ABORT_TO_DEBUG_ERRORS
6     //define ABORT_TO_DEBUG_ERRORS
7 #endif

```

10.4 Printing descriptions

There is a standard set of methods to print the contents of the descriptions in `MusicFormats` to standard output, depending on the granularity of the information to be displayed:

```

1     void                print (ostream& os) const override;
2
3     string              asString () const override;
4     string              asStringShort () const override;

```

There are also more specific methods such as:

```

1     void                printShort (ostream& os) const override;
2
3     void                printSummary (ostream& os) const override;

```

Note that:

- virtual method `asString ()` produces a rather condensed view of the data to be displayed as part of a single line;
- virtual method `print ()` may produce its output on multiples lines, which always ends with an end of line.

Most classes in `MusicFormats` can be printed with the `<<` operator. Since `MusicFormats` is a large, a test is done for nullity, which is safer and easier for the applications that use it:

```

1 ostream& operator<< (ostream& os, const S_msrElement& elt)
2 {
3     if (elt) {
4         elt->print (os);
5     }
6     else {
7         os << "*** NONE ***" << endl;
8     }
9
10    return os;
11 }

```

In simple cases, virtual method `print ()` merely calls virtual method `asString ()`:

```

1 void msrElement::print (ostream& os) const
2 {
3     os << asString () << endl;
4 }

```

All `asString ()` methods produce an output of the form [...], in order to facilitate selecting the whole with a double click to help the user, since such output can be nested:

```

1 string msrTransposition::asString () const
2 {
3     stringstream s;
4
5     s <<
6     "[Transposition" <<
7     ", fTranspositionDiatonic = " << fTranspositionDiatonic <<
8     ", fTranspositionChromatic = " << fTranspositionChromatic <<
9     ", fTranspositionOctaveChange = " << fTranspositionOctaveChange <<
10    ", fTranspositionDouble = " << fTranspositionDouble <<
11    ", line " << fInputLineNumber <<
12    "]" ;
13
14    return s.str ();
15 }

```

A typical sequence to produce indented output is:

```

1 void msrTransposition::print (ostream& os) const
2 {
3     const int fieldWidth = 22;
4
5     os <<
6     "Transposition" <<
7     ", line " << fInputLineNumber <<
8     endl;
9
10    ++gIndenter;
11
12    os << left <<
13    setw (fieldWidth) <<
14    "fTranspositionDiatonic" << " = " << fTranspositionDiatonic <<
15    endl <<
16    setw (fieldWidth) <<
17    "fTranspositionChromatic" << " = " << fTranspositionChromatic <<
18    endl <<
19    setw (fieldWidth) <<
20    "fTranspositionOctaveChange" << " = " << fTranspositionOctaveChange <<
21    endl <<
22    setw (fieldWidth) <<
23    "fTranspositionDouble" << " = " << fTranspositionDouble <<
24    endl << endl;
25 }

```

```
26 |     --gIndenter;  
27 | }
```

The main indented output streams are:

```
1 | #define gOutputStream *gGlobalOutputIndentedOstream  
2 | #define gLogStream     *gGlobalLogIndentedOstream
```


Chapter 11

Binary data output

Binary data output is done for Braille

Chapter 12

CPU measurements

Option `-cpu` displays the time spent in the successive passes, such as:

Activity	Description	Kind	CPU (sec)
	Handle the options and arguments from <code>argc/argv</code>	mandatory	0.01187
Pass 1	Create an MXSR reading a MusicXML file	mandatory	0.00471
Pass 2a	Create an MSR skeleton from the MXSR	mandatory	0.00222
Pass 2b	Populate the MSR skeleton from MusicXML data	mandatory	0.00405
Pass 4	Convert the MSR into an LPSR	mandatory	0.00137
Pass 5	Convert the LPSR score to LilyPond code	mandatory	0.00136
Total (sec)	Mandatory Optional		
0.02558	0.02558 0.00000		

These numbers are for the CPU only, not including input and output tasks. The time spent in options handling is roughly always the same on a given machine.

Class `mfTimingItemsList`, defined in `src/utilities/mfTiming.h/.cpp`, provides:

```
1 class EXP mfTimingItemsList {
2     // ... ..
3
4     public:
5
6         // global variable for general use
7         // -----
8
9         static mfTimingItemsList          gGlobalTimingItemsList;
10
11     public:
12
13         // public services
14         // -----
15
16         // add an item
17         void          appendTimingItem (
18                     string          activity,
19                     string          description,
20                     mfTimingItem::timingItemKind kind,
21                     clock_t         startClock,
22                     clock_t         endClock);
23
24     // ... ..
25 }
```

Functions `translateMsrToLpsrScore ()` in `src/passes/msr2lpsr/msr2lpsrInterface.cpp` measures time to perform the conversion this way:

```

1 S_lpsrScore translateMsrToLpsr (
2     S_msrScore          originalMsrScore,
3     S_msr0ahGroup       msr0pts,
4     S_lpsr0ahGroup       lpsr0pts,
5     string               passNumber,
6     string               passDescription,
7     S_mfcMultiComponent multiComponent)
8 {
9     if (gGlobalLpsr2lilypond0ahGroup->getNoLilypondCode ()) {
10         gLogStream <<
11             "Option '-nolpc, -no-lilypond-code' is set, no LPSR is created" <<
12             endl;
13
14         return nullptr;
15     }
16
17     // sanity check
18     mfAssert (
19         __FILE__, __LINE__,
20         originalMsrScore != nullptr,
21         "originalMsrScore is null");
22
23     // start the clock
24     clock_t startClock = clock ();
25
26 #ifdef TRACING_IS_ENABLED
27     if (gGlobal0ahEarlyOptions.getEarlyTracePasses ()) {
28         string separator =
29             "%-----";
30
31         gLogStream <<
32             endl <<
33             separator <<
34             endl <<
35             gTab <<
36             passNumber << ": " << passDescription <<
37             endl <<
38             separator <<
39             endl;
40     }
41 #endif
42
43     // create an msr2lpsrTranslator
44     msr2lpsrTranslator
45         translator (
46             originalMsrScore);
47
48     // build the LPSR score
49     S_lpsrScore
50         resultingLpsr =
51         translator.translateMsrToLpsr (
52             originalMsrScore,
53             multiComponent);
54
55     clock_t endClock = clock ();
56
57     // register time spent
58     mfTimingItemsList::gGlobalTimingItemsList.appendTimingItem (
59         passNumber,
60         passDescription,
61         mfTimingItem::kMandatory,
62         startClock,
63         endClock);

```

Part II

The two-phase visitors pattern

Chapter 13

The two-phase visitors pattern

MusicFormats uses a two-phase visitors pattern designed by Dominique Fober to traverse data structures such an `xmlElement tree` or an MSR description, handling each node in the structure in a systematic way. This is in contrast to a programmed top-down traversal.

Such data structures traversals is actually *data driven*: a visitor can decide to 'see' only selected node types.

There are case where visiting is not the way to go, see the sections below.

13.1 Basic mechanism

Visiting a node in a data structure is done in this order:

- first phase: visit the node for the fist time, top-down;
- visit the node contents, using the same two-phase visitors pattern;
- second phase: visit the node for the second time, bottom-up.

The first can be used to prepare data needed for the node contents visit, for example. Then the second phase can used such data, if relevant, as well as data created by the node contents visit, do consolidate the whole.

A visitor class should:

- inherit from `basevisitor`;
- inherit from the smart pointer classes it visits;
- define methods `visitStart ()` and/or `visitEnd ()` depending on which phases it wants to handle. The parameter of all such `visit* ()` methods is always a reference to a smart pointer.

`basevisitor` is defined in `libmusicxml/src/visitors!basevisitor.h`, and contains nothing:

```
1 class basevisitor
2 {
3     public:
4         virtual ~basevisitor() {}
5 };
```

It is used as the base class of all visitors in `browsedata ()` methods:

```

1 void msrWords::acceptIn (basevisitor* v)
2 {
3     if (gGlobalMsrOahGroup->getTraceMsrVisitors ()) {
4         gLogStream <<
5             "% ==> msrWords::acceptIn ()" <<
6             endl;
7     }
8
9     if (visitor<S_msrWords>*
10         p =
11         dynamic_cast<visitor<S_msrWords>*> (v)) {
12         S_msrWords elem = this;
13
14         if (gGlobalMsrOahGroup->getTraceMsrVisitors ()) {
15             gLogStream <<
16                 "% ==> Launching msrWords::visitStart ()" <<
17                 endl;
18         }
19         p->visitStart (elem);
20     }
21 }

```

13.2 Browser template classes

There are several such classes, all with the same specification as the one in [libmusicxml/src/lib!tree_browser.h](#), named to allow easy search for them in the code base. For example, in [src/formats/msr/msrElements.h](#), there is:

```

1 // -----
2 template <typename T> class msrBrowser : public browser <T>
3 {
4     public:
5
6         msrBrowser (basevisitor* v) : fVisitor (v) {}
7
8         virtual ~msrBrowser () {}
9
10    public:
11
12        virtual void set (basevisitor* v) { fVisitor = v; }
13
14        virtual void browse (T& t) {
15            enter (t);
16
17            t.browseData (fVisitor);
18
19            leave (t);
20        }
21
22    protected:
23
24        basevisitor* fVisitor;
25
26        virtual void enter (T& t) { t.acceptIn (fVisitor); }
27        virtual void leave (T& t) { t.acceptOut (fVisitor); }
28 };

```

13.3 A first example: counting notes in MusicXML data

In `libmusicxml/samples/countnotes.cpp`, counting the notes in MusicXML data needs only see `S_note` nodes. Class `countnotes` thus inherits only from a visitor for this type of node, and all the other node types are simply ignored.

vVisitor method `countnotes::visitStart` only has to increment the notes count:

Listing 13.1: `libmusicxml/samples/countnotes.cpp`

```

1 class countnotes :
2   public visitor<S_note>
3 {
4   public:
5     int fCount;
6
7     countnotes() : fCount (0) {}
8
9     virtual ~countnotes () {}
10
11    void visitStart ( S_note& elt )    { fCount++; }
12 };

```

13.4 A more complex example

Let's look at the `<scaling/>` MusicXML element:

```

1 <scaling>
2   <millimeters>7</millimeters>
3   <tenths>40</tenths>
4 </scaling>

```

It contains a `<millimeter/>` and a `<tenth/>` element. The latter two don't contain any other elements, so `visitStart ()` is enough for them.

There is nothing to do on the visit start upon `<scaling/>`, so there is no such method. On the visit end upon `<scaling/>`, though, the values grabbed from the `<millimeter/>` and `<tenth/>` elements are used to create the class `msrScaling` description.

Should a visit start method have been written, the execution order would have been:

```

1 mxsr2msrTranslator::visitStart ( S_scaling& elt)
2   mxsr2msrTranslator::visitStart ( S_millimeters& elt )
3   mxsr2msrTranslator::visitStart ( S_tenths& elt )
4   mxsr2msrTranslator::visitEnd ( S_scaling& elt)

```

or, depending on the order in which the subelements of `<scaling/>` are visited:

```

1 mxsr2msrTranslator::visitStart ( S_scaling& elt)
2   mxsr2msrTranslator::visitStart ( S_tenths& elt )
3   mxsr2msrTranslator::visitStart ( S_millimeters& elt )
4   mxsr2msrTranslator::visitEnd ( S_scaling& elt)

```

In `src/passes/mxsr2msr/mxsr2msrTranslator.cpp`, visiting a `<scaling/>` element is handled this way:

Listing 13.2: Visiting <scaling/>

```

1 void mxsr2msrTranslator::visitStart ( S_millimeters& elt )
2 {
3     #ifdef TRACING_IS_ENABLED
4         if (gGlobalMxsrOahGroup->getTraceMxsrVisitors ()) {
5             gLogStream <<
6                 "--> Start visiting S_millimeters" <<
7                 ", line " << elt->getInputLineNumber () <<
8                 endl;
9         }
10    #endif
11
12    fCurrentMillimeters = (float)(*elt);
13 }
14
15 void mxsr2msrTranslator::visitStart ( S_tenths& elt )
16 {
17     #ifdef TRACING_IS_ENABLED
18         if (gGlobalMxsrOahGroup->getTraceMxsrVisitors ()) {
19             gLogStream <<
20                 "--> Start visiting S_tenths" <<
21                 ", line " << elt->getInputLineNumber () <<
22                 endl;
23         }
24     #endif
25
26    fCurrentTenths = (float)(*elt);
27 }
28
29 void mxsr2msrTranslator::visitEnd ( S_scaling& elt)
30 {
31     int inputLineNumber =
32         elt->getInputLineNumber ();
33
34     #ifdef TRACING_IS_ENABLED
35         if (gGlobalMxsrOahGroup->getTraceMxsrVisitors ()) {
36             gLogStream <<
37                 "--> End visiting S_scaling" <<
38                 ", line " << inputLineNumber <<
39                 endl;
40         }
41     #endif
42
43     // create a scaling
44     S_msrScaling
45         scaling =
46             msrScaling::create (
47                 inputLineNumber,
48                 fCurrentMillimeters,
49                 fCurrentTenths);
50
51     #ifdef TRACING_IS_ENABLED
52         if (gGlobalTracingOahGroup->getTraceGeometry ()) {
53             gLogStream <<
54                 "There are " << fCurrentTenths <<
55                 " tenths for " << fCurrentMillimeters <<
56                 endl;
57         }
58     #endif
59
60     // set the MSR score's scaling
61     fMsrScore->
62         setScaling (scaling);
63 }

```


13.5 Data browsing order

The order of the visit of a node's subnodes is programmed in `browseData ()` methods, such as:

Listing 13.3: `msrDoubleTremolo::browseData (basevisitor* v)`

```

1 void msrDoubleTremolo::browseData (basevisitor* v)
2 {
3     if (fDoubleTremoloFirstElement) {
4         // browse the first element
5         msrBrowser<msrElement> browser (v);
6         browser.browse (*fDoubleTremoloFirstElement);
7     }
8
9     if (fDoubleTremoloSecondElement) {
10        // browse the second element
11        msrBrowser<msrElement> browser (v);
12        browser.browse (*fDoubleTremoloSecondElement);
13    }
14 }

```

Since this order is set in the `browsearch ()` methods, it cannot be influenced by the visitors of the corresponding class instances.

There are cases where the data should be sorted prior to being browsed, such as the staves in parts: this ensures that they are browsed in this order: harmonies staff, other staves, figured bass staff.

13.6 Selectively inhibiting data browsing

In some cases, it is desirable not to browse part of the data. This is the case when a given class contains non-normalized data, i.e. data that occurs elsewhere and will be browsed in another class instance.

For example, class `msrMultipleFullBarRests` contains class `msrMeasure` instances. class `msrScore` contains:

```

1 // in <multiple-rest/>, the multiple full-bar rests are explicit,
2 // whereas LilyPond only needs the number of multiple full-bar rests
3 Bool                                fInhibitMultipleFullBarRestsBrowsing;
4
5 void                                setInhibitMultipleFullBarRestsBrowsing ()
6 {
7     fInhibitMultipleFullBarRestsBrowsing = true;
8 }
9
10 Bool                                getInhibitMultipleFullBarRestsBrowsing () const
11 {
12     return
13         fInhibitMultipleFullBarRestsBrowsing;
14 };

```

Class `lpsr2lilypondTranslator` checks this setting:

```

1 void lpsr2lilypondTranslator::visitEnd (S_msrNote& elt)
2 {
3     // ... ..
4
5     if (fOnGoingMultipleFullBarRests) {
6         switch (elt->getNoteKind ()) {
7             case msrNoteKind::kNoteRestInMeasure:
8                 // don't handle multiple full-bar rests, that's done in visitEnd (
9                 S_msrMultipleFullBarRests&)
10                 if (elt->getNoteOccupiesAFullMeasure ()) {

```

```

10         Bool inhibitMultipleFullBarRestsBrowsing =
11             fVisitedLpsrScore->
12                 getMsrScore ()->
13                     getInhibitMultipleFullBarRestsBrowsing ();
14
15         if (inhibitMultipleFullBarRestsBrowsing) {
16 #ifdef TRACING_IS_ENABLED
17             if (
18                 gGlobalTracingOahGroup->getTraceNotes ()
19                 ||
20                 gGlobalTracingOahGroup->getTraceMultipleFullBarRests ()
21             ) {
22                 gLogStream <<
23                     "% ==> end visiting multiple full-bar rests is ignored" <<
24                     endl;
25             }
26 #endif
27
28 #ifdef TRACING_IS_ENABLED
29             if (gGlobalTracingOahGroup->getTraceNotesDetails ()) {
30                 gLogStream <<
31                     "% ==> returning from visitEnd (S_msrNote&)" <<
32                     endl;
33             }
34 #endif
35
36             noteIsToBeIgnored = true;
37         }
38     }
39     break;
40     // ... ..
41 }

```

Another example is in the class `lpsr2lilypondTranslator` constructor:

```

1 lpsr2lilypondTranslator::lpsr2lilypondTranslator (
2     S_lpsrScore      lpsrScore,
3     S_msrOahGroup&   msrOpts,
4     S_lpsrOahGroup&  lpsrOpts,
5     ostream&         lilypondCodeStream)
6 : fLilypondCodeStream (
7     lilypondCodeStream)
8 {
9     fMsrOahGroup = msrOpts;
10    fLpsrOahGroup = lpsrOpts;
11
12    // the LPSR score we're visiting
13    fVisitedLpsrScore = lpsrScore;
14
15    // inhibit the browsing of grace notes groups before,
16    // since they are handled at the note level
17    fVisitedLpsrScore->
18        getMsrScore ()->
19            setInhibitGraceNotesGroupsBeforeBrowsing ();
20
21    // inhibit the browsing of grace notes groups after,
22    // since they are handled at the note level
23    fVisitedLpsrScore->
24        getMsrScore ()->
25            setInhibitGraceNotesGroupsAfterBrowsing ();

```

The test for browsing inhibition is done in `src/formats/msr/msrNotes.cpp`:

```

1 void msrNote::browseData (basevisitor* v)
2 {
3     // browse the grace notes group before if any

```

```

4   if (fNoteGraceNotesGroupBefore) {
5       // fetch the score
6       S_msrScore
7       score =
8       fetchNoteScoreUpLink ();
9
10      if (score) {
11          Bool
12          inhibitGraceNotesGroupsBeforeBrowsing =
13          score->
14          getInhibitGraceNotesGroupsBeforeBrowsing ();
15
16          if (inhibitGraceNotesGroupsBeforeBrowsing) {
17              #ifdef TRACING_IS_ENABLED
18                  if (
19                      gGlobalMsrOahGroup->getTraceMsrVisitors ()
20                      ||
21                      gGlobalTracingOahGroup->getTraceNotes ()
22                      ||
23                      gGlobalTracingOahGroup->getTraceGraceNotes ()
24                  ) {
25                      gLogStream <<
26                      "% ==> visiting grace notes groups before is inhibited" <<
27                      endl;
28                  }
29              #endif
30          }
31          else {
32              // browse the grace notes group before
33              msrBrowser<msrGraceNotesGroup> browser (v);
34              browser.browse (*fNoteGraceNotesGroupBefore);
35          }
36      }
37  }
38
39  // ... ..
40 }

```

Choosing which elements to browse can be more selective:

```

1   void msrStaff::browseData (basevisitor* v)
2   {
3       // ... ..
4
5       if (fStaffAllVoicesList.size ()) {
6           for (S_msrVoice voice : fStaffAllVoicesList) {
7               // is this voice name in the ignore voices set?
8               Bool ignoreVoice (false);
9
10              string voiceName =
11              voice->
12              getVoiceName ();
13
14              const set<string>&
15              ignoreMsrVoicesSet =
16              gGlobalMsr2msrOahGroup->
17              getIgnoreMsrVoicesSet ();
18
19              // ... ..
20
21              if (ignoreMsrVoicesSet.size ()) {
22                  ignoreVoice =
23                  mfStringIsInStringSet (
24                      voiceName,
25                      ignoreMsrVoicesSet);
26              }

```

```

27
28     if (ignoreVoice) {
29 #ifdef TRACING_IS_ENABLED // JMI
30         if (gGlobalTracingOahGroup->getTraceVoices ()) {
31             gLogStream <<
32                 "Ignoring voice \"" <<
33                 voiceName <<
34                 "\"\" <<
35                 endl;
36         }
37 #endif
38     }
39
40     else {
41         msrBrowser<msrVoice> browser (v);
42         browser.browse (*voice);
43     }
44 } // for
45 }
46
47 // ... ..
48 }

```

13.7 Adapting visitors to data browsing order with booleans

A frequent situation is when the visitor's actions should be tuned depending upon which elements are being visited. In simple case, this can be handled with boolean variables.

For example, `<system-layout/>` may occur both in the `<defaults/>` and `<print/>` MusicXML markups:

```

1  <defaults>
2    <scaling>
3      <millimeters>7.3</millimeters>
4      <tenths>40</tenths>
5    </scaling>
6    <page-layout>
7      <page-height>1534</page-height>
8      <page-width>1151</page-width>
9      <page-margins type="both">
10        <left-margin>54.7945</left-margin>
11        <right-margin>54.7945</right-margin>
12        <top-margin>27.3973</top-margin>
13        <bottom-margin>27.3973</bottom-margin>
14      </page-margins>
15    </page-layout>
16    <system-layout>
17      <system-margins>
18        <left-margin>15</left-margin>
19        <right-margin>0</right-margin>
20      </system-margins>
21      <system-distance>92.5</system-distance>
22      <top-system-distance>27.5</top-system-distance>
23    </system-layout>
24
25    // ... ..
26
27    <part id="P1">
28      <measure number="1">
29        <print>
30          <system-layout>
31            <system-margins>
32              <left-margin>75.625</left-margin>
33              <right-margin>0</right-margin>

```

```

34         </system-margins>
35         <top-system-distance>410.9375</top-system-distance>
36     </system-layout>
37     <staff-layout>
38         <?DoletSibelius JustifyAllStaves=false?>
39         <?DoletSibelius ExtraSpacesAbove=3?>
40     </staff-layout>
41     <measure-layout>
42         <measure-distance>20</measure-distance>
43     </measure-layout>
44 </print>

```

To know which element is being visited, we use boolean `fOnGoing*` variables, such as `fOnGoingPrintLayout` in class `msr2mxsrTranslator`.

It is assigned in:

```

1 void msr2mxsrTranslator::visitStart (S_msrPrintLayout& elt)
2 {
3     // ... ..
4
5     fOnGoingPrintLayout = true;
6 }
7
8 void msr2mxsrTranslator::visitEnd (S_msrPrintLayout& elt)
9 {
10    // ... ..
11
12    fOnGoingPrintLayout = false;
13 }

```

and checked for example in:

```

1 void msr2mxsrTranslator::visitStart (S_msrSystemLayout& elt)
2 {
3     // ... ..
4
5     // create a system layout element
6     Sxmlelement
7     systemLayoutElement =
8         createMxmlElement (k_system_layout, "");
9
10    if (fOnGoingPrintLayout) {
11        // append it to the current print element
12        fCurrentPrintElement->push (
13            systemLayoutElement);
14    }
15    else {
16        // don't append it at once to the score defaults element
17        fScoreDefaultsSystemLayoutElement = systemLayoutElement;
18    }
19 }

```

When the data browsing order does not fit the needs of a visitor, the latter has to store the values gathered until they can be processed. This occurs for example in `mxsr2msrTranslator`, which uses `fCurrentPrintLayout` for this purpose:

```

1 void mxsr2msrTranslator::visitStart ( S_system_layout& elt )
2 {
3     // ... ..
4
5     // create the system layout
6     fCurrentSystemLayout =
7         msrSystemLayout::create (
8             inputLineNumber);
9 }

```

```

10  fOnGoingSystemLayout = true;
11  }
12
13  void mxsr2msrTranslator::visitEnd ( S_system_layout& elt )
14  {
15      // ... ..
16
17      if (fOnGoingPrint) {
18          // set the current print layout's system layout
19          fCurrentPrintLayout->
20              setSystemLayout (
21                  fCurrentSystemLayout);
22      }
23      else {
24          // set the MSR score system layout
25          fMsScore->
26              setSystemLayout (
27                  fCurrentSystemLayout);
28      }
29
30      // forget about the current system layout
31      fCurrentSystemLayout = nullptr;
32
33      fOnGoingSystemLayout = false;
34  }

```

13.8 Adapting visitors to data browsing order with stacks

In more complex cases, the visiting order leads to have several on-going elements simultaneously. This is the case with class `msrTuplet`, which can be nested.

They are handled in `src/passes/mxsr2msr/mxsr2msrTranslator` and `src/passes/lpsr2lilypond/lpsr2lilypond` for example, using a stack to keep track of them.

MusicFormats never uses C++ STL stacks, because they cannot be iterated over:

```

1  list<S_msrTuplet>          fOnGoingTupletsStack;

1  void lpsr2lilypondTranslator::visitStart (S_msrTuplet& elt)
2  {
3      // ... ..
4
5      if (fOnGoingTupletsStack.size ()) {
6          // elt is a nested tuplet
7
8          S_msrTuplet
9              containingTuplet =
10                 fOnGoingTupletsStack.top ();
11
12          // unapply containing tuplet factor,
13          // i.e 3/2 inside 5/4 becomes 15/8 in MusicXML...
14          elt->
15              unapplySoundingFactorToTupletMembers (
16                  containingTuplet->
17                      getTupletFactor ());
18      }
19
20      // ... ..
21
22      // push the tuplet on the tuplets stack
23      fOnGoingTupletsStack (elt);
24
25      // ... ..

```

```

26 }
27
28 void lpsr2lilypondTranslator::visitEnd (S_msrTuplet& elt)
29 {
30     // ... ..
31
32     // pop the tuple from the tuples stack
33     fOnGoingTuplesStack ();
34
35     // ... ..
36 }

```

13.9 Avoiding the visiting pattern by cascading

There are cases where we need a deterministic traversal of some data handled by MusicFormats. For example, appending a `msrStaffDetails` instance to a part should be cascaded to its staves. It would be an overkill to create a specific browser for this purpose.

This is what method `msrPart::appendStaffDetailsToPart ()` does:

```

1 void msrPart::appendStaffDetailsToPart (
2     S_msrStaffDetails staffDetails)
3 {
4     // ... ..
5
6     // register staff details in part
7     fCurrentPartStaffDetails = staffDetails;
8
9     // append staff details to registered staves
10    for (
11        map<int, S_msrStaff>::const_iterator i =
12            getPartStaveNumbersToStavesMap.begin ();
13        i != getPartStaveNumbersToStavesMap.end ();
14        ++i
15    ) {
16        S_msrStaff
17            staff = (*i).second;
18
19        staff->
20            appendStaffDetailsToStaff (
21                staffDetails);
22    } // for
23 }

```

Another case is the handling the various elements attached to an class `msrNote` instance, among them chords, grace notes groups and tuple, all of which contain notes too.

Doing things in the right order can be tricky, see <src/passes/lpsr2lilypond/lpsr2lilypondTranslator.h/.cpp>.

The time-oriented representation of scores in MSR is also printed by cascading through `printSlices ()` methods, see chapter 20 [MSR time-oriented representation], page 200.

Part III

Programming style and conventions

Chapter 14

Programming style and conventions

14.1 Files naming conventions

Most file names start with an identification of the component they belong to, such as 'oah', 'msr', 'lpsr', 'lilypond', 'bsr', 'braille', 'xml2ly', 'xml2brl' and msdl.

The ancillary files such as `src/utilities/mfIndentedTextOutput.h/.cpp` follow this rule too, with an mf prefix.

The '*Oah.*' files handle the options and help for the corresponding component, such as `'src/passes/msr2msr/msr2msrOah.h/.cpp'`.

The `'src/oah/tracingOah.h/.cpp'`, `src/oah/musicxmlOah.h/.cpp` 'extra' and 'general' prefixes are about the corresponding help groups.

There are a couple of 'global' files not related to any particular component, placed in `src/mfutilities/` with an mf name prefix:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev/src > ll mfutilities/
2 total 200
3 0 drwxr-xr-x 15 jacquesmenu staff 480 Oct 22 06:25:57 2021 ./
4 0 drwxr-xr-x 19 jacquesmenu staff 608 Oct 22 05:29:29 2021 ../
5 8 -rw-r--r--@ 1 jacquesmenu staff 3255 Oct 18 20:22:16 2021 mfBool.cpp
6 16 -rw-r--r--@ 1 jacquesmenu staff 4917 Oct 18 19:56:51 2021 mfBool.h
7 8 -rw-r--r--@ 1 jacquesmenu staff 1336 Oct 15 18:48:10 2021 mfEnumAll.h
8 16 -rw-r--r--@ 1 jacquesmenu staff 7182 Nov 8 13:08:51 2021 mfIndentedTextOutput.cpp
9 16 -rw-r--r--@ 1 jacquesmenu staff 7715 Nov 8 13:08:40 2021 mfIndentedTextOutput.h
10 8 -rw-r--r--@ 1 jacquesmenu staff 889 Oct 15 20:34:47 2021 mfMusicformatsError.cpp
11 8 -rw-r--r--@ 1 jacquesmenu staff 629 Oct 15 20:34:47 2021 mfMusicformatsError.h
12 8 -rw-r--r--@ 1 jacquesmenu staff 2541 Nov 5 11:29:25 2021 oahOptionsVector.cpp
13 8 -rw-r--r--@ 1 jacquesmenu staff 972 Oct 15 20:16:51 2021 oahBasicTypes.h
14 64 -rw-r--r--@ 1 jacquesmenu staff 29773 Oct 15 18:48:10 2021 mfStringsHandling.cpp
15 16 -rw-r--r--@ 1 jacquesmenu staff 6269 Oct 15 18:55:46 2021 mfStringsHandling.h
16 16 -rw-r--r--@ 1 jacquesmenu staff 5028 Oct 7 20:03:27 2021 mfTiming.cpp
17 8 -rw-r--r--@ 1 jacquesmenu staff 3726 Oct 8 08:21:09 2021 mfTiming.h
```

The files *Elements.h/.cpp contain base classes to variants, such as `src/formats/lpsr//lpsrElements.h/.cpp`, whose lpsrElement class is used in a number of other files:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev/src > grep -r 'public lpsrElement' *
2 formats/lpsr/lpsrStaves.h:29:class EXP lpsrNewStaffgroupBlock : public lpsrElement
3 formats/lpsr/lpsrStaves.h:87:class EXP lpsrNewStaffTuningBlock : public lpsrElement
4 formats/lpsr/lpsrStaves.h:150:class EXP lpsrNewStaffBlock : public lpsrElement
5 formats/lpsr/lpsrStaves.h:208:class EXP lpsrStaffBlock : public lpsrElement
6 formats/lpsr/lpsrVariables.h:27:class EXP lpsrVariableUseCommand : public lpsrElement
7 formats/lpsr/lpsrScores.h:35:class EXP lpsrScore : public lpsrElement
8 formats/lpsr/lpsrBarNumbers.h:26:class EXP lpsrBarNumberCheck : public lpsrElement
```

```
9 formats/lpsr/lpsrBarNumbers.h:85:class EXP lpsrBarCommand : public lpsrElement
10 formats/lpsr/lpsrLyrics.h:31:class EXP lpsrNewLyricsBlock : public lpsrElement
11 formats/lpsr/lpsrComments.h:25:class EXP lpsrComment : public lpsrElement
12 formats/lpsr/lpsrVoices.h:29:class EXP lpsrUseVoiceCommand : public lpsrElement
13 formats/lpsr/lpsrParts.h:27:class EXP lpsrPartBlock : public lpsrElement
14 formats/lpsr/lpsrPapers.h:32:class EXP lpsrPaper : public lpsrElement
15 formats/lpsr/lpsrPartGroups.h:29:class EXP lpsrPartGroupBlock : public lpsrElement
16 formats/lpsr/lpsrParallelMusic.h:28:class EXP lpsrParallelMusicBlock : public lpsrElement
17 formats/lpsr/lpsrLayouts.h:23:class EXP lpsrLayout : public lpsrElement
18 formats/lpsr/lpsrHeaders.h:27:class EXP lpsrHeader : public lpsrElement
19 formats/lpsr/lpsrScheme.h:29:class EXP lpsrSchemeVariable : public lpsrElement
20 formats/lpsr/lpsrScheme.h:140:class EXP lpsrSchemeFunction : public lpsrElement
21 formats/lpsr/lpsrBookBlockElements.h:35:class EXP lpsrBookBlockElement : public
    lpsrElement
22 formats/lpsr/lpsrBookBlockElements.h:237:class EXP lpsrBookBlock : public lpsrElement
23 formats/lpsr/lpsrContexts.h:30:class EXP lpsrContext : public lpsrElement
```

There are a number of self-explaning `*BasicTypes.h/.cpp` file names:

```
1 ./formats/msdl/msdlBasicTypes.h
2 ./formats/msdl/msdlBasicTypes.cpp
3 ./formats/msr/msrBasicTypes.cpp
4 ./formats/msr/msrBasicTypes.h
5 ./formats/lpsr/lpsrBasicTypes.cpp
6 ./formats/lpsr/lpsrBasicTypes.h
7 ./formats/bsr/bsrBasicTypes.h
8 ./formats/bsr/bsrBasicTypes.cpp
9 ./oah/oahBasicTypes.h
10 ./oah/oahBasicTypes.cpp
11 ./formatsgeneration/msrGeneration/msrGenerationBasicTypes.cpp
12 ./formatsgeneration/msrGeneration/msrGenerationBasicTypes.h
```

The files are grouped in the `src` folder according to the component they belong to:

- converters
- generators
- interfaces
- oah
- formatsgeneration
- passes
- formats
- utilities
- wae

14.2 Adding C++ files

Building MusicFormats relies on `build/CMakeLists.txt` to find the C++ files that should be compiled.

When building MusicFormats with:

```
1 cd build
2 make
```

a `cmake` cache is created in file `build/libdir/CMakeCache.txt`, containing the list of all the C++ files in the library, including those of the embedded `libmusicxml2`.

Adding individual files is fine, but adding new folders in the `src` hierarchy implies to update variable `SRC_FOLDERS` in `build/CMakeLists.txt` accordingly and to remove the `build/libdir/CMakeCache.txt` cache.

Care must be taken when adding a new file on a case insensitive file system: the type case in its name should be what is needed in the first place.

For example, renaming `src/formats/msr/msrBarlines.h` to `src/formats/msr/msrBarLines.h` (this author's experience) leads MusicFormats not to build successfully on Linux if you develop on Windows or MacOS:

- the latter two usually use case insensitive file names (even though one may choose to format as disk to be case-sensitive), but Linux does not;

- the renaming above is not pushed to the repository by `git push` on case insensitive file systems.

The best solution here, both for files and folders names, is to use `'git mv'` to do the renaming instead of the operating system tools:

- `git mv oldName newName`
- `git commit "..."` -a
- `git push`

14.3 Renaming C++ files

Renaming a C++ file causes `build/libdir/CMakeCache.txt` to be obsolete: it then has to be removed, and the library should be built anew.

For example, this author uses the `rmcache` bash alias to remove the cache:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev > type rmcache
2 rmcache is aliased to 'rm /Users/jacquesmenu/musicformats-git-dev/build/libdir/CMakeCache.txt'
```

Running `make` will re-create this cache with the new file name.

Caution has to be taken when a file name case is changed in a case-insensitive development environment such as Windows or MacOS. Cloning MusicFormats in Linux will then fail to find the file under its new name.

In such a case, the following Git command has to be used to actually change the file name in MusicFormats repository:

```
1 git mv -f <old name> <new name>
```

Changing the name of a directory in `src/` should be propagated to `build/CMakeLists.txt`, since this is where the set of files to be compiled is determined, as in:

```
1 if (MSR)
2   set (SRC_FOLDERS ${SRC_FOLDERS} passes/musicxml2mxsr formats/mxsr passes/mxsr2msr
        formats/msr passes/msr2msr formatsgeneration/multiGeneration formatsgeneration/
        msrGeneration generators/Mikrokosmos3Wandering generators/LilyPondIssue34)
3 endif()
```

In such a case, the cache should be removed before building, see `rmcache` above.

14.4 Source code layout

The following text-editing conventions are used:

- tabs are not used before the first non-space character in a line, two spaces are used instead;
- the code is not tightly packed: declarations in classes have the members' names aligned vertically, with many spaces before them if needed, and empty lines are used to separate successive activities in methods.

14.5 Defensive programming

The code base of `xml2ly` is *defensive programming* oriented, which means that:

- identifiers are explicit and long if needed – only very local ones are short, such as iteration loops indexes;
- the code is organized in sections, with an initial comment documenting what the code does;
- the C++17's `auto` declaration feature is used only for enumeration type `s`, see below. Writing the explicit types in a large code base helps the maintainer mastering the code;
- function `mfAssert ()` is used to perform sanity checks, such as detect a null pointer prior to using it.

The few uses of `auto` declarations are in range-based `for` loops over enumeration type `s`. There the type of the index is explicit from the `Enum*` being enumerated over. For example, in `src/formats/msr/msrBasicTypes.cpp`:

```
1  for (auto e : mfEnumAll<msrHarmonyKind> ()) {  
2      // create the harmony structure  
3      S_msrHarmonyStructure  
4          harmonyStructure =  
5          msrHarmonyStructure::create (  
6              e);  
7  
8      // register it in the map  
9      gGlobalHarmonyStructuresMap [e] =  
10         harmonyStructure;  
11 } // for
```

Class `mfEnumAll` is defined in `src/mfutilities/mfEnumAll.h` as:

```

1  template< typename T >
2  class mfEnumAll
3  {
4      public:
5
6          class Iterator
7          {
8              public:
9
10             Iterator (int value)
11                 : fIterationIndex (value)
12                 {}
13
14             T operator* (void) const
15                 { return (T) fIterationIndex; }
16
17             void operator++ (void)
18                 { ++fIterationIndex; }
19
20             Bool operator != (Iterator rhs)
21                 { return fIterationIndex != rhs.fIterationIndex; }
22
23             private:
24
25                 int fIterationIndex;
26
27         };
28 };

```

14.6 Sanity checks

They are performed to ensure that the formats in `MusicFormats` are consistent, to avoid ugly crashes. An example is:

```

1  // get voice to insert harmonies into
2  S_msrVoice
3      voiceToInsertHarmoniesInto =
4          fCurrentPart->
5              getPartHarmoniesVoice ();
6
7  // sanity check
8  mfAssert (
9      __FILE__, __LINE__,
10     voiceToInsertHarmoniesInto != nullptr,
11     "voiceToInsertHarmoniesInto is null");

```

14.7 JMI comments

Comments containing `JMI` indicates that the code may have to be reconsidered in the future, should a problem arise. They are removed when it becomes obvious that the code is fine. `JMI` was the acronym for the author's activity as a software contractor long time ago.

14.8 Exported symbols

The classes and functions that need to be exported from the MusicFormats library in the Windows sense are marked as such with an EXP specification:

```

1 class EXP smartable {
2     // ... ..
3 };

1 EXP S_mxsrOahGroup createGlobalMxsrOahGroup ();

```

14.9 Smart pointers

libmusicxml2 provides what Dominique Fober named smart pointers, because:

- a smart pointer is an instance of a class that contains the actual pointer in the usual C++ sense;
- the actual pointer is guaranteed to be initialized to `nullptr`;
- garbage collection is implicit, using reference counts.

The definitions are in `libmusicxml/src/lib!smartpointer.h`.

The reference counting is done in class `smartable`:

```

1 class EXP smartable {
2     private:
3         unsigned refCount;
4     public:
5         /// gives the reference count of the object
6         unsigned refs() const { return refCount; }
7         /// addReference increments the ref count and checks for refCount overflow
8         void addReference() { refCount++; assert(refCount != 0); }
9         /// removeReference delete the object when refCount is zero
10        void removeReference() { if (--refCount == 0) delete this; }
11
12    protected:
13        smartable() : refCount(0) {}
14        smartable(const smartable&): refCount(0) {}
15        /// destructor checks for non-zero refCount
16        virtual ~smartable() { assert (refCount == 0); }
17        smartable& operator=(const smartable&) { return *this; }
18    };
19
20    A smart pointer type is created with template class {\tt SMARTP}, for example:
21    template<class T> class SMARTP {
22    class EXP msrElement : public smartable
23    {
24        // ... ..
25    };
26    typedef SMARTP<msrElement> S_msrElement;

```

Smart pointer type name belonging to Dominique Fober's work can be told from those of MusicFormats by their prefix:

- in libmusicxml2, smart pointer type names start with an 'S', such as `$xmlelement`;
- in MusicFormats, they start with 'S_', such as `S_oahHandler`.

Inheriting from class `smartable` is used to create smart pointer types, as in `src/wae/waeHandlers.h`:

```

1 class EXP waeHandler : public smartable
2 {
3     public:
4
5         // creation
6         // -----
7
8         static SMARTP<waeHandler> create ();
9
10    public:
11
12        // constructors/destructor
13        // -----
14
15                waeHandler ();
16
17        virtual    ~waeHandler ();
18
19    public:
20
21        // set and get
22        // -----
23
24    public:
25
26        // public services
27        // -----
28
29    public:
30
31        // print
32        // -----
33
34        string                asString () const;
35
36        void                  print (ostream& os) const;
37
38    private:
39
40        // private fields
41        // -----
42 };
43 typedef SMARTP<waeHandler> S_waeHandler;
44 EXP ostream& operator<< (ostream& os, const S_waeHandler& elt);

```

The creation of the instances in `src/wae/waeHandlers.cpp` is done with:

```

1 S_waeHandler waeHandler::create ()
2 {
3     waeHandler* o =
4         new waeHandler ();
5     assert (o != nullptr);
6     return o;
7 }

```

14.10 Files contents layout

Indentation is done by two spaces, avoiding TAB characters.

In `*.h` files, the classes declarations contain all of part of the following:

- public data types, usually enumeration type `s`, if any;
- public static class `create* ()` methods, except for pure virtual classes, in which case they are commented out;
- constructors and destructor;
- public `set* ()` and `get* ()` methods;
- public services if any;
- public visiting methods, i.e. `acceptIn ()`, `acceptOut ()` and `browseData ()`, if the class contains browsable data such as STL lists, vectors, maps and sets;
- public print methods, such as `asString ()` and `print ()`;
- private methods if any;
- private fields.
- private work methods if any;
- private work fields.

A work method is used internally by the class, while a work field is one that evolves as the class contents is populated.

Most class declarations are followed by a smart pointer type and a `operator<<`, such as:

```
1 typedef SMARTP<msrHarmonyDegree> S_msrHarmonyDegree;
2 EXP ostream& operator<< (ostream& os, const S_msrHarmonyDegree& elt);
```

The same order for constructors, destructor and methods is followed in most `.cpp` files.

14.11 #define DEBUG* code sections

Some sections of code in `.cpp` are controlled by such definitions:

- `//#define DEBUG_EARLY_OPTIONS::in src/oah/oahEarlyOptions.cpp;`
- `//#define DEBUG_INDENTER::in src/oah/mfIndentedTextOutput.cpp;`
- `//#define DEBUG_SPLITTING::in src/mfutilities/mfStringsHandling.cpp`

These can be uncommented to obtain development-time tracing information, without there being a need for such in MusicFormats library regular use.

14.12 Identifiers naming conventions

The following rules apply:

- all enumeration type names describing variants in classes end in 'Kind';
- all enumeration constants start with 'k';
- all classes names have a prefix indicating which part of MusicFormats there belong to, such as class `msrTimeSignature`, `oahAtomStoringAValue` and `msdlKeywordsLanguageAtom`;
- all classes member fields start with 'f';
- all global variables start with 'gGlobal';
- all variables private to methods start with 'pPrivate';
- some `K_*` constants are defined with `#define` because creating global constants variables and accessing them would be too cumbersome, such as:

```

1  \#define msrPart::K_PART_HARMONIES_STAFF_NUMBER      10
2  \#define msrPart::K_PART_HARMONIES_VOICE_NUMBER     11
3
4  \#define msrPart::K_PART_FIGURED_BASS_STAFF_NUMBER   20
5  \#define msrPart::K_PART_FIGURED_BASS_VOICE_NUMBER  21

```

When a field is an STL container, such a `vector`, `list`, `map` or `set`, this is indicated as part of the identifier, such as:

```

1  map<string, string>    fPartsRenamingMap;

```

or

```

1  fStringToDalSegnoKindMapVariable;

```

or

```

1  map<string, Sxmlelement>    fPartMeasureNumbersToElementsMap;

```

All `create* ()` methods create class instances, and are paired with an explicit constructor with the same parameters:

```

1  // creation from MusicXML
2  // -----
3
4  static SMARTP<msrHarmonyDegree> create (
5      int                inputLineNumber,
6      int                harmonyDegreeValue,
7      msrAlterationKind  harmonyDegreeAlterationKind,
8      msrHarmonyDegreeTypeKind harmonyDegreeTypeKind);
9
10 protected:
11
12 // constructors/destructor
13 // -----
14
15 msrHarmonyDegree (
16     int                inputLineNumber,
17     int                harmonyDegreeValue,
18     msrAlterationKind  harmonyDegreeAlterationKind,
19     msrHarmonyDegreeTypeKind harmonyDegreeTypeKind);
20
21 virtual ~msrHarmonyDegree ();

```

Some classes use private fields and methods for their internal working. A field in the form `fCurrent*` denotes something whose value is not permanent once set. Fields named `fPending*` contain values gathered to be used later, such as `fPendingHarmoniesList` in `src/passes/mxsr2msr/mxsr2msrTranslator.h/.cpp`.

14.13 Exceptions and warnings/errors reporting

MusicFormats defines exceptions for its needs in `src/wae/waeExceptions.h/.cpp`. These exceptions can be related to a format, a pass or a converter. Exceptions named `*Internal*` are raised when something that should not happen occurs: this to avoid ugly crashes later in the execution.

All the exception classes are derived from `mfException`, that contains:

```

1 class EXP mfException: public exception
2 {
3     public:
4
5         // constructors/destructor
6         // -----
7
8         mfException (
9             string const& exceptionDescription = "",
10             int          exceptionNumber = 0,
11             int          exceptionLevel = 0
12         ) throw ()
13         : fExceptionDescription (
14             "mfException: " + exceptionDescription),
15           fExceptionNumber (exceptionNumber),
16           fExceptionLevel (exceptionLevel)
17         {}
18
19         // ... ..
20
21     private:
22
23         string          fExceptionDescription;
24
25         int             fExceptionNumber;
26         int             fExceptionLevel;
27 };

```

An example of exception is:

```

1 class EXP mxsr2msrException: public mfException
2 {
3     public:
4         mxsr2msrException (string const& exceptionDescription) throw ()
5         : mfException (exceptionDescription)
6         {}
7 };
8 typedef SMARTP<musicxmlException> S_musicxmlException;

```

There are warning and error reporting functions in `src/wae/wae.h.h/.cpp`. Examples are:

```

1 void oahAtomExpectingAValue::applyElement (ostream& os)
2 {
3     stringstream s;
4
5     s <<
6         "Applying atom expecting a value '" <<
7         fetchNames () <<
8         "' without a value";
9
10    oahInternalError (s.str ());

```

```
11 }
```

and:

```
1  case msrPedal::k_NoPedalType:
2  {
3      // should not occur
4
5      stringstream s;
6
7      s <<
8          "msrPedal '" <<
9          elt->asShortString () <<
10         "' has no pedal type";
11
12     msrInternalError (
13         gGlobalServiceRunData->getInputSourceName (),
14         inputLineNumber,
15         __FILE__, __LINE__,
16         s.str ());
17 }
18 break;
```

Another one is:

```
1 void mxsr2msrTranslator::visitEnd ( S_accordion_registration& elt )
2 {
3     int inputLineNumber =
4         elt->getInputLineNumber ();
5
6     #ifdef TRACING_IS_ENABLED
7         if (gGlobalMxsrOahGroup->getTraceMxsrVisitors ()) {
8             gLogStream <<
9                 "--> End visiting S_accordion_registration" <<
10                ", line " << inputLineNumber <<
11                endl;
12         }
13     #endif
14
15     // An accordion-registration element needs to have
16     // at least one of the child elements present
17
18     if (fCurrentAccordionNumbersCounter == 0) {
19         musicxmlWarning (
20             gGlobalServiceRunData->getInputSourceName (),
21             inputLineNumber,
22             "accordion-registration has 0 child element, ignoring it");
23     }
24
25     else {
26         // create the accordion registration
27         S_msrAccordionRegistration
28             accordionRegistration =
29             msrAccordionRegistration::create (
30                 inputLineNumber,
31                 fCurrentAccordionHigh,
32                 fCurrentAccordionMiddle,
33                 fCurrentAccordionLow);
34
35         // append it to the current part
36         fCurrentPart->
37             appendAccordionRegistrationToPart (
38                 accordionRegistration);
39     }
40 }
```

14.14 Exporting symbols for Windows DLLs

Windows needs export specifications for the symbols used by clients of a DLL.

<https://docs.microsoft.com/en-us/cpp/build/exporting-from-a-dll-using-declspec-dllexport?view=msvc-160> is titled "Exporting from a DLL Using `__declspec(dllexport)`". It states that:

- to export functions, the `__declspec(dllexport)` keyword must appear to the left of the calling-convention keyword, if a keyword is specified. For example:

```
1 __declspec(dllexport) void __cdecl Function1(void);
```

- to export all of the public data members and member functions in a class, the keyword must appear to the left of the class name as follows:

```
1 class __declspec(dllexport) CExampleExport : public CObject
2 { ... class definition ... };
```

MusicFormats uses symbol `EXP`, supplied by `libmusicxml/samples/`.

It is defined in `libmusicxml/src/elements!exports.h` to be empty except on Windows, where it is a default visibility attribute:

```
1 #ifndef __exports__
2 #define __exports__
3
4 #if defined(WIN32) // && !defined (GCC)
5
6 # ifdef MSVC
7 #  pragma warning (disable : 4267)
8 #  pragma warning (disable : 4275)
9 #  pragma warning (disable : 4251)
10 #  pragma warning (disable : 4786)
11 #  pragma warning (disable : 4251)
12 #  pragma warning (disable : 4275)
13 # endif
14
15 # ifdef LIBMUSICXML_EXPORTS
16 #  define EXP __declspec(dllexport)
17
18 # elif defined(LIBMUSICXML_STATIC)
19 #  define EXP
20
21 # else
22 #  define EXP __declspec(dllimport)
23 # endif
24
25 #else
26
27 # ifdef LIBMUSICXML_EXPORTS
28 #  define EXP __attribute__((visibility("default")))
29 # else
30 #  define EXP
31 # endif
32
33 #endif
34
35 #endif
```

14.15 Dynamic type checking

Enumeration type `s` are not ideal to distinguish variants when inheritance is used, mainly because adding new derived types imposes the addition of new constants, thus impacting other areas in the code base.

`dynamic_cast` is used in those cases, such as:

```

1  // handle the option
2  if (
3      // options group?
4      S_oahGroup
5      group =
6          dynamic_cast<oahGroup*>(&(*element))
7  ) {
8      registerOahElementUse (
9          group, optionNameUsed, ""); // "===group==="; // JMI to debug
10 }
11
12 else if (
13     // options subgroup?
14     S_oahSubGroup
15     subGroup =
16         dynamic_cast<oahSubGroup*>(&(*element))
17 ) {
18     registerOahElementUse (
19         subGroup, optionNameUsed, ""); // "===subGroup==="; // JMI to debug
20 }

```

14.16 Input line numbers

The passes and converters in MusicFormats convert formats of scores from one format to another. In order to produce helpful warning and error messages, several descriptions contain a field:

```

1  int fInputLineNumber;

```

An input line number in the `xmlelement` class is the only thing that has had to be added to `libmusicxml2` for the needs of MusicFormats.

Also, many methods contain an `int inputLineNumber` parameter, which is always the first one:

```

1  msrElement::msrElement (
2      int inputLineNumber)
3  {
4      fInputLineNumber = inputLineNumber;
5  }

```

Such input line numbers can be present in the output of the converters, such as:

```

1  jacquesmenu@macmini: ~/musicformats-git-dev/files > xml2ly -query input-line-numbers
2  --- Help for atom "input-line-numbers" in subgroup "Output"
3      -iln, -input-line-numbers
4          Generate after each note and barLine a comment containing
5          its MusicXML input line number.
6          This is useful when debugging xml2ly.

```

Generators such as Mikrokosmos3Wandering don't read any input, and the input line numbers they use are the ones in the source code, which is helpful for debugging. For example:

```

1 S_msrStaff Mikrokosmos3WanderingGenerator::createStaffInPart (
2   int staffNumber, S_msrPart part)
3 {
4   // create the staff
5   S_msrStaff
6   staff =
7       msrStaff::create (
8           __LINE__, msrStaffKind::kStaffKindRegular, staffNumber, part);
9
10  // append it to the part
11  part ->
12      addStaffToPartCloneByItsNumber ( // JMI NOT clone???
13          staff);
14
15  return staff;
16 }

```

In all output produced by MusicFormats tools, including trace informations and comments in the generated output referring to the input data, line numbers appear as:

```
1 line <number>
```

with a single space before the number, as in:

```
1 e16 %{ line 153 %} ] %{ line 163 kBeamEnd %}
```

This helps locating such occurrences in the debug process.

14.17 Static declarations

They are used for:

- classes methods such as method `msrTie::create ()`, method `msrTempo::createTempoPerMinute ()` and method `msrTemp::tempoKindAsString ()`;
- classes constant fields such as constant `msrStanza::K_NO_STANZA_NUMBER`, to be preferred to C-style `#define` preprocessor specifications for type safety;
- functions of methods remanent variables such as function private variable `pPrivateThisMethodHasBeenRun` in function `initializeMsrGenerationAPI ()`;
- library-wide variables such as global variable `gGlobalOutputStreamIndenter` and global variable `gGlobalTimingItem` that would be too cumbersome to pass to each and every method or function that uses them.

14.18 Avoiding MusicFormats multiple initializations

Such behaviour would create data structures several times, the result being unnecessary activities being performed. Avoiding it is done with function private variable `pPrivateThisMethodHasBeenRun`, here in [src/formats/bsr/bsr.cpp](#):

```

1 void initializeBSR ()
2 {
3     // protect library against multiple initializations
4     static Bool pPrivateThisMethodHasBeenRun (false);
5
6     if (! pPrivateThisMethodHasBeenRun) {
7         initializeBsrBasicTypes ();
8
9         pPrivateThisMethodHasBeenRun = true;
10    }
11 }

```

14.19 Enumeration types

All enumeration types use the C++17 'enum class' feature, such as:

```

1 enum class msrSlurTypeKind {
2     k_NoSlur,
3
4     kSlurTypeRegularStart, kSlurTypePhrasingStart,
5     kSlurTypeContinue,
6     kSlurTypeRegularStop, kSlurTypePhrasingStop
7 };

```

This prevents enumeration constants name conflicts across enumeration types, and qualified names such as constant `msrSlurTypeKind::kSlurTypeRegularStart` are quite explicit.

Many enumerations names end in 'Kind', which is a way distinguish them from rather similar classes names in some cases.

Enumeration constants in the form `k_No*` are used to indicate a value that *has not been set yet*. There are always the first on in the corresponding enumeration, to benefit from the the C++17 implicit initialization to the the equivalent of 0.

An enumeration constant may end in 'None', meaning that "none" is actually a possible value for the corresponding type:

```

1 // repeat winged
2 enum msrBarLineRepeatWingedKind {
3     kBarLineRepeatWingedNone,
4
5     kBarLineRepeatWingedStraight, kBarLineRepeatWingedCurved,
6     kBarLineRepeatWingedDoubleStraight, kBarLineRepeatWingedDoubleCurved
7 };

```

Here how the "winged" MusicXML attribute of `<repeat/>` is analysed in :

```

1 void mxsr2msrTranslator::visitStart ( S_repeat& elt )
2 {
3     // ... ..
4
5     string winged = elt->getAttributeValue ("winged");
6
7     fCurrentBarLineRepeatWingedKind =
8         msrBarLine::kBarLineRepeatWingedNone; // default value
9
10    if (winged.size ()) {
11        if (winged == "none") {
12            fCurrentBarLineRepeatWingedKind =
13                msrBarLine::kBarLineRepeatWingedNone;
14        }
15    }
16 }

```



```

15     else if (winged == "straight") {
16         fCurrentBarLineRepeatWingedKind =
17             msrBarLine::kBarLineRepeatWingedStraight;
18     }
19     else if (winged == "curved") {
20         fCurrentBarLineRepeatWingedKind =
21             msrBarLine::kBarLineRepeatWingedCurved;
22     }
23     else if (winged == "double-straight") {
24         fCurrentBarLineRepeatWingedKind =
25             msrBarLine::kBarLineRepeatWingedDoubleStraight;
26     }
27     else if (winged == "double-curved") {
28         fCurrentBarLineRepeatWingedKind =
29             msrBarLine::kBarLineRepeatWingedDoubleCurved;
30     }
31     else {
32         stringstream s;
33
34         s <<
35             "repeat winged \"" << winged <<
36             "\" is unknown";
37
38         musicxmlError (
39             gGlobalServiceRunData->getInputSourceName (),
40             inputLineNumber,
41             __FILE__, __LINE__,
42             s.str ());
43     }
44 }
45
46 // ... ..

```

The MusicFormats enumeration type `s` come with a `<<` operator to display their values in a user friendly way, such as type `msrChordInKind` in `src/formats/msr/msrBasicTypes.h/.cpp`:

```

1  enum class msrChordInKind {
2      k_NoChordIn,
3
4      kChordInMeasure,
5      kChordInTuplet,
6      kChordInGraceNotesGroup
7  };
8
9  EXP string msrChordInKindAsString (
10     msrChordInKind chordInKind);
11
12 ostream& operator<< (ostream& os, const msrChordInKind& elt);

```

The implementation is:

```

1  string msrChordInKindAsString (
2     msrChordInKind chordInKind)
3  {
4     string result;
5
6     switch (chordInKind) {
7         case msrChordInKind::k_NoChordIn:
8             result = "***k_NoChordIn***";
9             break;
10         case msrChordInKind::kChordInMeasure:
11             result = "kChordInMeasure";
12             break;
13         case msrChordInKind::kChordInTuplet:
14             result = "kChordInTuplet";
15             break;

```

```

16     case msrChordInKind::kChordInGraceNotesGroup:
17         result = "kChordInGraceNotesGroup";
18         break;
19     } // switch
20
21     return result;
22 }
23
24 ostream& operator<< (ostream& os, const msrChordInKind& elt)
25 {
26     os << msrChordInKindAsString (elt);
27     return os;
28 }

```

14.20 yes/no enumerations types

Boolean argument to methods calls are fine in simple cases such as:

```

1 void setCombinedBooleanVariables (Bool value);

```

But when there are multiple arguments, the semantics of the `true` or `false` constants is far from obvious.

This is why we use enum classes such as:

```

1 enum class msrVoiceCreateInitialLastSegmentKind {
2     kCreateInitialLastSegmentYes,
3     kCreateInitialLastSegmentNo
4 };

```

in such cases, so that the arguments have a clear semantics:

```

1 fPartHarmoniesVoice =
2     msrVoice::create (
3         inputLineNumber,
4         msrVoiceKind::kVoiceKindHarmonies,
5         partHarmoniesVoiceNumber,
6         msrVoiceCreateInitialLastSegmentKind::kCreateInitialLastSegmentYes,
7         fPartHarmoniesStaff);

```

14.21 Boolean values anyway

Defining a yes/no enumeration type for 'true' boolean values such as the variables containing the OAH options would be cumbersome. The C++ `bool` type suffers from the C heritage, in which integers and even pointers can be mixed in and considered as boolean values.

Moreover, a `bool` variable not explicitly initialized in the developer's code can lead to hard to fix bugs, in particular when the MusicFormats library is used on various hardware and operating systems.

For these reasons, MusicFormats features a class `Bool` defined in `src/utilities/mfBool.h/.cpp`. It encapsulates the actual `bool` value, enforcing that its initial value is not random, but known to the developer, through constructors. This also avoids in particular long sequences of initializations in the passes constructors.

14.22 On/off values

Some elements in MusicFormats are represented by a *three-state* value.

On/off values are handled by enumeration type `mfOnOffKind`, declared in `src/mflibrarymfOnOff.h`:

```

1 // -----
2 enum class mfOnOffKind {
3     kMfOnOffUnknown,
4     kMfOnOffOn, kMfOnOffOff
5 };
6
7 Bool mfOnOffKindAsBool (
8     mfOnOffKind onOffKind);
9
10 string mfOnOffKindAsString (
11     mfOnOffKind onOffKind);
12
13 ostream& operator<< (ostream& os, const mfOnOffKind elt);

```

This is the case for example of page ragging information in `src/formats/lpsr//lpsr/lpsrPapers.h`:

```

1 // on/off values
2 mfOnOffKind          fRaggedBottom;
3 S_oahOnOffAtom       fRaggedBottomAtom;
4
5 mfOnOffKind          fRaggedLast;
6 S_oahOnOffAtom       fRaggedLastAtom;
7
8 mfOnOffKind          fRaggedLastBottom;
9 S_oahOnOffAtom       fRaggedLastBottomAtom;
10
11 mfOnOffKind          fRaggedRight;
12 S_oahOnOffAtom       fRaggedRightAtom;

```

Care must be taken in `src/mflibrarymfOnOff.cpp` when converting an enumeration type `mfOnOffKind` value to type `Bool`:

```

1 Bool mfOnOffKindAsBool (
2     mfOnOffKind onOffKind)
3 {
4     Bool result;
5
6     switch (onOffKind) {
7         case mfOnOffKind::kMfOnOffUnknown:
8             {
9                 mfError (
10                     __FILE__, __LINE__,
11                     "mfOnOffKind::kMfOnOffUnknown cannot be converted to Bool");
12             }
13             break;
14         case mfOnOffKind::kMfOnOffOn:
15             result = true;
16             break;
17         case mfOnOffKind::kMfOnOffOff:
18             result = false;
19             break;
20     } // switch
21
22     return result;
23 }

```

14.23 Iterating over numeration types

Such iterations rely on template classes. For this to work, the enumeration type should provide specific `AllFirst` and `AllLast` 'aliases' for the first and last constants in the type.

This is done for enumeration type `msrHarmonyKind` in `src/formats/msr/msrBasicTypes.h`:

```

1 // harmonies
2 // -----
3 enum class msrHarmonyKind {
4     k_NoHarmony,
5
6     // MusicXML harmonies
7
8     kHarmonyMajor, kHarmonyMinor,
9     kHarmonyAugmented, kHarmonyDiminished,
10
11     // ... ..
12
13     // other
14
15     kHarmonyOther,
16
17     kHarmonyNone,
18
19     // aliases
20     // -----
21
22     AllFirst = k_NoHarmony,
23     AllLast  = kHarmonyNone,
24
25     // ... ..
26 };

```

Class `mfEnumAll` is defined in `src/mfutilities/mfEnumAll.h`:

```

1 // -----
2 /*
3  https://stackoverflow.com/questions/8498300/allow-for-range-based-for-with-enum-classes
4  */
5 template< typename T >
6 class mfEnumAll
7 {
8     public:
9
10     class Iterator
11     {
12     public:
13
14         Iterator (int value)
15             : fIterationIndex (value)
16             {}
17
18         T operator* (void) const
19             { return (T) fIterationIndex; }
20
21         void operator++ (void)
22             { ++fIterationIndex; }
23
24         Bool operator != (Iterator rhs)
25             { return fIterationIndex != rhs.fIterationIndex; }
26
27     private:
28
29         int fIterationIndex;
30 };

```

```

31 };
32
33 template< typename T >
34 typename mfEnumAll<T>::Iterator begin (mfEnumAll<T>)
35 {
36     return typename mfEnumAll<T>::Iterator ((int)T::AllFirst);
37 }
38
39 template< typename T >
40 typename mfEnumAll<T>::Iterator end (mfEnumAll<T>)
41 {
42     return typename mfEnumAll<T>::Iterator (((int)T::AllLast) + 1);
43 }

```

The mfEnumAll template class, defined in `src/mfutilities/mfEnumAll.h` can then be used to iterate from constant `msrHarmonyKind::AllFirst` to constant `msrHarmonyKind::AllLast`, here in `src/formats/msr/msrBasicTypes.h`

```

1 void initializeHarmonyStructuresMap ()
2 {
3     // protect library against multiple initializations
4     static Bool pPrivateThisMethodHasBeenRun (false);
5
6     if (! pPrivateThisMethodHasBeenRun) {
7         for (auto e : mfEnumAll<msrHarmonyKind> ()) {
8             // create the harmony structure
9             S_msrHarmonyStructure
10             harmonyStructure =
11                 msrHarmonyStructure::create (
12                     e);
13
14             // register it in the map
15             gGlobalHarmonyStructuresMap [e] =
16                 harmonyStructure;
17         } // for
18
19         pPrivateThisMethodHasBeenRun = true;
20     }
21 }

```

The mfEnumAll template class, defined in `src/mfutilities/mfEnumAll.h` can then be used to iterate from constant `msdlTokenKind::AllFirst` to constant `msdlTokenKind::AllLast`, here in `src/formats/msdl/msdlTokens.h`

```

1     for (auto e : EnumNonSeparators<msdlTokenKind> ()) {
2         string
3         nonSeparatorTokenAsMsdlString =
4             msdlTokenKindAsMsdlString (
5                 e,
6                 keywordsLanguageKind);
7
8         // ... ..
9     } // for

```

All such class Enum* classes in MusicFormats are:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src > grep -r 'class Enum' *
2 formats/msdl/msdlTokens.h:class EnumNonSeparators
3 formats/msdl/msdlTokens.h:class EnumLanguageIndependent
4 formats/msdl/msdlTokens.h:class EnumLanguageDependent
5 formats/msr/msrBasicTypes.h:class EnumTrueHarmonies
6 utilities/mfutilities.h:class mfEnumAll

```

For example class EnumTrueHarmonies, that relies on constant `msrHarmonyKind::TrueHarmoniesFirst` and constant `msrHarmonyKind::TrueHarmoniesLast`:

```

1 void msrHarmonyStructure::printAllHarmoniesStructures (ostream& os)
2 {
3     os <<
4     "All the known harmonies structures are:" <<
5     endl << endl;
6
7     ++gIndenter;
8
9     for (auto e : EnumTrueHarmonies<msrHarmonyKind> ()) {
10        // create the harmony intervals
11        S_msrHarmonyStructure
12        harmonyStructure =
13        msrHarmonyStructure::create (
14            e);
15
16        // print it
17        os <<
18        harmonyStructure <<
19        endl;
20    } // for
21
22    --gIndenter;
23 }

```

14.24 Rational numbers

MusicFormats uses rationals for notes sounding and display whole notes and positions in measures, among others. Class `rational` is defined by `libmusicxml2` in `libmusicxml/src/lib!rational.h/.cpp`:

```

1 class EXP rational {
2
3     private:
4
5         long int fNumerator;
6         long int fDenominator;
7
8         // Used by rationalise()
9         long int gcd(long int a, long int b);
10
11     public:
12
13         rational(long int num = 0, long int denom = 1);
14         rational(const rational& d);
15         rational(const string &str);
16
17         // ... ..
18 };

```

Rationals are not used, however, for triplets factors, see .

14.25 Default values

The guide lines for MusicFormats in this matter are:

- smart pointers are initialized to `nullptr` in the class `SMARTP` constructor (they're smart after all), defined by `libmusicxml2` in `libmusicxml/src/lib!smartpointer.h`:

```

1 template<class T> class SMARTP {
2     private:
3         ///! the actual pointer to the class
4         T* fSmartPtr;
5
6     public:
7         ///! an empty constructor - points to null
8         SMARTP() : fSmartPtr(0) {}
9
10        // ... ..

```

- all variables and classes fields of non-class types, such as `int`, `float` and enumeration type `s`, are to be initialized explicitly;
- MusicFormats functions and methods parameters never have default values: overloading is used instead.

14.26 create* methods

All concrete classes, i.e. those that are not pure virtual, have `create* ()` methods paired with a constructor with the exact same parameters.

In most cases, there are just named `create* ()`, but a couple of them have more explicit names.

One case is that of class `msrTempo` in `src/formats/msr/msrTempos.h/.cpp`, because calls to them would be hard to distinguish at first glance otherwise:

```

1 class EXP msrTempo : public msrMeasureElement
2 {
3     // ... ..
4
5     static SMARTP<msrTempo> createTempoWordsOnly (
6         int                inputLineNumber,
7         S_msrWords         tempoWords);
8
9     static SMARTP<msrTempo> createTempoPerMinute (
10        int                inputLineNumber,
11        msrDottedDuration  tempoBeatUnit,
12        string             tempoPerMinute,
13        msrTempoParenthesizedKind
14            tempoParenthesizedKind,
15        msrPlacementKind  tempoPlacementKind);
16
17    static SMARTP<msrTempo> createTempoBeatUnitEquivalent (
18        int                inputLineNumber,
19        msrDottedDuration  tempoBeatUnit,
20        msrDottedDuration  tempoEquivalentBeatUnit,
21        msrTempoParenthesizedKind
22            tempoParenthesizedKind,
23        msrPlacementKind  tempoPlacementKind);
24
25    static SMARTP<msrTempo> createTempoNotesRelationship (
26        int                inputLineNumber,
27        S_msrTempoNotesRelationshipshipElements
28            tempoNotesRelationshipLeftElements,
29        msrTempoNotesRelationshipKind
30            tempoNotesRelationshipKind,
31        S_msrTempoNotesRelationshipshipElements
32            tempoNotesRelationshipRightElements,
33        msrTempoParenthesizedKind
34            tempoParenthesizedKind,
35        msrPlacementKind  tempoPlacementKind);

```

```

36
37     // ... ..
38 };

```

Another case is that of class `msrKey` in `src/formats/msr/msrKeys.h/.cpp`, in which the variant chosen is made explicit:

```

1 class EXP msrKey : public msrMeasureElement
2 {
3     // ... ..
4
5     static SMARTP<msrKey> createTraditional (
6                                     int             inputLineNumber ,
7                                     msrQuarterTonesPitchKind keyTonicPitchKind ,
8                                     msrModeKind         modeKind ,
9                                     int             keyCancel);
10
11     static SMARTP<msrKey> createHumdrumScot (
12         int             inputLineNumber);
13
14     // ... ..
15 };

```

14.27 `get*()`, `set*()` and `fetch*()` methods

As is usual, classes private member variables are accessed through `set*()` () and `get*()` () methods. The name of these methods is obtained by replacing the 'f' in the field name by 'set' and 'get', respectively. In `src/formats/msr/msrTies.h`, one finds:

```

1     // set and get
2     // -----
3
4     void                setTieKind (msrTieKind tieKind)
5                           { fTieKind = tieKind; }
6
7     msrTieKind          getTieKind () const
8                           { return fTieKind; }
9
10    void                setTiePlacementKind (msrPlacementKind placementKind)
11                           { fTiePlacementKind = placementKind; }
12
13    msrPlacementKind     getTiePlacementKind () const
14                           { return fTiePlacementKind; }

```

`fetch` is used when the result is not store in a variable, but has to computed in some way. `src/formats/msr/msrSegme` contains:

```

1 S_msrStaff msrSegment::fetchSegmentStaffUpLink () const
2 {
3     S_msrStaff result;
4
5     if (fSegmentVoiceUpLink) {
6         result =
7             fSegmentVoiceUpLink->
8                 getVoiceStaffUpLink ();
9     }
10
11     return result;
12 }

```


Some methods exist in two versions, the second one with a `NonConst` suffix in the name. This can be the case if a private class field is to be modified outside the class, or if there are specific needs.

This happens for example in `src/formats/msr/mfslNotes.h/.cpp`:

```

1 // articulations
2 const list<S_msrArticulation>&
3     getNoteArticulations () const
4     { return fNoteArticulations; }
5
6 list<S_msrArticulation>&
7     getNoteArticulationsNonConst ()
8     { return fNoteArticulations; }

```

Another case is in `src/interpreters/mfsl/mfslDriver.h/.cpp`:

```

1 const yy::location& getScannerLocation () const
2     { return fScannerLocation; }
3
4 yy::location& getScannerLocationNonConst ()
5     // no const here
6     // due to constraints in the Flex-generated code
7     { return fScannerLocation; }

```

14.28 initialize*() and finalize*() methods

When a description contains many fields, the ones initialized by the values of the constructor's parameters are initialized in the latter, and the others are in an `initialize*() ()` method, such as:

```

1 msrPart::msrPart (
2     int            inputLineNumber,
3     string         partID,
4     S_msrPartGroup partPartGroupUpLink)
5     : msrPartGroupElement (inputLineNumber)
6 {
7     // replace spaces in partID to set fPartID
8     for_each (
9         partID.begin (),
10        partID.end (),
11        mfStringSpaceReplacer (fPartID, '_'));
12
13 /* JMI
14 // sanity check
15 mfAssert (
16     __FILE__, __LINE__,
17     partPartGroupUpLink != nullptr,
18     "partPartGroupUpLink is null");
19 */
20
21 // set part number
22 fPartAbsoluteNumber = ++gPartsCounter;
23
24 // set part's part group upLink
25 fPartPartGroupUpLink = partPartGroupUpLink;
26
27 // do other initializations
28 initializePart ();
29 }

```

Some `finalize*() ()` methods exist.

14.29 *asString() and *fromString() functions

Each enumeration type comes with an `*AsString()` () function, to display the constant values as strings. Some also have a `fromString` () function to convert strings to the corresponding constant. For example, one finds in `src/formats/msr/msrBasicTypes.h/.cpp`:

```
1 // placement
2 // -----
3 enum class msrPlacementKind {
4     k_NoPlacement,
5
6     kPlacementAbove, kPlacementBelow
7 };
```

```
1 // placement
2 // -----
3 msrPlacementKind msrPlacementKindFromString (
4     int     inputLineNumber,
5     string  placementString)
6 {
7     msrPlacementKind result = msrPlacementKind::k_NoPlacement; // default value
8
9     if      (placementString == "above")
10         result = msrPlacementKind::kPlacementAbove;
11     else if (placementString == "below")
12         result = msrPlacementKind::kPlacementBelow;
13     else {
14         if (placementString.size ()) {
15             stringstream s;
16
17             s <<
18                 "placement \"" << placementString <<
19                 "\" should be 'above' or 'below'";
20
21             musicxmlError (
22                 gGlobalServiceRunData->getInputSourceName (),
23                 inputLineNumber,
24                 __FILE__, __LINE__,
25                 s.str ());
26         }
27     }
28
29     return result;
30 }
```

```
1 string msrPlacementKindAsString (
2     msrPlacementKind placementKind)
3 {
4     string result;
5
6     switch (placementKind) {
7         case msrPlacementKind::k_NoPlacement:
8             result = "noPlacement";
9             break;
10        case msrPlacementKind::kPlacementAbove:
11            result = "placementAbove";
12            break;
13        case msrPlacementKind::kPlacementBelow:
14            result = "placementBelow";
15            break;
16    } // switch
17
18    return result;
19 }
```

Many classes have `asStringShort()` () methods to provide more compact a description as the one provided by the corresponding `asString()` () method.

14.30 `translate*()` methods and `convert*()` functions

To `translate` and to `convert` are aliases in the context of `MusicFormats`.

For semantic clearness, `translate*()` () methods are supplied by the individual translators, as in `src/passes/msr2m`

```

1 // -----
2 class EXP msr2msrTranslator :
3
4     // MSR score
5
6     public visitor<S_msrScore>,
7
8     // ... ..
9
10 {
11     public:
12
13         msr2msrTranslator ();
14
15         virtual ~msr2msrTranslator ();
16
17         S_msrScore translateMsrToMsr (
18             S_msrScore theMsrScore);
19
20     // ... ..
21 };

```

```

1 S_msrScore msr2msrTranslator::translateMsrToMsr (
2     S_msrScore theMsrScore)
3 {
4     // sanity check
5     mfAssert (
6         __FILE__, __LINE__,
7         theMsrScore != nullptr,
8         "theMsrScore is null");
9
10    // the MSR score we're visiting
11    fVisitedMsrScore = theMsrScore;
12
13    // create the resulting MSR score
14    fResultingNewMsrScore =
15        msrScore::create (
16            K_NO_INPUT_LINE_NUMBER,
17            "msrScore::create()");
18
19    // create a msrScore browser
20    msrBrowser<msrScore> browser (this);
21
22    // browse the visited score with the browser
23    browser.browse (*fVisitedMsrScore);
24
25    // forget about the visited MSR score
26    fVisitedMsrScore = nullptr;
27
28    return fResultingNewMsrScore;
29 }

```

The `convert*()` () functions are the interfaces to the translators, for example in `src/passes/msr2msr/msr2msrInte`

```

1 S_msrScore translateMsrToMsr (
2     S_msrScore      originalMsrScore,
3     S_msr0ahGroup    msr0pts,
4     S_msr2msr0ahGroup msr2msr0pts,
5     const string&     passNumber,
6     const string&     passDescription)
7 {
8     // ... ..
9
10    // the msr2msrTranslator
11    msr2msrTranslator
12        translator;
13
14    // build the resulting MSR score
15    S_msrScore
16        resultingNewMsrScore =
17        translator.translateMsrToMsr (
18            originalMsrScore);
19
20    // ... ..
21 }

```

14.31 context arguments

Some methods have such an argument, a string, to provide helpful information to the maintainer of MusicFormats. An example is method `msrMeasureRepeat::displayMeasureRepeat ()`, defined in `src/formats/msr/msrMeasureRepeat.cpp`.

```

1 void msrMeasureRepeat::displayMeasureRepeat (
2     int      inputLineNumber,
3     const string& context)
4 {
5     gLogStream <<
6     endl <<
7     "*****>> MeasureRepeat " <<
8     ", measureRepeatMeasuresNumber: '" <<
9     fMeasureRepeatMeasuresNumber <<
10    ", measureRepeatSlashesNumber: '" <<
11    fMeasureRepeatSlashesNumber <<
12    "', voice:" <<
13    endl <<
14    fMeasureRepeatVoiceUpLink->getVoiceName () <<
15    " (" << context << ")" <<
16    ", line " << inputLineNumber <<
17    " contains:" <<
18    endl;
19
20    ++gIndenter;
21    print (gLogStream);
22    --gIndenter;
23
24    gLogStream <<
25    " <<*****" <<
26    endl << endl;

```

An call example in `src/formats/msr/msrVoices.h` is:

```

1 displayVoiceMeasureRepeatAndVoice (
2     inputLineNumber,
3     "createMeasureRepeatFromItsFirstMeasures() 1");

```

14.32 Sorting and compare*() methods

MusicFormats sometimes needs to sort some data structures:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src > grep -r '\.sort (' *
2 oah/oahBasicTypes.cpp:  optionsMapElementsNamesList.sort ();
3 passes/lpsr2lilypond/lpsr2lilypondTranslator.cpp:  frameFrameNotesList.sort (
4 formats/msr/msrMeasuresSlices.cpp:  fSliceNotesFlatList.sort (
5 formats/msr/msrMeasuresSlices.cpp:  fSliceNoteEventsList.sort (
6 formats/msr/msrStaves.cpp:  fStaffAllVoicesList.sort (
7 formats/msr/msrStaves.cpp:  fStaffAllVoicesList.sort (
8 formats/msr/msrStaves.cpp:  fStaffRegularVoicesList.sort (
9 formats/msr/msrMeasures.cpp:  fMeasureElementsList.sort (
10 formats/msr/msrMeasures.cpp:  fMeasureElementsList.sort (
11 formats/msr/msrParts.cpp:  fPartAllStavesList.sort (
12 formats/msr/msrParts.cpp:  fPartAllStavesList.sort (
13 formats/lpsr/lpsrParts.cpp:  fPartBlockElementsList.sort (

```

There are thus a number of compare* () methods according to the needs:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src > grep -r compare * | grep '\.h'
2 oah/oahBasicTypes.h:  const multiset<S_oahElement, compareOahElements>&
3 oah/oahBasicTypes.h:  multiset<S_oahElement, compareOahElements>
4 oah/oahElements.h:struct compareOahElements {
5 formats/msr/msrParts.h:  static bool
6   compareStavesToHaveFiguredBassElementsBelowCorrespondingPart (
7 formats/msr/msrNotes.h:  static bool  compareNotesByIncreasingPositionInMeasure
8   (
9 formats/msr/msrMeasureElements.h:  static bool
10   compareMeasureElementsByIncreasingPositionInMeasure (
11 formats/msr/msrStaves.h:  static bool  compareVoicesByIncreasingNumber (
12 formats/msr/msrStaves.h:  static bool
13   compareVoicesToHaveHarmoniesAboveCorrespondingVoice (
14 formats/msr/msrStaves.h:  static bool
15   compareVoicesToHaveFiguredBassElementsBelowCorrespondingVoice (
16 formats/msr/msrMeasuresSlices.h:  static bool
17   compareNotesEventsByIncreasingPositionInMeasure (
18 formats/msr/msrMeasuresSlices.h:  static bool
19   compareSimultaneousNotesChunksByIncreasingPositionInMeasure (
20 formats/lpsr/lpsrParts.h:  static bool
21   compareElementsToHaveHarmoniesAboveCorrespondingStaff (
22 formats/lpsr/lpsrParts.h:  static bool  compareStaffBlockWithOtherElement (
23 formats/lpsr/lpsrParts.h:  static bool
24   compareChordNamesContextWithOtherElement (
25 utilities/mfutilities.h:  // compare indentation value

```

An example is:

```

1 bool msrPart::compareStavesToHaveFiguredBassElementsBelowCorrespondingPart (
2   const S_msrStaff& first,
3   const S_msrStaff& second)
4 {
5   int
6   firstStaffNumber =
7   first->getStaffNumber (),
8   secondStaffNumber =
9   second->getStaffNumber ();
10
11   if (firstStaffNumber > msrPart::K_PART_FIGURED_BASS_STAFF_NUMBER) {
12     firstStaffNumber -= msrPart::K_PART_FIGURED_BASS_STAFF_NUMBER + 1;
13   }
14   if (secondStaffNumber > msrPart::K_PART_FIGURED_BASS_STAFF_NUMBER) {
15     secondStaffNumber -= msrPart::K_PART_FIGURED_BASS_STAFF_NUMBER + 1;
16   }
17

```

```
18     bool result =  
19         firstStaffNumber > secondStaffNumber;  
20  
21     return result;  
22 }
```

Part IV

MusicFormats components

Chapter 15

MusicFormats components (MFC)

MusicFormats supports keeping the history of its components versions using a dedicated representation, as an alternative to separate release notes. The source files are in [src/components/](#).

15.1 Versions numbers

The basic data structure is class `mfcVersionNumber`:

```
1 class mfcVersionNumber: public smartable
2 {
3     // ... ..
4
5     public:
6
7         // public services
8         // -----
9
10        Bool                operator== (const mfcVersionNumber& other) const;
11
12        Bool                operator!= (const mfcVersionNumber& other) const;
13
14        Bool                operator<  (const mfcVersionNumber& other) const;
15
16        Bool                operator>= (const mfcVersionNumber& other) const;
17
18        Bool                operator>  (const mfcVersionNumber& other) const;
19
20        Bool                operator<= (const mfcVersionNumber& other) const;
21
22    public:
23
24        // print
25        // -----
26
27        string              asString () const;
28
29        void                print (ostream& os) const;
30
31    private:
32
33        // fields
34        // -----
35
36        int                 fMajorNumber;
37        int                 fMinorNumber;
38        int                 fPatchNumber;
```



```

39     string                fPreRelease;
40 };

```

15.2 Versions descriptions

Each component version is described by a class `mfcVersionDescr` instance:

```

1 class mfcVersionDescr : public smartable
2 {
3     // ... ..
4
5     private:
6
7         // fields
8         // -----
9
10        S_mfcVersionNumber    fVersionNumber;
11        string                fVersionDate;
12        list<string>          fVersionDescriptionItems;
13 };

```

15.3 Versions histories

An instance of `mfcVersionsHistory` is essentially a list of `mfcVersionDescr` instances:

```

1 class mfcVersionsHistory : public smartable
2 {
3     // ... ..
4
5     public:
6
7         // public services
8         // -----
9
10        void                appendVersionDescrToHistory (
11                               S_mfcVersionDescr versionDescr);
12
13        S_mfcVersionDescr    fetchMostRecentVersion () const;
14
15        S_mfcVersionNumber    fetchMostRecentVersionNumber () const;
16
17        // ... ..
18
19        protected:
20
21            // protected fields
22            // -----
23
24            list<S_mfcVersionDescr>
25                fVersionsList;
26 };

```

The current version of a component is the last one appended to `fVersionsList`:

```

1 S_mfcVersionDescr mfcVersionsHistory::fetchMostRecentVersion () const
2 {
3     // sanity check
4     mfAssert (
5         __FILE__, __LINE__,
6         fVersionsList.size () > 0,

```

```

7     "fVersionsList is empty");
8
9     return fVersionsList.back ();
10 }

```

15.4 Components descriptions

The components of MusicFormats are described by enumeration type `mfcComponenKind`:

```

1 enum class mfcComponenKind {
2     kComponentRepresentation,
3     kComponentPass,
4     kComponentGenerator,
5     kComponentConverter,
6     kComponentLibrary
7 };

```

The purely virtual class `mfcComponentDescr` is a superclass to the ones describing formats, passes, generators, converters and the MusicFormats library itself:

```

1 class mfcComponentDescr : public smartable
2 {
3     // ... ..
4
5     public:
6
7         // public services
8         // -----
9
10        S_mfcVersionDescr    fetchComponentMostRecentVersion () const
11                               {
12                               return
13                               fVersionsHistory->
14                               fetchMostRecentVersion ();
15                               }
16
17        // ... ..
18
19        public:
20
21            // print
22            // -----
23
24            string            asString () const;
25
26            string            mostRecentVersionNumberAndDateAsString () const;
27
28            virtual void      print (ostream& os) const;
29
30            virtual void      printVersion (ostream& os) const;
31            virtual void      printHistory (ostream& os) const;
32
33        protected:
34
35            // protected services
36            // -----
37
38            virtual void      printOwnHistory (ostream& os) const;
39
40        protected:
41
42            // protected fields
43            // -----

```

```

44
45     string                fComponentName;
46
47     mfcComponenKind       fComponenKind;
48
49     S_mfcVersionsHistory  fVersionsHistory;
50 };

```

The virtual `printVersion ()` and `printHistory ()` methods are called by the `--v`, `--version` and `--hist`, `--history` options to the various generators and converters.

Representations and passes have a single, linear history, whereas the generators, the converters and MusicFormats itself use several of them, each with its own history. This leads to a hierarchy of classes:

- class `mfcRepresentationComponent` for formats;
- class `mfcPassComponent` for passes;
- purely virtual class `mfcMultiComponent` for the generators, converters and MusicFormats library, itself the superclass of:
 - class `mfcGeneratorComponent`;
 - class `mfcConverterComponent`;
 - class `mfcLibraryComponent`.

Multi-components have their own history, hence field method `mfcComponentDescr::printOwnHistory ()`. Class `mfcMultiComponent` is described below.

15.5 Multi-components

Class `mfcMultiComponent` contains lists of the formats and passes used:

```

1  class mfcMultiComponent : public mfcComponentDescr
2  {
3      // ... ..
4
5      protected:
6
7          // protected fields
8          // -----
9
10         list<S_mfcRepresentationComponent>
11             fRepresentationComponentsList;
12         list<S_mfcPassComponent>
13             fPassComponentsList;
14
15         // should the version number be at least equal to
16         // the ones of the components?
17         mfcMultiComponentEntropicityKind
18             fComponentEntropicityKind;
19
20         mfcMultiComponentUsedFromTheCLIKind
21             fComponentUsedFromTheCLIKind;
22 };

```

Enumeration type `mfcMultiComponentEntropicityKind` is used to check that the version number of a `mfcMultiComponent` instance is at least equal to the version numbers of the formats and passes it uses:

```

1 enum class mfcMultiComponentEntropicityKind {
2     kComponentEntropicityYes,
3     kComponentEntropicityNo
4 };

```

Enumeration type `mfcMultiComponentUsedFromTheCLIKind` is used to display context sensitive output with the `-version`, `-v` and `-history`, `-hist` options when the library is used from command line tools or through the functional API:

```

1 enum class mfcMultiComponentUsedFromTheCLIKind {
2     kComponentUsedFromTheCLIYes,
3     kComponentUsedFromTheCLINo
4 };

```

This allows for the maintainers of little used tools not to worry about using components with version numbers greater than their own.

Only constant `mfcMultiComponentUsedFromTheCLIKind::kComponentUsedFromTheCLIYes` is used at the time of this writing.

Method `mfcMultiComponent::print ()` displays the regular version numbers:

```

1 jacquesmenu@macmini: ~ > xml2ly -version
2 Command line version of musicxml2lilypond converter v0.9.51 (October 12 2021)
3
4 Representations versions:
5   MXSR
6     v0.9.5 (October 6 2021)
7   MSR
8     v0.9.51 (October 14 2021)
9   LPSR
10    v0.9.5 (October 6 2021)
11
12 Passes versions:
13   mxsr2msr
14     v0.9.5 (October 6 2021)
15   msr2msr
16     v0.9.5 (October 6 2021)
17   msr2lpsr
18     v0.9.5 (October 6 2021)
19   lpsr2lilypond
20     v0.9.5 (October 6 2021)

```

Method `mfcMultiComponent::printHistory ()` displays information analogous to release notes:

```

1 jacquesmenu@macmini: ~ > xml2brl -history
2 Command line version of musicxml2braille converter v0.9.51 (October 12 2021)
3
4 Own history:
5   v0.9.5 (October 6 2021):
6     Start of sequential versions numbering
7
8   v0.9.51 (October 12 2021):
9     Fixed trace OAH issue
10
11 Representations history:
12   MXSR
13     v0.9.5 (October 6 2021):
14       Start of sequential versions numbering
15
16   MSR
17     v0.9.5 (October 6 2021):
18       Start of sequential versions numbering
19
20     v0.9.51 (October 14 2021):

```

```

21     Refined MSR names and summary display options
22
23     BSR
24     v0.9.5 (October 6 2021):
25         Start of sequential versions numbering
26
27 Passes history:
28     mxsr2msr
29     v0.9.5 (October 6 2021):
30         Start of sequential versions numbering
31
32     msr2msr
33     v0.9.5 (October 6 2021):
34         Start of sequential versions numbering
35
36     msr2bsr
37     v0.9.5 (October 6 2021):
38         Start of sequential versions numbering
39
40     bsr2bsr
41     v0.9.5 (October 6 2021):
42         Start of sequential versions numbering
43
44     bsr2braille
45     v0.9.5 (October 6 2021):
46         Start of sequential versions numbering

```

15.6 Versions history creation

MusicFormats uses *semantic* version numbering, such as v0.9.61:

- the library itself gets a new number right after a new branch as been created for it. Branching to "v0.9.61" causes the library to be numbered "v0.9.61" with `SetMusicFormatsVersionNumber.bash`;
- each representation, converter or pass that is modified this new branch has been created gets a new history element with the same number as the library.

The versions history must exist before the `-version`, `-v` and `-history`, `-hist` options are handled. They are thus created early by specific functions, placed in `*Component.h/.cpp` files.

The functions that create them ensure than that is done at most once.

15.6.1 Representations and passes components creation

This is done in `create*RepresentationComponent ()` and `create*PassComponent ()` functions, respectively.

For example, MSR versions are handled by function `createMsrRepresentationComponent ()` in `src/formats/msr/msrHistory.h/.cpp`:

```

1 S_mfcRepresentationComponent EXP createMsrRepresentationComponent ()
2 {
3     static S_mfcRepresentationComponent pRepresentationComponent;
4
5     // protect library against multiple initializations
6     if (! pRepresentationComponent) {
7
8     #ifdef TRACING_IS_ENABLED
9         if (gGlobalOahEarlyOptions.getEarlyTraceComponents ()) {

```

```

10     gLogStream <<
11         "Initializing MSR format component" <<
12         endl;
13     }
14 #endif
15
16     // create the format component
17     pRepresentationComponent =
18         mfcRepresentationComponent::create (
19             "MSR");
20
21     // populate it
22     pRepresentationComponent->
23         appendVersionDescrToComponent (
24             mfcVersionDescr::create (
25                 mfcVersionNumber::createFromString ("0.9.50"),
26                 "October 6, 2021",
27                 list<string> {
28                     "Start of sequential versions numbering"
29                 }
30             ));
31
32     pRepresentationComponent->
33         appendVersionDescrToComponent (
34             mfcVersionDescr::create (
35                 mfcVersionNumber::createFromString ("0.9.51"), // JMI
36                 "October 14, 2021",
37                 list<string> {
38                     "Refined MSR names and summary display options"
39                 }
40             ));
41     }
42
43     return pRepresentationComponent;
44 }

```

The conversion of MusicXML to MXSR does not belong to MusicFormats since it is provided by libmusicxml2.

15.6.2 Generators and converters components creation

In that case, the formats and passes components used by the multi-component should be created as well.

For example, the formats and passes used by the musicxml2braille converter are appended to the atoms versions list in its history in function `createMusicxml2brailleConverterComponent ()` in `src/converters/musicxml2braille/musicxml2brailleConverterComponent.cpp`:

```

1 S_mfcConverterComponent EXP createMusicxml2brailleConverterComponent ()
2 {
3     static S_mfcConverterComponent pConverterComponent;
4
5     // protect library against multiple initializations
6     if (! pConverterComponent) {
7
8 #ifdef TRACING_IS_ENABLED
9         if (gGlobalOptions.getEarlyTraceComponents ()) {
10             gLogStream <<
11                 "Creating the musicxml2braille component" <<
12                 endl;
13         }
14 #endif
15
16         // create the converter component
17         pConverterComponent =
18             mfcConverterComponent::create (

```

```

19     "musicxml2braille",
20     mfcMultiComponentEntropicityKind::kComponentEntropicityNo,
21     mfcMultiComponentUsedFromTheCLIKind::kComponentUsedFromTheCLIYes); // JMI ???
22
23 // populate the converter's own history
24 pConverterComponent->
25     appendVersionDescrToComponent (
26         mfcVersionDescr::create (
27             mfcVersionNumber::createFromString ("0.9.50"),
28             "October 6, 2021",
29             list<string> {
30                 "Start of sequential versions numbering"
31             }
32         ));
33
34 pConverterComponent->
35     appendVersionDescrToComponent (
36         mfcVersionDescr::create (
37             mfcVersionNumber::createFromString ("0.9.51"),
38             "October 12, 2021",
39             list<string> {
40                 "Fixed trace OAH issue"
41             }
42         ));
43
44 // populate the converter's formats list
45 pConverterComponent->
46     appendRepresentationToMultiComponent (
47         createMxsrRepresentationComponent ());
48 pConverterComponent->
49     appendRepresentationToMultiComponent (
50         createMsrRepresentationComponent ());
51 pConverterComponent->
52     appendRepresentationToMultiComponent (
53         createBsrRepresentationComponent ());
54
55 pConverterComponent->
56     appendPassToMultiComponent (
57         createMxsr2msrComponent ());
58
59 pConverterComponent->
60     appendPassToMultiComponent (
61         createMsr2msrComponent ());
62
63 pConverterComponent->
64     appendPassToMultiComponent (
65         createMsr2bsrComponent ());
66
67 pConverterComponent->
68     appendPassToMultiComponent (
69         createBsr2bsrComponent ());
70
71 pConverterComponent->
72     appendPassToMultiComponent (
73         createBsr2brailleComponent ());
74 }
75
76 return pConverterComponent;
77 }

```

15.6.3 MusicFormats library component creation

This is done in function `createLibraryComponent ()` in `src/utilities/mfcLibraryComponent.h/.cpp`:

```

1 S_mfcLibraryComponent EXP createLibraryComponent ()
2 {
3     static S_mfcLibraryComponent pLibraryComponent;
4
5     // protect library against multiple initializations
6     if (! pLibraryComponent) {
7
8 #ifdef TRACING_IS_ENABLED
9         if (gGlobalOahEarlyOptions.getEarlyTracingOah ()) {
10             gLogStream <<
11                 "Creating the MFC library component" <<
12                 endl;
13         }
14 #endif
15
16         // create the library's history
17         pLibraryComponent =
18             mfcLibraryComponent::create (
19                 "musicformats",
20                 mfcMultiComponentEntropicityKind::kComponentEntropicityNo,
21                 mfcMultiComponentUsedFromTheCLIKind::kComponentUsedFromTheCLISYes); // JMI ???
22
23         // populate the library's own history
24         pLibraryComponent->
25             appendVersionDescrToComponent (
26                 mfcVersionDescr::create (
27                     mfcVersionNumber::createFromString ("0.9.50"),
28                     "October 6, 2021",
29                     list<string> {
30                         "Start of sequential versions numbering"
31                     }
32                 ));
33
34         pLibraryComponent->
35             appendVersionDescrToComponent (
36                 mfcVersionDescr::create (
37                     mfcVersionNumber::createFromString ("0.9.51"),
38                     "October 12, 2021",
39                     list<string> {
40                         "Adding a version number to the MusicFormats library",
41                         "Fixed trace OAH issue in the musicxml2* converters)"
42                     }
43                 ));
44
45         pLibraryComponent->
46             appendVersionDescrToComponent (
47                 mfcVersionDescr::create (
48                     mfcVersionNumber::createFromString ("0.9.52"),
49                     "October 12, 2021",
50                     list<string> {
51                         "Added MusicFormats library versions history to '-hist, -history'"
52                     }
53                 ));
54
55         pLibraryComponent->
56             appendVersionDescrToComponent (
57                 mfcVersionDescr::create (
58                     mfcVersionNumber::createFromString ("0.9.53"),
59                     "October 22, 2021",
60                     list<string> {
61                         "Replaced bool by class Bool in variables and fields",
62                         "Created MFC (MusicFormats components)"
63                     }
64                 ));
65
66         pLibraryComponent->

```



```

67     appendVersionDescrToComponent (
68         mfcVersionDescr::create (
69             mfcVersionNumber::createFromString ("0.9.54"),
70             "November 6, 2021",
71             list<string> {
72                 "Replaced cout and cerr by gOutputStream and gLogStream respectively in the
CLI samples",
73                 "Finalized components numbering (MFC)"
74             }
75         ));
76
77 // populate the library's components history
78 pLibraryComponent->
79     appendRepresentationToMultiComponent (
80         createMsrRepresentationComponent ());
81 pLibraryComponent->
82     appendRepresentationToMultiComponent (
83         createLpsrRepresentationComponent ());
84 pLibraryComponent->
85     appendRepresentationToMultiComponent (
86         createBsrRepresentationComponent ());
87 pLibraryComponent->
88     appendRepresentationToMultiComponent (
89         createMxsrRepresentationComponent ());
90
91 pLibraryComponent->
92     appendPassToMultiComponent (
93         createMsr2msrComponent ());
94
95 pLibraryComponent->
96     appendPassToMultiComponent (
97         createMsr2lpsrComponent ());
98 pLibraryComponent->
99     appendPassToMultiComponent (
100         createLpsr2lilypondComponent ());
101
102 pLibraryComponent->
103     appendPassToMultiComponent (
104         createMsr2bsrComponent ());
105 pLibraryComponent->
106     appendPassToMultiComponent (
107         createBsr2bsrComponent ());
108 pLibraryComponent->
109     appendPassToMultiComponent (
110         createBsr2brailleComponent ());
111
112 pLibraryComponent->
113     appendPassToMultiComponent (
114         createMsr2mxsrComponent ());
115
116 pLibraryComponent->
117     appendPassToMultiComponent (
118         createMxsr2musicxmlComponent ());
119
120 pLibraryComponent->
121     appendPassToMultiComponent (
122         createMxsr2guidoComponent ());
123 }
124
125 return pLibraryComponent;
126 }

```

Functions `createLibraryComponent ()` is called in `src/clisamples/displayMusicformatsVersion.cpp` and `src/clisamples/displayMusicformatsHistory.cpp`.

15.6.4 Version and history options handling

In order to be able to execute the `-version`, `-v` and `-history`, `-hist` options of a generator or converter, a `oahHandler` instance must be supplied with a `mfcMultiComponent` instance.

Field `oahHandler::fHandlerMultiComponent` is used for this purpose:

```

1 // -----
2 class EXP oahHandler : public smartable
3 {
4     // ... ..
5
6     protected:
7
8         // protected initialization
9         // -----
10
11         virtual void        initializeHandlerMultiComponent () = 0;
12
13     public:
14
15         // set and get
16         // -----
17
18         // ... ..
19
20         S_mfcMultiComponent  getHandlerMultiComponent () const
21                             { return fHandlerMultiComponent; }
22
23         // ... ..
24
25     protected:
26
27         // protected fields
28         // -----
29
30         // ... ..
31
32         // compound versions
33         S_mfcMultiComponent  fHandlerMultiComponent;
34 };

```

Field `oahHandler::fHandlerMultiComponent` is set in the `oahHandler` subclasses constructors by a call to the overridden `initializeHandlerMultiComponent ()`.

For example in constructor `xml2xmlInsiderHandler::xml2xmlInsiderHandler ()`:

```

1 xml2xmlInsiderHandler::xml2xmlInsiderHandler (
2     const string& serviceName,
3     string handlerHeader)
4 : oahInsiderHandler (
5     serviceName,
6     handlerHeader,
7     R"(
8         Welcome to the MusicXML to MusicXML converter
9         delivered as part of the MusicFormats library.
10
11         --- https://github.com/jacques-menu/musicformats ---
12     )",
13     R"(
14 Usage: xml2xml [[option]* [MusicXMLFile|-] [[option]*
15 )")
16 {
17     // ... ..
18
19     // initialize the multi-component

```

```

20 initializeHandlerMultiComponent ();
21
22 // ... ..
23 }

```

The overridden `initializeHandlerMultiComponent ()` methods merely get the atom or compound versions to assign it to field `oahHandler::fHandlerMultiComponent`.

For example, for `Mikrokosmos3Wandering`, the compound versions is simply set in the corresponding insider class `Mikrokosmos3WanderingInsiderHandler`:

```

1 void Mikrokosmos3WanderingInsiderHandler::initializeHandlerMultiComponent ()
2 {
3     fHandlerMultiComponent =
4         createMikrokosmos3WanderingGeneratorComponent ();
5 }

```

15.7 Accessing versions in regular handlers

A regular handler merely gets the compound versions of the insider handler it relies upon in its overridden `initializeHandlerMultiComponent ()` method:

```

1 class EXP oahRegularHandler : public oahHandler
2 /*
3  A regular OAH handler relies on the existence of so-called 'insider' handler,
4  that contains all the options values gathered from the user,
5  grouped according to the internal representations and passes used.
6
7  The variables containing the values of the options chosen by the user
8  are actually held by the insider handler.
9 */
10 {
11     // ... ..
12
13     protected:
14
15         // protected initialization
16         // -----
17
18         // ... ..
19
20         void initializeHandlerMultiComponent () override
21         {
22             fHandlerMultiComponent =
23                 fInsiderHandler->
24                     getHandlerMultiComponent ();
25         }
26
27         // ... ..
28 };

```

15.8 Getting current version numbers

Apart from the version and history options, such current version numbers may be used in the output from generators and converters, depending on the options. A component description is the way to achieve that in the latter two cases.

15.8.1 Current version numbers in options

Option `-version`, `-v` displays the versions of generators and converters:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/files/musicxml > xml2xml -version
2 Command line version of musicxml2musicxml converter v0.9.51 (October 12 2021)
3
4 Representations versions:
5   MXSR
6     v0.9.5 (October 6 2021)
7   MSR
8     v0.9.51 (October 14 2021)
9
10 Passes versions:
11   mxsr2msr
12     v0.9.5 (October 6 2021)
13   msr2msr
14     v0.9.5 (October 6 2021)
15   msr2mxsr
16     v0.9.5 (October 6 2021)
17   mxsr2musicxml
18     v0.9.5 (October 6 2021)

```

Option `-history`, `-hist` display the versions history of generators and converters:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/files/musicxml > xml2gmn -history
2 Command line version of musicxml2guido converter v0.9.51 (October 12 2021)
3
4 Own history:
5   v0.9.5 (October 6 2021):
6     Start of sequential versions numbering
7
8   v0.9.51 (October 12 2021):
9     Fixed trace OAH issue
10
11 Representations history:
12   MXSR
13     v0.9.5 (October 6 2021):
14       Start of sequential versions numbering
15
16   MSR
17     v0.9.5 (October 6 2021):
18       Start of sequential versions numbering
19
20     v0.9.51 (October 14 2021):
21       Refined MSR names and summary display options
22
23 Passes history:
24   mxsr2msr
25     v0.9.5 (October 6 2021):
26       Start of sequential versions numbering
27
28   msr2msr
29     v0.9.5 (October 6 2021):
30       Start of sequential versions numbering
31
32   msr2mxsr
33     v0.9.5 (October 6 2021):
34       Start of sequential versions numbering
35
36   mxsr2guido
37     v0.9.5 (October 6 2021):
38       Start of sequential versions numbering

```

In `src/oah/oahAtomsCollection.h/.cpp`, class `oahVersionAtom` contains method `printVersion ()`:

```

1 class EXP oahVersionAtom : public oahPureHelpAtomWithoutAValue
2 {
3     // ... ..
4
5     public:
6
7         // public services
8         // -----
9
10        void                applyElement (ostream& os) override;
11
12        // ... ..
13
14        public:
15
16        // print
17        // -----
18
19        // ... ..
20
21        void                printVersion (ostream& os) const;
22 };

```

The option is applied by method `oahVersionAtom::applyElement ()`:

```

1 void oahVersionAtom::applyElement (ostream& os)
2 {
3     #ifdef TRACING_IS_ENABLED
4         if (gGlobalOahEarlyOptions.getEarlyTracingOah ()) {
5             gLogStream <<
6                 "=="> option ' ' << fetchNames () << " ' is a oahVersionAtom" <<
7                 endl;
8         }
9     #endif
10
11     int saveIndent = gIndenter.getIndent ();
12
13     gIndenter.resetToZero ();
14
15     printVersion (os);
16
17     gIndenter.setIndent (saveIndent);
18 }

```

The work is done by method `oahVersionAtom::printVersion ()`:

```

1 void oahVersionAtom::printVersion (ostream& os) const
2 {
3     // get the handler version
4     S_mfcMultiComponent
5     handlerMultiComponent =
6         fetchAtomHandlerUpLink ()->
7         getHandlerMultiComponent ();
8
9     // sanity check
10    mfAssert (
11        __FILE__, __LINE__,
12        handlerMultiComponent != nullptr,
13        "handlerMultiComponent is null");
14
15    handlerMultiComponent->
16        printVersion (os);
17 }

```

The situation is analog for histories with `printVersion ()` replaced by `printHistory ()`.

15.8.2 Current version numbers in formats

When creating LilyPond output, the current version number of the converter used is indicated as a comment when the option `-lilypond-generation-infos`, `-lpgi` option is used:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/files/musicxml > xml2ly --lilypond-generation-
  infos basic/HelloWorld.xml
2 \version "2.22.0"
3
4 % Pick your choice from the next two lines as needed
5 %myBreak = { \break }
6 myBreak = {}
7
8 % Pick your choice from the next two lines as needed
9 %myPageBreak = { \pageBreak }
10 myPageBreak = {}
11
12 % Generated by xml2ly v0.9.51 (October 12 2021)
13 % on Thursday 2021-11-11 @ 11:15:56 CET
14 % from "basic/HelloWorld.xml"
15
16 % ... ..

```

Class `lpsrScore` contains an MFC component field:

```

1 class EXP lpsrScore : public lpsrElement
2 {
3     // ... ..
4
5     private:
6
7         // private fields
8         // -----
9
10        // ... ..
11
12        // the multi-component
13        // -----
14        S_mfcMultiComponent    fMultiComponent;
15
16        // ... ..
17 };

```

In `src/formats/lpsr//lpsrScores.cpp`, constructor `lpsrScore::lpsrScore ()` stores the multi-component value and uses it to create an `lpsrComment` instance:

```

1 lpsrScore::lpsrScore (
2     int                inputLineNumber,
3     S_msrScore          theMsrScore,
4     S_mfcMultiComponent multiComponent)
5     : lpsrElement (inputLineNumber)
6 {
7     // ... ..
8
9     fMsrScore = theMsrScore;
10
11    fMultiComponent = multiComponent;
12
13    // should the initial comments about the service and the options used
14    // be generated?
15    if (gGlobalLpsr2lilypondOahGroup->getXml2lyInfos ()) {
16        // create the 'input source name and translation date' comment
17        {
18            stringstream s;
19

```

```

20     s <<
21     "Generated by " <<
22     gGlobalOahOahGroup->getOahOahGroupServiceName () <<
23     ' ' <<
24     fMultiComponent->
25         mostRecentVersionNumberAndDateAsString () <<
26     endl <<
27
28     "% on " <<
29     gGlobalServiceRunData->getTranslationDateFull () <<
30     endl <<
31
32     "% from ";
33
34     if (gGlobalServiceRunData->getInputSourceName () == "-") {
35         s << "standard input";
36     }
37     else {
38         s << "\" " << gGlobalServiceRunData->getInputSourceName () << "\"";
39     }
40
41     fInputSourceNameComment =
42         lpsrComment::create (
43             inputLineNumber,
44             s.str (),
45             lpsrComment::kGapAfterwardsNo);
46 }
47
48 // ... ..
49 }
50
51 // ... ..
52 }

```

15.8.3 Current version numbers in passes

Another case is that of the generation of MusicXML output:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/files/musicxml > xml2xml -musicxml-generation-
  infos basic/HelloWorld.xml
2 <?xml version="1.0" encoding="UTF-8" standalone="no"?>
3 <!DOCTYPE score-partwise PUBLIC "-//Recordare//DTD MusicXML 3.1 Partwise//EN"
4     "http://www.musicxml.org/dtds/partwise.dtd">
5 <score-partwise version="3.1">
6     <!--
7     =====
8     Created by xml2xml v0.9.5 (October 6 2021)
9     on Thursday 2021-11-11 @ 11:04:06 CET
10    from basic/HelloWorld.xml
11    =====
12    -->
13    <work>
14        <work-number/>
15        <work-title>Hello World!</work-title>
16    </work>
17    <movement-number/>
18    <movement-title/>
19    <identification>
20        <encoding>
21            <software>xml2xml v0.9.5 (October 6 2021), https://github.com/jacques-menu/
22            musicformats</software>
23            <encoding-date>2021-11-10</encoding-date>
24            </encoding>
25            <miscellaneous>

```

```

25         <miscellaneous-field name="description"/>
26     </miscellaneous>
27 </identification>
28
29 <!-- ... .. -->

```

In `src/passes/msr2mxsr/msr2mxsrTranslator.cpp`, the start visitor of `msrScore` instances does that this way:

```

1 void msr2mxsrTranslator::visitStart (S_msrScore& elt)
2 {
3     // ... ..
4
5     // get the pass component
6     S_mfcPassComponent
7     passComponent =
8         createMsr2mxsrComponent ();
9
10    // get the pass component current version number and date
11    string
12    passComponentMostRecentVersionNumberAndDateAsString =
13        passComponent->
14            mostRecentVersionNumberAndDateAsString ();
15
16    // create the initial creation comment
17    stringstream s;
18    s <<
19    endl <<
20    "===== " <<
21    endl <<
22    "Created by " <<
23    gGlobalOahOahGroup->getOahOahGroupServiceName () <<
24    ' ' <<
25    passComponentMostRecentVersionNumberAndDateAsString <<
26    endl <<
27
28    "on " <<
29    gGlobalServiceRunData->getTranslationDateFull () <<
30    endl <<
31
32    "from " <<
33    gGlobalServiceRunData->getInputSourceName () <<
34    endl <<
35
36    "===== " <<
37    endl;
38
39    // append the initial creation comment to the score part wise element
40    fResultingMusicxmlelement->push (createMxmlelement (kComment, s.str ()));
41
42    // create a software element
43    Sxmlelement
44    softwareElement =
45        createMxmlelement (
46            k_software,
47            gGlobalOahOahGroup->getOahOahGroupServiceName ()
48            + ' '
49            + passComponentMostRecentVersionNumberAndDateAsString +
50            ", https://github.com/jacques-menu/musicformats");
51
52    // append it to the identification encoding
53    appendToScoreIdentificationEncoding (softwareElement);
54
55    // ... ..
56 }

```

Part V

Options and help

Chapter 16

Options and help (OAH)

OAH is a powerful way of representing the options together with the corresponding help. The classical function `getopt* ()` family of functions are not up to the task because:

- there is a great number of options in MusicFormats;
- attaching the help to the options in a clean, neat way was highly desirable;
- more important still, the re-use of options whenever translators are combined into converters could only be achieved with an object oriented handling of the options and help.

The output of the help goes to standard output, so that the user can pipe it into a `more` or `less` command.

16.1 OAH basics

- OAH (Options And Help) is supposed to be pronounced something close to "whaaaah!" The intonation is left to the speaker, though... And as the saying goes: "OAH? why not!"
- options handling is organized as a hierarchical, introspective set of classes. An options and its corresponding help are grouped in a single object.
- the options can be supplied thru:
 - the command line, in `argv`. This allows for mixed options and arguments in any order, à la GNU;
 - the API functions such as function `musicxmlfile2lilypond ()`, in an options and arguments.
- class `oahElement` is the super-class of all options types, including groups and subgroups. It contains a short name and a long name, as well as a description. Short and long names can be used and mixed at will in the command line and in option vectors (API), as well as `'-'` and `'--'`. The short name is mandatory, but the long name may be empty if the short name is explicit enough.
- prefixes such `'-t='` and `-help='` allow for a contracted form of options. For example, `-t=meas,notes` is short for `'-t-meas, -tnotes'`. A `oahPrefix` contains the prefix name, the ersatz by which to replace it, and a description.
- a class `oahHandler` contains a list of `oahGroup`'s, each handled in a pair of `.h/.cpp` files such as `src/formats/msr/msrOah.h` and `src/formats/msr/msrOah.cpp`, and a list of options prefixes.
- a class `oahGroup` contains a list of `oahSubGroup`'s and an `upLink` to the containing `oahHandler`.
- a class `oahSubGroup` contains a list of `oahAtom`'s and an `upLink` to the containing `oahGroup`.
- each class `oahAtom` contains an atomic option and the corresponding help, and an `upLink` to the containing `oahSubGroup`.

16.2 Features

- the values of the various options can be displayed with the option `-display-options-values`, `-dov` option;
- partial help can be obtained, i.e. help about any group, subgroup or atom, showing the path in the hierarchy down to the corresponding option;
- there are various subclasses of class `oahAtom` such as class `oahIntegerAtom`, class `oahBooleanAtom` and class `oahRationalAtom`, to control options values of common types;
- class `oahThreeBooleansAtom`, for example, allows for three boolean settings to be controlled at once with a single option;
- class `oahAtomStoringAValue` describes options for which a value is supplied in the command line or in option vectors (API);
- a class such as class `lpsrPitchesLanguageAtom` is used to supply a string value to be converted into an internal enumerated type;
- a class `oahCombinedBooleansAtom` contains a list of boolean atoms to manipulate several such atoms as a single one, see the 'class cubase' combined booleans atom in `src/passes/mxsr2msr/mxsr2msrOah.cpp`;
- class `oahMultiplexBooleansAtom` contains a list of boolean atoms sharing a common prefix to display such atoms in a compact manner, see the 'ignore-redundant-clefs' multiplex booleans atom in `src/passes/mxsr2msr/mxsr2msrOah.cpp`;
- storing options and the corresponding help in class `oahGroup`'s makes it easy to re-use them. For example, file `xml2ly` and file `xml2lbr` have their three first passes in common, (up to obtaining the MSR description of the score), as well as the corresponding options and help;
- `src/oah/oahAtomsCollection` contains a bunch of general purpose options such as class `oahContactAtom`, class `oahFloatAtom` and class `oahLengthAtom`;
- a regular handler (used by default unless the option `-insider` is used), presents the options and help grouped by subject, such as voices and tuplets. It uses an insider handler, which groups them by internal representation and conversion pass. This is how options groups are re-used for various converters such as file `xml2ly`, file `xml2brl` and file `xml2xml`.

16.3 OAH classes inheritance


The picture at figure 16.1 [The OAH classes hierarchy], page 123, shows the hierarchy of the main OAH classes. The colors are used as follows:

The background colors are used as follows:

- **green**: a OAH element that is expected to be found in an options and help user view, such as class `oahHandler` and class `oahSubGroup`;
- **pink**: a complementary element provided by OAH, such as class `oahPrefix`;
- **yellow**: a base class with name class `oah*Element` for elements that can be used in another class, such as class `oahFindableElement`;

The arrows colors have the following meaning:

Figure 16.1: The OAH classes hierarchy



- **red**: a link from a class to its base class. For example, class `oahElement` is derived from class `oahFindableElement`;
- **blue**: a link from a class to another that uses smart pointers to one or more instances of the former. For example, an `msrTuplet` instance may be an element of an `msrGraceNotesGroup` instance.

There is a whole hierarchy of `oahAtom` sub-classes, some of which are provided in `src/oah/oahAtomsCollection.h.h/`. Here is the essentials of the OAH classes:

```

1 jacquesmenu@macmini:~/musicformats-git-dev/src/oah > gr Element | grep class
2 oahAtomsCollection.h:2085:class EXP oahNaturalNumbersSetElementAtom : public
   oahAtomStoringAValue
3 oahAtomsCollection.h:2271:class EXP oahIntSetElementAtom : public oahAtomStoringAValue
4 oahAtomsCollection.h:2357:class EXP oahStringSetElementAtom : public oahAtomStoringAValue
5 oahAtomsCollection.h:2450:class EXP oahStringToIntMapElementAtom : public
   oahAtomStoringAValue
6 oahAtomsCollection.h:2537:class EXP oahStringToStringMapElementAtom : public
   oahAtomStoringAValue
7 oahAtomsCollection.h:2624:class EXP oahStringToStringMultiMapElementAtom : public
   oahAtomStoringAValue
8 oahBasicTypes.h:373:class EXP oahPrefix : public oahFindableElement
9 oahBasicTypes.h:472:class EXP oahAtom : public oahElement
10 oahBasicTypes.h:994:class EXP oahSubGroup : public oahElement
11 oahBasicTypes.h:1163:class EXP oahGroup : public oahElement
12 oahBasicTypes.h:1396:class EXP oahHandler : public oahElement
13 oahElements.h:36:enum class oahElementValueKind {
14 oahElements.h:48:enum class oahElementVisibilityKind {
15 oahElements.h:60:enum class oahElementHelpOnlyKind {
16 oahElements.h:72:class oahElement;
17 oahElements.h:82:class EXP oahFindableElement : public smartable
18 oahElements.h:206:class EXP oahElement : public oahFindableElement
19 oahElements.h:391:class EXP oahElementUse : public smartable

```

Class `oahFindableElement` is the base class for all those that can be introspected with the `-find` option.

16.4 Atoms expecting a value

Some options expect a value, such a length or a color, to be supplied in the command line or in a type `oahOptionsVector`.

Purely virtual class `oahAtomExpectingAValue`, defined in `src/oah/oahBasicTypes.h/.cpp`, is a common ancestor to all the classes describing such options:

```

1 class EXP oahAtomExpectingAValue : public oahAtom
2 /*
3  a purely virtual common ancestor for all atom classes
4  that take a value from argv or an oahOptionsVector
5 */
6 {
7     // ... ..
8
9     public:
10
11         // public services
12         // -----
13
14         void                applyElement (ostream& os) override;
15                             // reports an error
16
17         virtual void        applyAtomWithValue (
18                             const string& theString,
19                             ostream&      os) = 0;
20
21         virtual void        applyAtomWithDefaultValue (ostream& os);
22                             // used only if fElementValueKind
23                             // is oahElementValueKind::kElementValueImplicit
24                             // or oahElementValueKind::kElementValueOptional
25 };

```

The classes derived from `oahAtomExpectingAValue` are:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src > grh 'public oahAtomExpectingAValue'
2 oah/oahBasicTypes.h:class EXP oahAtomStoringAValue : public oahAtomExpectingAValue
3 oah/oahBasicTypes.h:class EXP oahPureHelpAtomExpectingAValue : public
4   oahAtomExpectingAValue
5 passes/lpsr2lilypond/lpsr2lilypondOah.h:class EXP lilypondRelativeOctaveEntryAtom : public
6   oahAtomExpectingAValue
7 passes/lpsr2lilypond/lpsr2lilypondOah.h:class EXP lilypondFixedOctaveEntryAtom : public
8   oahAtomExpectingAValue

```

16.4.1 The `oahAtomStoringAValue` class

Purely virtual class `oahAtomStoringAValue`, defined in `src/oah/oahBasicTypes.h/.cpp`, is the base class for them:

```

1 class EXP oahAtomStoringAValue : public oahAtomExpectingAValue
2 {
3     // ... ..
4
5     public:
6
7         // print
8         // -----
9
10        virtual void        printAtomWithVariableEssentials (
11                             ostream& os,
12                             int fieldWidth) const;
13
14        virtual void        printAtomWithVariableEssentialsShort (

```

```

14         ostream& os,
15         int   fieldWidth) const;
16
17     void    print (ostream& os) const override;
18     void    printShort (ostream& os) const override;
19
20     void    printHelp (ostream& os) const override;
21
22     virtual void    printAtomWithVariableOptionsValues (
23         ostream& os,
24         int         valueFieldWidth) const override;
25
26 protected:
27
28     // protected fields
29     // -----
30
31     string    fValueSpecification;
32
33     string    fVariableName;
34     Bool      fSetByAnOption;
35 };

```

The field `oahAtomStoringAValue::fSetByAnOption` is necessary because some value types do not have an obvious 'neutral' element. This is the case for a note's octave, `oahLengthUnitKindAtom` and `oahRGBColorAtom`, for example. It is not used for data structures such as sets, lists and vector, since this is indicated by their size.

`fSetByAnOption` is set in `set*Variable ()` methods, as in method `oahIntegerAtom::setIntegerVariable ()` in `src/oah/oahAtomsCollection.cpp`:

```

1 void oahIntegerAtom::setIntegerVariable (int value)
2 {
3     #ifdef TRACING_IS_ENABLED
4         if (gGlobalOahEarlyOptions.getEarlyTracingOah ()) {
5             gLogStream <<
6                 "Setting option '" <<
7                 fetchNames () <<
8                 "' integer variable to '" <<
9                 value <<
10                "' <<
11             endl;
12         }
13     #endif
14
15     fIntegerVariable = value;
16     fSetByAnOption = true;
17 }

```

16.4.2 The `oahBooleanAtom` special case

Class `oahBooleanAtom` has its own `fSetByAnOption` field, because is it not derived from class `oahAtomStoringAValue`: there isn't any value to be supplied in the command line, since `fBooleanVariable` is false by default:

```

1 // -----
2 class EXP oahBooleanAtom : public oahAtom
3 {
4     /*
5     an atom controlling a Bool variable variableName,
6     but expecting no value to be supplied:
7     the variable is false initially,

```

```

8  and is set to true by the mere occurrence of the atom
9  */
10
11  // ... ..
12
13  protected:
14
15  // protected fields
16  // -----
17
18  string          fVariableName;
19  Bool&           fBooleanVariable;
20  Bool            fSetByAnOption;
21 };

```

16.4.3 Checking whether an option has been selected

This is done by calls to the `getSetByAnOption ()` methods.

For example, method `lpsr2lilypondTranslator::generateLilypondVersion ()` in `src/formats/lpsr//lpsr2lilypondTranslator.cpp` contains:

```

1  void lpsr2lilypondTranslator::generateLilypondVersion ()
2  {
3      // LilyPond version
4      Bool
5          lilypondVersionHasBeenSet =
6          gGlobalLpsr2lilypondOahGroup->
7          getLilypondVersionAtom ()->
8          getSetByAnOption ();
9
10     string
11         lilypondVersion =
12         lilypondVersionHasBeenSet
13         ? gGlobalLpsr2lilypondOahGroup->
14         getLilypondVersion ()
15         : gGlobalLpsr2lilypondOahGroup->
16         getLilypondVersionDefaultValue ();
17
18     fLilypondCodeStream <<
19     "\\version \"" <<
20     lilypondVersion <<
21     "\"" <<
22     endl << endl;
23 }

```

The default LilyPond version number is 2.22.0. Another can be chosen with the `-lilypond-version`, `-lpv` option:

```

1  jacquesmenu@macmini > xml2ly -find lilypond-version
2  1 occurrence of string "lilypond-version" has been found:
3  1:
4  -lilypond-version, -lpv
5  Set the Lilypond '\version' to STRING in the Lilypond code.
6  The default is '2.22.0'.

```

16.4.4 The oahAtomStoringAValue subclasses

The classes derived from oahAtomStoringAValue are:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src > grh 'public oahAtomStoringAValue'
2 oah/harmoniesExtraOah.h:class EXP extraShowAllHarmoniesStructuresAtom : public
   oahAtomStoringAValue
3 oah/harmoniesExtraOah.h:class EXP extraShowAllHarmoniesContentsAtom : public
   oahAtomStoringAValue
4 oah/harmoniesExtraOah.h:class EXP extraShowHarmonyDetailsAtom : public
   oahAtomStoringAValue
5 oah/harmoniesExtraOah.h:class EXP extraShowHarmonyAnalysisAtom : public
   oahAtomStoringAValue
6 oah/oahAtomsCollection.h:class EXP oahIntegerAtom : public oahAtomStoringAValue
7 oah/oahAtomsCollection.h:class EXP oahFloatAtom : public oahAtomStoringAValue
8 oah/oahAtomsCollection.h:class EXP oahStringAtom : public oahAtomStoringAValue
9 oah/oahAtomsCollection.h:class EXP oahRationalAtom : public oahAtomStoringAValue
10 oah/oahAtomsCollection.h:class EXP oahNaturalNumbersSetElementAtom : public
   oahAtomStoringAValue
11 oah/oahAtomsCollection.h:class EXP oahRGBColorAtom : public oahAtomStoringAValue
12 oah/oahAtomsCollection.h:class EXP oahIntSetElementAtom : public oahAtomStoringAValue
13 oah/oahAtomsCollection.h:class EXP oahStringSetElementAtom : public oahAtomStoringAValue
14 oah/oahAtomsCollection.h:class EXP oahStringToIntMapElementAtom : public
   oahAtomStoringAValue
15 oah/oahAtomsCollection.h:class EXP oahStringAndIntegerAtom : public oahAtomStoringAValue
16 oah/oahAtomsCollection.h:class EXP oahStringAndTwoIntegersAtom : public
   oahAtomStoringAValue
17 oah/oahAtomsCollection.h:class EXP oahLengthUnitKindAtom : public oahAtomStoringAValue
18 oah/oahAtomsCollection.h:class EXP oahLengthAtom : public oahAtomStoringAValue
19 oah/oahAtomsCollection.h:class EXP oahMidiTempoAtom : public oahAtomStoringAValue
20 formatsgeneration/brailleGeneration/brailleGenerationOah.h:class EXP brailleOutputKindAtom
   : public oahAtomStoringAValue
21 formatsgeneration/brailleGeneration/brailleGenerationOah.h:class EXP brailleUTFKindAtom :
   public oahAtomStoringAValue
22 formatsgeneration/brailleGeneration/brailleGenerationOah.h:class EXP
   brailleByteOrderingKindAtom : public oahAtomStoringAValue
23 formatsgeneration/msrGeneration/msrGenerationBasicTypes.h:class EXP
   msrGenerationAPIKindAtom : public oahAtomStoringAValue
24 formatsgeneration/multiGeneration/mfMultiGenerationOah.h:class EXP
   mfMultiGenerationOutputKindAtom : public oahAtomStoringAValue
25 passes/lpsr2lilypond/lpsr2lilypondOah.h:class EXP lilypondScoreOutputKindAtom : public
   oahAtomStoringAValue
26 passes/lpsr2lilypond/lpsr2lilypondOah.h:class EXP lilypondTransposePartNameAtom : public
   oahAtomStoringAValue
27 passes/lpsr2lilypond/lpsr2lilypondOah.h:class EXP lilypondTransposePartIDAtom : public
   oahAtomStoringAValue
28 passes/lpsr2lilypond/lpsr2lilypondOah.h:class EXP lilypondAccidentalStyleKindAtom : public
   oahAtomStoringAValue
29 passes/lpsr2lilypond/lpsr2lilypondOah.h:class EXP lilypondChordsDisplayAtom : public
   oahAtomStoringAValue
30 passes/lpsr2lilypond/lpsr2lilypondOah.h:class EXP lilypondLyricsDurationsKindAtom : public
   oahAtomStoringAValue
31 passes/lpsr2lilypond/lpsr2lilypondOah.h:class EXP
   lilypondDynamicsTextSpannersStyleKindAtom : public oahAtomStoringAValue
32 passes/lpsr2lilypond/lpsr2lilypondOah.h:class EXP lilypondBreakPageAfterMeasureNumberAtom
   : public oahAtomStoringAValue
33 passes/msr2lpsr/msr2lpsrOah.h:class EXP msr2lpsrScoreOutputKindAtom : public
   oahAtomStoringAValue
34 passes/msr2msr/msr2msrOah.h:class EXP msrIgnorePartAtom : public oahAtomStoringAValue
35 passes/msr2msr/msr2msrOah.h:class EXP msrKeepPartAtom : public oahAtomStoringAValue
36 passes/mxsr2msr/mxsr2msrOah.h:class EXP msrReplaceClefAtom : public oahAtomStoringAValue
37 formats/bsr/bsrOah.h:class EXP bsrFacSimileKindAtom : public oahAtomStoringAValue
38 formats/bsr/bsrOah.h:class EXP bsrTextsLanguageAtom : public oahAtomStoringAValue
39 formats/lpsr/lpsrOah.h:class EXP lpsrPitchesLanguageAtom : public oahAtomStoringAValue
40 formats/lpsr/lpsrOah.h:class EXP lpsrChordsLanguageAtom : public oahAtomStoringAValue
41 formats/lpsr/lpsrOah.h:class EXP lpsrTransposeAtom : public oahAtomStoringAValue

```



```

42 formats/msdl/msdlInputOah.h:class EXP msdlKeywordsLanguageAtom : public
    oahAtomStoringAValue
43 formats/msdl/msdlInputOah.h:class EXP msdlCommentsTypeAtom : public oahAtomStoringAValue
44 formats/msdl/msdlInputOah.h:class EXP msdlUserLanguageAtom : public oahAtomStoringAValue
45 formats/msdl/msdlInputOah.h:class EXP msdlPitchesLanguageAtom : public
    oahAtomStoringAValue
46 formats/msr/msrOah.h:class EXP msrPitchesLanguageAtom : public oahAtomStoringAValue
47 formats/msr/msrOah.h:class EXP msrRenamePartAtom : public oahAtomStoringAValue

```

16.5 Pure help atoms

Some options, such as `-a`, `-about`, only provide help to the user. Such pure help atoms can be with or without a value.

16.5.1 Pure help atoms without a value

The base `oahPureHelpAtomWithoutAValue` class is defined in `src/oah/oahBasicTypes.h/.cpp`:

```

1 // -----
2 class EXP oahPureHelpAtomWithoutAValue : public oahAtom
3 {
4     // ... ..
5
6     protected:
7
8     // protected fields
9     // -----
10
11     string                fHelpAtomWithoutAValueServiceName;
12 };

```

The actual pure help atoms without a value are:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src > grh 'public oahPureHelpAtomWithoutAValue
,
2 oah/oahAtomsCollection.h:class EXP oahOptionsUsageAtom : public
    oahPureHelpAtomWithoutAValue
3 oah/oahAtomsCollection.h:class EXP oahHelpAtom : public oahPureHelpAtomWithoutAValue
4 oah/oahAtomsCollection.h:class EXP oahHelpSummaryAtom : public
    oahPureHelpAtomWithoutAValue
5 oah/oahAtomsCollection.h:class EXP oahAboutAtom : public oahPureHelpAtomWithoutAValue
6 oah/oahAtomsCollection.h:class EXP oahVersionAtom : public oahPureHelpAtomWithoutAValue
7 oah/oahAtomsCollection.h:class EXP oahLibraryVersionAtom : public
    oahPureHelpAtomWithoutAValue
8 oah/oahAtomsCollection.h:class EXP oahHistoryAtom : public oahPureHelpAtomWithoutAValue
9 oah/oahAtomsCollection.h:class EXP oahLibraryHistoryAtom : public
    oahPureHelpAtomWithoutAValue
10 oah/oahAtomsCollection.h:class EXP oahContactAtom : public oahPureHelpAtomWithoutAValue

```

16.5.2 Pure help atoms expecting a value

The base `oahPureHelpAtomExpectingAValue` class is defined in `src/oah/oahBasicTypes.h/.cpp`:

```

1 class EXP oahPureHelpAtomExpectingAValue : public oahAtomExpectingAValue
2 {
3     // ... ..
4
5     protected:
6
7         // protected fields
8         // -----
9
10        string                fHelpAtomExpectingAValueServiceName; // JMI ???
11 };

```

The actual pure help atoms expecting a value are:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src > grh 'public
   oahPureHelpAtomExpectingAValue'
2 oah/oahAtomsCollection.h:class EXP oahQueryOptionNameAtom : public
   oahPureHelpAtomExpectingAValue
3 oah/oahAtomsCollection.h:class EXP oahFindStringAtom : public
   oahPureHelpAtomExpectingAValue
4 formats/msdl/msdlInputOah.h:class EXP oahDisplayMsdlKeywordsInLanguageAtom : public
   oahPureHelpAtomExpectingAValue
5 formats/msdl/msdlInputOah.h:class EXP oahDisplayMsdlTokensInLanguageAtom : public
   oahPureHelpAtomExpectingAValue

```

16.6 Options implicitly storing a value

There are options in multiGeneration to select the generated output :

```

1 jacquesmenu@macmini > msdlconverter --help-generate-output
2 --- Help for subgroup "Generated output" in group "Generated output group" ---
3 Generated output group (-help-generate-output-group, -hgc-group):
4 -----
5 Generated output (-help-generate-output, -hgo):
6     -guido
7         Generate Guido code as output.
8     -lilypond
9         Generate LilyPond code as output.
10    -braille
11        Generate braille code as output.
12    -musicxml
13        Generate MusicXML code as output.

```

No value is supplied in the command line or in a type `oahOptionsVector`, but a variable is used to store a value alright.

Purely virtual class `oahAtomImplicitlyStoringAValue` is the base class for this:

```

1 class EXP oahAtomImplicitlyStoringAValue : public oahAtom
2 /*
3     a purely virtual common ancestor for all atom classes
4     that store a value in a variable
5     without taking it from argv or an oahOptionsVector
6 */
7 {
8     // ... ..
9
10    protected:
11
12        // protected fields
13        // -----
14

```

```

15     string          fVariableName;
16     Bool           fSetByAnOption;
17 };

```

This used by class `mfMultiGenerationOutputKindAtom` defined in `src/formatsgeneration/multiGeneration/multiGenerationOah.h/.cpp`:

```

1 class EXP mfMultiGenerationOutputKindAtom : public oahAtomImplicitlyStoringAValue
2 {
3     // ... ..
4
5     private:
6
7     // private fields
8     // -----
9
10    mfMultiGenerationOutputKind&
11        fMultiGenerationOutputKindVariable;
12 };

```

The value is stored in the variable in constructor `mfMultiGenerationOutputKindAtom::mfMultiGenerationOutputKindAtom ()`:

```

1 mfMultiGenerationOutputKindAtom::mfMultiGenerationOutputKindAtom (
2     const string&      longName,
3     const string&      shortName,
4     const string&      description,
5     const string&      variableName,
6     mfMultiGenerationOutputKind& mfMultiGenerationOutputKindVariable)
7 : oahAtomImplicitlyStoringAValue (
8     longName,
9     shortName,
10    description,
11    variableName,
12    oahElementValueKind::kElementValueWithout),
13    fMultiGenerationOutputKindVariable ( // this is where the value is supplied
14        mfMultiGenerationOutputKindVariable)
15 {}

```

16.7 Options and help handling

- each option short name and non-empty long name must be unique in a given handler, to avoid ambiguities;
- an service `main ()` calls method `oahHandler::handleOptionsAndArgumentsFromArgcArgv ()`, in which:
 - method `oahHandler::handleOptionNameCommon ()` handles the option names;
 - `handleOptionValueOrArgument()` and the arguments to the service.
- contracted forms are expanded in method `oahHandler::handleOptionNameCommon ()` before the resulting, uncontracted options are handled;
- options handling works in two passes:
 - the first one creates a list of class `oahElementUse` instances from `argc/argv` or an options and arguments;
 - the second one traverses this list to apply the options that are used.

- the options are applied by virtual method `applyElement ()`, virtual method `applyAtomWithValue ()` and virtual method `applyAtomWithDefaultValue ()`;
- method `oahHandler::handleKnownArgvAtom ()` associates the value to the (preceding) field `oahHandler::fHandlerArgumentsVector` if not null, or appends it to field `oahHandler::fHandlerArgumentsVector` to otherwise;
- `fPendingArgvAtomExpectingAValue` is used in `argv` contents handling to associate an option name with it value, which is the next element in `argv`.

16.8 Basic OAH types

They are defined in `src/oah/oahBasicTypes.h/.cpp`. The classes are:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src/oah > grep class oahBasicTypes.h
2 // PRE-declarations for class mutual dependencies
3 class oahAtom;
4 class oahSubGroup;
5 class oahGroup;
6 class oahHandler;
7 enum class oahOptionsDefaultValuesStyle {
8 enum class oahHandlerUsedThruKind {
9 class oahPrefix;
10 class EXP oahPrefix : public smartable
11     a common ancestor for all atom classes,
12     this class contains only an uplink to the containing subgroup
13 class EXP oahAtom : public oahElement
14 /* this class is purely virtual
15 class EXP oahAtomExpectingAValue : public oahAtom
16     a common ancestor for all atom classes
17 /* this class is purely virtual
18     a common ancestor for all atom classes
19 class EXP oahAtomStoringAValue : public oahAtomExpectingAValue
20 /* this class is purely virtual
21 class EXP oahPureHelpAtomWithoutAValue : public oahAtom
22 /* this class is purely virtual
23 class EXP oahPureHelpAtomExpectingAValue : public oahAtomExpectingAValue
24 /* this class is purely virtual
25 class EXP oahSubGroup : public oahElement
26 class EXP oahGroup : public oahElement
27 class EXP oahHandler : public smartable
28 /* this class is purely virtual
29 enum class oahOptionalValuesStyleKind {
30 class EXP oahAtomWithoutAValue : public oahAtom
31 / * this class is purely virtual

```

16.9 Prefixes handling

16.10 argc/argv versus oahOptionsVector

Passing the options and arguments over to the library when using MusicFormats can be done in two ways:

- command line tools get them from `argc/argv` as usual;
- application using the library through the API should place them in an `oahOptionsVector`, defined in `src/mflibrarymfMusicformatsError.h`:

```

1 typedef std::vector<std::pair<std::string, std::string> > oahOptionsVector;

```

Using an `oahOptionsVector` can be done for example:

- in Web sites;
- in the generators CLI tools found in the `src/clisamples/` folder `src/clisamples/xml2Any.cpp`, `src/clisamples/libMultipleInitsTest.cpp`, `src/clisamples/Mikrokosmos3Wandering.cpp` and `src/clisamples/LilyPondIssue34.cpp`, as well as in `src/clisamples/msdl.cpp`, the MSDL converter command line interface.

In these tools, and `oahOptionsVector` is instantiated and populated from `argc/argv` with `convertArgcArgvToOptions` defined in `src/oah/oahBasicTypes.h`:

```
1 EXP Bool convertArgcArgvToOptionsAndArguments (
2     int          argc,
3     char         *argv[],
4     oahOptionsVector& theOptionsVector)
```

Class `oahHandler` in `src/oah/oahBasicTypes.h/.cpp` contains:

```
1 // options and arguments handling
2 oahElementHelpOnlyKind
3         handleOptionsFromOptionsAndArguments (
4             string          serviceName,
5             const oahOptionsVector& theOptionsVector);
6
7 oahElementHelpOnlyKind
8         handleOptionsAndArgumentsFromArgcArgv (
9             int    argc,
10            char*  argv[]);
11
12 virtual void    checkOptionsAndArgumentsConsistency ();
13
14 virtual void    checkOptionsAndArguments () const = 0;
```

16.11 Applying options

Each `oahElement`, defined in `src/oah/oahElements.h/.cpp`, has an `applyElement` method:

```
1 virtual void    applyElement (ostream& os) = 0;
```

Atoms that can have an associated value are described in `src/oah/oahBasicTypes.h/.cpp` by class `oahAtomExpectingValue` which has methods `applyAtomWithValue` and `applyAtomWithDefaultValue`:

```
1 virtual void    applyAtomWithValue (
2     const string& theString,
3     ostream& os) = 0;
4
5 virtual void    applyAtomWithDefaultValue (ostream& os);
6 // used only if fElementValueKind
7 // is oahElementValueKind::kElementValueImplicit
8 // or oahElementValueKind::kElementValueOptional
```

There are two methods for that:

```
1 void    applyElement (ostream& os) override; %%%JMI
```

The last option is checked by method `oahHandler::checkMissingPendingArgvAtomExpectingAValueValue ()` in `src/oah/oahBasicTypes.cpp`.

16.12 A OAH atoms collection

Frequent OAH atoms have been grouped in `src/oah/oahAtomsCollection.h/.cpp`. They are:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src/oah > grep class oahAtomsCollection.h
2 class EXP oahAtomAlias : public oahAtom
3 class EXP oahMacroAtom : public oahAtom
4 class EXP oahOptionsUsageAtom : public oahPureHelpAtomWithoutAValue
5 class EXP oahHelpAtom : public oahPureHelpAtomWithoutAValue
6 class EXP oahHelpSummaryAtom : public oahPureHelpAtomWithoutAValue
7 class EXP oahAboutAtom : public oahPureHelpAtomWithoutAValue
8 class EXP oahVersionAtom : public oahPureHelpAtomWithoutAValue
9 class EXP oahContactAtom : public oahPureHelpAtomWithoutAValue
10 class EXP oahBooleanAtom : public oahAtom
11 class EXP oahTwoBooleansAtom : public oahBooleanAtom
12 class EXP oahThreeBooleansAtom : public oahBooleanAtom
13 class EXP oahCombinedBooleansAtom : public oahAtom
14 class EXP oahCommonPrefixBooleansAtom : public oahAtom
15 class EXP oahIntegerAtom : public oahAtomStoringAValue
16 class EXP oahTwoIntegersAtom : public oahIntegerAtom
17 class EXP oahFloatAtom : public oahAtomStoringAValue
18 class EXP oahStringAtom : public oahAtomStoringAValue
19 class EXP oahFactorizedStringAtom : public oahAtom
20 class EXP oahStringWithDefaultValueAtom : public oahStringAtom
21 class EXP oahRationalAtom : public oahAtomStoringAValue
22 class EXP oahNaturalNumbersSetElementAtom : public oahAtomStoringAValue
23 class EXP oahRGBColorAtom : public oahAtomStoringAValue
24 class EXP oahIntSetElementAtom : public oahAtomStoringAValue
25 class EXP oahStringSetElementAtom : public oahAtomStoringAValue
26 class EXP oahStringToIntMapElementAtom : public oahAtomStoringAValue
27 class EXP oahStringAndIntegerAtom : public oahAtomStoringAValue
28 class EXP oahStringAndTwoIntegersAtom : public oahAtomStoringAValue
29 class EXP oahLengthUnitKindAtom : public oahAtomStoringAValue
30 class EXP oahLengthAtom : public oahAtomStoringAValue
31 class EXP oahMidiTempoAtom : public oahAtomStoringAValue
32 class EXP oahOptionNameHelpAtom : public oahStringWithDefaultValueAtom
33 class EXP oahQueryOptionNameAtom : public oahPureHelpAtomExpectingAValue
34 class EXP oahFindStringAtom : public oahPureHelpAtomExpectingAValue

```

See chapter 39 [The OAH atoms collection], page 266, for more details.

16.13 An option and help example

Option `-beam-all-grace-notes` controls whether beams should be added to grace notes. Here is how it is implemented and used.

First, we must determine to which internal representation or conversion pass it is applied to. In this case, that is the conversion pass of an MXSR to MSR. Thus we have in `src/passes/mxsr2msr/mxsr2msrOah.h`:

```

1 class EXP mxsr2msrOahGroup : public oahGroup
2
3     Bool                                fBeamAllGraceNotes;
4
5     Bool                                getBeamAllGraceNotes () const
6                                     { return fBeamAllGraceNotes; }

```

In `src/passes/mxsr2msr/mxsr2msrOah.cpp`, the option is created this way:

```

1 void mxsr2msrOahGroup::initializeNotesOptions ()
2
3 // beam all grace notes
4 // -----
5
6 fBeamAllGraceNotes = false;
7
8 S_oahBooleanAtom
9   beamAllGraceNotesAtom =
10     oahBooleanAtom::create (
11       "beamagn", "beam-all-grace-notes",
12 R"(Add a beam to all grace notes)",
13       "beamAllGraceNotes",
14       fBeamAllGraceNotes);
15   subGroup->
16     appendAtomToSubGroup (
17       beamAllGraceNotesAtom);

```

And that's it.

The option value is checked in `src/passes/mxsr2msr/mxsr2msrTranslator.cpp.h/.cpp`:

```

1 void mxsr2msrTranslator::visitStart ( S_grace& elt )
2
3 // should all grace notes be beamed?
4 if (gGlobalMxsr2msrOahGroup->getBeamAllGraceNotes ()) {
5   fCurrentGraceIsBeamed = true;
6 }
7
8 void mxsr2msrTranslator::handleStandaloneOrDoubleTremoloNoteOrGraceNoteOrRest (
9   S_msrNote newNote)
10
11 // create grace notes group
12 fPendingGraceNotesGroup =
13   msrGraceNotesGroup::create (
14     inputLineNumber,
15     msrGraceNotesGroup::kGraceNotesGroupBefore, // default value
16     fCurrentGraceIsSlashed,
17     fCurrentGraceIsBeamed,
18     fCurrentMeasureNumber);

```

16.14 Options and help introspection

OAH represents options and the associated help in a tree of groups containing subgroups containing atoms. Searching it is easy, and there are options `-query` and `-find` for that.

Option `'-query'` provides informations about an option name:

```

1 jacquesmenu@macmini > xml2ly -query cpu
2 --- Help for atom "cpu" in subgroup "Informations"
3   -cpu, -display-cpu-usage
4     Write information about CPU usage to standard error.

```

Option `-find` searches the OAH tree ignoring letter cases:

```

1 jacquesmenu@macmini > xml2ly -find grace
2 5 occurrences of string "grace" have been found:
3   1:
4     -hgraces-group, -help-grace-notes-group
5
6   2:
7     -hgraces, -help-grace-notes

```

```

8
9 3:
10 -slashagn, -slash-all-grace-notes
11 Add a slash to all grace notes
12 4:
13 -sluragn, -slur-all-grace-notes
14 Add a slur to all grace notes
15 5:
16 -beamagn, -beam-all-grace-notes
17 Add a beam to all grace notes

```

These two options are implemented as `oahQueryOptionNameAtom` and `oahFindStringAtom` respectively in `src/oah/oahAtomsCollection.h/.cpp`.

16.15 Insider versus regular handlers

MusicFormats features two 'views' of the options and help available:

- the full view, named 'insider', contains the options grouped by format or pass;
- the default user view, named 'regular', contains options grouped by topic, such as tuplets or MIDI.

The 'regular' views have been introduced because there are many options and it was cumbersome to browse them without a user-oriented view by topics.

Class `oahRegularHandler` relies on the corresponding insider handler:

```

1 protected:
2
3 // protected fields
4 // -----
5
6 S_oahHandler          fInsiderHandler;

```

A regular handler merely selects options from the `fInsiderHandler`, and presents them in groups and subgroups its own way. The group names are hidden to the user, and only the subgroups are seen in the help provided to the user.

For example, in `src/clisamples/xml2xml/xml2xmlRegularHandler.cpp`, there is:

```

1 void xml2xmlRegularHandler::createInformationsRegularGroup ()
2 {
3 // group
4
5 S_oahGroup
6 group =
7     oahGroup::create (
8         "Informations group",
9         "help-informations-group", "hinfos-group",
10        "",
11        oahElementVisibilityKind::kElementVisibilityWhole);
12 appendGroupToRegularHandler (group);
13
14 // subgroup
15
16 S_oahSubGroup
17 subGroup =
18     oahSubGroup::create (
19         "Informations",
20         "help-informations", "hinfos",
21         "",

```



```

22     oahElementVisibilityKind::kElementVisibilityWhole,
23     group);
24 group->
25     appendSubGroupToGroup (subGroup);
26
27 // atoms from the insider handler
28
29 registerAtomInRegularSubgroup ("about", subGroup);
30 registerAtomInRegularSubgroup ("version", subGroup);
31 registerAtomInRegularSubgroup ("version-full", subGroup);
32 registerAtomInRegularSubgroup ("history", subGroup);
33 registerAtomInRegularSubgroup ("mf-version", subGroup);
34 registerAtomInRegularSubgroup ("mf-history", subGroup);
35 registerAtomInRegularSubgroup ("contact", subGroup);
36 registerAtomInRegularSubgroup ("display-prefixes", subGroup);
37 registerAtomInRegularSubgroup ("display-single-character-options", subGroup);
38
39 registerAtomInRegularSubgroup ("display-cpu-usage", subGroup);
40 }

```

An insider handler is always created, and a regular one relying on it is created if relevant. Here is how this is done this way, here in `src/clisamples/msdl.cpp`:

```

1 // create an msdlConverter insider OAH handler
2 // -----
3
4 S_msdlConverterInsiderHandler
5     insiderOahHandler =
6         msdlConverterInsiderHandler::create (
7             serviceName,
8             serviceName + " insider OAH handler with argc/argv",
9             multiGenerationOutputKind);
10
11 // the OAH handler to be used, a regular handler is the default
12 // -----
13
14 if (insiderOption) {
15     // use the insider msdlConverter OAH handler
16     handler = insiderOahHandler;
17 }
18 else {
19     // create a regular msdlConverter OAH handler
20     handler =
21         msdlConverterRegularHandler::create (
22             serviceName,
23             serviceName + " regular OAH handler with argc/argv",
24             insiderOahHandler,
25             multiGenerationOutputKind);
26 }

```

16.16 Deciphering the options and arguments

16.16.1 Options and arguments multi-pass analysis

The options and arguments are first placed in a `mfOptionsAndArguments` instance:

- the command line services do this with interface function `convertArgcArgvToOptionsAndArguments ()` in their function, for example in `src/clisamples/Mikrokosmos3Wandering.cpp`:

```

1 int main (int argc, char* argv[])
2 //-----
3 {
4     // ... ..
5
6     // create the global run data
7     // -----
8
9     gGlobalServiceRunData =
10     mfServiceRunData::create (serviceName);
11
12     // ... ..
13 }

```

- the API functions receive an `mfOptionsAndArguments` as an argument, here in `src/converters/musicxml2musicxml`

```

1 EXP mfMusicformatsError musicxmlfile2musicxml (
2     const char*          fileName,
3     mfOptionsAndArguments& handlerOptionsAndArguments,
4     std::ostream&         out,
5     std::ostream&         err)
6 {
7     SXMLFile
8     sxmlfile =
9     createSXMLFileFromFile (
10         fileName,
11         "Pass 1",
12         "Create an MXSR reading a MusicXML file");
13
14     if (sxmlfile) {
15         return
16         xmlFile2musicxmlWithOptionsAndArguments (
17             sxmlfile,
18             handlerOptionsAndArguments,
19             out,
20             err);
21     }
22
23     return mfMusicformatsError::kErrorInvalidFile;
24 }

```

This is done using a two-pass scheme:

- first, a list of the options uses is built;
- then, the options and their arguments, if any, in this list are applied.

Class `oahHandler` contains:

```

1     // elements uses
2     list<S_oahElementUse> fElementUsesList;
3
4     // atoms waiting for a value
5     S_oahAtomExpectingAValue
6     fPendingArgvAtomExpectingAValue;
7     string
8     fNameUsedForPendingArgvAtomExpectingAValue;

```

16.16.2 Pure help runs

A pure help run is one in which MusicFormats in which help, without any other option. In such a case the run quit silently, otherwise it proceeds to performs its task. The type describing that is enumeration type `oahElementHelpOnlyKind`, defined in `src/oah/oahElements.h`:

```
1 enum class oahElementHelpOnlyKind {
2     kElementHelpOnlyYes,
3     kElementHelpOnlyNo
4 };
```

16.16.3 Applying options

The options are applied in `src/oah/oahBasicTypes.cpp` by method `oahHandler::applyOptionsFromElementUsesList` defined in `src/oah/oahBasicTypes.h/.cpp`:

```
1 oahElementHelpOnlyKind oahHandler::applyOptionsFromElementUsesList ()
```

The heart of it is:

```
1 oahElementHelpOnlyKind oahHandler::applyOptionsFromElementUsesList ()
2 {
3     // ... ..
4
5     // the heart of it
6     if (
7         // group?
8         S_oahGroup
9         group =
10            dynamic_cast<oahGroup*>(&(*elementUsed))
11     ) {
12         group->
13             applyElement (
14                 gOutputStream);
15     }
16
17     else if (
18         // subgroup?
19         S_oahSubGroup
20         subGroup =
21            dynamic_cast<oahSubGroup*>(&(*elementUsed))
22     ) {
23         subGroup->
24             applyElement (
25                 gOutputStream);
26     }
27
28     else {
29         // this is an atom
30
31         S_oahAtom
32         atom =
33            dynamic_cast<oahAtom*>(&(*elementUsed));
34
35         oahElementValueKind
36         atomValueKind =
37             atom->
38                 getElementValueKind ();
39
40         if (
41             // atom expecting a value?
42             S_oahAtomExpectingAValue
43             atomExpectingAValue =
```

```

44         dynamic_cast<oahAtomExpectingAValue*>(&(*elementUsed))
45     ) {
46         switch (atomValueKind) {
47             case oahElementValueKind::kElementValueWithout:
48                 {
49                     stringstream s;
50
51                     s <<
52                         "Atom with value " <<
53                         atomExpectingAValue->fetchNamesBetweenQuotes () <<
54                         " has been registered as without value";
55
56                     oahInternalError (s.str ());
57                 }
58                 break;
59
60             case oahElementValueKind::kElementValueImplicit:
61                 atomExpectingAValue->
62                     applyAtomWithDefaultValue (
63                         gOutputStream);
64                 break;
65
66             case oahElementValueKind::kElementValueMandatory:
67                 if (valueUsed.size ()) {
68                     atomExpectingAValue->
69                         applyAtomWithValue (
70                             valueUsed,
71                             gOutputStream);
72                 }
73                 else {
74                     stringstream s;
75
76                     s <<
77                         "Atom expecting a value " <<
78                         atomExpectingAValue->fetchNamesBetweenQuotes () <<
79                         " needs a non-empty value";
80
81                     oahInternalError (s.str ());
82                 }
83                 break;
84
85             case oahElementValueKind::kElementValueOptional:
86                 if (valueUsed.size ()) {
87                     atomExpectingAValue->
88                         applyAtomWithValue (
89                             valueUsed,
90                             gOutputStream);
91                 }
92                 else {
93                     atomExpectingAValue->
94                         applyAtomWithDefaultValue (
95                             gOutputStream);
96                 }
97                 break;
98             } // switch
99     }
100
101     else {
102 #ifdef TRACING_IS_ENABLED
103         if (gGlobalOahEarlyOptions.getEarlyTracingOah ()) {
104             gLogStream <<
105                 "**** Handling atom not expecting a value:" <<
106                 endl;
107
108             ++gIndenter;
109
110             gLogStream <<

```

```

111         atom <<
112         endl;
113
114         --gIndenter;
115     }
116 #endif
117
118     atom->
119     applyElement (
120         gOutputStream);
121 }
122 }
123
124 // has a help-only been applied?
125 switch (elementUsed->getElementHelpOnlyKind ()) {
126     case oahElementHelpOnlyKind::kElementHelpOnlyYes:
127         // a help option has been applied
128         this->
129         setOahHandlerFoundAHelpOption (
130             elementUsed->
131             fetchNamesBetweenQuotes ());
132         break;
133     case oahElementHelpOnlyKind::kElementHelpOnlyNo:
134         break;
135 } // switch
136 }
137
138 else {
139     stringstream s;
140
141     s <<
142     "Element from the from the atom uses list for \"" <<
143     nameUsed <<
144     "\" is null";
145
146     oahInternalError (s.str ());
147
148     // ... ..
149 }

```

16.16.4 Early handling of some options

Debugging OAH needs the trace handling tracing options option `-trace-oah`, `-toah` and option `-trace-oah-detail`. `-toahd` to be activated first, even if they are not the first ones supplied.

The same holds to handle the option `-insider` option, since it involves using the insider handler and not a regular one.

Also, the `-quiet`, `-q` option should be handled early, to avoid errors in the options being reported.

Another case is the option `-trace-components`, `-tcomps` option. The versions data should exist when the option `-version`, `-v` is applied in method `oahVersionAtom::applyElement ()` in `src/oah/oahAtomsCollection.c` but building them should be able to produce a trace if this option is selected. This circularity circularity should thus be broken. Version history handling is presented in chapter ?? [musicformats components], page ??.

The early options names are declared in `src/oah/oahEarlyOptions.h`:

```

1 // ... ..
2
3 // insider
4 EXP extern const string K_INSIDER_OPTION_LONG_NAME;
5 EXP extern const string K_INSIDER_OPTION_SHORT_NAME;
6
7 // ... ..
8
9 class EXP oahEarlyOptions
10 {
11     // ... ..
12
13     public:
14
15         // set and get
16         // -----
17
18         void                setEarlyInsiderOption ();
19         Bool                getEarlyInsiderOption () const
20                             { return fEarlyInsiderOption; }
21
22         // ... ..
23
24     private:
25
26         // fields
27         // -----
28
29         Bool                fEarlyInsiderOption;
30
31         // ... ..
32 }

```

Then, in `src/oah/oahEarlyOptions.cpp`, there is:

```

1 // ... ..
2
3 const string K_INSIDER_OPTION_LONG_NAME  = "insider";
4 const string K_INSIDER_OPTION_SHORT_NAME = "ins";
5
6 void oahEarlyOptions::setEarlyInsiderOption ()
7 {
8     if (fTraceEarlyOptions) {
9         gLogStream <<
10             "Setting fEarlyInsiderOption" <<
11             endl;
12     }
13
14     fEarlyInsiderOption = true;
15 }
16
17 // ... ..

```

Method `oahEarlyOptions::applyEarlyOptionIfRelevant ()` performs the analysis:

```

1 void oahEarlyOptions::applyEarlyOptionIfRelevant (
2     const string& argumentWithoutDashToBeUsed,
3     const string& optionValue)
4 {
5     // this is OAH handling pass 1
6     if (
7         isEarlyOptionRecognized (
8             argumentWithoutDashToBeUsed, K_INSIDER_OPTION_LONG_NAME)
9         ||
10        isEarlyOptionRecognized (

```

```

11     argumentWithoutDashToBeUsed, K_INSIDER_OPTION_SHORT_NAME)
12 ) {
13     setEarlyInsiderOption ();
14 }
15
16 // ... ..
17 }

```

16.17 Implementing the -find option

Class `oahFindableElement` in `src/oah/oahElements.h/.cpp` is the base class of all those that can be found with this introspection option:

```

1 class EXP oahFindableElement : public smartable
2 {
3     public:
4
5         // creation from MusicXML
6         // -----
7
8         /* this class is purely virtual
9          * static SMARTP<oahFindableElement> create ();
10        */
11
12        // ... ..
13
14        public:
15
16            // public services
17            // -----
18
19            virtual Bool          findStringInFindableElement (
20                const string&      lowerCaseString,
21                list<S_oahFindStringMatch>& foundMatchesList,
22                ostream&           os) const = 0;
23
24        public:
25
26            // print
27            // -----
28
29            virtual string        asString () const = 0;
30
31            virtual void          print (ostream& os) const = 0;
32
33            virtual const string  containingFindableElementAsString () const = 0;
34
35        private:
36
37            // private fields
38            // -----
39 };

```

When matches are found, there are stored in a list of instances of `oahFindStringMatch`:

```

1 class oahFindStringMatch : public smartable
2 {
3     // ... ..
4
5     protected:
6
7         // protected fields
8         // -----

```

```

9
10     string                fFoundString;
11     string                fContainingFindableElementInfo;
12 };

```

The `fContainingFindableElementInfo` describes the OAH element that the string was found in, either in its option name(s) or in its description.

For example, method `oahHandler::findStringInFindableElement ()` in `src/oah/oahElement.cpp` creates an instance and appends it to the list :

```

1 Bool oahHandler::findStringInFindableElement (
2     const string&                lowerCaseString,
3     list<S_oahFindStringMatch>& foundMatchesList,
4     ostream&                    os) const
5 {
6     Bool result;
7
8     // .. .. .
9
10    // does this handler's header match?
11    Bool headerMatches =
12        mfStringToLowerCase (fHandlerHeader).find (lowerCaseString) != string::npos;
13
14    // does this handler's description match?
15    Bool descriptionMatches =
16        mfStringToLowerCase (fHandlerDescription).find (lowerCaseString) != string::npos;
17
18    // does this handler's usage match?
19    Bool usageMatches =
20        mfStringToLowerCase (fHandlerUsage).find (lowerCaseString) != string::npos;
21
22    if (headerMatches || descriptionMatches || usageMatches) {
23        stringstream s;
24
25        s <<
26            fHandlerHeader <<
27            ' ' <<
28            fHandlerDescription <<
29            ' ' <<
30            fHandlerUsage;
31
32        // append the match to foundStringsList
33        foundMatchesList.push_back (
34            oahFindStringMatch::create (
35                s.str (),
36                containingFindableElementAsString ());
37
38        result = true;
39    }
40
41    // do this handler's prefixes match?
42    if (fHandlerPrefixesMap.size ()) {
43        ++gIndenter;
44
45        for (
46            map<string, S_oahPrefix>::const_iterator i =
47                fHandlerPrefixesMap.begin ();
48            i != fHandlerPrefixesMap.end ();
49            ++i
50        ) {
51            S_oahPrefix
52                prefix = (*i).second;
53
54            // does the prefix match?
55            prefix->

```



```

56         findStringInFindableElement (
57             lowerCaseString,
58             foundMatchesList,
59             os);
60     } // for
61
62     --gIndenter;
63 }
64
65 // do this handler's groups match?
66 if (fHandlerGroupsList.size ()) {
67     ++gIndenter;
68
69     for (S_oahGroup group : fHandlerGroupsList) {
70         group->
71             findStringInGroup (
72                 lowerCaseString,
73                 foundMatchesList,
74                 os);
75     } // for
76
77     --gIndenter;
78 }
79
80 return result;
81 }

```

The same holds for method `oahPrefix::findStringInFindableElement ()` in `src/oah/oahElements.cpp`.

16.18 Checking options consistency

The options groups have a `checkGroupOptionsConsistency ()` to check that the use of the options if this group are consistent.

For example:

```

1 void mxsr2msrOahGroup::checkGroupOptionsConsistency ()
2 {
3 }

```

16.19 Adding new options

In order to make a new option available, one should:

- choose a short name and possibly a long name for the option;
- choose an atom class in `src/oah/oahAtomsCollection.h/.cpp` or write a new one if needed;
- decide in which subgroup and group the option should be made available in an insider OAH group, and create the latter two if needed;
- create a suitable atom and append it to the desired OAH subgroup;
- check the use of the atom wherever needed in the code base;
- add the new atom's long name to the corresponding regular OAH group;
- and last but not least... test the result.

This should be done first with the `-insider`, `-ins` option, and then without it to ensure that the regular OAH handler knows the new option too.

16.19.1 Representations' vs. passes' options

When adding a new option, it is sometimes not clear whether to assign it to a format or to the passes that create or browse it.

For example, the tracing of <backup/> and <forward/> is used by both `mxsr2msr0ah` and `msr2mxsr0ah`. The corresponding options are thus placed in `src/formats/mxsr/mxsr0ah.h/.cpp`:

16.19.2 Using an existing OAH atom class

When option `-reverse-names-display-order`, `-rndo` was added to OAH by this author:

- class `oahBooleanAtom` was ready to be used;
- it was decided to place it in the global variable `gGlobalOahOahGroup` OAH group, in its `Options help` sub group;
- class `oahOahGroup` in `src/oah/oahOah.h/.cpp` got a new `fReverseNamesDisplayOrder` field:

```

1 class EXP oahOahGroup : public oahGroup
2 {
3     void                setReverseNamesDisplayOrder ()
4                         { fReverseNamesDisplayOrder = true; }
5     Bool                getReverseNamesDisplayOrder () const
6                         { return fReverseNamesDisplayOrder; }
7
8     // ... ..
9
10    Bool                fReverseNamesDisplayOrder;
11
12    // ... ..
13 };

```

- method `oahOahGroup::initializeOahBasicHelpOptions ()` was augmented with:

```

1 void oahOahGroup::initializeOahBasicHelpOptions (
2     string serviceName)
3 {
4     // ... ..
5
6     // reverse names display order
7
8     fReverseNamesDisplayOrder = false;
9
10    subGroup->
11        appendAtomToSubGroup (
12            oahBooleanAtom::create (
13                "rndo", "reverse-names-display-order",
14                R"(Write the short names before the long ones.)",
15                "reverseNamesDisplayOrder",
16                fReverseNamesDisplayOrder));
17
18    // ... ..
19 }

```

- method `oahOahGroup::printOahOahValues ()` was augmented with:

```

1 void oahOahGroup::printOahOahValues (int valueFieldWidth)
2 {
3     gLogStream <<
4         "The basic options are:" <<
5         endl;
6
7     // ... ..
8
9     // options and help display
10    // -----
11
12    gLogStream << left <<
13        setw (valueFieldWidth) << "Options trace and display:" <<
14        endl;
15
16    ++gIndenter;
17
18    gLogStream << left <<
19        setw (valueFieldWidth) << "fReverseNamesDisplayOrder" << " : " <<
20        fReverseNamesDisplayOrder <<
21        endl <<
22
23    // ... ..

```

- then tests of the use of option `-reverse-names-display-order`, `-rndo` were added in `src/oah/oahElements.c` such as in method `oahElement::fetchNames ()`:

```

1 string oahElement::fetchNames () const
2 {
3     stringstream s;
4
5     if (
6         fShortName.size ()
7         &&
8         fLongName.size ()
9     ) {
10        if (gGlobalOahOahGroup->getReverseNamesDisplayOrder ()) {
11            s <<
12                '- ' << fShortName <<
13                ", " <<
14                '- ' << fLongName;
15        }
16        else {
17            s <<
18                '- ' << fLongName <<
19                ", " <<
20                '- ' << fShortName;
21        }
22    }
23
24    else {
25        if (fShortName.size ()) {
26            s <<
27                '- ' << fShortName;
28        }
29        if (fLongName.size ()) {
30            s <<
31                '- ' << fLongName;
32        }
33    }
34
35    return s.str ();
36 }

```

- and finally, all `*RegularHandler::createOahRegularGroup ()` methods were augmented with:

```

1 void msdl2brailleRegularHandler::createOahRegularGroup ()
2 {
3     // ... ..
4
5     registerAtomInRegularSubgroup ("reverse-names-display-order", subGroup);
6
7     // ... ..
8 }

```

16.19.3 Creating a new OAH atom class without a value

When class `oahHistoryAtom` was added to OAH, the first thing has been to add a `printHistory ()` in class `mfcMultiComponent` in `src/mfutilities/mfcBasicTypes.h`:

```

1 class mfcMultiComponent : public smartable
2 {
3     // ... ..
4
5     public:
6
7         // print
8         // -----
9
10        void                print (ostream& os) const;
11        void                printHistory (ostream& os) const;
12
13        // ... ..
14 };

```

Then the next thing has been to clone class `oahVersionAtom` in `src/oah/oahAtomCollection.h/.cpp`, renaming `printVersion ()` to `printHistory ()`:

```

1 //-----
2 class EXP oahHistoryAtom : public oahPureHelpAtomWithoutAValue
3 {
4     // ... ..
5
6     public:
7
8         // public services
9         // -----
10
11        void                applyElement (ostream& os) override;
12
13        public:
14
15        // visitors
16        // -----
17
18        void                acceptIn (basevisitor* v) override;
19        void                acceptOut (basevisitor* v) override;
20
21        void                browseData (basevisitor* v) override;
22
23        // print
24        // -----
25
26        void                print (ostream& os) const override;
27
28        void                printHistory (ostream& os) const;
29 };

```

Then in method `oahHistoryAtom::printHistory ()`, the call to `printVersion ()` has been replaced by a call to `printHistory ()`:

```

1 void oahHistoryAtom::applyElement (ostream& os)
2 {
3 #ifdef TRACING_IS_ENABLED
4     if (gGlobalOahEarlyOptions.getEarlyTracingOah ()) {
5         gLogStream <<
6             "==> option '" << fetchNames () << "' is a oahHistoryAtom" <<
7             endl;
8     }
9 #endif
10
11     int saveIndent = gIndenter.getIndent ();
12
13     gIndenter.resetToZero ();
14
15     printHistory (os);
16
17     gIndenter.setIndent (saveIndent);
18 }

```

method `:: ()` has the be adapted as:

```

1 void oahHistoryAtom::printHistory (ostream& os) const
2 {
3     // get the handler history
4     S_mfcMultiComponent
5         handlerMultiComponent =
6             fetchAtomHandlerUpLink ()->
7             getHandlerMultiComponent ();
8
9     // sanity check
10    mfAssert (
11        __FILE__, __LINE__,
12        handlerMultiComponent != nullptr,
13        "handlerMultiComponent is null");
14
15    handlerMultiComponent->
16        printHistory (os);
17 }

```

Then a new option has been added in method `oahOahGroup::initializeOahBasicHelpOptions ()`, in `src/oah/oahOah.cpp`:

```

1 // history
2
3 subGroup->
4     appendAtomToSubGroup (
5         oahHistoryAtom::create (
6             "hist", "history",
7             regex_replace (
8 R"(Display EXECUTABLE_NAME's history.)",
9                 regex ("EXECUTABLE_NAME"),
10                 serviceName),
11                 serviceName));

```

And the new option long name `version` has been added to all regular OAH handlers that already contained the option `-version`, `-v`, such as in method `xml2lyRegularHandler::createInformationsRegularGroup ()`, alongside the existing option `-version`, `-v`:

```

1 registerAtomInRegularSubgroup ("version", subGroup);
2 registerAtomInRegularSubgroup ("version-full", subGroup);
3 registerAtomInRegularSubgroup ("history", subGroup);
4 registerAtomInRegularSubgroup ("mf-version", subGroup);
5 registerAtomInRegularSubgroup ("mf-history", subGroup);

```

16.19.4 Creating a new OAH atom class expecting a value

Let's look at how class `oahLengthAtom` is implemented.

class `msrLength` is defined in `src/formats/msr/msrBasicTypes.h/.cpp`:

```

1  class EXP msrLength : public smartable
2  {
3      // ... ..
4
5      // public services
6      // -----
7
8      Bool                operator== (const msrLength& other) const
9                          {
10                             // JMI convert to same length unit kind before comparing
11
12                             return
13                                 fLengthUnitKind == other.fLengthUnitKind
14                                 &&
15                                 fLengthValue == other.fLengthValue;
16
17      Bool                operator!= (const msrLength& other) const
18                          { return ! ((*this) == other); }
19
20      void                convertToLengthUnit (
21                          msrLengthUnitKind lengthUnitKind);
22
23      // ... ..
24
25  private:
26
27      // private fields
28      // -----
29
30      msrLengthUnitKind    fLengthUnitKind;
31      float                fLengthValue;
32  };

```

Enumeration type `msrLengthUnitKind` is defined in `src/formats/msr/msrBasicTypes.h` as:

```

1  enum class msrLengthUnitKind {
2      kUnitInch, kUnitCentimeter, kUnitMillimeter
3  };

```

Here is the declaration of class `oahLengthAtom` in `src/oah/oahAtomsCollection.h`:

```

1  class EXP oahLengthAtom : public oahAtomStoringAValue
2  {
3      /*
4       * an atom controlling a length variable
5       */
6
7      // ... ..
8
9      public:
10
11         // set and get
12         // -----
13
14         void                setLengthVariable (
15                             msrLength value)
16                             {
17                                 fLengthVariable = value;
18                                 fSetByAnOption = true;
19

```

```

19         }
20
21     msrLength      getLengthVariable () const
22                     { return fLengthVariable; }
23
24 public:
25
26     // public services
27     // -----
28
29     void            applyAtomWithValue (
30                     const string& theString,
31                     ostream&      os) override;
32
33     // ... ..
34
35 public:
36
37     // print
38     // -----
39
40     // ... ..
41
42     void            printAtomWithVariableOptionsValues (
43                     ostream& os,
44                     int      valueFieldWidth) const override;
45
46 private:
47
48     // private fields
49     // -----
50
51     msrLength&      fLengthVariable;
52 };

```

Method `oahLengthAtom::applyAtomWithValue ()` in `src/oah/oahAtomsCollection.cpp` deciphers the string supplied by the user and stores it the class `msrLength` variable:

```

1 void oahLengthAtom::applyAtomWithValue (
2     const string& theString,
3     ostream&      os)
4 {
5     // ... ..
6
7     regex e (regularExpression);
8     smatch sm;
9
10    regex_match (theString, sm, e);
11
12    unsigned int smSize = sm.size ();
13
14    // ... ..
15
16    if (smSize == 4) {
17        // leave the low level details to the STL...
18        float floatValue;
19        {
20            stringstream s;
21            // concatenate the integer and decimal parts
22            s << sm [ 1 ] << sm [ 2 ];
23            s >> floatValue;
24        }
25
26        string lengthUnitName = sm [ 3 ];
27
28        // is lengthUnitName known in the length unit names map?

```

```

29     map<string, msrLengthUnitKind>::const_iterator
30     it =
31         gGlobalMsrLengthUnitKindsMap.find (
32             lengthUnitName);
33
34     if (it == gGlobalMsrLengthUnitKindsMap.end ()) {
35         // no, length unit name is unknown in the map
36
37         stringstream s;
38
39         s <<
40             "length unit name \"" << lengthUnitName <<
41             "\" is unknown" <<
42             endl <<
43             "The " <<
44             gGlobalMsrLengthUnitKindsMap.size () <<
45             " known length unit names are:" <<
46             endl;
47
48         ++gIndenter;
49
50         s <<
51             existingMsrLengthUnitKinds (K_NAMES_LIST_MAX_LENGTH);
52
53         --gIndenter;
54
55         oahError (s.str ());
56     }
57
58     setLengthVariable (
59         msrLength (
60             (*it).second,
61             floatValue));
62 }
63
64 else {
65     stringstream s;
66
67     s <<
68         "length value \"" << theString <<
69         "\" for option '" << fetchNames () <<
70         "' is ill-formed";
71
72     oahError (s.str ());
73 }
74 }

```

Method `oahLengthAtom::printAtomWithVariableOptionsValues ()` is in charge of displaying the length value when option `-display-options-valuesdov` is chosen:

```

1 void oahLengthAtom::printAtomWithVariableOptionsValues (
2     ostream& os,
3     int valueFieldWidth) const
4 {
5     os << left <<
6         setw (valueFieldWidth) <<
7         fVariableName <<
8         " : " <<
9         fLengthVariable.asString ();
10    if (fSetByAnOption) {
11        os <<
12            ", set by user";
13    }
14    os << endl;
15 }

```


Then an option to set the LilyPond paper height can be added to the relevant OAH options group in method `lpsrOahGroup::initializeLpsrPaperOptions ()` in `src/formats/lpsr//lpsrOah.cpp` by:

```

1 // paper height
2
3 fPaperHeight.setLengthUnitKind (msrLengthUnitKind::kUnitMillimeter);
4 fPaperHeight.setLengthValue (297);
5
6 fPaperHeightAtom =
7   oahLengthAtom::create (
8     "paper-height", "",
9     R"(Set the LilyPond 'paper-height' paper variable to HEIGHT in the LilyPond code.
10    HEIGHT should be a positive floating point or integer number,
11    immediately followed by a unit name, i.e. 'in', 'mm' or 'cm'.
12    By default, LilyPond uses 297 mm (A4 format).)",
13     "HEIGHT",
14     "paperHeight",
15     fPaperHeight);
16 subGroup->
17   appendAtomToSubGroup (
18     fPaperHeightAtom);

```

16.20 Extra options

The description of music scores in MusicFormats is quite rich, and it was easy (and tempting...) to offer options such as:

```

1 jacquesmenu@macmini > xml2ly -query show-harmony-analysis
2 --- Help for atom "show-harmony-analysis" in subgroup "Harmony analysis" of group "Extra"
3 ---
4 -sca, -show-harmony-analysis HARMONY_SPEC
5     Write an analysis of the harmony for the given diatonic (semitones) pitch
6     in the current language and the given harmony to standard output.
7     HARMONY_SPEC can be:
8     'ROOT_DIATONIC_PITCH HARMONY_NAME INVERSION'
9     or
10    "ROOT_DIATONIC_PITCH = HARMONY_NAME INVERSION"
11    Using double quotes allows for shell variables substitutions, as in:
12    HARMONY="maj7"
13    INVERSION=2
14    xml2ly -show-harmony-analysis "bes ${HARMONY} ${INVERSION}"

```

This is done in `src/oah/harmoniesExtraOah.h/.cpp`. It suffices to call function `createGlobalHarmoniesExtraOahG`.

```

1 #ifdef EXTRA_OAH_IS_ENABLED
2 // create the extra OAH group
3 appendGroupToHandler (
4   createGlobalHarmoniesExtraOahGroup ());
5 #endif

```

Macro `EXTRA_OAH_IS_ENABLED` is defined or not in `src/oah/enableHarmoniesExtraOahIfDesired.h`:

```

1 // comment the following definition if no extra options are wanted
2
3 #ifndef EXTRA_OAH_IS_ENABLED
4   #define EXTRA_OAH_IS_ENABLED
5 #endif

```

16.21 man pages generation

MusicFormats can create man pages for its command line tools by browsing their OAH hierarchy. This has not been finalized yet.

16.22 Specific global OAH groups

Some informations need to be available globally in the MusicFormats library, such as the conversion date and command line. They are grouped in `src/oah/generalOah.h/.cpp`:

```

1 class EXP generalOahGroup : public oahGroup
2 {
3     // ... ..
4
5     private:
6
7         // translation date
8         // -----
9
10        string                fTranslationDateFull;
11        string                fTranslationDateYYYYMMDD;
12
13        // warning and error handling
14        // -----
15
16        Bool                  fQuiet;
17
18        Bool                  fDontShowErrors;
19        Bool                  fDontQuitOnErrors;
20
21        Bool                  fDisplaySourceCodePositions;
22
23        // CPU usage
24        // -----
25
26        Bool                  fDisplayCPUUsage;
27 };

```

There are also harmonies-specific options grouped in `src/oah/harmoniesExtraOah.h/.cpp`. They are available as icing on the cake icing on the cake independently of any conversion activity:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src/oah > grep class harmoniesExtraOah.h
2 class EXP extraShowAllHarmoniesStructuresAtom : public oahAtomStoringAValue
3 class EXP extraShowAllHarmoniesContentsAtom : public oahAtomStoringAValue
4 class EXP extraShowHarmonyDetailsAtom : public oahAtomStoringAValue
5 class EXP extraShowHarmonyAnalysisAtom : public oahAtomStoringAValue
6 class EXP harmoniesExtraOahGroup : public oahGroup

```

```

1 class EXP harmoniesExtraOahGroup : public oahGroup
2 {
3     // ... ..
4
5     public:
6
7         // fields
8         // -----
9
10        string                fHarmoniesRootAsString;
11 };

```

16.23 Visiting OAH groups

As an internal representation, OAH can be browsed with the two-phase visitors. This is useful:

- to produce man pages automatically from the options available;
- to create the code that proposes the options to the user in a Web site, also automatically.

Part VI

Representations

Chapter 17

Representations general principles

17.1 Trees vs graphs

17.2 Denormalization

In databases, denormalization means that some data is present in several places. This is usually done for speed, at the cost of making updates more complex, since no such place should be ignored in an update.

MSR uses denormalization explicitly, with smart pointers to class instances being stored in other instances.

In particular, class `msrChord` contains elements that are actually detained by the notes it is composed of:

```
1 // articulations
2 list<S_msrArticulation>
3     fChordArticulations;
4
5 // spanners
6 list<S_msrSpanner>     fChordSpanners;
7
8 // single tremolo
9 S_msrSingleTremolo     fChordSingleTremolo;
```

This is to avoid having to browse the chord's components to obtain the corresponding information each time it is needed.

All such denormalization is done in MSR internally: the code using MSR does not have to denormalize itself. It can use whichever occurrence of any given denormalized data safely, though.

17.3 Newborn clones

The multi-pass structure of the converters build with `musicformat` leads to a question: should an existing description, such as that of a `barLine` or a `note`, be used as is, or should it be built again?

Depending of the kind of description, both possibilities are used:

- the description is used as is if it is shallow, i.e. it doesn't contain smart-pointers to data;
- otherwise, a new description is built, sharing some non smart-pointers fields with the existing one. This newborn clone is then populated with whatever is needed.

For example, in `src/passes/msr2lpsr/`, the `S_msrBarLine` values found in the MSR data are used also in the LPSR data:

```

1 void msr2lpsrTranslator::visitStart (S_msrBarLine& elt)
2 {
3 #ifdef TRACING_IS_ENABLED
4     int inputLineNumber =
5         elt->getInputLineNumber ();
6 #endif
7
8 #ifdef TRACING_IS_ENABLED
9     if (gGlobalMsrOahGroup->getTraceMsrVisitors ()) {
10         gLogStream <<
11             "--> Start visiting msrBarLine " <<
12             ", line " << inputLineNumber <<
13             endl;
14     }
15 #endif
16
17     // ... ..
18
19     // append the barLine to the current voice clone
20     fCurrentVoiceClone->
21         appendBarLineToVoice (elt);
22 }

```

On the opposite, a new `S_msrVoice` description is built for use by LPSR: this is how the LilyPond #34 issue is circumvented, adding skip notes where needed in the voices that don't have grace notes at their beginning.

Such new descriptions are created by `*NewbornClone ()` methods, such as:

```

1 S_msrTuplet msrTuplet::createTupletNewbornClone ()
2 {
3 #ifdef TRACING_IS_ENABLED
4     if (gGlobalTracingOahGroup->getTraceTuplets ()) {
5         gLogStream <<
6             "Creating a newborn clone of tuplet " <<
7             asString () <<
8             endl;
9     }
10 #endif
11
12     S_msrTuplet
13         newbornClone =
14         msrTuplet::create (
15             fInputLineNumber,
16             fMeasureElementMeasureNumber,
17             fTupletNumber,
18             fTupletBracketKind,
19             fTupletLineShapeKind,
20             fTupletShowNumberKind,
21             fTupletShowTypeKind,
22             fTupletFactor,
23             fMemberNotesSoundingWholeNotes,
24             fMemberNotesDisplayWholeNotes);
25
26     return newbornClone;
27 }

```

17.4 Deep clones

Some classes in MusicFormats, such as class `msrVoice` in `src/formats/msr/msrVoices.h/.cpp`, have a `*DeepClone ()` method:

```

1 SMARTP<msrVoice> createVoiceDeepClone (
2         int          inputLineNumber,
3         msrVoiceKind voiceKind,
4         int          voiceNumber,
5         S_msrStaff   containingStaff);

```

Deep copies of the MSR data is not used currently. This can be changed should the need arise in the future.

17.5 Inheritance

17.5.1 Single inheritance

Many classes in MusicFormats use single inheritance. For example, in `src/formats/msr/msrTimeSignature.h`:

```

1 class EXP msrTimeSignature : public msrMeasureElement
2 {
3     public:
4
5     // creation from MusicXML
6     // -----
7
8     static SMARTP<msrTimeSignature> create (
9         int          inputLineNumber,
10        msrTimeSignatureSymbolKind timeSignatureSymbolKind);
11
12    // creation from the applications
13    // -----
14
15    static SMARTP<msrTimeSignature> createTwoEightsTime (
16        int inputLineNumber);
17
18    // ... ..
19
20    // creation from the applications
21    // -----
22
23    static SMARTP<msrTimeSignature> createTimeFromString (
24        int      inputLineNumber,
25        string timeString);
26
27    // ... ..

```

The definitions in in `src/formats/msr/msrTimeSignature.cpp` are:

```

1 S_msrTimeSignature msrTimeSignature::create (
2     int          inputLineNumber,
3     msrTimeSignatureSymbolKind timeSignatureSymbolKind)
4 {
5     msrTimeSignature* o =
6         new msrTimeSignature (
7             inputLineNumber, timeSignatureSymbolKind);
8     assert (o != nullptr);
9     return o;
10 }
11
12 msrTimeSignature::msrTimeSignature (
13     int          inputLineNumber,

```

```

14   msrTimeSignatureSymbolKind timeSignatureSymbolKind)
15       : msrMeasureElement (inputLineNumber)
16   {
17       fTimeSignatureSymbolKind = timeSignatureSymbolKind;
18
19       fTimeIsCompound = false;
20   }

```

17.5.2 Single inheritance for smart pointers

All classes for which smart pointers are needed should inherit from class `smartable`, such as in `src/formats/msdl/msd`

```

1  class msdlScanner : public smartable
2  {
3      public:
4
5          // creation
6          // -----
7
8          static SMARTP<msdlScanner> create (istream& inputStream);
9
10     public:
11
12         // constructors/destructor
13         // -----
14
15         msdlScanner (istream& inputStream);
16
17         // ... ..
18 };

```

This leads to the following in `src/formats/msdl/msdlScanner.cpp`:

```

1  S_msdlScanner msdlScanner::create (istream& inputStream)
2  {
3      msdlScanner* o =
4          new msdlScanner (inputStream);
5      assert (o != nullptr);
6      return o;
7  }
8
9  msdlScanner::msdlScanner (istream& inputStream)
10     : fInputStream (
11         inputStream),
12       fCurrentToken (
13         ),
14       fCurrentTokenKind (
15         fCurrentToken.getTokenKindNonConst ()),
16       fCurrentTokenDescription (
17         fCurrentToken.getTokenDescriptionNonConst ())
18 {
19     // trace
20     #ifdef TRACING_IS_ENABLED
21         fTraceTokens = gGlobalMsd12msr0ahGroup->getTraceTokens ();
22         fTraceTokensDetails = gGlobalMsd12msr0ahGroup->getTraceTokensDetails ();
23     #endif
24
25     // ... ..
26 }

```


17.5.3 Multiple inheritance for visitors

Multiple inheritance is used extensively in visitors, which is the way to specify what elements are it seen by the visitor. For example, in `src/formats/msr/msr2msrTranslator.h`, there is:

```

1 class EXP msr2msrTranslator :
2
3     public visitor<S_msrScore>,
4
5     // rights
6
7     public visitor<S_msrIdentification>,
8
9     public visitor<S_msrCredit>,
10    public visitor<S_msrCreditWords>,
11
12    // ... ..
13 };

```

Then there are `visitStart ()` and/or `visitEnd ()` methods to handle the corresponding elements:

```

1 void msr2msrTranslator::visitStart (S_msrIdentification& elt)
2 {
3     #ifdef TRACING_IS_ENABLED
4         if (gGlobalMsrOahGroup->getTraceMsrVisitors ()) {
5             gLogStream <<
6                 "--> Start visiting msrIdentification" <<
7                 ", line " << elt->getInputLineNumber () <<
8                 endl;
9         }
10    #endif
11
12    ++gIndenter;
13
14    // set the current identification
15    fCurrentIdentification = elt;
16
17    // store it in the resulting MSR score
18    fResultingNewMsrScore->
19        setIdentification (
20            fCurrentIdentification);
21
22    fOnGoingIdentification = true;
23 }

```

```

1 void msr2msrTranslator::visitEnd (S_msrIdentification& elt)
2 {
3     fOnGoingIdentification = false;
4
5     --gIndenter;
6
7     #ifdef TRACING_IS_ENABLED
8         if (gGlobalMsrOahGroup->getTraceMsrVisitors ()) {
9             gLogStream <<
10                "--> End visiting msrIdentification" <<
11                ", line " << elt->getInputLineNumber () <<
12                endl;
13        }
14    #endif
15 }

```

Forgetting to define those `visit* ()` methods causes *no error message whatsoever*: the corresponding elements are just not handled by the visitor.

The visitors trace options are useful to detect such cases:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/files/musicxml > xml2ly -find visitors
2 3 occurrences of string "visitors" have been found:
3   1:
4     -tmxmltvis, -trace-mxsr-visitors
5     Write a trace of the MusicXML tree visiting activity to standard error.
6   2:
7     -tmsrvis, -trace-msr-visitors
8     Write a trace of the MSR graphs visiting activity to standard error.
9   3:
10    -tlpsrvis, -trace-lpsr-visitors
11    Write a trace of the LPSR graphs visiting activity to standard error.

```

17.5.4 Multiple inheritance in other classes

The only such case is class `mfIndentedOstream` in `src/utilities/mfIndentedTextOutput.cpp.h/.cpp`:

```

1 class EXP mfIndentedOstream: public ostream, public smartable
2 {
3   /*
4   Reference for this class:
5   https://stackoverflow.com/questions/2212776/overload-handling-of-stdendl
6
7   Usage:
8   mfIndentedOstream myStream (cout);
9
10  myStream <<
11    1 << 2 << 3 << endl <<
12    5 << 6 << endl <<
13    7 << 8 << endl;
14  */
15
16  public:
17
18    // creation
19    // -----
20
21    static SMARTP<mfIndentedOstream> create (
22      ostream& theOStream,
23      mfOutputIndenter& theIndenter)
24    {
25      mfIndentedOstream* o = new mfIndentedOstream (
26        theOStream,
27        theIndenter);
28      assert (o != nullptr);
29
30      return o;
31    }
32
33    // constructors/destructor
34    // -----
35
36    mfIndentedOstream (
37      ostream& theOStream,
38      mfOutputIndenter& theIndenter)
39      : ostream (
40        & fIndentedStreamBuf(),
41        fIndentedStreamBuf (
42          theOStream,
43          theIndenter)
44      ) {}
45
46    virtual ~mfIndentedOstream () {};
47

```

```

48 public:
49
50 // public services
51 // -----
52
53 // flush
54 void flush ()
55     { fIndentedStreamBuf.flush (); }
56
57 // indentation
58 mfOutputIndenter& getIndenter () const
59     { return fIndentedStreamBuf.getOutputIndenter (); }
60
61 void incrIndentation ()
62     { ++ (fIndentedStreamBuf.getOutputIndenter ()); }
63
64 void decrIndentation ()
65     { -- (fIndentedStreamBuf.getOutputIndenter ()); }
66
67 private:
68
69 // private fields
70 // -----
71
72 // mfIndentedOstream just uses an mfIndentedStreamBuf
73 mfIndentedStreamBuf fIndentedStreamBuf;
74
75 };
76 typedef SMARTP<mfIndentedOstream> S_indentedOstream;

```

17.5.5 Reversibility

All formats in MusicFormats that can be obtained by a conversion from another one should be convertible back in the latter, without information loss.

Thus:

- MXSR contains nearly everything that can be described in MusicXML data. The main exception at the time of this writing is the MIDI information, see subsection [25.1.1](#) [MusicXML coverage], page [219](#);
- MSR contains MusicXML-related informations, so as to convert it back to MXSR;
- LSPR and BSR contain an MSR component. This is why converting those formats back to MSR is merely getting the corresponding field.

Chapter 18

Displaying formats

MusicFormats is equipped with option `-display*` options as a help to the maintainer.

18.1 Display categories

18.2 Displaying in practise

```
1 %void lpsr2lilypondTranslator::generateCodeForNoteRegularInMeasure (
2 %   S_msrNote note)
3 %{
4 %   int inputLineNumber =
5 %       note->getInputLineNumber ();
6 %
7 %#ifdef TRACING_IS_ENABLED
8 %   if (gGlobalTracingOahGroup->getTraceNotes ()) {
9 %       stringstream s;
10 %
11 %       s <<
12 %       endl <<
13 %       "% --> generating code for noteRegularInMeasure " <<
14 %       note->asString () <<
15 %       ", line " << inputLineNumber <<
16 %       endl;
17 %
18 %       gLogStream          << s.str ();
19 %       fLilypondCodeStream << s.str ();
20 %   }
21 %#endif
22 %
23 %
```

Chapter 19

Music Scores Representation (MSR)

MSR is the central format of music scores in MusicFormats. It contains a very detailed representation of western notation music score elements. Most of it is handling music in a sequential way. See chapter 20 [MSR time-oriented representation], page 200, for a presentation of how it handles time-oriented concerns.

Some of the data in MSR are supplied by the code that uses MSR, as in class `msrSlur`:

```
1  static SMARTP<msrSlur> create (
2      int                inputLineNumber ,
3      int                slurNumber ,
4      msrSlurTypeKind    slurTypeKind ,
5      msrLineTypeKind    slurLineTypeKind ,
6      msrPlacementKind   slurPlacementKind);
7
8  // ... ..
9
10 // private fields
11 // -----
12
13
14 int                fSlurNumber;
15
16 msrSlurTypeKind    fSlurTypeKind;
17
18 msrLineTypeKind    fSlurLineTypeKind;
19
20 msrPlacementKind   fSlurPlacementKind;
```

Other data are computed by the MSR private methods. For example, in `src/formats/msr/msrVoices.h`:

```
1  // there can only be 4 regular voices in a staff
2  // (those that can contain beamed notes)
3  // and we need a number for the orientation of beams
4  int                fRegularVoiceStaffSequentialNumber;
5
6  // ... ..
7
8  // fVoiceShortestNoteDuration and fVoiceShortestNoteTupletFactor
9  // are used to compute a number of divisions per quarter note
10 // if needed, such as when generating MusicXML from MSR
11 rational            fVoiceShortestNoteDuration;
12 msrTupletFactor      fVoiceShortestNoteTupletFactor;
```

There are also data that varies during the lifetime of the object, while it is being populated for example. One such case is class `msrMeasure`:

```

1    rational                fCurrentMeasureWholeNotesDuration;
2                            // this increases when musical elements
3                            // are appended to the measure

```

MSR has been designed to be as general as possible, leading it to contain informations fitted to the various textual formats that can be converted to it or output from it by MusicFormats tools.

It is a *very fine-grained* representation of scores:

- some informations it contains are present as such in the textual formats;
- others are computed when the representation is populated, such as, in `src/formats/msr/msrVoices.h`:

```

1    rational                fVoiceShortestNoteDuration;

```

This information is used when generating MusicXML output to set the `<divisions/>` value.

LPSR and BSR contain an MSR as a sub-component, in order to allow for easy two-way conversion. This avoids the loss of information. This is why converting LPSR and BSR to MSR is done at no cost: just get the MSR component.

Both LPSR and BSR complement their MSR sub-component with whatever is needed for their purpose:

- LPSR contains a description of the structure of the score for the needs of LilyPond output and export from LilyPond when this becomes available;
- BSR contains a description of how to layout the braille cell on the embossed page, in terms of cells per line and lines per page.

19.1 MSR basic types

Some types used throughout MSR are defined in `src/formats/msr/msrBasicTypes.h/.cpp`:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src/formats/msr > egrep -rIn '^// '
   msrBasicTypes.h
2 msrBasicTypes.h:29:// input line numbers
3 msrBasicTypes.h:34:// names lists max length
4 msrBasicTypes.h:35:// -----
5 msrBasicTypes.h:39:// XMLLang
6 msrBasicTypes.h:52:// diatonic pitches
7 msrBasicTypes.h:69:// alterations
8 msrBasicTypes.h:90:// accidentals
9 msrBasicTypes.h:124:// editorial accidentals
10 ... ..
11 msrBasicTypes.h:1840:// moments
12 msrBasicTypes.h:1938:// tuplet factors
13 msrBasicTypes.h:2024:// harmonies intervals
14 msrBasicTypes.h:2134:// harmonies structure
15 msrBasicTypes.h:2231:// harmonies contents
16 msrBasicTypes.h:2320:// harmonies details and analysis
17 msrBasicTypes.h:2333:// RGB colors
18 msrBasicTypes.h:2391:// AlphaRGB colors
19 msrBasicTypes.h:2444:// score notation kinds
20 msrBasicTypes.h:2455:// global variables
21 msrBasicTypes.h:2500:// initialization

```

19.2 Data matching across formats

Choices have to be made regarding the way we represent music scores elements, since this varies across formats.

In particular, the way MusicXML structures the elements is not what MSR does. For example, class `msrIdentification` in `src/formats/msr/msrIdentification.h` contains:

```

1 class EXP msrIdentification : public msrElement
2 {
3     // ... ..
4
5     private:
6
7         // private fields
8         // -----
9
10        // work
11        string                fWorkNumber;
12
13        // ... ..
14
15        // creators
16
17        // ... ..
18
19        list<string>          fSoftwaresList;
20
21        // ... ..
22 };

```

This information is stored in distinct elements in MusicXML:

```

1 <score-partwise>
2   <work>
3     <work-number>K. 331</work-number>
4     <work-title>Piano Sonata in A Major</work-title>
5   </work>
6   <identification>
7     <creator type="composer">Wolfgang Amadeus Mozart</creator>
8     <rights>Copyright © 2003 Recordare LLC</rights>
9     <encoding>
10      <software>Finale 2003 for Windows</software>
11      <software>Dolet for Finale 1.3</software>
12      <encoding-date>2003-03-14</encoding-date>
13    </encoding>

```

The same occurs for MusicXML's `<direction/>` elements, that contain distinct subelements `<words/>` and `<metronome/>`:

```

1   <direction>
2     <direction-type>
3       <words>Adagio</words>
4     </direction-type>
5     <direction-type>
6       <metronome>
7         <beat-unit>long</beat-unit>
8         <per-minute>100</per-minute>
9       </metronome>
10    </direction-type>
11  </direction>

```

Note that two `<direction-type/>` elements are needed, since only one of `<words/>` and `<metronome/>` can be present in a given instance, as stated in `direction.mod`:

```

1 <!ELEMENT direction-type (rehearsalMark+ | segno+ | coda+ |
2 (words | symbol)+ | wedge | dynamics+ | dashes |
3 bracket | pedal | metronome | octave-shift | harp-pedals |
4 damp | damp-all | eyeglasses | string-mute |
5 scordatura | image | principal-voice | percussion+ |
6 accordion-registration | staff-divide | other-direction)>

```

This is not a problem in GUI applications, since all those elements are simply *drawn*. MSR stores this in a single class `msrTempo` class in `src/formats/msr/msrTempos.h/.cpp`, since musicians use tempo indications as a whole. See chapter 43 [Tempos handling], page 297 and section 19.18 [Tempos], page 175 for more details.

19.3 Lengths

There are several cases where a length is used in MSR, hence:

```

1 enum class msrLengthUnitKind {
2     kUnitInch, kUnitCentimeter, kUnitMillimeter
3 };

```

```

1 class EXP msrLength : public smartable
2 {
3     // ... ..
4
5     msrLengthUnitKind    fLengthUnitKind;
6     float                fLengthValue;

```

19.4 Positions in measures and moments

Such positions are represented by rational numbers such as 3/8, 1/1 being a whole note.

Class `msrMoment` stores a position in a measure, with a relative offset since harmonies can be placed on a note during its sounding time:

```

1     rational                fWrittenPositionInMeseasure;
2     rational                fSoundingRelativeOffset;

```

19.5 Rests and skips

A skip is an invisible rest, i.e. the meaning is the same as that in LilyPond. Skips are created to fill the holes between notes wherever needed, in order for all voices to be notes/rests/skips sequences.

Skips are also created in `src/passes/msr2lpsr/` to circumvent the LilyPond #34 issue.

19.6 Solo notes and rests

A solo note or rest is characterized as sounding alone in its multi-voice staff for its whole duration.

In the case of a solo rests, such detection allows for better output, in particular when LilyPond code is generated.

An example is at figure 19.1 [The solo rests problem], page 168 : the eighth rests in the second measure of voice 1 of the first staff should be placed on the middle line of the staff, as **MuseScore** does.



Figure 19.1: The solo rests problem

19.7 Linear versus time-oriented representation

Most music scoring GUI applications handle music as containing voices, which are made of sequences of notes, chords, tuplets and such. This is a horizontal, linear view of the music in the score.

Another view of the music is time-oriented, i.e., what are notes being played at a given moment in time? This is a vertical view of the music, which is highlighted in piano roll views.

MSR stores descriptions of so-called 'measures slice' through class `msrMeasuresSlice`, defined in `src/formats/msr/msrMeasuresSlice.h`. Then a time-oriented view of a voice, staff or part is a sequence of such measure slices, defined in class `msrMeasuresSlicesSequence`.

An class `msrMeasuresSlice` contains basically a slice measures vector:

```
1 // the measures in the slice
2 vector<S_msrMeasure> fSliceMeasuresVector;
```

From this, the following other descriptions are derived:

```
1 // notes flat list
2 list<S_msrNote> fSliceNotesFlatList;
3
4 // note events list
5 list<S_msrNoteEvent> fSliceNoteEventsList;
6
7 // simultaneous notes chunks list
8 list<S_msrSimultaneousNotesChunk>
9 fSliceSimultaneousNotesChunksList;
```

Note events are distinguished with enumeration type `msrNoteEventKind`:

```
1 // -----
2 enum class msrNoteEventKind {
3     kNoteEventStart,
4     kNoteEventStop
5 };
```

Class `msrNoteEvent` contains:

```
1 rational fNoteEventPositionInMeasure;
2 S_msrNote fNoteEventNote;
3 msrNoteEventKind fNoteEventKind;
```

19.8 Spanners

A spanner... spans from one note or rest to another one. A choice to be made about when to use spanners: should wedges < and > be handled as spanners, or simply as being attached to notes? It has been chosen to use spanners only for ligatures apart from true spanners.

MusicXML uses "start", "start" and "start" attributes, which need to be present in MSR for MusicXML generation. They are reflected in MSR as enumeration type enumeration type `msrSpannerTypeKind`, defined this way:

```
1 // spanner types
2 // -----
3 enum class msrSpannerTypeKind {
4     k_NoSpannerType,
5
6     kSpannerTypeStart, kSpannerTypeContinue, kSpannerTypeStop
7 };
```

19.9 Uplinks and sidelinks

An uplink is a direct pointer from one class instance to one that contains it. class `msrNote` contains:

```
1     S_msrChord          fNoteDirectChordUpLink;
2     S_msrGraceNotesGroup fNoteDirectGraceNotesGroupUpLink;
3     S_msrTuplet         fNoteDirectTupletUpLink;
4     S_msrMeasure        fNoteDirectMeasureUpLink;
```

A sidelink is used in ligatures and spanners, so that each end of the structure can reference the other one:

```
1 msrLigatures.h:      S_msrLigature          fLigatureOtherEndSideLink; // two-way
2
3 msrSpanners.h:      S_msrSpanner          fSpannerOtherEndSideLink; // two-way
```

19.10 Sounding and displayed durations

All durations are represented by rational numbers whose denominators are powers of 2, such as `rational` (3, 16, and relative to the duration of a whole note).

This information is a field of class `msrMeasureElement`:

```
1     rational          fMeasureElementSoundingWholeNotes;
```

In a tuplet, the sounding durations is different than the written durations, so we store the sounding

```
1 // whole notes
2 rational          fNoteDisplayWholeNotes;
3
4 int              fNoteDotsNumber;
5
6 msrDurationKind   fNoteGraphicDurationKind;
7
8 msrTupletFactor    fNoteTupletFactor;
9
10 msrQuarterTonesPitchKind
11     fNoteQuarterTonesDisplayPitchKind;
12 msrOctaveKind     fNoteDisplayOctaveKind;
13 // for unpitched notes
14 // and pitched rests
```

19.11 Printing descriptions

There is a standard set of methods to print the contents of the descriptions in MusicFormats to standard output, depending on the granularity of the information to be displayed:

```

1 void print (ostream& os) const override;
2
3 string asString () const override;
4 string asStringShort () const override;
```

There are also more specific methods such as:

```

1 void printShort (ostream& os) const override;
2
3 void printSummary (ostream& os) const override;
```

Note that:

- virtual method `asString ()` produces a rather condensed view of the data to be displayed as part of a single line;
- virtual method `print ()` may produce its output on multiples lines, which always ends with an end of line.

Most classes in MusicFormats can be printed with the `<<` operator:

```

1 ostream& operator<< (ostream& os, const S_msrElement& elt)
2 {
3     if (elt) {
4         elt->print (os);
5     }
6     else {
7         os << "*** NONE ***" << endl;
8     }
9
10    return os;
11 }
```

In simple cases, virtual method `print ()` merely calls virtual method `asString ()`:

```

1 void msrElement::print (ostream& os) const
2 {
3     os << asString () << endl;
4 }
```

All virtual method `asString ()` methods produce an output of the form [...], in order to facilitate selecting the whole with a double click to help the user, since such output can be nested:

```

1 string msrTransposition::asString () const
2 {
3     stringstream s;
4
5     s <<
6     "[Transposition" <<
7     ", fTranspositionDiatonic = " << fTranspositionDiatonic <<
8     ", fTranspositionChromatic = " << fTranspositionChromatic <<
9     ", fTranspositionOctaveChange = " << fTranspositionOctaveChange <<
10    ", fTranspositionDouble = " << fTranspositionDouble <<
11    ", line " << fInputLineNumber <<
12    "]" ;
13
14    return s.str ();
15 }
```

A typical sequence to produce indented output is:

```

1 void msrTransposition::print (ostream& os) const
2 {
3     const int fieldWidth = 22;
4
5     os <<
6     "Transposition" <<
7     ", line " << fInputLineNumber <<
8     endl;
9
10    ++gIndenter;
11
12    os << left <<
13        setw (fieldWidth) <<
14        "fTranspositionDiatonic" << " = " << fTranspositionDiatonic <<
15        endl <<
16        setw (fieldWidth) <<
17        "fTranspositionChromatic" << " = " << fTranspositionChromatic <<
18        endl <<
19        setw (fieldWidth) <<
20        "fTranspositionOctaveChange" << " = " << fTranspositionOctaveChange <<
21        endl <<
22        setw (fieldWidth) <<
23        "fTranspositionDouble" << " = " << fTranspositionDouble <<
24        endl << endl;
25
26    --gIndenter;
27 }

```

The main indented output streams are:

```

1 #define gOutputStream *gGlobalOutputIndentedOstream
2 #define gLogStream    *gGlobalLogIndentedOstream

```

19.12 Pitches

MSR handle diatonic, semitone and quarter tone pitches, defined in `src/formats/msr/msrBasicTypes.h` as shown below. All pitches data is represented internally as quater tones pitches, and conversions are done wherever needed.

```

1 // diatonic pitches
2 // -----
3 enum class msrDiatonicPitchKind {
4     k_NoDiatonicPitch,
5
6     // starting at C for LilyPond relative octave calculations
7     kDiatonicPitchC,
8     kDiatonicPitchD, kDiatonicPitchE, kDiatonicPitchF,
9     kDiatonicPitchG, kDiatonicPitchA, kDiatonicPitchB
10 };

```

```

1 // semi tones pitches
2 // -----
3 enum class msrSemiTonesPitchKind {
4     kSTP_NoSemiTonesPitch,
5
6     kSTP_C_TripleFlat,
7     kSTP_C_DoubleFlat, kSTP_C_Flat,
8     kSTP_C_Natural,
9     kSTP_C_Sharp, kSTP_C_DoubleSharp,
10    kSTP_C_TripleSharp,
11 }

```

```

12  kSTP_D_TripleFlat,
13  kSTP_D_DoubleFlat, kSTP_D_Flat,
14  kSTP_D_Natural,
15  kSTP_D_Sharp, kSTP_D_DoubleSharp,
16  kSTP_D_TripleSharp,
17
18  kSTP_E_TripleFlat,
19  kSTP_E_DoubleFlat, kSTP_E_Flat,
20  kSTP_E_Natural,
21  kSTP_E_Sharp, kSTP_E_DoubleSharp,
22  kSTP_E_TripleSharp,
23
24  kSTP_F_TripleFlat,
25  kSTP_F_DoubleFlat, kSTP_F_Flat,
26  kSTP_F_Natural,
27  kSTP_F_Sharp, kSTP_F_DoubleSharp,
28  kSTP_F_TripleSharp,
29
30  kSTP_G_TripleFlat,
31  kSTP_G_DoubleFlat, kSTP_G_Flat,
32  kSTP_G_Natural,
33  kSTP_G_Sharp, kSTP_G_DoubleSharp,
34  kSTP_G_TripleSharp,
35
36  kSTP_A_TripleFlat,
37  kSTP_A_DoubleFlat, kSTP_A_Flat,
38  kSTP_A_Natural,
39  kSTP_A_Sharp, kSTP_A_DoubleSharp,
40  kSTP_A_TripleSharp,
41
42  kSTP_B_TripleFlat,
43  kSTP_B_DoubleFlat, kSTP_B_Flat,
44  kSTP_B_Natural,
45  kSTP_B_Sharp, kSTP_B_DoubleSharp,
46  kSTP_B_TripleSharp
47 };

```

```

1  // quarter tones pitches
2  // -----
3  enum class msrQuarterTonesPitchKind {
4      k_NoQuarterTonesPitch,
5
6      kQTP_Rest, kQTP_Skip,
7
8      kQTP_A_TripleFlat,
9      kQTP_A_DoubleFlat, kQTP_A_SesquiFlat, kQTP_A_Flat, kQTP_A_SemiFlat,
10     kQTP_A_Natural,
11     kQTP_A_SemiSharp, kQTP_A_Sharp, kQTP_A_SesquiSharp, kQTP_A_DoubleSharp,
12     kQTP_A_TripleSharp,
13
14     kQTP_B_TripleFlat,
15     kQTP_B_DoubleFlat, kQTP_B_SesquiFlat, kQTP_B_Flat, kQTP_B_SemiFlat,
16     kQTP_B_Natural,
17     kQTP_B_SemiSharp, kQTP_B_Sharp, kQTP_B_SesquiSharp, kQTP_B_DoubleSharp,
18     kQTP_B_TripleSharp,
19
20     kQTP_C_TripleFlat,
21     kQTP_C_DoubleFlat, kQTP_C_SesquiFlat, kQTP_C_Flat, kQTP_C_SemiFlat,
22     kQTP_C_Natural,
23     kQTP_C_SemiSharp, kQTP_C_Sharp, kQTP_C_SesquiSharp, kQTP_C_DoubleSharp,
24     kQTP_C_TripleSharp,
25
26     kQTP_D_TripleFlat,
27     kQTP_D_DoubleFlat, kQTP_D_SesquiFlat, kQTP_D_Flat, kQTP_D_SemiFlat,
28     kQTP_D_Natural,
29     kQTP_D_SemiSharp, kQTP_D_Sharp, kQTP_D_SesquiSharp, kQTP_D_DoubleSharp,

```

```

30  kQTP_D_TripleSharp,
31
32  kQTP_E_TripleFlat,
33  kQTP_E_DoubleFlat, kQTP_E_SesquiFlat, kQTP_E_Flat, kQTP_E_SemiFlat,
34  kQTP_E_Natural,
35  kQTP_E_SemiSharp, kQTP_E_Sharp, kQTP_E_SesquiSharp, kQTP_E_DoubleSharp,
36  kQTP_E_TripleSharp,
37
38  kQTP_F_TripleFlat,
39  kQTP_F_DoubleFlat, kQTP_F_SesquiFlat, kQTP_F_Flat, kQTP_F_SemiFlat,
40  kQTP_F_Natural,
41  kQTP_F_SemiSharp, kQTP_F_Sharp, kQTP_F_SesquiSharp, kQTP_F_DoubleSharp,
42  kQTP_F_TripleSharp,
43
44  kQTP_G_TripleFlat,
45  kQTP_G_DoubleFlat, kQTP_G_SesquiFlat, kQTP_G_Flat, kQTP_G_SemiFlat,
46  kQTP_G_Natural,
47  kQTP_G_SemiSharp, kQTP_G_Sharp, kQTP_G_SesquiSharp, kQTP_G_DoubleSharp,
48  kQTP_G_TripleSharp
49  };

```

19.13 Octaves

They are represented with enumeration type :

```

1  // octaves
2  // -----
3  enum class msrOctaveKind {
4      k_NoOctave,
5
6      kOctave0, kOctave1, kOctave2, kOctave3,
7      kOctave4, // that of middle C
8      kOctave5, kOctave6, kOctave7, kOctave8, kOctave9
9  };

```

For the needs of LilyPond and MSDL, MSR also contains a description of how to enter octaves:

```

1  // octave entry
2  // -----
3  enum class msrOctaveEntryKind {
4      kOctaveEntryRelative,
5      kOctaveEntryAbsolute,
6      kOctaveEntryFixed
7  };

```

19.14 Durations

MusicFormats represents durations with enumeration type `msrDurationKind`, defined in `src/formats/msr/msrBasic`

```

1  // durations
2  // -----
3  enum class msrDurationKind {
4      k_NoDuration,
5
6      // from longest to shortest for the algorithms
7      kMaxima, kLonga, kBreve, kWhole, kHalf,
8      kQuarter,
9      kEighth, k16th, k32nd, k64th, k128th, k256th, k512th, k1024th
10 };

```

19.15 Alterations

```

1 // alterations
2 // -----
3 enum class msrAlterationKind {
4     k_NoAlteration,
5
6     kAlterationTripleFlat, kAlterationDoubleFlat, kAlterationSesquiFlat,
7     kAlterationFlat, kAlterationSemiFlat,
8     kAlterationNatural,
9     kAlterationSemiSharp, kAlterationSharp, kAlterationSesquiSharp,
10    kAlterationDoubleSharp, kAlterationTripleSharp

```

19.16 Accidentals

```

1 // accidentals
2 // -----
3 enum class msrAccidentalKind {
4     kAccidentalNone,
5
6     kAccidentalSharp, kAccidentalNatural,
7     kAccidentalFlat, kAccidentalDoubleSharp,
8     kAccidentalSharpSharp,
9     kAccidentalFlatFlat, kAccidentalNaturalSharp,
10    kAccidentalNaturalFlat, kAccidentalQuarterFlat,
11    kAccidentalQuarterSharp, kAccidentalThreeQuartersFlat,
12    kAccidentalThreeQuartersSharp,
13
14    kAccidentalSharpDown, kAccidentalSharpUp,
15    kAccidentalNaturalDown, kAccidentalNaturalUp,
16    kAccidentalFlatDown, kAccidentalFlatUp,
17    kAccidentalTripleSharp, kAccidentalTripleFlat,
18    kAccidentalSlashQuarterSharp, kAccidentalSlashSharp,
19    kAccidentalSlashFlat, kAccidentalDoubleSlashFlat,
20    kAccidentalSharp_1, kAccidentalSharp_2,
21    kAccidentalSharp_3, kAccidentalSharp_5,
22    kAccidentalFlat_1, kAccidentalFlat_2,
23    kAccidentalFlat_3, kAccidentalFlat_4,
24    kAccidentalSori, kAccidentalKoron,
25
26    kAccidentalOther
27 };

```

19.17 Durations

They are represented in MSR with the enumeration type `msrDurationKind` enumeration type, defined in `src/formats/msr/msrBasicTypes.h`:

```

1 // durations
2 // -----
3 enum class msrDurationKind {
4     k_NoDuration,
5
6     // from longest to shortest for the algorithms
7     kMaxima, kLonga, kBreve, kWhole, kHalf,
8     kQuarter,
9     kEighth, k16th, k32nd, k64th, k128th, k256th, k512th, k1024th
10 };

```

Class `msrDottedDuration` contains:

```
1   msrDurationKind      fDurationKind;
2   int                  fDotsNumber;
```

19.18 Tempos

There are thus several kinds of tempos in MSR, with variants represented by enumeration type `msrTempoKind` in `src/formats/msr/msrTempos.h`:

```
1 class EXP msrTempo : public msrMeasureElement
2 {
3     public:
4
5         // data types
6         // -----
7
8         enum msrTempoKind {
9             k_NoTempoKind,
10            kTempoBeatUnitsWordsOnly,
11            kTempoBeatUnitsPerMinute,
12            kTempoBeatUnitsEquivalence,
13            kTempoNotesRelationship
14        };
15
16        // ... ..
17
18        enum msrTempoParenthesizedKind {
19            kTempoParenthesizedYes, kTempoParenthesizedNo
20        };
21
22        // ... ..
23
24        enum msrTempoNotesRelationshipKind {
25            kTempoNotesRelationshipNone, kTempoNotesRelationshipEquals
26        };
27
28        // ... ..
29    };
```

19.18.1 Tempos notes

A tempo indication can contain a note a notes in a tuplet. Such notes are described by class `msrTempoNote`:

```
1 class EXP msrTempoNote : public msrElement
2 {
3     public:
4
5         // creation from MusicXML
6         // -----
7
8         static SMARTP<msrTempoNote> create (
9             int          inputLineNumber,
10            const rational& tempoNoteWholeNotes,
11            Bool          tempoNoteBelongsToATuplet);
12
13     protected:
14
15         // constructors/destructor
16         // -----
17 }
```



```

18         msrTempoNote (
19             int            inputLineNumber ,
20             const rational& tempoNoteWholeNotes ,
21             Bool           tempoNoteBelongsToATuplet);
22
23     // ... ..
24
25 private:
26
27     // private fields
28     // -----
29
30     rational            fTempoNoteWholeNotes;
31
32     list<S_msrBeam>      fTempoNoteBeams;
33
34     Bool                fTempoNoteBelongsToATuplet;
35 };

```

19.18.2 Tempos tuplets

A tuplet in a tempo representation is described by class `msrTempoTuplet`:

```

1 // -----
2 class EXP msrTempoTuplet : public msrElement
3 {
4     public:
5
6     // data types
7     // -----
8
9     enum msrTempoTupletTypeKind {
10         kTempoTupletTypeNone ,
11         kTempoTupletTypeStart , kTempoTupletTypeStop
12     };
13
14     // ... ..
15
16     enum msrTempoTupletBracketKind {
17         kTempoTupletBracketYes , kTempoTupletBracketNo
18     };
19
20     // ... ..
21
22     enum msrTempoTupletShowNumberKind {
23         kTempoTupletShowNumberActual ,
24         kTempoTupletShowNumberBoth ,
25         kTempoTupletShowNumberNone
26     };
27
28     // ... ..
29
30     // creation from MusicXML
31     // -----
32
33     static SMARTP<msrTempoTuplet> create (
34         int            inputLineNumber ,
35         int            tempoTupletNumber ,
36         msrTempoTupletBracketKind tempoTupletBracketKind ,
37         msrTempoTupletShowNumberKind tempoTupletShowNumberKind ,
38         msrTupletFactor tempoTupletFactor ,
39         rational        memberNotesDisplayWholeNotes);
40
41     protected:

```

```

42
43 // constructors/destructor
44 // -----
45
46 msrTempoTuplet (
47     int                inputLineNumber,
48     int                tempoTupletNumber,
49     msrTempoTupletBracketKind  tempoTupletBracketKind,
50     msrTempoTupletShowNumberKind  tempoTupletShowNumberKind,
51     msrTupletFactor      tempoTupletFactor,
52     rational              memberNotesDisplayWholeNotes);
53
54 // ... ..
55
56 private:
57
58 // private fields
59 // -----
60
61 int                fTempoTupletNumber;
62
63 msrTempoTupletBracketKind  fTempoTupletBracketKind;
64
65 msrTempoTupletShowNumberKind  fTempoTupletShowNumberKind;
66
67 msrTupletFactor      fTempoTupletFactor;
68
69 rational              fMemberNotesDisplayWholeNotes;
70
71 rational              fTempoTupletDisplayWholeNotes;
72
73 list<S_msrElement>    fTempoTupletElements;
74
75 };

```

19.18.3 Tempos description

The private fields in class `msrTempo` are:

```

1 class EXP msrTempo : public msrMeasureElement
2 {
3     // ... ..
4
5     private:
6
7     // private fields
8     // -----
9
10    msrTempoKind                fTempoKind;
11
12    list<S_msrWords>            fTempoWordsList;
13
14    msrDottedDuration           fTempoBeatUnit;
15
16    string                      fTempoPerMinute; // '90' or '132-156' for example
17    msrDottedDuration           fTempoEquivalentBeatUnit;
18
19    S_msrTempoNotesRelationshipElements
20        fTempoNotesRelationshipLeftElements;
21    msrTempoNotesRelationshipKind  fTempoNotesRelationshipKind;
22    S_msrTempoNotesRelationshipElements
23        fTempoNotesRelationshipRightElements;
24

```

```

25     msrTempoParenthesizedKind
26                               fTempoParenthesizedKind;
27
28     msrPlacementKind          fTempoPlacementKind;
29 };

```

Among these fields:

- field `msrTempo::fTempoKind` denotes the variant;
- field `msrTempo::fTempoWordsList` contains the words that can be present, such as 'adagio molto';
- field `msrTempo::fTempoBeatUnit` is a dotted duration, as in '4.';
- field `msrTempo::fTempoPerMinute` is a string, since it can contain ranges indication as in '4. = 60-66';
- field `msrTempo::fTempoEquivalentBeatUnit` is a dotted duration;
- field `msrTempo::fTempoNotesRelationshipLeftElements`, field `msrTempo::fTempoNotesRelationshipKind` and field `msrTempo::fTempoNotesRelationshipRightElements` are used when a relationship is present, such as '2. = 1', in which case field `msrTempo::fTempoNotesRelationshipKind` contains field `msrTempo::kTempoNotesRelationshipKind`;
- field `msrTempo::fTempoParenthesizedKind` indicates whether the tempo indication is parenthesized;
- field `msrTempo::fTempoPlacementKind` tells whether the tempo is to be placed above or below the staff, constant `msrPlacementKind::kPlacementAbove` by default.

19.19 Clefs

Clefs are distinguished using enumeration type `msrClefKind`:

```

1  // clefs
2  // -----
3
4  enum class msrClefKind {
5      k_NoClef,
6
7      kClefTreble,
8      kClefSoprano, kClefMezzoSoprano, kClefAlto, kClefTenor, kClefBaritone, kClefBass,
9      kClefTrebleLine1,
10     kClefTrebleMinus15, kClefTrebleMinus8, kClefTreblePlus8, kClefTreblePlus15,
11
12     kClefBassMinus15, kClefBassMinus8, kClefBassPlus8, kClefBassPlus15,
13
14     kClefVarbaritone,
15
16     kClefTablature4, kClefTablature5, kClefTablature6, kClefTablature7,
17
18     kClefPercussion,
19
20     kClefJianpu
21 };

```

Class `msrClef` contains:

```

1     msrClefKind          fClefKind;
2     int                  fClefStaffNumber;

```

19.20 Keys

MSR, as MusicXML, supports Humdrum-Scot keys as well as traditional key such as C and 6/8.

A Humdrum-Scot key is composed of items represented by class `msrHumdrumScotKeyItem`, each containing:

```
1  msrDiatonicPitchKind    fKeyDiatonicPitchKind;
2  msrAlterationKind       fKeyAlterationKind;
3  msrOctaveKind           fKeyOctaveKind;
```

An example is at figure 19.2 [Humdrum-Scot keys], page 179. It has been produced by:

```
1  xml2ly -auto-output-file-name keys/HumdrumScotKeys.xml
```




Figure 19.2: Humdrum-Scot keys

Class `msrKey` thus contains:

```
1  // private fields
2  // -----
3
4  msrKeyKind          fKeyKind;
5
6  // traditional keys
7
8  msrQuarterTonesPitchKind
9                      fKeyTonicQuarterTonesPitchKind;
10 msrModeKind          fModeKind;
11 int                  fKeyCancel;
12
13 // Humdrum/Scot keys
14
15 vector<S_msHumdrumScotKeyItem>
16                               fHumdrumScotKeyItemsVector;
17 Bool                    fKeyItemsOctavesAreSpecified;
```

19.21 Time signatures

The variants in time signatures are distinguished by enumeration type enumeration type `msrTimeSignatureSymbolKind`

```

1 // time symbols
2 // -----
3 enum class msrTimeSignatureSymbolKind {
4     kTimeSignatureSymbolNone,
5     kTimeSignatureSymbolCommon,
6     kTimeSignatureSymbolCut,
7     kTimeSignatureSymbolNote,
8     kTimeSignatureSymbolDottedNote,
9     kTimeSignatureSymbolSingleNumber,
10    kTimeSignatureSymbolSenzaMisura
11 };

```

A time signature can also be structured, and this is described by those two types:

```

1 enum class msrTimeSignatureSeparatorKind {
2     kTimeSignatureSeparatorNone,
3     kTimeSignatureSeparatorHorizontal,
4     kTimeSignatureSeparatorDiagonal,
5     kTimeSignatureSeparatorVertical,
6     kTimeSignatureSeparatorAdjacent
7 };

```

```

1 enum class msrTimeSignatureRelationKind {
2     kTimeSignatureRelationNone,
3     kTimeSignatureRelationParentheses,
4     kTimeSignatureRelationBracket,
5     kTimeSignatureRelationEquals,
6     kTimeSignatureRelationSlash,
7     kTimeSignatureRelationSpace,
8     kTimeSignatureRelationHyphen
9 };

```

A brick that can be used in class `msrTimeSignature` is `msrTimeSignatureItem`, whose private fields are:

```

1     vector<int>          fTimeSignatureBeatsNumbersVector; // 5+3+1 is possible
2     int                 fTimeSignatureBeatValue;

```

Class `msrTimeSignature` contains:

```

1     msrTimeSignatureSymbolKind
2         fTimeSignatureSymbolKind;
3
4     vector<S_msTimeSignatureItem>
5         fTimeSignatureItemsVector;
6
7     // a time is compound if it contains several items
8     // or if the only one has several beats numbers
9     // i.e. 3/4 is not, (3+4)/8 is, and 2/4+3/4 is too
10    Bool          fTimeIsCompound;

```


19.22 MSR classes inheritance

The picture at figure 19.3 [The MSR classes hierarchy], page 181, shows the hierarchy of the main MSR classes. The colors are used as follows:

The background colors are used as follows:

- **green**: a score element that is expected to be found in a score representation, such as class `msrStaff` and class `msrChord`;

Figure 19.3: The MSR classes hierarchy



- **pink**: a element needed in MSR to structure the representation, such as class `msrSegment` and class `msrSyllable`;
- **yellow**: a base class with name class `msr*Element` for elements that can be used in another class, such as class `msrVoiceElement`;

The arrows colors have the following meaning:

- **red**: a link from a class to its base class. For example, class `msrPart` is derived from class `msrPartGroupElement`;
- **blue**: a link from a class to another that uses smart pointers to one or more instances of the former. For example, an class `msrTuplet` may be an element of an class `msrGraceNotesGroup`.

When not shown for clarity, the common base class of all these classes is class `msrElement`, that contains an integer input line number.

The `otherMeasureElements` classes are:

- bars:
 - class `msrBarCheck`
 - class `msrBarNumberCheck`
 - class `msrBarLine`
 - class `msrHiddenMeasureAndBarLine`
- breaks:
 - class `msrLineBreak`
 - class `msrPageBreak`
- notes:
 - class `msrVoiceStaffChange`
 - class `msrOctaveShift`
- clefs, keys, times, tempo:
 - class `msrClef`
 - class `msrKey`
 - class `msrTime`
 - class `msrTempo`
- instruments:
 - class `msrStaffDetails`
 - class `msrScordatura`
 - class `msrAccordionRegistration`
 - class `msrHarpPedalsTuning`
 - class `msrPedal`
 - class `msrDamp`
 - class `msrDampAll`

- lyrics:
 - class `msrSyllable`
- rehearsals, segno and coda:
 - class `msrRehearsalMark`
 - class `msrSegno`
 - class `msrDalSegno`
 - class `msrCoda`
- others:
 - class `msrPrintLayout`
 - class `msrEyeGlasses`
 - class `msrStaffLevelElement`
 - class `msrTransposition`
 - class `msrTupletElement`

19.23 Books

Books handling is presented at section 56 [Books handling], page 321.

LilyPond handles `\book {...}` by placing the scores one after the other in the resulting PDF or SVG files. It will also generate separate MIDI files if a `\markup {...}` block is used.

There is no such concept in MusicXML, but MSR uses it for completeness, creating an implicit class `msrBook` instance if needed.

An class `msrBook` contains a list and a set of `S_msrBookElement`:

```

1 // book elements
2 set<S_msrBookElement> fBookElementsSet;
3
4 list<S_msrBookElement> fBookElementsList;
```

Currently, the only book element used is the class `msrScore`, but others might come, such as texts, which LilyPond allows as `\markup {...}`:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src > grep -r 'public msrBook' *
2 formats/msr/msrScores.h: class EXP msrScore : public msrBookElement
```

19.24 Scores

Scores handling is presented at section ?? [Scores handling], page ??.

A score in MSR is the usual music score concept. It contains a set and a list of `S_msrPartGroup`:

```

1 // part groups
2 set<S_msrPartGroup> fScorePartGroupsSet;
3
4 list<S_msrPartGroup> fPartGroupsList;
```


19.25 Part groups

Part groups handling is presented at section 54 [Part groups handling], page 318.

A part group in MSR contains parts or other part groups. This concept is recursive, as it is in music score: the winds part group can oboes and horns part group, for example. An implicit part group exists in MSR if the score does not contain explicit part groups.

An class `msrPartGroup` thus contains parts and part groups in any order, as is found in symphonic music scores:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev/src > grep -r 'public msrPartGroupElement' *
2 formats/msr/msrParts.h:class EXP msrPart : public msrPartGroupElement
3 formats/msr/msrPartGroups.h:class EXP msrPartGroup : public msrPartGroupElement
```

which are stored in a list:

```
1 // allowing for both parts and (sub-)part groups as elements
2 list<S_msrPartGroupElement>
3     fPartGroupElementsList;
```

19.26 Parts

Parts handling is presented at section 53 [Parts handling], page 316.

A part in MSR is composed of voices, stored in:

```
1 // staves
2
3 map<int, S_msrStaff> getPartStaveNumbersToStavesMap;
4 list<S_msrStaff> fPartAllStavesList;
5
6 // harmonies
7
8 S_msrStaff fPartHarmoniesStaff;
9 S_msrVoice fPartHarmoniesVoice;
10
11 // figured bass
12
13 S_msrStaff fPartFiguredBassStaff;
14 S_msrVoice fPartFiguredBassVoice;
15
16 // voices
17
18 list<S_msrVoice> fPartAllVoicesList;
```

19.27 Staves

Staves handling is presented at section ?? [Staves handling], page ??.

A staff contains at most 4 numbered voices, stored in:

```

1 // the mapping of all the voices in the staff,
2 // including harmonies and figured bass voices
3 map<int, S_msrVoice> fStaffVoiceNumbersToAllVoicesMap;
4
5 // the mapping of voice numbers to regular voices
6 map<int, S_msrVoice> fStaffVoiceNumbersToRegularVoicesMap;
7
8 // we need to handle the regular voice specifically
9 // to assign them sequencing numbers from 1 to gMaxStaffVoices,
10 // needed to set the beams orientation (up or down)
11 int fStaffRegularVoicesCounter;
12
13 // harmonies and figured bass elements should be placed %%JMI
14 // in the first regular voice of the staff, hence:
15 list<S_msrVoice> fStaffRegularVoicesList;
16
17 // we need to sort the voices by increasing voice numbers,
18 // but with harmonies voices right before the corresponding regular voices
19 list<S_msrVoice> fStaffAllVoicesList;

```

19.28 Voice elements

Voices contain instances of class `msrVoiceElement`, defined in `src/formats/msr/msrVoiceElements.h/.cpp`:

```

1 // -----
2 /*
3  Various elements can found in voices,
4  hence class msrVoiceElement
5  */
6
7 class EXP msrVoiceElement : public msrElement
8 {
9     public:
10
11         // creation from MusicXML
12         // -----
13
14         // cloning
15         // -----
16
17     protected:
18
19         msrVoiceElement (
20             int inputLineNumber);
21
22         virtual ~msrVoiceElement ();
23
24     /*
25      The voice uplink is declared in the sub-classes,
26      to allow for separate *.h files, C++ constraint
27      */
28 };

```

The classes derived from class `msrVoiceElement` are:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src/formats/msr > grep 'public msrVoiceElement
2 ' *.h
3 msrBeatRepeats.h:class EXP msrBeatRepeat : public msrVoiceElement
4 msrMeasureRepeats.h:class EXP msrMeasureRepeat : public msrVoiceElement
5 msrRepeats.h:class EXP msrRepeat : public msrVoiceElement
6 msrMultipleFullBarRests.h:class EXP msrMultipleFullBarRests : public msrVoiceElement
7 msrSegments.h:class EXP msrSegment : public msrVoiceElement

```

They are describes in specific sections below.

19.29 Voices

Voices handling is presented at section 51 [Voices handling], page 314.

A voice is conceptually a sequence of `S_msrVoiceElement`, that may be:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev/src > grep -r 'public msrVoiceElement' *
2 formats/msr/msrMeasureRepeats.h:class EXP msrMeasureRepeat : public msrVoiceElement
3 formats/msr/msrRepeats.h:class EXP msrRepeat : public msrVoiceElement
4 formats/msr/msrMultipleFullBarRests.h:class EXP msrMultipleFullBarRests : public
   msrVoiceElement
5 formats/msr/msrBeatRepeats.h:class EXP msrBeatRepeat : public msrVoiceElement
6 formats/msr/msrSegments.h:class EXP msrSegment : public msrVoiceElement
```

More precisely and for technical reasons, an class `msrVoice` contains:

```
1 // voice initial elements list
2
3 list<S_msrVoiceElement>
4     fVoiceInitialElementsList;
5
6 // voice first and last segments
7
8 // fVoiceLastSegment contains the music
9 // not yet stored in fVoiceInitialElementsList,
10 // it is thus logically the end of the latter,
11 // and is created implicitly for every voice.
12 // It is needed 'outside' of the 'list<S_msrElement>'
13 // because it is not a mere S_msrElement, but a S_msrSegment
14 S_msrSegment     fVoiceLastSegment;
15
16 // fVoiceFirstSegment is used to work around LilyPond issue #34
17 S_msrSegment     fVoiceFirstSegment;
```

Each voice is described by a field of enumeration type `msrVoiceKind`, defined in `src/formats/msr/msrBasicTypes.h`:

```
1 enum class msrVoiceKind {
2     kVoiceKindRegular,
3     kVoiceKindDynamics,
4     kVoiceKindHarmonies, // for MusicXML <harmony/>, LilyPond ChordNames
5     kVoiceKindFiguredBass // for MusicXML <figured-bass/>, LilyPond FiguredBass
6 };
```

As stated in the comment above, `fVoiceLastSegment` is used because it because `fVoiceInitialElementsList` can contain any class `msrVoiceElement`, whereas all MSR elements appended to the voice are to be placed in a segment.

An class `msrSegment` instance should thus be created and stored in `fVoiceLastSegment` before class `msrVoiceElement` instances can be appended to the voice.

When repeats are handled, an class `msrRepeat` instance is created. Then the contents of field `msrVoice::fVoiceLastSegment` is moved into it and a new segment is created, see section 19.36 [Repeats], page 191.

Whether the last segment should be created right when the voice is created is controlled with enumeration type `msrVoiceCreateInitialLastSegmentKind`, defined in `src/formats/msr/msrVoices.h`:

```
1 enum class msrVoiceCreateInitialLastSegmentKind {
2     kCreateInitialLastSegmentYes,
3     kCreateInitialLastSegmentNo
4 };
```

19.30 Measures

Measures handling is presented at section 40 [Measures handling], page 271.

A measure is a linear, flat sequence of class `msrMeasureElements`, some of which are structured, such as class `msrChord`. Class `msrMeasre` is defined in `src/formats/msr/msrMeasre.h/.cpp`.

The measure elements are defined in `src/formats/msr/`:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev/src/formats/msr > grep 'public
  msrMeasureElement' *.h
2 msrBars.h:class EXP msrBarCheck : public msrMeasureElement
3 msrBars.h:class EXP msrBarNumberCheck : public msrMeasureElement
4 msrBars.h:class EXP msrBarLine : public msrMeasureElement
5 msrBreaks.h:class EXP msrLineBreak : public msrMeasureElement
6 msrBreaks.h:class EXP msrPageBreak : public msrMeasureElement
7 msrClefs.h:class EXP msrClef : public msrMeasureElement
8 msrCodas.h:class EXP msrCoda : public msrMeasureElement
9 msrDoubleTremolos.h:class EXP msrDoubleTremolo : public msrMeasureElement
10 msrEyeGlasses.h:class EXP msrEyeGlasses : public msrMeasureElement
11 msrFiguredBassElements.h:class EXP msrFiguredBassElement : public msrMeasureElement
12 msrHarmonies.h:class EXP msrHarmony : public msrMeasureElement
13 msrHiddenMeasureAndBarLines.h:class EXP msrHiddenMeasureAndBarLine : public
  msrMeasureElement
14 msrInstruments.h:class EXP msrScordatura : public msrMeasureElement
15 msrInstruments.h:class EXP msrAccordionRegistration : public msrMeasureElement
16 msrInstruments.h:class EXP msrHarpPedalsTuning : public msrMeasureElement
17 msrInstruments.h:class EXP msrPedal : public msrMeasureElement
18 msrInstruments.h:class EXP msrDamp : public msrMeasureElement
19 msrInstruments.h:class EXP msrDampAll : public msrMeasureElement
20 msrKeys.h:class EXP msrKey : public msrMeasureElement
21 msrLyrics.h:class EXP msrSyllable : public msrMeasureElement
22 msrMusicXMLSpecifics.h:class EXP msrPrintLayout : public msrMeasureElement
23 msrRehearsalMarks.h:class EXP msrRehearsalMark : public msrMeasureElement
24 msrSegnos.h:class EXP msrSegno : public msrMeasureElement
25 msrSegnos.h:class EXP msrDalSegno : public msrMeasureElement
26 msrStavesDetails.h:class EXP msrStaffDetails : public msrMeasureElement
27 msrTempos.h:class EXP msrTempo : public msrMeasureElement
28 msrTimeSignatures.h:class EXP msrTimeSignature : public msrMeasureElement
29 msrTranspositions.h:class EXP msrOctaveShift : public msrMeasureElement
30 msrTranspositions.h:class EXP msrTransposition : public msrMeasureElement
31 msrTupletElements.h:class EXP msrTupletElement : public msrMeasureElement
32 msrVoiceStaffChanges.h:class EXP msrVoiceStaffChange : public msrMeasureElement
```

In order to perform a time-wise analysis of the scores, MSR contains class `msrMeasusre` linear flat lists, without the class `msrRepeat` and such being represented.

This is used when identifying rest notes that are not 'heard' simultaneously with other notes or rests: this way, the rest can ignore the current voice number and be placed in the vertical middle of the staff.

Apart from the cloning methods, only one method creates measures, namely method `msrSegment::createAMeasureAndAppendItToSegment ()`, defined in `src/formats/msr/msrSegments.h/.cpp`:

```
1 S_msrMeasure msrSegment::createAMeasureAndAppendItToSegment (
2   int    inputLineNumber ,
3   string measureNumber ,
4   msrMeasureImplicitKind
5   measureImplicitKind)
6 {
7   // ... ..
8
9   ++gIndenter;
10
11   // determine new measure 'first in segment' kind
```

```

12  msrMeasure::msrMeasureFirstInSegmentKind
13      measureFirstInSegmentKind;
14
15  if (fSegmentElementsList.size () == 0) {
16      // this is the first measure in the segment
17      measureFirstInSegmentKind =
18          msrMeasure::kMeasureFirstInSegmentKindYes;
19  }
20  else {
21      // this is not the first measure in the segment
22      measureFirstInSegmentKind =
23          msrMeasure::kMeasureFirstInSegmentKindNo;
24  }
25
26  // create a measure
27  // ... ..
28
29  S_msrMeasure
30      result =
31          msrMeasure::create (
32              inputLineNumber,
33              measureNumber,
34              this);
35
36  // set result's ordinal number
37  result->
38      setMeasureOrdinalNumberInVoice (
39          fSegmentVoiceUpLink->
40              incrementVoiceCurrentMeasureOrdinalNumber ());
41
42  // append result to the segment
43  appendMeasureToSegment (result);
44
45  --gIndenter;
46
47  return result;
48  }

```

19.31 Repeats patterns and replicas

MSR represents repeated beats and measures this way:

- a pattern describes what is repeated;
- there are as many replicas of the music as needed.

This leads to:

```

1  jacquesmenu@macmini: ~/musicformats-git-dev/src/formats/msr > grep Pattern *.h | grep
   class
2  msrBeatRepeats.h:class EXP msrBeatRepeatPattern : public msrElement
3  msrMeasureRepeats.h:class EXP msrMeasureRepeatPattern : public msrElement
4  jacquesmenu@macmini: ~/musicformats-git-dev/src/formats/msr > grep Replicas *.h | grep
   class
5  msrBeatRepeats.h:class EXP msrBeatRepeatReplicas : public msrElement
6  msrMeasureRepeats.h:class EXP msrMeasureRepeatReplicas : public msrElement

```

These two repeat cases are described in the sections below.

19.32 Beat repeats

Beat repeats handling is presented at section 47 [Beat repeats handling], page 305.

Class `msrBeatRepeat`, defined in `src/formats/msr/msrBeatRepeats.h/.cpp`, contains a pattern and replicas:

```

1 class EXP msrBeatRepeat : public msrVoiceElement
2 {
3     // ... ..
4
5     private:
6
7         // private fields
8         // -----
9
10        // upLinks
11        S_msrVoice          fBeatRepeatVoiceUpLink;
12
13        // numbers
14        int                 fBeatRepeatMeasuresNumber;
15        int                 fBeatRepeatSlashesNumber;
16
17        // measures repeat pattern
18        S_msrBeatRepeatPattern
19        fBeatRepeatPattern;
20
21        // measures repeat replicas
22        S_msrBeatRepeatReplicas
23        fBeatRepeatReplicas;
24
25        // measures repeat build phase, used when building the measures repeat
26        msrBeatRepeatBuildPhaseKind
27        fCurrentBeatRepeatBuildPhaseKind; // unused??? JMI
28 };

```

Class `msrBeatRepeatPattern` contains a segment and an uplink:

```

1 class EXP msrBeatRepeatPattern : public msrElement
2 {
3     // ... ..
4
5     private:
6
7         // private fields
8         // -----
9
10        // upLinks
11        S_msrBeatRepeat      fBeatRepeatUpLink;
12
13        // segment
14        S_msrSegment         fBeatRepeatPatternSegment;
15 };

```

Class `msrBeatRepeatReplicas` contains a segment and an uplink:

```

1 class EXP msrBeatRepeatReplicas : public msrElement
2 {
3     // ... ..
4
5     private:
6
7         // private fields
8         // -----
9

```

```

10 // upLinks
11 S_msrBeatRepeat      fBeatRepeatUpLink;
12
13 // segment
14 S_msrSegment         fBeatRepeatReplicasSegment;
15 };

```

19.33 Measure repeats

Measure repeats handling is presented at section 48 [Measure repeats handling], page 306.

Class `msrMeasureRepeat`, defined in `src/formats/msr/msrMeasureRepeat.h/.cpp`, contains a pattern and replicas:

```

1 class EXP msrMeasureRepeat : public msrVoiceElement
2 {
3     // ... ..
4
5     private:
6
7         // private fields
8         // -----
9
10        // upLinks
11        S_msrVoice          fMeasureRepeatVoiceUpLink;
12
13        // numbers
14        int                 fMeasureRepeatMeasuresNumber;
15        int                 fMeasureRepeatSlashesNumber;
16
17        // measures repeat pattern
18        S_msrMeasureRepeatPattern
19            fMeasureRepeatPattern;
20
21        // measures repeat replicas
22        S_msrMeasureRepeatReplicas
23            fMeasureRepeatReplicas;
24
25        // measures repeat build phase, used when building the measures repeat
26        msrMeasureRepeatBuildPhaseKind
27            fCurrentMeasureRepeatBuildPhaseKind;
28 };

```

Class `msrMeasureRepeatPattern` contains a segment and an uplink:

```

1 class EXP msrMeasureRepeatPattern : public msrElement
2 {
3     // ... ..
4
5     private:
6
7         // private fields
8         // -----
9
10        // upLinks
11        S_msrMeasureRepeat  fMeasureRepeatUpLink;
12
13        // segment
14        S_msrSegment        fMeasureRepeatPatternSegment;
15 };

```

Class `msrMeasureRepeatReplicas` contain a segment and an uplink:

```

1 class EXP msrMeasureRepeatReplicas : public msrElement
2 {
3     // ... ..
4
5     private:
6
7         // private fields
8         // -----
9
10        // upLinks
11        S_msrMeasureRepeat    fMeasureRepeatUpLink;
12
13        // segment
14        S_msrSegment          fMeasureRepeatReplicasSegment;
15 };

```

19.34 Multiple full-bar rests

Full-bar rests handling is presented at section 49 [Multiple full-bar rests handling], page 307.

Class `msrMultipleFullBarRests`, defined in `src/formats/msr/msrMultipleFullBarRests.h/.cpp`, essentially contains a list of class `_msrMeasure` instances and a multiple full-bar rests number:

```

1 class EXP msrMultipleFullBarRests : public msrSegmentElement
2 {
3     // ... ..
4
5     private:
6
7         // private fields
8         // -----
9
10        S_msrSegment          fMultipleFullBarRestsSegmentUpLink;
11
12        int                   fMultipleFullBarRestsNumber; // supplied by MusicXML
13        list<S_msrMeasure>    fFullBarRestsMeasuresList;
14
15        int                   fMultipleFullBarRestsLastMeasurePuristNumber;
16
17        string                fMultipleFullBarRestsNextMeasureNumber;
18 };

```

19.35 Barlines

19.36 Repeats

Repeats handling is presented at section 50 [Repeats handling], page 308.

Contrary to MusicXML, MusicFormats represents the full structure of repeated music, not just barlines.

The following classes are defined in `src/formats/msr/msrRepeats.h/.cpp`, contains:


```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src/formats/msr > grep class msrRepeats.h
2 class msrRepeat;
3 class msrMultipleFullBarRests;
4 class msrMeasureRepeat;
5 class msrNote;
6 class EXP msrRepeatCommonPart : public msrElement
7 class EXP msrRepeatEnding : public msrElement
8 class EXP msrRepeat : public msrVoiceElement
9 class EXP msrRepeatDescr : public smartable
10 class EXP msrRepeatElement : public msrElement

```

Class `msrRepeat`, defined in `msrBothmsrRepeats`, contains an class `msrRepeatCommonPart`, followed by zero or more instances of class `msrRepeatEnding`:

```

1 class EXP msrRepeat : public msrVoiceElement
2 {
3     public:
4
5         // data types
6         // -----
7
8         enum msrRepeatExplicitStartKind {
9             kRepeatExplicitStartNo,
10            kRepeatExplicitStartYes
11        };
12
13        // ... ..
14
15        // common part
16        S_msRepeatCommonPart fRepeatCommonPart;
17
18        // repeat endings
19        vector<S_msRepeatEnding>
20            fRepeatEndings;
21        int
22            fRepeatEndingsInternalCounter;
23
24        // immediately preceding and following repeats
25        // detecting several repeats in a row helps LilyPond code generation
26        // depending on the options JMI
27        S_msRepeat          fImmediatelyPrecedingRepeat;
28        S_msRepeat          fImmediatelyFollowingRepeat;
29    };

```

Class `msrRepeatCommonPart` contains a list of class `msrVoiceElement`:

```

1     private:
2
3         // private fields
4         // -----
5
6         // upLinks
7         S_msRepeat          fRepeatCommonPartRepeatUpLink;
8
9         // elements list
10        list<S_msVoiceElement>
11            fRepeatCommonPartElementsList;

```

Enumeration type `msrRepeatEndingKind` is used to distinguish hooked and hookless repeat endings: hookless when the ending is simply overlined, and hooked when there a vertical line at the end of the ending's overline:

```

1 enum class msrRepeatEndingKind {
2     kRepeatEndingHooked,
3     kRepeatEndingHookless
4 };

```

Class `msrRepeatEnding` contains a list of class `msrVoiceElement` too, as well as a enumeration type `msrRepeatEndingKind` field:

```

1  private:
2
3  // private fields
4  // -----
5
6  // upLinks
7  S_msrRepeat          fRepeatEndingRepeatUpLink;
8
9  // numbers
10 string              fRepeatEndingNumber; // may be "1, 2"
11 int                 fRepeatEndingInternalNumber; // internally assigned
12
13 // kind
14 msrRepeatEndingKind  fRepeatEndingKind;
15
16 // elements list
17 list<S_msrVoiceElement>
18                      fRepeatEndingElementsList;

```

19.37 Segments

Segments handling is presented at section 46 [Segments handling], page 300.

Segment are not explicit in music scores, but they are there alright and we have to represent them in MSR:

- it is a sequence of music elements not containing a repeat. This is equivalent to so-called *basic blocs* in compiler technology, that are linear sequences of instructions without jumps, i.e. there is exactly one entry and one exit.

For example, at figure 19.4 [Three segments in a voice], page 193, there are three segments:

- the first one contains the `c1`, and belongs to a first repeat;
- the second one contains the `d1`, and is a member of the voice;
- the last one contains the `e1` and belongs to a second repeat.



Figure 19.4: Three segments in a voice

19.38 Notes and rests

Class `msrNote` is complex class: it handles many variants, but using classes to represent the variants would be too cumbersome. As shown at figure 19.3 [The MSR classes hierarchy], page 181:

- a note can be a standalone (regular) note or rest;
- it can belong to a grace notes group;
- it can belong to chord, which can itself belong to a grace notes group or a tuplet;
- it can belong to a tuplet;
- it can belong to double tremolo;
- and finally, a rest can be unpitched.

class `msrNote` thus uses enumeration type `msrNoteKind`, defined in `src/formats/msr/msrBasicType` to distinguish them:

```

1 enum class msrNoteKind {
2     k_NoNote,
3
4     // in measures
5     kNoteRegularInMeasure,
6     kNoteRestInMeasure,
7     kNoteSkipInMeasure, // an invisible rest
8     kNoteUnpitchedInMeasure,
9
10    // in chords
11    kNoteRegularInChord,
12
13    // in triplets
14    kNoteRegularInTriplet,
15    kNoteRestInTriplet,
16    kNoteUnpitchedInTriplet,
17
18    // in grace notes groups
19    kNoteRegularInGraceNotesGroup,
20    kNoteSkipInGraceNotesGroup, // used to circumvent LilyPond issue #34
21
22    // in chords in grace notes groups
23    kNoteInChordInGraceNotesGroup,
24
25    // in triplets in grace notes groups
26    kNoteInTripletInGraceNotesGroup,
27
28    // in double-tremolos
29    kNoteInDoubleTremolo
30 };

```

19.39 Articulations

19.40 Ornaments

19.41 Ties

19.42 Dynamics

19.43 Beams

19.44 Slurs

19.45 Grace notes groups

Grace notes groups handling is presented at section [62](#) [Grace notes groups handling], page [327](#).

19.46 Chords

A chord contains notes only, and can occur in measures, tuplets and grace notes groups, hence:

```
1 // chords
2 // -----
3
4 enum class msrChordInKind {
5     k_NoChordIn,
6
7     kChordInMeasure,
8     kChordInTuplet,
9     kChordInGraceNotesGroup
10 };
```

19.47 Tuplets

Tuplets handling is presented at section [64](#) [Tuplets handling], page [329](#).

A tuplet can contain:

- notes and rests;
- chords;
- other tuplets.

Tuplets can occur in measures and other tuplets, hence enumeration type `msrTupletInKind`:

```
1 enum class msrTupletInKind {
2     k_NoTupletIn,
3
4     kTupletInMeasure,
5     kTupletInTuplet
6 };
```

Tuplets factors are represented by class `msrTupletFactor`, defined in `src/formats/msr/msrBasicTypes.h/.cpp`.

```

1 class EXP msrTupletFactor
2 {
3     // ... ..
4
5 public:
6
7     // public services
8     // -----
9
10    Bool                isEqualToOne () const
11                        {
12                            return
13                                fTupletActualNotes == fTupletNormalNotes;
14                        }
15
16    rational            asRational () const
17                        {
18                            return
19                                rational (
20                                    fTupletActualNotes,
21                                    fTupletNormalNotes);
22                        }
23
24    // ... ..
25
26 private:
27
28     // private fields
29     // -----
30
31    int                  fTupletActualNotes;
32    int                  fTupletNormalNotes;
33 };

```

19.48 Harmonies and figured bass similarities

Harmonies and figured bass handling is presented at section 65 [Harmonies handling], page 330 and section 66 [Figured bass elements handling], page 346, respectively.

In MusicXML, harmonies and figured bass occur at the measure level:

```

1 <harmony print-frame="no">
2   <root>
3     <root-step>C</root-step>
4   </root>
5   <kind text="m">minor</kind>
6 </harmony>
7 <note default-x="75.17" default-y="-35.00">
8   <pitch>
9     <step>F</step>
10    <octave>4</octave>
11  </pitch>
12  <duration>2</duration>
13  <voice>1</voice>
14  <type>quarter</type>
15  <stem>up</stem>
16 </note>

```

```

1    <harmony>
2      <root>
3        <root-step>F</root-step>
4        <root-alter>1</root-alter>
5      </root>
6      <kind>major</kind>
7      <inversion>2</inversion>
8    </harmony>
9    <note>
10     <pitch>
11       <step>C</step>
12       <octave>4</octave>
13     </pitch>
14     <duration>4</duration>
15     <type>whole</type>
16   </note>

```

In MSR, the instances of class `msrHarmony` and class `msrFiguredBassElement` are present twice:

- each class `msrNote` instance contains the harmonies and figured bass attached to it:

```

1  class EXP msrNote : public msrTupletElement
2  {
3    // ... ..
4
5    private:
6
7      // private fields
8      // -----
9
10     // harmonies
11     // -----
12
13     list<S_msHarmony>      fNoteHarmoniesList;
14
15     // figured bass
16     // -----
17
18     list<S_msFiguredBassElement>
19         fNoteFiguredBassElementsList;
20
21     // ... ..
22 };

```

- each class `msrPart` instance contains a harmonies staff and voice, as well as a figured bass staff and voice:

```

1  class EXP msrPart : public msrPartGroupElement
2  {
3    // ... ..
4
5    private:
6
7      // private fields
8      // -----
9      // harmonies
10
11      S_msStaff      fPartHarmoniesStaff;
12      S_msVoice      fPartHarmoniesVoice;
13
14      // figured bass
15
16      S_msStaff      fPartFiguredBassStaff;
17      S_msVoice      fPartFiguredBassVoice;

```

```

18 |
19 | // ... ..
20 | };

```

The way harmonies and figured bass elements are represented in MusicFormats is presented in the next two sections.

19.49 Harmonies

Harmonies handling is presented at section [65](#) [Harmonies handling], page [330](#).

19.50 Figured bass elements

Figured bass elements handling is presented at section [66](#) [Figured bass elements handling], page [346](#).

19.51 Lyrics

Lyrics handling is presented at section [67](#) [Lyrics handling], page [360](#).

Lyrics are handled in rather a special way in music scores:

- they have a linear structure, independent of the repeats structure of the staff they belong too;
- they can be several lyrics stanzas associated to a given staff;
- the syllables in lyrics can apply to more than one note, and the subdivisions of words have to be handled.

The basic building block for lyrics in MSR is class `msrSyllable`, whose variants are distinguished by enumeration type enumeration type `msrSyllableKind`:

```

1  enum msrSyllableKind {
2      kSyllableNone,
3      kSyllableSingle,
4      kSyllableBegin, kSyllableMiddle, kSyllableEnd,
5
6      kSyllableOnRestNote,
7      kSyllableSkipRestNote,
8      kSyllableSkipNonRestNote,
9
10     kSyllableMeasureEnd,
11     kSyllableLineBreak, kSyllablePageBreak
12 };

```

Extensions are described by enumeration type :

```

1  enum msrSyllableExtendKind {
2      kSyllableExtendNone,
3      kSyllableExtendEmpty,
4      kSyllableExtendSingle,
5      kSyllableExtendStart, kSyllableExtendContinue, kSyllableExtendStop
6  };

```

Class `msrSyllable` contains:

```
1 // syllable kind
2 msrSyllableKind          fSyllableKind;
3
4 // texts list
5 list<string>              fSyllableTextsList;
6
7 // extend kind
8 msrSyllableExtendKind    fSyllableExtendKind;
9
10 // stanza number, may contain non-digits
11 string                   fSyllableStanzaNumber;
12
13 // syllable whole notes
14 rational                 fSyllableWholeNotes;
15
16 // syllable tuplet factor
17 msrTupletFactor          fSyllableTupletFactor;
```

Syllables are one case where the data in MSR is denormalized: a given class `msrSyllable` instance belongs both to an class `msrNote` instance and to a lyrics instance of class `msrVoice`.

At the higher level, syllables are organized as instances of class `msrStanza`, which contains:

```
1 // contents
2 vector<S_msrSyllable>    fSyllables;
3
4 Bool                     fStanzaTextPresent;
```

19.52 MIDI

MIDI handling is presented at section [68](#) [MIDI handling], page [361](#).

Chapter 20

MSR time-oriented representation

In order to represent the music according to simultaneous sounding time, MSR builds:

- a flat list of measures at the voice and staff levels;
- from this, a vector of measures slices at the voice, staff, part, part group and score levels.

The source files are in `src/formats/msr/msrMeasuresSlices.h/.cpp`.

20.1 Note events

Notes start and stop are represented by enumeration type `msrNoteEventKind`:

```
1 enum class msrNoteEventKind {  
2     kNoteEventStart ,  
3     kNoteEventStop  
4 };
```

A note event is described in class :

```
1 class msrNoteEvent : public smartable  
2 {  
3     // ... ..  
4  
5     private:  
6  
7         // private fields  
8         // -----  
9  
10        rational                fNoteEventPositionInMeasure;  
11        S_msrNote                fNoteEventNote;  
12        msrNoteEventKind         fNoteEventKind;  
13 };
```

20.2 Simultaneous notes chunks

Such a chunk is a set of notes or rests played simultaneously, i.e. that start and stop at the same time. The set is stored as a list actually:

```

1 class msrSimultaneousNotesChunk : public smartable
2 {
3     // ... ..
4
5     private:
6
7         // private fields
8         // -----
9
10        rational                fChunkPositionInMeasure;
11        list<S_msrNote>         fChunkNotesList;
12        rational                fChunkWholeNotes;
13 };

```

20.3 Measures slices

A measures slice, described by class `msrMeasuresSlice`, is a 'vertical' cut in the score across voices: it contains all the measures starting at the same time, one per voice:

```

1 class EXP msrMeasuresSlice : public smartable
2 {
3     // ... ..
4
5     protected:
6
7         // protected fields
8         // -----
9
10        int                    fSlicePuristMeasureNumber;
11        string                 fSliceMeasureNumber;
12
13        // the measures in the slice
14        vector<S_msrMeasure>   fSliceMeasuresVector;
15
16        // notes flat list
17        list<S_msrNote>        fSliceNotesFlatList;
18
19        // note events list
20        list<S_msrNoteEvent>    fSliceNoteEventsList;
21
22        // simultaneous notes chunks list
23        list<S_msrSimultaneousNotesChunk>
24                                fSliceSimultaneousNotesChunksList;
25 };

```

20.4 Measures slices sequences

A class `msrMeasuresSlicesSequence` contains a vector of `S_msrMeasuresSlice` instances:

```

1 class EXP msrMeasuresSlicesSequence : public smartable
2 {
3     // ... ..
4
5     private:
6
7         // private fields
8         // -----
9
10        string                fMeasuresOrigin;
11
12        vector<S_msrMeasuresSlice>
13                                fMeasuresSlicesVector;
14 };

```

A smart pointer to an `msrMeasuresSlicesSequence` instance is stored in `msrVoice`, `msrStaff`, `msrPart`, `msrPartGroup` and `msrScore`.

20.5 Building the measures slices

20.5.1 Part measures slices

At the part level, this is done in method `msrPart::collectPartMeasuresSlices ()`:

```

1 void msrPart::collectPartMeasuresSlices (
2     int inputLineNumber)
3 {
4     // ... ..
5
6     // create the part measures slices sequence
7     fPartMeasuresSlicesSequence =
8         msrMeasuresSlicesSequence::create (
9             fPartName); // origin
10
11    // populate it
12    for (S_msrStaff staff : fPartAllStavesList) {
13        // ... ..
14
15        ++gIndenter;
16
17        S_msrMeasuresSlicesSequence
18            staffMeasuresSlicesSequence =
19                staff->
20                getStaffMeasuresSlicesSequence ();
21
22        if (! staffMeasuresSlicesSequence) {
23            stringstream s;
24
25            s <<
26                "The staffMeasuresSlicesSequence of staff \"" <<
27                staff->getStaffName () <<
28                "\" is null";
29
30            musicxmlWarning (
31                gGlobalServiceRunData->getInputSourceName (),
32                inputLineNumber,
33                s.str ());
34        }
35        else {
36            fPartMeasuresSlicesSequence->
37                mergeWithMeasuresSlicesSequence (
38                    inputLineNumber,

```

```

39         getPartCombinedName (),
40         staffMeasuresSlicesSequence);
41     }
42
43     --gIndenter;
44 } // for
45
46 // ... ..
47 }

```

20.5.2 Staff measures slices

Method `msrStaff::collectStaffMeasuresSlices ()` builds them:

```

1 void msrStaff::collectStaffMeasuresSlices (
2     int inputLineNumber)
3 {
4     // ... ..
5
6     // create the staff measures slices sequence
7     fStaffMeasuresSlicesSequence =
8         msrMeasuresSlicesSequence::create (
9             fStaffName); // origin
10
11    // populate it
12    for (S_msrVoice voice : fStaffAllVoicesList) {
13        // ... ..
14
15        // get the voice measures slices sequence
16        S_msrMeasuresSlicesSequence
17            voiceMeasuresSlicesSequence =
18            voice->
19                getVoiceMeasuresSlicesSequence ();
20
21        // merge it with the voice measures slices sequence
22        if (voiceMeasuresSlicesSequence) { // JMI
23            fStaffMeasuresSlicesSequence =
24                fStaffMeasuresSlicesSequence->
25                    mergeWithMeasuresSlicesSequence (
26                        inputLineNumber,
27                        fStaffName,
28                        voiceMeasuresSlicesSequence);
29        }
30
31        // identify the solo notes and rests in the staff
32        fStaffMeasuresSlicesSequence->
33            identifySoloNotesAndRests ();
34
35        --gIndenter;
36    } // for
37
38    // ... ..
39 }

```

20.6 Solo notes and rests

A solo note or rest is one that occurs alone at some point in time for its whole duration, without any other note being played at the same time.

Identifying such solo notes or rests is done in method `msrMeasuresSlicesSequence::identifySoloNotesAndRests` using the measures slices of the staff they occur in, called method `msrStaff::collectStaffMeasuresSlices` () as shown above:

```
1 void msrMeasuresSlicesSequence::identifySoloNotesAndRests ()
2 {
3     // ... ..
4
5     // collect the notes from the sequence's measures slices
6     for (
7         vector<S_msrMeasuresSlice>::const_iterator i =
8             fMeasuresSlicesVector.begin ();
9         i != fMeasuresSlicesVector.end ();
10        ++i
11    ) {
12        S_msrMeasuresSlice measuresSlice = (*i);
13
14        measuresSlice->
15            collectNonSkipNotesFromMeasuresSliceMeasures ();
16    } // for
17 }
```

20.7 A measures slices example

Chapter 21

Path to voice

`src/formats/msr/msrPathToVoice.h.h/.cpp` defines class `msrPathToVoice`, used to create partial clones of class `msrBook` retaining only certain staves and/or voices, or to create new class `msrScore` instances containing each of them only:

```
1 class EXP msrPathToVoice : public smartable
2 {
3     // ... ..
4
5     public:
6
7         // public services
8         // -----
9
10        void                appendPartGroup (S_msrPartGroup partGroup)
11                                {
12                                    fPartGroupsList.push_back (partGroup);
13                                }
14
15        // ... ..
16
17        private:
18
19            // private fields
20            // -----
21
22            S_msrBook        fBook;
23
24            S_msrScore        fScore;
25
26            // part groups can be nested
27            list<S_msrPartGroup> fPartGroupsList;
28
29            S_msrPart        fPart;
30
31            S_msrStaff        fStaff;
32
33            S_msrVoice        fVoice;
34 };
```

Chapter 22

LilyPond Scores Representation (LPSR)

An LPSR description contains two components:

- the first one is an MSR, thus the whole music score description;
- the second one is a description of the structure of the score mirroring LilyPond's specific blocks such as `\book {...}` and `\layout {...}`.

Class `lpsrScore` thus contains:

```
1 // MSR data
2 S_msrScore          fMsrScore;
3
4 // ... ..
5
6 // LilyPond stuff
7 S_lpsrHeader        fScoreHeader;
8 S_lpsrPaper         fScorePaper;
9 S_lpsrLayout        fScoreLayout;
10
11 // variables, voices and stanzas
12 list<S_msrElement>  fScoreElementsList;
13
14 // score LPSR book blocks list
15 list<S_lpsrBookBlock> fScoreBookBlocksList;
16 S_lpsrScoreBlock    fScoreScoreBlock; // JMI ???
```

22.1 LPSR basic types

Some types used throughout LSPR are defined in `src/formats/lpsr//lpsrBasicTypes.h/.cpp`:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev/src/formats/lpsr > egrep -rIn '^// '
   lpsrBasicTypes.h
2 lpsrBasicTypes.h:28:// score output kinds
3 lpsrBasicTypes.h:50:// accidental styles
4 lpsrBasicTypes.h:53:// JMI there are new ones in LilyPond 2.22
5 lpsrBasicTypes.h:87:// chords languages
6 lpsrBasicTypes.h:107:// whole notes
7 lpsrBasicTypes.h:118:// dotted durations
8 lpsrBasicTypes.h:129:// rests measures
9 lpsrBasicTypes.h:135:// texts lists
10 lpsrBasicTypes.h:141:// pitches and octaves
11 lpsrBasicTypes.h:151:// lyrics durations
12 lpsrBasicTypes.h:168:// initialization
```

22.2 Adapting LilyPond code generation to the target version number

As of version 2.22, `compressMultipleFullBarRests` has been replaced by `compressFullBarRests` for clarity.

Such is done specific methods:



Chapter 23

Braille Scores Representation (BSR)

BSR represents braille scores as composed of lines of 6-dot cells.

23.1 BSR basic types

Some types used throughout BSR are defined in [src/formats/bsr/bsrBasicTypes.h/.cpp](#):

```
1 jacquesmenu@macmini: ~/musicformats-git-dev/src/formats/bsr > egrep -rIn '~/' '
    bsrBasicTypes.h
2 bsrBasicTypes.h:23:// cell kinds
3 bsrBasicTypes.h:107:// lower case letters
4 bsrBasicTypes.h:139:// capitals
5 bsrBasicTypes.h:143:// kCellCapitalsSequenceSign, // { kCellCapitalsSign,
    kCellCapitalsSign };
6 bsrBasicTypes.h:145:// decimal digits
7 bsrBasicTypes.h:160:// lower decimal digits
8 bsrBasicTypes.h:174:// alterations
9 bsrBasicTypes.h:181:// augmentation dots
10 bsrBasicTypes.h:186:// arithmetic operators
11 bsrBasicTypes.h:195:// words
12 bsrBasicTypes.h:205:// braille cells
13 bsrBasicTypes.h:212:// braille output kinds
14 bsrBasicTypes.h:231:// chords languages
15 bsrBasicTypes.h:251:// brailling numbers
16 bsrBasicTypes.h:255:// brailling characters and strings
17 bsrBasicTypes.h:261:// writing UTF-16 to ostream
18 bsrBasicTypes.h:273:// initialization
19 bsrBasicTypes.h:971:// constants
20 bsrBasicTypes.h:975:// computations
```

23.2 Representing cells

This is done basically with enumeration type enumeration type `bsrCellKind`, defined in [src/formats/bsr/bsrBasicTypes.h](#):

```
1 // cell kinds
2 // -----
3 enum class bsrCellKind {
4     kCellUnknown,
5
6     // non 6dots values
7     kCellEOL      , // L'\u000a'
8     kCellEOP      , // L'\u000c'
9
10    // 6dots values for Braille
```

```

11 kDotsNone      , // L'\u2800'
12 kDots1        , // L'\u2801'
13 kDots2        , // L'\u2802'
14
15 // ... ..
16
17 kDots23456     , // L'\u283e'
18 kDots123456    , // L'\u283f'
19 };

```

Enumeration type `bsrCellKind` constants are not used throughout the code base: instead, there are enumeration type `bsrCellKind` constants to provide context-specific names for the cells kinds.

Lower-case letters:

```

1 // lower case letters
2 // -----
3 const bsrCellKind
4     kCellA = bsrCellKind::kDots1,
5     kCellB = bsrCellKind::kDots12,
6
7
8     kCellY = bsrCellKind::kDots13456,
9     kCellZ = bsrCellKind::kDots1356;

```

Capital sign:

```

1 // capitals
2 // -----
3 const bsrCellKind
4     kCellCapitalsSign = bsrCellKind::kDots46;

```

Decimal digits:

```

1 // decimal digits
2 // -----
3 const bsrCellKind
4     kCellNumberSign = bsrCellKind::kDots3456,
5     kCell11 = kCellA,
6     kCell12 = kCellB,
7     kCell13 = kCellC,
8     kCell14 = kCellD,
9     kCell15 = kCellE,
10    kCell16 = kCellF,
11    kCell17 = kCellG,
12    kCell18 = kCellH,
13    kCell19 = kCellI,
14    kCell10 = kCellJ;

```

Alterations:

```

1 // alterations
2 // -----
3 const bsrCellKind
4     kCellFlat      = bsrCellKind::kDots126,
5     kCellNatural   = bsrCellKind::kDots16,
6     kCellSharp     = bsrCellKind::kDots146;

```

Augmentation dots:

```

1 // augmentation dots
2 // -----
3 const bsrCellKind
4     kCellAugmentationDot = bsrCellKind::kDots3;

```

Arithmetic operators:

```
1 // arithmetic operators
2 // -----
3 const bsrCellKind
4     kCell_ac_plus      = bsrCellKind::kDots235,
5     kCell_ac_minus     = bsrCellKind::kDots36,
6     kCell_ac_times     = bsrCellKind::kDots35,
7     kCell_ac_dividedBy = bsrCellKind::kDots25,
8     kCell_ac_equals    = bsrCellKind::kDots2356;
```

Words:

```
1 // words
2 // -----
3 const bsrCellKind
4     kCellWordSign      = bsrCellKind::kDots345,
5
6     kCellWordApostrophe = bsrCellKind::kDots6,
7
8     kCellParenthesis    = bsrCellKind::kDots2356,
9     kCellQuestionMark   = bsrCellKind::kDots26;
```

Chapter 24

MusicXML Scores Representation (MXSR)

This format is provided by `libmusicxml2`, even though Dominique Fober didn't give it that name. It is a tree of class `mxmlelement` nodes, mapped one to one to the MusicXML markups.

The files in `libmusicxml/src`.

A set of interface functions is contained in `src/formats/mxsr/mxsr.h/.cpp`:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev/src > ll formats/mxsr/
2 total 48
3  0 drwxr-xr-x   6 jacquesmenu  staff    192 May 26 08:20:55 2021 ./
4  0 drwxr-xr-x  10 jacquesmenu  staff    320 Jun 25 05:39:49 2021 ../
5  8 -rw-r--r--@   1 jacquesmenu  staff  3292 Jun  6 06:35:19 2021 mxsr.cpp
6  8 -rw-r--r--@   1 jacquesmenu  staff  1555 Jun  6 06:35:19 2021 mxsrGeneration.h
7 16 -rw-r--r--@   1 jacquesmenu  staff  7781 Jun  6 06:35:19 2021 mxsr0ah.cpp
8 16 -rw-r--r--@   1 jacquesmenu  staff  4829 Jun  6 06:35:19 2021 mxsr0ah.h
```

24.1 MusicXML elements and attributes

MusicXML data contains so-called elements, written as `<... />` markups, that can be nested:

```
1 <system-margins>
2   <left-margin>15</left-margin>
3   <right-margin>0</right-margin>
4 </system-margins>
```

In the example above, the values of the two margins are 15 and 0, respectively.

MusicXML elements can have attributes, such as `version` below:

```
1 <score-partwise version="3.1">
```

The values of the elements and attributes are strings.

There are two special elements at the beginning of MusicXML data:

- a `<?xml/>` element indicating the characters encoding used;
- a `<“!”DOCTYPE/>` element telling that the contents is in 'score-partwise' mode and containing the URL of the DTD.

An exemple is:

```

1 <?xml version="1.0" encoding="UTF-8"?>
2 <!DOCTYPE score-partwise PUBLIC "-//Recordare//DTD MusicXML 2.0 Partwise//EN"
3 "http://www.musicxml.org/dtds/partwise.dtd">

```

24.2 The xmlelement and xmlattribute types

xmlelementxmlattribute

These two classes are defined in `libmusicxml/src/elements!xml.h/.cpp`:

```

1 class xmlelement;
2 class xmlattribute;
3
4 typedef SMARTP<xmlattribute> Sxmlattribute;
5 typedef SMARTP<xmlelement> Sxmlelement;

```

Class xmlattribute contains:

```

1 //-----
2 class EXP xmlattribute : public smartable {
3     ///! the attribute name
4     std::string fName;
5     ///! the attribute value
6     std::string fValue;
7
8     // ... ..
9
10    ///! returns the attribute value as a int
11    operator int () const;
12    ///! returns the attribute value as a long
13    operator long () const;
14    ///! returns the attribute value as a float
15    operator float () const;

```

Class xmlelement contains:

```

1 class EXP xmlelement : public ctree<xmlelement>, public visitable
2 {
3     private:
4         ///! the element name
5         std::string fName;
6         ///! the element value
7         std::string fValue;
8         ///! list of the element attributes
9         std::vector<Sxmlattribute> fAttributes;
10
11     protected:
12         // the element type
13         int fType;
14         // the input line number for messages to the user
15         int fInputLineNumber;
16
17         // ... ..
18
19         ///! returns the element value as a long
20         operator long () const;
21         ///! returns the element value as a int
22         operator int () const;
23         ///! returns the element value as a float
24         operator float () const;
25         ///! elements comparison

```

```

26 Bool operator ==(const xmlelement& elt) const;
27 Bool operator !=(const xmlelement& elt) const { return !(*this == elt); }
28
29 ///! adds an attribute to the element
30 long add (const Sxmlattribute& attr);
31
32 // ... ..
33 };

```

Type Sxmlelement is a smart pointer to an xmlelement, so it is an xmlelement tree, since xmlelement is a recursive type.

fInputLineNumber is used for example in warning and error messages, to help the user locate the problem.

fType typically contains a value of some enumeration type , more on this below.

24.3 Enumeration types for xmlelement's fType

xmlelement

libmusicxml2 uses elements/templates/elements.bash, a Bash script, to generate the enumeration type constants and classes source code from the MusicXML DTD. This is not done in the Makefile, since it is to be run by hand only once.

The DTD files we use as reference are in libmusicxml/dtds/3.1/schema;

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/libmusicxml/dtds/3.1/schema > ls -sal *.mod
2 40 -rwxr-xr-x@ 1 jacquesmenu staff 20238 Apr 22 15:49 attributes.mod
3 16 -rwxr-xr-x 1 jacquesmenu staff 4943 Apr 22 15:49 barLine.mod
4 80 -rwxr-xr-x@ 1 jacquesmenu staff 37932 Apr 22 15:49 common.mod
5 88 -rwxr-xr-x@ 1 jacquesmenu staff 41960 Apr 22 15:49 direction.mod
6 16 -rwxr-xr-x@ 1 jacquesmenu staff 4097 Apr 22 15:49 identity.mod
7 24 -rwxr-xr-x@ 1 jacquesmenu staff 10266 Apr 22 15:49 layout.mod
8 8 -rwxr-xr-x@ 1 jacquesmenu staff 2833 Apr 22 15:49 link.mod
9 104 -rwxr-xr-x@ 1 jacquesmenu staff 51384 Apr 22 15:49 note.mod
10 32 -rwxr-xr-x@ 1 jacquesmenu staff 15476 Apr 22 15:49 score.mod

```

The first result of running libmusicxml/src/elements/templates!elements.bash is an anonymous enumeration type defined in libmusicxml/src/elements!elements.h:

```

1 enum {
2     kNoElement,
3     kComment,
4     kProcessingInstruction,
5     k_accent,
6     k_accidental,
7     k_accidental_mark,
8     k_accidental_text,
9
10    // ... ..
11
12    k_work,
13    k_work_number,
14    k_work_title,
15    kEndElement
16 };

```

The constants kNoElement, kComment and kProcessingInstruction are added by elements.bash.

24.4 Classes for the xmlelements

All the MusicXML classes are instantiated from the `musicxml` template class, defined in `libmusicxml/src/elements!`. This is where `fType` gets its value:

```
1 template <int elt> class musicxml : public xmlelement
2 {
3     protected:
4         musicxml (int inputLineNumber) : xmlelement (inputLineNumber) { fType = elt; }
5 };
```

The smart pointer `s` to the various elements are defined in `libmusicxml/src/elements!typedef.h`, using an anonymous enumeration type :

```
1 typedef SMARTP<musicxml<kComment> > S_comment;
2 typedef SMARTP<musicxml<kProcessingInstruction> > S_processing_instruction;
3
4 typedef SMARTP<musicxml<k_accent> > S_accent;
5 typedef SMARTP<musicxml<k_accidental> > S_accidental;
6 typedef SMARTP<musicxml<k_accidental_mark> > S_accidental_mark;
7 typedef SMARTP<musicxml<k_accidental_text> > S_accidental_text;
8
9 // ... ..
10
11 typedef SMARTP<musicxml<k_work> > S_work;
12 typedef SMARTP<musicxml<k_work_number> > S_work_number;
13 typedef SMARTP<musicxml<k_work_title> > S_work_title;
```

The two-way correspondance of MusicXML elements names to type `Sxmlelement` is stored `fMap` and `fType2Name`, defined in `libmusicxml/src/elements!factory.h`:

```
1 class EXP factory : public singleton<factory>{
2
3     std::map<std::string, functor<Sxmlelement>*> fMap;
4     std::map<int, const char*> fType2Name;
5
6     // ... ..
7 };
```

Those two maps are initialized in `libmusicxml/samples/elements/factory.cpp`:

```
1 factory::factory()
2 {
3     fMap["comment"] = new newElementFunctor<kComment>;
4     fMap["pi"] = new newElementFunctor<kProcessingInstruction>;
5     fType2Name[kComment] = "comment";
6     fType2Name[kProcessingInstruction] = "pi";
7
8     fMap["accent"] = new newElementFunctor<k_accent>;
9     fMap["accidental"] = new newElementFunctor<k_accidental>;
10    fMap["accidental-mark"] = new newElementFunctor<k_accidental_mark>;
11    fMap["accidental-text"] = new newElementFunctor<k_accidental_text>;
12
13    // ... ..
14
15    fMap["work"] = new newElementFunctor<k_work>;
16    fMap["work-number"] = new newElementFunctor<k_work_number>;
17    fMap["work-title"] = new newElementFunctor<k_work_title>;
18
19    fType2Name[k_accent] = "accent";
20    fType2Name[k_accidental] = "accidental";
21    fType2Name[k_accidental_mark] = "accidental-mark";
22    fType2Name[k_accidental_text] = "accidental-text";
23 }
```

```

24 // ... ..
25
26 fType2Name[k_work]    = "work";
27 fType2Name[k_work_number] = "work-number";
28 fType2Name[k_work_title]  = "work-title";
29 }

```

Class `newElementFunctor` is defined in `to` to provide call operator as:

```

1 template<int elt>
2 class newElementFunctor : public functor<Sxmlelement>
3 {
4     public:
5
6     Sxmlelement operator ()()
7     { return musicxml<elt>::new_musicxml (libmxmllineneno); }
8 };

```

24.5 xmlelement trees

This section describes features supplied by `libmusicxml2`.

An `xmlelement` is the basic brick to represent a MusicXML element.

Smart pointer type `SXMLFile` is defined in `libmusicxml/src/files/xmlfile.h`:

```

1 // -----
2 class EXP TXMLFile : public smartable
3 {
4     private:
5         TXMLDecl*      fXMLDecl;
6         TDocType*      fDocType;
7         Sxmlelement    fXMLTree;
8
9     protected:
10         TXMLFile () : fXMLDecl(0), fDocType(0) {}
11         virtual ~TXMLFile () { delete fXMLDecl; delete fDocType; }
12
13     public:
14         static SMARTP<TXMLFile> create();
15
16     public:
17         TXMLDecl*      getXMLDecl ()      { return fXMLDecl; }
18         TDocType*      getDocType ()      { return fDocType; }
19         Sxmlelement    elements ()        { return fXMLTree; }
20
21         void           set (Sxmlelement root) { fXMLTree = root; }
22         void           set (TXMLDecl * dec)  { fXMLDecl = dec; }
23         void           set (TDocType * dt)   { fDocType = dt; }
24
25         void           print (std::ostream& s);
26 };
27 typedef SMARTP<TXMLFile> SXMLFile;

```


24.5.1 Creating xmlelement trees from textual data

Reading MusicXML data creates instances of `xmlelement`. This is done by an instance of `xmlreader`, defined in `libmusicxml/src/files/xmlreader.h/.cpp`, which provides methods:

```
1 SXMLFile readbuff(const char* file);
2 SXMLFile read(const char* file);
3 SXMLFile read(FILE* file);
```

These three functions are defined this way:

```
1 // -----
2 SXMLFile xmlreader::readbuff(const char* buffer)
3 {
4     fFile = TXMLFile::create();
5     debug("read buffer", '-');
6     return readbuffer (buffer, this) ? fFile : 0;
7 }
8
9 // -----
10 SXMLFile xmlreader::read(const char* file)
11 {
12     fFile = TXMLFile::create();
13     debug("read", file);
14     return readfile (file, this) ? fFile : 0;
15 }
16
17 // -----
18 SXMLFile xmlreader::read(FILE* file)
19 {
20     fFile = TXMLFile::create();
21     return readstream (file, this) ? fFile : 0;
22 }
```

24.5.2 Printing xmlelement trees

An `xmlelement` can be printed by function `printMxsr ()`, defined in `src/formats/mxsr/mxsr.h/.cpp`:

```
1 void printMxsr (const Sxmlelement theMxsr, ostream& os)
2 {
3     xmlvisitor v (os);
4     tree_browser<xmlelement> browser (&v);
5     browser.browse (*theMxsr);
6 }
```

This how MusicXML and Guido output are generated.

24.6 The SXMLFile type

`SXMLFile` is defined in `libmusicxml/src/factory!musicxmlfactory.h` as a smart pointer to class `TXMLFile`:

```
1 // -----
2 class EXP TXMLFile : public smartable
3 {
4     private:
5         TXMLDecl*          fXMLDecl;
6         TDocType*          fDocType;
7         Sxmlelement       fXMLTree;
8
9     protected:
```

```

10     TXMLFile () : fXMLDecl(0), fDocType(0) {}
11     virtual ~TXMLFile () { delete fXMLDecl; delete fDocType; }
12
13     public:
14         static SMARTP<TXMLFile> create();
15
16     public:
17         TXMLDecl*      getXMLDecl ()      { return fXMLDecl; }
18         TDocType*      getDocType ()      { return fDocType; }
19         Sxmlelement    elements ()        { return fXMLTree; }
20
21         void           set (Sxmlelement root) { fXMLTree = root; }
22         void           set (TXMLDecl * dec)  { fXMLDecl = dec; }
23         void           set (TDocType * dt)   { fDocType = dt; }
24
25         void           print (std::ostream& s);
26 };
27 typedef SMARTP<TXMLFile> SXMLFile;

```

fXMLDecl describes the <?xml/> element and fDocType contains the <"!DOCTYPE"/> element.

Part VII

Passes

Chapter 25

The passes

A pass performs a single translation from one music score description into another, such as from MusicXML to an MXSR, or from an MXSR to an MSR. The name 'pass' comes from the compiler writing field.

25.1 Translating MusicXML data to an MXSR format

This is supplied by the `libmusicxml2` library, a version of which is distributed as part of MusicFormats to avoid the need of two installs and the potential associated problems.

25.1.1 MusicXML coverage

`src/passes/mxsr2msr/mxsr2msrSkeletonBuilder.h/.cpp` and `src/passes/mxsr2msr/mxsr2msrTranslator.h/.cpp` handle many of the MusicXML version 3.1 elements. Some of them are handled by both sub-passes, such as `S_voice`, `S_measure` and `S_harmony`.

Among the elements that MusicFormats does not handle are the ones for which there is no occurrence in the corpus in folder `files/musicxml`, such as `beat-unit-tied` and `metronome-tied`.

The elements that are new in MusicXML version 4.0 are not known nor handled yet.

25.2 Translating an MXSR to an MSR

This is done by class `mxsr2msrTranslator`.

25.3 Translating an MSR to an MXSR

25.4 Translating an MSR to another MSR

Such translation is meant to offer an opportunity to modify the score's description depending on options.

25.5 Translating an MSR to an LPSR

This converter embeds a specific converter of MSR to MSR, to circumvent the famous LilyPond issue #34.

25.6 Translating an LPSR to LilyPond code

There are two visiting trace options for the generation of LilyPond code, one for its MSR component, and the other one for its LPSR own part:

```
1 // %%JMI      Bool      fGenerateMsrVisitingInformation;  
2      Bool      fGenerateLpsrVisitingInformation;
```

25.7 Translating an MSR to an BSR

This converter embeds a specific converter of MSR to MSR, to circumvent the famous LilyPond issue #34.

25.8 Translating a BSR to another BSR

25.9 Translating an MXSR to Guido

Chapter 26

LilyPond code generation

LilyPond code is produced on standard output, unless options option `-output-file-name`, `-o` or option `-auto-output-file-name`, `-aofn` are used.

26.1 Basic principle

Lilypond generation is done in `src/passes/lpsr2lilypond/lpsr2lilypondTranslator.h/.cpp`.

Class `lpsr2lilypondTranslator` provides:

```
1 public:
2
3         lpsr2lilypondTranslator (
4             S_msrOahGroup&  msrOpts,
5             S_lpsrOahGroup& lpsrOpts,
6             ostream&        lilypondCodeStream);
7
8     virtual          ~lpsr2lilypondTranslator ();
9
10    void              translateLpsrToLilypondCode (
11        S_lpsrScore lpsrScore);
```

It contains these fields among others:

```
1 private:
2
3     // options
4     // -----
5
6     S_msrOahGroup      fMsrOahGroup;
7     S_lpsrOahGroup     fLpsrOahGroup;
8
9     // the LPSR score we're visiting
10    // -----
11    S_lpsrScore         fVisitedLpsrScore;
12
13    // the output stream
14    // -----
15
16    ostream&            fLilypondCodeStream;
```

26.2 Generating Scheme functions in the LilyPond output

xml2ly can generate Scheme code that is used by the LilyPond code it generates. This is described in class `lpsrScore` by a number of `*IsNeeded` fields, such as:

```
1 // files includes
2 Bool                fJianpuFileIncludeIsNeeded;
3
4 // Scheme modules
5 Bool                fScmAndAccregSchemeModulesAreNeeded;
6
7 // Scheme functions
8 Bool                fTongueSchemeFunctionIsNeeded;
```

Chapter 27

Braille generation

Braille is written to standard output or to files as binary data. Our reference is http://www.brailleauthority.org/music/Music_Braille_Code_2015.pdf.

27.1 Basic principle

Lilypond generation is done in `src/passes/bsr2braille/bsr2brailleTranslator.h/.cpp`.

Class `bsr2brailleTranslator` provides:

```
1 public:
2
3         bsr2brailleTranslator (
4             S_bsrScore      bsrScore,
5             const S_bsrOahGroup& bsrOpts,
6             ostream&         brailleOutputStream);
7
8     virtual      ~bsr2brailleTranslator ();
9
10    void          translateBsrToBraille ();
```

It contains these fields among others:

```
1 private:
2
3     // options
4     // -----
5
6     S_bsrOahGroup      fBsrOahGroup;
7
8     // the BSR score we're visiting
9     // -----
10
11    S_bsrScore          fVisitedBsrScore;
12
13    // the braille generator used
14    // -----
15
16    S_bsrBrailleGenerator fBrailleGenerator;
17
18    // the output stream
19    // -----
20
21    ostream&            fBrailleOutputStream;
```


27.2 Output files name and contents options

he contents options use the following enumeration types:

```

1 enum class bsrUTFKind {
2     kUTF8, kUTF16
3 };
4
5 enum class bsrByteOrderingKind {
6     kByteOrderingNone,
7     kByteOrderingBigEndian, kByteOrderingSmallEndian
8 };

```

xml2brl supplies a option -files options subgroup:

```

1 jacquesmenu@macmini > xml2brl -query files
2 --- Help for subgroup "files" in group "Files group" ---
3 Files group (-files-group):
4 -----
5 Files (-files):
6   -o, -output-file-name FILENAME
7       Write Braille to file FILENAME instead of standard output.
8   -aofn, -auto-output-file-name
9       This option can only be used when reading from a file.
10      Write MusicXML code to a file in the current working directory.
11      The file name is derived from that of the input file,
12      replacing any suffix after the '.' by 'xml'
13      or adding '.xml' if none is present.
14   -bok, -braille-output-kind OUTPUT_KIND
15       Use OUTPUT_KIND to write the generated Braille to the output.
16       The 4 output kinds available are:
17       ascii, utf16, utf8 and utf8d.
18       'utf8d' leads to every line in the braille score to be generated
19       as a line of cells followed by a line of text showing the contents
20       for debug purposes.
21       The default is 'ascii'.
22   -ueifn, -use-encoding-in-file-name
23       Append a description of the encoding used
24       and the presence of a BOM if any to the file name before the '.'.
25   -bom, -byte-ordering-mark BOM_ENDIAN
26       Generate an initial BOM_ENDIAN byte ordering mark (BOM)
27       ahead of the Braille nusic code,
28       which can be one of 'big' or 'small'.
29       By default, a big endian BOM is generated.

```

27.3 Braille generators

The following classes are defined in [src/formatsgeneration/brailleGeneration/brailleGeneration.h/.cpp](#)

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src/formatsgeneration/brailleGeneration > grep
2     class brailleGeneration.h
3 enum class bsrUTFKind {
4 enum class bsrByteOrderingKind {
5 class EXP bsrBrailleGenerator : public smartable
6 /* this class is purely virtual
7 class EXP bsrAsciiBrailleGenerator : public bsrBrailleGenerator
8 class EXP bsrUTF8BrailleGenerator : public bsrBrailleGenerator
9 class EXP bsrUTF8DebugBrailleGenerator : public bsrUTF8BrailleGenerator
10 class EXP bsrUTF16BigEndianBrailleGenerator : public bsrBrailleGenerator
11 class EXP bsrUTF16SmallEndianBrailleGenerator : public bsrBrailleGenerator

```

The base class bsrBrailleGenerator contains:

```

1 public:
2
3     // public services
4     // -----
5
6     virtual void          generateCodeForBrailleCell (
7                             bsrCellKind cellKind) = 0;
8
9     void                generateCodeForCellsList (
10                            S_bsrCellsList cellsList);
11
12     virtual void          generateCodeForMusicHeading (
13                             S_bsrMusicHeading musicHeading);
14
15     virtual void          generateCodeForLineContents (
16                             S_bsrLineContents lineContents);
17
18     // ... ..
19
20 protected:
21
22     // protected fields
23     // -----
24
25     ostream&              fBrailleOutputStream;

```

27.4 Writing braille cells

Braille cells are output to an `ostream` as hexadecimal strings by virtual method `generateCodeForBrailleCell ()` methods in `src/passes/bsr2braille/brailleGeneration.h`, depending on the kind of output chosen.

For example, ASCII braille generation is done by:

```

1 void bsrAsciiBrailleGenerator::generateCodeForBrailleCell (
2     bsrCellKind cellKind)
3 {
4     string stringForCell;
5
6     switch (cellKind) {
7         case bsrCellKind::kCellUnknown:
8             {
9                 stringstream s;
10
11                 s <<
12                     "cannot generate code for braille cell '" <<
13                     bsrCellKindAsString (cellKind) <<
14                     "'";
15                 msrInternalError (
16                     gGlobalServiceRunData->getInputSourceName (),
17                     -999, // inputLineNumber, TICINO JMI
18                     __FILE__, __LINE__,
19                     s.str ());
20             }
21             break;
22
23         case bsrCellKind::kCellEOL:      stringForCell = "\x0a"; break;
24         case bsrCellKind::kCellEOP:      stringForCell = "\x0c"; break;
25
26         case bsrCellKind::kDotsNone:     stringForCell = "\x20"; break;
27
28         case bsrCellKind::kDots1:        stringForCell = "\x41"; break;
29         case bsrCellKind::kDots2:        stringForCell = "\x31"; break;
30

```

```
31     // ... ..
32
33     case bsrCellKind::kDots23456:  stringForCell = "\x29"; break;
34     case bsrCellKind::kDots123456:  stringForCell = "\x3d"; break;
35 } // switch
36
37 fBrailleOutputStream <<
38     stringForCell;
39 }
```

Chapter 28

MusicXML generation

MusicXML text is produced on the standard output stream, unless options `'-output-file-name'` or `'-auto-output-f` are used.

28.1 Basic principle

MusicXML generation is done in two passes:

- first create and MXSR containing the data;
- then simply write this tree.

28.2 Creating an xmlelement

An simple example is:

```
1 // create a direction element
2 Sxmlelement directionElement = createMxmlelement (k_direction, "");
3
4 // set it's "placement" attribute if relevant
5 string
6     placementString =
7     msrPlacementKindAsMusicXMLString (placementKind);
8
9 if (placementString.size ()) {
10     directionElement->add (createMxmlAttribute ("placement", placementString));
11 }
```

This one supplies a value to the `xmlelement` it creates:

```
1 void msr2mxsrTranslator::visitStart (S_msrIdentification& elt)
2 {
3     // composers
4     const list<string>&
5     composersList =
6     elt->getComposersList ();
7
8     for (
9     list<string>::const_iterator i=composersList.begin ();
10     i!=composersList.end ();
11     ++i
12     ) {
13     string variableValue = (*i);
```

```

14
15 // create a creator element
16 Sxmlelement creatorElement = createMxmlelement (k_creator, variableValue);
17
18 // set its "type" attribute
19 creatorElement->add (createMxmlAttribute ("type", "composer"));
20
21 // append it to the composers elements list
22 fComposersElementsList.push_back (creatorElement);
23 } // for
24
25 // ... ..
26 }

```

28.3 Creating an xmlelement tree

In , this code:

```

1 void msr2mxsrTranslator::visitStart (S_msrClef& elt)
2 {
3     // ... ..
4
5     Sxmlelement clefElement = createMxmlelement (k_clef, "");
6
7     // set clefElement's "number" attribute if relevant
8     /*
9      0 by default in MSR,
10     1 by default in MusicXML:
11     The optional number attribute refers to staff numbers within the part,
12     from top to bottom on the system.
13     A value of 1 is assumed if not present.
14     */
15
16     int clefStaffNumber =
17         elt->getClefStaffNumber ();
18
19     if (clefStaffNumber > 1) {
20         clefElement->add (
21             createMxmlIntegerAttribute ("number", clefStaffNumber));
22     }
23
24     // populate clefElement
25     switch (elt->getClefKind ()) {
26         // ... ..
27
28         case msrClefKind::kClefTrebleMinus8:
29             {
30                 clefElement->push (
31                     createMxmlelement (
32                         k_sign,
33                         "G"));
34                 clefElement->push (
35                     createMxmlIntegerElement (
36                         k_line,
37                         2));
38                 clefElement->push (
39                     createMxmlIntegerElement (
40                         k_clef_octave_change,
41                         -1));
42             }
43             break;
44
45         // ... ..
46     }

```

creates this MusicXML element depending on the value returned by method `msrClef::getClefStaffNumber ()`:

```

1 <clef number="2">
2   <sign>G</sign>
3   <line>2</line>
4   <clef-octave-change>-1</clef-octave-change>
5 </clef>

```

28.4 Browsing the visited MSR score

The creation of the tree is done in `src/passes/msr2mxsr/msr2mxsrTranslator.h/.cpp`.

Class `msr2mxsrTranslator` is defined in those files, it contains:

```

1 public:
2
3         msr2mxsrTranslator (
4             S_msrScore visitedMsrScore);
5
6     virtual         ~msr2mxsrTranslator ();
7
8     Sxmlelement     translateMsrToMxsr ();
9
10    // ... ..
11
12 private:
13
14    // the MSR score we're visiting
15    // -----
16    S_msrScore         fVisitedMsrScore;
17
18
19    // the MXSR we're building
20    // -----
21    Sxmlelement         fResultingMusicxmlelement;

```

The method `msr2mxsrTranslator::translateMsrToMxsr ()` method does the following:

```

1 // -----
2 Sxmlelement msr2mxsrTranslator::translateMsrToMxsr ()
3 {
4     // sanity check
5     mfAssert (
6         __FILE__, __LINE__,
7         fVisitedMsrScore != nullptr,
8         "fVisitedMsrScore is null");
9
10    // create the current score part-wise element
11    fResultingMusicxmlelement =
12        createMxmlScorePartWiseElement ();
13
14    // create a msrScore browser
15    msrBrowser<msrScore> browser (this);
16
17    // browse the visited score with the browser
18    browser.browse (*fVisitedMsrScore);
19
20    return fResultingMusicxmlelement;
21 }

```

28.5 Ancillary functions to create MXSR data

The function `createMxmlScorePartWiseElement ()` is defined in `src/formats/mxsr/mxsr.h/.cpp`:

```
1 //-----  
2 Sxmlelement createMxmlScorePartWiseElement ()  
3 {  
4     Sxmlelement result = factory::instance ().create (k_score_partwise);  
5  
6     Sxmlelement versionAttribute = createMxmlAttribute("version", "3.1");  
7     result->add (versionAttribute);  
8  
9     return result;  
10 }
```

Chapter 29

Guido code generation

Guido code is produced on standard output, unless options option `-output-file-name`, `-o` or option `-auto-output-file-name`, `-aofn` are used.

29.1 Basic principle

As is done for MusicXML generation, Guido generation is done in two passes:

- first create and `mxsr` containing the data;
- then simply write this tree.

The creation of the tree is done in [src/passes/msr2mxsr/msr2mxsrTranslator.h/.cpp](#). See subsection [28.1](#) [musicxmlGeneration], page [227](#), for more details.

Part VIII

Generators

Chapter 30

The generators

A generator creates a music score ex-nihilo, without any description of the music being input. It's behaviour can be adapted to the users needs with options if needed.

Generators are supplied in the `src/generators/` directory. They don't have any interface in at the time of this writing, even though they could.

30.1 MusicAndHarmonies

`MusicAndHarmonies.cpp`

30.2 Mikrokosmos3Wandering

This service produces the score for Zoltán Kodály's Mikrokosmos III Wandering score, taking inspiration from the same example in Abjad (http://abjad.mbrsi.org/literature_examples/bartok.html). Is was written in the first place to check the MSR API before writing the MSDDL converter.

The score produced is shown at figure 30.1 [Zoltán Kodály's Mikrokosmos III Wandering], page 233.



Figure 30.1: Zoltán Kodály's Mikrokosmos III Wandering

30.3 LilyPondIssue34


This service produces the same score as that obtained by:

```
1 xml2ly -auto-output-file-name gracenotes/LilyPondIssue34.xml
```

The resulting score is shown at figure 30.2 [The LilyPondIssue34 score], page 234.

Piano Sonata in A Major

Wolfgang A



Piano

Figure 30.2: The LilyPondIssue34 score

The name LilyPondIssue34 stems from the fact that translating this MusicXML file to LilyPond with `musicxml2ly` exhibits the famous LilyPond issue #34.

This example was written to design a LilyPond-oriented interface to LPSR, preparing the grounds for LilyPond export to other formats. This work is in progress at the time of this writing.

Part IX

Converters

Chapter 31

The converters

A multi-pass converter performs a sequence of passes, i.e. a sequence of steps. For example, `xml2ly` performs the following passes:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev/files/musicxml > xml2ly -about
2 What xml2ly does:
3
4     This multi-pass converter basically performs 5 passes:
5         Pass 1:  reads the contents of MusicXMLFile or stdin ('-')
6                 and converts it to a MusicXML tree;
7         Pass 2a: converts that MusicXML tree into
8                 a first Music Score Representation (MSR) skeleton;
9         Pass 2b: populates the first MSR skeleton from the MusicXML tree
10                to get a full MSR;
11         Pass 3:  converts the first MSR into a second MSR to apply options
12         Pass 4:  converts the second MSR into a
13                 LilyPond Score Representation (LPSR);
14         Pass 5:  converts the LPSR to LilyPond code
15                 and writes it to standard output.
16
17     Other passes are performed according to the options, such as
18     displaying views of the internal data or printing a summary of the score.
19
20     The activity log and warning/error messages go to standard error.
```

31.1 xml2ly

MusicXML (*Music eXtended Markup Language*) is a specification language meant to represent music scores by texts, readable both by humans and computers. It has been designed by the W3C Music Notation Community Group (<https://www.w3.org/community/music-notation/>) to help sharing music score files between applications, through export and import mechanisms.

The homepage to MusicXML is <https://www.musicxml.com>.

MusicXML data contains very detailed information about the music score, and it is quite verbose by nature. This makes creating such data by hand quite difficult, and this is done by applications actually.

The MusicXML data is not systematically checked for correctness. Checks are done, however, to ensure it won't crash due to missing values.

31.2 xml2brl

`xml2brl` is mentioned here, but not described in detail.

31.3 xml2xml**31.4** xml2gmh**31.5** msdlconverter

Part X

Interfaces

Chapter 32

Library interfaces

Chapter 33

Representations interfaces

These interfaces are a set of functions to create formats for various needs.

33.1 MSR interfaces

The MSR interfaces are in `interfaces/msrinterfaces/`:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev/src > ll interfaces/msrinterfaces/  
2 total 32  
3 0 drwxr-xr-x  5 jacquesmenu  staff    160 May 26 08:20:55 2021 ./  
4 0 drwxr-xr-x  8 jacquesmenu  staff    256 Jun 25 05:59:13 2021 ../  
5 8 -rw-r--r--@ 1 jacquesmenu  staff     77 Apr 22 15:49:27 2021 README.md  
6 16 -rw-r--r--@ 1 jacquesmenu  staff   5796 Jun 24 17:47:02 2021 msrInterface.cpp  
7 8 -rw-r--r--@ 1 jacquesmenu  staff   1371 Jun 13 07:38:04 2021 msrInterface.h
```

33.2 LPSR interfaces

The LSPR interfaces are in `interfaces/lpsrinterfaces/`:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev/src > ll interfaces/lpsrinterfaces/  
2 total 24  
3 0 drwxr-xr-x  5 jacquesmenu  staff    160 Jun 13 07:36:53 2021 ./  
4 0 drwxr-xr-x  8 jacquesmenu  staff    256 Jun 25 05:59:13 2021 ../  
5 8 -rw-r--r--@ 1 jacquesmenu  staff     78 Jun 13 07:37:13 2021 README.md  
6 8 -rw-r--r--@ 1 jacquesmenu  staff    670 Jun 13 07:41:01 2021 lpsrInterface.cpp  
7 8 -rw-r--r--@ 1 jacquesmenu  staff   1450 Jun 13 07:39:29 2021 lpsrInterface.h
```

33.3 MSDL interfaces

The MSDL interfaces are in `interfaces/msdlinterfaces/`:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev/src > ll interfaces/msdlinterfaces/  
2 total 8  
3 0 drwxr-xr-x  3 jacquesmenu  staff     96 Jun 25 05:57:39 2021 ./  
4 0 drwxr-xr-x  8 jacquesmenu  staff    256 Jun 25 05:59:13 2021 ../  
5 8 -rw-r--r--@ 1 jacquesmenu  staff   1967 Jun  6 06:38:55 2021 libmsdl.h
```

Chapter 34

Passes interfaces

MusicFormats provides its functionality in two ways:

- a set of API functions providing its services to any application, including the ones hosted on the Web;
- a set of CLI tools, to be used in terminals and scripts.

The CLI tool actually use the API functions to do their job. For example, in `mfcli`, the `main ()` function does:

```
1 int main (int argc, char* argv[])
2 // -----
3 {
4     // setup signals catching
5     // -----
6
7     catchSignals ();
8
9     // ... ..
10
11     switch (multiGenerationOutputKind) {
12         case mfMultiGenerationOutputKind::k_NoGeneration:
13             // should not occur, unless the run is a pure help one
14             break;
15
16             // ... ..
17
18         case mfMultiGenerationOutputKind::k_GenerationGuido:
19             err =
20                 msrScore2guidoWithHandler (
21                     theMsrScore,
22                     "Pass 2",
23                     "Convert the MSR score into a second MSR",
24                     "Pass 3",
25                     "Convert the second MSR into an MXSR",
26                     "Pass 4",
27                     "Convert the MXSR into Guido text",
28                     cout,
29                     cerr,
30                     handler);
31             break;
32
33             // ... ..
34     }
```

34.1 Translating MusicXML data to an MXSR

34.2 Translating an MXSR to an MSR

34.3 Translating an MSR to an MXSR

34.4 Translating an MSR to another MSR

Such translation is meant to offer an opportunity to modify the score's description depending on options.

34.5 Translating an MSR to an LPSR

This converter embeds a specific converter of MSR to MSR, to circumvent the famous LilyPond issue #34.

34.6 Translating an LPSR to LilyPond code

34.7 Translating an MSR to an BSR

This converter embeds a specific converter of MSR to MSR, to circumvent the famous LilyPond issue #34.

34.8 Translating a BSR to another BSR

34.9 Translating an MXSR to Guido

Chapter 35

Converters interfaces

These interfaces are a set of functions to run the various converters. They are placed in the corresponding subdirectories of `src/converters/`, such as `src/converters/musicxml2musicxml/musicxml2musicxmlInterface`.

```
1 jacquesmenu@macmini: ~/musicformats-git-dev/src/converters/musicxml2musicxml > cat
   musicxml2musicxmlInterface.h
2 /*
3  MusicFormats Library
4  Copyright (C) Jacques Menu 2016-2022
5
6  This Source Code Form is subject to the terms of the Mozilla Public
7  License, v. 2.0. If a copy of the MPL was not distributed with this
8  file, You can obtain one at http://mozilla.org/MPL/2.0/.
9
10 https://github.com/jacques-menu/musicformats
11 */
12
13 #ifndef __musicxml2musicxmlInterface__
14 #define __musicxml2musicxmlInterface__
15
16 #include "mfMusicformatsError.h" // for mfMusicformatsError
17
18
19 using namespace std;
20
21 namespace MusicFormats
22 {
23 /*
24  The API functions with an options and arguments and no handler
25  are declared in libmusicxml.h
26 */
27
28 //-----
29 EXP mfMusicformatsError convertMusicxmlFile2musicxmlWithHandler (
30     const char*   fileName,
31     ostream&      out,
32     ostream&      err,
33     S_oahHandler  handler);
34
35 //-----
36 EXP mfMusicformatsError convertMusicxmlFd2musicxmlWithHandler (
37     FILE*         fd,
38     ostream&      out,
39     ostream&      err,
40     S_oahHandler  handler);
41
42 //-----
43 EXP mfMusicformatsError convertMusicxmlString2musicxmlWithHandler (
44     const char*   buffer,
```

```
45     ostream&      out ,
46     ostream&      err ,
47     S_oahHandler  handler);
48
49
50 }
51
52
53 #endif
```

Part XI

Distributions and versions

Chapter 36

MusicFormats distributions

The MusicFormats repository is hosted by GitHub and uses so-called *actions* to build the library on Mac OS™, Ubuntu and Windows™. The resulting files are then uploaded to the repository, where they are available to create the distributions for these three operating systems.

The distributions Zip archives are supplied with all MusicFormats versions, i.e. the current, most recent version of MusicFormats (the default master branch in the repository), and the earlier versions such as the v0.9.60 branch.

36.1 GitHub actions

These actions are defined in .yaml files in .github/workflows/:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev/.github/workflows > ls -sal
2 total 32
3 0 drwxr-xr-x  6 jacquesmenu  staff    192 Feb 19 08:07 .
4 0 drwxr-xr-x@ 4 jacquesmenu  staff    128 May  5 2021 ..
5 8 -rw-r--r--@ 1 jacquesmenu  staff  1285 Feb 11 17:55 macos-check.yaml
6 8 -rw-r--r--@ 1 jacquesmenu  staff  1343 Feb 11 17:55 ubuntu-check.yaml
7 8 -rw-r--r--@ 1 jacquesmenu  staff  1396 Feb 11 17:55 windows-check.yaml
```

For example, the Ubuntu action in file ubuntu-check.yaml is shown below. It is executed each time a `git push` is performed to the master branch:

```
1 # This is a workflow to build MusicFormats and create a distribution of it
2
3 name: Ubuntu
4
5 # Controls when the action will run.
6 on:
7   # Triggers the workflow on push or pull request events but only for the master branch
8   push:
9     branches: [ master ]
10  pull_request:
11    branches: [ master ]
12
13 # Allows you to run this workflow manually from the Actions tab
14 workflow_dispatch:
15
16 # A workflow run is made up of one or more jobs that can run sequentially or in parallel
17 jobs:
18   # This workflow contains a single job called "build"
19   build:
20     # The type of runner that the job will run on
21     runs-on: ubuntu-latest
```

```

22
23 # Steps represent a sequence of tasks that will be executed as part of the job
24 steps:
25 # Checks-out your repository under $GITHUB_WORKSPACE, so your job can access it
26 - uses: actions/checkout@v2
27
28 - name: Build MusicFormats for Ubuntu
29   run: make -C build
30
31 - name: Upload libraries and executables for Ubuntu
32   uses: actions/upload-artifact@v2
33   with:
34     name: musicformats-ubuntu-distrib
35     path: |
36       MusicFormatsVersionNumber.txt
37       build/bin
38       build/lib/*.a
39       build/lib/*.so
40       documentation/IntroductionToMusicXML/IntroductionToMusicXML.pdf
41       documentation/MusicFormatsUserGuide/MusicFormatsUserGuide.pdf

```

After a push to the master branch:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev > git commit -m "Switched from C++11 to C++17
  for <filesystem>" -a[master 77d3d29] Switched from C++11 to C++17 for <filesystem>
2 7 files changed, 10 insertions(+), 10 deletions(-)
3
4 jacquesmenu@macmini: ~/musicformats-git-dev > git push
5 Enumerating objects: 33, done.
6 Counting objects: 100% (33/33), done.
7 Delta compression using up to 8 threads
8 Compressing objects: 100% (16/16), done.
9 Writing objects: 100% (17/17), 1.47 KiB | 1.47 MiB/s, done.
10 Total 17 (delta 14), reused 0 (delta 0), pack-reused 0
11 remote: Resolving deltas: 100% (14/14), completed with 13 local objects.
12 To https://github.com/jacques-menu/musicformats.git
13 a880063..77d3d29 master -> master

```

we get for example:

github.com/jacques-menu/musicformats/actions

Bienvenue sur e-PJ MusicFormats Qt C++ MusicXML Brother Mac OS 12 LilyPond Mac OS 11 Mac OS X JavaScript Sax Soprano

Actions · jacques-menu/musicformats

Search or jump to...

Pull requests Issues Marketplace Explore

jacques-menu / musicformats Public

Pin Unwatch 2 Fork 0 Star 0

<> Code Issues Pull requests Actions Projects Wiki Security Insights Settings

Workflows

New workflow

All workflows

MacOS

Node.js Package

Ubuntu

Windows

All workflows

Showing runs from all workflows

Filter workflow runs

777 workflow runs

Event Status Branch Actor

Switched from C++11 to C++17 for <filesystem>

Ubuntu #8: Commit 38b584f pushed by jacques-menu

master

4 hours ago 37m 47s

Switched from C++11 to C++17 for <filesystem>

Windows #8: Commit 38b584f pushed by jacques-menu

master

4 hours ago 46m 25s

Switched from C++11 to C++17 for <filesystem>

MacOS #8: Commit 38b584f pushed by jacques-menu

master

4 hours ago 20m 22s

Then clicking on the link leads to:

248/415

github.com/jacques-menu/musicformats/actions/runs/1921985888

Bienvenue sur e-PJ MusicFormats Qt C++ MusicXML Brother Mac OS 12 LilyPond Mac OS 11 Mac OS X JavaScript Sax Soprano

Switched from C++11 to C++17 for <filesystem> - jacques-menu/musicformats@38b584f

Search or jump to... Pull requests Issues Marketplace Explore

jacques-menu / musicformats Public

Pin Unwatch 2 Fork 0 Star 0

Code Issues Pull requests **Actions** Projects Wiki Security Insights Settings

Switched from C++11 to C++17 for <filesystem> Ubuntu #8 Re-run all jobs

Summary

Jobs

build

Triggered via push 19 hours ago

jacques-menu pushed 38b584f master

Status **Success** Total duration **37m 47s** Artifacts **1**

ubuntu-check.yml
on: push

build 37m 35s

Artifacts
Produced during runtime

Name	Size
musicformats-ubuntu-distrib	79.3 MB

The musicformats-ubuntu-distrib archive has to be clicked to get downloaded, since its URL cannot be guessed by an algorithm (it contains numbers internal to GitHub).

Doing so for the three distributions, we get the following, here in the Downloads/ folder on Mac OS™, with the Zip archives are automatically uncompressed :

```

1 jacquesmenu@macmini: ~/Downloads > ls -sal musicformats-*-distrib
2 musicformats-macos-distrib:
3 total 8
4 0 drwx-----@ 5 jacquesmenu staff 160 Mar 3 09:18 .
5 0 drwx-----+ 72 jacquesmenu staff 2304 Mar 3 09:18 ..
6 8 -rw-r--r--@ 1 jacquesmenu staff 6 Mar 3 07:10 MusicFormatsVersionNumber.txt
7 0 drwxr-xr-x@ 3 jacquesmenu staff 96 Mar 3 09:18 build
8 0 drwxr-xr-x@ 4 jacquesmenu staff 128 Mar 3 09:18 documentation
9
10 musicformats-ubuntu-distrib:
11 total 8
12 0 drwx-----@ 5 jacquesmenu staff 160 Mar 3 09:18 .
13 0 drwx-----+ 72 jacquesmenu staff 2304 Mar 3 09:18 ..
14 8 -rw-r--r--@ 1 jacquesmenu staff 6 Mar 3 07:31 MusicFormatsVersionNumber.txt
15 0 drwxr-xr-x@ 4 jacquesmenu staff 128 Mar 3 09:18 build
16 0 drwxr-xr-x@ 4 jacquesmenu staff 128 Mar 3 09:18 documentation
17
18 musicformats-windows-distrib:
19 total 8
20 0 drwx-----@ 5 jacquesmenu staff 160 Mar 3 09:18 .
21 0 drwx-----+ 72 jacquesmenu staff 2304 Mar 3 09:18 ..
22 8 -rw-r--r--@ 1 jacquesmenu staff 6 Mar 3 07:43 MusicFormatsVersionNumber.txt
23 0 drwxr-xr-x@ 4 jacquesmenu staff 128 Mar 3 09:18 build

```

```
24 0 drwxr-xr-x@ 4 jacquesmenu staff 128 Mar 3 09:18 documentation
```

```
1 jacquesmenu@macmini: ~/Downloads > ls -sal musicformats-ubuntu-distrib/*
2 8 -rw-r--r--@ 1 jacquesmenu staff 6 Mar 3 07:31 musicformats-ubuntu-distrib/
   MusicFormatsVersionNumber.txt
3
4 musicformats-ubuntu-distrib/build:
5 total 0
6 0 drwxr-xr-x@ 4 jacquesmenu staff 128 Mar 3 09:18 .
7 0 drwx-----@ 5 jacquesmenu staff 160 Mar 3 09:18 ..
8 0 drwxr-xr-x@ 25 jacquesmenu staff 800 Mar 3 09:18 bin
9 0 drwxr-xr-x@ 4 jacquesmenu staff 128 Mar 3 09:18 lib
10
11 musicformats-ubuntu-distrib/documentation:
12 total 0
13 0 drwxr-xr-x@ 4 jacquesmenu staff 128 Mar 3 09:18 .
14 0 drwx-----@ 5 jacquesmenu staff 160 Mar 3 09:18 ..
15 0 drwxr-xr-x@ 3 jacquesmenu staff 96 Mar 3 09:18 IntroductionToMusicXML
16 0 drwxr-xr-x@ 3 jacquesmenu staff 96 Mar 3 09:18 MusicFormatsUserGuide
```

```
1 jacquesmenu@macmini: ~/Downloads > ls -sal musicformats-ubuntu-distrib/*/*
2 musicformats-ubuntu-distrib/build/bin:
3 total 2272
4 0 drwxr-xr-x@ 25 jacquesmenu staff 800 Mar 3 09:18 .
5 0 drwxr-xr-x@ 4 jacquesmenu staff 128 Mar 3 09:18 ..
6 96 -rw-r--r--@ 1 jacquesmenu staff 49008 Mar 3 07:31 LilyPondIssue34
7 96 -rw-r--r--@ 1 jacquesmenu staff 49048 Mar 3 07:31 Mikrokosmos3Wandering
8 96 -rw-r--r--@ 1 jacquesmenu staff 47280 Mar 3 07:31 MusicAndHarmonies
9 96 -rw-r--r--@ 1 jacquesmenu staff 47272 Mar 3 07:31 RandomChords
10 96 -rw-r--r--@ 1 jacquesmenu staff 47272 Mar 3 07:31 RandomMusic
11 72 -rw-r--r--@ 1 jacquesmenu staff 33848 Mar 3 07:31 countnotes
12 40 -rw-r--r--@ 1 jacquesmenu staff 17648 Mar 3 07:31 displayMusicformatsHistory
13 40 -rw-r--r--@ 1 jacquesmenu staff 17648 Mar 3 07:31 displayMusicformatsVersion
14 104 -rw-r--r--@ 1 jacquesmenu staff 50400 Mar 3 07:31 msdlconverter
15 544 -rw-r--r--@ 1 jacquesmenu staff 276024 Mar 3 07:31 partsummary
16 88 -rw-r--r--@ 1 jacquesmenu staff 43768 Mar 3 07:31 readunrolled
17 80 -rw-r--r--@ 1 jacquesmenu staff 39064 Mar 3 07:31 xml2brl
18 80 -rw-r--r--@ 1 jacquesmenu staff 39104 Mar 3 07:31 xml2gmn
19 48 -rw-r--r--@ 1 jacquesmenu staff 23192 Mar 3 07:31 xml2guido
20 72 -rw-r--r--@ 1 jacquesmenu staff 34816 Mar 3 07:31 xml2ly
21 88 -rw-r--r--@ 1 jacquesmenu staff 42928 Mar 3 07:31 xml2midi
22 80 -rw-r--r--@ 1 jacquesmenu staff 39104 Mar 3 07:31 xml2xml
23 88 -rw-r--r--@ 1 jacquesmenu staff 43416 Mar 3 07:31 xmlclone
24 48 -rw-r--r--@ 1 jacquesmenu staff 22616 Mar 3 07:31 xmlfactory
25 160 -rw-r--r--@ 1 jacquesmenu staff 79440 Mar 3 07:31 xmliter
26 56 -rw-r--r--@ 1 jacquesmenu staff 28472 Mar 3 07:31 xmlread
27 64 -rw-r--r--@ 1 jacquesmenu staff 28704 Mar 3 07:31 xmltranspose
28 40 -rw-r--r--@ 1 jacquesmenu staff 17360 Mar 3 07:31 xmlversion
29
30 musicformats-ubuntu-distrib/build/lib:
31 total 158600
32 0 drwxr-xr-x@ 4 jacquesmenu staff 128 Mar 3 09:18 .
33 0 drwxr-xr-x@ 4 jacquesmenu staff 128 Mar 3 09:18 ..
34 113728 -rw-r--r--@ 1 jacquesmenu staff 58227464 Mar 3 07:31 libmusicformats.a
35 44872 -rw-r--r--@ 1 jacquesmenu staff 22971160 Mar 3 07:31 libmusicformats.so
36
37 musicformats-ubuntu-distrib/documentation/IntroductionToMusicXML:
38 total 1704
39 0 drwxr-xr-x@ 3 jacquesmenu staff 96 Mar 3 09:18 .
40 0 drwxr-xr-x@ 4 jacquesmenu staff 128 Mar 3 09:18 ..
41 1704 -rw-r--r--@ 1 jacquesmenu staff 869211 Mar 3 07:31 IntroductionToMusicXML.pdf
42
43 musicformats-ubuntu-distrib/documentation/MusicFormatsUserGuide:
44 total 3000
45 0 drwxr-xr-x@ 3 jacquesmenu staff 96 Mar 3 09:18 .
46 0 drwxr-xr-x@ 4 jacquesmenu staff 128 Mar 3 09:18 ..
```

```
47 3000 -rw-r--r--@ 1 jacquesmenu staff 1532300 Mar 3 07:31 MusicFormatsUserGuide.pdf
```

The contents of `musicformats-windows-distrib/` differs in the `lib/` contents:

```
1 jacquesmenu@macmini: ~/Downloads > ls -sal musicformats-windows-distrib/build/lib/
2 total 37672
3      0 drwxr-xr-x@ 4 jacquesmenu staff      128 Mar 3 09:18 .
4      0 drwxr-xr-x@ 4 jacquesmenu staff      128 Mar 3 09:18 ..
5 14768 -rw-r--r--@ 1 jacquesmenu staff 7558913 Mar 3 07:44 musicformats.exp
6 22904 -rw-r--r--@ 1 jacquesmenu staff 11726392 Mar 3 07:44 musicformats.lib
```

For Mac OS™, there is no `lib/` directory, since the executables in `bin/` are self-sufficient. They can be placed anywhere on a disk except the trash. Usually, they are placed in the `/Applications/` directory.

36.1.1 Creating the distributions

The hierarchy in the `musicformats-*-distrib/` directories comes from the MusicFormats repository untouched, which is not convenient for the users.

Their contents is thus re-structured by `scripts/MakeMusicFormatsDistributions.bash`:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev > scripts/MakeMusicFormatsDistributions.bash
2 ... ..
3
4 ==> final distrib contents:
5 -----
6
7 4208 -rw-r--r-- 1 jacquesmenu staff 2153547 Mar 3 12:55 /Users/jacquesmenu/
8 musicformats-git-dev/distrib/MusicFormatsForWindows.zip
9 34576 -rw-r--r-- 1 jacquesmenu staff 17559638 Mar 3 12:55 /Users/jacquesmenu/
10 musicformats-git-dev/distrib/MusicFormatsForUbuntu.zip
11 109512 -rw-r--r-- 1 jacquesmenu staff 55888914 Mar 3 12:55 /Users/jacquesmenu/
12 musicformats-git-dev/distrib/MusicFormatsForMacOS.zip
13 1704 -rw-r--r--@ 1 jacquesmenu staff 869211 Mar 3 07:10 /Users/jacquesmenu/
14 musicformats-git-dev/distrib/IntroductionToMusicXML.pdf
15 3000 -rw-r--r--@ 1 jacquesmenu staff 1532300 Mar 3 07:10 /Users/jacquesmenu/
16 musicformats-git-dev/distrib/MusicFormatsUserGuide.pdf
17 8 -rw-r--r--@ 1 jacquesmenu staff 6 Mar 3 07:10 /Users/jacquesmenu/
18 musicformats-git-dev/distrib/MusicFormatsVersionNumber.txt
19
20 /Users/jacquesmenu/musicformats-git-dev/distrib/MusicFormatsForWindows:
21 total 8
22 0 drwxr-xr-x 16 jacquesmenu staff 512 Mar 3 12:55 ..
23 0 drwxr-xr-x 5 jacquesmenu staff 160 Mar 3 12:55 .
24 0 drwxr-xr-x@ 4 jacquesmenu staff 128 Mar 3 09:18 lib
25 0 drwxr-xr-x@ 25 jacquesmenu staff 800 Mar 3 09:18 bin
26 8 -rw-r--r--@ 1 jacquesmenu staff 6 Mar 3 07:43 MusicFormatsVersionNumber.txt
27
28 /Users/jacquesmenu/musicformats-git-dev/distrib/MusicFormatsForUbuntu:
29 total 8
30 0 drwxr-xr-x 16 jacquesmenu staff 512 Mar 3 12:55 ..
31 0 drwxr-xr-x 5 jacquesmenu staff 160 Mar 3 12:55 .
32 0 drwxr-xr-x@ 4 jacquesmenu staff 128 Mar 3 09:18 lib
33 0 drwxr-xr-x@ 25 jacquesmenu staff 800 Mar 3 09:18 bin
34 8 -rw-r--r--@ 1 jacquesmenu staff 6 Mar 3 07:31 MusicFormatsVersionNumber.txt
35
36 /Users/jacquesmenu/musicformats-git-dev/distrib/MusicFormatsForMacOS:
37 total 8
38 0 drwxr-xr-x 16 jacquesmenu staff 512 Mar 3 12:55 ..
39 0 drwxr-xr-x 4 jacquesmenu staff 128 Mar 3 12:55 .
40 0 drwxr-xr-x@ 25 jacquesmenu staff 800 Mar 3 07:10 bin
41 8 -rw-r--r--@ 1 jacquesmenu staff 6 Mar 3 07:10 MusicFormatsVersionNumber.txt
```

The contents of `distrib/` is now:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/distrib > ls -sal
2 total 154128
3      0 drwxr-xr-x  16 jacquesmenu  staff          512 Mar  3 13:18 .
4      0 drwxr-xr-x  35 jacquesmenu  staff         1120 Mar  3 07:13 ..
5     24 -rw-r--r--@   1 jacquesmenu  staff        8196 Feb 24 13:33 .DS_Store
6    1704 -rw-r--r--@   1 jacquesmenu  staff       869211 Mar  3 07:10 IntroductionToMusicXML.pdf
7      0 drwxr-xr-x   4 jacquesmenu  staff         128 Mar  3 13:18 MusicFormatsForMacOS
8 109960 -rw-r--r--   1 jacquesmenu  staff    55888914 Mar  3 13:18 MusicFormatsForMacOS.zip
9      0 drwxr-xr-x   5 jacquesmenu  staff         160 Mar  3 13:18 MusicFormatsForUbuntu
10   35216 -rw-r--r--   1 jacquesmenu  staff    17559638 Mar  3 13:18 MusicFormatsForUbuntu.zip
11      0 drwxr-xr-x   5 jacquesmenu  staff         160 Mar  3 13:18 MusicFormatsForWindows
12   4208 -rw-r--r--   1 jacquesmenu  staff    2153547 Mar  3 13:18 MusicFormatsForWindows.zip
13   3000 -rw-r--r--@   1 jacquesmenu  staff    1532300 Mar  3 07:10 MusicFormatsUserGuide.pdf
14      8 -rw-r--r--@   1 jacquesmenu  staff          6 Mar  3 07:10 MusicFormatsVersionNumber.
    txt
15      8 -rwxr-xr-x@   1 jacquesmenu  staff          95 Mar  3 12:54 doClean.bash
16      0 drwx-----@   6 jacquesmenu  staff         192 Mar  3 10:56 musicformats-macos-distrib
17      0 drwx-----@   6 jacquesmenu  staff         192 Mar  3 10:56 musicformats-ubuntu-
    distrib
18      0 drwx-----@   6 jacquesmenu  staff         192 Mar  3 10:56 musicformats-windows-
    distrib

```

36.1.2 Security issue in recent MacOS™ versions

Mac OS™ gets more and more stringent over time regarding security. The operating system part in charge of this is named Gatekeeper.

When downloading the MusicFormats distributions from the repository on versions up to 10 (High Sierra), the executables in `bin` are usable alright.

From version 11 (Catalina) on, though, the executables you get are not executable actually, because their developer is unknown to the operating system, and actions have to be taken for them to be usable.

The trouble is that these executables are in *quarantine* by default. To make them usable, they have to quit quarantine and explicitly be made executable.

This is done this way using `chmod` and `xattr` in `scripts/MakeMusicFormatsDistributions.bash`:

```

1 # make the executables actually executable
2 chmod +x bin/*
3 xattr -d com.apple.quarantine bin/*

```


From then on, the MusicFormats executables can be used seamlessly on the given machine.

Having to perform the preceding task for each executable is the price to pay for security. And it has to be performed again when installing new versions...

The above can be done in the GUI file by file too. Right after you got the message above:


- open *System Preferences*, choose the *Security & Privacy* tab, and there click on the *General* button;

- click on the lock at the bottom left of the dialog to make changes:



- click on the *Allow Anyway* button.

Re-execute the executable from the command line. This pops-up a dialog to confirm you actually want to use this software:



Click on the *Open* button to register the executable in Gatekeeper and go ahead.

Chapter 37

MusicFormats branches and versions

The MusicFormats repository contains:

- a master branch, that contains the current evolution of the code base, examples and documentation;
- vX.Y.Z branches, created from the master branch where it is in a useful state. An example is v0.9.63.

When a `git push` is performed, the `musicformats-*-distrib` archives are created, but they cannot be added to the MusicFormats repository by GitHub on the fly.

Thus, in order to create a new version of a satisfactory state of the local development repository, one should:

1. check that the version number and date are fine in `MusicFormatsVersionNumber.txt` and `MusicFormatsVersionDate.txt`:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev > cat MusicFormatsVersionNumber.txt
2 0.9.63jacquesmenu@macmini: ~/musicformats-git-dev > cat MusicFormatsVersionDate.txt
3 June 9, 2022
```

Note that file `MusicFormatsVersionNumber.txt` should not end with an end of line, since that would disturb the creation of the PDF documentation files with `LATEX`;

These informations can be displayed with `scripts/ShowMusicFormatsVersion.bash`:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev > scripts/ShowMusicFormatsVersion.bash
2 Version number:
3 0.9.63Version date:
4 June 9, 2022
```

2. (re-)create the up-to-date documentation with:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev > scripts/CreateDocumentationPDFs.bash
```

3. add all new and/or modified files to the local repository. The `addAll` function is defined for this:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev > type addAll
2 addAll is a function
3 addAll ()
4 {
5     git add -f ${MUSIC_FORMATS_DEV}/MusicFormatsVersionNumber.txt;
6     git add -f ${MUSIC_FORMATS_DEV}/MusicFormatsVersionDate.txt;
7     git add -f ${MUSIC_FORMATS_DEV}/src/MusicFormatsVersionNumber.h;
8     git add -f ${MUSIC_FORMATS_DEV}/src/MusicFormatsVersionDate.h;
9     addSrc;
10    addBuild;
11    addScripts;
```

```

12     addDistrib;
13     addDoc;
14     addFXML;
15     addFmfs1
16 }

```

4. commit a first time to the local repository clone with a 'Pre' version number:

```
1 git commit -m "Pre v0.9.63" -a
```

5. push this to the MusicFormats repo with:

```
1 git push
```

6. the actions in the MusicFormats repository perform a build on Linux, Windows™ and Mac OS™. Check that they were executed successfully at <https://github.com/jacques-menu/musicformats/actions>:

The screenshot displays the GitHub Actions interface for the `musicformats` repository. The 'All workflows' section is active, showing a list of workflow runs. The table below summarizes the visible runs:

Workflow Run	Event	Status	Branch	Actor	Duration
Pre v0.9.63 Windows #40: Commit b4b09f8 pushed by jacques-menu	push	Success	master	jacques-menu	1h 0m 14s
Pre v0.9.63 Ubuntu #40: Commit b4b09f8 pushed by jacques-menu	push	Success	master	jacques-menu	34m 14s
Pre v0.9.63 MacOS #40: Commit b4b09f8 pushed by jacques-menu	push	Success	master	jacques-menu	16m 49s

7. when that is the case, download each of the three resulting `musicformats-*-distrib` archives locally in turn:

jacques-menu / musicformats Public

Notifications Fork 0 Star 0

<> Code Issues Pull requests Actions Projects Wiki Security Insights

✓ Pre v0.9.63 Ubuntu #40 Sign in to view logs

Summary

Jobs

✓ build

Triggered via push 2 hours ago

jacques-menu pushed -> b4b09f8 master

Status **Success** Total duration **34m 14s** Artifacts **1**

ubuntu-check.yml
on: push

✓ build 34m 3s

Artifacts
Produced during runtime

Name	Size
musicformats-ubuntu-distrib	83.7 MB

On this authors's machine, they go to `${HOME}/Downloads`:

```

1 jacquesmenu@macmini: ~/Downloads > ls -sal musicformats-*-distrib
2 musicformats-macos-distrib:
3 total 8
4 0 drwx-----@ 5 jacquesmenu staff 160 Jun 9 11:44 .
5 0 drwx-----+ 28 jacquesmenu staff 896 Jun 9 11:44 ..
6 8 -rw-r--r--@ 1 jacquesmenu staff 6 Jun 9 07:40 MusicFormatsVersionNumber.txt
7 0 drwxr-xr-x@ 3 jacquesmenu staff 96 Jun 9 11:44 build
8 0 drwxr-xr-x@ 4 jacquesmenu staff 128 Jun 9 11:44 documentation
9
10 musicformats-ubuntu-distrib:
11 total 8
12 0 drwx-----@ 5 jacquesmenu staff 160 Jun 9 11:44 .
13 0 drwx-----+ 28 jacquesmenu staff 896 Jun 9 11:44 ..
14 8 -rw-r--r--@ 1 jacquesmenu staff 6 Jun 9 07:57 MusicFormatsVersionNumber.txt
15 0 drwxr-xr-x@ 4 jacquesmenu staff 128 Jun 9 11:44 build
16 0 drwxr-xr-x@ 4 jacquesmenu staff 128 Jun 9 11:44 documentation
17
18 musicformats-windows-distrib:
19 total 8
20 0 drwx-----@ 5 jacquesmenu staff 160 Jun 9 11:43 .
21 0 drwx-----+ 28 jacquesmenu staff 896 Jun 9 11:44 ..
22 8 -rw-r--r--@ 1 jacquesmenu staff 6 Jun 9 08:14 MusicFormatsVersionNumber.txt
23 0 drwxr-xr-x@ 4 jacquesmenu staff 128 Jun 9 11:43 build
24 0 drwxr-xr-x@ 4 jacquesmenu staff 128 Jun 9 11:43 documentation

```

8. create the distributions in the local MusicFormats repository clone:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev > scripts/MakeMusicFormatsDistributions.
  bash
2 ... ..
3 -----

```

```

4 ==> final distrib contents:
5 -----
6
7 4368 -rw-r--r-- 1 jacquesmenu staff 2234811 Jun 9 11:47 /Users/jacquesmenu/
  musicformats-git-dev/distrib/MusicFormatsForWindows.zip
8 35312 -rw-r--r-- 1 jacquesmenu staff 18076799 Jun 9 11:47 /Users/jacquesmenu/
  musicformats-git-dev/distrib/MusicFormatsForUbuntu.zip
9 127824 -rw-r--r-- 1 jacquesmenu staff 65442854 Jun 9 11:47 /Users/jacquesmenu/
  musicformats-git-dev/distrib/MusicFormatsForMacOS.zip
10 1712 -rw-r--r--@ 1 jacquesmenu staff 872863 Jun 9 07:40 /Users/jacquesmenu/
  musicformats-git-dev/distrib/IntroductionToMusicXML.pdf
11 5328 -rw-r--r--@ 1 jacquesmenu staff 2724130 Jun 9 07:40 /Users/jacquesmenu/
  musicformats-git-dev/distrib/MusicFormatsUserGuide.pdf
12 8 -rw-r--r--@ 1 jacquesmenu staff 6 Jun 9 07:40 /Users/jacquesmenu/
  musicformats-git-dev/distrib/MusicFormatsVersionNumber.txt
13
14 /Users/jacquesmenu/musicformats-git-dev/distrib/MusicFormatsForWindows:
15 total 8
16 0 drwxr-xr-x 14 jacquesmenu staff 448 Jun 9 11:47 ..
17 0 drwxr-xr-x 5 jacquesmenu staff 160 Jun 9 11:47 .
18 0 drwxr-xr-x@ 4 jacquesmenu staff 128 Jun 9 11:43 lib
19 0 drwxr-xr-x@ 26 jacquesmenu staff 832 Jun 9 11:43 bin
20 8 -rw-r--r--@ 1 jacquesmenu staff 6 Jun 9 08:14 MusicFormatsVersionNumber.txt
21
22 /Users/jacquesmenu/musicformats-git-dev/distrib/MusicFormatsForUbuntu:
23 total 8
24 0 drwxr-xr-x 14 jacquesmenu staff 448 Jun 9 11:47 ..
25 0 drwxr-xr-x 5 jacquesmenu staff 160 Jun 9 11:47 .
26 0 drwxr-xr-x@ 4 jacquesmenu staff 128 Jun 9 11:44 lib
27 0 drwxr-xr-x@ 26 jacquesmenu staff 832 Jun 9 11:44 bin
28 8 -rw-r--r--@ 1 jacquesmenu staff 6 Jun 9 07:57 MusicFormatsVersionNumber.txt
29
30 /Users/jacquesmenu/musicformats-git-dev/distrib/MusicFormatsForMacOS:
31 total 8
32 0 drwxr-xr-x 14 jacquesmenu staff 448 Jun 9 11:47 ..
33 0 drwxr-xr-x 4 jacquesmenu staff 128 Jun 9 11:47 .
34 0 drwxr-xr-x@ 26 jacquesmenu staff 832 Jun 9 07:40 bin
35 8 -rw-r--r--@ 1 jacquesmenu staff 6 Jun 9 07:40 MusicFormatsVersionNumber.txt

```

Now, the local master branch contains the distribution files of itself:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/distrib > ls -al
2 total 174552
3 drwxr-xr-x 14 jacquesmenu staff 448 Jun 9 11:47 .
4 drwxr-xr-x 29 jacquesmenu staff 928 Jun 9 09:13 ..
5 -rw-r--r--@ 1 jacquesmenu staff 872863 Jun 9 07:40 IntroductionToMusicXML.pdf
6 drwxr-xr-x 4 jacquesmenu staff 128 Jun 9 11:47 MusicFormatsForMacOS
7 -rw-r--r-- 1 jacquesmenu staff 65442854 Jun 9 11:47 MusicFormatsForMacOS.zip
8 drwxr-xr-x 5 jacquesmenu staff 160 Jun 9 11:47 MusicFormatsForUbuntu
9 -rw-r--r-- 1 jacquesmenu staff 18076799 Jun 9 11:47 MusicFormatsForUbuntu.zip
10 drwxr-xr-x 5 jacquesmenu staff 160 Jun 9 11:47 MusicFormatsForWindows
11 -rw-r--r-- 1 jacquesmenu staff 2234811 Jun 9 11:47 MusicFormatsForWindows.zip
12 -rw-r--r--@ 1 jacquesmenu staff 2724130 Jun 9 07:40 MusicFormatsUserGuide.pdf
13 -rw-r--r--@ 1 jacquesmenu staff 6 Jun 9 07:40 MusicFormatsVersionNumber.
  txt
14 drwx-----@ 5 jacquesmenu staff 160 Jun 9 11:44 musicformats-macos-distrib
15 drwx-----@ 5 jacquesmenu staff 160 Jun 9 11:44 musicformats-ubuntu-distrib
16 drwx-----@ 5 jacquesmenu staff 160 Jun 9 11:43 musicformats-windows-distrib

```

9. *commit and push again* with the new version name, no 'Pre' this time, in the `-m "... .."` message, such as:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev > git commit -m "v0.9.63" -a
2
3 jacquesmenu@macmini: ~/musicformats-git-dev > git push

```

10. create the new version branch locally and remotely:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev > git push --set-upstream origin v0.9.63
2 Total 0 (delta 0), reused 0 (delta 0), pack-reused 0
3 remote:
4 remote: Create a pull request for 'v0.9.63' on GitHub by visiting:
5 remote:     https://github.com/jacques-menu/musicformats/pull/new/v0.9.63
6 remote:
7 To https://github.com/jacques-menu/musicformats.git
8 * [new branch]      v0.9.63 -> v0.9.63
9 branch 'v0.9.63' set up to track 'origin/v0.9.63'.
10
11 jacquesmenu@macmini: ~/musicformats-git-dev > git branch -r
12 origin/HEAD -> origin/master
13 origin/gh-pages
14 origin/master
15 origin/v0.9.60
16 origin/v0.9.61
17 origin/v0.9.62
18 origin/v0.9.63
19
20 jacquesmenu@macmini: ~/musicformats-git-dev > git branch
21 * master
22   v0.9.63

```

11. create a new version number and date, for example:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev > scripts/SetMusicFormatsVersionNumber.
   bash 0.9.64
2 -bash: scripts/SetMusicFormatsVersionNumber.: No such file or directory
3 jacquesmenu@macmini: ~/musicformats-git-dev > scripts/SetMusicFormatsVersionNumber.
   bash 0.9.64
4 ==> PWD is:
5 /Users/jacquesmenu/musicformats-git-dev
6
7 ==> Writing MusicFormats version number 0.9.64 to MusicFormatsVersionNumber.txt
8
9 8 -rw-r--r--  1 jacquesmenu  staff   6 Jun  9 12:14:57 2022 MusicFormatsVersionNumber.
   txt
10 0.9.64
11 ==> PWD is:
12 /Users/jacquesmenu/musicformats-git-dev/src
13
14 ==> Writing MusicFormats version number 0.9.64 to MusicFormatsVersionNumber.h
15
16 8 -rw-r--r--  1 jacquesmenu  staff  45 Jun  9 12:14:57 2022 MusicFormatsVersionNumber
   .h
17 #define MUSICFORMATS_VERSION_NUMBER "0.9.64"

```

```

1 jacquesmenu@macmini: ~/musicformats-git-dev > scripts/SetMusicFormatsVersionDate.bash
   "June 9, 2022"
2 ==> PWD is:
3 /Users/jacquesmenu/musicformats-git-dev
4
5 ==> Writing MusicFormats version date June 9, 2022 to MusicFormatsVersionDate.txt
6
7 8 -rw-r--r--  1 jacquesmenu  staff  13 Jun  9 12:15:52 2022 MusicFormatsVersionDate.
   txt
8 June 9, 2022
9
10 ==> PWD is:
11 /Users/jacquesmenu/musicformats-git-dev/src
12
13 ==> Writing MusicFormats version date June 9, 2022 to MusicFormatsVersionDate.h
14
15 8 -rw-r--r--  1 jacquesmenu  staff  49 Jun  9 12:15:52 2022 MusicFormatsVersionDate.h
16 #define MUSICFORMATS_VERSION_DATE "June 9, 2022"

```

Check the result with:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev > scripts/ShowMusicFormatsVersion.bash
2 Version number:
3 0.9.64Version date:
4 June 9, 2022
```

Part XII

Selected topics

Chapter 38

Initializations

Some initialization activities in MusicFormats use the OAH facility. OAH should thus be initialized first.

38.1 Options and help initializations

There is no initialization of the OAH architecture as such, but there are `create*OahGroup ()` functions to create the various OAH groups.

For example, global variable `gGlobalServiceRunData` is supplied by `src/mflibrary/mfServiceRunData.h/.cpp`:

```
1 EXP extern S_generalOahGroup gGlobalServiceRunData;
2
3 // -----
4 EXP S_generalOahGroup createGlobalGeneralOahGroup ();

1 S_generalOahGroup createGlobalGeneralOahGroup ()
2 {
3 #ifdef TRACING_IS_ENABLED
4     if (gGlobalOahEarlyOptions.getEarlyTracingOah ()) {
5         gLogStream <<
6             "Creating global general OAH group" <<
7             endl;
8     }
9 #endif
10
11 // protect library against multiple initializations
12 if (! gGlobalServiceRunData) {
13     // create the global general options group
14     gGlobalServiceRunData =
15         generalOahGroup::create ();
16     assert (gGlobalServiceRunData != 0);
17 }
18
19 // return the global OAH group
20 return gGlobalServiceRunData;
21 }
```

38.2 Representations initializations

There are `initialize*` () functions such as `initializeLPSR` () and `initializeBSR` (). They essentially build global data structures, such as the tables of supported languages and their correspondance with an internal enumeration type both ways.

For example, `initializeMSR` () is defined in `src/formats/msr/msr.h/.cpp`:

```

1 void EXP initializeMSR ();

1 static S_mfcVersions pMsrRepresentationComponent;
2
3 static void initializeMsrRepresentationComponent ()
4 {
5     // create the component
6     pMsrRepresentationComponent =
7         mfcVersions::create ("MSR");
8
9     // populate it
10    pMsrRepresentationComponent->
11        appendVersionDescrToComponent (
12            mfcVersionDescr::create (
13                mfcVersionDescr::create (
14                    mfcVersionNumber::createFromString ("0.9.50"),
15                    "October 6, 2021",
16                    list<string> {
17                        "Start of sequential versions numbering"
18                    }
19                ));
20 }
21
22 void initializeMSR ()
23 {
24     // protect library against multiple initializations
25     static Bool pPrivateThisMethodHasBeenRun (false);
26
27     if (! pPrivateThisMethodHasBeenRun) {
28         // initialize the history
29         initializeMsrRepresentationComponent ();
30
31         // initialize
32         initializeMsrBasicTypes ();
33
34         pPrivateThisMethodHasBeenRun = true;
35     }
36 }

```

38.2.1 MSR initialization

`src/formats/msr/msrBasicTypes.h/.cpp` defines function `initializeMSRBasicTypes` () for this initialization:

```

1 void initializeMsrBasicTypes ()
2 {
3     // protect library against multiple initializations
4     static Bool pPrivateThisMethodHasBeenRun (false);
5
6     if (! pPrivateThisMethodHasBeenRun) {
7 #ifdef TRACING_IS_ENABLED
8         if (gGlobalOahEarlyOptions.getEarlyTracingOah () && ! gGlobalOahEarlyOptions.
9             getEarlyQuietOption ()) {
10             gLogStream <<

```

```

10     "Initializing MSR basic types handling" <<
11     endl;
12 }
13 #endif
14
15 // languages handling
16 // -----
17
18 initializeQuarterTonesPitchesLanguageKinds ();
19
20 // clefs handling
21 // -----
22
23 initializeClefKinds ();
24
25 // harmonies handling
26 // -----
27
28 initializeHarmonyKinds ();
29
30 // harmony structures handling
31 // -----
32
33 initializeHarmonyStructuresMap ();
34
35 // MSR lengths handling
36 // -----
37
38 initializeMsrLengthUnitKindsMap ();
39
40 // MSR margins types handling
41 // -----
42
43 initializeMsrMarginTypeKindsMap ();
44
45 pPrivateThisMethodHasBeenRun = true;
46 }
47 }

```

38.2.2 LPSR initialization

38.2.3 BSR initialization

38.3 Passes initializations

38.4 Converters initializations

The converters create only the global OAH groups they need. Since the order of initializations is critical, initialization of the formats is done when the latter's insider handler is created.

This is how class `xml2lyInsiderHandler` initializes the MSR and LSPR formats in method `xml2lyInsiderHandler::createTheXml2lyOptionGroups ()` in [src/converters/musicxml2lilypond/musicxml2lilypondInsiderHandler.cpp](#):

```

1 void xml2lyInsiderHandler::createTheXml2lyOptionGroups (
2     string serviceName)
3 {
4     // ... ..
5
6     // initialize options handling, phase 1

```



```

7 // -----
8
9 // create the OAH OAH group first
10 appendGroupToHandler (
11     createGlobalOahOahGroup (
12         serviceName));
13
14 // create the WAE OAH group
15 appendGroupToHandler (
16     createGlobalWaeOahGroup ());
17
18 #ifdef TRACING_IS_ENABLED
19 // create the tracing OAH group
20 appendGroupToHandler (
21     createGlobalTracingOahGroup (
22         this));
23 #endif
24
25 // create the output file OAH group
26 appendGroupToHandler (
27     createGlobalOutputFileOahGroup ());
28
29 // initialize the library
30 // -----
31
32 initializeMSR ();
33 initializeLPSR ();
34
35 // initialize options handling, phase 2
36 // -----
37
38 // create the MXSR OAH group
39 appendGroupToHandler (
40     createGlobalMxsrOahGroup ());
41
42 // create the mxsr2msr OAH group
43 appendGroupToHandler (
44     createGlobalMxsr2msrOahGroup (
45         this));
46
47 // create the MSR OAH group
48 appendGroupToHandler (
49     createGlobalMsrOahGroup ());
50
51 // create the msr2msr OAH group
52 appendGroupToHandler (
53     createGlobalMsr2msrOahGroup ());
54
55 // create the msr2lpsr OAH group
56 appendGroupToHandler (
57     createGlobalMsr2lpsrOahGroup ());
58
59 // create the LPSR OAH group
60 appendGroupToHandler (
61     createGlobalLpsrOahGroup ());
62
63 // create the LilyPond generation OAH group
64 appendGroupToHandler (
65     createGlobalLpsr2lilypondOahGroup ());
66
67 #ifdef EXTRA_OAH_IS_ENABLED
68 // create the extra OAH group
69 appendGroupToHandler (
70     createGlobalHarmoniesExtraOahGroup ());
71 #endif
72
73 // create the global xml2ly OAH group only now,

```

```
74 // after the groups whose options it may use
75 // have been created
76 appendGroupToHandler (
77     createGlobalXml2lyInsiderOahGroup ());
78
79 // ... ..
80 }
```

Chapter 39

The OAH atoms collection

These handy general-purpose OAH atoms are used in MusicFormats itself. They are defined in [src/oah/oahAtomsCollection.h](#).

```
1 jacquesmenu@macmini: ~/musicformats-git-dev/src/oah > grep class oahAtomsCollection.h
2 class EXP oahAtomAlias : public oahAtom
3 class EXP oahMacroAtom : public oahAtom
4 class EXP oahOptionsUsageAtom : public oahPureHelpAtomWithoutAValue
5 class EXP oahHelpAtom : public oahPureHelpAtomWithoutAValue
6 class EXP oahHelpSummaryAtom : public oahPureHelpAtomWithoutAValue
7 class EXP oahAboutAtom : public oahPureHelpAtomWithoutAValue
8 class EXP oahVersionAtom : public oahPureHelpAtomWithoutAValue
9 class EXP oahContactAtom : public oahPureHelpAtomWithoutAValue
10 class EXP oahBooleanAtom : public oahAtom
11 class EXP oahTwoBooleansAtom : public oahBooleanAtom
12 class EXP oahThreeBooleansAtom : public oahBooleanAtom
13 class EXP oahCombinedBooleansAtom : public oahAtom
14 class EXP oahCommonPrefixBooleansAtom : public oahAtom
15 class EXP oahIntegerAtom : public oahAtomStoringAValue
16 class EXP oahTwoIntegersAtom : public oahIntegerAtom
17 class EXP oahFloatAtom : public oahAtomStoringAValue
18 class EXP oahStringAtom : public oahAtomStoringAValue
19 class EXP oahFactorizedStringAtom : public oahAtom
20 class EXP oahStringWithDefaultValueAtom : public oahStringAtom
21 class EXP oahRationalAtom : public oahAtomStoringAValue
22 class EXP oahNaturalNumbersSetElementAtom : public oahAtomStoringAValue
23 class EXP oahRGBColorAtom : public oahAtomStoringAValue
24 class EXP oahIntSetElementAtom : public oahAtomStoringAValue
25 class EXP oahStringSetElementAtom : public oahAtomStoringAValue
26 class EXP oahStringToIntMapElementAtom : public oahAtomStoringAValue
27 class EXP oahStringAndIntegerAtom : public oahAtomStoringAValue
28 class EXP oahStringAndTwoIntegersAtom : public oahAtomStoringAValue
29 class EXP oahLengthUnitKindAtom : public oahAtomStoringAValue
30 class EXP oahLengthAtom : public oahAtomStoringAValue
31 class EXP oahMidiTempoAtom : public oahAtomStoringAValue
32 class EXP oahOptionNameHelpAtom : public oahStringWithDefaultValueAtom
33 class EXP oahQueryOptionNameAtom : public oahPureHelpAtomExpectingAValue
34 class EXP oahFindStringAtom : public oahPureHelpAtomExpectingAValue
```

39.1 OAH macro atoms

A OAH macro atom is a combination, a list of several options under a single name. The `oahMacroAtom` class is defined in [src/oah/oahAtomsCollection.h/.cpp](#):

```

1 class EXP oahMacroAtom : public oahAtom
2 {
3     /*
4      a list of atoms
5     */
6
7     // ... ..
8
9     public:
10
11     // public services
12     // -----
13
14     void                appendAtomToMacro (S_oahAtom atom);
15
16     void                applyElement (ostream& os) override;
17
18
19     private:
20
21     // private fields
22     // -----
23
24
25     list<S_oahAtom>      fMacroAtomsList;
26 };

```

Populating field `oahMacroAtom::fMacroAtomsList` is straightforward:

```

1 void oahMacroAtom::appendAtomToMacro (S_oahAtom atom)
2 {
3     // sanity check
4     mfAssert (
5         __FILE__, __LINE__,
6         atom != nullptr,
7         "atom is null");
8
9     fMacroAtomsList.push_back (atom);
10 }

```

Applying the macro atom is done in method `oahMacroAtom::applyElement ()`:

```

1 void oahMacroAtom::applyElement (ostream& os)
2 {
3     #ifdef TRACING_IS_ENABLED
4         if (gGlobalOahEarlyOptions.getEarlyTracingOah ()) {
5             gLogStream <<
6                 "=> option ' ' << fetchNames () << ' ' is a oahMacroAtom" <<
7                 endl;
8         }
9     #endif
10
11     for (
12         list<S_oahAtom>::const_iterator i =
13             fMacroAtomsList.begin ();
14         i != fMacroAtomsList.end ();
15         ++i
16     ) {
17         S_oahAtom atom = (*i);
18
19         if (
20             // oahAtomStoringAValue?
21             S_oahAtomStoringAValue
22             atomWithVariable =
23                 dynamic_cast<oahAtomStoringAValue*>(&(*atom))

```

```

24     } {
25     //      atomWithVariable-> JMI ???
26     //      applyAtomWithValue (theString, os);
27     }
28     else {
29     // valueless atom
30     atom->
31     applyElement (os);
32     }
33 } // for
34 }

```

39.2 A OAH macro atom example

xml2brl has the `-auto-utf8`, `-au8d` option:

```

1 jacquesmenu@macmini > xml2brl -query auto-utf8d
2 --- Help for atom "auto-utf8d" in subgroup "Files"
3   -auto-utf8d, -au8d
4   Combines -auto-output-file-name, -utf8d and -use-encoding-in-file-name

```

This macro options is defined in `src/formatsgeneration/brailleGeneration/brailleGenerationOah.cpp` the following way:

```

1 void brailleGenerationOahGroup::initializeMacroOptions ()
2 {
3     S_oahSubGroup
4     subGroup =
5     oahSubGroup::create (
6     "Macros",
7     "help-braille-generation-macros", "hbgm",
8     R"()",
9     oahElementVisibilityKind::kElementVisibilityWhole,
10    this);
11
12    appendSubGroupToGroup (subGroup);
13
14    // create the auto utfd8 macro
15
16    S_oahMacroAtom
17    autoUTFd8MacroAtom =
18    oahMacroAtom::create (
19    "auto-utf8d", "au8d",
20    "Combines -auto-output-file-name, -utf8d and -use-encoding-in-file-name");
21
22    subGroup->
23    appendAtomToSubGroup (
24    autoUTFd8MacroAtom);
25
26    // populate it
27    autoUTFd8MacroAtom->
28    appendAtomToMacro (
29    gGlobalOutputFileOahGroup->getAutoOutputFileNameAtom ());
30
31    fBrailleOutputKindAtom->
32    applyAtomWithValue (
33    "utf8d",
34    gLogStream);
35    autoUTFd8MacroAtom->
36    appendAtomToMacro (
37    fBrailleOutputKindAtom);
38
39    autoUTFd8MacroAtom->

```

```

40     appendAtomToMacro (
41         fUseEncodingInFileNameAtom);
42 }

```

39.3 LilyPond octave entry

Pass `lpsr2lilypond` has three options to choose this, all controlling one and the same variable:

```

1 jacquesmenu@macmini > xml2ly -query absolute
2 --- Help for atom "absolute" in subgroup "Notes"
3     -abs, -absolute
4         Use absolute octave entry in the generated LilyPond code.

```

```

1 jacquesmenu@macmini > xml2ly -query relative
2 --- Help for atom "relative" in subgroup "Notes"
3     -rel, -relative
4         Use relative octave entry reference PITCH_AND_OCTAVE in the generated LilyPond
5         code.
6         PITCH_AND_OCTAVE is made of a diatonic pitch and
7         an optional sequence of commas or single quotes.
8         It should be placed between double quotes if it contains single quotes, such as:
9         -rel "c'".
10        The default is to use LilyPond's implicit reference 'f'.

```

```

1 jacquesmenu@macmini > xml2ly -query fixed
2 --- Help for atom "fixed" in subgroup "Notes"
3     -fixed
4         Use fixed octave entry reference PITCH_AND_OCTAVE in the generated LilyPond code
5         .
6         PITCH_AND_OCTAVE is made of a diatonic pitch and
7         an optional sequence of commas or single quotes.
8         It should be placed between double quotes if it contains single quotes, such as:
9         -fixed "c'"

```

This is done in `src/formatsgeneration/lilypondGeneration/lpsr2lilypondOah.h/.cpp` using a single instance of class `msrOctaveEntryVariable`:

```

1 class EXP msrOctaveEntryVariable : public smartable
2 {
3     // ... ..
4
5     private:
6
7         // private fields
8         // -----
9
10        string          fVariableName;
11        msrOctaveEntryKind fOctaveEntryKind;
12
13        Bool            fSetByAnOption;
14 };

```

The three classes:

- `lilypondAbsoluteOctaveEntryAtom`
- `lilypondRelativeOctaveEntryAtom`
- `lilypondFixedOctaveEntryAtom`

all contain an alias for an class `msrOctaveEntryVariable` variable:

```
1 // private fields
2 // -----
3
4 msrOctaveEntryVariable&
5     fOctaveEntryKindVariable;
```

The `fOctaveEntryVariable` field of class `lpsr2lilypondOahGroup` shared by all three options atoms is:

```
1 // notes
2 // -----
3
4 msrOctaveEntryVariable
5     fOctaveEntryVariable;
```

Chapter 40

Measures handling

Measures are presented at section [19.30](#) [Measures], page [187](#).

40.1 Voices contents

Class `msrVoice` contain a list of the first elements and a last segment:

```
1  list<S_msrVoiceElement>
2      fVoiceInitialElementsList;
3
4  // fVoiceLastSegment contains the music
5  // not yet stored in fVoiceInitialElementsList,
6  // it is thus logically the end of the latter,
7  // and is created implicitly for every voice.
8  // It is needed 'outside' of the 'list<S_msrElement>'
9  // because it is not a mere S_msrElement, but a S_msrSegment
10 S_msrSegment      fVoiceLastSegment;
```

40.2 Voice elements

The class `msrVoiceElement` subclasses instances in `fVoiceInitialElementsList` can be of types:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev/src > grep 'public msrVoiceElement' formats/
   msr/*.h
2 formats/msr/msrBeatRepeats.h:class EXP msrBeatRepeat : public msrVoiceElement
3 formats/msr/msrMeasureRepeats.h:class EXP msrMeasureRepeat : public msrVoiceElement
4 formats/msr/msrRepeats.h:class EXP msrRepeat : public msrVoiceElement
5 formats/msr/msrMultipleFullBarRests.h:class EXP msrMultipleFullBarRests : public
   msrVoiceElement
6 formats/msr/msrSegments.h:class EXP msrSegment : public msrVoiceElement
```

Class `msrSegment` contains a list of measures:

```
1  // the measures in the segment contain the mmusic
2  list<S_msrMeasure>      fSegmentElementsList;
```

Class `msrMeasure` contains a list of measure elements:

```
1  // elements
2
3  list<S_msrMeasureElement>
4      fMeasureElementsList;
```


40.3 Measure elements

The class `msrMeasureElements` subclasses instances in can be of types:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src/formats/msr > grep 'public
  msrMeasureElement' *.h
2 msrBarChecks.h:class EXP msrBarCheck : public msrMeasureElement
3 msrBarLines.h:class EXP msrBarLine : public msrMeasureElement
4 msrBarNumberChecks.h:class EXP msrBarNumberCheck : public msrMeasureElement
5 msrBreaks.h:class EXP msrLineBreak : public msrMeasureElement
6 msrBreaks.h:class EXP msrPageBreak : public msrMeasureElement
7 msrClefs.h:class EXP msrClef : public msrMeasureElement
8 msrCodas.h:class EXP msrCoda : public msrMeasureElement
9 msrDoubleTremolos.h:class EXP msrDoubleTremolo : public msrMeasureElement
10 msrEyeGlasses.h:class EXP msrEyeGlasses : public msrMeasureElement
11 msrFiguredBassElements.h:class EXP msrFiguredBassElement : public msrMeasureElement
12 msrHarmonies.h:class EXP msrHarmony : public msrMeasureElement
13 msrHiddenMeasureAndBarLines.h:class EXP msrHiddenMeasureAndBarLine : public
  msrMeasureElement
14 msrInstruments.h:class EXP msrScordatura : public msrMeasureElement
15 msrInstruments.h:class EXP msrAccordionRegistration : public msrMeasureElement
16 msrInstruments.h:class EXP msrHarpPedalsTuning : public msrMeasureElement
17 msrInstruments.h:class EXP msrPedal : public msrMeasureElement
18 msrInstruments.h:class EXP msrDamp : public msrMeasureElement
19 msrInstruments.h:class EXP msrDampAll : public msrMeasureElement
20 msrKeys.h:class EXP msrKey : public msrMeasureElement
21 msrLyrics.h:class EXP msrSyllable : public msrMeasureElement
22 msrMusicXMLSpecifics.h:class EXP msrPrintLayout : public msrMeasureElement
23 msrRehearsalMarks.h:class EXP msrRehearsalMark : public msrMeasureElement
24 msrSegnos.h:class EXP msrSegno : public msrMeasureElement
25 msrSegnos.h:class EXP msrDalSegno : public msrMeasureElement
26 msrStavesDetails.h:class EXP msrStaffDetails : public msrMeasureElement
27 msrTempos.h:class EXP msrTempo : public msrMeasureElement
28 msrTimeSignatures.h:class EXP msrTimeSignature : public msrMeasureElement
29 msrTranspositions.h:class EXP msrOctaveShift : public msrMeasureElement
30 msrTranspositions.h:class EXP msrTransposition : public msrMeasureElement
31 msrTupletElements.h:class EXP msrTupletElement : public msrMeasureElement
32 msrVoiceStaffChanges.h:class EXP msrVoiceStaffChange : public msrMeasureElement

```

40.4 Appending measure elements to a measure

Appending music elements to a measure is done by method `msrMeasure::appendElementToMeasure ()`, defined in `src/formats/msr/msrMeasures.h/.cpp`:

```

1 void msrMeasure::appendElementToMeasure (S_msrMeasureElement elem)
2 {
3     int inputLineNumber =
4         elem->getInputLineNumber ();
5
6     #ifdef TRACING_IS_ENABLED
7         if (gGlobalTracingOahGroup->getTraceMeasures ()) {
8             gLogStream <<
9                 "Appending element " <<
10                 elem->asShortString () <<
11                 " to measure " <<
12                 asShortString () <<
13                 " in voice \"" <<
14                 fetchMeasureVoiceUpLink ()->
15                 getVoiceName () <<
16                 "\", currentMeasureWholeNotesDuration = " <<
17                 fCurrentMeasureWholeNotesDuration <<
18                 ", line " << inputLineNumber <<
19                 endl;

```

```

20 }
21 #endif
22
23 // set elem's measure number
24 elem->
25     setMeasureElementMeasureNumber (
26         fMeasureElementMeasureNumber);
27
28 // set elem's position in measure
29 elem->
30     setMeasureElementPositionInMeasure (
31         fCurrentMeasureWholeNotesDuration,
32         "appendElementToMeasure()");
33
34 fMeasureElementsList.push_back (elem);
35
36 // take elem's sounding whole notes into account JMI ???
37 if (false) // JMI CAFE
38     incrementCurrentMeasureWholeNotesDuration (
39         inputLineNumber,
40         elem->
41             getMeasureElementSoundingWholeNotes ());
42 }

```

Here is how a harmony instance is appended to a measure:

```

1 void msrMeasure::appendHarmonyToMeasure (S_msrHarmony harmony)
2 {
3     int inputLineNumber =
4         harmony->getInputLineNumber ();
5
6 #ifdef TRACING_IS_ENABLED
7     if (gGlobalTracingOahGroup->getTraceHarmonies ()) {
8         gLogStream <<
9             "Appending harmony " << harmony->asString () <<
10             " to measure " <<
11             this->asShortString () <<
12             " in segment '" <<
13             fMeasureSegmentUpLink->getSegmentAbsoluteNumber () <<
14             "' in voice \"" <<
15             fMeasureSegmentUpLink->
16                 getSegmentVoiceUpLink ()->
17                     getVoiceName () <<
18             "\", currentMeasureWholeNotesDuration = " <<
19             fCurrentMeasureWholeNotesDuration <<
20             ", line " << inputLineNumber <<
21             endl;
22     }
23 #endif
24
25 // set harmony's measure number
26 harmony->
27     setMeasureElementMeasureNumber (
28         fMeasureElementMeasureNumber);
29
30 // append the harmony to the measure elements list
31 // DON'T call 'appendElementToMeasure (harmony)':
32 // that would override harmony's position in measure,
33 // which already has the correct value, thus:
34 fMeasureElementsList.push_back (harmony);
35
36 // get harmony sounding whole notes
37 rational
38     harmonySoundingWholeNotes =
39         harmony->
40             getHarmonySoundingWholeNotes ();

```

```

41
42 // account for harmony duration in measure whole notes
43 incrementCurrentMeasureWholeNotesDuration (
44     inputLineNumber,
45     harmonySoundingWholeNotes);
46
47 // this measure contains music
48 fMeasureContainsMusic = true;
49 }

```

The task is simpler when appending a harmony to a measure clone, because the clone's harmony's measure number comes from the clone's original:

```

1 void msrMeasure::appendHarmonyToMeasureClone (S_msrHarmony harmony)
2 {
3     int inputLineNumber =
4         harmony->getInputLineNumber ();
5
6 #ifdef TRACING_IS_ENABLED
7     if (gGlobalTracingOahGroup->getTraceHarmonies ()) {
8         gLogStream <<
9             "Appending harmony " << harmony->asString () <<
10             " to measure clone " <<
11             this->asShortString () <<
12             " in segment clone '" <<
13             fMeasureSegmentUpLink->getSegmentAbsoluteNumber () <<
14             "' in voice clone \"" <<
15             fMeasureSegmentUpLink->
16                 getSegmentVoiceUpLink ()->
17                 getVoiceName () <<
18             "\", currentMeasureWholeNotesDuration = " <<
19             fCurrentMeasureWholeNotesDuration <<
20             ", line " << inputLineNumber <<
21             endl;
22     }
23 #endif
24
25     ++gIndenter;
26
27     // append the harmony to the measure elements list
28     appendElementToMeasure (harmony);
29
30     // fetch harmony sounding whole notes
31     rational
32         harmonySoundingWholeNotes =
33         harmony->
34             getHarmonySoundingWholeNotes ();
35
36     // account for harmony duration in measure whole notes
37     incrementCurrentMeasureWholeNotesDuration (
38         inputLineNumber,
39         harmonySoundingWholeNotes);
40
41     // this measure contains music
42     fMeasureContainsMusic = true;
43
44     --gIndenter;
45 }

```

40.5 Appending measures to a segment

Measures are appended to a segment by method `msrSegment::appendMeasureToSegment ()` in `src/formats/msr/msrSegments.h/.cpp`:

```

1 void msrSegment::appendMeasureToSegment (S_msrMeasure measure)
2 {
3     int inputLineNumber =
4         measure->getInputLineNumber ();
5
6     string measureNumber =
7         measure->getMeasureElementMeasureNumber ();
8
9     unsigned int segmentElementsListSize =
10         fSegmentElementsList.size ();
11
12     string currentMeasureNumber =
13         segmentElementsListSize == 0
14             ? ""
15             : fSegmentElementsList.back ()->getMeasureElementMeasureNumber ();
16
17 #ifdef TRACING_IS_ENABLED
18     if (gGlobalTracingOahGroup->getTraceMeasures ()) {
19         gLogStream <<
20             "Appending measure '" << measureNumber <<
21             "' to segment " << asString ();
22
23         if (fSegmentElementsList.size () == 0)
24             gLogStream <<
25                 ", as first measure";
26         else
27             gLogStream <<
28                 ", after measure number '" << currentMeasureNumber << "'";
29
30         gLogStream <<
31             "' in voice \"" <<
32             fSegmentVoiceUpLink->getVoiceName () <<
33             "\" " <<
34             ", line " << measure->getInputLineNumber () <<
35             endl;
36     }
37 #endif
38
39     if (measureNumber == currentMeasureNumber) {
40         stringstream s;
41
42         s <<
43             "appending measure number '" << measureNumber <<
44             "' occurs twice in a row in segment " <<
45             asString () <<
46             " in voice \"" <<
47             fSegmentVoiceUpLink->getVoiceName () <<
48             "\"";
49
50         // msrInternalWarning ( // JMI
51         msrInternalError (
52             gGlobalServiceRunData->getInputSourceName (),
53             inputLineNumber,
54             __FILE__, __LINE__,
55             s.str ());
56     }
57
58     // is measure the first one this segment?
59     if (segmentElementsListSize == 0) {
60         measure->
61             setMeasureFirstInSegmentKind (
62                 msrMeasure::kMeasureFirstInSegmentKindYes);
63     }
64     else {
65         measure->
66             setMeasureFirstInSegmentKind (

```

```

67     msrMeasure::kMeasureFirstInSegmentKindNo);
68 }
69
70 // is measure the first one in the voice?
71 // this is necessary for voice clones,
72 // which don't go down the part-staff-voice-segment hierarchy
73 if (! fSegmentVoiceUpLink->getVoiceFirstMeasure ()) {
74     // yes, register it as such
75     fSegmentVoiceUpLink->
76         setVoiceFirstMeasure (measure);
77
78     measure->
79         setMeasureFirstInVoice ();
80 }
81
82 // append measure to the segment
83 fSegmentElementsList.push_back (measure);
84 }

```

Calls to method `msrSegment::appendMeasureToSegment ()` occur in:

- method `msrSegment::createAMeasureAndAppendItToSegment ()` called from:
method `msrVoice::createAMeasureAndAppendItToVoice ()`
- method `msrVoice::appendMeasureCloneToVoiceClone ()` called from:
visitor method `msr2msrTranslator::visitStart (S_msrMeasure& elt)`
- method `msrMultipleFullBarRests::appendMeasureCloneToMultipleFullBarRests ()` called from:
visitor method `msr2msrTranslator::visitStart (S_msrMeasure& elt)`
- method `msrVoice::appendMeasureCloneToVoiceClone ()` called from:
visitor method `msr2lpsrTranslator::visitStart (S_msrMeasure& elt)`
- method `msrVoice::createNewLastSegmentFromItsFirstMeasureForVoice ()` called from:
method `msrVoice::handleVoiceLevelRepeatStart ()`,
method `msrVoice::handleVoiceLevelRepeatEndingStartWithoutExplicitStart ()`,
method `msrVoice::handleVoiceLevelRepeatEndingStartWithExplicitStart ()`,
method `msrVoice::createMeasureRepeatFromItsFirstMeasures ()`,
method `msrVoice::appendPendingMeasureRepeatToVoice ()`,
method `msrVoice::appendMultipleFullBarRestsToVoice ()`

40.6 Appending measures to a voice

Method `msrVoice::appendMeasureCloneToVoiceClone ()` does the job in `src/formats/msr/msrVoices.h/.cpp`.

```

1 S_msrMeasure msrVoice::createAMeasureAndAppendItToVoice (
2     int     inputLineNumber,
3     string  measureNumber,
4     msrMeasureImplicitKind
5         measureImplicitKind)
6 {
7     fVoiceCurrentMeasureNumber = measureNumber;
8
9     #ifdef TRACING_IS_ENABLED
10     if (gGlobalTracingOahGroup->getTraceMeasures ()) {

```

```

11     gLogStream <<
12     "Creating measure '" <<
13     measureNumber <<
14     "' and appending it to voice \"" << getVoiceName () << "\" " <<
15     "', line " << inputLineNumber <<
16     endl;
17 }
18 #endif
19
20 fCallsCounter++;
21
22 if (
23 //     true
24 //     ||
25     false
26     &&
27     (
28         fCallsCounter == 2 && getVoiceName ()
29         ==
30         "Part_POne_HARMONIES_Staff_Voice_Eleven_HARMONIES"
31     )
32 ) { // POUSSE JMI
33     gLogStream <<
34     endl <<
35     "++++ createAMeasureAndAppendItToVoice() POUSSE, fCallsCounter: " << fCallsCounter
36     << " ++++" <<
37     endl;
38     this->print (gLogStream);
39     gLogStream <<
40     endl;
41 }
42 #ifdef TRACING_IS_ENABLED
43 if (gGlobalTracingOahGroup->getTraceMeasuresDetails ()) {
44     displayVoice (
45         inputLineNumber,
46         "createAMeasureAndAppendItToVoice() 1");
47 }
48 #endif
49
50 ++gIndenter;
51
52 // create the voice last segment if needed
53 if (! fVoiceLastSegment) {
54     createNewLastSegmentForVoice (
55         inputLineNumber,
56         "createAMeasureAndAppendItToVoice() 2");
57 }
58
59 // append a new measure with given number to voice last segment
60 S_msrMeasure
61 result =
62     fVoiceLastSegment->
63     createAMeasureAndAppendItToSegment (
64         inputLineNumber,
65         measureNumber,
66         measureImplicitKind);
67
68 // result is the new voice last appended measure
69 fVoiceLastAppendedMeasure = result;
70
71 #ifdef TRACING_IS_ENABLED
72 if (gGlobalTracingOahGroup->getTraceMeasuresDetails ()) {
73     displayVoice (
74         inputLineNumber,
75         "createAMeasureAndAppendItToVoice() 3");
76 }

```

```

77 #endif
78
79 --gIndenter;
80
81 return result;
82 }

```

40.7 Translating from MXSR to MSR

This is done in `src/passes/mxsr2msr/`.

Upon the first visit of `S_measure`, as class `msrMeasure` instance is created and append to the current part:

```

1 void mxsr2msrTranslator::visitStart (S_measure& elt)
2 {
3     // ... ..
4
5     // take this measure into account
6     ++fPartMeasuresCounter;
7
8     // ... ..
9
10    // implicit
11
12    /*
13     Measures with an implicit attribute set to "yes"
14     never display a measure number,
15     regardless of the measure-numbering setting.
16     *
17     The implicit attribute is set to "yes" for measures where
18     the measure number should never appear, such as pickup
19     measures and the last half of mid-measure repeats. The
20     value is "no" if not specified.
21    */
22
23    string
24        implicit =
25        elt->getAttributeValue ("implicit");
26
27    msrMeasureImplicitKind
28        measureImplicitKind =
29        msrMeasureImplicitKind::kMeasureImplicitKindNo; // default value
30
31    if (implicit == "yes") {
32        measureImplicitKind =
33        msrMeasureImplicitKind::kMeasureImplicitKindYes;
34    }
35    else if (implicit == "no") {
36        measureImplicitKind =
37        msrMeasureImplicitKind::kMeasureImplicitKindNo;
38    }
39    else {
40        if (implicit.size ()) {
41            stringstream s;
42
43            s <<
44            "implicit \"" << implicit <<
45            "\" is unknown";
46
47            musicxmlError (
48                gGlobalServiceRunData->getInputSourceName (),
49                inputLineNumber,
50                __FILE__, __LINE__,

```

```

51         s.str ());
52     }
53 }
54
55 // append a new measure to the current part
56 fCurrentPart->
57     createAMeasureAndAppendItToPart (
58         inputLineNumber,
59         fCurrentMeasureNumber,
60         measureImplicitKind);
61
62 // ... ..
63 }

```

Upon the second visit of `S_measure`, the last appended measure appended to the current part is finalized:

```

1 void mxsr2msrTranslator::visitEnd (S_measure& elt)
2 {
3     // ... ..
4
5     // finalize current measure in the part,
6     // to add skips if necessary and set measure kind
7     fCurrentPart->
8         finalizeLastAppendedMeasureInPart (
9             inputLineNumber);
10
11     // ... ..
12 }

```

40.8 Translating from MXSR to MSR

A new class `msrMeasure` instance is created in `src/passes/mxsr2msr/mxsr2msrTranslator.cpp` upon the first visit of `S_measure`:

```

1 // -----
2 void mxsr2msrTranslator::visitStart (S_measure& elt)
3 {
4     // ... ..
5
6     // append a new measure to the current part
7     fCurrentPart->
8         createAMeasureAndAppendItToPart (
9             inputLineNumber,
10            fCurrentMeasureNumber,
11            measureImplicitKind);
12
13     // ... ..
14 }

```

This can lead to several class `msrMeasure` instances being created, depending on the MusicXML data. Hence there is no notion of a current measure in this translator.

Method `msrPart::createAMeasureAndAppendItToPart ()` creates and appends a measure to the part harmonies and figured bass staves if relevant, and then cascade s to the part staves:

```

1 void msrPart::createAMeasureAndAppendItToPart (
2     int    inputLineNumber,
3     string measureNumber,
4     msrMeasureImplicitKind
5     measureImplicitKind)
6 {
7     // ... ..

```



```
8
9  // set part current measure number
10 fPartCurrentMeasureNumber = measureNumber;
11
12 // create and append measure in all the staves
13 for (S_msrStaff staff : fPartAllStavesList) {
14     staff->
15         createAMeasureAndAppendItToStaff (
16             inputLineNumber,
17             measureNumber,
18             measureImplicitKind);
19 } // for
20
21 // ... ..
```

40.9 Translating from MSR to MSR

This is done in [src/passes/msr2msr/](#).

40.10 Translating from MSR to LPSR

This is done in [src/passes/msr2lpsr/](#).

40.11 Translating from LPSR to LilyPond

This is done in [src/passes/lpsr2lilypond/](#).

Chapter 41

Positions in measures

Positions in measures is stored in field `msrMeasureElement::fMeasureElementPositionInMeasure` in class `msrMeasureElement`, defined in `src/formats/msr/msrMeasureElement.h/.cpp`:

```
1 class EXP msrMeasureElement : public msrElement
2 {
3     // ... ..
4
5     protected:
6
7         // protected fields
8         // -----
9
10        /*
11         The measure uplink is declared in the sub-classes,
12         to allow for separate *.h files, C++ constraint
13        */
14
15        rational          fMeasureElementSoundingWholeNotes;
16
17        string            fMeasureElementMeasureNumber;
18
19        rational          fMeasureElementPositionInMeasure;
20        rational          fMeasureElementPositionInVoice;
21
22        msrMoment         fMeasureElementMomentInMeasure;
23        msrMoment         fMeasureElementMomentInVoice;
24 };
```

41.1 Determining positions in measures

Chapter 42

Finalizations

42.1 Clones vs non-clones finalization

Finalizing clones may be simpler than finalizing a just-created and populated non-clone, due to the information available in the clone's original.

For example, method `msrMeasure::finalizeMeasure ()` delegates part of the job to methods handling the three kinds of voices, respectively:

```
1 void msrMeasure::finalizeMeasure (
2     int                inputLineNumber,
3     msrMeasureRepeatContextKind measureRepeatContextKind,
4     string              context)
5 {
6     // ... ..
7
8     S_msrVoice
9     voice =
10         fMeasureSegmentUpLink->
11         getSegmentVoiceUpLink ();
12
13     // ... ..
14
15     // delegate to voice kind specific methods
16     switch (voice->getVoiceKind ()) {
17     case msrVoiceKind::kVoiceKindRegular:
18         finalizeRegularMeasure (
19             inputLineNumber,
20             measureRepeatContextKind,
21             context);
22         break;
23
24     case msrVoiceKind::kVoiceKindDynamics:
25         break;
26
27     case msrVoiceKind::kVoiceKindHarmonies:
28         finalizeHarmoniesMeasure (
29             inputLineNumber,
30             measureRepeatContextKind,
31             context);
32         break;
33
34     case msrVoiceKind::kVoiceKindFiguredBass:
35         finalizeFiguredBassMeasure (
36             inputLineNumber,
37             measureRepeatContextKind,
38             context);
39         break;
```

```

40     } // switch
41
42     // ... ..
43 }

```

In the case of harmony and figured bass voices, padding may have to be added to obtain a complete measure. This does not happen for clones of such voices: the padding skips are in the original voice and will be visited and handled without anything special to be done.

42.2 The finalization methods

There is a set of virtual method `finalize* ()` methods in `MusicFormats`. There basic ones are:

- method `msrPart::finalizePart ()` and method `msrPart::finalizePartClone ()`, defined in `src/formats/msr/msrParts.h/.cpp`
- method `msrStaff::finalizeStaff ()`, defined in `src/formats/msr/msrStaves.h/.cpp`
- method `msrVoice::finalizeVoice ()`, defined in `src/formats/msr/msrVoices.h/.cpp`
- method `msrSegment::finalizeAllTheMeasuresOfSegment ()`, defined in `src/formats/msr/msrSegments.h/.cpp`
- method `msrMeasure::finalizeMeasure ()`, method `msrMeasure::finalizeMeasureClone ()` and method `msrMeasure::finalizeRegularMeasure ()`, defined in `src/formats/msr/msrMeasures.h/.cpp`
- method `msrChord::finalizeChord ()`, defined in `src/formats/msr/msrChords.h/.cpp`
- method `msrTuplets::finalizeTuplet ()`, defined in `src/formats/msr/msrTuplets.h/.cpp`
- method `mxsr2msrTranslator::finalizeTupletAndPopItFromTupletsStack ()`, defined in `src/passes/mxsr2msr/mxsr2msrTranslator.h.h/.cpp`
- method `msrMeasure::finalizeFiguredBassMeasure ()`, defined in `src/formats/msr/msrMeasures.h/.cpp`
- method `msrMeasure::finalizeHarmoniesMeasure ()`, defined in `src/formats/msr/msrMeasures.h/.cpp`
- method `msr2bsrTranslator::finalizeCurrentMeasureClone ()`, defined in `src/passes/msr2bsr/(.h/.cppmsr2bsrTranslator)`
- method `mxsr2msrTranslator::finalizeCurrentChord ()`, defined in `src/passes/mxsr2msr/mxsr2msrTranslator.h/.cpp`

Handling repeats is rather complex in `MusicFormats`. Repeat ends are finalized with these methods:

- method `msrPart::finalizeRepeatEndInPart ()`,
defined in `src/formats/msr/msrParts.h/.cpp`
- method `msrStaff::finalizeRepeatEndInStaff ()`,
defined in `src/formats/msr/msrStaves.h/.cpp`
- method `msrVoice::finalizeRepeatEndInVoice ()`,
defined in `src/formats/msr/msrVoices.h/.cpp`

There are also 'cascading' finalization methods: they propagate finalization going from class `msrPart` towards class `msrVoice`:

- method `msrPart::finalizeLastAppendedMeasureInPart ()`,
defined in `src/formats/msr/msrParts.h/.cpp`
- method `msrStaff::finalizeLastAppendedMeasureInStaff ()`,
defined in `src/formats/msr/msrStaves.h/.cpp`
- method `msrVoice::finalizeLastAppendedMeasureInVoice ()`,
defined in `src/formats/msr/msrVoices.h/.cpp`
- method `msrPart::finalizePartAndAllItsMeasures ()`,
defined in `src/formats/msr/msrParts.h/.cpp`
- method `msrVoice::finalizeVoiceAndAllItsMeasures ()`,
defined in `src/formats/msr/msrVoices.h/.cpp`

A typical example of cascading finalization is method `msrPart::finalizePartAndAllItsMeasures ()`:

```

1 void msrPart::finalizePartAndAllItsMeasures (
2     int inputLineNumber)
3 {
4     #ifdef TRACING_IS_ENABLED
5         if (gGlobalTracingOahGroup->getTraceParts ()) {
6             gLogStream <<
7                 "Finalizing part clone " <<
8                 getPartCombinedName () <<
9                 ", line " << inputLineNumber <<
10                endl;
11        }
12    #endif
13
14    #ifdef TRACING_IS_ENABLED
15        if (gGlobalTracingOahGroup->getTraceVoices ()) {
16            gLogStream <<
17                "Finalizing all the measures of part \"" <<
18                getPartCombinedName () <<
19                "\", line " << inputLineNumber <<
20                endl;
21        }
22    #endif
23
24    for (
25        list<S_msrVoice>::const_iterator i = fPartAllVoicesList.begin ();
26        i != fPartAllVoicesList.end ();
27        ++i
28    ) {
29        S_msrVoice voice = (*i);
30
31        voice->
32            finalizeVoiceAndAllItsMeasures (
33                inputLineNumber);
34    } // for
35
36    // collect the part measures slices from the staves
37    collectPartMeasuresSlices (
38        inputLineNumber);
39 }

```

42.3 Finalizing parts

Method `msrPart::finalizePart ()` warns if there are no staves in the part, and otherwise handles them, including cascading to method `msrStaff::finalizeStaff ()`:

```

1 void msrPart::finalizePart (
2     int inputLineNumber)
3 {
4     #ifdef TRACING_IS_ENABLED
5         if (gGlobalTracingOahGroup->getTraceParts ()) {
6             gLogStream <<
7                 "Finalizing part " <<
8                 getPartCombinedName () <<
9                 ", line " << inputLineNumber <<
10                endl;
11        }
12    #endif
13
14    ++gIndenter;
15
16    if (! getPartStaveNumbersToStavesMap.size ()) {
17        stringstream s;
18
19        s <<
20            "Part " <<
21            getPartCombinedName () <<
22            " appears in the part list, but doesn't contain any stave";
23
24        musicxmlWarning (
25            gGlobalServiceRunData->getInputSourceName (),
26            inputLineNumber,
27            s.str ());
28    }
29
30    else {
31        // sort the staves to have harmonies above and figured bass below the part
32        fPartAllStavesList.sort (
33            compareStavesToHaveFiguredBassElementsBelowCorrespondingPart);
34
35        // finalize the staves
36        for (
37            map<int, S_msrStaff>::const_iterator i =
38            getPartStaveNumbersToStavesMap.begin ();
39            i != getPartStaveNumbersToStavesMap.end ();
40            ++i
41        ) {
42            S_msrStaff staff = (*i).second;
43
44            staff->
45                finalizeStaff (
46                    inputLineNumber);
47        } // for
48    }
49
50    // set score instrument names max lengths if relevant
51    setPartInstrumentNamesMaxLengths ();
52
53    // collect the part measures slices from the staves
54    collectPartMeasuresSlices (
55        inputLineNumber);
56
57    --gIndenter;
58 }

```

42.4 Finalizing staves

Method `msrStaff::finalizeStaff ()` cascade s to method `msrVoice::finalizeVoice ()` and collects the staff measusres slices:

```

1 void msrStaff::finalizeStaff (int inputLineNumber)
2 {
3     #ifdef TRACING_IS_ENABLED
4         if (gGlobalTracingOahGroup->getTraceStaves ()) {
5             gLogStream <<
6                 "Finalizing staff \"" <<
7                 getStaffName () << "\" " <<
8                 ", line " << inputLineNumber <<
9                 endl;
10        }
11    #endif
12
13    ++gIndenter;
14
15    // finalize the voices
16    #ifdef TRACING_IS_ENABLED
17        if (gGlobalTracingOahGroup->getTraceVoices ()) {
18            gLogStream <<
19                "Finalizing the voices in staff \"" <<
20                getStaffName () << "\" " <<
21                ", line " << inputLineNumber <<
22                endl;
23        }
24    #endif
25
26    for (
27        map<int, S_msrVoice>::const_iterator i =
28            fStaffVoiceNumbersToAllVoicesMap.begin ();
29        i != fStaffVoiceNumbersToAllVoicesMap.end ();
30        ++i
31    ) {
32        S_msrVoice
33            voice = (*i).second;
34
35        voice->
36            finalizeVoice (
37                inputLineNumber);
38    } // for
39
40    // collect the staff measures slices from the voices
41    collectStaffMeasuresSlices (
42        inputLineNumber);
43
44    --gIndenter;
45 }

```

42.5 Finalizing voices

Method `msrVoice::finalizeVoice ()` handles pending repeats if any and collects the voice measures into a flat list. It does not, however, cascade to finalizing the voice repeats and measures.

```

1 void msrVoice::finalizeVoice (
2     int inputLineNumber)
3 {
4     // ... ..
5
6     if (fVoiceHasBeenFinalized) {

```



```

7      stringstream s;
8
9      s <<
10     "Attempting to finalize voice \"" <<
11     asShortString () <<
12     "\" more than once";
13
14     msrInternalError (
15         gGlobalServiceRunData->getInputSourceName (),
16         fInputLineNumber,
17         __FILE__, __LINE__,
18         s.str ());
19 }
20
21 // set part shortest note duration if relevant
22 S_msrPart
23     voicePart =
24         fetchVoicePartUpLink ();
25
26 rational
27     partShortestNoteDuration =
28         voicePart->
29             getPartShortestNoteDuration ();
30
31 // ... ..
32
33 if (fVoiceShortestNoteDuration < partShortestNoteDuration) {
34     // set the voice part shortest note duration
35     voicePart->
36         setPartShortestNoteDuration (
37             fVoiceShortestNoteDuration);
38
39     // set the voice part shortest note tuplet factor // JMI
40     voicePart->
41         setPartShortestNoteTupletFactor (
42             fVoiceShortestNoteTupletFactor);
43 }
44
45 // is this voice totally empty? this should be rare...
46 if (
47     fVoiceInitialElementsList.size () == 0
48     &&
49     fVoiceLastSegment->getSegmentElementsList ().size () == 0
50 ) {
51     stringstream s;
52
53     s <<
54     "Voice \"" <<
55     getVoiceName () <<
56     "\" is totally empty, no contents ever specified for it" <<
57     endl;
58
59     musicxmlWarning (
60         gGlobalServiceRunData->getInputSourceName (),
61         inputLineNumber,
62         s.str ());
63 }
64
65 // are there pending repeats in the voice repeats stack???
66 unsigned int voicePendingRepeatDescrsStackSize =
67     fVoicePendingRepeatDescrsStack.size ();
68
69 // ... ..
70
71 // collect the voice measures into the flat list
72 collectVoiceMeasuresIntoFlatList (
73     inputLineNumber);

```

```

74
75     fVoiceHasBeenFinalized = true;
76
77     // ... ..
78 }

```

42.6 Finalizing repeats

42.7 Finalizing measures

Method `msrMeasure::finalizeMeasure ()` is not cascaded. It delegates finalization to voice kind specific methods presented in the subsections below, handles pending repeats if any, and assigns positions in the measure to the measure's elements:

```

1 void msrMeasure::finalizeMeasure (
2     int inputLineNumber,
3     msrMeasureRepeatContextKind measureRepeatContextKind,
4     string context)
5 {
6     if (fMeasureHasBeenFinalized) {
7         stringstream s;
8
9         s <<
10         "Attempting to finalize measure " <<
11         this->asShortString () <<
12         " more than once in segment '" <<
13         fMeasureSegmentUpLink->getSegmentAbsoluteNumber () <<
14         "', context: " << context <<
15         "', measureFinalizationContext: " << fMeasureFinalizationContext <<
16         " in voice \"" <<
17         fMeasureSegmentUpLink->
18         getSegmentVoiceUpLink ()->
19         getVoiceName () <<
20         "\" (" << context << ")" <<
21         ", line " << inputLineNumber;
22
23         // ... ..
24
25         msrInternalWarning (
26             gGlobalServiceRunData->getInputSourceName (),
27             fInputLineNumber,
28             s.str ());
29     }
30
31     else {
32         S_msrVoice
33         voice =
34             fMeasureSegmentUpLink->
35             getSegmentVoiceUpLink ();
36
37         // ... ..
38
39         // delegate to voice kind specific methods
40         switch (voice->getVoiceKind ()) {
41             case msrVoiceKind::kVoiceKindRegular:
42                 finalizeRegularMeasure (
43                     inputLineNumber,
44                     measureRepeatContextKind,
45                     context);
46                 break;
47
48             case msrVoiceKind::kVoiceKindDynamics:

```

```

49     break;
50
51     case msrVoiceKind::kVoiceKindHarmonies:
52         finalizeHarmoniesMeasure (
53             inputLineNumber,
54             measureRepeatContextKind,
55             context);
56     break;
57     case msrVoiceKind::kVoiceKindFiguredBass:
58         finalizeFiguredBassMeasure (
59             inputLineNumber,
60             measureRepeatContextKind,
61             context);
62     break;
63 } // switch
64
65 // position in voice
66 rational
67     positionInVoice =
68     fetchMeasureVoiceUpLink ()->
69     getCurrentPositionInVoice ();
70
71 // assign measure' elements position in measure
72 for (
73     list<S_msrMeasureElement>::const_iterator i = fMeasureElementsList.begin ();
74     i != fMeasureElementsList.end ();
75     ++i
76 ) {
77     S_msrMeasureElement measureElement = (*i);
78
79     measureElement->
80     assignMeasureElementPositionInVoice (
81         positionInVoice,
82         "finalizeMeasure()");
83 } // for
84
85 // register finalization
86 fMeasureHasBeenFinalized = true;
87 fMeasureFinalizationContext = context;
88 }
89 }

```

42.7.1 Finalizing regular measures

```

1 void msrMeasure::finalizeRegularMeasure (
2     int inputLineNumber,
3     msrMeasureRepeatContextKind measureRepeatContextKind,
4     string context)
5 {
6     // fetch the regular voice
7     S_msrVoice
8     voice =
9     fMeasureSegmentUpLink->
10     getSegmentVoiceUpLink ();
11
12     // fetch the regular voice's part
13     S_msrPart
14     regularPart =
15     voice->
16     fetchVoicePartUpLink ();
17
18     mfAssert (
19         __FILE__, __LINE__,
20         regularPart != nullptr,

```

```

21     "regularPart is null");
22
23     if (false) { // JMI
24         gLogStream <<
25             "---> regularPart: " <<
26             endl;
27
28         ++gIndenter;
29         gLogStream <<
30             regularPart <<
31             endl;
32         --gIndenter;
33         gLogStream << endl;
34     }
35
36     rational
37         measureWholeNotesDurationFromPartMeasuresVector =
38         regularPart->
39             getPartMeasuresWholeNotesDurationsVector () [
40                 fMeasureOrdinalNumberInVoice - 1 ];
41
42 #ifdef TRACING_IS_ENABLED
43     if (gGlobalTracingOahGroup->getTraceMeasures ()) {
44         gLogStream <<
45             "Finalizing regular measure " <<
46             this->asShortString () <<
47             " in segment '" <<
48             fMeasureSegmentUpLink->getSegmentAbsoluteNumber () <<
49             "' in regular voice \"" <<
50             voice->getVoiceName () <<
51             "\" (" << context << ")" <<
52             ", measureWholeNotesDurationFromPartMeasuresVector: " <<
53             measureWholeNotesDurationFromPartMeasuresVector <<
54             ", line " << inputLineNumber <<
55             endl;
56     }
57 #endif
58
59     ++gIndenter;
60
61 #ifdef TRACING_IS_ENABLED
62     if (gGlobalTracingOahGroup->getTraceMeasuresDetails ()) {
63         displayMeasure (
64             inputLineNumber,
65             "finalizeRegularMeasure() 1");
66     }
67 #endif
68
69     padUpToPositionAtTheEndOfTheMeasure (
70         inputLineNumber,
71         measureWholeNotesDurationFromPartMeasuresVector);
72
73     // register this measures's length in the part
74     S_msrPart
75     part =
76         this->fetchMeasurePartUpLink ();
77
78     part->
79         registerOrdinalMeasureNumberWholeNotesDuration (
80             inputLineNumber,
81             fMeasureOrdinalNumberInVoice,
82             fCurrentMeasureWholeNotesDuration);
83
84     // determine the measure kind and purist number
85     determineMeasureKindAndPuristNumber (
86         inputLineNumber,
87         measureRepeatContextKind);

```

```

88
89 // pad measure up to whole measure whole notes high tide JMI ???
90 switch (fMeasureKind) {
91     case msrMeasureKind::kMeasureKindCadenza:
92         break;
93
94     case msrMeasureKind::kMeasureKindOvercomplete:
95     case msrMeasureKind::kMeasureKindAnacrusis:
96     case msrMeasureKind::kMeasureKindRegular:
97     case msrMeasureKind::kMeasureKindIncompleteStandalone: // JMI
98     case msrMeasureKind::kMeasureKindIncompleteLastInRepeatCommonPart: // JMI
99     case msrMeasureKind::kMeasureKindIncompleteLastInRepeatHookedEnding: // JMI
100    case msrMeasureKind::kMeasureKindIncompleteLastInRepeatHooklessEnding: // JMI
101    case msrMeasureKind::kMeasureKindIncompleteNextMeasureAfterCommonPart: // JMI
102    case msrMeasureKind::kMeasureKindIncompleteNextMeasureAfterHookedEnding: // JMI
103    case msrMeasureKind::kMeasureKindIncompleteNextMeasureAfterHooklessEnding: // JMI
104        break;
105
106    case msrMeasureKind::kMeasureKindUnknown:
107        // JMI ???
108        break;
109
110    case msrMeasureKind::kMeasureKindMusicallyEmpty:
111    {
112        /* JMI
113         */
114    }
115    break;
116 } // switch
117
118 // is there a single note or rest occupying the full measure?
119 if (fMeasureLongestNote) {
120     if (
121         fMeasureLongestNote->getNoteSoundingWholeNotes ()
122         ==
123         fFullMeasureWholeNotesDuration
124     ) {
125 #ifdef TRACING_IS_ENABLED
126         if (gGlobalTracingOahGroup->getTraceMeasures ()) {
127             gLogStream <<
128                 "Note '" <<
129                 fMeasureLongestNote->asShortString () <<
130                 "' occupies measure " <<
131                 this->asShortString () <<
132                 " fully in segment '" <<
133                 fMeasureSegmentUpLink->getSegmentAbsoluteNumber () <<
134                 "' in voice \"" <<
135                 voice->getVoiceName () <<
136                 "\", line " << inputLineNumber <<
137                 endl;
138         }
139 #endif
140
141         fMeasureLongestNote->
142             setNoteOccupiesAFullMeasure ();
143     }
144 }
145
146 #ifdef TRACING_IS_ENABLED
147     if (gGlobalTracingOahGroup->getTraceMeasuresDetails ()) {
148         displayMeasure (
149             inputLineNumber,
150             "finalizeRegularMeasure() 2");
151     }
152 #endif
153
154 --gIndenter;

```

155 }

42.7.2 Finalizing harmonies measures

```

1 void msrMeasure::finalizeHarmoniesMeasure (
2     int                    inputLineNumber,
3     msrMeasureRepeatContextKind measureRepeatContextKind,
4     string                 context)
5 {
6     // fetch the harmonies voice
7     S_msrVoice
8     harmoniesVoice =
9         fMeasureSegmentUpLink->
10         getSegmentVoiceUpLink ();
11
12     // fetch the harmonies part
13     S_msrPart
14     harmoniesPart =
15         harmoniesVoice->
16         fetchVoicePartUpLink ();
17
18     mfAssert (
19         __FILE__, __LINE__,
20         harmoniesPart != nullptr,
21         "harmoniesPart is null");
22
23 #ifdef TRACING_IS_ENABLED
24     if (gGlobalTracingOahGroup->getTraceHarmonies ()) {
25         gLogStream <<
26             "Finalizing harmonies measure " <<
27             this->asShortString () <<
28             " in segment '" <<
29             fMeasureSegmentUpLink->getSegmentAbsoluteNumber () <<
30             "' in harmonies voice \"" <<
31             harmoniesVoice->getVoiceName () <<
32             "\" (" << context << ")" <<
33             ", line " << inputLineNumber <<
34             endl;
35     }
36 #endif
37     ++gIndenter;
38
39 #ifdef TRACING_IS_ENABLED
40     if (gGlobalTracingOahGroup->getTraceHarmoniesDetails ()) {
41         displayMeasure (
42             inputLineNumber,
43             "finalizeHarmoniesMeasure() 1");
44     }
45 #endif
46
47 #ifdef TRACING_IS_ENABLED
48     // get the harmoniesPart number of measures
49     int
50     harmoniesPartNumberOfMeasures =
51         harmoniesPart->
52         getPartNumberOfMeasures ();
53
54     if (gGlobalTracingOahGroup->getTraceHarmonies ()) {
55         gLogStream <<
56             "fMeasureOrdinalNumberInVoice = " <<
57             fMeasureOrdinalNumberInVoice <<
58             ", harmoniesPartNumberOfMeasures = " <<
59             harmoniesPartNumberOfMeasures <<

```

```

61     endl;
62 }
63 #endif
64
65 // the measureWholeNotesDuration has to be computed
66 rational
67     measureWholeNotesDurationFromPartMeasuresVector =
68     harmoniesPart->
69     getPartMeasuresWholeNotesDurationsVector () [
70         fMeasureOrdinalNumberInVoice - 1 ];
71
72 // handle the harmonies in this measure
73 finalizeHarmoniesInHarmoniesMeasure (
74     inputLineNumber,
75     context);
76
77 // pad the measure up to measureWholeNotesDurationFromPartMeasuresVector
78 padUpToPositionAtTheEndOfTheMeasure (
79     inputLineNumber,
80     measureWholeNotesDurationFromPartMeasuresVector);
81
82 // determine the measure kind and purist number
83 determineMeasureKindAndPuristNumber (
84     inputLineNumber,
85     measureRepeatContextKind);
86
87 #ifdef TRACING_IS_ENABLED
88     if (gGlobalTracingOahGroup->getTraceHarmoniesDetails ()) {
89         displayMeasure (
90             inputLineNumber,
91             "finalizeHarmoniesMeasure() 2");
92     }
93 #endif
94
95     --gIndenter;
96 }

```

42.7.3 Finalizing figured bass measures

```

1 void msrMeasure::finalizeFiguredBassMeasure (
2     int inputLineNumber,
3     msrMeasureRepeatContextKind measureRepeatContextKind,
4     string context)
5 {
6     // fetch the figured bass voice
7     S_msrVoice
8         figuredBassVoice =
9         fMeasureSegmentUpLink->
10         getSegmentVoiceUpLink ();
11
12     // fetch the figured bass part
13     S_msrPart
14         figuredBassPart =
15         figuredBassVoice->
16         fetchVoicePartUpLink ();
17
18     mfAssert (
19         __FILE__, __LINE__,
20         figuredBassPart != nullptr,
21         "figuredBassPart is null");
22
23 #ifdef TRACING_IS_ENABLED
24     if (gGlobalTracingOahGroup->getTraceFiguredBass ()) {
25         gLogStream <<

```

```

26     "Finalizing figured bass measure " <<
27     this->asShortString () <<
28     " in segment '" <<
29     fMeasureSegmentUpLink->getSegmentAbsoluteNumber () <<
30     "' in figured bass voice \"" <<
31     figuredBassVoice->getVoiceName () <<
32     "\" (" << context << ")" <<
33     ", line " << inputLineNumber <<
34     endl;
35 }
36 #endif
37
38 ++gIndenter;
39
40 #ifdef TRACING_IS_ENABLED
41 if (gGlobalTracingOahGroup->getTraceFiguredBassDetails ()) {
42     displayMeasure (
43         inputLineNumber,
44         "finalizeFiguredBassMeasure() 1");
45 }
46 #endif
47
48 #ifdef TRACING_IS_ENABLED
49 // get the figuredBassPart number of measures
50 int
51 figuredBassPartNumberOfMeasures =
52     figuredBassPart->
53     getPartNumberOfMeasures ();
54
55 if (gGlobalTracingOahGroup->getTraceHarmonies ()) {
56     gLogStream <<
57     "fMeasureOrdinalNumberInVoice = " <<
58     fMeasureOrdinalNumberInVoice <<
59     ", figuredBassPartNumberOfMeasures = " <<
60     figuredBassPartNumberOfMeasures <<
61     endl;
62 }
63 #endif
64
65 // the measureWholeNotesDuration has to be computed
66 rational
67 measureWholeNotesDuration =
68     figuredBassPart->
69     getPartMeasuresWholeNotesDurationsVector () [
70         fMeasureOrdinalNumberInVoice - 1 ];
71
72 // handle the figured bass elements in this measure
73 finalizeFiguredBassElementsInFiguredBassMeasure (
74     inputLineNumber,
75     context);
76
77 // pad the measure up to fFullMeasureWholeNotesDuration
78 padUpToPositionAtTheEndOfTheMeasure (
79     inputLineNumber,
80     measureWholeNotesDuration);
81
82 // determine the measure kind and purist number
83 determineMeasureKindAndPuristNumber (
84     inputLineNumber,
85     measureRepeatContextKind);
86
87 #ifdef TRACING_IS_ENABLED
88 if (gGlobalTracingOahGroup->getTraceFiguredBassDetails ()) {
89     displayMeasure (
90         inputLineNumber,
91         "finalizeFiguredBassMeasure() 2");
92 }

```



```
93 #endif
94
95 --gIndenter;
96 }
```

42.8 Determining positions in measures

Chapter 43

Tempos handling

Tempos are presented at section [19.18](#) [Tempos], page [175](#).

43.1 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

43.2 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

43.3 Translating from MSR to MSR ([src/passes/msr2msr/](#))

43.4 Translating from MSR to LPSR ([src/passes/msr2lpsr/](#))

43.5 Translating from LPSR to LilyPond ([src/passes/lpsr2lilypond/](#))

Chapter 44

Positions in measures

Positions in measures is stored in field `msrMeasureElement::fMeasureElementPositionInMeasure` in class `msrMeasureElement`, defined in `src/formats/msr/msrMeasureElement.h/.cpp`:

```
1 class EXP msrMeasureElement : public msrElement
2 {
3     // ... ..
4
5     protected:
6
7         // protected fields
8         // -----
9
10        /*
11         The measure uplink is declared in the sub-classes,
12         to allow for separate *.h files, C++ constraint
13        */
14
15        rational          fMeasureElementSoundingWholeNotes;
16
17        string            fMeasureElementMeasureNumber;
18
19        rational          fMeasureElementPositionInMeasure;
20        rational          fMeasureElementPositionInVoice;
21
22        msrMoment         fMeasureElementMomentInMeasure;
23        msrMoment         fMeasureElementMomentInVoice;
24 };
```

44.1 Determining positions in measures

Chapter 45

Notes handling

Notes are presented at section ?? [Notes], page ??.

45.1 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

45.2 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

45.3 Translating from MSR to MSR ([src/passes/msr2msr/](#))

45.4 Translating from MSR to LPSR ([src/passes/msr2lpsr/](#))

45.5 Translating from LPSR to LilyPond ([src/passes/lpsr2lilypond/](#))

Chapter 46

Segments handling

Segments are presented at section [19.37](#) [Segments], page [193](#).

The segments concept used by MusicFormats to describe music scores is not apparent to the users of GUI applications, in which music elements are *drawn* on the page. Their need is inherent to the representation of repeats, which contain music elements sequences (the segments) and even other repeats.

ALL SEGMENTS HANDLING in MusicFormats IS DONE INTERNALLY: the class `msrSegment` instances are created in voices and repeats BEHIND THE CURTAINS.

46.1 Segments creation

Instances of class `msrSegment` are created at four places in `src/formats/msr/msrVoices.cpp`:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev/src/formats/msr > grep 'msrSegment::create ('  
   *.cpp  
2 msrSegments.cpp:S_msrSegment msrSegment::create (  
3 msrSegments.cpp:      msrSegment::create (  
4 msrSegments.cpp:      msrSegment::create (  
5 msrVoices.cpp:      msrSegment::create (  
6 msrVoices.cpp:      msrSegment::create (  
7 msrVoices.cpp:      msrSegment::create (  
8 msrVoices.cpp:      msrSegment::create (  
9
```

Calls to method `msrSegment::createSegmentNewbornClone ()` occurs only when visiting class `msrSegment` instances in passes:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev/src/passes > grep createSegmentNewbornClone  
   */*  
2 msr2bsr/msr2bsrTranslator.cpp:      elt->createSegmentNewbornClone (  
3 msr2lpsr/msr2lpsrTranslator.cpp:      elt->createSegmentNewbornClone (  
4 msr2msr/msr2msrTranslator.cpp:      elt->createSegmentNewbornClone (  
5
```

Method `msrSegment::createSegmentDeepClone ()` is not used at the time of this writing.

Explicit segments creation is thus entirely done in methods inside `src/formats/msr/msrVoices.cpp`: the passes are not aware of this happening.

The first occurrence of method `msrSegment::create ()` is in method `msrVoice::initializeVoice ()`: when a voice is created, a segment is created and stored in its `fVoiceLastSegment` if requested :

```

1 void msrVoice::initializeVoice (
2     msrVoiceCreateInitialLastSegmentKind
3     voiceCreateInitialLastSegmentKind)
4 {
5     // ... ..
6
7     // create the initial last segment if requested
8     switch (voiceCreateInitialLastSegmentKind) {
9         case msrVoiceCreateInitialLastSegmentKind::kCreateInitialLastSegmentYes:
10            // sanity check // JMI LAST
11            mfAssert (
12                __FILE__, __LINE__,
13                fVoiceLastSegment == nullptr,
14                "fVoiceLastSegment is null");
15
16            // create the last segment
17            fVoiceLastSegment =
18                msrSegment::create (
19                    fInputLineNumber,
20                    this);
21
22            if (! fVoiceFirstSegment) {
23                fVoiceFirstSegment = fVoiceLastSegment;
24            }
25            break;
26        case msrVoiceCreateInitialLastSegmentKind::kCreateInitialLastSegmentNo:
27            break;
28    } // switch
29
30    // ... ..
31 };

```

Method `msrVoice::createMeasureRepeatFromItsFirstMeasures ()` is presented in section 48 [Measure repeats handling], page 306, and the remaining two are presented in the next sections.

46.1.1 Creating a new last segment for a voice

There is method `msrVoice::createNewLastSegmentForVoice ()`, called at many places in `src/formats/msr/msrVoices.cpp`:

```

1 void msrVoice::createNewLastSegmentForVoice (
2     int    inputLineNumber,
3     const string& context)
4 {
5     // ... ..
6
7     // create the last segment
8     fVoiceLastSegment =
9         msrSegment::create (
10             inputLineNumber,
11             this);
12
13     if (! fVoiceFirstSegment) {
14         fVoiceFirstSegment = fVoiceLastSegment;
15     }
16
17     // ... ..
18 }

```

The calls to method `msrVoice::createNewLastSegmentForVoice ()` are in:

- method `msrVoice::createAMeasureAndAppendItToVoice ()`
- method `msrVoice::appendStaffDetailsToVoice ()`
- method `msrVoice::addGraceNotesGroupBeforeAheadOfVoiceIfNeeded ()`
- method `msrVoice::handleVoiceLevelRepeatStart ()`
- method `msrVoice::handleVoiceLevelRepeatEndWithoutStart ()`
- method `msrVoice::handleVoiceLevelContainingRepeatEndWithoutStart ()`
- method `msrVoice::handleVoiceLevelRepeatEndWithStart ()`
- method `msrVoice::handleVoiceLevelRepeatEndingStartWithoutExplicitStart ()`
- method `msrVoice::handleVoiceLevelRepeatEndingStartWithExplicitStart ()`
- method `msrVoice::handleMultipleFullBarRestsStartInVoiceClone ()`
- method `msrVoice::handleHooklessRepeatEndingEndInVoice ()`
- method `msrVoice::appendBarLineToVoice ()`
- method `msrVoice::appendSegnoToVoice ()`
- method `msrVoice::appendCodaToVoice ()`
- method `msrVoice::appendEyeGlassesToVoice ()`
- method `msrVoice::appendPedalToVoice ()`
- method `msrVoice::appendDampToVoice ()`
- method `msrVoice::appendDampAllToVoice ()`

46.1.2 Creating a new last segment for a voice from its first measure

Method `msrVoice::createNewLastSegmentFromItsFirstMeasureForVoice ()` is used at several places in [src/formats/msr/msrVoices.cpp](#):

```

1 void msrVoice::createNewLastSegmentFromItsFirstMeasureForVoice (
2     int          inputLineNumber,
3     S_msrMeasure firstMeasure,
4     string       context)
5 {
6     // create the last segment
7     fVoiceLastSegment =
8         msrSegment::create (
9             inputLineNumber,
10            this);
11
12     if (! fVoiceFirstSegment) {
13         fVoiceFirstSegment = fVoiceLastSegment;
14     }
15
16     // ... ..
17

```

```

18 // append firstMeasure to fVoiceLastSegment
19 fVoiceLastSegment->
20     appendMeasureToSegment (firstMeasure);
21
22 // firstMeasure is the new voice last appended measure
23 fVoiceLastAppendedMeasure = firstMeasure;
24
25 // is firstMeasure the first one in the voice?
26 if (! fVoiceFirstMeasure) {
27     // yes, register it as such
28     setVoiceFirstMeasure (
29         firstMeasure);
30
31     firstMeasure->
32         setMeasureFirstInVoice ();
33 }
34
35 // ... ..
36 }

```

All the uses of this method concern repeats (section 50 [Repeats handling], page 308), measure repeats (section 48 [Measure repeats handling], page 306) and multiple full-bar rests (section ?? [Full-bar rests handling], page ??).

46.2 Appending measures to a segment

Method `msrSegment::assertSegmentElementsListIsNotEmpty ()` is called as a sanity check by many methods in `src/formats/msr/msrSegments.cpp`:

```

1 void msrSegment::assertSegmentElementsListIsNotEmpty (
2     int inputLineNumber) const
3 {
4     if (! fSegmentElementsList.size ()) {
5 #ifdef TRACING_IS_ENABLED
6         if (
7             gGlobalTracingOahGroup->getTraceMeasuresDetails ()
8             ||
9             gGlobalTracingOahGroup->getTraceSegmentsDetails ()
10            ||
11            gGlobalTracingOahGroup->getTraceRepeatsDetails ()
12        ) {
13            fSegmentVoiceUpLink->
14                displayVoiceRepeatsStackMultipleFullBarRestsMeasureRepeatAndVoice (
15                inputLineNumber,
16                "assertSegmentElementsListIsNotEmpty()");
17        }
18 #endif
19
20        gLogStream <<
21            "assertSegmentElementsListIsNotEmpty()" <<
22            ", fSegmentElementsList is empty" <<
23            ", segment: " <<
24            this->asString () <<
25            ", in voice \"" <<
26            fSegmentVoiceUpLink->getVoiceName () <<
27            "\" " <<
28            ", line " << inputLineNumber <<
29            endl;
30
31        mfAssert (
32            __FILE__, __LINE__,
33            false,
34            ", fSegmentElementsList is empty");

```



```

35 }
36 }

```

One such call is:

```

1 void msrSegment::appendKeyToSegment (S_msrKey key)
2 {
3 #ifdef TRACING_IS_ENABLED
4     if (gGlobalTracingOahGroup->getTraceKeys ()) {
5         gLogStream <<
6             "Appending key " << key->asString () <<
7             " to segment " << asString () <<
8             ", in voice \"" <<
9             fSegmentVoiceUpLink->getVoiceName () <<
10            "\" <<
11         endl;
12     }
13 #endif
14
15     // sanity check
16     assertSegmentElementsListIsNotEmpty (
17         key->getInputLineNumber ());
18
19     ++gIndenter;
20
21     // register key in segments's current measure
22     fSegmentElementsList.back ()->
23         appendKeyToMeasure (key);
24
25     --gIndenter;
26 }

```

46.3 Translating from MXSR to MSR

46.4 Translating from MXSR to MSR

This is done in `src/passes/mxsr2msr/`.

46.5 Translating from MSR to MSR

This is done in `src/passes/msr2msr/`.

46.6 Translating from MSR to LPSR

This is done in `src/passes/msr2lpsr/`.

46.7 Translating from LPSR to LilyPond

This is done in `src/passes/lpsr2lilypond/`.

Chapter 47

Beat repeats handling

Beat repeats are presented at section [19.32](#) [Beat repeats], page [189](#).

47.1 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

47.2 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

47.3 Translating from MSR to MSR ([src/passes/msr2msr/](#))

47.4 Translating from MSR to LPSR ([src/passes/msr2lpsr/](#))

47.5 Translating from LPSR to LilyPond ([src/passes/lpsr2lilypond/](#))

Chapter 48

Measure repeats handling

Measure repeats are presented at section [19.33](#) [Measure repeats], page [190](#).

48.1 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

```
method msrVoice::createMeasureRepeatFromItsFirstMeasures ():
```

48.2 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

48.3 Translating from MSR to MSR ([src/passes/msr2msr/](#))

48.4 Translating from MSR to LPSR ([src/passes/msr2lpsr/](#))

48.5 Translating from LPSR to LilyPond ([src/passes/lpsr2lilypond/](#))

Chapter 49

Multiple full-bar rests handling

Multiple full-bar rests are presented at section [19.34](#) [Multiple full-bar rests], page [191](#).

Chapter 50

Repeats handling

Repeats are presented at section [19.36](#) [Repeats], page [191](#).

50.1 Translating repeats from MXSR to MSR

This is done in `src/passes/mxsr2msr/`.

The tough part is to handle MusicXML `<barLine/>` markups, since they are meant for drawing, and do not structure repeats as such.

Recognizing the structure of repeat relies on the attributes of the barLines. The following enumeration types are defined in `src/formats/msr/msrBarLines.h` local to class `msrBarLine`:

```
1 // location
2 enum msrBarLineLocationKind {
3     kBarLineLocationNone,
4
5     kBarLineLocationLeft,
6     kBarLineLocationMiddle,
7     kBarLineLocationRight // by default
8 };
```

```
1 // style
2 enum msrBarLineStyleKind {
3     kBarLineStyleNone,
4
5     kBarLineStyleRegular, // by default
6
7     kBarLineStyleDotted, kBarLineStyleDashed, kBarLineStyleHeavy,
8     kBarLineStyleLightLight, kBarLineStyleLightHeavy,
9     kBarLineStyleHeavyLight, kBarLineStyleHeavyHeavy,
10    kBarLineStyleTick, kBarLineStyleShort
11 };
```

```
1 // repeat direction
2 enum msrBarLineRepeatDirectionKind {
3     kBarLineRepeatDirectionNone,
4     kBarLineRepeatDirectionForward, kBarLineRepeatDirectionBackward
5 };
```

```

1 // ending type
2 enum msrBarLineEndingTypeKind {
3     kBarLineEndingNone,
4
5     kBarLineEndingTypeStart,
6     kBarLineEndingTypeStop,
7     kBarLineEndingTypeDiscontinue
8 };

```

```

1 // category
2 enum msrBarLineCategoryKind {
3     k_NoBarLineCategory,
4
5     kBarLineCategoryStandalone,
6
7     kBarLineCategoryRepeatStart, kBarLineCategoryRepeatEnd,
8
9     kBarLineCategoryHookedEndingStart, kBarLineCategoryHookedEndingEnd,
10    kBarLineCategoryHooklessEndingStart, kBarLineCategoryHooklessEndingEnd
11 };

```

```

1 // segno
2 enum msrBarLineHasSegnoKind {
3     kBarLineHasSegnoYes, kBarLineHasSegnoNo
4 };

```

```

1 // coda
2 enum msrBarLineHasCodaKind {
3     kBarLineHasCodaYes, kBarLineHasCodaNo
4 };

```

```

1 // repeat winged
2 enum msrBarLineRepeatWingedKind {
3     kBarLineRepeatWingedNone,
4
5     kBarLineRepeatWingedStraight, kBarLineRepeatWingedCurved,
6     kBarLineRepeatWingedDoubleStraight, kBarLineRepeatWingedDoubleCurved
7 };

```

The attributes of <barline/> are deciphered upon the first visit of S_barline in [src/passes/mxsr2msr/mxsr2msrTranslator.cpp](#):

```

1 void mxsr2msrTranslator::visitStart ( S_barline& elt )
2 {
3     // ... ..
4
5     // location
6
7     {
8         string
9         location =
10            elt->getAttributeValue ( "location" );
11
12         fCurrentBarLineLocationKind =
13            msrBarLine::kBarLineLocationRight; // by default
14
15         if (location == "left") {
16             fCurrentBarLineLocationKind = msrBarLine::kBarLineLocationLeft;
17         }
18         else if (location == "middle") {
19             fCurrentBarLineLocationKind = msrBarLine::kBarLineLocationMiddle;
20         }
21         else if (location == "right") {
22             fCurrentBarLineLocationKind = msrBarLine::kBarLineLocationRight;

```

```

23     }
24     else {
25         stringstream s;
26
27         s <<
28             "barLine location \"" << location <<
29             "\" is unknown, using 'right' by default";
30
31         // JMI    musicxmlError (
32             musicxmlWarning (
33                 gGlobalServiceRunData->getInputSourceName (),
34                 inputLineNumber,
35                 //    __FILE__, __LINE__,
36                 s.str ());
37     }
38 }
39
40 fOnGoingBarLine = true;
41 }

```

Then the class `msrBarLine` instance is created upon the second visit of `S_barline`:

```

1 void mxsr2msrTranslator::visitEnd ( S_barline& elt )
2 {
3     // ... ..
4
5     // create the barLine
6     S_msrBarLine
7     barLine =
8         msrBarLine::create (
9             inputLineNumber,
10            fCurrentBarLineLocationKind,
11            fCurrentBarLineStyleKind,
12            fCurrentBarLineRepeatDirectionKind,
13            fCurrentBarLineEndingTypeKind,
14            fCurrentBarLineEndingNumber,
15            fCurrentBarLineTimes,
16            msrBarLine::k_NoBarLineCategory, // will be set afterwards
17            fCurrentBarLineHasSegnoKind,
18            fCurrentBarLineHasCodaKind,
19            fCurrentBarLineRepeatWingedKind);
20
21     // ... ..
22
23     // wait until its category is defined
24     // to append the barLine to the current segment
25
26     // handle the barLine according to: JMI
27     // http://www.musicxml.com/tutorial/the-midi-compatible-part/repeats/
28
29     Bool barLineHasBeenHandled = false;
30
31     switch (fCurrentBarLineLocationKind) {
32     case msrBarLine::kBarLineLocationNone:
33         // should not occur
34         break;
35
36     case msrBarLine::kBarLineLocationLeft:
37         if (
38             fCurrentBarLineEndingTypeKind
39             ==
40             msrBarLine::kBarLineEndingTypeStart
41         ) {
42             // ending start, don't know yet whether it's hooked or hookless
43             // -----
44             if (! fCurrentBarLineEndingNumber.size ()) {

```

```

45     musicxmlWarning (
46         gGlobalServiceRunData->getInputSourceName (),
47         inputLineNumber,
48         "mandatory ending number is missing, assuming \"1\\\"");
49
50     fCurrentBarLineEndingNumber = "1";
51 }
52
53 // don't know yet whether repeat ending start barLine is hooked or hookless
54 // remember it in fCurrentRepeatEndingStartBarLine,
55 fCurrentRepeatEndingStartBarLine = barLine;
56
57 // handle the repeat ending start
58 handleRepeatEndingStart (barLine);
59
60 barLineHasBeenHandled = true;
61 }
62
63 else if (
64     fCurrentBarLineRepeatDirectionKind
65     ==
66     msrBarLine::kBarLineRepeatDirectionForward
67 ) {
68     // repeat start
69     // -----
70     // set the barLine category
71     barLine->
72         setBarLineCategory (
73             msrBarLine::kBarLineCategoryRepeatStart);
74
75     // handle the repeat start
76     handleRepeatStart (barLine);
77
78     barLineHasBeenHandled = true;
79 }
80 break;
81
82 case msrBarLine::kBarLineLocationMiddle:
83     // JMI ???
84     break;
85
86 case msrBarLine::kBarLineLocationRight:
87     {
88         if (
89             fCurrentBarLineEndingTypeKind == msrBarLine::kBarLineEndingTypeStop
90             &&
91             fCurrentBarLineEndingNumber.size () != 0
92         ) {
93             // hooked ending end
94             // -----
95             // set current barLine ending start category
96             fCurrentRepeatEndingStartBarLine->
97                 setBarLineCategory (
98                     msrBarLine::kBarLineCategoryHookedEndingStart);
99
100             // set this barLine's category
101             barLine->
102                 setBarLineCategory (
103                     msrBarLine::kBarLineCategoryHookedEndingEnd);
104
105             // handle the repeat hooked ending end
106             handleRepeatHookedEndingEnd (barLine);
107
108             barLineHasBeenHandled = true;
109         }
110
111     else if (

```



```

112         fCurrentBarLineRepeatDirectionKind
113         ==
114         msrBarLine::kBarLineRepeatDirectionBackward
115     ) {
116         // repeat end
117         // -----
118
119         // set this barLine's category
120         barLine->
121             setBarLineCategory (
122                 msrBarLine::kBarLineCategoryRepeatEnd);
123
124         // handle the repeat end
125         handleRepeatEnd (barLine);
126
127         barLineHasBeenHandled = true;
128     }
129
130     else if (
131         fCurrentBarLineEndingTypeKind == msrBarLine::kBarLineEndingTypeDiscontinue
132         &&
133         fCurrentBarLineEndingNumber.size () != 0
134     ) {
135         // hookless ending end
136         // -----
137         // set current barLine ending start category
138         fCurrentRepeatEndingStartBarLine->
139             setBarLineCategory (
140                 msrBarLine::kBarLineCategoryHooklessEndingStart);
141
142         // set this barLine's category
143         barLine->
144             setBarLineCategory (
145                 msrBarLine::kBarLineCategoryHooklessEndingEnd);
146
147         // handle the repeat hookless ending end
148         handleRepeatHooklessEndingEnd (barLine);
149
150         barLineHasBeenHandled = true;
151     }
152
153     // forget about current repeat ending start barLine
154     fCurrentRepeatEndingStartBarLine = nullptr;
155 }
156 break;
157 } // switch
158
159 // set the barLine category to stand alone if not yet handled
160 if (! barLineHasBeenHandled) {
161     switch (fCurrentBarLineStyleKind) {
162     case msrBarLine::kBarLineStyleRegular:
163     case msrBarLine::kBarLineStyleDotted:
164     case msrBarLine::kBarLineStyleDashed:
165     case msrBarLine::kBarLineStyleHeavy:
166     case msrBarLine::kBarLineStyleLightLight:
167     case msrBarLine::kBarLineStyleLightHeavy:
168     case msrBarLine::kBarLineStyleHeavyLight:
169     case msrBarLine::kBarLineStyleHeavyHeavy:
170     case msrBarLine::kBarLineStyleTick:
171     case msrBarLine::kBarLineStyleShort:
172         barLine->
173             setBarLineCategory (
174                 msrBarLine::kBarLineCategoryStandalone);
175
176         // append the bar line to the current part
177         // ... ..
178

```

```

179         fCurrentPart->
180             appendBarLineToPart (barLine);
181
182         barLineHasBeenHandled = true;
183         break;
184
185     case msrBarLine::kBarLineStyleNone:
186         stringstream s;
187
188         s <<
189             "barLine " <<
190             barLine->asString () <<
191             " has no barLine style";
192
193         musicxmlWarning (
194             gGlobalServiceRunData->getInputSourceName (),
195             inputLineNumber,
196             //      __FILE__, __LINE__,
197             s.str ());
198         break;
199     } // switch
200 }
201
202 // has this barLine been handled?
203 if (! barLineHasBeenHandled) {
204     stringstream s;
205
206     s << left <<
207         "cannot handle a barLine containing: " <<
208         barLine->asString ();
209
210     msrInternalWarning (
211         gGlobalServiceRunData->getInputSourceName (),
212         inputLineNumber,
213         s.str ());
214 }
215
216 fOnGoingBarLine = false;
217 }

```

50.2 Translating repeats from MXSR to MSR

This is done in `src/passes/mxsr2msr/`.

50.3 Translating repeats from MSR to MSR

This is done in `src/passes/msr2msr/`.

50.4 Translating repeats from MSR to LPSR

This is done in `src/passes/msr2lpsr/`.

50.5 Translating repeats from LPSR to LilyPond

This is done in `src/passes/lpsr2lilypond/`.

Chapter 51

Voices handling

Voices are presented at section [19.29](#) [Voices], page [186](#).

51.1 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

51.2 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

51.3 Translating from MSR to MSR ([src/passes/msr2msr/](#))

51.4 Translating from MSR to LPSR ([src/passes/msr2lpsr/](#))

51.5 Translating from LPSR to LilyPond ([src/passes/lpsr2lilypond/](#))

Chapter 52

Staves handling

Staves are presented at section [19.27](#) [Staves], page [184](#).

52.1 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

52.2 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

52.3 Translating from MSR to MSR ([src/passes/msr2msr/](#))

52.4 Translating from MSR to LPSR ([src/passes/msr2lpsr/](#))

52.5 Translating from LPSR to LilyPond ([src/passes/lpsr2lilypond/](#))

Chapter 53

Parts handling

Parts are presented at section [19.26](#) [Parts], page 184.

53.1 Parts browsing

Method `msrPart::browseData ()` defined in `src/formats/msr/msrParts.h/.cpp` is peculiar in that it imposes a *partial order* on the part staves browsing:

```
1 void msrPart::browseData (basevisitor* v)
2 {
3     if (gGlobalMsrOahGroup->getTraceMsrVisitors ()) {
4         gLogStream <<
5             "% ==> msrPart::browseData ()" <<
6             endl;
7     }
8
9     #ifdef TRACING_IS_ENABLED // JMI
10    if (gGlobalMsrOahGroup->getTraceMsrVisitors ()) { // JMI TEMP
11        gLogStream <<
12            "+++++++ fPartAllStavesList.size(): " <<
13            fPartAllStavesList.size () <<
14            endl;
15
16        if (fPartAllStavesList.size ()) {
17            for (S_msrStaff staff : fPartAllStavesList) {
18                gLogStream <<
19                    endl <<
20                    "+++++++ staff: ++++++" <<
21                    " \\" << staff->getStaffName () << "\\" <<
22                    endl;
23            } // for
24        }
25
26        gLogStream <<
27            "+++++++ fPartNonHarmoniesNorFiguredBassStavesList.size(): " <<
28            fPartNonHarmoniesNorFiguredBassStavesList.size () <<
29            endl;
30
31        if (fPartNonHarmoniesNorFiguredBassStavesList.size ()) {
32            for (S_msrStaff staff : fPartNonHarmoniesNorFiguredBassStavesList) {
33                gLogStream <<
34                    endl <<
35                    "+++++++ staff: ++++++" <<
36                    " \\" << staff->getStaffName () << "\\" <<
37                    endl;
38            } // for
39        }
```

```

40 }
41 #endif
42
43 /* don't enforce any order here, leave it to the client thru sorting JMI */
44
45 // browse the part harmonies staff if any right now, JMI
46 // to place it before the corresponding part
47 if (fPartHarmoniesStaff) {
48     msrBrowser<msrStaff> browser (v);
49     browser.browse (*fPartHarmoniesStaff);
50 }
51
52 // browse all non harmonies and non figured bass staves
53 for (S_msrStaff staff : fPartNonHarmoniesNorFiguredBassStavesList) {
54     // browse the staff
55     msrBrowser<msrStaff> browser (v);
56     browser.browse (*staff);
57 } // for
58
59 // browse the part figured bass staff if any only now, JMI
60 // to place it after the corresponding part
61 if (fPartFiguredBassStaff) {
62     msrBrowser<msrStaff> browser (v);
63     browser.browse (*fPartFiguredBassStaff);
64 }
65
66 // // browse all the part staves JMI
67 // for (S_msrStaff staff : fPartAllStavesList) {
68 //     if (staff != fPartHarmoniesStaff && staff != fPartFiguredBassStaff) {
69 //         // browse the staff
70 //         msrBrowser<msrStaff> browser (v);
71 //         browser.browse (*staff);
72 //     }
73 // } // for
74 }

```

53.2 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

53.3 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

53.4 Translating from MSR to MSR ([src/passes/msr2msr/](#))

53.5 Translating from MSR to LPSR ([src/passes/msr2lpsr/](#))

53.6 Translating from LPSR to LilyPond ([src/passes/lpsr2lilypond/](#))

Chapter 54

Part groups handling

MusicFormats part groups are presented at chapter [19.25](#) [Part groups], page [184](#).

In MusicXML, part groups can overlap, even though no one seems ever to have needed that. That seems to be more a feature in the Finale handling of MusicXMLexport that a true musical need.

MSR does not support overlapping part group. Handling part groups is done in `src/passes/mxsr2msr/mxsr2msrTran` where overlapping groups are identified and rejected:

```
1 jacquesmenu@macmini > xml2ly partgroups/OverlappingPartGroups.xml
2 ### MusicXML ERROR ### partgroups/OverlappingPartGroups.xml:169:
3 There are overlapping part groups, namely:
4   '2' ==> PartGroup_6 ('2', partGroupName "1
5 2"), lines 164..169
6 and
7   '1' ==> PartGroup_2 ('1', partGroupName ""), lines 76..170
8
9 Please contact the maintainers of MusicFormats (see option '-c, -contact'):
10 either you found a bug in the xml2ly converter,
11 or this MusicXML data is the first-ever real-world case
12 of a score exhibiting overlapping part groups.
13 Exception caught: mfException:
14 There are overlapping part groups, namely:
15   '2' ==> PartGroup_6 ('2', partGroupName "1
16 2"), lines 164..169
17 and
18   '1' ==> PartGroup_2 ('1', partGroupName ""), lines 76..170
19
20 Please contact the maintainers of MusicFormats (see option '-c, -contact'):
21 either you found a bug in the xml2ly converter,
22 or this MusicXML data is the first-ever real-world case
23 of a score exhibiting overlapping part groups.
24
25 Error message(s) were issued for input line 169
26 ### xml2ly gIndenter final value: 1 ###
27 ### Conversion from MusicXML to LilyPond failed ###
```

Class `mxmlPartGroupDescr` contains:

```
1 struct mxmlPartGroupDescr : public smartable
2 {
3   /*
4    positions represent the order in which the parts appear in <part-list />
5   */
6
7   // ... ..
8
9   private:
10
```

```

11 // private fields
12 // -----
13
14 int                fStartInputLineNumber;
15 int                fStopInputLineNumber;
16
17 int                fPartGroupNumber; // may be reused later
18
19 S_msrPartGroup     fPartGroup;
20
21 int                fStartPosition;
22 int                fStopPosition;
23 };

```

Part groups numbers number re-used and they can be nested, so there is an implicit part group at the top of their hierarchy, attached to the class `msrScore`:

```

1 class EXP mxsr2msrSkeletonBuilder :
2 // ... ..
3
4 // an implicit part group has to be created to contain everything,
5 // since there can be parts out of any explicit part group
6 S_mxmlPartGroupDescr    fImplicitPartGroupDescr;
7 S_msrPartGroup          fImplicitPartGroup;
8
9 void                    createImplicitPartGroup ();
10
11 // part groups numbers can be re-used, they're no identifier
12 // we use a map to access them by part group number
13 int                    fPartGroupsCounter;
14 vector<S_mxmlPartGroupDescr>
15                        fPartGroupDescsVector;
16 map<int, S_mxmlPartGroupDescr>
17                        fAllPartGroupDescrsMap;
18 map<int, S_mxmlPartGroupDescr>
19                        fStartedPartGroupDescrsMap;
20
21 // ... ..

```


Chapter 55

Scores handling

Scores are presented at section [19.24](#) [Scores], page [183](#).

55.1 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

55.2 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

55.3 Translating from MSR to MSR ([src/passes/msr2msr/](#))

55.4 Translating from MSR to LPSR ([src/passes/msr2lpsr/](#))

55.5 Translating from LPSR to LilyPond ([src/passes/lpsr2lilypond/](#))

Chapter 56

Books handling

Books are presented at section [19.23](#) [Books], page [183](#).

56.1 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

56.2 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

56.3 Translating from MSR to MSR ([src/passes/msr2msr/](#))

56.4 Translating from MSR to LPSR ([src/passes/msr2lpsr/](#))

56.5 Translating from LPSR to LilyPond ([src/passes/lpsr2lilypond/](#))

Chapter 57

Ornaments handling

Ornaments are presented at section [19.40](#) [Ornaments], page [195](#).

57.1 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

57.2 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

57.3 Translating from MSR to MSR ([src/passes/msr2msr/](#))

57.4 Translating from MSR to LPSR ([src/passes/msr2lpsr/](#))

57.5 Translating from LPSR to LilyPond ([src/passes/lpsr2lilypond/](#))

Chapter 58

Ties handling

Ties are presented at section [19.41](#) [Ties], page [195](#).

58.1 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

58.2 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

58.3 Translating from MSR to MSR ([src/passes/msr2msr/](#))

58.4 Translating from MSR to LPSR ([src/passes/msr2lpsr/](#))

58.5 Translating from LPSR to LilyPond ([src/passes/lpsr2lilypond/](#))

Chapter 59

Dynamics handling

Dynamics are presented at section [19.42](#) [Dynamics], page [195](#).

59.1 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

59.2 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

59.3 Translating from MSR to MSR ([src/passes/msr2msr/](#))

59.4 Translating from MSR to LPSR ([src/passes/msr2lpsr/](#))

59.5 Translating from LPSR to LilyPond ([src/passes/lpsr2lilypond/](#))

Chapter 60

Beams handling

Beams are presented at section [19.43](#) [Beams], page [195](#).

60.1 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

60.2 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

60.3 Translating from MSR to MSR ([src/passes/msr2msr/](#))

60.4 Translating from MSR to LPSR ([src/passes/msr2lpsr/](#))

60.5 Translating from LPSR to LilyPond ([src/passes/lpsr2lilypond/](#))

Chapter 61

Slurs handling

Slurs are presented at section [19.44](#) [Slurs], page [195](#).

61.1 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

61.2 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

61.3 Translating from MSR to MSR ([src/passes/msr2msr/](#))

61.4 Translating from MSR to LPSR ([src/passes/msr2lpsr/](#))

61.5 Translating from LPSR to LilyPond ([src/passes/lpsr2lilypond/](#))

Chapter 62

Grace notes groups handling

Grace notes groups are presented at section [19.45](#) [Grace notes groups], page [195](#).

62.1 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

62.2 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

62.3 Translating from MSR to MSR ([src/passes/msr2msr/](#))

62.4 Translating from MSR to LPSR ([src/passes/msr2lpsr/](#))

62.5 Translating from LPSR to LilyPond ([src/passes/lpsr2lilypond/](#))

Chapter 63

Chords handling

Chords are presented at section [19.46](#) [Chords], page [195](#).

63.1 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

63.2 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

63.3 Translating from MSR to MSR ([src/passes/msr2msr/](#))

63.4 Translating from MSR to LPSR ([src/passes/msr2lpsr/](#))

63.5 Translating from LPSR to LilyPond ([src/passes/lpsr2lilypond/](#))

Chapter 64

Tuples handling

Tuples are presented at section [19.47](#) [Tuples], page [195](#).

64.1 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

64.2 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

64.3 Translating from MSR to MSR ([src/passes/msr2msr/](#))

64.4 Translating from MSR to LPSR ([src/passes/msr2lpsr/](#))

64.5 Translating from LPSR to LilyPond ([src/passes/lpsr2lilypond/](#))

Chapter 65

Harmonies handling

Harmonies are presented at section [19.49](#) [Harmonies], page [198](#).

The useful options here are:

- option `-trace-harmonies`, `-tharms`
- option `-display-msr-skeleton`, `-dmsrskel`
- option `-display-msr-1`, `-dmsr1`
- option `-display-msr-1-short`, `-dmsr1s` and option `-display-msr-1-details`, `-dmsr1d`
- option `-display-msr-2msr2`, `-dmsr2`
- option `-display-msr-2-short`, `-msr2s` and option `-display-msr-2-details`, `-dmsr2d`

Harmonies need special treatment since we need to determine their position in a harmony voice. This is different than MusicXML, where they are simply *drawn* at the current music position, so to say.

They are handled this way:

- harmonies are stored in class `msrNote`:
- they are also stored in class `msrPart`, class `msrChord` and class `msrTuplet` (denormalization);

In class `msrNote`, there is:

```
1  // harmonies
2  void                appendHarmonyToNoteHarmoniesList (
3                      S_msrHarmony harmony);
4
5  const list<S_msrHarmony>&
6      getNoteHarmoniesList () const
7      { return fNoteHarmoniesList; }
8
9  // ... ..
10
11 // harmonies
12 // -----
13
14 list<S_msrHarmony>    fNoteHarmoniesList;
15
16 // ... ..
```

65.1 Harmonies staves and voices

Every class `msrVoice` instance in `MusicFormats` belongs to an class `msrStaff` instance. Staves are created specifically to hold harmonies voices, using specific numbers defined in `src/formats/msr/msrParts.h`:

```

1 public:
2
3     // constants
4     // -----
5
6     #define msrPart::K_PART_HARMONIES_STAFF_NUMBER      10
7     #define msrPart::K_PART_HARMONIES_VOICE_NUMBER     11

```

In class `msrStaff`, there is:

```

1 void registerHarmoniesVoiceByItsNumber (
2         int inputLineNumber,
3         S_msrVoice voice);

```

Class `msrPart` also contains:

```

1 // harmonies
2
3 S_msrVoice createPartHarmoniesVoice (
4         int inputLineNumber,
5         string currentMeasureNumber);
6
7 void appendHarmonyToPart (
8         S_msrVoice harmonySupplierVoice,
9         S_msrHarmony harmony);
10
11 void appendHarmonyToPartClone (
12         S_msrVoice harmonySupplierVoice,
13         S_msrHarmony harmony);

```

```

1 // harmonies
2
3 S_msrStaff fPartHarmoniesStaff;
4 S_msrVoice fPartHarmoniesVoice;

```

65.2 Harmonies staves creation

This is done in `src/passes/mxsr2msr/mxsr2msrSkeletonBuilder.cpp.h/.cpp`:

```

1 S_msrVoice mxsr2msrSkeletonBuilder::createPartHarmoniesVoiceIfNotYetDone (
2     int inputLineNumber,
3     S_msrPart part)
4 {
5     // is the harmonies voice already present in part?
6     S_msrVoice
7     partHarmoniesVoice =
8     part->
9     getPartHarmoniesVoice ();
10
11     if (! partHarmoniesVoice) {
12         // create the harmonies voice and append it to the part
13         partHarmoniesVoice =
14         part->
15         createPartHarmoniesVoice (
16             inputLineNumber,
17             fCurrentMeasureNumber);

```

```

18 }
19
20 return partHarmoniesVoice;
21 }

```

Method `msrPartcreatePartHarmoniesVoice` creates the part harmonies staff and the part harmonies voice, and then registers the latter in the former:

```

1 S_msrVoice msrPart::createPartHarmoniesVoice (
2     int     inputLineNumber,
3     string  currentMeasureNumber)
4 {
5     // ... ..
6
7     // create the part harmonies staff
8     int partHarmoniesStaffNumber =
9         msrPart::K_PART_HARMONIES_STAFF_NUMBER;
10
11    // ... ..
12
13    fPartHarmoniesStaff =
14        addHarmoniesStaffToPart (
15            inputLineNumber);
16
17    // ... ..
18
19    // create the part harmonies voice
20    int partHarmoniesVoiceNumber =
21        msrPart::K_PART_HARMONIES_VOICE_NUMBER;
22
23    // ... ..
24
25    fPartHarmoniesVoice =
26        msrVoice::create (
27            inputLineNumber,
28            msrVoiceKind::kVoiceKindHarmonies,
29            partHarmoniesVoiceNumber,
30            msrVoiceCreateInitialLastSegmentKind::kCreateInitialLastSegmentYes,
31            fPartHarmoniesStaff);
32
33    // register the part harmonies voice in part harmonies staff
34    fPartHarmoniesStaff->
35        registerVoiceInStaff (
36            inputLineNumber,
37            fPartHarmoniesVoice);
38
39    // ... ..
40
41    return fPartHarmoniesVoice;
42 }

```

65.3 Harmonies creation

There are several methods for harmonies creation:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src > grep create formats/msr/msrHarmonies.h
2     static SMARTP<msrHarmonyDegree> create (
3     static SMARTP<msrHarmony> createWithoutVoiceUplink (
4     SMARTP<msrHarmony> createHarmonyNewbornClone (
5 //     SMARTP<msrHarmony> createHarmonyDeepClone ( // JMI ???
6     static SMARTP<msrHarmony> createWithVoiceUplink (

```

65.4 Translating harmonies from MXSR to MSR

This is done in `src/passes/mxsr2msr/`.

The MSR score skeleton created in `src/passes/mxsr2msr/mxsr2msrSkeletonBuilder.h/.cpp` contains the part groups, parts, staves and voices, as well as the number of measures. The voices do not contain any music elements yet.

A harmony belongs to a `<part/>` in MusicXML, but we sometimes need to have it attached to a note. When visiting an `S_harmony` element, field `mxsr2msrSkeletonBuilder::fThereAreHarmoniesToBeAttachedToCurrentNote` is used to account for that:

```

1 void mxsr2msrSkeletonBuilder::visitStart ( S_harmony& elt )
2 {
3     #ifdef TRACING_IS_ENABLED
4         if (gGlobalMxsrOahGroup->getTraceMxsrVisitors ()) {
5             gLogStream <<
6                 "--> Start visiting S_harmony" <<
7                 ", harmoniesVoicesCounter = " << fHarmoniesVoicesCounter <<
8                 ", line " << elt->getInputLineNumber () <<
9                 endl;
10        }
11    #endif
12
13    /* JMI ???
14       several harmonies can be attached to a given note,
15       leading to as many harmonies voices in the current part
16    */
17
18    // take harmonies voice into account
19    ++fHarmoniesVoicesCounter; // UNUSED JMI
20
21    fThereAreHarmoniesToBeAttachedToCurrentNote = true;
22 }

```

Upon the second visit of class `msrNote`, the part harmonies voice is created if harmonies are not to be ignored due to option `-ignore-harmonies`, `-oharms` and it has not been created yet:

```

1 void mxsr2msrSkeletonBuilder::visitEnd ( S_note& elt )
2 {
3     // ... ..
4
5     // are there harmonies attached to the current note?
6     if (fThereAreHarmoniesToBeAttachedToCurrentNote) {
7         if (gGlobalMxsr2msrOahGroup->getIgnoreHarmonies ()) {
8             #ifdef TRACING_IS_ENABLED
9                 if (gGlobalTracingOahGroup->getTraceHarmonies ()) {
10                    gLogStream <<
11                        "Ignoring the harmonies" <<
12                        ", line " <<
13                        inputLineNumber <<
14                        endl;
15                }
16            #endif
17        }
18        else {
19            // create the part harmonies voice if not yet done
20            S_msrVoice
21                partHarmoniesVoice =
22                createPartHarmoniesVoiceIfNotYetDone (
23                    inputLineNumber,
24                    fCurrentPart);
25        }
26
27        fThereAreHarmoniesToBeAttachedToCurrentNote = false;

```

```

28 }
29
30 // ... ..
31 }

```

Creating the part harmonies voice is delegated to the part:

```

1 S_msrVoice mxsr2msrSkeletonBuilder::createPartHarmoniesVoiceIfNotYetDone (
2     int         inputLineNumber,
3     S_msrPart   part)
4 {
5     // is the harmonies voice already present in part?
6     S_msrVoice
7     partHarmoniesVoice =
8     part->
9     getPartHarmoniesVoice ();
10
11     if (! partHarmoniesVoice) {
12         // create the harmonies voice and append it to the part
13         partHarmoniesVoice =
14         part->
15         createPartHarmoniesVoice (
16             inputLineNumber,
17             fCurrentMeasureNumber);
18     }
19
20     return partHarmoniesVoice;
21 }

```

65.5 Translating harmonies from MXSR to MSR

This is done in `src/passes/mxsr2msr/`.

This is where the class `msrHarmony` instances are created.

65.5.1 First S_harmony visit

The first visit of `S_harmony` initializes the fields storing values to be gathered visiting subelements:

```

1 void mxsr2msrTranslator::visitStart ( S_harmony& elt )
2 {
3     int inputLineNumber =
4     elt->getInputLineNumber ();
5
6     #ifdef TRACING_IS_ENABLED
7     if (gGlobalMxsrOahGroup->getTraceMxsrVisitors ()) {
8         gLogStream <<
9         "--> Start visiting S_harmony" <<
10        ", line " << inputLineNumber <<
11        endl;
12    }
13    #endif
14
15    ++fHarmoniesVoicesCounter;
16
17    fCurrentHarmonyInputLineNumber      = inputLineNumber;
18
19    fCurrentHarmonyRootDiatonicPitchKind = msrDiatonicPitchKind::k_NoDiatonicPitch;
20    fCurrentHarmonyRootAlterationKind   = msrAlterationKind::k_AlterationNatural;
21    fCurrentHarmonyKind                 = msrHarmonyKind::k_NoHarmony;
22    fCurrentHarmonyKindText              = "";

```

```

23     fCurrentHarmonyInversion                = K_HARMONY_NO_INVERSION;
24     fCurrentHarmonyBassDiatonicPitchKind    = msrDiatonicPitchKind::k_NoDiatonicPitch;
25     fCurrentHarmonyBassAlterationKind       = msrAlterationKind::kAlterationNatural;
26     fCurrentHarmonyDegreeValue              = -1;
27     fCurrentHarmonyDegreeAlterationKind     = msrAlterationKind::kAlterationNatural;
28
29     fCurrentHarmonyWholeNotesOffset = rational (0, 1);
30
31     fOnGoingHarmony = true;
32 }

```

65.5.2 Second S_harmony visit

Upon the second visit of `S_harmony`, a class `msrHarmony` instance is created, populated and appended to `mxsr2msrTranslator.fPendingHarmoniesList`.

The voice uplink will be set later, hence the use of method `msrHarmony::createWithoutVoiceUplink ()`:

```

1 void mxsr2msrTranslator::visitEnd ( S_harmony& elt )
2 {
3     // ... ..
4
5     if (gGlobalMxsr2msrOahGroup->getIgnoreHarmonies ()) {
6         #ifdef TRACING_IS_ENABLED
7             if (gGlobalTracingOahGroup->getTraceHarmonies ()) {
8                 gLogStream <<
9                     "Ignoring harmony" <<
10                    ", line " <<
11                    inputLineNumber <<
12                    endl;
13             }
14         #endif
15     }
16     else {
17         // create the harmony
18         #ifdef TRACING_IS_ENABLED
19             if (gGlobalTracingOahGroup->getTraceHarmoniesDetails ()) {
20                 gLogStream <<
21                     "Creating a harmony" <<
22                     ", line " << inputLineNumber << ":" <<
23                     endl;
24             }
25             // ... ..
26         }
27         #endif
28
29         S_msrHarmony
30         harmony =
31             msrHarmony::createWithoutVoiceUplink (
32                 fCurrentHarmonyInputLineNumber,
33                 // no harmoniesVoiceUplink yet
34
35                 fCurrentHarmonyRootQuarterTonesPitchKind,
36
37                 fCurrentHarmonyKind,
38                 fCurrentHarmonyKindText,
39
40                 fCurrentHarmonyInversion,
41
42                 fCurrentHarmonyBassQuarterTonesPitchKind,
43
44                 rational (1, 1),           // harmonySoundingWholeNotes,
45                                           // will be set upon next note handling
46                 rational (1, 1),           // harmonyDisplayWholeNotes,
47                                           // will be set upon next note handling

```



```

48         fCurrentHarmoniesStaffNumber,
49         msrTupletFactor (1, 1),      // will be set upon next note handling
50         fCurrentHarmonyWholeNotesOffset);
51
52     // append pending harmony degrees if any to the harmony
53     if (! fCurrentHarmonyDegreesList.size ()) {
54 #ifdef TRACING_IS_ENABLED
55         if (gGlobalTracingOahGroup->getTraceHarmoniesDetails ()) {
56             musicxmlWarning (
57                 gGlobalServiceRunData->getInputSourceName (),
58                 inputLineNumber,
59                 "harmony has no degrees contents");
60         }
61 #endif
62     }
63
64     else {
65         // handle harmony degrees if any
66         while (fCurrentHarmonyDegreesList.size ()) {
67             S_msrHarmonyDegree
68             harmonyDegree =
69                 fCurrentHarmonyDegreesList.front ();
70
71             // ... ..
72
73             // append it to harmony's degrees list
74             harmony->
75                 appendHarmonyDegreeToHarmony (
76                     harmonyDegree);
77
78             // remove it from the list
79             fCurrentHarmonyDegreesList.pop_front ();
80         } // while
81     }
82
83     // attach the current frame if any to the harmony
84     if (fCurrentFrame) {
85         harmony->setHarmonyFrame (fCurrentFrame);
86     }
87
88     // append the harmony to the pending harmonies list
89     fPendingHarmoniesList.push_back (harmony);
90 }
91
92 fOnGoingHarmony = false;
93 }

```

65.5.3 Attaching msrHarmony instances to notes

msrHarmony

The contents of `mxsr2msrTranslator::fPendingHarmoniesList` is attached to the class `msrNote` instance in method `mxsr2msrTranslator::populateNote ()`:

```

1 void mxsr2msrTranslator::populateNote (
2     int         inputLineNumber,
3     S_msrNote newNote)
4 {
5     // ... ..
6
7     // handle the pending harmonies if any
8     if (fPendingHarmoniesList.size ()) {
9         // get voice to insert harmonies into
10        S_msrVoice

```

```

11     voiceToInsertHarmoniesInto =
12         fCurrentPart->
13             getPartHarmoniesVoice ();
14
15     // ... ..
16
17     handlePendingHarmonies (
18         newNote,
19         voiceToInsertHarmoniesInto);
20
21     // reset harmony counter
22     fHarmoniesVoicesCounter = 0;
23 }
24 }

```

65.5.4 Populating msrHarmony instances

msrHarmony

The class `msrHarmony` instances are populated further in `src/formats/msr/mxsr2msrTranslator.cpp` and attached to the note by method `msrNote::appendHarmonyToNoteHarmoniesList ()`:

```

1 void mxsr2msrTranslator::handlePendingHarmonies (
2     S_msrNote newNote,
3     S_msrVoice voiceToInsertInto)
4 {
5     // ... ..
6
7     rational
8     newNoteSoundingWholeNotes =
9         newNote->
10             getNoteSoundingWholeNotes (),
11     newNoteDisplayWholeNotes =
12         newNote->
13             getNoteDisplayWholeNotes ();
14
15     while (fPendingHarmoniesList.size ()) { // recompute at each iteration
16         S_msrHarmony
17         harmony =
18             fPendingHarmoniesList.front ();
19
20         /*
21          MusicXML harmonies don't have a duration,
22          and MSR could follow this line, but LilyPond needs one...
23          So:
24          - we register all harmonies with the duration of the next note
25          - they will be sorted by position in the measure in finalizeMeasure(),
26            at which time their duration may be shortened
27            so that the offsets values are enforced
28            and they don't overflow the measure
29          It is VITAL that harmonies measures be finalized
30          AFTER the corresponding measure in the regular voice,
31          since the current sounding whole notes of the latter is needed for that
32          */
33
34         // set the harmony's sounding whole notes
35         harmony->
36             setHarmonySoundingWholeNotes (
37                 newNoteSoundingWholeNotes);
38
39         // set the harmony's display whole notes JMI useless???
40         harmony->
41             setHarmonyDisplayWholeNotes (
42                 newNoteDisplayWholeNotes);

```

```

43
44 // set the harmony's tuplet factor
45 harmony->
46   setHarmonyTupletFactor (
47     msrTupletFactor (
48       fCurrentNoteActualNotes,
49       fCurrentNoteNormalNotes));
50
51 // attach the harmony to newNote
52 newNote->
53   appendHarmonyToNoteHarmoniesList (
54     harmony);
55
56 // get the part harmonies voice
57 S_msrVoice
58   partHarmoniesVoice =
59     fCurrentPart->
60     getPartHarmoniesVoice ();
61
62 // sanity check
63 mfAssert (
64   __FILE__, __LINE__,
65   partHarmoniesVoice != nullptr,
66   "partHarmoniesVoice is null");
67
68 // set the harmony's voice upLink
69 // only now that we know which harmonies voice will contain it
70 harmony->
71   setHarmoniesVoiceUpLink (
72     partHarmoniesVoice);
73
74 /* JMI CAFE
75 // append the harmony to the part harmonies voice
76 partHarmoniesVoice->
77   appendHarmonyToVoice (
78     harmony);
79 */
80 // don't append the harmony to the part harmonies voice // BLARK
81 // before the note itself has been appended to the voice
82
83 // remove the harmony from the list
84 fPendingHarmoniesList.pop_front ();
85 } // while
86 }

```

65.5.5 First S_harmony visit

msrHarmony

Method `msrNote::appendHarmonyToNoteHarmoniesList ()` is where the harmony's note uplink is set:

```

1 void msrNote::appendHarmonyToNoteHarmoniesList (S_msrHarmony harmony)
2 {
3 #ifdef TRACING_IS_ENABLED
4   if (gGlobalTracingOahGroup->getTraceHarmonies ()) {
5     gLogStream <<
6       "Appending harmony " <<
7       harmony->asString () <<
8       " to the harmonies list of " <<
9       asString () <<
10      ", line " << fInputLineNumber <<
11      endl;
12   }
13 #endif

```

```

14
15 // update the harmony whole notes if it belongs to a tuplet ??? utf8.xml JMI
16
17 fNoteHarmoniesList.push_back (harmony);
18
19 // register this note as the harmony note upLink
20 harmony->
21     setHarmonyNoteUpLink (this);
22 }

```

When a harmony is attached to a note that is a chord member, we have to attach it to the chord too, to facilitate setting its position in measure when setting the chord's one.

```

1 void mxsr2msrTranslator::copyNoteHarmoniesToChord (
2     S_msrNote note, S_msrChord chord)
3 {
4     // copy note's harmony if any from the first note to chord
5
6     const list<S_msrHarmony>&
7         noteHarmoniesList =
8         note->getNoteHarmoniesList ();
9
10    if (noteHarmoniesList.size ()) {
11        list<S_msrHarmony>::const_iterator i;
12        for (i=noteHarmoniesList.begin (); i!=noteHarmoniesList.end (); ++i) {
13            S_msrHarmony harmony = (*i);
14
15#ifdef TRACING_IS_ENABLED
16            if (gGlobalTracingOahGroup->getTraceHarmonies ()) {
17                gLogStream <<
18                    "Copying harmony '" <<
19                    harmony->asString () <<
20                    "' from note " << note->asString () <<
21                    " to chord '" << chord->asString () <<
22                    "'" <<
23                endl;
24            }
25#endif
26
27            chord->
28                appendHarmonyToChord (harmony);
29
30        } // for
31    }
32 }

```

65.5.6 Inserting msrHarmony instances in the part harmonies voice

msrHarmony

Inserting the harmonies in the part harmonies voice is done in method `msrVoice::appendNoteToVoice ()` in `src/formats/msr/msrNotes.cpp`:

```

1 void msrVoice::appendNoteToVoice (S_msrNote note)
2 {
3     // ... ..
4
5     // are there harmonies attached to this note? // BLARK
6     const list<S_msrHarmony>&
7         noteHarmoniesList =
8         note->
9             getNoteHarmoniesList ();
10 }

```

```

11  if (noteHarmoniesList.size ()) {
12      // get the current part's harmonies voice
13      S_msrVoice
14      partHarmoniesVoice =
15      part->
16      getPartHarmoniesVoice ();
17
18      for (S_msrHarmony harmony : noteHarmoniesList) {
19          // append the harmony to the part harmonies voice
20          partHarmoniesVoice->
21          appendHarmonyToVoice (
22              harmony);
23      } // for
24  }
25
26  // ... ..
27  };

```

65.6 Translating harmonies from MSR to MSR

This is done in `src/passes/msr2msr/`.

In `src/passes/msr2msr/msr2msrTranslator.cpp`, a newborn clone of the harmony is created upon the first visit, stored in `msr2msrTranslatorfCurrentHarmonyClone`, and appended to the current non grace note clone, the current chord clone or to the current voice clone, if the latter is a harmonies voice:

```

1  void msr2msrTranslator::visitStart (S_msrHarmony& elt)
2  {
3      #ifdef TRACING_IS_ENABLED
4          if (gGlobalMsrOahGroup->getTraceMsrVisitors ()) {
5              gLogStream <<
6                  "--> Start visiting msrHarmony '" <<
7                  elt->asString () <<
8                  ", fOnGoingNonGraceNote: " << fOnGoingNonGraceNote <<
9                  ", fOnGoingChord: " << fOnGoingChord <<
10                 ", fOnGoingHarmoniesVoice: " << fOnGoingHarmoniesVoice <<
11                 ", fOnGoingHarmony: " << fOnGoingHarmony <<
12                 "'", line " << elt->getInputLineNumber () <<
13                 endl;
14          }
15      #endif
16
17      // create a harmony new born clone
18      fCurrentHarmonyClone =
19      elt->
20      createHarmonyNewbornClone (
21          fCurrentVoiceClone);
22
23      if (fOnGoingNonGraceNote) {
24          // register the harmony in the current non-grace note clone
25          fCurrentNonGraceNoteClone->
26          appendHarmonyToNoteHarmoniesList (
27              fCurrentHarmonyClone);
28
29          // don't append the harmony to the part harmony,
30          // this has been done in pass2b // JMI ???
31      }
32
33      else if (fOnGoingChord) {
34          // register the harmony in the current chord clone
35          fCurrentChordClone->
36          appendHarmonyToChord (fCurrentHarmonyClone); // JMI
37      }

```

```

38
39 else if (fOnGoingHarmoniesVoice) {
40 /* JMI
41 // get the harmony whole notes offset
42 rational
43     harmonyWholeNotesOffset =
44     elt->getHarmonyWholeNotesOffset ();
45
46 // is harmonyWholeNotesOffset not equal to 0?
47 if (harmonyWholeNotesOffset.getNumerator () != 0) {
48 // create skip with duration harmonyWholeNotesOffset
49 S_msrNote
50     skip =
51     msrNote::createSkipNote (
52         elt->                getInputLineNumber (),
53         "666", // JMI elt->                getHarmoniesMeasureNumber (),
54         elt->                getHarmonyDisplayWholeNotes (), // would be 0/1 otherwise
55
56         JMI
57         elt->                getHarmonyDisplayWholeNotes (),
58         0, // JMI elt->                getHarmonyDotsNumber (),
59         fCurrentVoiceClone-> getRegularVoiceStaffSequentialNumber (), // JMI
60         fCurrentVoiceClone-> getVoiceNumber ());
61
62 // append it to the current voice clone
63 // to 'push' the harmony aside
64 fCurrentVoiceClone->
65     appendNoteToVoice (skip);
66 }
67 */
68
69 // append the harmony to the current voice clone
70 fCurrentVoiceClone->
71     appendHarmonyToVoiceClone (
72         fCurrentHarmonyClone);
73 }
74
75 else {
76     stringstream s;
77
78     s <<
79     "harmony is out of context, cannot be handled: '" <<
80     elt->asShortString () <<
81     "'";
82
83     msrInternalError (
84         gGlobalServiceRunData->getInputSourceName (),
85         elt->getInputLineNumber (),
86         __FILE__, __LINE__,
87         s.str ());
88 }
89
90 fOnGoingHarmony = true;
91 }

```

There are only fields updates upon the second visit:

```

1 void msr2msrTranslator::visitEnd (S_msrHarmony& elt)
2 {
3 #ifdef TRACING_IS_ENABLED
4     if (gGlobalMsrOahGroup->getTraceMsrVisitors ()) {
5         gLogStream <<
6         "--> End visiting msrHarmony '" <<
7         elt->asString () <<
8         "' <<
9         ", line " << elt->getInputLineNumber () <<
10        endl;

```

```

11 }
12 #endif
13
14 fCurrentHarmonyClone = nullptr;
15 fOnGoingHarmony = false;
16 }

```

65.7 Translating harmonies from MSR to LPSR

This is done in `src/passes/msr2lpsr/`.

The same occurs in `src/passes/msr2lpsr/msr2lpsrTranslator.cpp`: a newborn clone of the harmony is created and appended to the current non grace note clone, the current chord clone or to the current voice clone, if the latter is a harmonies voice: :

```

1 void msr2lpsrTranslator::visitStart (S_msrHarmony& elt)
2 {
3 #ifdef TRACING_IS_ENABLED
4   if (gGlobalMsrOahGroup->getTraceMsrVisitors ()) {
5     gLogStream <<
6       "--> Start visiting msrHarmony '" <<
7       elt->asString () <<
8       ", onGoingNonGraceNote: " << fOnGoingNonGraceNote <<
9       ", onGoingChord: " << fOnGoingChord <<
10      ", onGoingHarmoniesVoice: " << fOnGoingHarmoniesVoice <<
11      ", onGoingHarmony: " << fOnGoingHarmony <<
12      "', line " << elt->getInputLineNumber () <<
13      endl;
14   }
15 #endif
16
17   // create a harmony new born clone
18   fCurrentHarmonyClone =
19     elt->
20     createHarmonyNewbornClone (
21       fCurrentVoiceClone);
22
23   if (fOnGoingNonGraceNote) {
24     // register the harmony in the current non-grace note clone
25     fCurrentNonGraceNoteClone->
26       appendHarmonyToNoteHarmoniesList (
27         fCurrentHarmonyClone);
28
29     // don't append the harmony to the part harmony,
30     // this has been done in pass2b // JMI ???
31   }
32
33   else if (fOnGoingChord) {
34     // register the harmony in the current chord clone
35     fCurrentChordClone->
36       appendHarmonyToChord (fCurrentHarmonyClone); // JMI
37   }
38
39   else if (fOnGoingHarmoniesVoice) {
40     /* JMI
41     // get the harmony whole notes offset
42     rational
43       harmonyWholeNotesOffset =
44       elt->getHarmonyWholeNotesOffset ();
45
46     // is harmonyWholeNotesOffset not equal to 0?
47     if (harmonyWholeNotesOffset.getNumerator () != 0) {
48       // create skip with duration harmonyWholeNotesOffset

```

```

49     S_msrNote
50     skip =
51         msrNote::createSkipNote (
52             elt->                getInputLineNumber (),
53             "666", // JMI elt->                getHarmoniesMeasureNumber (),
54             elt->                getHarmonyDisplayWholeNotes (), // would be 0/1 otherwise
55     JMI
56             elt->                getHarmonyDisplayWholeNotes (),
57             0, // JMI elt->                getHarmonyDotsNumber (),
58             fCurrentVoiceClone-> getRegularVoiceStaffSequentialNumber (), // JMI
59             fCurrentVoiceClone-> getVoiceNumber ());
60
61     // append it to the current voice clone
62     // to 'push' the harmony aside
63     fCurrentVoiceClone->
64         appendNoteToVoice (skip);
65 }
66
67 /*
68 // append the harmony to the current voice clone
69 fCurrentVoiceClone->
70     appendHarmonyToVoiceClone (
71         fCurrentHarmonyClone);
72 }
73
74 else {
75     stringstream s;
76
77     s <<
78     "harmony is out of context, cannot be handled: '" <<
79     elt->asShortString () <<
80     "'";
81
82     msrInternalError (
83         gGlobalServiceRunData->getInputSourceName (),
84         elt->getInputLineNumber (),
85         __FILE__, __LINE__,
86         s.str ());
87 }
88
89 fOnGoingHarmony = true;
90 }

```


Here too, there are only fields updates upon the second visit of `S_msrHarmony` instances:

```

1 void msr2lpsrTranslator::visitEnd (S_msrHarmony& elt)
2 {
3 #ifdef TRACING_IS_ENABLED
4     if (gGlobalMsrOahGroup->getTraceMsrVisitors ()) {
5         gLogStream <<
6             "--> End visiting msrHarmony '" <<
7             elt->asString () <<
8             "' " <<
9             ", line " << elt->getInputLineNumber () <<
10            endl;
11    }
12 #endif
13
14    fCurrentHarmonyClone = nullptr;
15    fOnGoingHarmony = false;
16 }

```

65.8 Translating harmonies from LPSR to LilyPond

This is done in `src/passes/lpsr2lilypond/`.

There is only one visit of class `msrHarmony` instances in `src/passes/lpsr2lilypond/lpsr2lilypondTranslator.cpp`

The LilyPond code is generated only if the harmony belongs to a voice: this is where denormalization ends in the workflow:

```

1 void lpsr2lilypondTranslator::visitStart (S_msrHarmony& elt)
2 {
3 #ifdef TRACING_IS_ENABLED
4     {
5         Bool
6         traceMsrVisitors =
7             gGlobalMsrOahGroup->
8             getTraceMsrVisitors (),
9         generateMsrVisitingInformation =
10            gGlobalLpsr2lilypondOahGroup->
11            getGenerateMsrVisitingInformation ();
12
13         if (traceMsrVisitors || generateMsrVisitingInformation) {
14             stringstream s;
15
16             s <<
17                 "% --> Start visiting msrHarmony '" <<
18                 elt->asString () <<
19                 "' " <<
20                 ", fOnGoingNotesStack.size () = " <<
21                 fOnGoingNotesStack.size () <<
22                 ", fOnGoingChord = " <<
23                 fOnGoingChord <<
24                 ", fOnGoingHarmoniesVoice = " <<
25                 fOnGoingHarmoniesVoice <<
26                 ", line " << elt->getInputLineNumber () <<
27                endl;
28
29             if (traceMsrVisitors) {
30                 gLogStream << s.str ();
31             }
32
33             if (generateMsrVisitingInformation) {
34                 fLilypondCodeStream << s.str ();
35             }
36         }
37     }
38 }

```

```

37     }
38 #endif
39
40     if (fOnGoingNotesStack.size () > 0) {
41         /* JMI
42 #ifdef TRACING_IS_ENABLED
43         if (gGlobalTracingOahGroup->getTraceHarmonies ()) {
44             fLilypondCodeStream <<
45                 "%{ fOnGoingNotesStack.size () S_msrHarmony JMI " <<
46                 elt->asString () <<
47                 " %}" <<
48                 endl;
49         }
50 #endif
51 */
52     }
53
54     else if (fOnGoingChord) { // JMI
55     }
56
57     else if (fOnGoingHarmoniesVoice) {
58         // actual LilyPond code generation
59         fLilypondCodeStream <<
60             harmonyAsLilypondString (elt) <<
61             ' ';
62
63         // generate the input line number as comment if relevant
64         if (
65             gGlobalLpsr2lilypondOahGroup->getInputLineNumbers ()
66             ||
67             gGlobalLpsr2lilypondOahGroup->getGeneratePositionsInMeasures ()
68         ) {
69             generateInputLineNumberAndOrPositionInMeasureAsAComment (
70                 elt);
71         }
72     }
73 }

```

Chapter 66

Figured bass elements handling

Figured bass elements are presented at section [19.50](#) [Figured bass elements], page [198](#).

The useful options here are:

- option `-trace-figured-bass`, `-tfigbass`
- option `-display-msr-skeleton`, `-dmsrskel`
- option `-display-msr-1`, `-dmsr1`
- option `-display-msr-1-short`, `-dmsr1s` and option `-display-msr-1-details`, `-dmsr1d`
- option `-display-msr-2`, `-dmsr2`
- option `-display-msr-2-short`, `-dmsr2s` and option `-display-msr-2-details`, `-dmsr2d`

Figured bass elements need special treatment since we need to determine their position in a figured bass voice. This is different than MusicXML, where they are simply *drawn* at the current music position, so to say.

They are handled this way:

- figured bass elements are stored in class `msrNote`:
- they are also stored in class `msrPart` and class `msrChord` and class `msrTuplet` (denormalization);

In class `msrNote`, there is:

```
1  // figured bass
2  void                                appendFiguredBassToNoteFiguredBassElementsList (
3                                     S_msrFiguredBassElement figuredBass);
4
5  const list<S_msrFiguredBassElement>&
6      getNoteFiguredBassElementsList () const
7      { return fNoteFiguredBassElementsList; }
8
9  // ... ..
10
11 // figured bass
12 // -----
13
14 list<S_msrFiguredBassElement>
15     fNoteFiguredBassElementsList;
```

66.1 Figured bass staves and voices

Every class `msrVoice` instance in `MusicFormats` belongs to an class `msrStaff` instance. Staves are created specifically to hold figured bass voices, using specific numbers defined in `src/formats/msr/msrParts.h`:

```

1 public:
2
3     // constants
4     // -----
5
6     // ... ..
7
8     #define msrPart::K_PART_FIGURED_BASS_STAFF_NUMBER  20
9     #define msrPart::K_PART_FIGURED_BASS_VOICE_NUMBER  21

```

In class `msrStaff`, there is:

```

1 void registerFiguredBassVoiceByItsNumber (
2     int inputLineNumber,
3     S_msrVoice voice);

```

Class `msrPart` also contains:

```

1 // figured bass
2
3 S_msrVoice createPartFiguredBassVoice (
4     int inputLineNumber,
5     string currentMeasureNumber);
6
7 void appendFiguredBassToPart (
8     S_msrVoice figuredBassSupplierVoice,
9     S_msrFiguredBassElement figuredBass);
10
11 void appendFiguredBassToPartClone (
12     S_msrVoice figuredBassSupplierVoice,
13     S_msrFiguredBassElement figuredBass);

```

```

1 // figured bass
2
3 S_msrStaff fPartFiguredBassStaff;
4 S_msrVoice fPartFiguredBassVoice;

```

66.2 Figured bass staves creation

This is done in `src/passes/mxsr2msr/mxsr2msrSkeletonBuilder.cpp.h/.cpp`:

```

1 S_msrVoice mxsr2msrSkeletonBuilder::createPartFiguredBassVoiceIfNotYetDone (
2     int inputLineNumber,
3     S_msrPart part)
4 {
5     // is the figured bass voice already present in part?
6     S_msrVoice
7     partFiguredBassVoice =
8     part->
9     getPartFiguredBassVoice ();
10
11     if (! partFiguredBassVoice) {
12         // create the figured bass voice and append it to the part
13         partFiguredBassVoice =
14         part->
15         createPartFiguredBassVoice (

```

```

16         inputLineNumber,
17         fCurrentMeasureNumber);
18     }
19
20     return partFiguredBassVoice;
21 }

```

Method `msrPart::createPartFiguredBassVoice ()` creates the part figured bass staff and the part figured bass voice, and then registers the latter in the former:

```

1 S_msrVoice msrPart::createPartFiguredBassVoice (
2     int     inputLineNumber,
3     string  currentMeasureNumber)
4 {
5     // ... ..
6
7     // create the part figured bass staff
8     int partFiguredBassStaffNumber =
9         msrPart::K_PART_FIGURED_BASS_STAFF_NUMBER;
10
11    // ... ..
12
13    fPartFiguredBassStaff =
14        addHFiguredBassStaffToPart (
15            inputLineNumber);
16
17    // ... ..
18
19    // create the figured bass voice
20    int partFiguredBassVoiceNumber =
21        msrPart::K_PART_FIGURED_BASS_VOICE_NUMBER;
22
23    // ... ..
24
25    fPartFiguredBassVoice =
26        msrVoice::create (
27            inputLineNumber,
28            msrVoiceKind::kVoiceKindFiguredBass,
29            partFiguredBassVoiceNumber,
30            msrVoiceCreateInitialLastSegmentKind::kCreateInitialLastSegmentYes,
31            fPartFiguredBassStaff);
32
33    // register the figured bass voice in the part figured bass staff
34    fPartFiguredBassStaff->
35        registerVoiceInStaff (
36            inputLineNumber,
37            fPartFiguredBassVoice);
38
39    // ... ..
40
41    return fPartFiguredBassVoice;
42 }

```

66.3 Figured bass elements creation

There several methods for Figured bass elements creation:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src > grep create formats/msr/
   msrFiguredBassElements.h
2     static SMARTP<msrBassFigure> create (
3     SMARTP<msrBassFigure> createFigureNewbornClone (
4 //     SMARTP<msrBassFigure> createFigureDeepClone ( // JMI ???
5     static SMARTP<msrFiguredBassElement> create (

```

```

6 static SMARTP<msrFiguredBassElement> create (
7 SMARTP<msrFiguredBassElement> createFiguredBassElementNewbornClone (
8 // SMARTP<msrFiguredBassElement> createFiguredBassElementDeepClone ();

```

66.4 Translating figured bass elements from MXSR to MSR

This is done in `src/passes/mxsr2msr/`, and this is where the class `msrFiguredBassElement` instances are created.

The MSR score skeleton created in `src/passes/mxsr2msr/mxsr2msrSkeletonBuilder.h/.cpp` contains the part groups, parts, staves and voices, as well as the number of measures. The voices do not contain any music elements yet.

A figured bass element belongs to `<part/>` in MusicXML, but we sometimes need to have it attached to a note.

Field `mxsr2msrSkeletonBuilder::fThereAreFiguredBassToBeAttachedToCurrentNote` is used when visiting an `S_FiguredBassElement` element to account for that:

```

1 void mxsr2msrSkeletonBuilder::visitStart ( S_figured_bass& elt )
2 {
3 #ifdef TRACING_IS_ENABLED
4     if (gGlobalMxsr0ahGroup->getTraceMxsrVisitors ()) {
5         gLogStream <<
6             "--> Start visiting S_figured_bass" <<
7             ", figuredBassVoicesCounter = " << fFiguredBassVoicesCounter <<
8             ", line " << elt->getInputLineNumber () <<
9             endl;
10    }
11 #endif
12
13    /* JMI
14       several figured bass elements can be attached to a given note,
15       leading to as many figured bass voices in the current part JMI TRUE???
16    */
17
18    // take figured bass voice into account
19    ++fFiguredBassVoicesCounter;
20
21    fThereAreFiguredBassToBeAttachedToCurrentNote = true;
22 }

```

Upon the second visit of class `msrNote`, the part figured bass voice is created if figured bass elements are not to be ignored due to option `-ignore-figured-bass`, `-ofigbass` and it has not been created yet:

```

1 void mxsr2msrSkeletonBuilder::visitEnd ( S_note& elt )
2 {
3     // ... ..
4
5     // are there figured bass attached to the current note?
6     if (fThereAreFiguredBassToBeAttachedToCurrentNote) {
7         if (gGlobalMxsr2msr0ahGroup->getIgnoreFiguredBassElements ()) {
8 #ifdef TRACING_IS_ENABLED
9             if (gGlobalTracing0ahGroup->getTraceFiguredBass ()) {
10                 gLogStream <<
11                     "Ignoring the figured bass elements" <<
12                     ", line " <<
13                     inputLineNumber <<
14                     endl;
15             }
16 #endif
17         }

```

```

18     else {
19         // create the part figured bass voice if not yet done
20         S_msrVoice
21             partFiguredBassVoice =
22                 createPartFiguredBassVoiceIfNotYetDone (
23                     inputLineNumber,
24                     fCurrentPart);
25     }
26
27     fThereAreFiguredBassToBeAttachedToCurrentNote = false;
28
29     // ... ..
30 }

```

Creating the part figured bass voice is delegated to the part:

```

1 S_msrVoice mxsr2msrSkeletonBuilder::createPartFiguredBassVoiceIfNotYetDone (
2     int         inputLineNumber,
3     S_msrPart   part)
4 {
5     // is the figured bass voice already present in part?
6     S_msrVoice
7         partFiguredBassVoice =
8             part->
9                 getPartFiguredBassVoice ();
10
11     if (! partFiguredBassVoice) {
12         // create the figured bass voice and append it to the part
13         partFiguredBassVoice =
14             part->
15                 createPartFiguredBassVoice (
16                     inputLineNumber,
17                     fCurrentMeasureNumber);
18     }
19
20     return partFiguredBassVoice;
21 }

```

66.4.1 First S_figured_bass visit

The first visit of S_figured_bass initializes the fields storing values to be gathered visiting subelements:

```

1 void mxsr2msrTranslator::visitStart ( S_figured_bass& elt )
2 {
3     int inputLineNumber =
4         elt->getInputLineNumber ();
5
6     #ifdef TRACING_IS_ENABLED
7         if (gGlobalMxsrOahGroup->getTraceMxsrVisitors ()) {
8             gLogStream <<
9                 "--> Start visiting S_figured_bass" <<
10                 ", line " << inputLineNumber <<
11                 endl;
12         }
13     #endif
14
15     ++fFiguredBassVoicesCounter;
16
17     string parentheses = elt->getAttributeValue ("parentheses");
18
19     fCurrentFiguredBassParenthesesKind =
20         msrFiguredBassElement::kFiguredBassElementParenthesesNo; // default value
21
22     if (parentheses.size ()) {

```

```

23     if (parentheses == "yes")
24         fCurrentFiguredBassParenthesesKind =
25             msrFiguredBassElement::kFiguredBassElementParenthesesYes;
26
27     else if (parentheses == "no")
28         fCurrentFiguredBassParenthesesKind =
29             msrFiguredBassElement::kFiguredBassElementParenthesesNo;
30
31     else {
32         stringstream s;
33
34         s <<
35             "parentheses value " << parentheses <<
36             " should be 'yes' or 'no'";
37
38         musicxmlError (
39             gGlobalServiceRunData->getInputSourceName (),
40             inputLineNumber,
41             __FILE__, __LINE__,
42             s.str ());
43     }
44 }
45
46 fCurrentFiguredBassInputLineNumber    = -1;
47
48 fCurrentFigureNumber = -1;
49
50 fCurrentFigurePrefixKind = msrBassFigure::k_NoFigurePrefix;
51 fCurrentFigureSuffixKind = msrBassFigure::k_NoFigureSuffix;
52
53 fCurrentFiguredBassSoundingWholeNotes = rational (0, 1);
54 fCurrentFiguredBassDisplayWholeNotes  = rational (0, 1);
55
56 fOnGoingFiguredBass = true;
57 }

```

66.4.2 Second S_figured_bass visit

Upon the second visit of `S_figured_bass`, the class `msrFiguredBassElement` instance is created, populated and appended to `mxsr2msrTranslator::fPendingFiguredBassElementsList`:

```

1 void mxsr2msrTranslator::visitEnd ( S_figured_bass& elt )
2 {
3     int inputLineNumber =
4         elt->getInputLineNumber ();
5
6     #ifdef TRACING_IS_ENABLED
7         if (gGlobalMxsrOahGroup->getTraceMxsrVisitors ()) {
8             gLogStream <<
9                 "--> End visiting S_figured_bass" <<
10                 ", line " << inputLineNumber <<
11                 endl;
12         }
13     #endif
14
15     // create the figured bass element
16     #ifdef TRACING_IS_ENABLED
17         if (gGlobalTracingOahGroup->getTraceFiguredBass ()) {
18             gLogStream <<
19                 "Creating a figured bass" <<
20                 ", line " << inputLineNumber << ":" <<
21                 endl;
22         }
23     #endif

```



```

24
25 // create the figured bass element
26 // if the sounding whole notes is 0/1 (no <duration /> was found), JMI ???
27 // it will be set to the next note's sounding whole notes later
28 S_msrFiguredBassElement
29     figuredBassElement =
30         msrFiguredBassElement::create (
31             inputLineNumber,
32             // JMI         fCurrentPart,
33             fCurrentFiguredBassSoundingWholeNotes,
34             fCurrentFiguredBassDisplayWholeNotes,
35             fCurrentFiguredBassParenthesesKind,
36             msrTupletFactor (1, 1));    // will be set upon next note handling
37
38 // attach pending figures to the figured bass element
39 if (! fPendingFiguredBassFiguresList.size ()) {
40     musicxmlWarning (
41         gGlobalServiceRunData->getInputSourceName (),
42         inputLineNumber,
43         "figured-bass has no figures contents, ignoring it");
44 }
45 else {
46     // append the pending figures to the figured bass element
47     for (S_msrBassFigure bassFigure : fPendingFiguredBassFiguresList) {
48         figuredBassElement->
49             appendFigureToFiguredBass (bassFigure);
50     } // for
51
52     // forget about those pending figures
53     fPendingFiguredBassFiguresList.clear ();
54
55     // append the figured bass element to the pending figured bass elements list
56     fPendingFiguredBassElementsList.push_back (figuredBassElement);
57 }
58
59 fOnGoingFiguredBass = false;
60 }

```

66.4.3 Attaching msrFiguredBassElement instances to notes

msrFiguredBassElement

The contents of mxsr2msrTranslatorfPendingFiguredBassElementsList is attached to the class msrNote instance in method

method mxsr2msrTranslator::populateNote ():

```

1 void mxsr2msrTranslator::populateNote (
2     int         inputLineNumber,
3     S_msrNote newNote)
4 {
5     // ... ..
6
7     // handle the pending figured bass elements if any
8     if (fPendingFiguredBassElementsList.size ()) {
9         // get voice to insert figured bass elements into
10        S_msrVoice
11        voiceToInsertFiguredBassElementsInto =
12            fCurrentPart->
13                getPartFiguredBassVoice ();
14
15        // ... ..
16
17        handlePendingFiguredBassElements (
18            newNote,

```

```

19     voiceToInsertFiguredBassElementsInto);
20
21     // reset figured bass counter
22     fFiguredBassVoicesCounter = 0;
23 }
24 }

```

66.4.4 Populating msrFiguredBassElement instances

msrFiguredBassElement

In `src/formats/msr/mxsr2msrTranslator.cpp`, the class `msrFiguredBassElement` instances are populated further and attached to the note by method `mxsr2msrTranslator::handlePendingFiguredBassElements ()`:

```

1 void mxsr2msrTranslator::handlePendingFiguredBassElements (
2     S_msrNote newNote,
3     S_msrVoice voiceToInsertInto)
4 {
5     // ... ..
6
7     rational
8     newNoteSoundingWholeNotes =
9     newNote->
10         getNoteSoundingWholeNotes (),
11     newNoteDisplayWholeNotes =
12     newNote->
13         getNoteDisplayWholeNotes ();
14
15     while (fPendingFiguredBassElementsList.size ()) { // recompute at each iteration
16         S_msrFiguredBassElement
17         figuredBassElement =
18             fPendingFiguredBassElementsList.front ();
19
20         /*
21          Figured bass elements take their position from the first
22          regular note (not a grace note or chord note) that follows
23          in score order. The optional duration element is used to
24          indicate changes of figures under a note.
25          */
26
27         // set the figured bass element's sounding whole notes
28         figuredBassElement->
29             setMeasureElementSoundingWholeNotes (
30                 newNoteSoundingWholeNotes,
31                 "handlePendingFiguredBassElements()");
32
33         // set the figured bass element's display whole notes JMI useless???
34         figuredBassElement->
35             setFiguredBassDisplayWholeNotes (
36                 newNoteDisplayWholeNotes);
37
38         // set the figured bass element's tuplet factor
39         figuredBassElement->
40             setFiguredBassTupletFactor (
41                 msrTupletFactor (
42                     fCurrentNoteActualNotes,
43                     fCurrentNoteNormalNotes));
44
45         // append the figured bass to newNote
46         newNote->
47             appendFiguredBassElementToNoteFiguredBassElementsList (
48                 figuredBassElement);
49
50         /* JMI

```

```

51 // get the figured bass voice for the current voice
52 S_msrVoice
53     voiceFiguredBassVoice =
54         voiceToInsertInto->
55             getRegularVoiceFiguredBassVoiceForwardLink ();
56
57 // sanity check
58 mfAssert (
59     __FILE__, __LINE__,
60     voiceFiguredBassVoice != nullptr,
61     "voiceFiguredBassVoice is null");
62
63 // set the figuredBassElement's voice upLink
64 // only now that we know which figured bass voice will contain it
65 figuredBassElement->
66     setFiguredBassVoiceUpLink (
67         voiceFiguredBassVoice);
68
69 // append the figured bass to the figured bass voice for the current voice
70 voiceFiguredBassVoice->
71     appendFiguredBassElementToVoice (
72         figuredBassElement);
73 */
74
75 // don't append the figured bass to the part figured bass voice
76 // before the note itself has been appended to the voice
77
78 // remove the figured bass from the list
79 fPendingFiguredBassElementsList.pop_front ();
80 } // while
81 }

```

```

1 %void mxsr2msrTranslator::copyNoteHarmoniesToChord (
2 % S_msrNote note, S_msrChord chord)
3 %{
4 % // copy note's harmony if any from the first note to chord
5 %
6 % const list<S_msrHarmony>&
7 %     noteHarmoniesList =
8 %     note->getNoteHarmoniesList ();
9 %
10 % if (noteHarmoniesList.size ()) {
11 %     list<S_msrHarmony>::const_iterator i;
12 %     for (i=noteHarmoniesList.begin (); i!=noteHarmoniesList.end (); ++i) {
13 %         S_msrHarmony harmony = (*i);
14 %
15 % #ifdef TRACING_IS_ENABLED
16 %     if (gGlobalTracingOahGroup->getTraceHarmonies ()) {
17 %         gLogStream <<
18 %             "Copying harmony '" <<
19 %             harmony->asString () <<
20 %             "' from note " << note->asString () <<
21 %             " to chord '" << chord->asString () <<
22 %             "'" <<
23 %             endl;
24 %     }
25 % #endif
26 %
27 %     chord->
28 %         appendHarmonyToChord (harmony);
29 %
30 %     } // for
31 % }
32 %}
33 %

```

66.4.5 Inserting S_msrFiguredBassElement instances in the part figured bass voice

Method `msrVoice::appendNoteToVoice ()` in `src/formats/msr/msrNotes.cpp` inserts the figured bass elements in the part figured bass voice:

```

1 void msrVoice::appendNoteToVoice (S_msrNote note)
2 {
3     // ... ..
4
5     // are there figured bass elements attached to this note?
6     const list<S_msrFiguredBassElement>&
7         noteFiguredBassElementsList =
8         note->
9             getNoteFiguredBassElementsList ();
10
11     if (noteFiguredBassElementsList.size ()) {
12         // get the current part's figured bass voice
13         S_msrVoice
14             partFiguredBassVoice =
15             part->
16                 getPartFiguredBassVoice ();
17
18         for (S_msrFiguredBassElement figuredBassElement : noteFiguredBassElementsList) {
19             // append the figured bass element to the part figured bass voice
20             partFiguredBassVoice->
21                 appendFiguredBassElementToVoice (
22                     figuredBassElement);
23         } // for
24     }
25 };

```

66.5 Translating figured bass elements from MSR to MSR

This is done in `src/passes/msr2msr/`.

In `src/passes/msr2msr/msr2msrTranslator.cpp`, a newborn clone of the figured bass element is created upon the first visit, stored in `msr2msrTranslatorfCurrentFiguredBassElementClone`, and appended to the current non grace note clone, the current chord clone or to the current voice clone, if the latter is a figured bass voice:

```

1 void msr2msrTranslator::visitStart (S_msrFiguredBassElement& elt)
2 {
3     #ifdef TRACING_IS_ENABLED
4         if (gGlobalMsr0ahGroup->getTraceMsrVisitors ()) {
5             gLogStream <<
6                 "--> Start visiting msrFiguredBassElement '" <<
7                 elt->asString () <<
8                 "' " <<
9                 ", fOnGoingFiguredBassVoice = " << fOnGoingFiguredBassVoice <<
10                ", line " << elt->getInputLineNumber () <<
11                endl;
12         }
13     #endif
14
15     // create a figured bass element new born clone
16     fCurrentFiguredBassElementClone =
17         elt->
18             createFiguredBassElementNewbornClone (
19                 fCurrentVoiceClone);
20
21     if (fOnGoingNonGraceNote) {
22         // append the figured bass to the current non-grace note clone

```

```

23     fCurrentNonGraceNoteClone->
24         appendFiguredBassElementToNoteFiguredBassElementsList (
25             fCurrentFiguredBassElementClone);
26
27     // don't append the figured bass to the part figured bass, JMI ???
28     // this will be done below
29 }
30
31 /* JMI
32 else if (fOnGoingChord) {
33     // register the figured bass in the current chord clone
34     fCurrentChordClone->
35         setChordFiguredBass (fCurrentFiguredBassElementClone); // JMI
36 }
37 */
38
39 else if (fOnGoingFiguredBassVoice) { // JMI
40     /*
41     // register the figured bass in the part clone figured bass
42     fCurrentPartClone->
43         appendFiguredBassElementToPartClone (
44             fCurrentVoiceClone,
45             fCurrentFiguredBassElementClone);
46     */
47     // append the figured bass to the current voice clone
48     fCurrentVoiceClone->
49         appendFiguredBassElementToVoiceClone (
50             fCurrentFiguredBassElementClone);
51 }
52
53 else {
54     stringstream s;
55
56     s <<
57     "figured bass is out of context, cannot be handled:'" <<
58     elt->asShortString () <<
59     "'";
60
61     msrInternalError (
62         gGlobalServiceRunData->getInputSourceName (),
63         elt->getInputLineNumber (),
64         __FILE__, __LINE__,
65         s.str ());
66 }
67 }

```

There are only fields updates upon the second visit:

```

1 void msr2msrTranslator::visitEnd (S_msrFiguredBassElement& elt)
2 {
3     #ifdef TRACING_IS_ENABLED
4         if (gGlobalMsrOahGroup->getTraceMsrVisitors ()) {
5             gLogStream <<
6             "--> End visiting msrFiguredBassElement '" <<
7             elt->asString () <<
8             "' " <<
9             ", line " << elt->getInputLineNumber () <<
10            endl;
11        }
12    #endif
13
14    fCurrentFiguredBassElementClone = nullptr;
15 }

```

66.6 Translating figured bass elements from MSR to LPSR

This is done in `src/passes/msr2lpsr/`.

The same occurs in `src/passes/msr2lpsr/msr2lpsrTranslator.cpp`: a newborn clone of the figured bass element is created and appended to the current non grace note clone, the current chord clone or to the current voice clone, if the latter is a figured bass voice:

```

1 void msr2lpsrTranslator::visitStart (S_msrFiguredBassElement& elt)
2 {
3     #ifdef TRACING_IS_ENABLED
4         if (gGlobalMsrOahGroup->getTraceMsrVisitors ()) {
5             gLogStream <<
6                 "--> Start visiting msrFiguredBassElement '" <<
7                 elt->asString () <<
8                 "' " <<
9                 ", fOnGoingFiguredBassVoice = " << fOnGoingFiguredBassVoice <<
10                ", line " << elt->getInputLineNumber () <<
11                endl;
12        }
13    #endif
14
15    // create a figured bass new born clone
16    fCurrentFiguredBassElementClone =
17        elt->
18        createFiguredBassElementNewbornClone (
19            fCurrentVoiceClone);
20
21    if (fOnGoingNonGraceNote) {
22        // append the figured bass to the current non-grace note clone
23        fCurrentNonGraceNoteClone->
24            appendFiguredBassElementToNoteFiguredBassElementsList (
25                fCurrentFiguredBassElementClone);
26
27        // don't append the figured bass to the part figured bass, JMI ???
28        // this will be done below
29    }
30
31    /* JMI
32    else if (fOnGoingChord) {
33        // register the figured bass in the current chord clone
34        fCurrentChordClone->
35            setChordFiguredBass (fCurrentFiguredBassElementClone); // JMI
36    }
37    */
38
39    else if (fOnGoingFiguredBassVoice) { // JMI
40        /*
41        // register the figured bass in the part clone figured bass
42        fCurrentPartClone->
43            appendFiguredBassElementToPartClone (
44                fCurrentVoiceClone,
45                fCurrentFiguredBassElementClone);
46        */
47        // append the figured bass to the current voice clone
48        fCurrentVoiceClone->
49            appendFiguredBassElementToVoiceClone (
50                fCurrentFiguredBassElementClone);
51    }
52
53    else {
54        stringstream s;
55
56        s <<
57            "figured bass is out of context, cannot be handled:'" <<
58            elt->asShortString () <<

```

```

59     "''";
60
61     msrInternalError (
62         gGlobalServiceRunData->getInputSourceName (),
63         elt->getInputLineNumber (),
64         __FILE__, __LINE__,
65         s.str ());
66     }
67 }

```

Here too, there are only fields updates upon the second visit of `S_msrFiguredBassElement` instances:

```

1 void msr2lpsrTranslator::visitEnd (S_msrFiguredBassElement& elt)
2 {
3     #ifdef TRACING_IS_ENABLED
4         if (gGlobalMsr0ahGroup->getTraceMsrVisitors ()) {
5             gLogStream <<
6                 "--> End visiting msrFiguredBassElement '" <<
7                 elt->asString () <<
8                 "''" <<
9                 ", line " << elt->getInputLineNumber () <<
10                endl;
11        }
12    #endif
13
14    fCurrentFiguredBassElementClone = nullptr;
15 }

```

66.7 Translating figured bass elements from LPSR to LilyPond

This is done in `src/passes/lpsr2lilypond/`.

There is only one visit of class `msrFiguredBassElement` instances in `src/passes/lpsr2lilypond/lpsr2lilypondTranslator.cpp`.

The LilyPond code is generated only if the figured bass element belongs to a figured bass voice: this is where denormalization ends in the workflow:

```

1 void msr2lpsrTranslator::visitStart (S_msrFiguredBassElement& elt)
2 {
3     #ifdef TRACING_IS_ENABLED
4         if (gGlobalMsr0ahGroup->getTraceMsrVisitors ()) {
5             gLogStream <<
6                 "--> Start visiting msrFiguredBassElement '" <<
7                 elt->asString () <<
8                 "''" <<
9                 ", fOnGoingFiguredBassVoice = " << fOnGoingFiguredBassVoice <<
10                ", line " << elt->getInputLineNumber () <<
11                endl;
12        }
13    #endif
14
15    // create a figured bass new born clone
16    fCurrentFiguredBassElementClone =
17        elt->
18        createFiguredBassElementNewbornClone (
19            fCurrentVoiceClone);
20
21    if (fOnGoingNonGraceNote) {
22        // append the figured bass to the current non-grace note clone
23        fCurrentNonGraceNoteClone->
24            appendFiguredBassElementToNoteFiguredBassElementsList (
25                fCurrentFiguredBassElementClone);

```

```

26
27 // don't append the figured bass to the part figured bass, JMI ???
28 // this will be done below
29 }
30
31 /* JMI
32 else if (fOnGoingChord) {
33 // register the figured bass in the current chord clone
34 fCurrentChordClone->
35 setChordFiguredBass (fCurrentFiguredBassElementClone); // JMI
36 }
37 */
38
39 else if (fOnGoingFiguredBassVoice) { // JMI
40 /*
41 // register the figured bass in the part clone figured bass
42 fCurrentPartClone->
43 appendFiguredBassElementToPartClone (
44 fCurrentVoiceClone,
45 fCurrentFiguredBassElementClone);
46 */
47 // append the figured bass to the current voice clone
48 fCurrentVoiceClone->
49 appendFiguredBassElementToVoiceClone (
50 fCurrentFiguredBassElementClone);
51 }
52
53 else {
54 stringstream s;
55
56 s <<
57 "figured bass is out of context, cannot be handled:'" <<
58 elt->asShortString () <<
59 "'";
60
61 msrInternalError (
62 gGlobalServiceRunData->getInputSourceName (),
63 elt->getInputLineNumber (),
64 __FILE__, __LINE__,
65 s.str ());
66 }
67 }

```


Chapter 67

Lyrics handling

Lyrics are presented at section [19.51](#) [Lyrics], page [198](#).

67.1 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

67.2 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

67.3 Translating from MSR to MSR ([src/passes/msr2msr/](#))

67.4 Translating from MSR to LPSR ([src/passes/msr2lpsr/](#))

67.5 Translating from LPSR to LilyPond ([src/passes/lpsr2lilypond/](#))

Chapter 68

MIDI handling

MIDI is presented at section [19.52](#) [MIDI], page [199](#).

At the day of this writing, MIDI handling is partial, i.e. not all MIDI elements present in MusicXML are incorporated in MSR and no MIDI data can generated generated by MusicFormats.

68.1 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

68.2 Translating from MXSR to MSR ([src/passes/mxsr2msr/](#))

68.3 Translating from MSR to MSR ([src/passes/msr2msr/](#))

68.4 Translating from MSR to LPSR ([src/passes/msr2lpsr/](#))

68.5 Translating from LPSR to LilyPond ([src/passes/lpsr2lilypond/](#))

Part XIII

MusicFormats Scripting Language (MFSL)

Chapter 69

MFSL (MusicFormats Scripting Language)

69.1 A script example

This script illustrates the basic features of MFSL:

```
1 #!//Users/jacquesmenu/musicformats-git-dev/build/bin/mfsl
2
3 # the MusicFormats tool to be used
4 tool : xml2ly
5
6 # the input file
7 input : test.mfsl
8
9 # parts
10 -keep-musicxml-part-id P1
11
12 # the voices choice
13 choice VOICES_CHOICE : voice1Only | voice2Only ;
14 # could be : choice VOICES_CHOICE : ... .. ;
15
16 set VOICES_CHOICE = voice1Only ;
17 # change this to voice2Only to switch to another subset of options
18 # could even be parameter to the script such a $1
19
20 # choose which options to use according to VOICES_CHOICE
21 case VOICES_CHOICE :
22   voice1Only:
23     -title "Joli morceau - voix 1"
24     -ignore-msr-voice Part_P0ne_Staff_One_Voice_Two
25   ;
26
27   voice2Only:
28     -title "Joli morceau - voix 2"
29     --ignore-msr-voice Part_P0ne_Staff_One_Voice_One
30
31     -display-options-values
32
33     -global-staff-size 25.5
34   ;
35 ;
```

This first line of an MFSL script is the so-called *shebang* containing the path to the interpreter, allow for running such scripts by their name provided they are made executable.

69.2 Implementation principles

MFSL is implemented with the `flex` and `bison` C++ code generators:

- `src/interpreters/mfsl/mfslScanner.ll` contains the `flex` lexical description of MFSL.
It is used to create `src/interpreters/mfsl/mfslScanner.cpp`;
- `src/interpreters/mfsl/mfslParser.yy` is the syntax and semantics description of MFSL.
From it, `bison` creates `src/interpreters/mfsl/mfslParser.h`, `src/interpreters/mfsl/mfslParser.cpp` and `src/interpreters/mfsl/mfslParser.output`.
The latter file can be used to check the grammar, in particular if LR conflicts are detected;
- communication between the code generated this way is done by a so-called *driver*, along the lines of the C++-calc example provided by `bison` v3.8.1;
- the way the tokens description is shared by the scanner and parser is described at section 69.7 [Tokens description], page 366;
- the whole power of OAH is used to handle the contents of MFSL scripts as well as the options to the MFSL interpreter itself.

Only the predefined `bool` type is used, since the generated C++ code relies on this. This is why `getValue ()` is used in `src/clisamples/mfsl.cpp`:

```

1  string          theMfTool;
2  string          theInputFile;
3  oahOptionsAndArguments optionsAndArguments;
4
5  err =
6      launchMfslInterpreter (
7          inputSourceName,
8          traceScanning.getValue (),
9          traceParsing.getValue (),
10         displayTokens.getValue (),
11         displayNonTerminals.getValue (),
12         theMfTool,
13         theInputFile,
14         optionsAndArguments);

```

69.3 The contents of the MFSL folder

`src/interpreters/mfsl/location.hh` defines the `yy::location` class, that contains the script file name and input line number:

```

1  jacquesmenu@macmini: ~/musicformats-git-dev/src/interpreters/mfsl > ls -sal
2  total 776
3   0 drwxr-xr-x  28 jacquesmenu  staff      896 Mar 15 05:16 .
4   0 drwxr-xr-x@  4 jacquesmenu  staff      128 Mar 13 00:47 ..
5  16 -rw-r--r--@  1 jacquesmenu  staff    6148 Mar 14 10:18 .DS_Store
6   8 -rw-r--r--@  1 jacquesmenu  staff    1266 Mar 15 05:15 Makefile
7  16 -rw-r--r--@  1 jacquesmenu  staff    7864 Mar 15 05:16 location.hh
8  24 -rw-r--r--@  1 jacquesmenu  staff   10106 Mar 14 18:26 mfslBasicTypes.cpp
9  16 -rw-r--r--@  1 jacquesmenu  staff    4568 Mar 14 18:16 mfslBasicTypes.h
10   8 -rw-r--r--@  1 jacquesmenu  staff    1585 Mar 15 05:12 mfslDriver.cpp
11   8 -rw-r--r--@  1 jacquesmenu  staff    3413 Mar 15 05:12 mfslDriver.h
12   8 -rw-r--r--@  1 jacquesmenu  staff    3041 Mar  9 07:35 mfslInterpreterComponent.cpp
13   8 -rw-r--r--@  1 jacquesmenu  staff     661 Mar  9 07:02 mfslInterpreterInterface.h

```

```

14 24 -rw-r--r--@ 1 jacquesmenu staff 11981 Mar 10 11:38 mfs1InterpreterInsiderHandler.
    cpp
15 16 -rw-r--r--@ 1 jacquesmenu staff 5270 Mar 10 07:11 mfs1InterpreterInsiderHandler.h
16 8 -rw-r--r--@ 1 jacquesmenu staff 1161 Mar 15 05:13 mfs1InterpreterInterface.h
17 16 -rw-r--r--@ 1 jacquesmenu staff 7116 Mar 14 15:53 mfs1Interpreter0ah.cpp
18 16 -rw-r--r--@ 1 jacquesmenu staff 4692 Mar 14 15:51 mfs1Interpreter0ah.h
19 24 -rw-r--r--@ 1 jacquesmenu staff 10070 Mar 14 15:53 mfs1InterpreterRegularHandler.
    cpp
20 8 -rw-r--r--@ 1 jacquesmenu staff 3533 Mar 9 08:22 mfs1InterpreterRegularHandler.h
21 88 -rw-r--r-- 1 jacquesmenu staff 43880 Mar 15 05:16 mfs1Parser.cpp
22 96 -rw-r--r-- 1 jacquesmenu staff 45868 Mar 15 05:16 mfs1Parser.h
23 24 -rw-r--r--@ 1 jacquesmenu staff 10722 Mar 13 16:57 mfs1Parser.output
24 16 -rw-r--r--@ 1 jacquesmenu staff 5930 Mar 14 18:19 mfs1Parser.yy
25 136 -rw-r--r-- 1 jacquesmenu staff 68514 Mar 15 05:16 mfs1Scanner.cpp
26 24 -rw-r--r--@ 1 jacquesmenu staff 11251 Mar 15 05:12 mfs1Scanner.ll
27 144 -rw-r--r--@ 1 jacquesmenu staff 71091 Mar 15 05:14 mfs1Scanner.log
28 8 -rw-r--r--@ 1 jacquesmenu staff 2047 Mar 9 11:45 mfs1Wae.cpp
29 8 -rw-r--r--@ 1 jacquesmenu staff 3681 Mar 9 11:44 mfs1Wae.h
30 8 -rwxr-xr-x@ 1 jacquesmenu staff 817 Mar 14 18:20 test.mfs1

```

69.4 The MFSL basic types

69.5 The MFSL Makefile

This Makefile is quite simple: the options to flex and bison are placed in `src/interpreters/mfs1/mfs1Scanner.ll` and `src/interpreters/mfs1/mfs1Parser.yy`, respectively:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src/interpreters/mfs1 > cat Makefile
2 # ... ..
3
4 # variables
5 # -----
6
7 MAKEFILE = Makefile
8
9 GENERATED_FILES = mfs1Parser.h mfs1Scanner.cpp mfs1Parser.cpp
10
11 BISON = bison
12 FLEX = flex
13
14 CXXFLAGS = -I.. -DMAIN
15
16
17 # implicit target
18 # -----
19
20 all : $(GENERATED_FILES)
21
22
23 # generation rules
24 # -----
25
26 mfs1Scanner.cpp : $(MAKEFILE) mfs1Scanner.ll
27     $(FLEX) -omfs1Scanner.cpp mfs1Scanner.ll
28
29
30 mfs1Parser.h mfs1Parser.cpp : $(MAKEFILE) mfs1Parser.yy
31     $(BISON) --defines=mfs1Parser.h -o mfs1Parser.cpp mfs1Parser.yy
32
33
34 # clean
35 # -----

```

```

36
37 clean:
38   rm -f $(GENERATED_FILES)

```

69.6 Locations handling

69.7 Tokens description

The tokens are described in `src/interpreters/mfsl/mfslParser.yy`, such as:

```
1 %token <string> OPTION "option"
```

Both `OPTION` and `"option"` can be used in the productions, but the grammar is more readable if the capitalized name is used:

```

1 Option
2   : OPTION
3     {
4       if (drv.getDisplayNonTerminals ()) {
5         gLogStream <<
6           " ==> option " << $1 <<
7           endl << endl;
8       }
9
10      $$ = oahOptionNameAndValue::create ($1, "");
11    }
12
13  | OPTION OptionValue
14    {
15      if (drv.getDisplayNonTerminals ()) {
16        gLogStream <<
17          " ==> option " << $1 << ' ' << $2 <<
18          endl << endl;
19      }
20
21      $$ = oahOptionNameAndValue::create ($1, $2);
22    }
23 ;

```

In case of error, `"option"` is used to display a message to the user.

The name `OPTION` is used in `src/interpreters/mfsl/mfslScanner.ll` prefixed by `yy::parser::make_`:

```

1 "--{name} |
2 "--{name} {
3   if (drv.getTraceTokens ()) {
4     gLogStream << "--> " << drv.getScannerLocation () <<
5     ": option [" << yytext << "]" <<
6     endl;
7   }
8   return yy::parser::make_OPTION (yytext, loc);
9 }

```

The suffix after `make_` has to be defined in the `src/interpreters/mfsl/mfslParser.yy` for this to do the link between the Flex-generated and Bison-generated code:

```
1 %token <string> OPTION "option"
```

In `src/interpreters/mfsl/mfslParser.cpp`, this becomes:

```
1 case symbol_kind::S_OPTION: // "option"
```

We don't have to create method `yy::parser::make_OPTION ()` ourselves, though: it is taken care of by Bison itself, since it returns a type `char*`.

The `calc++` example in the `bison` documentation contains the case of numbers:

```
1 %{
2 // A number symbol corresponding to the value in S.
3 yy::parser::symbol_type
4 make_NUMBER (const std::string &s, const yy::parser::location_type& loc);
5 %}
6
7 // ... ..
8
9 yy::parser::symbol_type
10 make_NUMBER (const std::string &s, const yy::parser::location_type& loc)
11 {
12     errno = 0;
13     long n = strtol (s.c_str(), NULL, 10);
14     if (! (INT_MIN <= n && n <= INT_MAX && errno != ERANGE))
15         throw yy::parser::syntax_error (loc, "integer is out of range: " + s);
16     return yy::parser::make_NUMBER ((int) n, loc);
17 }
```

69.8 The driver

Class `mfslDriver` contains everything needed to let the code generated by `flex` and `bison` communicate with each other, as well as any work variables needed during the analysis of MFSL input. This latter point allows for multiple analyzers to coexist.

`src/interpreters/mfsl/mfslDriver.h` contains a prototype of function `yylex ()`:

```
1 // -----
2 // Give Flex the prototype of yylex we want ...
3 # define YY_DECL \
4     yy::parser::symbol_type yylex (mfslDriver& drv)
5 // ... and declare it for the parser's sake.
6 YY_DECL;
```

Then it contains the declaration of class `mfslDriver`:

```
1 // Conducting the whole scanning and parsing of MFSL
2 class mfslDriver
3 {
4     public:
5
6         // constants
7         // -----
8
9         static const string    K_ALL_PSEUDO_LABEL_NAME;
10
11         // // constructor/destructor
12         // -----
13
14         mfslDriver ();
15
16         virtual                ~mfslDriver ();
17
18         // ... ..
19 }
```



```

20 public:
21
22     // public services
23     // -----
24
25     // run the parser, return 0 on success
26     int                parseInput_Pass1 ();
27
28     // handling the scanner
29     void                scanBegin ();
30     void                scanEnd ();
31
32     // ... ..
33
34 private:
35
36     // private fields
37     // -----
38
39     // the name of the MusicFormats tool
40     string              fTool;
41
42     // the name of the MusicFormats script
43     string              fScriptName;
44
45     // the names of the input sources
46     list<string>        fInputSoucesList;
47
48
49     // scanning
50     bool                fTraceScanning;
51     mfs::location       fScannerLocation;
52
53     // ... ..
54 };

```

The definitions are placed in two files due to the specificity of the sharing of variables and function in the flex and bison-generated code:

- `src/interpreters/mfs/mfsDriver.cpp` contains method `mfsDriver::parseInput_Pass1 ()`, that runs the parser:

```

1 int mfsDriver::parseInput_Pass1 ()
2 {
3     // initialize scanner location
4     fScannerLocation.initialize (
5         &fScriptName);
6
7     // begin scan
8     scanBegin ();
9
10    if (fScriptName.empty () || fScriptName == "-") {
11        fScriptName = "stdin"; // nicer for warning and error messages
12    }
13
14    // do the parsing
15    mfs::parser theParser (*this);
16
17    theParser.set_debug_level (
18        fTraceParsing);
19
20    int parseResult = theParser ();
21
22    // end scan
23    scanEnd ();

```

```

24
25 // ... ..
26
27 // do the final semantics check
28 finalSemanticsCheck ();
29
30 return parseResult;
31 }

```

- the remaining code is placed in the third part (service code) of `src/interpreters/mfsl/mfslScanner.ll`, since it needs to access variables in the code generated by `flex`:

```

1 void mfslDriver::scanBegin ()
2 {
3     yy_flex_debug = fTraceScanning;
4
5     if (fScriptName.empty () || fScriptName == "-") {
6         yyin = stdin;
7     }
8
9     else if (!(yyin = fopen (fScriptName.c_str (), "r")))
10    {
11        stringstream s;
12
13        char*
14            errorString =
15                strerror (errno);
16
17        if (errorString != nullptr) {
18            s <<
19                "cannot open " <<
20                fScriptName << ": " <<
21                errorString <<
22                endl;
23
24            mfslFileError (
25                fScriptName,
26                s.str ());
27        }
28    }
29 }
30
31 void mfslDriver::scanEnd ()
32 {
33     fclose (yyin);
34 }

```

69.9 Lexical analysis

The lexical definition of MFSL in `src/interpreters/mfsl/mfslScanner.ll` is described below.

69.9.1 Flex options

The `prefix` is used to allow for multiple `flex`-generated analyzers to coexist:

```

1 %option prefix="mfsl"
2
3 %option yylineno
4
5 %option noyywrap
6

```

```
7 %option nounput noinput debug interactive
```

69.9.2 Flex regular expressions

The basic ones are:

```
1 blank          [ \t\r]
2 endOfLine      [\n]
3 character      .
4
5 letter         [A-Za-zéèâäöùîí]
6 digit         [0-9]
7
8 name           {letter}(_|-|\.|{letter}|{digit})*
9 integer        {digit}+
10 exponent      [eE][+-]?{integer}
11
12 singleQuote    [']
13 doubleQuote    ["]
14 tabulator      [\t]
15 backSlash      [\\]
16
17 ... ..
18
19 %{
20     // Code run each time a pattern is matched.
21     # define YY_USER_ACTION  loc.columns (yyleng);
22 %}
```

Some exclusive modes are used for strings and comments:

```
1 %x              SINGLE_QUOTED_STRING_MODE
2 %x              DOUBLE_QUOTED_STRING_MODE
3
4 %x              COMMENT_TO_END_OF_LINE_MODE
5 %x              PARENTHESESIZED_COMMENT_MODE
```

Strings must be stored in a private buffer:

```
1 /* strings */
2
3 #define          STRING_BUFFER_SIZE 1024
4 char            pStringBuffer [STRING_BUFFER_SIZE];
5
6 // A handy shortcut to the location held by the mfsldriver
7 mfsll::location& loc = drv.getScannerLocationNonConst ();
```

Locating the tokens in the the MFSL input text is done with:

```
1 // Code run each time yylex() is called
2 loc.step ();
```

This lead for example to:

```
1 {blank} {
2     loc.step ();
3 }
4
5 {endOfLine} {
6     loc.lines (yyleng); loc.step ();
7 }
```

The numbers are handled by:

```

1 {integer} "." {integer} ({exponent})? |
2 {integer} {exponent} {
3   if (drv.getTraceTokens ()) {
4     gLogStream <<
5       "--> " << drv.getScannerLocation () <<
6       " double: " << yytext <<
7       endl;
8   }
9   return yy::parser::make_DOUBLE (yytext, loc);
10 }
11
12 {integer} {
13   if (drv.getTraceTokens ()) {
14     gLogStream <<
15       "--> " << drv.getScannerLocation () <<
16       " integer: " << yytext <<
17       endl;
18   }
19   return yy::parser::make_INTEGER (yytext, loc);
20 }

```

The MFSL keywords are handled with the make_... facility:

```

1 "tool" {
2   if (drv.getTraceTokens ()) {
3     gLogStream <<
4       "--> " << drv.getScannerLocation () << ": " << yytext <<
5       endl;
6   }
7   return yy::parser::make_TOOL (loc);
8 }

```

The names and the options are handled by:

```

1 {name} {
2   if (drv.getDisplayTokens ()) {
3     gLogStream << "--> " << drv.getScannerLocation () <<
4       ": name [" << yytext << "]" <<
5       endl;
6   }
7
8   loc.begin.column += yyleng;
9   loc.step ();
10
11   return
12     mfs1::parser::make_NAME (yytext, loc);
13 }
14
15
16
17 "--" {name} |
18 "-" {name} {
19   if (drv.getTraceTokens ()) {
20     gLogStream << "--> " << drv.getScannerLocation () <<
21       ": option [" << yytext << "]" <<
22       endl;
23   }
24   return yy::parser::make_OPTION (yytext, loc);
25 }
26
27
28
29 "(" {
30   if (drv.getTraceTokens ()) {

```

```

31     gLogStream <<
32         "--> " << drv.getScannerLocation () << ": " << yytext <<
33         endl;
34     }
35     return yy::parser::make_LEFT_PARENTHESIS (loc);
36 }

```

The catchall rule issues an error message:

```

1  . {
2      throw mfs1::parser::syntax_error (
3          loc,
4          "### invalid character: " + std::string (yytext));
5  }

```

And the end of the MFSL input is handled this way:

```

1  <<EOF>> {
2      return
3      mfs1::parser::make_YEEOF (loc);
4  }

```

69.10 Syntax and semantic analysis

69.10.1 Bison options for MFSL

Setting `api.prefix` allows for multiple analyzers to coexist:

```

1  %skeleton "lalr1.cc" // -*- C++ -*-
2  %require "3.8.1"
3  %defines
4
5  %define api.prefix {mfs1}
6
7  %define api.token.raw
8
9  %define api.token.constructor
10 %define api.value.type variant
11 %define parse.assert
12
13 %code requires {
14     #include <string>
15
16     class mfs1Driver;
17 }
18
19 // the parsing context
20 %param { mfs1Driver& drv } // declaration, any parameter name is fine
21
22 %verbose // to produce mfs1Parser.output
23
24 %locations
25
26 // other Bison options
27 %define parse.trace
28 %define parse.error detailed
29 %define parse.lac full
30 // %define api.pure full
31
32 %printer { yyo << $$; } <*>;
33
34

```

```

35 %code {
36     #include "mfs1BasicTypes.h"
37 }

```

69.10.2 The MFSL tokens

The MFSL tokens are:

```

1 %define api.token.prefix {MFSL_TOK_}
2
3 %token
4     BAR            "|"
5     AMPERSAND      "&"
6     EQUAL          "="
7     SEMICOLON      ";"
8     COLON          ":"
9     COMMA          ","
10
11     TOOL           "tool"
12     INPUT          "input"
13
14     CHOICE          "choice"
15     DEFAULT         "default"
16
17     CASE            "case"
18
19     SELECT          "select"
20     ALL             "all"
21 ;
22
23 %code {
24     #include "mfs1Driver.h"
25 }
26
27 %token <string> INTEGER "integer number"
28 %token <string> DOUBLE  "double number"
29
30 %token <string> SINGLE_QUOTED_STRING "single quoted_string"
31 %token <string> DOUBLE_QUOTED_STRING "double quoted_string"
32
33 %token <string> NAME "name"
34
35 %token <string> OPTION "option"

```

69.10.3 The MFSL non-terminals and axiom

They are:

```

1 // the MFSL non-terminals
2 // -----
3
4 %nterm <string> Number
5
6 %nterm <string> SingleString
7 %nterm <string> String
8
9 %nterm <string> OptionValue
10
11 %nterm <string> LabelName
12
13
14 // the MFSL axiom

```

```

15 //-----
16
17 %start Script

```

69.11 Interface to the MFSL parser

This is provided by `src/interpreters/mfsl/mfslInterpreterInterface.h`:

```

1 EXP extern mfMusicformatsError launchMfslInterpreter (
2     const string&      inputSourceName,
3     bool               traceScanning,
4     bool               traceParsing,
5     bool               displayTokens,
6     bool               displayNonTerminals,
7     string&            theMfTool,
8     string&            theInputFile,
9     oahOptionsAndArguments& optionsAndArguments);

```

The definition of this function is placed in `src/interpreters/mfsl/mfslScanner.ll`:

```

1 mfMusicformatsError launchMfslInterpreter (
2     const string&      inputSourceName,
3     bool               traceScanning,
4     bool               traceParsing,
5     bool               displayTokens,
6     bool               displayNonTerminals,
7     string&            theMfTool,
8     string&            theInputFile,
9     oahOptionsAndArguments& optionsAndArguments)
10 {
11     mfMusicformatsError
12     result =
13         mfMusicformatsError::k_NoError;
14
15     mfslDriver
16     theDriver (
17         traceScanning,
18         traceParsing,
19         displayTokens,
20         displayNonTerminals);
21
22     int parseResult =
23         theDriver.parseFile (inputSourceName);
24
25     gLogStream <<
26         "--> parseResult: " << parseResult <<
27         endl;
28
29     if (! parseResult) {
30         result =
31             mfMusicformatsError::k_ErrorInvalidFile;
32     }
33
34     gLogStream <<
35         "inputFileName: " << theDriver.getInputFileName () <<
36         endl <<
37         "toolName: " << theDriver.getToolName () <<
38         endl;
39
40     theMfTool      = theDriver.getToolName ();
41     theInputFile   = theDriver.getInputFileName ();
42
43     return result;
44 }

```

69.12 Running the example MFSL script

Let's show show the MFSL interpreter uses the options above:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/src/interpreters/mfsl > ./test.mfsl -display-
  tokens -display-non-terminals -display-options-values
2 The options values for //Users/jacquesmenu/musicformats-git-dev/build/bin/mfsl are:
3 MFSL group (-help-mfsl-group, -hmfsl-group), 2 atoms chosen:
4 -----
5 MFSL (-help-mfsl, -hmfsl), 2 atoms chosen:
6 fTraceTokens : true, set by user
7 fDisplayNonTerminals : true, set by user
8
9 Options and help group (-help-oah-group, -hoah-group), 1 atom chosen:
10 -----
11 Options and help (-help-oah, -hoah), 1 atom chosen:
12 fDisplayOptionsValues : true, set by user
13
14
15 --> ./test.mfsl:2.1-39: tool
16 --> ./test.mfsl:2.41: :
17 --> ./test.mfsl:2.43-48: name [xml2ly]
18 ==> tool: xml2ly
19
20 --> ./test.mfsl:4.1-22: input
21 --> ./test.mfsl:4.24: :
22 --> ./test.mfsl:4.25-33: name [test.mfsl]
23 ==> input: test.mfsl
24
25 --> test.mfsl:6.11-32: option [-keep-musicxml-part-id]
26 --> test.mfsl:6.34-35: name [P1]
27 ==> option -keep-musicxml-part-id P1
28
29 --> test.mfsl:8.1-26: choice
30 --> test.mfsl:8.28-40: name [VOICES_CHOICE]
31 --> test.mfsl:8.42: :
32 --> test.mfsl:8.44-53: name [voice10only]
33 --> test.mfsl:8.55: |
34 --> test.mfsl:8.57-66: name [voice20only]
35 --> test.mfsl:8.68: ;
36 ==> ChoiceDeclaration VOICES_CHOICE : ...
37
38 --> test.mfsl:10.1-3: set
39 --> test.mfsl:10.5-17: name [VOICES_CHOICE]
40 --> test.mfsl:10.19: =
41 --> test.mfsl:10.21-30: name [voice10only]
42 --> test.mfsl:10.32: ;
43 ==> ChoiceSetting, set VOICES_CHOICE = voice10only
44
45 --> test.mfsl:12.1-61: case
46 --> test.mfsl:12.63-75: name [VOICES_CHOICE]
47 --> test.mfsl:12.77: :
48 --> test.mfsl:13.2-11: name [voice10only]
49 --> test.mfsl:13.12: :
50 --> test.mfsl:14.5-10: option [-title]
51 --> test.mfsl:14.12-34: double quoted string ["]
52 ==> option -title "
53
54 --> test.mfsl:15.5-21: option [-ignore-msr-voice]
55 --> test.mfsl:15.23-51: name [Part_P0ne_Staff_One_Voice_Two]
56 ==> option -ignore-msr-voice Part_P0ne_Staff_One_Voice_Two
57
58 --> test.mfsl:16.3: ;
59 ==> Case voice10only : ...
60
61 --> test.mfsl:18.2-11: name [voice20only]

```



```

62 --> test.mfsl:18.12: :
63 --> test.mfsl:19.5-10: option [-title]
64 --> test.mfsl:19.12-34: double quoted string ["]
65 ==> option -title "
66
67 --> test.mfsl:20.5-22: option [--ignore-msr-voice]
68 --> test.mfsl:20.24-52: name [Part_P0ne_Staff_One_Voice_One]
69 ==> option --ignore-msr-voice Part_P0ne_Staff_One_Voice_One
70
71 --> test.mfsl:22.5-27: option [-display-options-values]
72 --> test.mfsl:24.5-22: option [-global-staff-size]
73 ==> option -display-options-values
74
75 --> test.mfsl:24.24-27 double: 25.5
76 ==> option -global-staff-size 25.5
77
78 --> test.mfsl:25.3: ;
79 ==> Case voice20nly : ...
80
81 --> test.mfsl:26.1: ;
82 ==> CaseStatement, VOICES_CHOICE : ...
83
84 --> parseResult: 0
85 ==> inputFileName: test.mfsl
86 ==> toolName:      xml2ly
87 jacquesmenu@macmini: ~/musicformats-git-dev/src/interpreters/mfsl >

```

69.12.1 Error recovery

The MFSL interpreter uses a variant of the *stopper sets* method that was present in the early Pascal and Pascal-S converters. The latter passed a set of tokens not to be overtaken to the procedures in charge of accepting the various statements in the language. Strangely enough, this was not done for declarations.

We use a stack of tokens sets that grows and shrinks in parallel with the accepting functions, to know more contextual informations when deciding wether to consume a token or not. The corresponding term is it shift when building the analysis tables in LR technology.

Part XIV

Music Scores Description Language (MSDL)

Chapter 70

MSDL (Music Scores Description Language)

MSDL is an attempt at a description of music score in a non-linear way, much like a painter puts touches of paint on his work. This is also what users do with GUI music scoring applications, but scores textual descriptions such as LilyPond and Guido impose a linear, left to right, writing of the scores contents.

Contrary to LilyPond, the `|` token in MSDL is not the end of a measure. Writing `|2` means that the music that follows will be placed in a new layer in measure 2.

70.1 Main features of MSDL

They are:

- note are written much like in LilyPond such as `b2...`;
- the keywords such as `pitches` and `music`, are reserved;
- they are available in a number of languages such as english, french, german and italian. It is easy to add other languages;

A first, limited converter is provided by MusicFormats with service `msdl`. It also performs reserved keywords translation from one language to another:

70.2 MSDL basic types

Some types used throughout MSR are defined in [src/formats/msdl/msdlBasicTypes.h/.cpp](#):

```
1 jacquesmenu@macmini: ~/musicformats-git-dev/src/formats/msdl > egrep -rIn '^\s*//\s*'
   msdlBasicTypes.h
2 msdlBasicTypes.h:28:// user languages
3 msdlBasicTypes.h:52:// comments types
4 msdlBasicTypes.h:74:// initialization
```

70.3 What the MSDL converter does

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/files/msdl > msdl -about
2 What msdlConverter does:
3
4     This multi-pass converter performs various passes depending on the output generated,
5     which should be specified a '-lilypond', '-braille', '-musicxml' or '-guido' option.
6
7     Other passes are performed according to the options, such as
8     displaying views of the internal data or printing a summary of the score.
9
10    The activity log and warning/error messages go to standard error.
11
12    The output format is selected via options.

```

70.3.1 LilyPond generation

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/files/msdl > msdl -lilypond -about
2 What msdlConverter does:
3
4     This multi-pass converter basically performs 3 passes when generating LilyPond output
5     output:
6
7     Pass 1:  converts the MSDL input into a first MSR
8     Pass 2:  converts the first MSR into a second MSR;
9     Pass 3:  converts the second MSR into a
10             LilyPond Score Representation (LPSR);
11     Pass 4:  converts the LPSR to LilyPond code
12             and writes it to standard output.
13
14     Other passes are performed according to the options, such as
15     displaying views of the internal data or printing a summary of the score.
16
17     The activity log and warning/error messages go to standard error.

```

70.3.2 Braille generation

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/files/msdl > msdl -braille -about
2 What msdlConverter does:
3
4     This multi-pass converter basically performs 4 passes when generating braille output
5     output:
6
7     Pass 1:  converts the MSDL input into a first MSR
8     Pass 2:  converts the first MSR into a second MSR;
9     Pass 3a: converts the second MSR into a
10             Braille Score Representation (BSR)
11             containing one Braille page per MusicXML page;
12     Pass 3b: converts the BSR into another BSR
13             with as many Braille pages as needed
14             to fit the line and page lengths;
15     Pass 4:  converts the BSR to Braille text
16             and writes it to standard output.)
17
18     In this preliminary version, pass 2b merely clones the BSR it receives.
19
20     Other passes are performed according to the options, such as
21     displaying views of the internal data or printing a summary of the score.
22
23     The activity log and warning/error messages go to standard error.

```

70.3.3 MusicXML generation

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/files/msdl > msdl -musicxml -about
2 What msdlConverter does:
3
4     This multi-pass converter basically performs 4 passes when generating MusicXML output
5     output:
6
7         Pass 1:  converts the MSDL input into a first MSR
8         Pass 2:  converts the first MSR into a second MSR;
9         Pass 3:  converts the second MSR into an MusicXML tree;
10        Pass 4:  converts the MusicXML tree to MusicXML code
11                and writes it to standard output.
12
13    Other passes are performed according to the options, such as
14    displaying views of the internal data or printing a summary of the score.
15
16    The activity log and warning/error messages go to standard error.

```

70.3.4 Guido generation

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/files/msdl > msdl -guido -about
2 What msdlConverter does:
3
4     This multi-pass converter basically performs 4 passes when generating Guido output
5     output:
6
7         Pass 1:  converts the MSDL input into a first MSR
8         Pass 2:  converts the first MSR into a second MSR;
9         Pass 3:  converts the second MSR into an MusicXML tree;
10        Pass 4:  converts the MusicXML tree to Guido code
11                and writes it to standard output.
12
13    Other passes are performed according to the options, such as
14    displaying views of the internal data or printing a summary of the score.
15
16    The activity log and warning/error messages go to standard error.
17 jacquesmenu@macmini: ~/musicformats-git-dev/files/msdl >

```

70.4 A first example

HelloWorld.msd is a minimal example:

```

1 %{
2     The unavoidable HelloWorld score
3     %}
4
5
6 % the language used for the pitches
7 % -----
8
9 pitches english           % default is english
10
11
12 % is there an anacrusis?
13 % -----
14
15 anacrusis                % measure numbers start at 0
16
17
18 % the structure

```

```

19 % -----
20
21 % score helloWorld = "Hello World in MSPL" {
22
23   music {
24     |1 c2.. d''8
25     |||                               % final bar
26   }
27
28 % } % helloWorld

```

70.5 First example output from the MSDL converter

Compiling HelloWorld.msd1 to LilyPond, we get the output below.

70.5.1 LilyPond output

```

1 \version "2.22.0"
2
3 % Comment or adapt next line as needed (default is 20)
4 #(set-global-staff-size 20 )
5
6 % Pick your choice from the next two lines as needed
7 %myBreak = { \break }
8 myBreak = {}
9
10 % Pick your choice from the next two lines as needed
11 %myPageBreak = { \pageBreak }
12 myPageBreak = {}
13
14 \header {
15   title               = ""
16   encodingDate        = "Sunday 2021-05-30 @ 12:11:50 CEST"
17   software             = "MSDL converter 1.0"
18 }
19
20 \paper {
21 }
22
23 \layout {
24   \context {
25     \Score
26     autoBeaming = ##f % to display tuplets brackets
27   }
28   \context {
29     \Voice
30   }
31 }
32
33 Part_Part_One_Staff_One_Voice_One = \absolute {
34   \language "nederlands"
35   c2.. d''8 }
36
37 \book {
38   \score {
39     <<
40
41     \new Staff = "Part_Part_One_Staff_One"
42     \with {
43       }
44     <<

```

```

45     \context Voice = "Part_Part_One_Staff_One_Voice_One" <<
46     \Part_Part_One_Staff_One_Voice_One
47     >>
48 >>
49
50 >>
51
52 \layout {
53   \context {
54     \Score
55     autoBeaming = ##f % to display tuplets brackets
56   }
57   \context {
58     \Voice
59   }
60 }
61
62 \midi {
63   \tempo 4 = 90
64 }
65 }
66
67 }

```

70.5.2 Braille output

With:

```
1 msdl -braille HelloWorld.msd1 -use-encoding-in-file-name -braille-output-kind utf8d
```

we get in file HelloWorld.msd1_UTF8Debug.brf Braille 6-dots cells, which can be displayed in a suitable editor as:




Figure 70.1: Braille for HelloWorld.xml with interpretation

The interpretation shows a textual view of the contents of the previous line. **o*** indicates the octave number.

70.5.3 MusicXML output

Compiling HelloWorld.msd1 to MusicXML, we get:

```

1 <?xml version="1.0" encoding="UTF-8" standalone="no"?>
2 <!DOCTYPE score-partwise PUBLIC "-//Recordare//DTD MusicXML 3.1 Partwise//EN"
3   "http://www.musicxml.org/dtds/partwise.dtd">
4 <score-partwise version="3.1">
5   <!-- ===== Created by msdl 0.02 on Sunday 2021-05-30 @ 12:15:44 CEST from HelloWorld.
6   msdl ===== -->
7   <work>
8     <work-number/>
9     <work-title/>

```

```

9      </work>
10     <movement-number/>
11     <movement-title/>
12     <identification>
13         <encoding>
14             <software>msdl 0.02, https://github.com/jacques-menu/musicformats</software>
15             <encoding-date>2021-05-30</encoding-date>
16         </encoding>
17         <miscellaneous>
18             <miscellaneous-field name="description"/>
19         </miscellaneous>
20     </identification>
21     <part-list>
22         <score-part id="Part_One">
23             <part-name/>
24             <score-instrument id="Part_OneI1">
25                 <instrument-name/>
26             </score-instrument>
27         </score-part>
28     </part-list>
29     <part id="Part_One">
30         <measure number="1">
31             <attributes>
32                 <divisions>2</divisions>
33             </attributes>
34             <note>
35                 <pitch>
36                     <step>C</step>
37                     <octave>3</octave>
38                 </pitch>
39                 <duration>7</duration>
40                 <voice>1</voice>
41                 <type>half</type>
42                 <dot/>
43                 <dot/>
44                 <staff>1</staff>
45             </note>
46             <note>
47                 <pitch>
48                     <step>D</step>
49                     <octave>5</octave>
50                 </pitch>
51                 <duration>1</duration>
52                 <voice>1</voice>
53                 <type>eighth</type>
54                 <staff>1</staff>
55             </note>
56         </measure>
57     </part>
58 </score-partwise>

```

70.5.4 Guido output

Compiling HelloWorld.msd1 to Guido, we get:

```

1  {[ \staff<1> \set<autoHideTiedAccidentals="on"> \title<"> \barFormat<style= "system",
   range="1"> \bar<hidden="true"> \beamsOff c0/2.. \beamsOff d2/8 ]
2  }

```


70.6 A more realistic example

Thanks to Jean Abou-Samra for providing UnPetitAir.msd1:

```

1  %{
2  An explicit and implicit voices piano score
3  %}
4
5
6  % l'identification
7  % -----
8
9  titre      "Un petit air"
10 compositeur "Jean Abou Samra"
11
12
13 % la langue pour les hauteurs de notes
14 % -----
15
16 hauteurs francais          % par défaut: english
17
18
19 % la partition
20 % -----
21
22 musique unPetitAir =
23 {
24 |1  clef treble
25     key c
26     time 9/8
27     r4. a,4-> <e g bf>8~ <e g bf>4.~
28
29 |2  <e g bf>4. r2.
30
31 % Maintenant, je reviens en arrière pour la voix supérieure.
32 |2  fs''16 gs'' fs''8 cs'' ds'' e'' b' d'' a' e'
33
34 % La voix inférieure s'éteint.
35 |3  c''8 gs' d' c' fs' a' b' gs' b
36 |4  a'8 e' a g as gs' d'( a ds)
37 |5  e8( b g d' a' e'' b'' c'' b''
38 |6  e''4.) % Rien à la fin.
39
40 % Je décide d'ajouter une tenue de la basse.
41 |5  e2.~ e4.
42
43 % J'ajoute encore une voix. Au passage, je change la métrique.
44 |6  time 6/8
45 |6  r8 e'( f') e' c'' d''
46
47 % Et encore un changement de métrique.
48 |7  time 4/4
49 |7  e''1~
50
51 % Je finis la phrase.
52 |7  e''4 e' d''8 c'' b' a'
53 |8  b'1
54
55 % Je retourne sur mes pas pour introduire l'ostinato.
56 |7  r8 e8 f e f e c' a
57 |8  r8 e8 f e c' a e f
58 |9  r8 ds e ds e ds b fs
59
60 % etc.
61 }
```

Jean also provided the output created by hand with LilyPond, see figure 70.2 [Un Petit Air, par Jean Abou-Samra], page 385:




Figure 70.2: Un Petit Air, par Jean Abou-Samra

70.7 Multi-language support

70.7.1 Multi-language messages handling

70.7.2 Multi-language keywords handling

70.8 Lexical analysis

70.9 Music Scores Descriptions Representation (MSDR)

70.10 Syntax and semantic analysis

The language-dependent keywords leads to a recursive descent parser, since `flex`-generated scanners need 'fixed' keyword in the language description.

70.10.1 Error recovery

The MSDDL converter uses a variant of the *stopper sets* method that was present in the early Pascal and Pascal-S converters. The latter passed a set of tokens not to be overtaken to the procedures in charge of accepting the various statements in the language. Strangely enough, this was not done for declarations.

We use a stack of tokens sets that grows and shrinks in parallel with the accepting functions, to know more contextual informations when deciding wether to consume a token or not. The corresponding term is it shift when building the analysis tables in LR technology.

Part XV

Debugging

Chapter 71

Debugging

Debugging MusicFormats can be quite time-consuming. The trace options available have been designed to provide fine-grained tracing information to help locate issues.

Functions `catchSignals ()` at the beginning of the `main ()` function can be commented out in order to run a tool under a debugger.

File `src/wae/enableAbortToDebugErrors.h` contains:

```
1  /*
2   MusicFormats Library
3   Copyright (C) Jacques Menu 2016-2022
4
5   This Source Code Form is subject to the terms of the Mozilla Public
6   License, v. 2.0. If a copy of the MPL was not distributed with this
7   file, You can obtain one at http://mozilla.org/MPL/2.0/.
8
9   https://github.com/jacques-menu/musicformats
10  */
11
12  #ifndef __enableAbortToDebugErrorsIfDesired__
13  #define __enableAbortToDebugErrorsIfDesired__
14
15
16  // comment the following definition if abort on internal errors is desired
17  // CAUTION: DON'T USE THIS IN PRODUCTION CODE,
18  // since that could kill a session on a \Web\ server, for example
19
20  #ifndef ABORT_TO_DEBUG_ERRORS
21  #define ABORT_TO_DEBUG_ERRORS
22  #endif
23
24
25  #endif
```

71.1 Useful options

Here are the most basing options used when debugging:

- option `-trace-passes`, `-tpasses` this is the first option to use, to locate in which pass the problem arises
- option `-input-line-numbers`, `-iln` this option produces the music elements input-line numbers in the output files
- the `-display*` options

71.2 Removing the results of a build

The contents of `distrib/` after a build is:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev > ll build/
2 total 80
3  0 drwxr-xr-x  10 jacquesmenu  staff    320 May  2 18:18:50 2022 ./
4  0 drwxr-xr-x  39 jacquesmenu  staff   1248 May  2 18:18:51 2022 ../
5 16 -rw-r--r--@  1 jacquesmenu  staff   6148 May  2 15:45:10 2022 .DS_Store
6  8 -rw-r--r--@  1 jacquesmenu  staff   1815 Jun 29 09:10:50 2021 Building.md
7 32 -rw-r--r--   1 jacquesmenu  staff  14849 May  2 18:18:50 2022 CMakeLists.txt
8  8 -rw-r--r--   1 jacquesmenu  staff    291 Jun 29 09:10:50 2021 MakePkg.bat
9 16 -rw-r--r--   1 jacquesmenu  staff   7463 May  2 18:18:50 2022 Makefile
10 0 drwxr-xr-x@ 27 jacquesmenu  staff    864 May  2 18:21:17 2022 bin/
11 0 drwxr-xr-x@  7 jacquesmenu  staff    224 May  2 18:21:11 2022 lib/
12 0 drwxr-xr-x  12 jacquesmenu  staff    384 May  2 18:19:25 2022 libdir/
```

The built files are in `distrib/bin`, `distrib/lib` and `distrib/libdir`. There is no `clean` target in `Makefile`. They can be removed in a single step with this alias:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev > type rmbuild
2 rmbuild is aliased to 'cd ${MUSIC_FORMATS_DEV}/build ; rm -r bin lib libdir; ls -sal'
```

71.3 Reverting to a previous MusicFormats version

The GitHub MusicFormats repository keeps a number of recent releases, such as:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev > git branch
2 * master
3   v0.9.60
4   v0.9.61
5   v0.9.62
```

Then `master` branch contains the development version. To switch back to another version, one should check it out:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev > git checkout v0.9.61
2 Switched to branch 'v0.9.61'
3 Your branch is up to date with 'master/v0.9.61'.
4 jacquesmenu@macmini: ~/musicformats-git-dev > git branch
5   master
6   v0.9.60
7 * v0.9.61
8   v0.9.62
```

Now building this version with `make`, we get:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev/build > xml2ly -version
2 Command line version of musicxml2lilypond converter v0.9.61 (March 3, 2022)
```

Chapter 72

Locating a bug with Git's bisection

A bug appeared in v0.9.63, in which the `-display-lpsr-short`, `-dlpsrshort` option causes `xml2ly` to crash. The symptom varies with the operating system, pointing to a probable memory corruption.

Reverting to MusicFormats previous versions show that:

- v0.9.60 behaves alright;
- v0.9.61 exhibits the bug:

```

1 jacquesmenu@macmini: ~/Desktop > lldb -- xml2ly fullbarrests/
   FullBarRestWithoutBarLine.xml -display-lpsr-short -aofn
2 (lldb) target create "xml2ly"
3 Current executable set to 'xml2ly' (x86_64).
4 (lldb) settings set -- target.run-args "fullbarrests/FullBarRestWithoutBarLine.xml"
   "-display-lpsr-short" "-aofn"
5 (lldb) r
6 Process 28676 launched: '/Users/jacquesmenu/musicformats-git-dev/build/bin/xml2ly' (
   x86_64)
7     The measure with ordinal number 3 is now registered with a duration of 1/1 in
   part Part_P0ne (partID "P1", partName "Soprano"),
   fPartMeasuresWholeNotesDurationsVector.size () = 2
8     The measure with ordinal number 4 is now registered with a duration of 1/1 in
   part Part_P0ne (partID "P1", partName "Soprano"),
   fPartMeasuresWholeNotesDurationsVector.size () = 2
9 %-----
10 Pass (ptional): displaying the LPSR as text, short version
11 %-----
12
13 ... ..
14
15 [PartGroup "PartGroup_1 ('0', fPartGroupName "Implicit")" (1 part), line 0
16   fPartGroupName
17   : "Implicit"
18 Process 28676 stopped
19 * thread #1, queue = 'com.apple.main-thread', stop reason = EXC_BAD_ACCESS (code=1,
   address=0x1)
20   frame #0: 0x00000001007b879a xml2ly`MusicFormats::msrPartGroup::printShort(this=0
   x0000600003e08100, os=0x000000010ca04650) const at msrPartGroups.cpp:1185:13
21   1182         i         = iBegin;
22   1183
23   1184     for ( ; ; ) {
24 -> 1185         (*i)->printShort (os);
25   1186         if (++i == iEnd) break;
26   1187         os << endl;
27   1188     } // for
28 Target 0: (xml2ly) stopped.
29 (lldb)

```

This bug has thus been introduced between v0.9.60 and v0.9.61. There have been several `git push` occurrences leading from v0.9.60 to v0.9.61.

72.1 Locating a bug at random in the Git log

git provides various ways to display the commits history of the repository through `git log` options, for example:

```
1 jacquesmenu@macmini: ~/musicformats-git-dev > git log --pretty=format:"%h - %ad : %s"
2 ea338fd - Tue May 3 10:09:04 2022 +0200 : Complement to the Makefile
3 083db8a - Tue May 3 07:43:09 2022 +0200 : Before reverting to v0.9.60
4 12b6d93 - Mon May 2 09:41:37 2022 +0200 : Prior to bisecting
5 03d98be - Tue Apr 26 11:15:23 2022 +0200 : Finalized sone tracing options
6 3dd7b72 - Tue Apr 26 10:10:38 2022 +0200 : Finalized sone tracing options
7 7f7507c - Thu Apr 14 17:01:14 2022 +0200 : Finalized MFSL syntax and semantics, fixed a
   couple of issues
8 06109d3 - Thu Apr 14 17:00:50 2022 +0200 : Finalized MFSL syntax and semantics, fixed a
   couple of issues
9 62aa64c - Thu Apr 7 07:18:44 2022 +0200 : v0.9.62
10 671ffa4 - Thu Apr 7 06:26:34 2022 +0200 : Pre v0.9.62
11 bf9eb63 - Wed Apr 6 23:42:44 2022 +0200 : Pre v0.9.62
12 db4397c - Wed Apr 6 22:14:43 2022 +0200 : Pre v0.9.62
13 9a80b24 - Mon Apr 4 13:06:12 2022 +0200 : Added MFSL (MusicFormats Script Language)
14 2ef1150 - Mon Apr 4 12:07:07 2022 +0200 : Added MFSL (MusicFormats Script Language)
15 3f56d52 - Tue Mar 29 16:34:23 2022 +0200 : Added MFSL (MusicFormats Script Language)
16 fc1ea21 - Tue Mar 29 08:58:34 2022 +0200 : Added MFSL (MusicFormats Script Language)
17 737b996 - Mon Mar 28 23:42:03 2022 +0200 : Added MFSL (MusicFormats Script Language)
18 8c91155 - Sat Mar 26 08:35:55 2022 +0100 : Added MFSL (MusicFormats Script Language)
19 fc68a93 - Fri Mar 18 15:11:19 2022 +0100 : Added MFSL (MusicFormats Script Language)
20 01430a9 - Fri Mar 18 15:11:12 2022 +0100 : Added MFSL (MusicFormats Script Language)
21 4082813 - Thu Mar 17 18:50:02 2022 +0100 : Added MFSL (MusicFormats Script Language)
22 2696628 - Sun Mar 13 00:48:05 2022 +0100 : Added MFSL (MusicFormats Script Language)
23 a828231 - Thu Mar 10 14:28:11 2022 +0100 : Added MFSL (MusicFormats Script Language)
24 bf04937 - Wed Mar 9 12:53:17 2022 +0100 : Added MFSL (MusicFormats Script Language)
25 a855ee4 - Tue Mar 8 16:39:28 2022 +0100 : Added MFSL (MusicFormats Script Language)
26 b636816 - Mon Mar 7 14:49:54 2022 +0100 : Added MFSL (MusicFormats Script Language)
27 ecd5eaa - Sun Mar 6 00:11:05 2022 +0100 : Added 'keep-msr-voice, kmv' option
28 ec1c8ef - Sat Mar 5 08:48:39 2022 +0100 : Added 'ignore-msr-voice, imv' option
29 8246467 - Thu Mar 3 16:11:37 2022 +0100 : v0.9.61
30 603e19c - Thu Mar 3 13:43:48 2022 +0100 : Switched from C++11 to C++17 for <filesystem>
31 77d3d29 - Thu Mar 3 07:56:00 2022 +0100 : Switched from C++11 to C++17 for <filesystem>
32 a880063 - Thu Mar 3 07:44:08 2022 +0100 : Switched from C++11 to C++17 for <filesystem>
33 38b584f - Wed Mar 2 12:44:22 2022 +0100 : Switched from C++11 to C++17 for <filesystem>
34 662454a - Tue Mar 1 17:14:47 2022 +0100 : Pre-v0.9.61
35 2cb4d5f - Mon Feb 28 11:53:04 2022 +0100 : Renamed some documentation folders and files
36 c7839a8 - Mon Feb 28 09:56:46 2022 +0100 : Renamed some documentation folders and files
37 0e85f99 - Mon Feb 28 09:06:16 2022 +0100 : Renames some documentation folders and files
38 c5a43d9 - Fri Feb 25 17:48:29 2022 +0100 : Finalized files/musicxmlfiles/Makefile
39 21e3898 - Thu Feb 24 21:54:28 2022 +0100 : Added '-replicate-msr-measure' option
40 9738598 - Thu Feb 24 21:53:00 2022 +0100 : Added '-replicate-msr-measure' option
41 ae751c3 - Mon Feb 21 09:58:35 2022 +0100 : Added various options
42 f2d2f57 - Sat Feb 19 08:09:02 2022 +0100 : Workflow to publish Mac OS release
43 ac5ad6b - Sat Feb 19 08:00:57 2022 +0100 : Initializa npm package
44 29de34d - Fri Feb 18 11:00:42 2022 +0100 : v0.9.60
45 7c067d6 - Fri Feb 18 10:56:17 2022 +0100 : v0.9.60
46 5e3ba90 - Fri Feb 18 09:57:50 2022 +0100 : Pre v0.9.60
47 dfef7be - Fri Feb 18 09:56:07 2022 +0100 : Pre v0.9.60
48 c31dde3 - Wed Feb 16 11:50:42 2022 +0100 : Updates to the make and cmake configuration
49 fd6fef0 - Wed Feb 16 09:45:44 2022 +0100 : Complements to the installation doc
50 b7ad2af - Tue Feb 15 17:40:53 2022 +0100 : Distrib test 17
51 50a904c - Tue Feb 15 17:37:53 2022 +0100 : Distrib test 16
52 cf65bd3 - Tue Feb 15 08:41:14 2022 +0100 : Distrib test 15
53 9cda15e - Tue Feb 15 08:38:57 2022 +0100 : Distrib test 14
54 74a2b7f - Tue Feb 15 08:30:21 2022 +0100 : Distrib test 13
```

```

55 ee011e9 - Mon Feb 14 15:06:59 2022 +0100 : Distrib test 13
56 4d6f9cb - Mon Feb 14 08:54:23 2022 +0100 : Distrib test 12
57 7692b7b - Mon Feb 14 08:52:50 2022 +0100 : Distrib test 12
58 d9e943d - Sat Feb 12 09:30:45 2022 +0100 : Distrib test 11
59 3dde810 - Sat Feb 12 09:29:51 2022 +0100 : Distrib test 11
60 f07b02a - Fri Feb 11 17:55:34 2022 +0100 : Distrib test 10
61 5113824 - Fri Feb 11 16:47:17 2022 +0100 : Distrib test 9
62 7f0fa8e - Fri Feb 11 16:45:21 2022 +0100 : Distrib test 8
63 93f72f4 - Fri Feb 11 16:32:33 2022 +0100 : Distrib test 6
64 121aa64 - Fri Feb 11 14:35:38 2022 +0100 : Distrib test 5
65 547556f - Fri Feb 11 11:30:17 2022 +0100 : Creation of MusicFormats repository

```

One can pick one of the commits, revert to it and check whether the bug is present in it.

72.2 Locating a bug in the commits with Git's bisection

Locating the particular push that introduced the bug can be facilitated by git's *bisect* facility. Here is how it works:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev > git bisect start
2
3 jacquesmenu@macmini: ~/musicformats-git-dev > git bisect good v0.9.60
4
5 jacquesmenu@macmini: ~/musicformats-git-dev > git bisect bad v0.9.61
6 Bisecting: 7 revisions left to test after this (roughly 3 steps)
7 [0e85f994ab00ea2dd94ddcb1895cbae5a32f072a] Renames some documentation folders and files
8
9 jacquesmenu@macmini: ~/musicformats-git-dev > git branch
10 * (no branch, bisect started on v0.9.61)
11 master
12 v0.9.60
13 v0.9.61
14 v0.9.62

```

The bisection proposes commit 0e85f994ab00ea2dd94ddcb1895cbae5a32f072a as a middle point between v0.9.60 and v0.9.61. So let us check it out:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev > git checkout 0
   e85f994ab00ea2dd94ddcb1895cbae5a32f072a
2 HEAD is now at 0e85f99 Renames some documentation folders and files
3
4 jacquesmenu@macmini: ~/musicformats-git-dev > git branch
5 * (no branch, bisect started on v0.9.61)
6 master
7 v0.9.60
8 v0.9.61
9 v0.9.62

```

Then, building this intermediate development version leads to:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev/build > make
2 make macos
3 cd libdir && cmake .. -G Xcode -Wno-dev
4 -- VERSION: v0.9.61
5
6 -- Configuring version v0
7 .v9
8 .v61
9
10 ... ..
11

```



```

12 /Users/jacquesmenu/musicformats-git-dev/src/components/mfcLibraryComponent.cpp:12:10:
    fatal error:
13   ' ../../../../MusicFormatsVersionNumber.h' file not found
14 #include " ../../../../MusicFormatsVersionNumber.h"
15   ~~~~~
16 1 error generated.
17
18 ... ..
19
20 ** BUILD FAILED **

```

Well, this dev version had been pushed to have new files and/or contents saved on the MusicFormats repository ...and we should try other commits around it.

A first possibility is to use `git bisect skip`, that moves to :

```

1 jacquesmenu@macmini: ~/musicformats-git-dev > git bisect skip
2 Bisecting: 7 revisions left to test after this (roughly 3 steps)
3 [c7839a87549660963a8b1ef0898d5cbcce8305aa] Renamed some documentation folders and files

```

Checking commit `c7839a87549660963a8b1ef0898d5cbcce8305aa` out, we get:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev > git checkout
   c7839a87549660963a8b1ef0898d5cbcce8305aa
2 HEAD is now at c7839a8 Renamed some documentation folders and files

```

Building that leads to the same error as above. Let us skip one again:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev > git bisect skip
2 Bisecting: 7 revisions left to test after this (roughly 3 steps)
3 [a880063c134a7ba49b31f5fb52b47f682058f64a] Switched from C++11 to C++17 for <filesystem>

```

It turns out the commit `a880063c134a7ba49b31f5fb52b47f682058f64a` does not build either. Let us skip to the next commit:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev > git bisect skip
2 Bisecting: 7 revisions left to test after this (roughly 3 steps)
3 [2cb4d5f2133d34a19fea8f47d9ed2ccfb24d0fad] Renamed some documentation folders and files
4
5 jacquesmenu@macmini: ~/musicformats-git-dev > git checkout 2
   cb4d5f2133d34a19fea8f47d9ed2ccfb24d0fad
6 HEAD is now at 2cb4d5f Renamed some documentation folders and files

```

Here the code base builds alright, and bug does not show up, so we should continue skipping.

72.3 Locating the bug in the code base

The bug we're after is found to have been introduced at this point:

- commit `2cb4d5f`, does not exhibit the bug;
- the next one, commit `662454a`, does.

The changes brought by commit can be shown with:

```

1 jacquesmenu@macmini: ~/musicformats-git-dev > git log --patch -1 662454a > patch_662454a.
   txt
2
3 jacquesmenu@macmini: ~/musicformats-git-dev > ls -sal patch_662454a.txt
4 256 -rw-r--r--@ 1 jacquesmenu staff 80782 May  4 10:59 patch_662454a.txt

```

The bug shows up with `files/musicxmlfiles/fullbarrests/FullBarRestWithoutBarLine.xml`, but not with others such as `files/musicxmlfiles/multistaff/SATBExample.xml`.

Analysing the patch description in `patch_662454a.txt`, we find that nothing in the differences between those two successive patches can explain the crash. The problem thus lies elsewhere...

Part XVI

Indexes

Files index

Symbols

.cpp	80	libmusicxml/build/bin	27
.h	48	libmusicxml/src	211
<regex>	24	lilypond	35, 72
*.cpp	45	lilypondGeneration	34
Interface.	39	lpsr	34, 72
.github/workflows/	246	lpsr2lilypond	34
/Applications/	251	mfsl/	24
1.0.0	35	mfutilities	33
CommonLaTeXFiles/	19	msdl	34, 72
Downloads/	249	msdl2braille	32
Interface	36	msdl2guido	32
IntroductionToMusicxml/	20	msdl2lilypond	32
LaTeXCommonSettings.tex	30	msdl2musicxml	32
LilyPondIssue34	32, 234	msdlconverter	32
Makefile	25, 27, 35	msdr	34
Makefile_ORIGINAL	28	msr	34, 72
Mikrokosmos3Wandering	32, 114	msr2braille	32
MusicFormatsVersionDate.txt	20, 254	msr2bsr	34
MusicFormatsVersionNumber.txt	20, 21, 254	msr2guido	32
oah	72	msr2lilypond	32
bin/	251	msr2lpsr	34
braille	72	msr2msr	34
brailleGeneration	34	msr2musicxml	32
bsr	34, 72	msr2mxsr	34
bsr2braille	34	msr2mxsrOah	145
bsr2bsr	34	msrGeneration	34
build	27	msrapi	34
build/bin	25	multiGeneration	34
clean	35	musicformats-*-distrib/	251
clisamples	31	musicformats-windows-distrib/	251
common	30	musicformatsversion.txt	35
components	32	musicxml2braille	32, 109
converters	32	musicxml2guido	32
countnotes	27	musicxml2lilypond	32
doc	27	musicxml2musicxml	32
documentation/	19	mxsr	34, 72, 231
elements.bash	31	mxsr2guido	34
elements.h	29	mxsr2msr	34
elements.txt	29	mxsr2msrOah	145
files	27, 35	mxsr2musicxml	34
formats	34	mxsrGeneration	34
formatsgeneration	34	oah	33
generators	32	ostream	225
graphics/	20	packages	27
guidoGeneration	34	passes	32, 34
javascript	27	patch_662454a.txt	393
lib/	251	presentation	31
libmusicxml	27	presentation/	20
		samples	27

schemas27
 scripts31
 src27, 31
 ubuntu-check.yml246
 validation27
 wae34
 win3227
 xml2brl72, 122
 xml2guido27
 xml2lbr122
 xml2ly47, 72, 122
 xml2xml122
 musicxml2ly234

B

build
 CMakeLists.txt75
 CMakesList.txt25
 lib21
 Makefile25

C

clisamples132
 displayMusicformatsHistory.cpp112
 displayMusicformatsVersion.cpp112
 libMultipleInitsTest.cpp132
 LilyPondIssue34.cpp41, 132
 Makefile25
 mfsl.cpp364
 Mikrokosmos3Wandering.cpp 17, 40, 132, 136
 msdl.cpp132, 136
 xml2Any.cpp132
 xml2ly.cpp43
 tt *Component.h/.cpp108

D

distrib
 252, 388
 bin388
 lib388
 libdir388
 documentation
 CommonLaTeXFiles21
 CommonLaTeXFiles/MSRClassesHierarchyPicture.tex
 20
 CommonLaTeXFiles/MSRScoreRepresentation.tex
 20
 MusicFormatsAPIGuide/MusicFormatsAPIGuide.pdf
 23
 MusicFormatsMaintenanceGuide/MusicFormatsMaintenanceGuide.pdf
 23
 MusicFormatsUserGuide/MusicFormatsUserGuide.pdf
 23

F

files
 musicxmlfiles/fullbarrests/FullBarRestWithoutBarLines.xml
 393
 musicxmlfiles/multistaff/SATBExample.xml
 393

I

InsiderHandler.cpp48

L

libmusicxml/samples
 84
 countnotes.cpp62
 elements/factory.cpp214
 libmusicxml/src/files
 xmlfile.h215
 xmlreader.h/.cpp216

M

main ()31, 45, 130, 241

S

scripts
 MakeMusicFormatsDistributions.bash ...251,
 252
 ShowMusicFormatsVersion.bash254
 src
 75
 clisamples45
 formats38
 MusicFormatsVersionDate.h20
 MusicFormatsVersionNumber.h20
 passes39
 representations38
 src/clisamples132
 displayMusicformatsHistory.cpp112
 displayMusicformatsVersion.cpp112
 libMultipleInitsTest.cpp132
 LilyPondIssue34.cpp41, 132
 Makefile25
 mfsl.cpp364
 Mikrokosmos3Wandering.cpp 17, 40, 132, 136
 msdl.cpp132, 136
 xml2Any.cpp132
 xml2ly.cpp43
 src/components
 103
 mfcComponents.h37
 mfIndentedTextOutput.h53
 src/formats/bsr
 bsr.cpp86
 bsrBasicTypes.h208
 bsrBasicTypes.h/.cpp208
 src/formats/lpsr
 lpsr/lpsrPapers.h90
 lpsr2lilypondTranslator.cpp126
 lpsrBasicTypes.h/.cpp206
 lpsrElements.h/.cpp72
 lpsrOah.cpp152
 lpsrScores.cpp117
 lpsrScores.h/.cpp43
 src/formats/msdl
 msdlBasicTypes.h/.cpp378
 msdlScanner.cpp159
 msdlScanner.h159
 msdlTokens.cpp92
 src/formats/msr187

mfslNotes.h/.cpp	96	mfslParser.yy	364--366
msr.h/.cpp	262	mfslScanner.cpp	364
msr2msrTranslator.h	160	mfslScanner.ll	364--366, 369, 374
msrBarLines.h	74, 308	src/interpretersmfslinterpreter//mfsl	
msrBarlines.h	74	mfslDriver.h/.cpp	96
msrBasicTypes.cpp	76, 92	src/mflibrary	
msrBasicTypes.h	91, 149, 171, 173, 174, 186, 194	mfMusicformatsError.h	131
msrBasicTypes.h/.cpp	88, 97, 149, 165, 196, 262	mfOnOff.cpp	90
msrBeatRepeats.h/.cpp	189	mfOnOff.h	90
msrChords.h/.cpp	283	mfServiceRunData.h/.cpp	42, 261
msrElements.h	61	src/mfutilities	72
msrHistory.h/.cpp	108	mfcBasicTypes.h	147
msrIdentification.h	166	mfEnumAll.h	77, 91, 92
msrKeys.h/.cpp	95	mfIndentedTextOutput.h	51, 52
msrMeasureElement.h/.cpp	281, 298	mfStringsHandling.cpp	80
msrMeasureRepeat.h/.cpp	190	src/oah	
msrMeasureRepeats.h/.cpp	99	tracingOah.h/.cpp	72
msrMeasures.h/.cpp	272, 283	enableHarmoniesExtraOahIfDesired.h	152
msrMeasuresSlice.h	168	enableTracingIfDesired.h	47
msrMeasuresSlices.h/.cpp	200	generalOah.h/.cpp	153
msrMeausre.h/.cpp	187	harmoniesExtraOah.h/.cpp	152, 153
msrMultipleFullBarRests.h/.cpp	191	mfIndentedTextOutput.cpp	80
msrNotes.cpp	65, 339, 355	musicxmlOah.h/.cpp	72
msrOah.cpp	121	oahAtomCollection.h/.cpp	147
msrOah.h	121	oahAtomsCollection	122
msrParts.h	331, 347	oahAtomsCollection.cpp	125, 140, 150
msrParts.h/.cpp	283--285, 316	oahAtomsCollection.h	149
msrPathToVoice.h.h/.cpp	205	oahAtomsCollection.h.h/.cpp	123
msrRepeats.h/.cpp	191	oahAtomsCollection.h/.cpp	115, 133, 135, 144, 266
msrSegment.cpp	95	oahBasicTypes.cpp	132, 138
msrSegments.cpp	303	oahBasicTypes.h	132
msrSegments.h/.cpp	187, 274, 283	oahBasicTypes.h/.cpp	124, 128, 131, 132, 138
msrStaves.h/.cpp	283--285	oahEarlyOptions.cpp	80, 141
msrTempos.h	175	oahEarlyOptions.h	140
msrTempos.h/.cpp	94, 167	oahElement.cpp	143
msrTies.h	95	oahElements.cpp	144, 146
msrTimeSignature.cpp	158	oahElements.h	138
msrTimeSignature.h	158	oahElements.h/.cpp	132, 142
msrTuplets.h/.cpp	283	oahOah.cpp	148
msrVoiceElements.h/.cpp	185	oahOah.h/.cpp	145
msrVoices.cpp	300--302	tracingOah.h/.cpp	47
msrVoices.h	99, 164, 165, 186	src/utilities	
msrVoices.h/.cpp	158, 276, 283--285	mfBool.h/.cpp	89
mxsr2msrTranslator.cpp	337, 353	mfcLibraryComponent.h/.cpp	110
src/formats/mxsr		mfIndentedTextOutput.cpp.h/.cpp	161
mxsr.h/.cpp	211, 216, 230	mfIndentedTextOutput.h/.cpp	50, 72
mxsrOah.h/.cpp	145	mfTiming.h/.cpp	57
src/interpreters/mfslinterpreter/mfsl		src/wae	
location.hh	364	enableAbortToDebugErrors.h	46, 53, 387
mfslDriver.cpp	368	wae.h.h/.cpp	82
mfslDriver.h	367	waeExceptions	46
mfslInterpreterInterface.h	374	waeExceptions.h/.cpp	82
mfslParser.cpp	364, 366	waeHandlers.cpp	79
mfslParser.h	364	waeHandlers.h	79
mfslParser.output	364		

Types index

Symbols

,	213	mfslDriver	367
:	214	msr*Element	182
Bool	89, 90	msr2mxsrTranslator	68, 229
Enum*	92	msrAccordionRegistration	182
EnumTrueHarmonies	92	msrBarCheck	182
Mikrokosmos3WanderingInsiderHandler	114	msrBarLine	182, 308, 310
SMARTP	93	msrBarNumberCheck	182
SXMLFile	216	msrBeatRepeat	189
S_FiguredBassElement	349	msrBeatRepeatPattern	189
S_figured_bass	350, 351	msrBeatRepeatReplicas	189
S_harmony	333--335	msrBook	183, 205
S_msrBarLine	157	msrChord	156, 180, 187, 330, 346
S_msrFiguredBassElement	355, 358	msrChordInKind	88
S_msrHarmony	344	msrClef	178, 182
S_msrVoice	157	msrClefKind	178
S_part_name	30	msrCoda	183
TXMLFile	216	msrDalSegno	183
	149, 213, 262	msrDamp	182
_msrMeasure	191	msrDampAll	182
bsr2brailleTranslator	223	msrDottedDuration	175
bsrBrailleGenerator	224	msrDurationKind	173, 174
bsrCellKind	208, 209	msrElement	182
c	97	msrEyeGlasses	183
char*	367	msrFiguredBassElement	197, 349, 351--353, 358
cubase	122	msrGraceNotesGroup	123, 182
lpsr2lilypondTranslator	64, 65, 221	msrHarmony	197, 334--339, 344
lpsrComment	117	msrHarmonyKind	91
lpsrPitchesLanguageAtom	122	msrHarpPedalsTuning	182
lpsrScore	43, 117, 206, 222	msrHiddenMeasureAndBarLine	182
mfEnumAll	77	msrHumdrumScotKeyItem	179
mfMultiGenerationOutputKindAtom	130	msrIdentification	166
mfOnOffKind	90	msrKey	95, 179, 182
mfOptionsAndArguments	136	msrLength	149, 150
mfServiceRunData	41	msrLineBreak	182
mfTimingItemsList	57	msrMeasure	64, 164, 278, 279
mfcComponenKind	105	msrMeasureElement	169, 281, 298
mfcComponentDescr	105	msrMeasureElements	187, 272
mfcConverterComponent	106	msrMeasureRepeat	190
mfcGeneratorComponent	106	msrMeasureRepeatPattern	190
mfcLibraryComponent	106	msrMeasureRepeatReplicas	190
mfcMultiComponent	106, 113, 147	msrMeasuresSlice	168, 201
mfcMultiComponentEntropyKind	106	msrMeasuresSlicesSequence	168, 201
mfcMultiComponentUsedFromTheCLIKind	107	msrMeasusre	187
mfcPassComponent	106	msrMeausre	187
mfcRepresentationComponent	106	msrMoment	167
mfcVersionDescr	104	msrMultipleFullBarRests	64, 191
mfcVersionNumber	103	msrNote	70, 169, 194, 197, 199, 330, 333, 336, 346, 349, 352
mfcVersionsHistory	104	msrNoteEvent	168

Types index

msrNoteEventKind	168, 200	msrVoiceStaffChange	182
msrNoteKind	194	mxmlelement	211
msrOctaveEntryVariable	269, 270	mxsr2msrSkeletonBuilder	30, 39
msrOctaveShift	182	mxsr2msrTranslator	219
msrPageBreak	182	oah*Element	122
msrPart	182, 197, 285, 330, 331, 346, 347	oahAtom	121--123
msrPartGroup	184	oahAtomExpectingAValue	124
msrPartGroupElement	182	oahAtomImplicitlyStoringAValue	129
msrPathToVoice	205	oahAtomStoringAValue	122, 124, 125, 127
msrPedal	182	oahBooleanAtom	122, 125, 145
msrPrintLayout	183	oahCombinedBooleansAtom	122
msrRehearsalMark	183	oahContactAtom	122
msrRepeat	186, 187, 192	oahElement	121, 123
msrRepeatCommonPart	192	oahElementHelpOnlyKind	138
msrRepeatEnding	192, 193	oahElementUse	130
msrRepeatEndingKind	192, 193	oahFindStringMatch	142
msrScaling	62	oahFindableElement	122, 123, 142
msrScordatura	182	oahFloatAtom	122
msrScore	64, 119, 183, 205, 319	oahGroup	121, 122
msrSegment	182, 186, 271, 300	oahHandler	113, 121, 122
msrSegno	183	oahHistoryAtom	147
msrSlur	164	oahIntegerAtom	122
msrSpannerTypeKind	169	oahLengthAtom	122, 149
msrStaff	180, 331, 347	oahLengthUnitKindAtom	125
msrStaffDetails	182	oahMacroAtom	266
msrStaffLevelElement	183	oahMultiplexBooleansAtom	122
msrStanza	199	oahOahGroup	145
msrSyllable	182, 183, 198, 199	oahOptionsVector	124, 129
msrSyllableKind	198	oahPrefix	122
msrTempo	94, 167, 177, 182	oahPureHelpAtomExpectingAValue	128
msrTempoKind	175	oahPureHelpAtomWithoutAValue	128
msrTempoNote	175	oahRGBColorAtom	125
msrTempoTuplet	176	oahRationalAtom	122
msrTime	182	oahSubGroup	121, 122
msrTimeSignature	81, 180	oahThreeBooleansAtom	122
msrTimeSignatureSymbolKind	179	oahVersionAtom	115, 147
msrTransposition	183	s	76, 80, 85, 87, 88, 94, 308
msrTuplet	69, 123, 182, 330, 346	v	90
msrTupletElement	183	xml2lyInsiderHandler	263
msrTupletFactor	196	xmlattribute	212
msrTupletInKind	195	xmlelement	212, 213
msrVoice	158, 186, 199, 271, 285, 331, 347	yy::location	364
msrVoiceCreateInitialLastSegmentKind	186		
msrVoiceElement	182, 185, 186, 192, 193, 271	S	
msrVoiceKind	186	SXMLFile	216

Methods and fields index

Symbols

*DeepClone ()	158
*IsNeeded	222
*NewbornClone ()	157
fBooleanVariable	125
fContainingFindableElementInfo	143
fInsiderHandler	135
fReverseNamesDisplayOrder	145
fSetByAnOption	125
fVersionsList	104
msr2msrTranslator	340 , 355
mxsr2msrTranslator	335 , 336 , 351 , 352
RegularHandler	
createOahRegularGroup ()	146
acceptIn ()	80
acceptOut ()	80
applyAtomWithDefaultValue ()	131
applyAtomWithValue ()	131
applyElement ()	131
asString() ()	98
asStringShort() ()	98
asString ()	53 , 54 , 80 , 170
browseData ()	64 , 80
browseData ()	60 , 64
checkGroupOptionsConsistency ()	144
compare* ()	100
countnotes	
visitStart	62
create* ()	80 , 81 , 94
createGlobalMxsr2msrOahGroup ()	48
finalize*() ()	96
finalize* ()	283
generateCodeForBrailleCell ()	225
get*() ()	95
get* ()	80
getSetByAnOption ()	126
getValue ()	364
initialize*() ()	96
initializeHandlerMultiComponent ()	113 , 114
lpsr2lilypondTranslator	
generateLilypondVersion ()	126
lpsrOahGroup	
initializeLpsrPaperOptions ()	152
lpsrScore	
lpsrScore ()	117
mfIndentedStreamBuf	
sync ()	50
mfMultiGenerationOutputKindAtom	
mfMultiGenerationOutputKindAtom ()	130
mfcComponentDescr	
printOwnHistory ()	106
mfcMultiComponent	
printHistory ()	107
print ()	107
mfs1Driver	
parseInput_Pass1 ()	368
msr2bsrTranslator	
finalizeCurrentMeasureClone ()	283
msr2lpsrTranslator	
visitStart (S_msrMeasure& elt)	276
msr2msrTranslator	
visitStart (S_msrMeasure& elt)	276
msr2mxsrTranslator	
translateMsrToMxsr ()	229
msrChord	
finalizeChord ()	283
msrClef	
getClefStaffNumber ()	229
msrHarmony	
createWithoutVoiceUplink ()	335
msrMeasureElement	
fMeasureElementPositionInMeasure	281 , 298
msrMeasureRepeat	
displayMeasureRepeat ()	99
msrMeasuresSlicesSequence	
identifySoloNotesAndRests ()	204
msrMeasure	
appendElementToMeasure ()	272
finalizeFiguredBassMeasure ()	283
finalizeHarmoniesMeasure ()	283
finalizeMeasureClone ()	283
finalizeMeasure ()	282 , 283 , 289
finalizeRegularMeasure ()	283
msrMultipleFullBarRests	
appendMeasureCloneToMultipleFullBarRests ()	276
msrNote	
appendHarmonyToNoteHarmoniesList ()	337 , 338
msrPart	
appendStaffDetailsToPart ()	70
browseData ()	316
collectPartMeasuresSlices ()	202
createAMeasureAndAppendItToPart ()	279
createPartFiguredBassVoice ()	348
finalizeLastAppendedMeasureInPart ()	285
finalizePartAndAllItsMeasures ()	285
finalizePartClone ()	283

- finalizePart () 283, 286
- finalizeRepeatEndInPart () 284
- msrSegment
 - appendMeasureToSegment () 274, 276
 - assertSegmentElementsListIsNotEmpty () 303
 - createAMeasureAndAppendItToSegment () 187, 276
 - createSegmentDeepClone () 300
 - createSegmentNewbornClone () 300
 - create () 300
 - finalizeAllTheMeasuresOfSegment () 283
- msrStaff
 - collectStaffMeasuresSlices () 203, 204
 - finalizeLastAppendedMeasureInStaff () . 285
 - finalizeRepeatEndInStaff () 284
 - finalizeStaff () 283, 286, 287
- msrTempo
 - createTempoPerMinute () 86
 - fTempoBeatUnit 178
 - fTempoEquivalentBeatUnit 178
 - fTempoKind 178
 - fTempoNotesRelationshipKind 178
 - fTempoNotesRelationshipLeftElements ... 178
 - fTempoNotesRelationshipRightElements .. 178
 - fTempoParenthesizedKind 178
 - fTempoPerMinute 178
 - fTempoPlacementKind 178
 - fTempoWordsList 178
 - kTempoNotesRelationshipEquals 178
- msrTemp
 - tempoKindAsString () 86
- msrTie
 - create () 86
- msrTuplets
 - finalizeTuplet () 283
- msrVoice
 - addGraceNotesGroupBeforeAheadOfVoiceIfNeeded () 302
 - appendBarLineToVoice () 302
 - appendCodaToVoice () 302
 - appendDampAllToVoice () 302
 - appendDampToVoice () 302
 - appendEyeGlassesToVoice () 302
 - appendMeasureCloneToVoiceClone () 276
 - appendMultipleFullBarRestsToVoice () .. 276
 - appendNoteToVoice () 339, 355
 - appendPedalToVoice () 302
 - appendPendingMeasureRepeatToVoice () .. 276
 - appendSegnoToVoice () 302
 - appendStaffDetailsToVoice () 302
 - createAMeasureAndAppendItToVoice () .. 276, 302
 - createMeasureRepeatFromItsFirstMeasures () 276, 301, 306
 - createNewLastSegmentForVoice () 301
 - createNewLastSegmentFromItsFirstMeasureForVoice () 276, 302
 - fVoiceLastSegment 186
 - finalizeLastAppendedMeasureInVoice () . 285
 - finalizeRepeatEndInVoice () 284
 - finalizeVoiceAndAllItsMeasures () 285
 - finalizeVoice () 283, 287
 - handleHooklessRepeatEndingEndInVoice () 302
 - handleMultipleFullBarRestsStartInVoiceClone () 302
 - handleVoiceLevelContainingRepeatEndWithoutStart () 302
 - handleVoiceLevelRepeatEndWithStart () . 302
 - handleVoiceLevelRepeatEndWithoutStart () 302
 - handleVoiceLevelRepeatEndingStartWithExplicitStart 276, 302
 - handleVoiceLevelRepeatEndingStartWithoutExplicitStart 276, 302
 - handleVoiceLevelRepeatStart () ... 276, 302
 - initializeVoice () 300
- mxsr2msrSkeletonBuilder
 - fThereAreHarmoniesToBeAttachedToCurrentNote 333
- mxsr2msrTranslator
 - finalizeCurrentChord () 283
 - finalizeTupletAndPopItFromTupletsStack () 283
 - handlePendingFiguredBassElements () ... 353
 - populateNote () 336, 352
 - visitStart (S_bass& elt) 30
 - visitStart (S_notations& elt) 30
 - visitStart (S_other_notation& elt) 30
 - visitStart (S_part_name& elt) 30
- oahAtomStoringAValue
 - fSetByAnOption 125
- oahEarlyOptions
 - applyEarlyOptionIfRelevant () 141
- oahElement
 - fetchNames () 146
- oahHandler
 - handleOptionNameCommon () 130
 - applyOptionsFromElementUsesList () 138
 - checkMissingPendingArgvAtomExpectingAValueValue () 132
 - fHandlerArgumentsVector 131
 - fHandlerMultiComponent 113, 114
 - fPendingArgvAtomExpectingAValue 131
 - findStringInFindableElement () 143
 - handleKnownArgvAtom () 131
 - handleOptionNameCommon () 130
 - handleOptionsAndArgumentsFromArgcArgv () 130
- oahHistoryAtom
 - printHistory () 148
- oahIntegerAtom
 - setIntegerVariable () 125
- oahLengthAtom
 - applyAtomWithValue () 150
 - printAtomWithVariableOptionsValues () . 151
- oahMacroAtom
 - applyElement () 267
 - fMacroAtomsList 267
- oahOahGroup
 - initializeOahBasicHelpOptions () . 145, 148
 - printOahOahValues () 145

oahPrefix		
findStringInFindableElement ()	144
oahVersionAtom		
applyElement ()	116, 140
printVersion ()	116
printHistory ()	106, 116, 147, 148
printSlices ()	70
printVersion ()	106, 115, 116, 147, 148
print ()	53, 54, 80, 170
set*() ()	95
set*Variable ()	125
set* ()	80
translate*() ()	98
visit* ()	60, 160
visitEnd ()	60, 160
visitStart ()	30, 60, 62, 160
xml2lyInsiderHandler		
createTheXml2lyOptionGroups ()	263
xml2lyRegularHandler		
createInformationsRegularGroup ()	148
xml2xmlInsiderHandler		
xml2xmlInsiderHandler ()	113
xmlelement		
fType	213
yy::parser		
make_OPTION ()	367
()	148

Constants, functions and variables index

Symbols

AllFirst	92
AllLast	92
K_NO_STANZA_NUMBER	86
TrueHarmoniesFirst	92
TrueHarmoniesLast	92
gGlobalOStreamIndenter	86
gGlobalOahOahGroup	145
gGlobalServiceRunData	261
gGlobalTimingItemsList	86
gIndenter	51
i	80
kComponentUsedFromTheCLIYes	107
kPlacementAbove	178
kSlurTypeRegularStart	87
k_bass	30
k_notations	30
k_other_notation	30
k_part_name	30
pPrivateThisMethodHasBeenRun	86
*AsString() ()	97
catchSignals ()	387
convert*() ()	98
convertArgcArgvToOptionsAndArguments () ..132,	136
create*OahGroup ()	261

create*PassComponent ()	108
create*RepresentationComponent ()	108
createGlobalHarmoniesExtraOahGroup ()	152
createLibraryComponent ()	110, 112
createMsrRepresentationComponent ()	108
createMusicxml2brailleConverterComponent ()	109
createMxmlScorePartWiseElement ()	230
fromString ()	97
getopt* ()	121
initialize* ()	262
initializeBSR ()	262
initializeLPSR ()	262
initializeMSRBasicTypes ()	262
initializeMSR ()	262
initializeMsrGenerationAPI ()	86
main ()	387
mfAssert ()	76
musicxmlfile2lilypond ()	121
printMxsr ()	216
translateLpsrToLilypondWithHandler ()	51
translateMsrToLpsrScore ()	58
yylex ()	367

A

argc/argv	130--132
-----------------	----------

Options

Symbols

--hist, --history	106	-find	123
--v, --version	106	-history, -hist	107, 108, 113, 115
-auto-output-file-name, -aofn	221, 231	-ignore-figured-bass, -ofigbass	349
-auto-utf8, -au8d	268	-ignore-harmonies, -oharms	333
-cpu	57	-input-line-numbers, -iln	387
-display*	163, 387	-insider	47, 122, 140
-display-lpsr-short, -dlpsrshort	389	-insider, -ins	144
-display-msr-1, -dmsr1	330, 346	-lilypond-generation-infos, -lpgi	117
-display-msr-1-details, -dmsr1d	330, 346	-lilypond-version, -lpv	126
-display-msr-1-short, -dmsr1s	330, 346	-output-file-name, -o	221, 231
-display-msr-2, -dmsr2	346	-quiet, -q	140
-display-msr-2-details, -dmsr2d	330, 346	-reverse-names-display-order, -rndo ..	145, 146
-display-msr-2-short, -dmsr2s	346	-trace-components, -tcomps	140
-display-msr-2-short, -msr2s	330	-trace-figured-bass, -tfigbass	346
-display-msr-2msr2, -dmsr2	330	-trace-harmonies, -tharms	330
-display-msr-skeleton, -dmsrskel	330, 346	-trace-oah, -toah	140
-display-options-values	151	-trace-oah-details, -toahd	140
-display-options-values, -dov	122	-trace-passes, -tpasses	387
-files	224	-version, -v	107, 108, 113, 115, 140, 148

MusicXML index

Symbols

!DOCTYPE </>	211, 217
?xml </>	211, 217
backup </>	145
barLine </>	308
barline </>	309
defaults </>	67
direction </>	166
direction-type </>	166
divisions </>	165
forward </>	145

metronome </>	166
millimeter </>	62
notations </>	29
part </>	333, 349
print </>	67
repeat </>	87
scaling </>	62, 63
system-layout </>	67
tenth </>	62
words </>	166

Main index

Symbols

.	84, 103
.cpp	80
.h	48
	136
	392
TEX root	19
<!DOCTYPE />	211, 217
<<	88
<?xml />	211, 217
<backup />	145
<barLine />	308
<barline />	309
<defaults />	67
<direction />	166
<direction-type />	166
<divisions />	165
<forward />	145
<metronome />	166
<millimeter />	62
<notations />	29
<part />	333, 349
<print />	67
<regex>	24
<repeat />	87
<scaling />	62, 63
<system-layout />	67
<tenth />	62
<words />	166
*.cpp	45
Both	22
Interface.	39
Name	22
*Repr	22
,	213
--hist, --history	106
--v, --version	106
-auto-output-file-name, -aofn	221, 231
-auto-utf8, -au8d	268
-cpu	57
-display*	163, 387
-display-lpsr-short, -dlpsrshort	389
-display-msr-1, -dmsr1	330, 346
-display-msr-1-details, -dmsr1d	330, 346
-display-msr-1-short, -dmsr1s	330, 346
-display-msr-2, -dmsr2	346
-display-msr-2-details, -dmsr2d	330, 346
-display-msr-2-short, -dmsr2s	346
-display-msr-2-short, -msr2s	330
-display-msr-2msr2, -dmsr2	330
-display-msr-skeleton, -dmsrskel	330, 346
-display-options-values	151
-display-options-values, -dov	122
-files	224
-find	123
-history, -hist	107, 108, 113, 115
-ignore-figured-bass, -ofigbass	349
-ignore-harmonies, -oharms	333
-input-line-numbers, -iln	387
-insider	47, 122, 140
-insider, -ins	144
-lilypond-generation-infos, -lpgi	117
-lilypond-version, -lpv	126
-m hyperpage	257
-output-file-name, -o	221, 231
-quiet, -q	140
-reverse-names-display-order, -rndo	145, 146
-trace-components, -tcomps	140
-trace-figured-bass, -tfigbass	346
-trace-harmonies, -tharms	330
-trace-oah, -toah	140
-trace-oah-details, -toahd	140
-trace-passes, -tpasses	387
-version, -v	107, 108, 113, 115, 140, 148
.github/workflows	246
.yaml	246
/Applications	251
0e85f994ab00ea2dd94ddcb1895cbae5a32f072a	391
1.0.0	35
2.22.0	126
2cb4d5f	392
662454a	392
:	214
AllFirst	92
AllLast	92
Bool	89, 90
C++-calc	364
CommonLaTeXFiles	19
Downloads	249
EXP	84
Enum*	92
EnumTrueHarmonies	92
Interface	36
IntroductionToMusicxml	20
K_NO_STANZA_NUMBER	86
LaTeXCommonSettings.tex	30
LilyPondIssue34	32, 234
Makefile	25, 27, 28, 35, 365, 388

Makefile_ORIGINAL	28	elements.txt	29
Mikrokosmos3Wandering	32, 114	f	95
Mikrokosmos3WanderingInsiderHandler	114	fBooleanVariable	125
MusicAndHarmonies.cpp	233	fContainingFindableElementInfo	143
MusicFormatsVersionDate.txt	20, 254	fHandlerArgumentsVector	131
MusicFormatsVersionNumber.txt	20, 21, 254	fHandlerMultiComponent	113, 114
NonConst	96	fInsiderHandler	135
OPTION	366	fMacroAtomsList	267
SMARTP	93	fMeasureElementPositionInMeasure	281, 298
SXMLFile	216	fPendingArgvAtomExpectingAValue	131
S_FiguredBassElement	349	fReverseNamesDisplayOrder	145
S_accidental	28	fSetByAnOption	125
S_figured_bass	350, 351	fTempoBeatUnit	178
S_harmony	333--335	fTempoEquivalentBeatUnit	178
S_msrBarLine	157	fTempoKind	178
S_msrFiguredBassElement	355, 358	fTempoNotesRelationshipKind	178
S_msrHarmony	344	fTempoNotesRelationshipLeftElements	178
S_msrVoice	157	fTempoNotesRelationshipRightElements	178
S_part_name	30	fTempoParenthesizedKind	178
SetMusicFormatsVersionNumber.bash	108	fTempoPerMinute	178
TRACING_IS_ENABLED	47	fTempoPlacementKind	178
TXMLFile	216	fTempoWordsList	178
TrueHarmoniesFirst	92	fThereAreHarmoniesToBeAttachedToCurrentNote	
TrueHarmoniesLast	92	333	
.....	149, 213, 262	fType	213
\${HOME}/Downloads	256	fVersionsList	104
oah	72	fVoiceLastSegment	186
__declspec(dllexport)	84	false	125
_msrMeasure	191	fetch	95
a880063c134a7ba49b31f5fb52b47f682058f64a	392	files	27, 35
addAll	254	formats	34
api.prefix	372	formatsgeneration	34
bin	251, 252	gGlobalOStreamIndenter	86
bool	89, 364	gGlobalOahOahGroup	145
braille	72	gGlobalServiceRunData	261
brailleGeneration	34	gGlobalTimingItemsList	86
bsr	34, 72	gIndenter	51
bsr2braille	34	generators	32
bsr2brailleTranslator	223	get	95
bsr2bsr	34	git bisect skip	392
bsrBrailleGenerator	224	git log	390
bsrCellKind	208, 209	git push	246, 254, 390
build	27	graphics	20
build/bin	25	guidoGeneration	34
c	97	i	80
calc++	367	javascript	27
char*	367	kComponentUsedFromTheCLIYes	107
chmod	252	kPlacementAbove	178
clean	35, 388	kSlurTypeRegularStart	87
clisamples	31	kTempoNotesRelationshipEquals	178
cmake	24, 74	k_accidental	28
common	30	k_bass	30
components	32	k_notations	29, 30
converters	32	k_other_notation	30
countnotes	27	k_part_name	30
cubase	122	lib	251
doc	27	libmusicxml	27
documentation	19	libmusicxml/build/bin	27
dynamic_cast	85	libmusicxml/src	211
elements.bash	31	lilypond	35, 72
elements.h	29	lilypondGeneration	34

lpsr	34, 72	msrChord	156, 180, 187, 330, 346
lpsr2lilypond	34	msrChordInKind	88
lpsr2lilypondTranslator	64, 65, 221	msrClef	178, 182
lpsrComment	117	msrClefKind	178
lpsrPitchesLanguageAtom	122	msrCoda	183
lpsrScore	43, 117, 206, 222	msrDalSegno	183
make	24, 27, 35, 75, 388	msrDamp	182
make_	366	msrDampAll	182
make_...	371	msrDottedDuration	175
master	388	msrDurationKind	173, 174
mf	72	msrElement	182
mfEnumAll	77	msrEyeGlasses	183
mfMultiGenerationOutputKindAtom	130	msrFiguredBassElement	197, 349, 351--353, 358
mfOnOffKind	90	msrGeneration	34
mfOptionsAndArguments	136, 137	msrGraceNotesGroup	123, 182
mfServiceRunData	41	msrHarmony	197, 334--339, 344
mfTimingItemsList	57	msrHarmonyKind	91
mfcComponentKind	105	msrHarpPedalsTuning	182
mfcComponentDescr	105	msrHiddenMeasureAndBarLine	182
mfcConverterComponent	106	msrHumdrumScotKeyItem	179
mfcGeneratorComponent	106	msrIdentification	166
mfcLibraryComponent	106	msrKey	95, 179, 182
mfcMultiComponent	106, 113, 147	msrLength	149, 150
mfcMultiComponentEntropicityKind	106	msrLineBreak	182
mfcMultiComponentUsedFromTheCLIKind	107	msrMeasure	64, 164, 278, 279
mfcPassComponent	106	msrMeasureElement	169, 281, 298
mfcRepresentationComponent	106	msrMeasureElements	187, 272
mfcVersionDescr	104	msrMeasureRepeat	190
mfcVersionNumber	103	msrMeasureRepeatPattern	190
mfcVersionsHistory	104	msrMeasureRepeatReplicas	190
mfsl	24	msrMeasuresSlice	168, 201
mfslDriver	367	msrMeasuresSlicesSequence	168, 201
mfutilities	33	msrMeasusre	187
msdl	34, 72	msrMeausre	187
msdl2braille	32	msrMoment	167
msdl2guido	32	msrMultipleFullBarRests	64, 191
msdl2lilypond	32	msrNote	70, 169, 194, 197, 199, 330, 333, 336, 346, 349, 352
msdl2musicxml	32	msrNoteEvent	168
msdlconverter	32	msrNoteEventKind	168, 200
msdr	34	msrNoteKind	194
msr	34, 72	msrOctaveEntryVariable	269, 270
msr*Element	182	msrOctaveShift	182
msr2braille	32	msrPageBreak	182
msr2bsr	34	msrPart	182, 197, 285, 330, 331, 346, 347
msr2guido	32	msrPartGroup	184
msr2lilypond	32	msrPartGroupElement	182
msr2lpsr	34	msrPathToVoice	205
msr2msr	34	msrPedal	182
msr2msrTranslator	340, 355	msrPrintLayout	183
msr2musicxml	32	msrRehearsalMark	183
msr2mxsr	34	msrRepeat	186, 187, 192
msr2mxsr0ah	145	msrRepeatCommonPart	192
msr2mxsrTranslator	68, 229	msrRepeatEnding	192, 193
msrAccordionRegistration	182	msrRepeatEndingKind	192, 193
msrBarCheck	182	msrScaling	62
msrBarLine	182, 308, 310	msrScordatura	182
msrBarNumberCheck	182	msrScore	64, 119, 183, 205, 319
msrBeatRepeat	189	msrSegment	182, 186, 271, 300
msrBeatRepeatPattern	189	msrSegno	183
msrBeatRepeatReplicas	189	msrSlur	164
msrBook	183, 205		

msrSpannerTypeKind	169	oahIntegerAtom	122
msrStaff	180, 331, 347	oahLengthAtom	122, 149
msrStaffDetails	182	oahLengthUnitKindAtom	125
msrStaffLevelElement	183	oahMacroAtom	266
msrStanza	199	oahMultiplexBooleansAtom	122
msrSyllable	182, 183, 198, 199	oahOahGroup	145
msrSyllableKind	198	oahOptionsVector	124, 129
msrTempo	94, 167, 177, 182	oahPrefix	122
msrTempoKind	175	oahPureHelpAtomExpectingAValue	128
msrTempoNote	175	oahPureHelpAtomWithoutAValue	128
msrTempoTuplet	176	oahRGBColorAtom	125
msrTime	182	oahRationalAtom	122
msrTimeSignature	81, 180	oahSubGroup	121, 122
msrTimeSignatureSymbolKind	179	oahThreeBooleansAtom	122
msrTransposition	183	oahVersionAtom	115, 147
msrTuplet	69, 123, 182, 330, 346	option hyperpage	366
msrTupletElement	183	ostream	225
msrTupletFactor	196	pPrivateThisMethodHasBeenRun	86
msrTupletInKind	195	packages	27
msrVoice ...	158, 186, 199, 271, 285, 331, 347	passes	32, 34
msrVoiceCreateInitialLastSegmentKind	186	patch_662454a.txt	393
msrVoiceElement	182, 185, 186, 192, 193, 271	prefix	369
msrVoiceKind	186	presentation	20, 31
msrVoiceStaffChange	182	rmcache	75
msrapi	34	s	76, 80, 85, 87, 88, 94, 308
multiGeneration	34	samples	27
musicformats-*--distrib	251, 254, 255	schemas	27
musicformats-ubuntu-distrib	249	scripts	31
musicformats-windows-distrib	251	set	95
musicformatsversion.txt	35	src	27, 31
musicxml2braille	32, 109	star*	22
musicxml2guido	32	ubuntu-check.yml	246
musicxml2lilypond	32	v	90
musicxml2musicxml	32	v*	47
mxmlelement	211	v....	17
mxsr	34, 72, 231	v0.9.60	246
mxsr2guido	34	v0.9.61	108
mxsr2msr	34	v0.9.63	254
mxsr2msrOah	145	vX.Y.Z	254
mxsr2msrSkeletonBuilder	30, 39	validation	27
mxsr2msrTranslator ...	219, 335, 336, 351, 352	visitStart	62
mxsr2musicxml	34	visitStart (S_msrMeasure& elt)	276
mxsrGeneration	34	wae	34
oah	33	win32	27
oah*Element	122	xattr	252
oahAtom	121--123	xml2brl	72, 122
oahAtomExpectingAValue	124	xml2guido	27
oahAtomImplicitlyStoringAValue	129	xml2lbr	122
oahAtomStoringAValue	122, 124, 125, 127	xml2ly	47, 72, 122
oahBooleanAtom	122, 125, 145	xml2lyInsiderHandler	263
oahCombinedBooleansAtom	122	xml2xml	122
oahContactAtom	122	xmlattribute	212
oahElement	121, 123	xmlelement	212, 213
oahElementHelpOnlyKind	138	yy::location	364
oahElementUse	130	yy::parser::make_	366
oahFindStringMatch	142	musicxml2ly	234
oahFindableElement	122, 123, 142	*AsString() ()	97
oahFloatAtom	122	//#define DEBUG_EARLY_OPTIONS	
oahGroup	121, 122	i	80
oahHandler	113, 121, 122	//#define DEBUG_INDENTER	
oahHistoryAtom	147	i	80

//#define DEBUG_SPLITTING		
i	80	
handleOptionNameCommon ()	130	
acceptIn ()	80	
acceptOut ()	80	
addGraceNotesGroupBeforeAheadOfVoiceIfNeeded ()		
302		
appendBarLineToVoice ()	302	
appendCodaToVoice ()	302	
appendDampAllToVoice ()	302	
appendDampToVoice ()	302	
appendElementToMeasure ()	272	
appendEyeGlassesToVoice ()	302	
appendHarmonyToNoteHarmoniesList ()	337, 338	
appendMeasureCloneToMultipleFullBarRests ()		
276		
appendMeasureCloneToVoiceClone ()	276	
appendMeasureToSegment ()	274, 276	
appendMultipleFullBarRestsToVoice ()	276	
appendNoteToVoice ()	339, 355	
appendPedalToVoice ()	302	
appendPendingMeasureRepeatToVoice ()	276	
appendSegnoToVoice ()	302	
appendStaffDetailsToPart ()	70	
appendStaffDetailsToVoice ()	302	
applyAtomWithDefaultValue ()	131	
applyAtomWithValue ()	131, 150	
applyEarlyOptionIfRelevant ()	141	
applyElement ()	116, 131, 140, 267	
applyOptionsFromElementUsesList ()	138	
asString() ()	98	
asStringShort() ()	98	
asString ()	53, 54, 80, 170	
assertSegmentElementsListIsNotEmpty ()	303	
browseData ()	64, 80, 316	
browsedata ()	60, 64	
catchSignals ()	387	
checkGroupOptionsConsistency ()	144	
checkMissingPendingArgvAtomExpectingAValueValue ()		
132		
collectPartMeasuresSlices ()	202	
collectStaffMeasuresSlices ()	203, 204	
compare* ()	100	
convert*() ()	98	
convertArgcArgvToOptionsAndArguments ()	132,	
136		
countnotes		
visitStart	62	
create*OahGroup ()	261	
create*PassComponent ()	108	
create*RepresentationComponent ()	108	
create* ()	80, 81, 94	
createAMeasureAndAppendItToPart ()	279	
createAMeasureAndAppendItToSegment ()	187,	
276		
createAMeasureAndAppendItToVoice ()	276, 302	
createGlobalHarmoniesExtraOahGroup ()	152	
createGlobalMxsr2msrOahGroup ()	48	
createInformationsRegularGroup ()	148	
createLibraryComponent ()	110, 112	
createMeasureRepeatFromItsFirstMeasures ()		
276, 301, 306		
createMsrRepresentationComponent ()	108	
createMusicxml2brailleConverterComponent ()		
109		
createMxmlScorePartWiseElement ()	230	
createNewLastSegmentForVoice ()	301	
createNewLastSegmentFromItsFirstMeasureForVoice ()		
276, 302		
createPartFiguredBassVoice ()	348	
createSegmentDeepClone ()	300	
createSegmentNewbornClone ()	300	
createTempoPerMinute ()	86	
createTheXml2lyOptionGroups ()	263	
createWithoutVoiceUplink ()	335	
create ()	86, 300	
displayMeasureRepeat ()	99	
fetchNames ()	146	
finalize*() ()	96	
finalize* ()	283	
finalizeAllTheMeasuresOfSegment ()	283	
finalizeChord ()	283	
finalizeCurrentChord ()	283	
finalizeCurrentMeasureClone ()	283	
finalizeFiguredBassMeasure ()	283	
finalizeHarmoniesMeasure ()	283	
finalizeLastAppendedMeasureInPart ()	285	
finalizeLastAppendedMeasureInStaff ()	285	
finalizeLastAppendedMeasureInVoice ()	285	
finalizeMeasureClone ()	283	
finalizeMeasure ()	282, 283, 289	
finalizePartAndAllItsMeasures ()	285	
finalizePartClone ()	283	
finalizePart ()	283, 286	
finalizeRegularMeasure ()	283	
finalizeRepeatEndInPart ()	284	
finalizeRepeatEndInStaff ()	284	
finalizeRepeatEndInVoice ()	284	
finalizeStaff ()	283, 286, 287	
finalizeTupletAndPopItFromTupletsStack ()	283	
finalizeTuplet ()	283	
finalizeVoiceAndAllItsMeasures ()	285	
finalizeVoice ()	283, 287	
findStringInFindableElement ()	143, 144	
fromString ()	97	
generateCodeForBrailleCell ()	225	
generateLilypondVersion ()	126	
get*() ()	95	
get* ()	80	
getClefStaffNumber ()	229	
getSetByAnOption ()	126	
getValue ()	364	
getopt* ()	121	
handleHooklessRepeatEndingEndInVoice ()	302	
handleKnownArgvAtom ()	131	
handleMultipleFullBarRestsStartInVoiceClone ()		
302		
handleOptionNameCommon ()	130	
handleOptionsAndArgumentsFromArgcArgv ()	130	
handlePendingFiguredBassElements ()	353	

handleVoiceLevelContainingRepeatEndWithoutStart ()	AllFirst	92
302	AllLast	92
handleVoiceLevelRepeatEndWithStart ()	TrueHarmoniesFirst	92
handleVoiceLevelRepeatEndWithoutStart ()	TrueHarmoniesLast	92
handleVoiceLevelRepeatEndingStartWithExplicitStart ()	msrHarmony	
276, 302	createWithoutVoiceUplink ()	335
handleVoiceLevelRepeatEndingStartWithoutExplicitStart ()	msfMeasureElement	
276, 302	fMeasureElementPositionInMeasure	281, 298
handleVoiceLevelRepeatStart ()	msrMeasureRepeat	
displayMeasureRepeat ()		99
identifySoloNotesAndRests ()	msrMeasuresSlicesSequence	
initialize*() ()	identifySoloNotesAndRests ()	204
initialize* ()	msrMeasure	
initializeBSR ()	appendElementToMeasure ()	272
initializeHandlerMultiComponent ()	finalizeFiguredBassMeasure ()	283
initializeLPSR ()	finalizeHarmoniesMeasure ()	283
initializeLpsrPaperOptions ()	finalizeMeasureClone ()	283
initializeMSRBasicTypes ()	finalizeMeasure ()	282, 283, 289
initializeMSR ()	finalizeRegularMeasure ()	283
initializeMSrGenerationAPI ()	msrMultipleFullBarRests	
initializeOahBasicHelpOptions ()	appendMeasureCloneToMultipleFullBarRests ()	276
initializeVoice ()	msrNote	
lpsr2lilypondTranslator	appendHarmonyToNoteHarmoniesList ()	337, 338
generateLilypondVersion ()	msrPart	
lpsrOahGroup	appendStaffDetailsToPart ()	70
initializeLpsrPaperOptions ()	browseData ()	316
lpsrScore	collectPartMeasuresSlices ()	202
lpsrScore ()	createAMeasureAndAppendItToPart ()	279
lpsrScore ()	createPartFiguredBassVoice ()	348
main ()	finalizeLastAppendedMeasureInPart ()	285
make_OPTION ()	finalizePartAndAllItsMeasures ()	285
mfAssert ()	finalizePartClone ()	283
mfIndentedStreamBuf	finalizePart ()	283, 286
sync ()	finalizeRepeatEndInPart ()	284
mfMultiGenerationOutputKindAtom	msrPlacementKind	
mfMultiGenerationOutputKindAtom ()	kPlacementAbove	178
mfMultiGenerationOutputKindAtom ()	msrSegment	
mfComponentDescr	appendMeasureToSegment ()	274, 276
printOwnHistory ()	assertSegmentElementsListIsEmpty ()	303
mfComponentUsedFromTheCLIKind	createAMeasureAndAppendItToSegment ()	187, 276
kComponentUsedFromTheCLIYes	createSegmentDeepClone ()	300
mfComponent	createSegmentNewbornClone ()	300
printHistory ()	create ()	300
print ()	finalizeAllTheMeasuresOfSegment ()	283
mfslDriver	msrSlurTypeKind	
parseInput_Pass1 ()	kSlurTypeRegularStart	87
msdlTokenKind	msrStaff	
AllFirst	collectStaffMeasuresSlices ()	203, 204
AllLast	finalizeLastAppendedMeasureInStaff ()	285
msr2bsrTranslator	finalizeRepeatEndInStaff ()	284
finalizeCurrentMeasureClone ()	finalizeStaff ()	283, 286, 287
msr2lpsrTranslator	msrStanza	
visitStart (S_msrMeasure& elt)	K_NO_STANZA_NUMBER	86
msr2msrTranslator	msrTempo	
visitStart (S_msrMeasure& elt)	createTempoPerMinute ()	86
msr2mxsrTranslator	fTempoBeatUnit	178
translateMsrToMxsr ()	fTempoEquivalentBeatUnit	178
msrChord	fTempoKind	178
finalizeChord ()		
msrClef		
getClefStaffNumber ()		
msrHarmonyKind		

fTempoNotesRelationshipKind	178	finalizeCurrentChord ()	283
fTempoNotesRelationshipLeftElements ...	178	finalizeTupletAndPopItFromTupletsStack ()	283
fTempoNotesRelationshipRightElements ..	178	handlePendingFiguredBassElements () ...	353
fTempoParenthesizedKind	178	populateNote ()	336, 352
fTempoPerMinute	178	visitStart (S_bass& elt) ()	30
fTempoPlacementKind	178	visitStart (S_notations& elt) ()	30
fTempoWordsList	178	visitStart (S_other_notation& elt) ()	30
kTempoNotesRelationshipEquals	178	visitStart (S_part_name& elt) ()	30
msrTemp		oahAtomStoringAValue	
tempoKindAsString ()	86	fSetByAnOption	125
msrTie		oahEarlyOptions	
create ()	86	applyEarlyOptionIfRelevant ()	141
msrTuplets		oahElement	
finalizeTuplet ()	283	fetchNames ()	146
msrVoice		oahHandler	
addGraceNotesGroupBeforeAheadOfVoiceIfNeeded ()	302	handleOptionNameCommon ()	130
appendBarLineToVoice ()	302	applyOptionsFromElementUsesList ()	138
appendCodaToVoice ()	302	checkMissingPendingArgvAtomExpectingAValueValue ()	132
appendDampAllToVoice ()	302	fHandlerArgumentsVector	131
appendDampToVoice ()	302	fHandlerMultiComponent	113, 114
appendEyeGlassesToVoice ()	302	fPendingArgvAtomExpectingAValue	131
appendMeasureCloneToVoiceClone ()	276	findStringInFindableElement ()	143
appendMultipleFullBarRestsToVoice ()	276	handleKnownArgvAtom ()	131
appendNoteToVoice ()	339, 355	handleOptionNameCommon ()	130
appendPedalToVoice ()	302	handleOptionsAndArgumentsFromArgvArgv ()	130
appendPendingMeasureRepeatToVoice ()	276	oahHistoryAtom	
appendSegnoToVoice ()	302	printHistory ()	148
appendStaffDetailsToVoice ()	302	oahIntegerAtom	
createAMeasureAndAppendItToVoice ()	276, 302	setIntegerVariable ()	125
createMeasureRepeatFromItsFirstMeasures ()	276, 301, 306	oahLengthAtom	
createNewLastSegmentForVoice ()	301	applyAtomWithValue ()	150
createNewLastSegmentFromItsFirstMeasureForVoice ()	276, 302	printAtomWithVariableOptionsValues ()	151
fVoiceLastSegment	186	oahMacroAtom	
finalizeLastAppendedMeasureInVoice ()	285	applyElement ()	267
finalizeRepeatEndInVoice ()	284	fMacroAtomsList	267
finalizeVoiceAndAllItsMeasures ()	285	oahOahGroup	
finalizeVoice ()	283, 287	initializeOahBasicHelpOptions ()	145, 148
handleHooklessRepeatEndingEndInVoice ()	302	printOahOahValues ()	145
handleMultipleFullBarRestsStartInVoiceClone ()	302	oahPrefix	
handleVoiceLevelContainingRepeatEndWithoutStart ()	302	findStringInFindableElement ()	144
handleVoiceLevelRepeatEndWithStart ()	302	oahVersionAtom	
handleVoiceLevelRepeatEndWithoutStart ()	302	applyElement ()	116, 140
handleVoiceLevelRepeatEndingStartWithExplicitStart ()	276, 302	printVersion ()	116
handleVoiceLevelRepeatEndingStartWithoutExplicitStart ()	276, 302	parseInput_Pass1 ()	368
handleVoiceLevelRepeatStart ()	276, 302	populateNote ()	336, 352
initializeVoice ()	300	printAtomWithVariableOptionsValues ()	151
musicxmlfile2lilypond ()	121	printHistory ()	106, 107, 116, 147, 148
mxsr2msrSkeletonBuilder		printMxsr ()	216
fThereAreHarmoniesToBeAttachedToCurrentNote	333	printOahOahValues ()	145
mxsr2msrTranslator		printOwnHistory ()	106
		printSlices ()	70
		printVersion ()	106, 115, 116, 147, 148
		print ()	53, 54, 80, 107, 170
		set*() ()	95
		set*Variable ()	125
		set* ()	80
		setIntegerVariable ()	125
		sync ()	50

tempoKindAsString ()86
 translate*() ()98
 translateLpsrToLilypondWithHandler ()51
 translateMsrToLpsrScore ()58
 translateMsrToMxsr ()229
 visit* ()60, 160
 visitEnd ()60, 160
 visitStart (S_bass& elt) ()30
 visitStart (S_notations& elt) ()30
 visitStart (S_other_notation& elt) ()30
 visitStart (S_part_name& elt) ()30
 visitStart ()30, 60, 62, 160
 xml2lyInsiderHandler
 createTheXml2lyOptionGroups ()263
 xml2lyRegularHandler
 createInformationsRegularGroup ()148
 xml2xmlInsiderHandler
 xml2xmlInsiderHandler ()113
 xml2xmlInsiderHandler ()113
 xmlelement
 fType213
 yy::parser
 make_OPTION ()367
 yylex ()367
 ()148
 ()148

A

actions246
 Allow Anyway253
 API ..17, 23, 40, 41, 51, 107, 121, 122, 131,
 137, 233, 241
 argc/argv130--132
 auto24

B

basic blocs193
 bisect391
 BMML31
 Braille17, 382
 branch17, 24, 47, 254, 258
 BSR17, 36, 162, 208
 bsr.cpp86
 bsrBasicTypes208
 bsrBasicTypes.h208

C

C++1724, 76, 87
 cache74, 75
 cascade279, 287
 cascaded70, 289
 cascading70, 285, 286
 Catalina252
 circularity140
 command line ...23, 24, 31, 40, 41, 107, 121,
 122, 124, 129, 131, 136, 153
 commit and push again257
 component103, 105
 tt *Component.h/.cpp108
 converter36, 41
 countnotes.cpp62

D

data driven60
 *DeepClone158
 default17, 246
 defensive programming76
 denormalization156, 330, 344, 346, 358
 description17
 displayMusicformatsHistory.cpp112
 displayMusicformatsVersion.cpp112
 DLL84
 Dominique Fober ..16, 17, 20, 31, 60, 78, 211
 drawing308
 drawn167, 300, 330, 346
 driver364
 DTD24

E

elements/factory.cpp214
 enableAbortToDebugErrors.h46, 53, 387
 enableHarmoniesExtraOahIfDesired.h152
 enableTracingIfDesired.h47
 encapsulates89
 enumeration type76, 80, 85, 87, 88, 90,
 91, 94, 97, 105--107, 138, 149, 168, 169,
 173--175, 178, 179, 186, 192--195, 198,
 200, 208, 209, 213, 214, 262, 308

F

format38
 frozen17
 functions31, 121

G

Gatekeeper252, 253
 General button252
 generator40
 Git75
 git390, 391
 GitHub246, 249, 254, 388
 GUI167, 252
 Guido17, 378

H

has not been set yet87
 High Sierra252

I

initialization87, 261--263
 insider114, 122, 135, 136, 140, 144, 263
 InsiderHandler.cpp48
 introspection142
 *IsNeeded222

L

libMultipleInitsTest.cpp132
 libmusicxml2 ..16, 17, 20, 27, 28, 31, 74, 78,
 85, 93, 109, 211, 213, 215, 219
 LilyPond 17, 41, 51, 117, 126, 167, 183, 206,
 219--222, 234, 242, 344, 358, 378, 385
 LilyPondIssue34.cpp41, 132
 Linux255
 location.hh364
 lpsr/lpsrPapers.h90

lpsr2lilypondTranslator.cpp 126
 lpsrOah.cpp 152
 lpsrScores.cpp 117
 LSPR 36, 162, 206, 240, 263

M

Mac OS™ 246, 249, 251, 252, 255
 main () 31, 45, 130, 241
 Makefile 25
 master 17, 24
 master branch 246, 247, 254, 257
 MEI 31
 mfBool.h/.cpp 89
 MFC 117
 mfcBasicTypes.h 147
 mfcComponents.h 37
 mfcLibraryComponent.h/.cpp 110
 mfEnumAll.h 77, 91, 92
 mfIndentedTextOutput.cpp 80
 mfIndentedTextOutput.cpp.h/.cpp 161
 mfIndentedTextOutput.h 51--53
 mfIndentedTextOutput.h/.cpp 50, 72
 mfMusicformatsError.h 131
 mfOnOff.cpp 90
 mfOnOff.h 90
 MFSL 363, 364, 367, 369, 371--373
 mfs1.cpp 364
 mfs1Driver.cpp 368
 mfs1Driver.h 367
 mfs1InterpreterInterface.h 374
 mfs1Parser.cpp 364, 366
 mfs1Parser.h 364
 mfs1Parser.output 364
 mfs1Parser.yy 364--366
 mfs1Scanner.cpp 364
 mfs1Scanner.ll 364--366, 369, 374
 mfStringsHandling.cpp 80
 mfTiming.h/.cpp 57
 Mikrokosmos3Wandering.cpp ... 17, 40, 132, 136
 MSDL 27, 378
 msdl.cpp 132, 136
 msdlScanner.cpp 159
 msdlScanner.h 159
 msdlTokens.cpp 92
 MSR 20,
 36, 70, 108, 133, 158, 162, 165--167, 175,
 186, 188, 219, 240, 263, 318, 361, 378
 msr2msrTranslator.h 160
 msrBarLines.h 74, 308
 msrBarLines.h 74
 msrBasicTypes.cpp 76, 92
 msrBasicTypes.h .91, 149, 171, 173, 174, 186,
 194
 msrElements.h 61
 msrIdentification.h 166
 msrMeasuresSlice.h 168
 msrNotes.cpp 65, 339, 355
 msrOah.cpp 121
 msrOah.h 121
 msrParts.h 331, 347
 msrSegment.cpp 95

msrSegments.cpp 303
 msrTempos.h 175
 msrTies.h 95
 msrTimeSignature.cpp 158
 msrTimeSignature.h 158
 msrVoices.cpp 300--302
 msrVoices.h 99, 164, 165, 186
 MuseScore 167
 Music eXtended Markup Language 236
 MusicFormats 1, 16, 17, 19--21,
 23, 24, 27--29, 31, 32, 34, 36, 37, 41,
 45--47, 49, 51--53, 60, 69, 70, 74, 75,
 77, 78, 80--82, 84--86, 88--90, 92--94,
 98--100, 103, 105, 106, 108, 109, 121,
 131, 135, 138, 152, 153, 158, 162--165,
 170, 173, 191, 198, 219, 241, 246, 251,
 252, 254--256, 261, 266, 283, 300, 318,
 331, 347, 361, 378, 387--389, 392
 MusicXML 16, 17, 24, 27--31, 39, 45,
 62, 67, 87, 109, 118, 162, 165, 166, 169,
 179, 191, 196, 211, 213--216, 219, 227,
 229, 231, 234, 236, 279, 308, 318, 330,
 333, 346, 349, 361, 382
 musicxmlfiles/fullbarrests/FullBarRestWithoutBarLine.x
 393
 musicxmlfiles/multistaff/SATBExample.xml .393
 MXSR .17, 24, 28, 30, 36, 109, 133, 162, 219,
 227
 mxsr2msrTranslator.cpp 337, 353

N

*NewbornClone 157
 no error message whatsoever 160

O

OAH .. 123, 143--145, 147, 148, 152, 153, 261,
 263, 364
 oahAtomsCollection 122
 oahAtomsCollection.cpp 125, 140, 150
 oahAtomsCollection.h 149
 oahBasicTypes.cpp 132, 138
 oahBasicTypes.h 132
 oahEarlyOptions.cpp 80, 141
 oahEarlyOptions.h 140
 oahElement.cpp 143
 oahElements.cpp 144, 146
 oahElements.h 138
 oahOah.cpp 148
 On/off 90
 Open 253
 operating system ... 24, 75, 89, 246, 252, 389

P

partial order 316
 pass 39
 PNG 20
 position in measure 339
 programming 17
 pure help 128

Q

quarantine 252

R

regular114, 122, 135, 136, 140, 144, 148
 RegularHandler
 createOahRegularGroup ()146
 createOahRegularGroup ()146
 release notes103, 107
 repository 246, 251, 252, 254--256, 388, 390,
 392
 representation38
 run41

S

Security & Privacy252
 semantic108
 service41, 136
 shebang363
 smart pointer202, 213, 214, 216
 standard output ...51, 53, 121, 170, 221, 231
 stopper sets376, 385
 System Preferences252

T

TeXShop19
 three-state90
 type30, 88, 90, 124, 129, 367

U

Ubuntu246

V

version24, 47
 very fine-grained165

W

waeExceptions46
 waeHandlers.cpp79
 waeHandlers.h79
 Web23, 27, 51, 132, 154, 241
 Windows84
 Windows™.....246, 255

X

xml2Any.cpp132
 xml2ly.cpp43
 xmlfile.h215
 xmlreader.h/.cpp216

Z

Zip246, 249