

Jaxer Guide

- [Introduction](#)
- [Setup](#)
- [Develop](#)
- [Debug](#)

Handling SSL Errors

Supplying a handler for Jaxer.XHR.SendOptions.onsslcerterror allows you to inspect a failing SSL certificate. You may then ignore or abort the request by returning true or false, respectively.

Using onsslcerterror in the Jaxer shell

API Links

[Jaxer.XHR.SendOptions](#)
[Jaxer.XHR.ResponseData](#)
[Jaxer.Web.Get](#)

```
01. var options =
02. {
03.     extendedResponse: true,
04.     onsslcerterror: function(socketInfo, sslStatus, targetSite) { return true; }
05. }
06. try
07. {
08.     var resp = Jaxer.Web.get("https://example.aptanacloud.com/", options);
09.     print(uneval(resp.certInfo) + "\n" + resp.text);
10. }
11. catch (e)
12. {
13.     print(e);
14. }
15.
16. // This should print out:
17.
18. ({emailAddress:"(no email address)",
19.   subjectName:"CN=example.aptanacloud.com.aptanacloud.com",
20.   organization:"",
21.   issuerName:"CN=example.aptanacloud.com.aptanacloud.com",
22.   issuerOrganization:"example.aptanacloud.com.aptanacloud.com",
23.   validity:"1224439493000000/1255975493000000",
24.   targetSite:"example.aptanacloud.com:443",
25.   isDomainMismatch:true,
26.   isValidAtThisTime:false,
27.   isUntrusted:true,
28.   isSelfSigned:true})
```