



- [products](#)
- [store](#)
- [blog](#)
- [support](#)
- [community](#)
- [careers](#)
- [company](#)

[Home](#)

Using Jaxer with Apache Tomcat

Jaxer support can be added to Apache Tomcat via the inclusion of two WAR files.

Configuring Tomcat and Jaxer

Copy the jaxer.war and jaxer-server.war files into your webapps directory in your Tomcat home directory.

Configuring the two web.xml files in these war files allows you to connect the Jaxer servlet and Jaxer filter with your running Jaxer server. The two most common parameters that may need to be changed will be the hostname and port of your currently running Jaxer server. The included web.xml files use localhost and 5370 by default.

Jaxer Filter Parameters configured via the init-param element in the web.xml:

- JAXER_PORT - the connector port of the Jaxer server
- JAXER_HOSTNAME - the hostname of the Jaxer server
- IGNORE_PATHS - a list of path segments that when encountered should bypass being processed by Jaxer
- REQUEST_PATH - the request path of the Jaxer callback, only needed when using the JaxerFilter as a callback filter

Jaxer Servlet Parameters configured via the init-param element in the web.xml:

- REQUEST_PATH - the request path of the Jaxer callback that should be handled exclusively by the Jaxer servlet

Necessary WAR files:

- jaxer-server.war
 - This war file is used to handle Jaxer callbacks made by your page
 - WEB-INF
 - web.xml
 - This file configures a filter and server for the /callback URL pattern.
 - lib
 - interfaces.jar (Interfaces implemented by the filter and servlet to allow runtime configuration)
 - jaxer_servlet.jar (Servlet and filter classes as well as classes to communicate directly with Jaxer)
- jaxer.war
 - This war file contains a sample Jaxer application that uses JSP and HTML
 - WEB-INF
 - web.xml
 - This file configures a filter that communicates directly with Jaxer for all requests ending in .html, .html, .HTML, .HTM, .jsp, .jspx
 - lib
 - interfaces.jar (Interfaces implemented by the filter and servlet to allow runtime configuration)
 - jaxer_servlet.jar (Servlet and filter classes as well as classes to communicate directly with Jaxer)

Include Jaxer-Tomcat sample

The jaxer-server.war is required to run any Tomcat applications through Jaxer. It provides the handlers needed for any Jaxer callbacks used by your pages. The jaxer.war file contains two samples of integration between Jaxer and Tomcat. The console.html file contains a simple console written in HTML that uses Javascript and the Jaxer Framework to run entered content as a JSP page and view the results. The index.html shows a sample is mixing client-side JavaScript, server-side JavaScript, and JSP to create a simple application that allows users to translate date and number formats to their current locale.

Once you install the WAR files open a browser to http://<TOMCAT_ADDRESS>/jaxer/ or http://<TOMCAT_ADDRESS>/jaxer/console.html to view the sample applications.

How do I use Tomcat in Aptana Studio?

1. Open the Servers view via Window->Show View->Other...->Aptana Standard Views->Servers
2. Select the Add Server dropdown menu on the Servers view toolbar and select Connect to Generic Web Server
3. Enter a server name such as myTomcat
4. Enter the hostname (Tomcat default is localhost)
5. Enter the port (Tomcat default is 8080)
6. You can optionally add a heartbeat URL for monitoring your server status from Aptana Studio (a sample would be <http://localhost:8080/jaxer>)
7. Select OK
8. Select File->New->Project...
9. Select Default Web Project under the Aptana Projects category and select Next
10. Enter jaxer as the project name
11. Deselect the Use default location checkbox
12. Enter the location <TOMCAT_HOME>/webapps/jaxer and select Next
13. Select Default custom preview settings for this project on the HTML Preview Settings wizard page
14. Select the Use Server radio button
15. Select your Tomcat server from the Server drop-down
16. Select the box for Append project name
17. Select Finish

Files inside the project can now be previewed against your Tomcat server inside the HTML editor.

Servlet Source code:

The source code for the Jaxer filter and servlet code can be found at the following SVN urls:

The com.apтана.ide.framework.jaxer.server.servlet package in the [Jaxer plugin](#)

The com.apтана.ide.server.jetty.interfaces package in the [Jetty plugin](#)

Attachment	Size
jaxer-server.war	79.18 KB
jaxer.war	93.23 KB

Site Navigation

- [Downloads](#)
- [Products](#)
 - [Aptana Jaxer](#)
 - [Download Jaxer](#)
 - [Getting Started with Jaxer](#)
 - [Jaxer Installation Guide \(Mac Standalone\)](#)
 - [Jaxer Installation Guide \(Windows standalone\)](#)
 - [Jaxer FAQ](#)
 - [Jaxer Technical FAQ](#)
 - [Jaxer Legal FAQ](#)
 - [Jaxer Samples](#)
 - [Jaxer Chat Walkthrough](#)
 - [Jaxer Wiki Lite Walkthrough](#)
 - [Your First Full Jaxer Application](#)
 - [Known Jaxer Limitations](#)
 - [Jaxer API](#)

- [Jaxer-Studio Integration](#)
- [Jaxer-Studio Walkthrough](#)
- [Jaxer Quick Start Guide](#)
- [Aptana Studio](#)
 - [Studio Professional Edition](#)
 - [Studio Community Edition](#)
 - [What's New in Studio 1.1](#)
 - [Download Studio](#)
 - [Studio FAQ](#)
 - [Studio Legal FAQ](#)
- [Aptana RadRails](#)
- [Adobe AIR Plugin for Studio](#)
- [Apple iPhone Plugin for Studio](#)
- [Aptana PHP Plugin for Studio](#)
- [Legal](#)
 - [Aptana Public License](#)
 - [GNU Public License](#)
 - [GNU Public License Exception](#)
- [Privacy Policy](#)
- [Support policy](#)

Copyright 2005-2008 Aptana, Inc. | [Contact Us](#) | [Privacy](#).

