

```

<!DOCTYPE html>
<html lang="en">
  <head>
    <!-- Meta data -->
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1">

    <title>Jaxer Counter</title>
  </head>
  <style>
  </style>

  <script type="text/javascript" runat="server">

    //Application starts here
    function initAuthentication()
    {
      var countExampleSql = "CREATE TABLE IF NOT EXISTS countExample " +
        "( id INTEGER PRIMARY KEY AUTO_INCREMENT " +
        ", countAmount INTEGER " +
        ")";
      Jaxer.DB.execute(countExampleSql);

      var countTotal = Jaxer.DB.execute("SELECT COUNT(*) FROM countExample").singleResult;

      if(countTotal<1) {
        Jaxer.DB.execute("INSERT INTO countExample (countAmount) VALUES (?)",
          [0]);
      }

      countTotal = Jaxer.DB.execute("SELECT COUNT(*) FROM countExample").singleResult;

      var resultSet = Jaxer.DB.execute("SELECT * FROM countExample");
      var counterAmount = resultSet.rows[0];

      var countspan = document.createElement("span");
      countspan.id = "countSpan";
      countspan.textContent = "Count: " + counterAmount.countAmount;
      $("countStart").insertBefore(countspan, $("countStart").firstChild);
    }
  </script>

  <!-- This script block will execute only on the server with a prxy to the user because of the
        runat="server-proxy" attributes. -->
  <script type="text/javascript" runat="server-proxy">
    function serverIncrement(filler){
      var resultSet = Jaxer.DB.execute("SELECT * FROM countExample");
      var counterAmount = resultSet.rows[0].countAmount+=1;
      Jaxer.DB.execute("UPDATE countExample SET countAmount = ? WHERE id = 1",
        [counterAmount]);
      return counterAmount;
    }

    function serverDecrement(filler){
      var resultSet = Jaxer.DB.execute("SELECT * FROM countExample");
      var counterAmount = Math.max(resultSet.rows[0].countAmount-=1,0);
      Jaxer.DB.execute("UPDATE countExample SET countAmount = ? WHERE id = 1",
        [counterAmount]);
      return counterAmount;
    }
  </script>

```

```

        <!-- This script block will be available on both client and server since the
              runat attribute is set to 'both'. -->
<script type="text/javascript" runat="both">
    /*
     * Easy access to a named element in the DOM
     */
    function $(id) {
        return document.getElementById(id);
    }
</script>

<body class="nes-container is-dark" onserverload="initAuthentication();">
    <div class="main">
        <h1 id="countStart">

        </h1>

        <button id="incrementButton">
            Increment
        </button>
        <button id="decrementButton">
            Decrement
        </button>
    </div>
</div>

<script defer type="text/javascript">
    function incrementDecrementResponse(msg){
        $("countSpan").textContent = "Count: " + msg;
    }

    incrementButton.addEventListener("click", function () {
        serverIncrement.async(incrementDecrementResponse, "hello");
    });

    decrementButton.addEventListener("click", function () {
        serverDecrement.async(incrementDecrementResponse, "hello");
    });
</script>
</body>
</html>

```