

```

<!DOCTYPE html>
<html lang="en">
  <head>
    <!-- Meta data -->
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1">

    <title>Jaxer Counter</title>
  </head>
  <style>
  </style>

  <script type="text/javascript">
    function increment(){
      serverIncrement.async(incrementDecrementResponse, "hello");
    }

    function decrement(){
      serverDecrement.async(incrementDecrementResponse, "hello");
    }

    function incrementDecrementResponse(msg){
      $("#countSpan").innerHTML = "Count: " + msg;
    }
  </script>

  <script type="text/javascript" runat="server">

    //Application starts here
    function initAuthentication()
    {
      var countExampleSql = "CREATE TABLE IF NOT EXISTS countExample " +
        "( id INTEGER PRIMARY KEY AUTO_INCREMENT " +
        ", countAmount INTEGER " +
        ")";
      Jaxer.DB.execute(countExampleSql);

      var countTotal = Jaxer.DB.execute("SELECT COUNT(*) FROM countExample").singleResult;
      const countStartVar = 0;

      if(countTotal<1) {
        Jaxer.DB.execute("INSERT INTO countExample (countAmount) VALUES (?)",
          [0]);
      }

      countTotal = Jaxer.DB.execute("SELECT COUNT(*) FROM countExample").singleResult;

      var resultSet = Jaxer.DB.execute("SELECT * FROM countExample");
      var counterAmount = resultSet.rows[0];

      var countspan = document.createElement("span");
      countspan.id = "countSpan";
      countspan.innerHTML = "Count: " + counterAmount.countAmount;
      $("#countStart").insertBefore(countspan, $("#countStart").firstChild);
    }
  </script>

  <!-- This script block will execute only on the server with a prxy to the user because of the
        runat="server-proxy" attributes. -->
  <script type="text/javascript" runat="server-proxy">

```

```

function serverIncrement(filler){
    var resultSet = Jaxer.DB.execute("SELECT * FROM countExample");
    var counterAmount = resultSet.rows[0].countAmount+=1;
    Jaxer.DB.execute("UPDATE countExample SET countAmount = ? WHERE id = 1",
        [counterAmount]);
    return counterAmount;
}

function serverDecrement(filler){
    var resultSet = Jaxer.DB.execute("SELECT * FROM countExample");
    var counterAmount = Math.max(resultSet.rows[0].countAmount-=1,0);
    Jaxer.DB.execute("UPDATE countExample SET countAmount = ? WHERE id = 1",
        [counterAmount]);
    return counterAmount;
}
</script>

```

<!-- This script block will be available on both client and server since the
runat attribute is set to 'both'. -->

```

<script type="text/javascript" runat="both">
/*
 * Easy access to a named element in the DOM
 */
function $(id) {
    return document.getElementById(id);
}
</script>

```

```

<body class="nes-container is-dark" onserverload="initAuthentication();">
    <div class="main">
        <h1 id="countStart">

        </h1>

        <button onclick="increment()">
            Increment
        </button>
        <button onclick="decrement()">
            Decrement
        </button>
    </div>
</div>
</body>
</html>

```