

```

<!DOCTYPE html>
<html lang="en">
  <head>
    <!-- Meta data -->
    <meta charset="UTF-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width, initial-scale=1">

    <title>Codes With Pankaj</title>
    <script src="js/bootstrap.min.js"></script>
    <link rel='stylesheet' type='text/css' href='css/bootstrap.min.css'>

    <style>
/* Table utility style declarations */
.collapseabletable {
  border-collapse: collapse;
  border-spacing: 0;
  border: 1px solid;
}

.collapseabletabletr {
  border: 1px solid;
}

.double-wall-padding {
  padding-left: 16px;
  padding-right: 16px;
}
</style>
</head>
<body>
<nav id="headerTag">
  <div id="header" class="container">
    <header class="container mt-5 py-3 mb-4 border-bottom">
      <div class="row align-items-left">
        <div class="col">
          <a href="javascript:viewIndex(); void(0)">
             &nbsp;
            <span>Codes With Pankaj - @p4n.in </span>
          </a>
        </div>
        <div class="col col-sm-3">
          <ul class="nav nav-pills">
            <li class="nav-item"><a href="javascript:viewAddUser(); void(0)" class="nav-link active ml-3 mr-1 mt-3" aria-current="page">Add User</a></li>
            <li class="nav-item"><a href="javascript:viewShowUsers(); void(0)" class="nav-link active mt-3">View Users</a></li>
          </ul>
        </div>
      </div>
    </header>
    <p> - Jaxer CRUD operations</p>
  </div>
</nav>

<!-- BEGINNING OF TEMPLATES -->
<div id="userform" class="container mt-5" style="display:none">
  <div class="mb-3">
    <label for="user-Form-Name" class="form-label">Name:</label>
    <input type="text" class="form-control" id="user-Form-Name" name="user-Form-Name">
  </div>
  <div class="mb-3">
    <label for="user-Form-Password" class="form-label">Password:</label>

```

```

word">
    <input type="password" class="form-control" id="user-Form-Password" name="user-Form-Pass-
</div>
<div class="mb-3">
    <label for="user-Form-Email" class="form-label">Email:</label>
    <input type="email" class="form-control" id="user-Form-Email" name="user-Form-Email">
</div>
<div class="mb-3">
    <label for="user-Form-Gender" class="form-label">Gender:</label>
    <select class="form-select" id="user-Form-Gender" name="user-Form-Gender">
        <option value="Other">--Select--</option>
        <option value="Male">Male</option>
        <option value="Female">Female</option>
    </select>
</div>
<div class="mb-3">
    <label for="user-Form-Country" class="form-label">Country:</label>
    <select class="form-select" id="user-Form-Country" name="user-Form-Country">
        <option value="India">India</option>
        <option value="Pakistan">Pakistan</option>
        <option value="Afghanistan">Afghanistan</option>
        <option value="Burma">Burma</option>
        <option value="Australia">Australia</option>
        <option value="Canada">Canada</option>
        <option value="Brazil">Brazil</option>
        <option value="France">France</option>
        <option value="Japan">Japan</option>
        <option value="Mexico">Mexico</option>
        <option value="South Africa">South Africa</option>
        <option value="Other">Other</option>
    </select>
</div>
</div>
<div id="usersTable" class="container mt-5" style="display:none">
    <div class="mb-3">
        <h4 class="display-5 fw-bold text-body-emphasis">Users</h4>
        <table class="collapseabletable">
            <thead>
                <tr>
                    <td class="double-wall-padding collapseabletable">Username</td>
                    <td class="double-wall-padding collapseabletable">Password</td>
                    <td class="double-wall-padding collapseabletable">Email</td>
                    <td class="double-wall-padding collapseabletable">Gender</td>
                    <td class="double-wall-padding collapseabletable">Country</td>
                    <td class="double-wall-padding collapseabletable">Edit box</td>
                    <td class="double-wall-padding collapseabletable">Delete box</td>
                </tr>
            </thead>
            <tbody id="outputTable">

                </tbody>
        </table>
    </div>
</div>
<div id="addUserButton" class="container mt-5" style="display:none">
    <input type="button" class="btn btn-primary" id="addUserButton" value="Add User" onclick="addUser()">
</div>
<div id="editUserButton" class="container mt-5" style="display:none">
    <input type="button" class="btn btn-primary" id="editUserButton" value="Edit User" onclick="editUser()">
</div>

```

```
<!-- END OF TEMPLATES -->
```

```
</body>
```

```
<script>
```

```
//views
```

```
function viewIndex()
```

```
{
```

```
    document.getElementById("usersTable").style.display = "none";
```

```
    document.getElementById("userform").style.display = "none";
```

```
    document.getElementById("addUserButton").style.display = "none";
```

```
    document.getElementById("editUserButton").style.display = "none";
```

```
}
```

```
function viewAddUser()
```

```
{
```

```
    $('user-Form-Name').value = "";
```

```
    $('user-Form-Password').value = "";
```

```
    $('user-Form-Email').value = "";
```

```
    $('user-Form-Gender').value = "";
```

```
    $('user-Form-Country').value = "";
```

```
    document.getElementById("usersTable").style.display = "none";
```

```
    document.getElementById("userform").style.display = "block";
```

```
    document.getElementById("addUserButton").style.display = "block";
```

```
    document.getElementById("editUserButton").style.display = "none";
```

```
}
```

```
function viewShowUsers()
```

```
{
```

```
    document.getElementById("usersTable").style.display = "block";
```

```
    document.getElementById("userform").style.display = "none";
```

```
    document.getElementById("addUserButton").style.display = "none";
```

```
    document.getElementById("editUserButton").style.display = "none";
```

```
    databaseViewUsers.async(addUserToUI, "action");
```

```
}
```

```
function viewEditUser()
```

```
{
```

```
    document.getElementById("usersTable").style.display = "none";
```

```
    document.getElementById("userform").style.display = "block";
```

```
    document.getElementById("addUserButton").style.display = "none";
```

```
    document.getElementById("editUserButton").style.display = "block";
```

```
}
```

```
function editUser()
```

```
{
```

```
    editUserButton.value = "editing user...";
```

```
    editUserButton.disabled = true;
```

```
    var userFormName = $('user-Form-Name').value;
```

```
    var userFormPassword = $('user-Form-Password').value;
```

```
    var userFormEmail = $('user-Form-Email').value;
```

```
    var userFormGender = $('user-Form-Gender').value;
```

```
    var userFormCountry = $('user-Form-Country').value;
```

```
    if(userFormName == "" || userFormPassword == "" || userFormEmail == "" || userFormGender == "" || user-  
FormCountry == "")
```

```
{
```

```
    alert("One of the fields is blank, please enter values for all fields.");
```

```
    editUserButton.value = "edit User";
```

```
    editUserButton.disabled = false;
```

```
    return;
```

```
}
```

```

        saveUserInDBEditUser.async(databaseFinishedEditUser, userFormName, userFormPassword, user-
FormEmail, userFormGender, userFormCountry);
    }

    function databaseFinishedEditUser(msg)
    {
        // Set the button state and label back to normal
        editUserButton.value = "edit User";
        editUserButton.disabled = false;

        switch (msg) {
            case "Successfully edited to database":
                var pom = document.createElement('a');
                pom.href = "javascript:viewIndex(); void(0)";
                document.body.appendChild(pom);
                pom.click();
                pom.parentNode.removeChild(pom);
                break;
            default:
                alert(msg);
        }
    }

    /*
    * We override the ontimeoutAsync function so that we can know if we timed out
    * in trying to talk to the server.
    */
    Jaxer.Callback.ontimeoutAsync = function(xhr, timeout, extra)
    {
        databaseFinishedAddUser("The request timed out after " + timeout/1000 + " seconds, aborting.");
    }

    function addUser()
    {
        addUserButton.value = "Adding user...";
        addUserButton.disabled = true;

        var userFormName = $('user-Form-Name').value;
        var userFormPassword = $('user-Form-Password').value;
        var userFormEmail = $('user-Form-Email').value;
        var userFormGender = $('user-Form-Gender').value;
        var userFormCountry = $('user-Form-Country').value;

        if($('user-Form-Name').value == "" || $('user-Form-Password').value == "" || $('user-Form-Email').value == "" ||
$('user-Form-Gender').value == "" || $('user-Form-Country').value == "")
        {
            alert("One of the fields is blank, please enter values for all fields.");
            addUserButton.value = "Add User";
            addUserButton.disabled = false;
            return;
        }

        var newId = Math.ceil(1000000000 * Math.random());
        saveUserInDBAddUser.async(databaseFinishedAddUser, newId, userFormName, userFormPassword,
userFormEmail, userFormGender, userFormCountry);
    }

    function databaseFinishedAddUser(msg)
    {
        // Set the button state and label back to normal
        addUserButton.value = "Add User";
        addUserButton.disabled = false;
    }

```

```

switch (msg) {
    case "Successfully added to database":
        var pom = document.createElement('a');
        pom.href = "javascript:viewIndex(); void(0)";
        document.body.appendChild(pom);
        pom.click();
        pom.parentNode.removeChild(pom);
        break;
    default:
        alert(msg);
}
}

```

```

function addUserToUI(resultSet)

```

```

{
    $("outputTable").innerHTML = "";
    for (var i=0; i<resultSet.rows.length; i++)
    {
        var task = resultSet.rows[i];

```

```

        var userFormName = `<td class="double-wall-padding collapseabletable">${task.userFormName}</td>
        <td class="double-wall-padding collapseabletable">${task.userFormPassword}</td>
        <td class="double-wall-padding collapseabletable">${task.userFormEmail}</td>
        <td class="double-wall-padding collapseabletable">${task.userFormGender}</td>
        <td class="double-wall-padding collapseabletable">${task.userFormCountry}</td>
        <td class="double-wall-padding collapseabletable"><input id="editUserCheckBox_${task.id}"
type="checkbox" title="done" onclick="editUserTask(${task.id})" class="double-wall-padding collapseabletable"></td>
        <td class="double-wall-padding collapseabletable"><input id="deleteUserCheckBox_${task.id}"
type="checkbox" title="done" onclick="completeTask(${task.id})" class="double-wall-padding collapseabletable"></td>`;

```

```

        var tr = document.createElement("tr");
        tr.id = "task_" + task.id;
        tr.className = "task";

```

```

        tr.innerHTML = userFormName;

```

```

        $("outputTable").insertBefore(tr, $("outputTable").firstChild);
    }
}

```

```

function completeTask(taskId)

```

```

{
    var tr = $("task_" + taskId);
    tr.parentNode.removeChild(tr);
    deleteSavedTask(taskId);
}

```

```

function editUserTask(taskId)

```

```

{
    var tr = $("task_" + taskId);
    editSavedTask.async(databaseFinishedSelectUser, taskId);
}

```

```

function databaseFinishedSelectUser(msg)

```

```

{
    $('#user-Form-Name').value = msg.userFormName;
    $('#user-Form-Password').value = msg.userFormPassword;
    $('#user-Form-Email').value = msg.userFormEmail;
    $('#user-Form-Gender').value = msg.userFormGender;
    $('#user-Form-Country').value = msg.userFormCountry;
    viewEditUser();
}

```

```

    }
</script>

<script type="text/javascript" runat="both">
function $(id)
{
    return document.getElementById(id);
}

function fromTemplate(idTarget, idSource) { $(idTarget).innerHTML = $(idSource).innerHTML.re-
place(/(\W)\$id\=/g, "$1id="); }
</script>

<script type="text/javascript" runat="server">
window.onload = function()
{
    var addUsersSql = "CREATE TABLE IF NOT EXISTS users " +
        "( id INTEGER NOT NULL " +
        ", userFormName VARCHAR(255)" +
        ", userFormPassword VARCHAR(255)" +
        ", userFormEmail VARCHAR(255)" +
        ", userFormGender VARCHAR(255)" +
        ", userFormCountry VARCHAR(255)" +
        ", created DATETIME NOT NULL " +
        ")";

        Jaxer.DB.execute(addUsersSql);
    }

    function deleteSavedTask(id)
    {
        Jaxer.DB.execute("DELETE FROM users WHERE id = ?", [id]);
    }
    deleteSavedTask.proxy = true;

function makeEditSelection(Selection)
{
    Jaxer.session.usertoEdit = Selection.id;
}

function removeEditSelection()
{
    delete Jaxer.session.usertoEdit;
}
</script>

<script type="text/javascript" runat="server-proxy">
function editSavedTask(id)
{
    var resultSet = Jaxer.DB.execute("SELECT * FROM users WHERE id = ?", [id]);
    var task = resultSet.rows[0];
    makeEditSelection(task);
    return task;
}

function saveUserInDBAddUser(id, userFormName, userFormPassword, userFormEmail, userFormGender, user-
FormCountry)
{
    try {
        Jaxer.DB.execute("INSERT INTO users (id, userFormName, userFormPassword,
userFormEmail, userFormGender, userFormCountry, created)" +
        "VALUES (?, ?, ?, ?, ?, ?, ?)",
        [id, userFormName, userFormPassword, userFormEmail, userFormGender, userFormCountry, new Date()]);
    }
}

```

```

        catch (e) {
            return e.toString();
        }
        return "Successfully added to database";
    }

    function saveUserInDBEditUser(userFormName, userFormPassword, userFormEmail, userFormGender, userFormCountry)
    {
        try {
            user = Jaxer.session.usertoEdit;

            Jaxer.DB.execute("UPDATE users SET userFormName = ?, userFormPassword = ?,
userFormEmail = ?, userFormGender = ?, userFormCountry = ? WHERE id = ?",
[userFormName, userFormPassword, userFormEmail, userFormGender, userFormCountry, user]);
        }
        catch (e) {
            return e.toString();
        }

        removeEditSelection();
        return "Successfully edited to database";
    }

    function databaseViewUsers(action)
    {
        var resultSet = Jaxer.DB.execute("SELECT * FROM users ORDER BY created");
        return resultSet;
    }
}
</script>
</html>

```