

# Nonobtuse remeshing with a guaranteed angle bound

**Abstract**—Quality meshing is an important problem in geometric modeling, visualization and scientific computing. In this paper, we propose a 3D triangular remeshing method with a *guaranteed* angle bound of  $[30^\circ, 90^\circ]$ . Given a original 2-manifold, open or closed, a rough approximate mesh with the proposed angle bound is first generated. This is achieved by a novel extension of the classical marching cubes algorithm. Next, an iterative constrained optimization, along with constrained Laplacian smoothing, decimation, and subdivision, is performed to arrive at a close approximation of the original mesh.

**Index Terms**—Remeshing, non-obtuse meshes, marching cube, deform-to-fit.

## 1 INTRODUCTION

The most commonly used shape representation is triangular mesh. Efficient rendering, finite element analysis, and geometry processing such as compression, smoothing and deformation benefit from high quality meshes. Thus, a lot remeshing methods have been proposed to improve the mesh quality [1], both in terms of geometry [2], [3] and connectivity [4], [5].

In terms of geometry quality, it is desirable for the triangular mesh to have no small angles and/or no larger angles, depending on the targeted applications [6]. For example, an essential condition of the accuracy of finite element solutions on triangular meshes is that the angle of any triangle, independent of its size, should not be small. This is called the minimum angle condition. Furthermore, both small and large angles can cause poor condition of the stiffness matrix [6]. For some applications, nonobtuse mesh, in which every angle is no larger than  $90^\circ$ , are desirable. Nonobtuse meshes result in more efficient and more accurate geodesic distances computation by fast marching method [7]. Also, nonobtusity ensures the well-known cotangent weights of discrete Laplace-Beltrami operator would be positive [8].

Thus, there have been lots of works on 2D triangulation with angle bounds and remeshing of curved surfaces with angle quality criterion. Chew develops a refinement scheme to ensure an angle bound of  $[30^\circ, 120^\circ]$  based on constrained Delaunay triangulation [9]. Bern et al. propose an  $O(n \log^2 n)$  nonobtuse triangulating algorithm [10]. Cheng and Shi [11] use restricted union of balls to generate an  $\varepsilon$ -sampling of a surface and extract a mesh from the Delaunay triangulation of the sample points, where a lower angle bound of  $30^\circ$  can be obtained. A survey on

nonobtuse simplicial partitions is given in [12]. A novel obtuse triangle suppression method is proposed in [13] based on centroidal Voronoi tessellation.

In this paper, we extend our nonobtuse remeshing work [14] to the angle bound of  $[30^\circ, 90^\circ]$ . Furthermore, our method can preserve the sharp feature during the process of remeshing.

### 1.1 Subsection Heading Here

Subsection text here.

### 1.1.1 Subsubsection Heading Here

Subsubsection	text	here.Subsubsection	text
here.Subsubsection	text	here.Subsubsection	text
here.Subsubsection	text	here.Subsubsection	text
here.Subsubsection	text	here.Subsubsection	text
here.Subsubsection	text	here.Subsubsection	text
here.Subsubsection	text	here.Subsubsection	text
here.Subsubsection	text	here. Subsubsection	text
here.Subsubsection	text	here.Subsubsection	text here.

[illegible]

## 2 CONCLUSION

[illegible]

- ...
- ...

here. The conclusion goes here. The conclusion goes here. The conclusion goes here. The conclusion goes here.

## APPENDIX A

## PROOF OF THE FIRST ZONKLAR EQUATION

Appendix one text goes here.

## APPENDIX B

Appendix two text goes here.Appendix two text goes  
here.Appendix two text goes here.Appendix two text  
goes here.Appendix two text goes here.Appendix two  
text goes here.Appendix two text goes here.Appendix  
two text goes here.Appendix two text goes  
here.Appendix two text goes here.Appendix two text  
goes here.Appendix two text goes here.Appendix two  
text goes here.Appendix two text goes here.Appendix  
two text goes here.Appendix two text goes  
here.Appendix two text goes here.Appendix two  
text goes here.

## ACKNOWLEDGMENTS

[illegible]

## REFERENCES

- [1] P. Alliez, G. Ucelli, C. Gotsman, and M. Attene, "Recent advances in remeshing of surfaces," *Shape Analysis and Structuring*, pp. 53–82, 2008.
- [2] P. Alliez, E. C. de Verdiere, O. Devillers, and M. Isenburg, "Isotropic surface remeshing," in *Proceedings of Shape Modeling International*, 2003, pp. 49–58.
- [3] P. Alliez, D. Cohen-Steiner, O. Devillers, B. Lévy, and M. Desbrun, "Anisotropic polygonal remeshing," *ACM Transactions on Graphics*, vol. 22, no. 3, pp. 485–493, 2003.
- [4] I. Guskov, "Manifold-based approach to semi-regular remeshing," *Graphical Models*, vol. 69, no. 1, pp. 1–18, 2007.
- [5] N. Aghdaii, H. Younesy, and H. Zhang, "5-6-7 meshes," in *Graphics Interface*, 2012, pp. 27–34.
- [6] J. R. Shewchuk, "What is a good linear element? interpolation, conditioning, and quality measures," in *Proceedings of 11th International Meshing Roundtable*, 2002, pp. 115–126.
- [7] R. Kimmel and J. A. Sethian, "Computing geodesic paths on manifolds," *Proc. of National Academy of Science USA*, vol. 95, no. 15, pp. 8431–8435, 1998.
- [8] M. Wardetzky, S. Mathur, F. Küberer, and E. Grinspun, "Discrete laplace operators: No free lunch," in *Symposium on Geometry Processing*, 2007, pp. 33–37.
- [9] L. P. Chew, "Guaranteed-quality mesh generation for curved surfaces," in *ACM Symposium on Computational Geometry*, 1993, pp. 274–280.

- [10] M. Bern, S. Mitchell, and J. Ruppert, "Linear-size nonobtuse triangulation of polygons," in *Symposium on Computational Geometry*, 1994, pp. 221–230.
- [11] H.-L. Cheng and X. Shi, "Quality mesh generation for molecular skin surfaces using restricted union of balls," in *IEEE Visualization*, 2005, pp. 399–405.
- [12] J. Brandts, S. Korotov, M. Křížek, and J. Šolc, "On nonobtuse simplicial partitions," *ALAM Review*, vol. 51, no. 2, pp. 317–335, 2009.
- [13] F. Sun, Y.-K. Choi, W. Wang, D.-M. Yan, Y. Liu, and B. Lèvy, "Obtuse triangle suppression in anisotropic meshes," *Computer Aided Geometric Design*, vol. 28, no. 9, pp. 537–548, 2011.
- [14] J. Y. S. Li and H. Zhang, "Nonobtuse remeshing and mesh decimation," in *Eurographics Symposium on Geometry Processing*, 2006, pp. 235–238.