```
local ReplicatedStorage = game:GetService("ReplicatedStorage")
local Players = game:GetService("Players")
local RunService = game:GetService("RunService")
local event = ReplicatedStorage:WaitForChild("AnimationEvent")

local idleKeyframe = script:WaitForChild("Idle")
local walkKeyframe = script:WaitForChild("Walk")
local runKeyframe = script:WaitForChild("Run")
local jumpKeyframe = script:WaitForChild("Jump")

-- Settings
local RUN_SPEED = 18      -- speed at or above this = Run, below = Walk
local MOVE_DEADZONE = 0.2 -- how much input counts as "moving"

-- speed = animation length multiplier (smaller = faster)
local animations = {
    Idle = {kf = idleKeyframe, speed = 1},
    Walk = {kf = walkKeyframe, speed = 0.5},
    Run  = {kf = runKeyframe,  speed = 0.3},
    Jump = {kf = jumpKeyframe, speed = 1},
}

local function playAnimate(kf, chr, multi)
    event:Fire("SwitchAnimation", chr, kf, multi)
end

local function setupCharacter(chr)
    local humanoid = chr:WaitForChild("Humanoid")
    local root = chr:WaitForChild("HumanoidRootPart")
    local state = nil

    local function setState(newState)
        if state == newState then return end
        state = newState
        local data = animations[newState]
        playAnimate(data.kf, chr, data.speed)
    end

    local connection
    connection = RunService.Heartbeat:Connect(function()
        if not chr.Parent or humanoid.Health <= 0 then
            connection:Disconnect()
            return
```

```
        end

        if humanoid.FloorMaterial == Enum.Material.Air then
            setState("Jump")
        elseif humanoid.MoveDirection.Magnitude > MOVE_DEADZONE then
            local v = root.AssemblyLinearVelocity
            local speed = Vector3.new(v.X, 0, v.Z).Magnitude
            if speed >= RUN_SPEED then
                setState("Run")
            else
                setState("Walk")
            end
        else
            setState("Idle")
        end
    end)
end

local function setupPlayer(plr)
    plr.CharacterAdded:Connect(setupCharacter)
    if plr.Character then
        setupCharacter(plr.Character)
    end
end

Players.PlayerAdded:Connect(setupPlayer)
for _, plr in pairs(Players:GetPlayers()) do
    setupPlayer(plr)
end
```