```
#=============================================================================================
# SADMIN Alert Group file definition  v 2.5
#---------------------------------------------------------------------------------------------
# This file is use when an Error or a Warning is detected by SADM System Monitor or when a script
# need to send an Alert. The scripts (Shell and Python) and SADMIN System Monitor sent alert to
# an alert group defined in this file.
#
# - If the Alert Group file ($SADMIN/cfg/alert_group.cfg) file doesn't exist then it's created
#   from the default Alert Group file ($SADMIN/cfg/.alert_group.cfg).
# - Blank line or line beginning with a pound sign (#) are ignored.
# - Field delimiter is a space.
# - Each Alert Group Name MUST be unique and cannot contain spaces.
#
# FIRST COLUMN (GROUP NAME)
#   - Alert Group name is use in the SysMon (hostname.smon) config file to designated who to alert.
#   - Alert Group name MUST be unique within this file and can used up to 15 characters (No Space).
#
#
#   ALERT GROUP SPECIFIED IN A SCRIPT (Bash Shell & Python)
#       - You specify the Alert Group by changing the appropriate line(s) below in the SADMIN
#         section at the beginning of your script.
#
#         Shell Script :
#           export SADM_ALERT_TYPE=3            # 0=NoAlert 1=OnlyOnError 2=OnlyOnSucces 3=Always
#           export SADM_ALERT_GROUP="default"   # [ ERROR ] Alert Group Name (Default Alert Group)
#           export SADM_WARNING_GROUP="default" # [ WARNING ] Alert Group Name
#           export SADM_INFO_GROUP="default"    # [ INFO ] Alert Group Name
#
#         Python Script :
#            sa.sadm_alert_type    = 3          # 0=NoAlert 1=AlertOnError 2=AlertOnSuccess 3=Always
#            sa.sadm_alert_group   = "default"  # Error Alert Group
#            sa.sadm_warning_group = "warning"  # Warning Alert Group
#            sa.sadm_info_group    = "info"     # Info Alert    Group
#
#   - USING ALERT GROUP IN SADMIN SYSTEM MONITOR
#       - You specify the Alert Group you want to use for System Monitor Warning in column J and
#         for Error in column K. In the example below, we use alerting group 'sdevops' for Warning
#         and 'sprod' for Error.
#       - Example of a ping test in line a hostname.smon of a client.
#           Column 1            2 3  4  5  6    7   8   9 A B C D E F G    H       I     J    K   L
#           ping_www.google.com 0 = 01 00 000 0000 0000 Y Y Y Y Y Y Y Y 00000000 0000 sdevops sprod -
#       - If the Alert group used in SysMon configuration don't exist in this file, the default group
#         ('default') is use.
#
```

```
45  #
46  # SECOND COLUMN (GROUP TYPE)
47  #   - This column can only have the values a 'm', 't', 'n' and a 's' (Lowercase/Uppercase allowed).
48  #   - If it contain other value then 'm' is assumed.
49  #   - This column specify the alert group type :
50  #       - 'm' Specify a Mail Group.
51  #       - 's' Specify a Slack Group .
52  #             For now only one slack channel can be use per group (change will come)
53  #       - 't' Specify a SMS (Texto) Group.
54  #       - 'n' Specify Notification group for ntfy
55  #
56  #
57  # THIRD COLUMN (GROUP RECIPIENT)
58  #   - For Alert of type 'm' (Email) :
59  #       - Email address(es) corresponding to the mail group in column one.
60  #       - If you specify more than one email address, they must be separated by a comma.
61  #   - For Alert of type 's' (Slack) :
62  #       - Slack Channel defined in SADMIN Slack Channel File.
63  #       - Channel name used MUST be define in the Slack Channel file ($SADMIN/cfg/alert_slack.cfg).
64  #       - For now only one slack channel can be use per group (change will come)
65  #   - For Alert of type 't' (Texto, SMS) :
66  #       - Third column is use to group cellular number together to form an alert Group.
67  #         If more than one is specified, they must be separated by a comma.
68  #   - For Alert of type 'n" for ntfy :
69  #         Notification Alert using ntfy application on your tablet or cellular
70  #
71  # The 'default' Alert Group MUST always exist and MUST refer to one Email, Slack or Texto group.
72  #---------------------------------------------------------------------------------------------

73  # Choose your default group, to send notification to who it may concern.
74  #default            s   slack_sprod
75  #default            t   sms_emergency
76  #ntfy               n   ntfy_default
77  default                m   mail_sysadmin

78  # Email Alert Group
79  mail_sysadmin       m   20sadm22@gmail.com
80  mail_webteam        m   webteam@acme.com,sysadmin@acme.com
81  mail_app            m   batman@batcave.com,robin@batcave.com,alfred@batcave.com
82  mail_alfred         m   alfred@batcave.com

83  # NTFY Alert Group (Topics)
84  ntfy_default        n   batntfy
```

```
 85  # SMS (Texto) Alert Group, members are Cellular name
 86  sms_sysadmin        t   cell_john_doe
 87  sms_emergency       t   cell_john_doe,cell_support,cell_robert_smith,cell_diane_watson
 88  sms_webteam             t   cell_diane_watson

 89  # Cellular number of individual (Use only in SMS alert group)
 90  cell_john_doe       c   5147577706
 91  cell_robert_smith   c   4187570067
 92  cell_support        c   5147570068
 93  cell_jerry_calder       c   5147779302
 94  cell_diane_watson   c   5147779303

 95  # Slack Alert Group
 96  # 3th column is the channel name defined in Slack Alert file ($SADMIN/cfg/alert_slack.cfg).
 97  slack_sdev     s  sadm_dev    https://hooks.slack.com/services/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
 98  slack_sprod    s  sadm_prod   https://hooks.slack.com/services/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
 99  slack_sinfo    s  sadm_info   https://hooks.slack.com/services/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
100  slack_sdevops  s  sadm_devops https://hooks.slack.com/services/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
101
```