## **Details**

Form factor 55mm x 86mm x 19mm (with mbed)

128x32 Graphics LCD, SPI Interface Newhaven C12832A1Z

> MOSI:p5 nRESET:p6 SCK:p7 8q:0A

3 Axis +/1 1.5g Accelerometer,I2C Interface Freescale MMA7660

> SCL:p27 SDA:p28 Address:0x98

Temperature sensor LM75B

> SCL:p27 SDA:p28 Address:0x90

**ALPS SKRHADE010** 5 way Joystick

> Down:p12 Left:p13 Centre:p14 Up:p15 Right:p16

2 x Potentiometers Iskra PNZ10ZA, 10k

> Pot 1 (left):p19 Pot 2 (right):p20

CUI Inc SJ-3523-SMT 2 x 3.5mm Audio jack (Analog In/Out)

> Analog In:p17 Analog Out:p18

2 x Servo motor headers PWM1:p22

PWM2:p21

RGB LED, PWM connected Cree Inc CLV1A-FKB

> Red:p23 Green:p24 Blue:p25

Speaker, PWM Connected MULTICOMP MCSMT-8030B-3717

p26

**USB-B Connector** Neltron, 5075ABMR-05-SM1 RJ45 Ethernet conenctor Pulse Jack, J00-0045NL

1.3mm DC Jack input

CLIFF, FC68145S

1.3mm 6v-9v

Centre positive