

Ex No 8:

-- PRE-DEFINED EXCEPTIONS

DECLARE

c_id customer.id%TYPE := 5;

c_name customer.name%TYPE;

c_addr customer.address%TYPE;

BEGIN

SELECT name, address INTO c_name, c_addr

FROM customer WHERE id = c_id;

DBMS_OUTPUT.PUT_LINE('name: ' || c_name);

DBMS_OUTPUT.PUT_LINE('address: ' || c_addr);

EXCEPTION

WHEN NO_DATA_FOUND THEN

DBMS_OUTPUT.PUT_LINE('no such customer!');

WHEN OTHERS THEN

DBMS_OUTPUT.PUT_LINE('error!');

END;

/

-- USER-DEFINED EXCEPTIONS

DECLARE

c_id customers.id%TYPE := &cc_id;

c_name customers.name%TYPE;

c_addr customers.address%TYPE;

ex_invalid_id EXCEPTION;

BEGIN

IF c_id <= 0 THEN

RAISE ex_invalid_id;

ELSE

SELECT name, address INTO c_name, c_addr

FROM customers WHERE id = c_id;

DBMS_OUTPUT.PUT_LINE('Name: ' || c_name);

DBMS_OUTPUT.PUT_LINE('Address: ' || c_addr);

END IF;

EXCEPTION

WHEN ex_invalid_id THEN

DBMS_OUTPUT.PUT_LINE('ID must be greater than zero!');

WHEN NO_DATA_FOUND THEN

DBMS_OUTPUT.PUT_LINE('No such customer!');

```
WHEN OTHERS THEN
    DBMS_OUTPUT.PUT_LINE('Error!');
END;
/
```

```
-- Example output:
-- Enter value for cc_id: -6
-- ID must be greater than zero!
```

Output:

```
SQL> SET SERVEROUTPUT ON;
```

```
SQL> -- Pre-defined exception
```

```
SQL> /
```

```
no such customer!
```

```
PL/SQL procedure successfully completed.
```

```
SQL> -- User-defined exception
```

```
Enter value for cc_id: -6
```

```
ID must be greater than zero!
```

```
PL/SQL procedure successfully completed.
```

```
Example with a valid customer ID:
```

```
Enter value for cc_id: 1
```

```
Name: <customer name>
```

```
Address: <customer address>
```

```
PL/SQL procedure successfully completed.
```