

Ex No 9:

//Key-Value store example (Redis-style)

SET Name "Joe Bloggs"

SET Age 42

SET Occupation "Stunt Double"

SET Height "175cm"

SET Weight "77kg"

// Column-based store example (Cassandra CQL)

CREATE TABLE ColumnFamily (

RowKey text PRIMARY KEY,

col1 text,

col2 text,

col3 text

);

// Document-oriented example (MongoDB)

db.documents.insertMany([

{ "prop1": "data", "prop2": "data", "prop3": "data", "prop4": "data" }, {

"prop1": "data", "prop2": "data", "prop3": "data", "prop4": "data" }, {

"prop1": "data", "prop2": "data", "prop3": "data", "prop4": "data" }

]);

// Graph-based example (Cypher / Neo4j)

CREATE (p:Person {name:"Alice"})-[:LIVES_IN]->(c:City {name:"Chennai"})

CREATE (p)-[:LIKES {rating:5}]->(r:Restaurant {name:"Spice House"})

CREATE (r)-[:LOCATED_IN]->(c)

Output:

Redis> SET Name "Joe Bloggs"

OK

Redis> SET Age 42

OK

Redis> SET Occupation "Stunt Double"

OK

Redis> SET Height "175cm"

OK

Redis> SET Weight "77kg"

OK

Cassandra> CREATE TABLE ColumnFamily (...);

Query OK

MongoDB> db.documents.insertMany([...])

{

acknowledged: true,

insertedIds: {

'0': ObjectId('...'),

'1': ObjectId('...'),

'2': ObjectId('...')

}

}

Neo4j> CREATE (p:Person {name:"Alice"})-[:LIVES_IN]->

(c:City {name:"Chennai"})

CREATE (p)-[:LIKES {rating:5}]->

(r:Restaurant {name:"Spice House"})

CREATE (r)-[:LOCATED_IN]->(c)