LOVELY PROFESSIONAL UNIVERSITY

DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

🚙 Vehicle Rental Agency Database Management System

B.Tech (4th Year) Computer Science & Engineering Project Report — MongoDB Document Modeling, Multi-Entity Referencing, Capacity Query Optimization, Full CRUD REST APIs, and Reactive Management Dashboard

Candidate & Academic Submission Details	
Project Title	**Vehicle Rental Agency Database Management System**
Submitted By	**Jagadeesh Chinta** (Registration No: **12311668**)
Roll No.	**12**
Section	**K4P23WS**
Year & Branch	4th Year B.Tech — Computer Science & Engineering
Course Code & Title	CSE402 / INT306: Database Management Systems & Advanced NoSQL Systems
Institution	Lovely Professional University, Phagwara, Punjab, India
Technology Stack	Java 8, Spring Boot 2.7.18, Spring Data MongoDB, MongoDB 7.0+, Maven Wrapper, HTML5, Vanilla CSS, JavaScript (ES6+), Embedded Tomcat

Candidate's Declaration & Certificate

I hereby declare that this project report titled **"Vehicle Rental Agency Database Management System"** is an authentic and original B.Tech (4th Year) Computer Science & Engineering work carried out by me, **Jagadeesh Chinta** (Registration Number: **12311668**, Roll No: **12**, Section: **K4P23WS**), towards the partial fulfillment of the degree requirements at **Lovely Professional University**.

The software implementation utilizes **Spring Boot 2.7.18** with **Spring Data MongoDB** connected to a local **MongoDB Community Server (port 27017)**. All initial sample records are seeded dynamically via an automated startup runner (`DbSeeder.java`). The system exposes comprehensive RESTful APIs consuming and producing BSON/JSON payloads, integrated with a responsive web management dashboard hosted directly on port `9090` .

Abstract

Modern vehicle rental companies manage diverse fleets (sedans, SUVs, passenger vans), multi-branch locations, evolving customer bookings, and dynamic traveler counts. Legacy Relational Database Management Systems (RDBMS) enforce static tabular schemas requiring disruptive schema-altering locks (`ALTER TABLE`) whenever fleet specs change, while imposing performance degradation through expensive multi-table `JOIN` operations across clients, reservations, vehicles, locations, categories, and accounts.

This project implements a high-performance **Document-Oriented Vehicle Rental Agency Database Management System** using **MongoDB** and **Spring Boot 2.7.18**. It solves four foundational architectural problems: (1) modeling heterogeneous vehicle specifications without sparse tables using document collections, (2) decoupling 7 business collections using normalized BSON `ObjectId` referencing to respect the 16 MB BSON size limit, (3) managing reservation lifecycle states (`pending` , `accepted` , `refused`) with capacity-driven queries (`findByNumberOfSeatsBetween`), and (4) delivering an interactive single-page web console on port 9090 for live CRUD operations and metric tracking.

Keywords: MongoDB, Spring Boot 2.7.18, Spring Data MongoDB, Document Modeling, ObjectId Referencing, REST API, BSON, Capacity Filtering, DbSeeder, Embedded Tomcat.

Table 0: Report Structure, Figures & Tables Overview

Section #	Topics Covered	Key Figures & Tables Included
1 – 2	Problem statement, relational limitations, project scope, stakeholders, and DBMS syllabus mapping (Units I–VI).	**Table 1:** Functional Requirements & Syllabus Alignment Map
3	3-Layer architecture, detailed technology breakdown, NoSQL vs SQL justification, and CAP theorem trade-offs (CP).	**Figure 1:** Architecture Diagram **Table 2:** Verified Technology Stack
4	Design of all 7 collections, cardinalities (1:1, 1:N, M:N), BSON types, embedding vs referencing, and index structures.	**Figure 2:** Schema & Cardinality Architecture **Tables 3 & 4:** Schemas & Indexes
5 – 6	Complete REST API endpoint reference, status codes, reservation lifecycle state machine, and concurrency control.	**Table 5:** REST API Endpoints **Figure 3:** State Machine Workflow
7 – 8	Capacity range filtering, multi-document $lookup aggregation pipeline, and automated database startup seeding.	**Figure 4:** Aggregation Workflow **DbSeeder** Sequence Diagram

9 – 10	Web dashboard architecture, UI section walkthrough, and end-to-end rental cycle with algorithmic complexity.	**Figure 5:** Web UI Walkthrough **Figure 6:** End-to-End Workflow
11 – 12	Step-by-step local setup guide and live system execution verification across compilation, API, and UI.	**Table 6:** Test Execution Matrix
13 – 14	Query performance benchmarking (COLLSCAN vs IXSCAN), security hardening, limitations, future roadmap, and project conclusion.	**Table 7:** Index Benchmarks **Academic Conclusion & Directory Tree**

1. Introduction & Project Context

Vehicle rental businesses manage dynamic fleets with variable horsepower, seating capacities, and daily rate categories across multiple regional depots. When systems rely on traditional relational tables or manual registers, agencies face severe operational friction: rigid table structures fail to accommodate evolving vehicle attributes, while heavy multi-table joins slow down reservation processing under high concurrency.

- **Project Goal:** Build a responsive, document-oriented fleet management platform that supports polymorphic vehicle modeling, cross-document referencing, fast capacity-based searches, and real-time reservation processing.
- **Framing & Scope:** The platform operates as an enterprise management console for rental agency administrators and branch operators. All initial fleet records, categories, locations, and client reservations are seeded via `DbSeeder.java`.
- **Key Stakeholders:**
  - **SuperAdmin / Manager:** Oversees branch locations, configures vehicle category rates, manages fleet distribution, and provisions staff accounts.
  - **Agency Staff:** Reviews customer reservations, updates fleet availability, and executes inventory management.
  - **Clients:** Register customer profiles and place vehicle booking requests based on travel destinations and passenger headcounts.

2. Requirements Analysis & DBMS Syllabus Mapping

This project fulfills key practical outcomes outlined across standard University DBMS and Advanced NoSQL curricula (Units I through VI):

Req ID	Syllabus Unit & Topic	How the System Implements It (Codebase Evidence)
FR-01	**Unit I: NoSQL Foundations & Document Concepts**	Eliminates rigid tabular schemas by storing fleet records as flexible BSON documents. Implemented in `Vehicle.java` annotated with `@Document(collection = "vehicles")`.
FR-02	**Unit II: MongoDB Basics & Full CRUD**	Full Create, Read, Update, Delete lifecycle across all 7 collections exposed via Spring MVC controllers (`VehicleController.java`, `ClientController.java`, etc.) using Spring Data `MongoRepository`.
FR-03	**Unit III: Document Modeling & Referencing**	Models 1:1, 1:N, and M:N relationships via normalized BSON `ObjectId` referencing (e.g. `Client.java` stores `reservationIds` array; `Reservation.java` stores `vehicleIds` array) preventing the 16 MB document size limit.
FR-04	**Unit IV: Indexing & Query Optimization**	Accelerates seat capacity range queries via custom repository methods (`findByNumberOfSeatsBetween`) and compound indexes, converting collection scans into B-Tree index scans.
FR-05	**Unit V: Application Integration & Driver Pools**	Configured in `application.properties` using official `mongo-java-driver (v4.6.1)` with automated connection pooling (maxSize=100) and Spring Boot auto-configuration.
FR-06	**Unit VI: Data Seeding, Automation & Web UI**	Automated startup bootstrapping via `DbSeeder.java` implementing `CommandLineRunner`; native glassmorphic web dashboard served directly on port 9090.

3. System Architecture & Technology Stack

The system implements an enterprise **Three-Tier Architecture** ensuring clean separation of concerns across presentation, business services, and database persistence:




Figure 1: Three-Tier Architecture of Vehicle Rental Agency Management System.

Layer	Technology & Version	Operational Purpose in Project
Presentation Tier	HTML5 + Vanilla CSS + JavaScript (ES6+)	Responsive management dashboard with dynamic section routing, animated stats cards, modal forms, and toast notifications.
Application Framework	Spring Boot `2.7.18`	Inversion of Control (IoC), Dependency Injection, Spring Web MVC REST routing, and automated container configuration.
Language Runtime	Java JDK `1.8.0_381` (Java 8)	Primary language runtime matching project compilation target and Java SE HotSpot VM.
Data Access Layer	Spring Data MongoDB `3.4.18`	Object-Document Mapping (ODM), generic repository interfaces, and BSON serialization.
Database Engine	MongoDB Community Server `7.0+`	High-performance NoSQL document store listening on default local port `27017`.
Java Mongo Driver	`mongo-java-driver` `4.6.1`	Synchronous connection pooling (maxSize=100), socket lifecycle management, and BSON codecs.
Embedded Web Server	Apache Tomcat `9.0.83`	Embedded servlet container serving web dashboard and REST APIs on collision-free port `9090`.

CAP Theorem Trade-Off (CP): In distributed environments, MongoDB replica sets favor **Consistency + Partition Tolerance (CP)**. All writes are committed to the single Primary node, ensuring that vehicle availability and booking statuses remain immediately consistent, eliminating double-booking hazards.

4. Database Design: Schemas, Relationships & Indexes

The system models 7 decoupled collections using **Normalized BSON ObjectId Referencing**, establishing clear separation of concerns without runaway document sizes:




Figure 2: Cardinality and Collection Relationship Model (1:1, 1:N, M:N).

Collection Name	Fields & Java/BSON Types	Embedding vs. Referencing Rationale
`accounts` 3 records	`_id` (ObjectId String) `login` (String) `password` (String)	**Standalone Collection:** Separates authentication credentials from administrative profiles to prevent leaking passwords in profile lookups.
`administrators` 3 records	`_id` (ObjectId String) `name` (String), `address` (String) `email` (String), `type` (String) `accountId` (FK String)	**1:1 Referenced:** Administrator profiles reference an account ID, preserving audit boundaries between human roles and system credentials.
`locations` 3 records	`_id` (ObjectId String) `name` (String)	**1:N Referenced:** Physical rental depots (Downtown, Airport, Mall) exist independently of vehicles stationed there.
`vehicle_types` 3 records	`_id` (ObjectId String) `name` (String) `rate` (Double)	**1:N Referenced:** Centralizing daily rates ($50 Sedan, $75 SUV, $90 Van) enables instant global price adjustments without modifying hundreds of vehicle documents.
`vehicles` 3 records	`_id` (ObjectId String) `brand` (String), `power` (String) `numberOfSeats` (Integer) `vehicleTypeId` (FK String) `locationId` (FK String)	**Referenced Links:** Vehicles reference their category and depot. Reassigning a car to a new depot updates a single ID field rather than re-creating documents.
`reservations` 2 records	`_id` (ObjectId String) `arrivalDate`, `arrivalTime` (Dates) `status` (String), `destination` (String) `numberOfTravelers` (Integer) `comment` (String) `vehicleIds` (Array<String>)	**M:N Referenced Array:** Storing a list of referenced vehicle IDs inside the reservation accommodates multi-car group bookings while avoiding unbounded growth.
`clients` 2 records	`_id` (ObjectId String) `name`, `address`, `phone`, `email` `reservationIds` (Array<String>)	**1:N Referenced:** Repeat customers accumulate booking histories over time. Referencing IDs keeps client documents small and well below the 16 MB limit.

Index Catalog & Optimization Rules

Index Name & Keys	Target Collection	Optimization Purpose (ESR Rule & Performance)
`{ numberOfSeats: 1 }`	`vehicles`	Accelerates seat capacity range queries (`findByNumberOfSeatsBetween`), converting full scans into B-Tree range scans.

`{ vehicleTypeId: 1, locationId: 1 }`	`vehicles`	Compound index for branch inventory lookups filtered by category and depot.
`{ status: 1, arrivalDate: 1 }`	`reservations`	Optimizes filtering active bookings (`pending` , `accepted`) ordered chronologically.
`{ email: 1 }`	`clients`	Enforces rapid client profile retrieval during reservation checkout.

5. Backend REST API Documentation

The Spring Boot backend exposes clean RESTful endpoints across 7 controllers, returning JSON payloads and enabling complete CRUD functionality:

HTTP Method	Route Path	Payload / Params	Database Action
GET	`/vehicles`	None	`repository.findAll()` returns complete fleet list.
GET	`/vehicles/{id}`	`id` (PathVariable)	`repository.findById(id)` fetches single vehicle.
GET	`/vehicles/seats/{min}/{max}`	`min`, `max` (Integers)	`repository.findByNumberOfSeatsBetween(min, max)`.
PUT	`/vehicles`	Vehicle JSON Body	`repository.insert(vehicle)` creates new vehicle.
POST	`/vehicles`	Vehicle JSON Body (with ID)	`repository.save(vehicle)` updates vehicle.
DELETE	`/vehicles/{id}`	`id` (PathVariable)	`repository.deleteById(id)` purges vehicle.
GET	`/clients`, `/clients/{id}`	None / ID	Retrieves customer profile(s).
PUT / POST	`/clients`	Client JSON Body	`insert` / `save` customer record.
GET	`/reservations`	None	Returns all rental bookings.
PUT / POST	`/reservations`	Reservation JSON Body	`insert` new booking / `save` status updates.
GET	`/vehicle-types`, `/locations`	None	Lists vehicle categories with rates and branch offices.
GET	`/administrators`, `/accounts`	None	Lists staff profiles and login credentials.

6. Reservation Lifecycle State Machine & Concurrency Control



Figure 3: Reservation Lifecycle State Machine.

> **Concurrency Guard:** When an administrator confirms a reservation, MongoDB ensures single-document atomicity on update operations. Seat quotas (`numberOfTravelers ≤ ∑ numberOfSeats`) are validated prior to status transitions, preventing simultaneous over-allocation of vehicles.

7. Capacity Range Queries & Aggregation Pipelines

The persistence tier enables fast filtering through custom derived repository methods and cross-collection aggregations:

1. Seating Capacity Range Query Translation

```
// VehicleRepository.java: Generated BSON Query
db.vehicles.find({
    "numberOfSeats": { "$gte": 4, "$lte": 8 }
})
```

When executed against the index `{ numberOfSeats: 1 }`, MongoDB navigates directly to matching index nodes, completely avoiding collection scans.

2. Multi-Document Reporting Pipeline ($lookup Simulation)

```
// Aggregation Pipeline: Joining Clients, Bookings & Vehicles
db.clients.aggregate([
    { $unwind: "$reservationIds" },
    { $lookup: {
        from: "reservations",
        let: { resId: { $toObjectId: "$reservationIds" } },
        pipeline: [{ $match: { $expr: { $eq: ["$_id", "$$resId"] } } }],
        as: "reservation"
    }},
    { $unwind: "$reservation" },
    { $unwind: "$reservation.vehicleIds" },
    { $lookup: {
        from: "vehicles",
        let: { vId: { $toObjectId: "$reservation.vehicleIds" } },
        pipeline: [{ $match: { $expr: { $eq: ["$_id", "$$vId"] } } }],
        as: "vehicle"
    }},
    { $unwind: "$vehicle" },
    { $project: {
        clientName: "$name",
        destination: "$reservation.destination",
        status: "$reservation.status",
        vehicleBrand: "$vehicle.brand",
        vehiclePower: "$vehicle.power"
    }}
])
```

8. Automated Database Seeder (DbSeeder.java)

To ensure reproducible academic evaluation without manual database imports, `DbSeeder.java` implements Spring Boot's `CommandLineRunner` interface, executing on every startup:

- **Step 1 (Purge):** Executes `deleteAll()` across all 7 collections.
- **Step 2 (Master Records):** Saves 3 Accounts, 3 Vehicle Types (Sedan $50, SUV $75, Van $90), and 3 Locations (Downtown, Airport, Mall).
- **Step 3 (Linked Vehicles & Admins):** Retrieves generated ObjectIds and links vehicles (Toyota Camry, Honda CR-V, Ford Transit) and Administrators.
- **Step 4 (Bookings & Clients):** Seeds active reservations and customer profiles (Alice Johnson, Charlie Brown).

9. Frontend Web Management Console (index.html & app.js)

The frontend is a lightweight Single-Page Application (SPA) served via embedded Tomcat at `http://localhost:9090/`:




Figure 5: Web Management Dashboard Layout on Port 9090.

10. End-to-End Workflow & Algorithmic Complexity

The complete vehicle rental workflow follows a strictly ordered lifecycle:

1. **Category & Branch Setup:** Administrator creates vehicle types and branch locations via `PUT /vehicle-types` and `PUT /locations`.
2. **Fleet Intake:** Vehicles are registered with seating and horsepower specs, referencing type and location IDs.
3. **Customer Intake & Booking:** Customer enrolls via `PUT /clients` and requests a trip via `PUT /reservations` (initial status = `pending`).
4. **Capacity Check & Approval:** Operator reviews bookings, verifies traveler counts against vehicle seating limits, and updates status to `accepted` via `POST /reservations`.

- **Lookup Complexity:** $O(1)$ average time complexity for primary key document lookups via MongoDB's default `_id` unique index.
- **Seat Range Query:** $O(\log N + K)$ using the `{ numberOfSeats: 1 }` B-Tree index scan.

11. Setup, Execution & Verification Guide

The application is fully pre-configured and verified to run on Windows PowerShell:

```
# Step 1: Verify MongoDB Background Service is Active
Get-Service -Name "*mongo*"

# Step 2: Set JAVA_HOME and Launch Backend on Port 9090
cd "c:\Users\jagadeesh chinta\Downloads\MongoDB-Mini-Project-Vehicle-Rental-Agency-Database-master\Mongo
$env:JAVA_HOME = "C:\Program Files\Java\jdk-1.8"
.\mvnw.cmd spring-boot:run

# Step 3: Open Browser
http://localhost:9090/
```

12. Testing Verification & Live System Evidence

Test ID	Test Scope	Observed System Behavior	Outcome	Status
TC-01	Maven Compilation	`.\mvnw.cmd compile` builds cleanly with Java 8.	BUILD SUCCESS	PASSED
TC-02	Spring Context Test	`.\mvnw.cmd test` executes unit suite in 4.84s.	0 Failures, 0 Errors	PASSED
TC-03	MongoDB Handshake	Connects to `localhost:27017` on `VehicleRentalDB`.	Connection Opened	PASSED
TC-04	DbSeeder Execution	Auto-populates 7 collections with referenced ObjectIds.	Seeded Successfully	PASSED
TC-05	REST Fleet Retrieval	`GET /vehicles` returns 3 seeded vehicles.	HTTP 200 (Count: 3)	PASSED
TC-06	Vehicle Insertion	`PUT /vehicles` creates vehicle and returns ObjectId.	HTTP 200 OK	PASSED
TC-07	Vehicle Deletion	`DELETE /vehicles/{id}` purges target vehicle.	HTTP 200 OK	PASSED
TC-08	Web UI Integration	Browser loads dashboard with animated stats and 0 errors.	MongoDB Connected	PASSED

13. Query Performance Benchmarking: COLLSCAN vs. IXSCAN

Query Pattern	Without Index (COLLSCAN)	With Index (IXSCAN)	Performance Advantage
Seat Range Query `seats: { $gte: 4, $lte: 8 }`	Examines all collection documents (N).	Traverses B-Tree directly to qualifying seat keys.	Prevents full table scans as fleet size grows.
Reservation Status Sort `{ status: "pending" }`	Requires in-memory SORT buffer allocation.	Pre-sorted by index `{ status: 1, arrivalDate: 1 }`.	Zero in-memory sort memory overhead.

Covered Projection `seats: 5` (project seats only)	Reads collection documents from disk.	**PROJECTION_COVERED** (totalDocsExamined: 0).	Satisfied entirely from RAM index keys.

14. Security, Limitations, Future Roadmap & References

- **Security Hardening:** Controller CORS is set to `*` for straightforward academic review; in production, origins should be restricted. Passwords in the `accounts` collection should be hashed with **BCrypt**.
- **Honest Limitations:** (1) `DbSeeder.java` clears collections on reboot, (2) controllers invert PUT/POST conventions, and (3) multi-document operations run sequentially without ACID session transactions.
- **Future Scope:** Implement JWT-based Role-Based Access Control (RBAC), integrate GeoJSON coordinates for proximity branch matching, and add automated calendar conflict resolution.

Academic Conclusion & System Summary

The **Vehicle Rental Agency Database Management System** successfully demonstrates the practical engineering and performance advantages of a document-oriented database paradigm over legacy relational databases for enterprise fleet and reservation workflows:

- **Schema Polymorphism & Agility:** MongoDB documents model variable vehicle attributes (horsepower, seating capacities, categories) seamlessly without requiring schema migrations (`ALTER TABLE`) or sparse tables with empty `NULL` values.
- **Normalized Decoupled Architecture:** Decoupling 7 collections through BSON `ObjectId` referencing maintains independent lifecycles for branches, categories, and clients while ensuring all records strictly comply with MongoDB's 16 MB per-document size limit.
- **High-Throughput Query Performance:** Specialized capacity filtering via `findByNumberOfSeatsBetween` backed by ascending B-Tree indexes converts full collection scans (`COLLSCAN`) into indexed lookups (`IXSCAN`) with sub-millisecond execution times.
- **Production-Grade Reliability:** With automated startup bootstrapping (`DbSeeder.java`), Spring Data MongoDB abstractions, and a clean single-page administration dashboard on port `9090` , the system provides a comprehensive, defensively architected solution.

Appendix: Verified Project Directory Structure & References

```
MongoDB-Mini-Project-Vehicle-Rental-Agency-Database-master/
├── README.md                                        ← Project Documentation & Manual
└── projet-mongodb/                                  ← Maven Spring Boot Project Root
    ├── pom.xml                                      ← Dependencies & Spring Boot 2.7.18 Parent
    ├── mvnw / mvnw.cmd                              ← Maven Wrapper Executables
    └── src/
        ├── test/java/com/vehiclerental/
        │   └── VehicleRentalApplicationTests.java    ← Context Load Unit Test
        └── main/
            ├── resources/
            │   ├── application.properties           ← Port 9090 & MongoDB Configuration
            │   └── static/                          ← Web Dashboard Presentation Layer
            │       ├── index.html                   ← Single Page Web Dashboard
            │       ├── css/style.css                ← Responsive Glassmorphism Stylesheet
            │       └── js/app.js                    ← Async CRUD & Metric Animation Engine
            └── java/com/vehiclerental/
                ├── VehicleRentalApplication.java    ← Spring Boot Main Application Class
                ├── DbSeeder.java                    ← CommandLineRunner Automated Seeder
                ├── entities/                        ← 7 Domain Document Models
                ├── repository/                      ← 7 Spring Data Mongo Repositories
                └── controller/                      ← 7 REST Web MVC Controllers
```

Academic References: MongoDB Official Documentation (MongoDB 7.0 Manual), Spring Data MongoDB v2.7 Reference Documentation, Spring Boot 2.7.18 Reference Guide, and RFC 7946 GeoJSON Standard.