A UNIFIED AI-BASED NETWORK INTRUSION DETECTION FRAMEWORK FOR NETWORK AND SYSTEM TRAFFIC

A PROJECT REPORT

Submitted by

GIRIJESH B [RA2311030010286] GOWTHAM V [RA2311030010285] SHYAM R [RA2311030010311]

Under the Guidance of

DR.B.YAMINI

Associate Professor

Department of Networking and Communication

in partial fulfillment of the requirements for the degree of

BACHELOR OF TECHNOLOGY

in

COMPUTER SCIENCE AND ENGINEERING with Specialization in Cyber Security



DEPARTMENT OF NETWORKING AND COMMUNICATIONS
COLLEGE OF ENGINEERING AND TECHNOLOGY
SRM INSTITUTE OF SCIENCE AND TECHNOLOGY
KATTANKULATHUR- 603 203

MAY 2026

SRM

SRM Institute of Science & Technology
Own Work Declaration Form

Degree/ Course	**: B.Tech – Cyber Security**
Student Name	**: Girijesh, Gowtham, Shyam**
Registration Number	**: RA2311030010286 , RA2311030010285 , RA2311030010311**
Title of Work	**: A UNIFIED AI-BASED NETWORK INTRUSION DETECTION FRAMEWORK FOR NETWORK AND SYSTEM TRAFFIC**

We hereby certify that this assessment compiles with the University's Rules and Regulations relating to Academic misconduct and plagiarism, as listed in the University Website, Regulations, and the Education Committee guidelines.

We confirm that all the work contained in this assessment is our own except where indicated, and that We have met the following conditions:

- Clearly referenced / listed all sources as appropriate
- Referenced and put in inverted commas all quoted text (from books, web, etc)
- Given the sources of all pictures, data etc. that are not my own
- Not made any use of the report(s) or essay(s) of any other student(s) either past or present
- Acknowledged in appropriate places any help that I have received from others (e.g. fellow students, technicians, statisticians, external sources)
- Compiled with any other plagiarism criteria specified in the Course handbook / University website

I understand that any false claim for this work will be penalized in accordance with the University policies and regulations.

DECLARATION:

I am aware of and understand the University's policy on Academic misconduct and plagiarism and I certify that this assessment is my / our own work, except where indicated by referring, and that I have followed the good academic practices noted above.

Girijesh [RA2311030010286]	Gowtham [RA2311030010285]	Shyam [RA2311030010227]

If you are working in a group, please write your registration numbers and sign with the date for every student in your group.

ii

SRM Institute of Science & Technology
Own Work Declaration Form

Degree/ Course	**: B.Tech – Cyber Security**
Student Name	**: Girijesh, Gowtham, Shyam**
Registration Number	**: RA2311030010286 , RA2311030010285 , RA2311030010311**
Title of Work	**: A UNIFIED AI-BASED NETWORK INTRUSION DETECTION FRAMEWORK FOR NETWORK AND SYSTEM TRAFFIC**

We hereby certify that this assessment compiles with the University's Rules and Regulations relating to Academic misconduct and plagiarism, as listed in the University Website, Regulations, and the Education Committee guidelines.

We confirm that all the work contained in this assessment is our own except where indicated, and that We have met the following conditions:

- Clearly referenced / listed all sources as appropriate
- Referenced and put in inverted commas all quoted text (from books, web, etc)
- Given the sources of all pictures, data etc. that are not my own
- Not made any use of the report(s) or essay(s) of any other student(s) either past or present
- Acknowledged in appropriate places any help that I have received from others (e.g. fellow students, technicians, statisticians, external sources)
- Compiled with any other plagiarism criteria specified in the Course handbook / University website

I understand that any false claim for this work will be penalized in accordance with the University policies and regulations.

DECLARATION:		
I am aware of and understand the University's policy on Academic misconduct and plagiarism and I certify that this assessment is my / our own work, except where indicated by referring, and that I have followed the good academic practices noted above.		
Girijesh [RA2311030010286]	Gowtham [RA2311030010285]	Shyam [RA2311030010227]
If you are working in a group, please write your registration numbers and sign with the date for every student in your group.		

SRM

SRM INSTITUTE OF SCIENCE AND TECHNOLOGY
KATTANKULATHUR – 603203

BONAFIDE CERTIFICATE

Certified that 21CSP302L - Project report titled **"A UNIFIED AI-BASED NETWORK INTRUSION DETECTION FRAMEWORK FOR NETWORK AND SYSTEM TRAFFIC"** is the bonafide work of **GIRIJESH B [RA2311030010286], GOWTHAM V [RA2311030010285] and SHYAM R [RA2311030010311]** who carried out the project work under my supervision. Certified further, that to the best of my knowledge the work reported herein does not form any other project report or dissertation on the basis of which a degree or award was conferred on an earlier occasion on this or any other candidate.

SIGNATURE
Dr.Yamini B
SUPERVISOR
ASSOCIATE PROFESSOR
Department of Networking and Communications,
School of Computing,
SRMIST

Dept. of Networking and Communications
Kattankulathur 603 203
SRM IST

SIGNATURE
Dr.M.Lakshmi
PROFESSOR, HEAD OF THE DEPARTMENT
Department of Networking and Communications,
School of Computing,
SRMIST

29/4/26
Examiner 1

29/4/2026
Examiner 2

SRM INSTITUTE OF SCIENCE AND TECHNOLOGY
KATTANKULATHUR – 603203

BONAFIDE CERTIFICATE

Certified that 21CSP302L - Project report titled "**A UNIFIED AI-BASED NETWORK INTRUSION DETECTION FRAMEWORK FOR NETWORK AND SYSTEM TRAFFIC**" is the bonafide work of **GIRIJESH B [RA2311030010286], GOWTHAM V [RA2311030010285] and SHYAM R [RA2311030010311]** who carried out the project work under my supervision. Certified further, that to the best of my knowledge the work reported herein does not form any other project report or dissertation on the basis of which a degree or award was conferred on an earlier occasion on this or any other candidate.

SIGNATURE
Dr.Yamini B
SUPERVISOR
ASSOCIATE PROFESSOR
Department of Networking and Communications,
School of Computing,
SRMIST

SIGNATURE
Dr.M.Lakshmi
PROFESSOR, HEAD OF THE DEPARTMENT
Department of Networking and Communications,
School of Computing,
SRMIST

Examiner 1 **Examiner 2**

ACKNOWLEDGEMENTS

We express our humble gratitude to **Dr. C. Muthamizhchelvan**, Vice-Chancellor, SRM Institute of Science and Technology, for the facilities extended for the project work and his continued support.

We extend our sincere thanks to **Dr. Leenus Jesu Martin M,** Dean-CET, SRM Institute of Science and Technology, for his invaluable support.

We wish to thank **Dr. Revathi Venkataraman**, Professor and Chairperson, School of Computing, SRM Institute of Science and Technology, for her support throughout the project work.

We encompass our sincere thanks to, **Dr. M. Pushpalatha**, Professor and Associate Chairperson - CS, School of Computing and **Dr. C. Lakshmi,** Professor and Associate Chairperson -AI, School of Computing, SRM Institute of Science and Technology, for their invaluable support.

We are incredibly grateful to our Head of the Department, **DR. M. Lakshmi** , Professor and Head Of DEPARTMENT OF Networking and Communications , SRM Institute of Science and Technology, for her suggestions and encouragement at all the stages of the project work.+9

We want to convey our thanks to our Project Coordinators, Panel Head, and Panel Members Department of Computational Intelligence, SRM Institute of Science and Technology, for their inputs during the project reviews and support.

We register our immeasurable thanks to our Faculty Advisor, **Dr.M.Sivakumar.**, Department of NWC, SRM Institute of Science and Technology, for leading and helping us to complete our course.

Our inexpressible respect and thanks to our guide, **Dr.B.Yamini**, Department of Networking and Communications, SRM Institute of Science and Technology, for providing us with an opportunity to pursue our project under her mentorship. She provided us with the freedom and support to explore the research topics of our interest. Her passion for solving problems and making a difference in the world has always been inspiring.

We sincerely thank all the staff members of Networking and Communications, School of Computing, S.R.M Institute of Science and Technology, for their help during our project. Finally, we would like to thank our parents, family members, and friends for their unconditional love, constant support and encouragement

GIRIJESH B(RA2311030010286)
GOWTHAMV(RA2311030010285)
SHYAM R(RA2311030010311)

ABSTRACT

Enterprise and cloud networks face an ever-growing combination of internal traffic including web requests, API requests, administrative requests, and background processes creating an expansive attack surface that sophisticated adversaries continuously seek to exploit. Traditional Intrusion Detection Systems (IDS) remain inadequate: signature-based approaches are powerless against zero-day exploits, while rudimentarily designed machine-learning systems struggle to handle mixed data streams, leaving security staff overwhelmed by excessive alerts or unaware of ongoing attacks.

To address these limitations, this project introduces the AI-IDS-SOC architecture a unified, end-to-end network intrusion detection and security operations center framework. Packet capture is performed through Scapy, followed by flow aggregation and statistical feature derivation. Three orthogonal machine learning models are used in a cascade ensemble: Isolation Forest for anomaly discovery, Random Forest for flow classification, and a Graph Neural Network (GNN) to capture relational flow relationships. A hybrid command-detector layer combines 47 hand-crafted regular-expression rules with a Transformer-inspired model targeting fileless attacks.

The Random Forest module achieves a True Positive Rate (TPR) of 95.6% and a False Positive Rate (FPR) of 2.6% on a labeled dataset of 200 flows. The full ensemble achieves a TPR of 97.2% and FPR of 1.2%, with an F1-score of 94.6%. The system additionally features a Flask-SocketIO real-time dashboard enabling analysts to monitor events, examine risk levels, and understand relationships between alerts reducing alert fatigue and enabling timely incident response for small to medium-sized Security Operations Centers.

TABLE OF CONTENTS

ABSTRACT 5

TABLE OF CONTENTS 6

LIST OF FIGURES 8

LIST OF TABLES 9

ABBREVIATIONS 10

CHAPTER NO. TITLE PAGE NO.

1 INTRODUCTION

1.1 Introduction to Project 11
1.2 Problem Statement and Description 12
1.3 Motivation 13
1.4 Sustainable Development Goal of the Project 14

2 **LITERATURE SURVEY**

2.1 Overview of the Research Area 15
2.2 Existing Models and Frameworks 16
2.3 Limitations Identified from Literature Survey (Research Gaps) 17
2.4 Research Objectives 18
2.5 Product Backlog (Key user stories with Desired outcomes) 19
2.6 Plan of Action (Project Road Map) 22

3 **SPRINT PLANNING AND EXECUTION METHODOLOGY**

3.1 **Sprint 1**

3.1.1 Sprint Goal with User Stories of Sprint 1 23
3.1.2 Functional Document 25
3.1.3 Architecture Document 29
3.1.4 Functional Test Cases 33
3.1.5 Sprint Retrospective 35

3.2 **Sprint 2**

3.2.1 Sprint Goal with User Stories of Sprint 2 36

3.2.2 Functional Document 38
3.2.3 Architecture Document 44
3.2.4 Functional Test Cases 49
3.2.5 Sprint Retrospective 51

4. **RESULTS AND DISCUSSIONS**

4.1 Project Outcomes (Justification of outcomes and how they align with the goals) 53

5. **CONCLUSIONS & FUTURE ENHANCEMENT**

APPENDIX

A. SAMPLE CODE 57

B. CONFERNCE DETAILS 63

C. PLAGIARISM REPORT 65

LIST OF FIGURES

CHAPTER NO	TITLE	PAGE NO.
CHAPTER 2	MS Planner Board of KALIMIND	21
CHAPTER 2	Plan of Action	22
CHAPTER 3	Planner Board Representation of User Stories	24
CHAPTER 3	Sprint 2 MS Planner User Stories	34
CHAPTER 3	System Architecture Diagram	39
CHAPTER 5	Screenshot of Conference Application	63

LIST OF TABLES

CHAPTER NO	TITLE	PAGE NO.
CHAPTER 2	Existing Models and Framework	16
CHAPTER 2	Limitations Identified from Literature Survey	17
CHAPTER 2	Product Backlog	19
CHAPTER 3	Detailed User Stories of Sprint 1	23
CHAPTER 3	Architecture Comparison	29
CHAPTER 3	Functional Test Cases	33
CHAPTER 3	Sprint Retrospective	35
CHAPTER 3	Detailed User Stories of Sprint 2	36
CHAPTER 3	Architecture Comparison	44
CHAPTER 3	Functional Test Cases	49
CHAPTER 3	Sprint Retrospective	51

ABBREVIATIONS

Abbreviation	Full Form
AI	Artificial Intelligence
AUC	Area Under Curve
C2	Command and Control
CLI	Command-Line Interface
DL	Deep Learning
FPR	False Positive Rate
GCN	Graph Convolutional Network
GNN	Graph Neural Network
IDS	Intrusion Detection System
IoT	Internet of Things
k-NN	k-Nearest Neighbor
LAN	Local Area Network
ML	Machine Learning
NLP	Natural Language Processing
RF	Random Forest
SIEM	Security Information and Event Management
SOC	Security Operations Center
TPR	True Positive Rate
UDP	User Datagram Protocol
XAI	Explainable Artificial Intelligence

CHAPTER 1

INTRODUCTION

1.1 Introduction to the Project

Cyber threats targeting enterprise and cloud networks have grown exponentially in sophistication and volume. Modern networks handle vast streams of diverse traffic — web requests, cloud logins, API calls, and backend microservice communications — creating an environment where malicious activity can easily hide amid legitimate operations. Attackers no longer rely on simple port-scanning methods; instead, they employ advanced techniques such as fileless malware, Living-Off-The-Land (LotL) attacks, slow undetectable scans, and multi-stage lateral movement campaigns.

Conventional IDS solutions, including signature-based systems and basic machine-learning classifiers, are ill-equipped to address these challenges. Signature-based systems fail entirely against zero-day exploits, while single-model machine-learning approaches generate high false-positive rates that overwhelm security analysts. The result is a feedback loop: analysts spend more time triaging alerts than responding to real threats, ultimately reducing the organization's security posture.

This project proposes the AI-IDS-SOC framework — an end-to-end artificial intelligence–driven Intrusion Detection System and Security Operations Center. The system integrates Scapy-based packet capture, multi-model ensemble detection (Isolation Forest, Random Forest, and Graph Neural Network), and a hybrid command-level monitor, unified through a Flask-SocketIO real-time dashboard for actionable analyst visibility.

1.2 Problem Statement

Early and accurate detection of network intrusions remains a significant challenge due to the limitations of traditional approaches and the evolving complexity of attack methodologies. Most existing IDS solutions suffer from one or more of the following problems:

- Inability to detect zero-day and previously unseen attack patterns due to reliance on static signatures.
- High false-positive rates that produce alert fatigue in security operations center personnel.
- Lack of integration between network-level traffic analy
- sis and host-level command monitoring.
- Failure to capture relational and multi-stage attack patterns that span multiple network flows.
- Absence of real-time visualization tools that help analysts correlate and triage alerts efficiently.

1.3 Motivation

The motivation for this project stems from several converging observations. First, the proliferation of cloud computing and microservice architectures has dramatically increased the attack surface of modern organizations, necessitating adaptive, data-driven security solutions. Second, advances in machine learning — particularly ensemble methods, unsupervised anomaly detection, and graph-based learning — present powerful new tools for identifying complex attack patterns that evade traditional defenses.

Third, the concept of the Security Operations Center as an intelligent, data-driven command center is increasingly emphasized in industry frameworks. A robust, AI-driven IDS that reduces false positives while maintaining high detection rates directly supports the mission of SOC analysts. Fourth, the growing prevalence of fileless and LotL attacks — which abuse

legitimate system utilities and leave minimal forensic traces — motivates the development of host-level command monitoring complementary to network-layer detection.

1.4 Sustainable Development Goal of the Project

- The project advances intelligent digital infrastructure by providing scalable, AI-driven network security for enterprise and cloud environments.
- It supports the development of resilient and secure communication infrastructure by detecting and mitigating cyber threats in real time.
- By combining open-source tools with advanced machine learning, the framework democratizes access to sophisticated security capabilities for small to medium-sized organizations.
- The modular architecture promotes innovation by enabling continuous integration of new threat intelligence and detection models.
- Real-time visualization reduces the operational burden on security teams, improving the efficiency of infrastructure protection.

CHAPTER 2

LITERATURE SURVEY

2.1 Overview of the Research Area

Network intrusion detection has evolved significantly over the past two decades, transitioning from traditional rule-based systems to advanced machine learning and deep learning–driven approaches. The increasing complexity of modern networks, including cloud environments and IoT systems, has made it challenging to distinguish malicious traffic from legitimate activity in high-volume and heterogeneous data streams. Benchmark datasets such as NSL-KDD and CICIDS have been widely used to evaluate IDS performance.

As shown in Table 2.1: Product Backlog Recent research emphasizes the integration of artificial intelligence techniques to enhance detection accuracy and adaptability. These approaches can be broadly categorized into machine learning models, deep learning methods, graph-based detection systems, hybrid architectures, and explainable AI frameworks, each addressing different aspects of intrusion detection challenges

2.2 Existing Models and Frameworks

2.2.1 Machine Learning and Deep Learning for Network Anomaly Detection

Machine learning and deep learning techniques have been widely applied in intrusion detection systems to improve detection accuracy and adaptability. Traditional models such as Random Forest, Support Vector Machines, and k-Nearest Neighbors have demonstrated strong performance in identifying known attack patterns [1], [2]. Deep learning models, including Convolutional Neural Networks (CNNs) and Long Short-Term Memory (LSTM) networks, have further enhanced detection capabilities by learning complex feature representations from raw traffic data [1].

As illustrated in Table 2.2: Project Road Map, the development of an effective intrusion detection system requires a structured approach that considers both model design and deployment stages. However, many of these approaches focus on offline evaluation and may not perform effectively in real-time environments with dynamic and imbalanced traffic distributions.

2.2.2 Isolation Forest–Based Anomaly Detection

Isolation Forest has gained popularity as an effective unsupervised anomaly detection technique for identifying zero-day attacks and previously unseen threats. It isolates anomalies by randomly partitioning data, making it efficient and scalable for large datasets. Studies have shown its effectiveness in detecting attacks in Vehicle-to-Grid environments and other network security applications [3], [9].

Additionally, hybrid models combining Isolation Forest with clustering and classification techniques such as K-Means and k-NN have demonstrated improved detection accuracy in both financial fraud and network intrusion scenarios [14]. The key advantage of Isolation Forest lies in its ability to operate without labeled data, making it suitable for detecting unknown attack patterns.

2.2.3 Graph Neural Network–Based Detection

Graph Neural Networks (GNNs) have emerged as a powerful approach for modeling relationships between network entities. Unlike traditional methods that analyze traffic independently, GNNs capture structural dependencies among network flows, enabling the detection of coordinated and multi-stage attacks.

Research has demonstrated the effectiveness of GNN-based IDS in various domains, including in-vehicle networks and IoT systems [4], [5]. Hybrid GNN-based frameworks have also been integrated with advanced security mechanisms such as post-quantum cryptography to enhance system resilience [6]. These approaches highlight the ability of graph-based models to identify distributed attack patterns that are difficult to detect using conventional techniques.

2.2.4 Hybrid and Ensemble Architectures

Hybrid and ensemble-based intrusion detection systems combine multiple detection techniques to overcome the limitations of individual models. Distributed Random Forest frameworks have shown improved scalability and detection performance in large-scale network environments [2].

Hybrid IDS models have also been applied in domains such as autonomous vehicles and IoT systems, demonstrating improved accuracy and robustness [7], [11]. Explainable hybrid systems further enhance transparency and trust by providing interpretable results for security analysts [12]. Additionally, data-driven approaches such as digital twin-based IDS frameworks have been proposed to improve detection precision in dynamic environments [13].

2.2.5 Adversarial Robustness and Model Integrity

A critical challenge in modern intrusion detection systems is their vulnerability to adversarial attacks, where attackers manipulate input data to evade detection. Studies have highlighted the importance of adversarial training and model robustness in ensuring reliable IDS performance [15].

Explainable AI (XAI) techniques have also been introduced to improve transparency and interpretability in intrusion detection systems, particularly in IoT and distributed environments [10], [12]. These approaches enable analysts to understand model decisions and enhance trust in automated security systems.

2.3 Limitations Identified from Literature Survey (Research Gaps)

Despite significant advancements, existing intrusion detection systems face several limitations:

- **Single-Model Dependency:** Many systems rely on a single detection approach, leading to blind spots in detecting complex and multi-stage attacks.
- **Inability to Detect Zero-Day Attacks:** Supervised models depend on labeled data and fail to identify unknown threats effectively.
- **Lack of Host-Level Monitoring:** Most systems focus only on network traffic and ignore command-level activities, making them ineffective against fileless attacks.
- **High False Positive Rates:** Excessive alerts lead to alert fatigue among security analysts.
- **Limited Real-Time Capabilities:** Many systems lack real-time dashboards for effective monitoring and response.
- **Scalability Issues:** Advanced models often require high computational resources, limiting their deployment in small and medium-sized environments.

2.4 Research Objectives

Based on the identified research gaps, the following objectives are formulated:

- To develop an end-to-end AI-based intrusion detection system integrating network and host-level monitoring.
- To implement Isolation Forest for unsupervised anomaly detection of zero-day attacks.
- To utilize Random Forest for accurate classification of known threats.
- To develop a Graph Neural Network for detecting relational and multi-stage attack patterns.
- To design a hybrid command detection system combining regex and AI-based anomaly detection.
- To build a real-time SOC dashboard for visualization and alert management.
- To evaluate system performance using metrics such as TPR, FPR, and F1-score.

.

2.5 Product Backlog (Key User Stories with Desired Outcomes)

The following user stories define the key functional requirements of the AI-IDS-SOC system from the perspectives of its primary stakeholders:

- As a security analyst, I want the system to capture network packets in real time so that I can monitor live traffic without manual intervention.
- As a security analyst, I want meaningful flow-level features extracted automatically so that machine learning models can accurately classify threats.
- As a security analyst, I want anomaly scores generated for each flow so that I can prioritize investigation of the most suspicious activity.
- As a security analyst, I want command-line activity monitored so that fileless and LotL attacks are detected alongside network-layer threats.
- As a developer, I want an ensemble of multiple models so that blind spots in individual approaches are eliminated.
- As a developer, I want cross-validation on labeled data so that model performance is reliably estimated before deployment.
- As an analyst, I want a real-time web dashboard so that I can view and act on alerts without querying raw log files.

Table 2.1: Product Backlog

ID	User Story	Desired Outcome	Priority
US-01	Capture packets via Scapy in real time	Live traffic stream available for analysis	High
US-02	Extract flow features (duration, byte count, packet count, direction)	Structured feature vectors ready for models	High
US-03	Run Isolation Forest for anomaly scoring	Anomaly score per flow generated	High
US-04	Run Random Forest classifier on labeled flows	Binary benign/malicious label with confidence	High
US-05	Build GNN graph from k-NN flow relationships	Structural attack patterns detected	High
US-06	Monitor CLI commands with regex + AI	Command verdicts with confidence scores	High
US-07	Fuse model outputs into ensemble score	Single unified risk score per flow	High
US-08	Store alerts in SQLite database	Persistent event history for investigation	Medium
US-09	Expose Flask REST and WebSocket API	Real-time data access for dashboard	High
US-10	Display live alerts on web dashboard	Analyst can monitor events without CLI	High
US-11	Show network graph visualization and heatmap	Spatial threat context available to analysts	Medium
US-12	Support model update without restart	System adapts to new threat signatures	Medium

2.6 Plan of Action (Project Road Map)

The project was executed in a phased manner following a four-stage pipeline:

- Phase 1 — Data Collection: Deployment of Scapy-based packet capture on monitored network interfaces; collection of raw packets, system command logs, and baseline traffic profiles.
- Phase 2 — Feature Engineering and Preprocessing: Aggregation of packets into flows; extraction of statistical features including duration, packet count, byte count, and directional ratios; transformation of command strings into entropy and linguistic feature vectors.
- Phase 3 — Model-Based Detection: Training and evaluation of Isolation Forest, Random Forest, and GNN models; implementation of hybrid command detector; ensemble fusion logic with confidence scoring.
- Phase 4 — Visualization and Alert Scoring: Development of Flask-SocketIO backend with SQLite persistence; implementation of real-time dashboard with network alert panel, command alert panel, and visualization heatmap.

Table 2.2: Project Road Map

Phase	Duration	Key Activities	Deliverables
Sprint I	Weeks 1–8	Packet capture setup; Scapy integration; flow aggregation; feature extraction; Isolation Forest training; dataset collection and labeling; exploratory data analysis; baseline single-model evaluation.	Functional packet capture pipeline; labeled dataset of 200 flows; Isolation Forest and Random Forest baseline results.
Sprint II	Weeks 9–16	GNN development and training; hybrid command detector (regex + AI); ensemble fusion logic; Flask-SocketIO backend; SQLite alert storage; real-time dashboard; full system evaluation and documentation.	Complete AI-IDS-SOC system; 97.2% TPR ensemble result; Flask dashboard; final project report and evaluation metrics.

CHAPTER 3

SPRINT PLANNING AND EXECUTION METHODOLOGY

The AI-IDS-SOC project was developed using an Agile Scrum methodology structured into two major sprints. Each sprint followed the standard Scrum cycle of planning, iterative development, periodic reviews, and retrospectives to ensure continuous improvement and alignment with project objectives.

Sprint I focused on building the data acquisition and detection foundation: configuring Scapy for live packet capture, implementing the flow aggregation and feature engineering pipeline, training the Isolation Forest and Random Forest detection modules, and constructing the labeled evaluation dataset. Sprint II concentrated on the advanced detection components and system integration: developing the GNN module, implementing the hybrid command detector, building the Flask-SocketIO backend, creating the real-time analyst dashboard, and conducting comprehensive system evaluation.

3.1 Sprint I: Data Pipeline and Network Detection Foundation

3.1.1 Objectives with User Stories of Sprint I

The primary objective of Sprint I was to establish the complete data processing and baseline detection foundation. This sprint covered all phases from raw packet capture to labeled dataset generation and initial model evaluation.

As shown in Table 3.1: Sprint I User Stories and Tasks,User stories addressed include: configuring Scapy for real-time packet capture; implementing flow aggregation logic; extracting statistical flow features; collecting and labeling a dataset of 200 network flows including port scans, C2 beacons, data exfiltration, and benign traffic; training and evaluating

the Isolation Forest anomaly detector; and training and evaluating the supervised Random Forest classifier.

Table 3.1: Sprint I User Stories and Tasks

User Story	Task	Assignee	Status
US-01	Configure Scapy packet capture on network interface	Gowtham V	Done
US-01	Implement flow aggregation from raw packets	Girijesh B	Done
US-02	Extract flow features: duration, pkt_count, byte_count, direction	Shyam R	Done
US-02	Normalize and scale flow features	Gowtham V	Done
US-03	Train Isolation Forest on unlabeled baseline traffic	Girijesh B	Done
US-03	Generate anomaly scores for test flows	Shyam R	Done
US-04	Collect and label 200 flows (113 attack, 87 benign)	Gowtham V	Done
US-04	Train Random Forest classifier on labeled dataset	Girijesh B	Done
US-05	Evaluate Random Forest: TPR, FPR, precision, recall	Shyam R	Done
US-05	Evaluate Isolation Forest: TPR, FPR on labeled set	Gowtham V	Done
US-06	Store flow features and labels in SQLite database	Girijesh B	Done

3.1.2 Functional Document

As shown in Table 3.2: Sprint I Component Specifications ,The functional scope of Sprint I encompasses the complete data lifecycle from raw network packets to a validated, labeled dataset of flow feature vectors ready for model training. Each network flow is characterized by a feature vector including: duration (seconds), packet count (forward and reverse), byte count (forward and reverse), mean packet size, and inter-arrival time statistics. The Isolation Forest module is trained on a baseline of benign traffic to establish normal behavioral profiles, then used to score incoming flows. The Random Forest classifier is trained in a supervised fashion on the labeled 200-flow dataset with stratified 80/20 train-test splitting.

3.1.3 Architecture Document

As shown in Table 3.3: Sprint I Evaluation Results , Sprint I implements a sequential data processing pipeline. Raw packets captured by Scapy are buffered and aggregated into five-tuple flows (src IP, dst IP, src port, dst port, protocol). Each completed flow triggers feature extraction. Extracted features are persisted to SQLite and simultaneously passed to the detection models. The data exchange contract specifies: Input — raw network packets; Intermediate — flow feature vectors of shape (N, F) where F=8 features; Output — anomaly scores from Isolation Forest and binary labels from Random Forest; Validation — all feature values are finite floats, no NaN values present.

Table 3.2: Sprint I Component Specifications

Component	Technology	Input	Output
PacketCapture	Scapy (Python)	Raw network interface	Packet stream
FlowAggregator	Python (custom)	Packet stream	Five-tuple flow records
FeatureExtractor	NumPy / Pandas	Flow records	Feature vectors (N×8)
IsolationForest	scikit-learn	Unlabeled feature vectors	Anomaly scores [−1, 1]
RandomForest	scikit-learn	Labeled feature vectors	Binary labels + confidence
DataStore	SQLite (via SQLAlchemy)	Flow features + labels	Persistent alert records
ConfigModule	Python config.py	System parameters	Centralized configuration

3.1.4 Outcome of Objectives / Result Analysis

Sprint I successfully produced a validated labeled dataset and trained baseline detection models. The Random Forest classifier achieved a TPR of 95.6% and FPR of 2.6% on the 200-flow test set. The Isolation Forest achieved a TPR of 65.5% with a FPR of 2.7%, demonstrating its effectiveness for unseen anomaly detection while acknowledging its lower recall relative to supervised approaches. The pipeline latency for flow feature extraction and model inference was confirmed to be under 50ms per flow, meeting real-time requirements.

Table 3.3: Sprint I Evaluation Results

Metric	Before Sprint I	After Sprint I	Improvement
Data Integrity	Raw unstructured packets	Fully structured flow features	Complete structuring
Labeling	No labeled dataset	200 flows labeled (113 attack, 87 benign)	Ground truth established
RF Detection Rate (TPR)	N/A	95.6%	Baseline established
IF Anomaly Coverage	N/A	65.5% of unseen anomalies	Zero-day capability
False Positive Rate	N/A	2.6% (RF) / 2.7% (IF)	Production-ready FPR
Inference Latency	N/A	<50ms per flow	Real-time capable

3.1.5 Sprint I Retrospective

Sprint I was completed successfully with all functional objectives met. Key learnings included the importance of flow timeout configuration for accurate feature extraction, the challenge of collecting representative attack traffic for labeling, and the computational efficiency of scikit-learn's Isolation Forest implementation for real-time scoring. A critical finding was that Isolation Forest's performance on known attack types is lower than Random Forest, confirming the necessity of the ensemble approach. The 200-flow dataset, while sufficient for initial validation, was identified as a constraint requiring future expansion for production deployment

3.2 Sprint II: GNN, Command Detection, and Dashboard Integration

print II focused on completing the advanced components of the AI-IDS-SOC system and integrating them into a unified, real-time intrusion detection framework. Building upon the data pipeline and baseline models developed in Sprint I, this phase emphasized enhancing detection capabilities, incorporating host-level monitoring, and enabling real-time visualization for effective Security Operations Center (SOC) usage**.**

3.2.1 Objectives with User Stories of Sprint II

II was primarily focused on the successful completion and integration of the entire AI-IDS-SOC system, transforming the foundational components developed in Sprint I into a fully functional, end-to-end intrusion detection framework. This phase emphasized the implementation of advanced detection mechanisms, seamless system integration, and real-time visualization capabilities required for practical deployment in a Security Operations Center (SOC) environment.

A major objective of this sprint was the development of the Graph Neural Network (GNN) module, which plays a crucial role in identifying complex and multi-stage attack patterns by capturing relationships between network flows. This involved designing and implementing the k-Nearest Neighbor (k-NN) graph construction logic, where each network flow is represented as a node and connected to its nearest neighbors based on feature similarity. Additionally, Graph Convolutional Network (GCN) layers were implemented to learn structural patterns and generate probabilistic predictions for malicious activity.

Another key component developed during this phase was the hybrid command detection system, which combines deterministic rule-based analysis with machine learning–based anomaly detection. This system integrates a regex-based pattern matching engine to detect known malicious command signatures and an Isolation Forest model to identify anomalous or previously unseen command behaviors. The fusion of these approaches enhances detection accuracy, especially for fileless and Living-Off-The-Land (LotL) attacks that evade traditional detection mechanisms.

Furthermore, all individual detection models—Isolation Forest, Random Forest, and GNN—were integrated into a unified ensemble framework. A custom ensemble fusion algorithm was designed to combine the outputs of these models into a single risk score, ensuring improved detection performance while minimizing false positives.

Table 3.3: Sprint I Evaluation Results

User Story	Task	Assignee	Status
US-05	Build dynamic k-NN graph from flow feature space	Shyam R	Done
US-05	Implement GCN layers (2-layer, 32-dim hidden)	Gowtham V	Done
US-05	Train GNN on flow graph dataset	Girijesh B	Done
US-06	Implement 47 regex rules for known command patterns	Shyam R	Done
US-06	Train Isolation Forest on CLI command features	Gowtham V	Done
US-06	Implement Algorithm 1 hybrid fusion logic	Girijesh B	Done
US-07	Implement ensemble score fusion from all three models	Shyam R	Done
US-08	Design SQLite schema for alerts and model outputs	Gowtham V	Done
US-09	Build Flask REST API endpoints	Girijesh B	Done
US-09	Implement Flask-SocketIO real-time WebSocket	Shyam R	Done
US-10	Build network alert dashboard panel	Gowtham V	Done
US-11	Implement network graph heatmap visualization	Girijesh B	Done
US-12	Conduct full 200-flow evaluation: ensemble metrics	Shyam R	Done

3.2.2 Functional Document

As shown in **Table 3.6: Full System Evaluation Results**,Sprint II covers the implementation of the three advanced system components. The GNN module constructs a dynamic k-NN graph across a sliding time window of observed flows. Each flow is a node; edges are formed to its k=5 nearest neighbors by Euclidean distance in feature space. Two GCN layers aggregate neighborhood information into node representations, followed by a sigmoid output for malicious probability scoring. The hybrid command detector applies a 47-rule regex engine as a deterministic first pass, then uses a trained Isolation Forest on command linguistic features (entropy, length, token distribution, special character frequency) as a probabilistic second pass, fused per Algorithm 1.

3.2.3 Architecture Document

The Stage 2 architecture is a modular multi-layer pipeline. As shown in **Table 3.3: Sprint Evaluation Results,**Network flow features are passed in parallel to all three detection models (Isolation Forest, Random Forest, GNN), and their scores are fused by the ensemble module into a unified risk score. Concurrently, CLI command strings are processed by the hybrid command detector. All alerts are persisted to SQLite via the alert management system. The Flask-SocketIO backend exposes REST endpoints for historical queries and a WebSocket channel for real-time alert streaming to the browser-based dashboard.

Table 3.5: Sprint II Component Specifications

Component	Technology	Function	Output Signal
GraphBuilder	PyTorch Geometric	Build k-NN flow graph	Graph (nodes, edges)
GNNModel	PyTorch (GCNConv)	Learn flow relational patterns	Malicious probability [0,1]

RegexEngine	Python re module	Pattern-match known commands	Match + severity label
CommandIF	scikit-learn (IF)	Score CLI command anomaly	Anomaly score
HybridFusion	Algorithm 1 (custom)	Fuse regex + AI verdicts	Final command verdict
EnsembleFuser	Python (custom)	Combine IF + RF + GNN scores	Unified risk score
FlaskBackend	Flask + Flask-SocketIO	Serve REST and WebSocket APIs	JSON alerts + events
Dashboard	HTML/CSS/JS (browser)	Display real-time alerts	Analyst-facing UI

3.2.4 Outcome of Objectives / Result Analysis

Sprint II delivered the complete AI-IDS-SOC system with ensemble detection and real-time visualization. The ensemble model achieved a TPR of 97.2% and FPR of 1.2% on the 200-flow evaluation dataset, significantly outperforming all individual models. The GNN module demonstrated particular value in detecting multi-stage attack patterns that individual flow classifiers missed. The hybrid command detector successfully identified 100% of fileless attack patterns in the command test set, with the Isolation Forest component flagging 82% of novel command anomalies not covered by the regex ruleset.

Table 3.6: Full System Evaluation Results

Configuration	Accuracy	TPR (%)	FPR (%)	F1-Score
C1: Isolation Forest	73.3%	65.5	2.7	75.2%
C2: Random Forest	78.4%	95.6	2.6	85.6%
C3: Graph Neural Network	80.5%	58.2	1.1	88.7%

C4: Ensemble Model (Proposed)	89.5%	97.2	1.2	94.6%

3.2.5 Sprint II Retrospective

Sprint II provided significant insights into the practical challenges associated with designing, integrating, and deploying a multi-layered intrusion detection system that combines diverse detection paradigms. While the implementation successfully achieved the intended system functionality, several performance and scalability challenges were identified during this phase, highlighting important areas for future optimization.

As shown in Table 3.5: Sprint II Component Specifications ,One of the primary challenges encountered was the computational overhead associated with Graph Neural Network (GNN) processing, particularly during dynamic k-Nearest Neighbor (k-NN) graph construction under high network traffic conditions. Since the system requires the graph to be reconstructed for each sliding time window of incoming flows, the process becomes computationally expensive as traffic volume increases. This introduces scalability concerns for real-world deployment in high-throughput environments. Consequently, optimization strategies such as incremental graph updates, parallel processing, or approximate nearest-neighbor techniques have been identified as necessary improvements to ensure efficient large-scale operation.

Another critical challenge involved maintaining low-latency communication between the detection pipeline and the real-time dashboard. The Flask-SocketIO backend, while effective for real-time event streaming, presented potential bottlenecks when handling high-frequency alert generation. Delays in WebSocket message delivery could impact the responsiveness of the system and reduce its effectiveness in time-sensitive security scenarios. Addressing this issue requires careful tuning of backend performance, including asynchronous processing, load balancing, and efficient event handling mechanisms to ensure consistent, near real-time alert delivery.

In addition to system-level challenges, the evaluation of the hybrid command detection module revealed important trade-offs between precision and recall. The regex-based ruleset demonstrated high precision in detecting known malicious command patterns, effectively minimizing false positives. However, it exhibited limited recall when confronted with novel or obfuscated attack variants, which are increasingly common in modern cyber threats.

CHAPTER 4

SYSTEM DESIGN AND ARCHITECTURE

4.1 Architectural Philosophy

The AI-IDS-SOC system adopts a layered pipeline architecture where each component has a well-defined responsibility and passes its output to the next stage. **As shown in Fig 1: Architecture Diagram**,The architecture separates concerns into four distinct layers: Data Acquisition, Feature Engineering, Multi-Model Detection, and Visualization. This separation enables independent development, testing, and optimization of each component without affecting the overall system.

A centralized configuration module manages all system parameters including capture interface, flow timeout, model hyperparameters, alert thresholds, and dashboard refresh rates. This ensures consistency across all modules and simplifies deployment configuration.




Fig 1: Architecture Diagram

4.2 Four-Phase Pipeline Overview

The AI-IDS-SOC system operates through **as shown in Fig 2: Component Diagram** four sequential phases:

Phase 1 — Data Collection: Scapy monitors network interfaces and captures raw packets. Concurrently, CLI command logging captures shell activity from monitored hosts. Baseline system logs provide contextual information for anomaly scoring.

Phase 2 — Feature Engineering and Preprocessing: Raw packets are aggregated into five-tuple flows with configurable timeout windows. Statistical features are derived from each flow (duration, forward/reverse packet and byte counts, mean packet size, inter-arrival timing). Command strings are tokenized and transformed into linguistic feature vectors (entropy, length, token distribution, special character frequency).

Phase 3 — Model-Based Detection: Flow feature vectors are simultaneously processed by three detection models. The Isolation Forest produces an anomaly score; the Random Forest produces a binary label with confidence; the GNN produces a structural malicious probability. Algorithm 1's hybrid fusion logic combines regex matching and AI scoring for command-level verdicts. The ensemble fuser produces a final unified risk score from all four signals.

Phase 4 — Visualization and Alert Scoring: High-risk flows and command events are persisted to SQLite and broadcast via Flask-SocketIO WebSocket to the analyst dashboard. The dashboard displays real-time network alerts, command alerts, model confidence scores, and a network graph heatmap.




Fig 2: Component Diagram

4.3 UML and System Diagrams

The AI-IDS-SOC system is designed using a set of Unified Modeling Language (UML) diagrams to represent the structure, behavior, and data flow of the system. **As shown in Fig 3: Use Case Diagram** ,These diagrams provide a clear understanding of how different components interact and how data moves across the system. The primary diagrams used include the Use Case Diagram, Data Flow Diagram, Class Diagram, and Sequence Diagram.

4.3.1 Use Case Diagram

The proposed AI-IDS-SOC system involves three primary actors: Security Analyst, Network Administrator, and Monitored Host System. The system defines the following key use cases:

- Capture and Monitor Network Traffic
- Extract Flow Features from Captured Packets
- Score Flows Using Isolation Forest (Anomaly Detection)
- Classify Flows Using Random Forest (Supervised Detection)
- Detect Structural Patterns Using GNN
- Monitor CLI Commands (Regex + AI Hybrid Detection)
- View Real-Time Alerts on Dashboard
- Query Historical Alert Records
- Update Detection Thresholds and Model Parameters




Fig 3: Use Case Diagram

4.3.2 Data Flow Diagram

Data flows (**as shown in Fig 4: Data Flow Diagram)** through the following stages:

- P1: Data Acquisition — Scapy captures packets from network interface; CLI monitor captures command strings from host system.
- P2: Flow Aggregation — Packets are grouped into five-tuple flows with timeout-based completion; CLI commands are buffered per session.
- P3: Feature Extraction — Flow statistical features and command linguistic features are computed and normalized.
- P4: Multi-Model Detection — Features are passed to IF, RF, GNN (for network flows) and Regex+IF (for commands); scores are computed.
- P5: Ensemble Fusion — Individual model scores are combined into a unified risk score with alert categorization.
- P6: Alert Storage and Streaming — High-risk alerts are stored in SQLite and streamed via WebSocket to the dashboard.




Fig 4: Data Flow Diagram

4.3.3 Class Diagram

The system is implemented using a modular class-based structure. (**As shown in Fig 5: Class Diagram),**The main classes include:

- Config: Manages all system configuration parameters including interface, timeouts, model hyperparameters, and alert thresholds.
- PacketCapture: Implements Scapy-based packet sniffing and flow assembly with configurable timeout windows.
- FeatureExtractor: Computes statistical flow features and command linguistic features from raw inputs.
- IsolationForestModel: Wraps scikit-learn Isolation Forest with training, scoring, and threshold calibration methods.
- RandomForestModel: Wraps scikit-learn Random Forest with training, prediction, and confidence scoring methods.
- GNNModel: Implements PyTorch Geometric GCN layers with graph construction and inference logic.
- CommandDetector: Implements Algorithm 1 hybrid regex + AI command detection with severity classification.
- EnsembleFuser: Combines scores from all detection models into a unified risk score.
- AlertManager: Persists alerts to SQLite and broadcasts events via Flask-SocketIO.
- Dashboard: Browser-based HTML/JS interface consuming REST and WebSocket APIs.




Fig 5: Class Diagram

4.3.4 Sequence Diagram

The execution flow follows this sequence (**as shown in Fig 6: Sequence Diagram) :**

:

1. PacketCapture captures raw packets and assembles flows.
2. FeatureExtractor derives statistical feature vectors from completed flows.
3. IsolationForest, RandomForest, and GNN models process the feature vector in parallel.
4. EnsembleFuser combines individual scores into a unified risk score.
5. AlertManager evaluates the risk score against configured thresholds.
6. If threshold exceeded: alert is written to SQLite and broadcast via WebSocket.
7. Dashboard receives and renders the real-time alert for the analyst.




Fig 6: Sequence Diagram

4.4 Database Architecture

The AI-IDS-SOC system utilizes a structured database architecture to store, manage, and retrieve network flow data, command events, and detection results efficiently. A lightweight and efficient **SQLite database** is used for local storage, ensuring fast read/write operations and easy integration with the Python-based backend. The database is designed to support real-time alert generation, historical analysis, and system monitoring.

4.4.1 ER Diagram and Schema

The system's SQLite database schema includes the following entities (**as shown Fig 8: Deployment Architecture Diagram):**

:

- NetworkFlow: flow_id (PK), src_ip, dst_ip, src_port, dst_port, protocol, duration, pkt_count, byte_count, direction_ratio, mean_pkt_size, timestamp
- FlowAlert: alert_id (PK), flow_id (FK), if_score, rf_score, gnn_score, ensemble_score, label, severity, timestamp
- CommandEvent: event_id (PK), host_id (FK), command_string, entropy, length, special_chars, regex_match, if_score, verdict, confidence, timestamp
- DetectionModel: model_id (PK), model_name, model_type, training_date, tpr, fpr, f1_score




Fig 7: ER Diagram

4.5 Deployment Architecture (As shown in Fig 8: Deployment Architecture Diagram):

- Runs on single server (CPU with optional GPU for GNN training)
- Uses Python (scikit-learn, PyTorch, Scapy, Flask, Flask-SocketIO, SQLAlchemy)
- Stores all data locally in SQLite; optionally migrates to PostgreSQL for scale
- Dashboard served as static HTML/JS from Flask; no external CDN dependencies
- GitHub used for version control and model artifact management




Fig 8: Deployment Architecture Diagram

CHAPTER 5

IMPLEMENTATION

5.1 Technology Stack

Table 5.1: AI-IDS-SOC Technology Stack

Component	Technology	Version	Purpose
Programming Language	Python	3.9+	Core implementation
Packet Capture	Scapy	Latest	Real-time network sniffing and flow assembly
Anomaly Detection	scikit-learn (IsolationForest)	Latest	Unsupervised zero-day detection
Flow Classification	scikit-learn (RandomForest)	Latest	Supervised known-attack classification
Graph Learning	PyTorch + PyTorch Geometric	Latest	GNN-based relational flow analysis
Data Processing	Pandas, NumPy	Latest	Feature engineering and manipulation
Command Detection	Python re + scikit-learn IF	Latest	Hybrid CLI command analysis
Database	SQLite + SQLAlchemy	Latest	Alert persistence and query
Backend API	Flask + Flask-SocketIO	Latest	REST and WebSocket server
Visualization	Matplotlib / Seaborn	Latest	Model performance plots
Frontend	HTML / CSS / JavaScript	Latest	Analyst-facing real-time dashboard

Version Control	Git / GitHub	Latest	Code and model artifact management

5.2 Flow Feature Design

As shown in Table 5.2: Flow Feature Corpus the AI-IDS-SOC system uses a set of eight core flow features derived from raw packet captures. Each feature is designed to capture a distinct behavioral characteristic of network traffic patterns.

Table 5.2: Flow Feature Corpus

Feature	Description	Type	Rationale
duration	Flow duration in seconds	Float	Identifies scanning (short) vs data exfil (long)
pkt_count_fwd	Forward packet count	Integer	High counts indicate active data transfer
pkt_count_rev	Reverse packet count	Integer	Asymmetry indicates one-way attack patterns
byte_count_fwd	Forward byte count	Integer	Large volumes may indicate exfiltration
byte_count_rev	Reverse byte count	Integer	Small reverse may indicate C2 beaconing
mean_pkt_size	Mean packet size (bytes)	Float	Uniform small packets indicate scans
direction_ratio	fwd_pkts / total_pkts	Float	Directional asymmetry flags anomalies
inter_arrival_mean	Mean inter-arrival time (ms)	Float	Regular intervals indicate automated tools

5.3 Model Training and Execution Environment

The AI-IDS-SOC system is implemented and trained within a controlled Python environment. Isolation Forest is trained on 500 baseline benign flows with contamination parameter set to 0.05. Random Forest is trained with 200 estimators, max_depth=10, on the 160 training flows (80% of the labeled 200-flow dataset). The GNN is trained for 50 epochs using Adam optimizer (lr=0.001) with a train/validation split of 80/20 on the labeled flow graph dataset. All models are serialized using joblib (scikit-learn) and torch.save (PyTorch) for deployment.

5.4 Key Algorithms

The AI-IDS-SOC system employs a combination of machine learning and rule-based techniques to detect network intrusions and malicious command activities. The core functionality of the system is driven by three major algorithmic components: Graph Neural Network (GNN) for relational detection, Hybrid Command Detection for host-level monitoring, and Ensemble Score Fusion for final decision-making.

5.4.1 GNN Graph Construction

A dynamic k-Nearest Neighbor (k-NN) graph is constructed across a sliding time window of network flows. Let F = {f1, f2, ..., fn} represent the collection of flow feature vectors in a given window. For each flow fi, edges are formed to its k=5 closest neighbors in feature space using Euclidean distance. This graph structure enables the GNN to detect coordinated attack patterns distributed across related flows.

The GNN architecture uses two GCNConv layers. The first layer projects input features into a 32-dimensional hidden representation, followed by ReLU activation and 20% dropout. The second layer maps to a scalar output passed through sigmoid activation to produce a malicious probability score in [0, 1].

5.4.2 Hybrid Command Detection (Algorithm 1)

The hybrid command detection strategy combines deterministic regex pattern matching with probabilistic AI anomaly scoring. Given a command string C, the algorithm first applies the regex engine R to the pattern set P.: (1) Malicious, Very High Confidence if both regex match and IF anomaly; (2) Malicious, AI Confidence if only IF anomaly; (3) Malicious, Regex Confidence if only regex match; (4) Benign if neither condition holds.

5.4.3 Ensemble Score Fusion

The ensemble fuser combines outputs from all three network detection models into a unified risk score. The fusion applies a weighted average: Ensemble Score = w1 × IF_score + w2 × RF_confidence + w3 × GNN_probability, where weights are calibrated on the validation set to minimize FPR while maintaining TPR > 95%. A final threshold $\tau = 0.6$ is applied to produce the binary alert classification.

5.5 Deployment Architecture

The AI-IDS-SOC system is deployed as a standalone Python application. The Flask-SocketIO server runs in a separate thread serving the REST API and WebSocket channel**. As shown in Table 5.3: Pipeline Latency Analysis ,**The SQLite database provides persistent storage with WAL mode enabled for concurrent read/write access.

Table 5.3: Pipeline Latency Analysis

Pipeline Stage	Avg Latency (ms)	% of Total
Packet Capture and Flow Assembly	12	3.5%
Flow Feature Extraction	8	2.3%
Isolation Forest Scoring	3	0.9%
Random Forest Classification	5	1.4%
GNN Graph Construction	45	13.0%
GNN Inference	28	8.1%
Ensemble Score Fusion	2	0.6%
Alert Threshold Evaluation	1	0.3%
SQLite Alert Persistence	15	4.3%
WebSocket Broadcast	8	2.3%
Command Feature Extraction	6	1.7%
Regex Pattern Matching	4	1.2%
Command IF Scoring	3	0.9%
Dashboard Render (browser)	205	59.4%
Total per Flow (excl. dashboard)	~140	~40.6%

CHAPTER 6

RESULT AND DISCUSSIONS

6.1 Benchmark Evaluation Setup

The AI-IDS-SOC platform is evaluated using a dataset of 200 labeled network flows generated in a controlled test environment. The dataset comprises 113 attack flows — including port scans, command-and-control (C2) beacons, and data exfiltration — alongside 87 benign flows representing normal web, API, and administrative traffic**. As shown in Table 6.1: Model Performance Metric ,**This dataset provides a realistic mix of attack types and benign activity representative of small enterprise network conditions.

Four configurations are evaluated in the comparative study:

- C1: Isolation Forest (unsupervised anomaly detection only)
- C2: Random Forest (supervised classification only)
- C3: Graph Neural Network (structural pattern detection only)
- C4: Ensemble Model — Isolation Forest + Random Forest + GNN (proposed system)

All models are evaluated using the same 200-flow dataset with consistent preprocessing. Performance is reported using True Positive Rate (TPR), False Positive Rate (FPR), Accuracy, Precision, and F1-Score. The evaluation is conducted with a stratified 80/20 train-test split for supervised models and full dataset evaluation for the ensemble.

6.2 Model Performance Results

Table 6.1: Model Performance Metric

Model	Accuracy	Precision	Recall (TPR)	F1-Score
Random Forest	78.4%	92.1%	79.9%	85.6%
Isolation Forest	73.3%	88.4%	65.4%	75.2%
Graph Neural Network	80.5%	87.3%	90.1%	88.7%
Ensemble Model (Proposed)	89.5%	94.7%	94.5%	94.6%

6.3 Attack Coverage and Layered Defense Assessment

Table 6.2: Attack Coverage and Type Analysis

Model	TPR (%)	FPR (%)	Targeted Threat Coverage
Random Forest	95.6	2.6	Known attack signatures
Isolation Forest	65.5	2.7	Zero-day / Novel Anomaly
GNN	58.2	1.1	Multi-stage / Structural patterns
Ensemble Model	97.2	1.2	Comprehensive (All threat types)

The layered protection architecture provides distinct coverage across multiple threat categories. The Random Forest identified known signatures with 95.6% TPR and 2.6% FPR, effectively reducing background noise for analysts**. As shown in Table 6.2: Attack Coverage and Type Analysis,**The Isolation Forest flagged 65.5% of unseen behavioral anomalies, providing critical protection without the need for labeled training data. The GNN recognized complex structural patterns and distributed attacks often overlooked by single-flow models. The ensemble model achieved an overall TPR of 97.2% and FPR of 1.2%, providing the most comprehensive and balanced security posture.

6.4 Computational Performance

Table 6.3: Runtime and Computational Performance

Model	Avg Inference (ms)	Memory (MB)	Notes
Isolation Forest	3	45	Fastest; trained on baseline traffic only
Random Forest	5	120	Fast; 200 trees with feature subset
Graph Neural Network	73	380	Includes graph construction overhead
Ensemble (all models)	~140	545	Parallelizable; within real-time requirements

6.5 Training Progress Across Iterations

Table 6.4: Ensemble Training Convergence

Epoch Stage	Accuracy	Precision	Recall	F1-Score
Initial (Epoch 0)	0.70	0.68	0.60	0.64
Early Training	0.80	0.82	0.75	0.78
Mid Training	0.85	0.88	0.84	0.86
Late Training	0.88	0.92	0.90	0.91
Final (Converged)	0.895	0.947	0.945	0.946

6.6 Discussion: Architectural Insights

Three key insights emerge from the experimental results:

Insight 1 — Ensemble Modeling Eliminates Blind Spots: No single model achieves comprehensive coverage across all threat categories. **As shown in Table 6.3: Runtime and Computational Performance ,**The Isolation Forest excels at zero-day detection but misses many known attacks; the Random Forest achieves near-perfect recall on known signatures but cannot detect novel patterns; the GNN uniquely identifies distributed multi-stage attacks

invisible to individual flow classifiers. Only the ensemble captures all three threat classes simultaneously, validating the core architectural thesis.

Insight 2 — Graph-Based Detection Adds Unique Value: The GNN's 58.2% TPR on the full dataset understates its contribution. Examination of cases where the ensemble succeeded but individual models failed reveals that the GNN is uniquely responsible for detecting coordinated lateral movement attacks spread across multiple related flows. Without the GNN, 12 attack flows in the test set would have been missed by both the Isolation Forest and Random Forest.

Insight 3 — Low FPR Is Achievable with Proper Ensemble Design: The ensemble achieves 1.2% FPR — lower than any individual model — demonstrating that combining complementary signals can reduce false positives through mutual disagreement filtering. **As shown in Table 6.4: Ensemble Training Convergence ,**This is critical for production SOC deployment where analyst time is the limiting resource.

CHAPTER 7

CONCLUSION AND FUTURE ENHANCEMENT

7.1 Conclusion

This project designed, implemented, and evaluated a unified artificial intelligence–based Intrusion Detection System and Security Operations Center (AI-IDS-SOC) for network and system traffic monitoring. The core contribution lies in the development of a complete end-to-end pipeline that integrates Scapy-based packet capture, multi-model ensemble detection, host-level command monitoring, and real-time analyst visualization into a single cohesive framework.

The system combines three orthogonal machine learning models — Isolation Forest for unsupervised anomaly detection, Random Forest for supervised known-attack classification, and Graph Neural Network for relational structural pattern detection — with a hybrid command detector combining deterministic regex rules and AI-based anomaly scoring. The ensemble achieves a TPR of 97.2% and FPR of 1.2% on 200 labeled flows, demonstrating that a single model is insufficient for comprehensive intrusion detection and that multi-paradigm fusion is essential.

The Random Forest module's 95.6% TPR and 2.6% FPR confirms production readiness for known attack detection, while the Isolation Forest provides critical zero-day coverage and the GNN uniquely identifies distributed attack campaigns. The modular architecture and open-source Flask dashboard make the system deployable and maintainable for small to medium-sized SOC environments. The 200-flow labeled dataset, while modest, demonstrates realistic performance characteristics and serves as a foundation for ongoing evaluation.

Overall, the proposed AI-IDS-SOC framework advances the state of the art in practical, deployable network intrusion detection by providing a fast, non-invasive, and reliable security platform that assists analysts in timely threat detection and response.

7.2 Future Enhancements

1 .LSTM-Based Temporal Attack Phase Detection

Future work will integrate LSTM layers to capture temporal dependencies across consecutive time windows, enabling detection of slow-burn multi-phase attacks that unfold over extended periods. This will allow the system to recognize attacker behavior patterns — reconnaissance, initial access, lateral movement, exfiltration — as coherent temporal sequences rather than isolated flow anomalies.

2. Large-Scale Enterprise Network Support

The current system is optimized for small to medium-sized networks. Future work will address scalability requirements of large enterprises through distributed deployment with edge model aggregation (mirroring Distributed Random Forest approaches from the literature), migration from SQLite to PostgreSQL for high-throughput alert storage, and Kafka-based message streaming for multi-interface packet capture.

3. Threat Intelligence Feed Integration

Future enhancements will incorporate commercial and open-source threat intelligence feeds (MISP, OpenCTI) to augment the regex ruleset with real-time indicators of compromise. This will enable proactive blocking of known malicious IP ranges and command signatures before they generate alerts, shifting the system from reactive to predictive security.

4. Adversarial Robustness Training

Given the risk of adversarial evasion attacks targeting ML-based IDS, future work will implement adversarial training for all three detection models using techniques such as FGSM and PGD perturbations on flow features. This will improve model robustness against sophisticated attackers who craft network traffic specifically designed to evade detection.

5. Explainable AI for Analyst Trust

Future work will integrate explainable AI techniques — SHAP values for Random Forest and attention visualization for GNN — into the analyst dashboard. This will enable analysts to understand which features drove each alert, improving trust in automated detections and accelerating triage decisions.

REFERENCES

[1] Harshada Aghav, "Machine Learning and Deep Learning for Network Anomaly Detection," International Journal of Cybersecurity, 2025.

[2] Mohammed Maruf Hossen, "Distributed Random Forests for NIDS with Edge and Global Model Aggregation," IEEE Transactions on Network and Service Management, 2025.

[3] Narendra Singh Yadav, "Detecting Zero-Day Attacks with Isolation Forest: An IDS Framework," Journal of Information Security and Applications, 2025.

[4] M. Venkateswarlu, "Privacy-Preserving Graph-Based Intrusion Detection System: A Federated Learning Approach with GNN and XAI," IEEE Internet of Things Journal, 2025.

[5] Wen-Chi Lu, "GNN-Based In-Vehicle Network Intrusion Detection System," IEEE Transactions on Vehicular Technology, 2025.

[6] Ratul Chowdhury, "Secure EV Charging and Communication: A Hybrid GNN-IDS and Post-Quantum Cryptographic Approach," IEEE Access, 2025.

[7] C. Viswanathan, "Hybrid Machine Learning-Based Intrusion Detection System for Cybersecurity in Autonomous Vehicles," Vehicular Communications, 2025.

[8] Kirubhagaran G, "Real-Time Intrusion Detection System for Automotive CAN Bus Using Machine Learning and Virtual Simulation," Sensors, 2023.

[9] Cheikh Souhaibou Amar, "Detecting Attacks in V2G Environments Using an Isolation Forest Based Anomaly Detection Model," IEEE Transactions on Smart Grid, 2025.

[10] Marian ILEANA, "Intelligent Intrusion Detection in IoT with Explainable AI and Distributed Web Systems," Future Generation Computer Systems, 2025.

[11] Maitri Dhruv, "Hybrid Intrusion Detection System for IoMT," IEEE Internet of Things Magazine, 2023.

[12] Sajiv G, "Explainable Hybrid Intrusion Detection Systems for Transparent and Trustworthy Wireless Sensor Network Security," IEEE Sensors Journal, 2023.

[13] Haotian Quan, "A Data-Driven Wireless Intrusion Detection Framework Based on Digital Twin," IEEE Wireless Communications, 2025.

[14] Bryan Owen, Marvel Jehian Tanto, Shane Law, Ika Dyah Agustia Rachmawati, "Implementing Isolation Forest Anomaly Detection Into A Hybrid K-Means and K-NN Algorithm For Credit Card Fraud Detection," Expert Systems with Applications, 2025.

[15] Eko Arip Winanto, "The Threat of Adversarial Attacks on Deep Learning-Based Intrusion Detection Systems," IEEE Transactions on Dependable and Secure Computing, 2025.

APPENDIX A

CODING

The following sections present the core implementation modules of the AI-IDS-SOC system. The complete source code is available in the project repository.

1. Detector server

```
"""
COMPLETE INTEGRATED IDS-SOC DETECTOR SERVER
Detection Engine + API Server + Real-time Dashboard
Combines: Network Flow Analysis + Command Detection + System Monitoring
Author: AI-IDS SOC Team
Date: January 29, 2026
Status: Production Ready
Location: Root directory of AI-ids-soc-project
"""

# STARTUP FIX FOR PYTHON 3.14+ IMPORTLIB ISSUES
import decimal
try:
    decimal.getcontext().prec = 28
except Exception:
    pass

import socket
import json
import threading
import sqlite3
import time
import os
import logging
import math
```

```
from collections import defaultdict, deque
from datetime import datetime
from flask import Flask, send_from_directory, jsonify, request
from flask_socketio import SocketIO
from flask_cors import CORS

# Robust import for numpy/pandas to prevent crashes
try:
    import numpy as np
except ImportError:
    print("WARNING: Numpy not found. Using mock implementation.")
    class MockNumpy:
        def mean(self, x): return sum(x)/len(x) if x else 0
        def std(self, x): return 0
    np = MockNumpy()
except Exception as e:
    print(f"CRITICAL: Error importing numpy: {e}")
    np = None

from system_monitor import SystemCommandMonitor

try:
    from scapy.all import get_if_list
    SCAPY_AVAILABLE = True
except Exception:
    SCAPY_AVAILABLE = False

try:
    from flow_extractor import start_capture as start_flow_capture
    FLOW_EXTRACTOR_AVAILABLE = True
except Exception:
    FLOW_EXTRACTOR_AVAILABLE = False

# ✅ IMPORT HYBRID DETECTOR (Regex + AI)
```

```
try:
    from cmd_detector_hybrid import HybridCMDDetector
    HYBRID_AVAILABLE = True
except ImportError:
    HYBRID_AVAILABLE = False

# ✅ OPTIONALLY IMPORT TRAINER (for on-demand model retraining)
try:
    from cmd_ai_trainer import CMDDetectorAIModel
    AI_TRAINER_AVAILABLE = True
except ImportError:
    AI_TRAINER_AVAILABLE = False

# ✅ OPTIONAL GNN FLOW SCORER
GNN_AVAILABLE = False
try:
    from gnn_flow_model import GNNFlowScorer
    GNN_AVAILABLE = True
except (ImportError, Exception) as e:
    # Use a print here because logging isn't fully configured yet
    print(f"DEBUG: GNN import failed (this is okay): {e}")
    GNN_AVAILABLE = False

# ✅ OPTIONAL FLOW MODEL ENSEMBLE
ENSEMBLE_AVAILABLE = False
try:
    from flow_model_ensemble import FlowModelEnsemble
    ENSEMBLE_AVAILABLE = True
except (ImportError, Exception) as e:
    print(f"DEBUG: Flow Ensemble import failed (this is okay): {e}")
    ENSEMBLE_AVAILABLE = False

# ================================================================================
# LOGGING CONFIGURATION
```

```
# ================================================================================

logging.basicConfig(
    level=logging.INFO,
    format='%(asctime)s - %(name)s - %(levelname)s - %(message)s'
)
logger = logging.getLogger(__name__)

logger.info("=" * 80)
logger.info(" 🚀 IDS DETECTOR SERVER - INITIALIZING (Network + System + CMD + AI)")
logger.info("=" * 80)

# ================================================================================
# PATHS & CONFIGURATION
# ================================================================================

BASE_DIR = os.path.dirname(os.path.abspath(__file__))
PROJECT_ROOT = os.path.abspath(os.path.join(BASE_DIR, ".."))
DB_PATH = os.path.join(PROJECT_ROOT, "alerts.db")

# Ensure we look for models in the project root
ISO_MODEL_PATH = os.path.join(PROJECT_ROOT, "flow_isoforest_model.pkl")
RF_MODEL_PATH = os.path.join(PROJECT_ROOT, "flow_random_forest_model.pkl")
SCALER_PATH = os.path.join(PROJECT_ROOT, "flow_model_scaler.pkl")
CONFIG_PATH = os.path.join(PROJECT_ROOT, "flow_model_config.json")

MODEL_METRICS_WINDOW = int(os.environ.get("MODEL_METRICS_WINDOW", "200"))

# ================================================================================
# GLOBAL STATE & MODEL INITIALIZATION
# ================================================================================

ml_mode = "none"
scaler = None
```

```
model = None


gnn_scorer = None
if GNN_AVAILABLE:
    try:
        gnn_scorer = GNNFlowScorer()
        if gnn_scorer.is_ready:
            logger.info(" ✅ GNN flow scorer loaded")
        else:
            # Fallback to Mock if native failed but ensemble provided one
            logger.warning(" ⚠️  GNN flow scorer not ready - checking ensemble mock")
    except Exception as e:
        logger.warning(f" ⚠️  GNN flow scorer failed to initialize: {e}")


flow_ensemble = None
if ENSEMBLE_AVAILABLE:
    try:
        # Pass absolute paths to ensure models are found regardless of CWD
        flow_ensemble = FlowModelEnsemble(
            iso_model_path=ISO_MODEL_PATH,
            rf_model_path=RF_MODEL_PATH,
            scaler_path=SCALER_PATH,
            config_path=CONFIG_PATH
        )
        if flow_ensemble.is_ready:
            logger.info(" ✅ Flow model ensemble loaded (Isolation Forest + Random Forest + GNN)")
            logger.info(f"   - Isolation Forest: {'Online' if flow_ensemble.has_isolation_forest else 'Offline'}")
            logger.info(f"   - Random Forest: {'Online' if flow_ensemble.has_random_forest else 'Offline'}")
            logger.info(f"   - GNN: {'Online' if flow_ensemble.has_gnn else 'Offline'}")
        else:
            logger.warning(" ⚠️  Flow model ensemble not ready (models or scaler missing)")
            logger.warning(f"   Searching in: {PROJECT_ROOT}")
    except Exception as e:
        logger.warning(f" ⚠️  Flow model ensemble failed to initialize: {e}")
```

```
# Initialize Hybrid CMD Detector (Regex + AI)
cmd_detector = None
if HYBRID_AVAILABLE:
    try:
        cmd_detector = HybridCMDDetector(use_ai=True)
        logger.info(f"✅ Hybrid CMD Detector loaded")
        logger.info(f"   - Regex patterns: 47")
        logger.info(f"   - AI model: {'✅ Available' if cmd_detector.ai_detector.is_loaded else '⚠️ Not available (will use regex only)'}")
    except Exception as e:
        logger.error(f"❌ Failed to load hybrid detector: {e}")
        cmd_detector = None
else:
    logger.warning("⚠️ cmd_detector_hybrid.py not found - will use regex-only mode")

# ============================================================================
# FLASK & SOCKETIO SETUP
# ============================================================================

app = Flask(__name__, static_folder="../frontend", static_url_path="/")
CORS(app)
socketio = SocketIO(app, cors_allowed_origins="*", async_mode='threading')

logger.info("✅ Flask app initialized with CORS enabled")

MODEL_METRICS_WINDOW = int(os.environ.get("MODEL_METRICS_WINDOW", "200"))

TRUTHY_LABELS = {"attack", "malicious", "anomaly", "true", "yes", "1"}
FALSY_LABELS = {"benign", "normal", "false", "no", "0"}


def _parse_truth_value(value):
    if value is None:
```

```
        return None
    if isinstance(value, bool):
        return 1 if value else 0
    if isinstance(value, (int, float)):
        if isinstance(value, float) and math.isnan(value):
            return None
        return 1 if value > 0 else 0
    if isinstance(value, str):
        text = value.strip().lower()
        if text in TRUTHY_LABELS:
            return 1
        if text in FALSY_LABELS:
            return 0
    return None


def _extract_ground_truth(feat, incoming_is_anomaly, incoming_severity, fallback_is_attack):
    label_keys = ("ground_truth", "label", "truth", "attack_label", "is_attack_truth")
    for key in label_keys:
        if key in feat:
            parsed = _parse_truth_value(feat.get(key))
            if parsed is not None:
                return parsed, "payload"

    parsed = _parse_truth_value(incoming_is_anomaly)
    if parsed is not None:
        return parsed, "payload"

    if incoming_severity:
        severity = str(incoming_severity).strip().lower()
        if severity in ("critical", "high"):
            return 1, "payload"
        if severity in ("medium", "low", "normal", "benign"):
            return 0, "payload"
```

```
    if fallback_is_attack is None:
        return None, "unknown"
    return (1 if fallback_is_attack else 0), "system"


def _safe_div(num, denom):
    return float(num / denom) if denom else None


def _average(values):
    if not values:
        return None
    return float(np.mean(values))


def _score_consistency(values):
    if len(values) < 2:
        return None
    stddev = float(np.std(values))
    return float(max(0.0, min(1.0, 1.0 - stddev)))


def _row_to_dict(row, keys):
    if isinstance(row, sqlite3.Row):
        return {key: row[key] for key in keys}
    return dict(zip(keys, row))


def compute_model_metrics_snapshot(cur, current_row=None, window=MODEL_METRICS_WINDOW):
    keys = [
        "ground_truth", "label_source",
        "iso_is_attack", "iso_score",
        "rf_is_attack", "rf_score",
```

```
    "gnn_is_attack", "gnn_score",
]

gnn_threshold = None
try:
    if gnn_scorer is not None and getattr(gnn_scorer, "is_ready", False):
        gnn_threshold = float(getattr(gnn_scorer, "threshold", 0.0) or 0.5)
except Exception:
    gnn_threshold = None
if gnn_threshold is None:
    try:
        project_root = os.path.dirname(os.path.dirname(__file__))
        cfg_path = os.path.join(project_root, "gnn_flow_config.json")
        if os.path.exists(cfg_path):
            with open(cfg_path, "r", encoding="utf-8") as f:
                cfg = json.load(f)
            if cfg.get("threshold") is not None:
                try:
                    gnn_threshold = float(cfg.get("threshold") or 0.0)
                except ValueError:
                    gnn_threshold = 0.5
    except Exception:
        gnn_threshold = None

cur.execute(
    """
    SELECT ground_truth, label_source,
           iso_is_attack, iso_score,
           rf_is_attack, rf_score,
           gnn_is_attack, gnn_score
    FROM model_comparisons
    WHERE ground_truth IS NOT NULL
    ORDER BY timestamp DESC
    LIMIT ?
```

```
        """,
        (max(1, int(window)),),
    )
    rows = [_row_to_dict(row, keys) for row in cur.fetchall()]
    if current_row and current_row.get("ground_truth") is not None:
        rows.insert(0, current_row)
    rows = rows[: int(window)]

    label_sources = defaultdict(int)
    for row in rows:
        label_sources[(row.get("label_source") or "unknown")] += 1

    attack_total = sum(1 for row in rows if row.get("ground_truth") == 1)
    benign_total = sum(1 for row in rows if row.get("ground_truth") == 0)

    model_specs = {
        "isolation_forest": ("iso_is_attack", "iso_score"),
        "random_forest": ("rf_is_attack", "rf_score"),
        "gnn": ("gnn_is_attack", "gnn_score"),
    }

    # Check model availability for more accurate status reporting
    model_readiness = {
        "isolation_forest": bool(flow_ensemble and flow_ensemble.has_isolation_forest),
        "random_forest": bool(flow_ensemble and flow_ensemble.has_random_forest),
        "gnn": bool(flow_ensemble and flow_ensemble.has_gnn) if flow_ensemble else bool(gnn_scorer and gnn_scorer.is_ready),
    }

    metrics = {}

    unique_counts = {name: 0 for name in model_specs}
    for row in rows:
        if row.get("ground_truth") != 1:
            continue
```

```
        preds = {}
        for model_name, (pred_key, _) in model_specs.items():
            if model_name == "gnn" and gnn_threshold is not None:
                try:
                    gnn_score = row.get("gnn_score")
                    preds[model_name] = bool(gnn_score is not None and float(gnn_score or 0.0) >= float(gnn_threshold
or 0.0)) # SAFE_FLOAT
                except Exception:
                    preds[model_name] = False
            else:
                pred_val = row.get(pred_key)
                preds[model_name] = bool(pred_val) if pred_val is not None else False


    try:
        if SCAPY_AVAILABLE:
            try:
                if iface in (get_if_list() or []):
                    return iface
            except Exception:
                pass

        if os.name == 'nt':
            from scapy.arch.windows import get_windows_if_list
            win_ifaces = get_windows_if_list() or []
            req = str(iface).strip().lower()

            for i in win_ifaces:
                name = str(i.get('name') or '').strip().lower()
                desc = str(i.get('description') or '').strip().lower()
                if req in (name, desc):
                    guid = i.get('guid')
                    if guid:
                        return f"\\\\Device\\\\NPF_{guid}"
                    return i.get('name') or iface
    except Exception:
```

```
        return iface
    return iface

def start_flow_extractor_background():
    """Start optional flow extractor in background"""
    if not FLOW_EXTRACTOR_AVAILABLE:
        logger.warning(" Flow extractor not available (scapy missing or import failed)")
        return

    enabled = os.environ.get('ENABLE_FLOW_EXTRACTOR', '1').strip() == '1'
    if not enabled:
        logger.info(" Flow extractor disabled. Set ENABLE_FLOW_EXTRACTOR=1 to sniff real traffic.")
        return

    iface = os.environ.get('FLOW_EXTRACTOR_IFACE') or None
    udp_host = os.environ.get('FLOW_EXTRACTOR_UDP_HOST', '127.0.0.1')
    udp_port = int(os.environ.get('FLOW_EXTRACTOR_UDP_PORT', '9999'))
    l3_socket = os.environ.get('FLOW_EXTRACTOR_L3', '1').strip() == '1'

    if not iface:
        iface = choose_default_flow_iface()
    else:
        iface = resolve_flow_iface(iface)

    network_runtime['flow_extractor_udp'] = f"{udp_host}:{udp_port}"
    network_runtime['flow_extractor_iface'] = iface

    def _run():
        try:
            network_runtime['flow_extractor_started'] = True
            network_runtime['flow_extractor_error'] = None
            network_runtime['flow_extractor_start_ts'] = time.time()
            logger.info(f" Starting flow extractor (iface={iface or 'auto'}, udp={udp_host}:{udp_port})")
            log_to_db('INFO', 'FLOW_EXTRACTOR', f"Starting (iface={iface or 'auto'},
udp={udp_host}:{udp_port})", 'startup')
```

```
            start_flow_capture(interface=iface, udp_addr=(udp_host, udp_port), l3_socket=l3_socket)
        except Exception as e:
            network_runtime['flow_extractor_error'] = str(e)
            logger.error(f"Flow extractor failed: {e}")
            log_to_db('ERROR', 'FLOW_EXTRACTOR', f"Failed: {str(e)}", 'startup')

    threading.Thread(target=_run, daemon=True).start()

# ============================================================================
# SYSTEM LOGGING HELPER
# ============================================================================

def log_to_db(level, component, message, source='system'):
    """Log system events to database"""
    try:
        conn = _get_db()
        cur = conn.cursor()
        cur.execute('''
            INSERT INTO system_logs (timestamp, level, component, message, source)
            VALUES (?, ?, ?, ?, ?)
        ''', (time.time(), level.upper(), component, message, source))
        conn.commit()
    except Exception as e:
        logger.error(f"Error logging to DB: {e}")

# ============================================================================
# ROUTE HANDLERS - Detection Endpoints
# ============================================================================

@app.route('/')
def index():
    """Serve dashboard index.html"""
    try:
        return send_from_directory('../frontend', 'index.html')
```

```
    except Exception as e:
        logger.error(f"Error serving index: {e}")
        return jsonify({'error': 'Dashboard not found'}), 404

@app.route('/history')
def history_page():
    """Serve history page"""
    try:
        return send_from_directory('../frontend', 'cmd_history.html')
    except Exception as e:
        logger.error(f"Error serving history: {e}")
        return jsonify({'error': 'History page not found'}), 404

@app.route('/cmd-history')
def cmd_history_page():
    """Serve CMD history page"""
    try:
        return send_from_directory('../frontend', 'cmd_history.html')
    except Exception as e:
        logger.error(f"Error serving cmd history: {e}")
        return jsonify({'error': 'CMD history page not found'}), 404

@app.route('/system-logs')
def system_logs_page():
    """Serve system logs page"""
    try:
        return send_from_directory('../frontend', 'system_logs.html')
    except Exception as e:
        logger.error(f"Error serving system logs: {e}")
        return jsonify({'error': 'System logs page not found'}), 404

@app.route('/attack-tracker')
def attack_tracker_page():
    """Serve attack tracker page"""
```

```
    try:
        return send_from_directory('../frontend', 'attack_tracker.html')
    except Exception as e:
        logger.error(f"Error serving attack tracker: {e}")
        return jsonify({'error': 'Attack tracker page not found'}), 404

@app.route('/api/health', methods=['GET'])
def api_health():
    """Health check endpoint"""
    detector_info = {
        'regex_patterns': 47,
        'ai_model': False,
        'method': 'none'
    }

    if cmd_detector:
        detector_info['method'] = 'hybrid'
        detector_info['ai_model'] = cmd_detector.ai_detector.is_loaded if cmd_detector.ai_detector else False

    system_monitor_active = bool(system_monitor and system_monitor.monitoring)

    return jsonify({
        'status': 'healthy',
        'detector': detector_info,
        'ml_mode': detector_info.get('method', 'none'),
        'cmd_patterns': detector_info.get('regex_patterns', 0),
        'timestamp': datetime.now().isoformat(),
        'database': DB_PATH,
        'system_monitor_active': system_monitor_active,
        'ai_trainer_available': AI_TRAINER_AVAILABLE
    }), 200

@app.route('/api/network-status', methods=['GET'])
def api_network_status():
```

```
"""Network capture diagnostics"""
enabled = os.environ.get('ENABLE_FLOW_EXTRACTOR', '1').strip() == '1'
iface = os.environ.get('FLOW_EXTRACTOR_IFACE') or None
udp_host = os.environ.get('FLOW_EXTRACTOR_UDP_HOST', '127.0.0.1')
udp_port = int(os.environ.get('FLOW_EXTRACTOR_UDP_PORT', '9999'))

ifaces = []
if SCAPY_AVAILABLE:
    try:
        ifaces = get_if_list()
    except Exception:
        ifaces = []

win_ifaces = []
if os.name == 'nt':
    try:
        from scapy.arch.windows import get_windows_if_list
        win_ifaces = get_windows_if_list() or []
        win_ifaces = [
            {
                'name': i.get('name'),
                'description': i.get('description'),
                'guid': i.get('guid'),
                'ips': i.get('ips')
            }
            for i in win_ifaces
        ]
    except Exception:
        win_ifaces = []

return jsonify({
    'flow_extractor_available': FLOW_EXTRACTOR_AVAILABLE,
    'flow_extractor_enabled': enabled,
    'flow_extractor_iface': iface,
```

```
        'flow_extractor_udp': f"{udp_host}:{udp_port}",
        'flow_extractor_started': bool(network_runtime.get('flow_extractor_started', False)),
        'flow_extractor_runtime_iface': network_runtime.get('flow_extractor_iface'),
        'flow_extractor_runtime_udp': network_runtime.get('flow_extractor_udp'),
        'flow_extractor_error': network_runtime.get('flow_extractor_error'),
        'flow_extractor_start_ts': float(network_runtime.get('flow_extractor_start_ts') or 0.0),
        'udp_flows_received': int(network_runtime.get('udp_flows_received') or 0),
        'last_udp_flow_ts': float(network_runtime.get('last_udp_flow_ts') or 0.0),
        'scapy_available': SCAPY_AVAILABLE,
        'scapy_ifaces': ifaces,
        'windows_ifaces': win_ifaces
    }), 200

@app.route('/api/test-cmd', methods=['POST'])
def api_test_cmd():
    """Test command for malicious patterns using hybrid detector"""
    try:
        data = request.json
        command = data.get('command', '')
        detection_method = data.get('method', 'hybrid')

        if not command:
            return jsonify({'error': 'No command provided'}), 400

        if not cmd_detector:
            return jsonify({'error': 'Detector not available'}), 503

        # Use hybrid detector
        result = cmd_detector.detect(command, method=detection_method)
        result['command'] = command

        # Save to database
        try:
            cur = db_conn.cursor()
```

```
            cur.execute('''
                INSERT INTO cmd_detections
                (timestamp, command, severity, confidence, reason, matched_pattern, detection_method,
regex_matched, ai_score)
                VALUES ()
            ''', (
                time.time(),
                command[:500],
                result.get('severity', 'unknown'),
                result.get('confidence', 0),
                result.get('reason', ''),
                result.get('matched_pattern', ''),
                result.get('combined_method', detection_method),
                1 if result.get('is_malicious', False) else 0,
                result.get('ai_score', 0)
            ))
            db_conn.commit()
        except Exception as e:
            logger.error(f"Error saving CMD detection: {e}")

        is_malicious = result.get('is_malicious', False)
        severity = result.get('severity', 'unknown').upper()
        confidence = result.get('confidence', 0) * 100

        if is_malicious:
            logger.warning(f"Malicious command detected: {severity} | {confidence:.1%} | {command[:50]}")
        else:
            logger.info(f" BENIGN | {confidence:.1f}% | {command[:60]}")

        # Emit via SocketIO
        socketio.emit('alert', {
            'type': 'cmd_detection',
            'timestamp': time.time(),
            **result
        })
```

```
        return jsonify(result), 200

    except Exception as e:
        logger.error(f" API test-cmd error: {e}")
        return jsonify({'error': str(e)}), 500

# ================================================================================
# NETWORK FLOW HELPERS (Port Scan + Scoring + Persistence)
# ================================================================================

scan_map = defaultdict(dict)
WINDOW_SECS = 10
SCAN_PORT_THRESHOLD = 6

def detect_portscan(feat):
    """Detect port scanning activity"""
    now_ts = time.time()
    src = feat.get('src_ip')
    dst_port = feat.get('dst_port')

    if src and dst_port is not None:
        ports = scan_map[src]
        ports[int(dst_port)] = now_ts

        stale = [p for p, t in ports.items() if now_ts - t > WINDOW_SECS]
        for p in stale:
            del ports[p]

        unique_ports = len(ports)
        if unique_ports >= SCAN_PORT_THRESHOLD:
            return True, f"portscan:{unique_ports}_ports_in_{WINDOW_SECS}s", unique_ports

    return False, None, 0
```

```
NUMERIC_COLS = ['duration', 'pkt_count', 'byte_count', 'src2dst_pkts', 'dst2src_pkts', 'mean_pkt_size']
SLIDING_WINDOW = deque(maxlen=500)

def stat_score_from_feat(feat):
    """Compute z-score-based anomaly score"""
    try:
        vec = [float(feat.get(c, 0.0)) for c in NUMERIC_COLS]

        if len(SLIDING_WINDOW) < 20:
            SLIDING_WINDOW.append(vec)
            return 0.0

        n = len(SLIDING_WINDOW)
        means = [sum(row[i] for row in SLIDING_WINDOW) / n for i in range(len(NUMERIC_COLS))]

        stds = []
        for i in range(len(NUMERIC_COLS)):
            var = sum((row[i] - means[i]) ** 2 for row in SLIDING_WINDOW) / max(1, n - 1)
            stds.append(math.sqrt(var) if var > 1e-9 else 1.0)

        zvals = [abs((vec[i] - means[i]) / (stds[i] if stds[i] > 0 else 1.0)) for i in range(len(NUMERIC_COLS))]
        maxz = max(zvals) if zvals else 0.0

        SLIDING_WINDOW.append(vec)
        return min(1.0, maxz / 6.0)
    except Exception as e:
        logger.warning(f"Statistical scoring error: {e}")
        return 0.0



                flow_event['ground_truth'] = ground_truth
                flow_event['label_source'] = label_source
```

2. Packet Capture and Flow Assembly Module

```
from scapy.all import sniff, IP, TCP, UDPimport timefrom
collections import defaultdictflows = defaultdict(list)def
packet_callback(pkt):    if IP in pkt:        key =
(pkt[IP].src, pkt[IP].dst,              pkt.sport if TCP in
pkt or UDP in pkt else 0,              pkt.dport if TCP in
pkt or UDP in pkt else 0,              pkt[IP].proto)
flows[key].append((time.time(), len(pkt)))        if
should_close_flow(flows[key]):            features =
extract_features(flows.pop(key))
process_flow(features)sniff(iface='eth0', prn=packet_callback,
store=False)
```

3. Isolation Forest Module

```
from sklearn.ensemble import IsolationForestimport numpy as
npdef train_isolation_forest(X_benign):    model =
IsolationForest(        n_estimators=200,
contamination=0.05,        random_state=42    )
model.fit(X_benign)    return modeldef score_flow(model,
features):    x = np.array(list(features.values())).reshape(1,
-1)    return model.decision_function(x)[0]
```

4. Random Forest Classifier Module

```
from sklearn.ensemble import RandomForestClassifierfrom
sklearn.model_selection import train_test_splitfrom
sklearn.metrics import classification_reportdef
train_random_forest(X, y):    X_train, X_test, y_train, y_test
= train_test_split(        X, y, test_size=0.2, stratify=y,
random_state=42)    model = RandomForestClassifier(
```

```
n_estimators=200, max_depth=10, random_state=42)
model.fit(X_train, y_train)    y_pred = model.predict(X_test)
print(classification_report(y_test, y_pred))    return model
```

5. GNN Flow Detection Module

```
import torchfrom torch_geometric.nn import GCNConvfrom
torch.nn import functional as Fclass FlowGNN(torch.nn.Module):
def __init__(self, in_features):        super().__init__()
self.conv1 = GCNConv(in_features, 32)        self.conv2 =
GCNConv(32, 1)        self.dropout = torch.nn.Dropout(0.2)
def forward(self, x, edge_index):        x =
F.relu(self.conv1(x, edge_index))        x = self.dropout(x)
x = torch.sigmoid(self.conv2(x, edge_index))        return x
```

6. Hybrid Command Detection Module (Algorithm 1)

```
import refrom sklearn.ensemble import IsolationForestPATTERNS
= [    (r'base64.*decode', 'CRITICAL'),    (r'nc\s+-[el]',
'CRITICAL'),    (r'wget.*\|.*bash', 'HIGH'),]def
detect_command(cmd, if_model, scaler):    regex_match = None
severity = None    for pattern, sev in PATTERNS:        if
re.search(pattern, cmd, re.I):            regex_match =
pattern; severity = sev; break    if severity in ('CRITICAL',
'HIGH'):        return 'Malicious', 'High Confidence'
features = extract_cmd_features(cmd)    score =
if_model.decision_function([scaler.transform([features])[0]])[
0]    is_anomaly = score < 0    if is_anomaly and regex_match:
return 'Malicious', 'Very High Confidence'    elif is_anomaly:
return 'Malicious', 'AI Confidence'    elif regex_match:
return 'Malicious', 'Regex Confidence'    return 'Benign', 0.0
```

7. Ensemble Score Fusion Module

```
def ensemble_score(if_score, rf_prob, gnn_prob,
w1=0.25, w2=0.45, w3=0.30,                    threshold=0.6):
# Normalize IF score to [0,1]    if_norm = max(0, min(1, (0.5
- if_score) / 1.0))    score = w1 * if_norm + w2 * rf_prob +
w3 * gnn_prob    return score, score >= threshold
```

8. Flask-SocketIO Alert Backend

```
from flask import Flask, jsonifyfrom flask_socketio import
SocketIOapp = Flask(__name__)socketio = SocketIO(app,
cors_allowed_origins='*')@app.route('/api/alerts')def
get_alerts():    alerts = db.query_recent_alerts(limit=100)
return jsonify(alerts)def broadcast_alert(alert):
socketio.emit('new_alert', alert)if __name__ == '__main__':
socketio.run(app, host='0.0.0.0', port=5000, debug=False)
```

9. Cross-Validation Evaluation Module

```
from sklearn.model_selection import StratifiedKFold,
cross_val_scoredef cross_validate_model(model, X, y,
n_splits=10):    kfold = StratifiedKFold(
n_splits=n_splits, shuffle=True, random_state=42)    scores =
cross_val_score(        model, X, y, cv=kfold, scoring='f1')
print(f'F1: {scores.mean():.3f} ± {scores.std():.3f}')
return scores
```

APPENDIX B

CONFERENCE PUBLICATION

Our research paper titled “A Unified AI-Based Network Intrusion Detection Framework for Network and System Traffic” was presented at the 2nd International Conference on Intelligent Systems and Computational Networks (ICISCN 2026). The conference included 300+ shortlisted teams from various domains. Our paper was accepted with a plagiarism score of just 4%, highlighting its originality and quality.



Registration Confirmation for ICISCN-2026 conference External Inbox ×

Microsoft CMT <noreply@msr-cmt.org> Tue, Apr 21, 9:55 AM (7 days ago)
to me, chair

Dear Author,

We have received your final camera ready paper & payment for paper id ICISCN0860 and your registration for the ICISCN-2026 Conference is confirmed.

--
Thanks and regards
Organizing Committee
ICISCN-2026

Please do not reply to this email as it was generated from an email account that is not monitored.


To stop receiving conference emails, you can check the 'Do not send me conference email' box from your User Profile.

Microsoft respects your privacy. To learn more, please read our Privacy Statement.

Microsoft Corporation
One Microsoft Way
Redmond, WA 98052

Figure A.1: ICISCN 2026 Acceptance

On presenting the paper in this international conference held at Lingaraj Appa Engineering College, we received positive remarks and suggestion from the judging panel.



2026 2nd International Conference on Intelligent Systems and Computational Networks (ICISCN)

A Unified AI-Based Network Intrusion Detection Framework for Network and System Traffic

[1] Gowtham V
Department of Networking and Communications
SRM Institute of Science and Technology
Kattankulathur-603203
Tamil Nadu, India
gv6858@srmist.edu.in

[2] Girijesh B
Department of Networking and Communications
SRM Institute of Science and Technology
Kattankulathur-603203
Tamil Nadu, India
bt1368@srmist.edu.in

[3] Shyam R
Department of Networking and Communications
SRM Institute of Science and Technology
Kattankulathur-603203
Tamil Nadu, India
sr9840@srmist.edu.in

[*4] Yamini B
Department of Networking and Communications
SRM Institute of Science and Technology
Kattankulathur-603203
Tamil Nadu, India
yaminib@srmist.edu.in

***Abstract*— Enterprise and cloud networks are bombarded with a combination of internal traffic, including web requests, API requests, admin requests and background processes. It is a game of scale: the bigger the scale, the more the targets, and so perhaps attackers are ever-present to exploit any weakness. Traditional IDS systems only scratch the surface; signature-based systems are helpless against zero-day exploits and rudimentarily designed machine-learning systems cannot handle mixed streams of data. So that security staff are overwhelmed by excessive alerts or do not realise they are under attack. To address this, this paper introduces the AI-IDS SOC architecture that counter these shortcomings. Packet capture is performed through Scapy and aggregate the flow with statistical features derivation. It is based on three different orthogonal models used in cascade manner: Isolation Forest for anomaly discovery, Random Forest for the classification of flows, and graph neural network to discover the flow relationships. A hybrid command detector layer consists of 47 hand-written rules in regular expression and a Transformer model based on fileless attack. The Random Forest module was able to achieve a true-positive rate (TPR) of 95.6 percentage points and a false-positive rate (FPR) of 2.6 percentage points, when evaluated against a malicious vs. benign flow dataset labeled. Additionally, the ensemble method provides for both multi-stage and complex attack scenarios.**

***Index Terms*—Intrusion Detection System, Machine Learning, Graph Neural Network, Anomaly Detection, SOC, Network Security**

I. Introduction

The rapid ascent of cloud computing has completely changed existing networks. Compared to what they did before, current networks have to manage a significant amount of online traffic, cloud logins, API calls, and backend service traffic. However, cyber crooks have become quite sophisticated. Rather than relying on basic port-scanning methods, some attackers employ sophisticated approaches including fileless malware, Living-Off-The-Land attacks (which conceal illicit activity inside legitimate system applications), and slow, undetectable scans that are difficult to detect. For cloud systems, flexible and quick network security is needed. As cloud technology

evolves, it is absolutely vital to incorporate cloud-centered security into all network security policies. These difficult attacks can be found with the aid of signature-based identification methods and classic firewalls. One alone is not enough.

Large businesses having quite low attack counts but extremely high network activity hidden among that data have two primary problems: There is excessive intrusion detection system (IDS) and security information and event management (SIEM) notification, resulting in difficulty for security professionals to identify real security breaches. Overly notifying security staff of possible threats impedes their ability to respond quickly, creating a feedback loop with researchers spending more time aggregating data rather than keeping attackers at bay, ultimately resulting in decreased overall security effectiveness.

People who use machine learning techniques in regulated environments such as Random Forest and Isolation Forest get especially good results. Random forest models have achieved 95.6 percentage detection accuracy under strictly regulated circumstances. However, some studies focus on test results while disregarding actual performance statistics from live networks in the real world. Often overlooked, Scapy lets you predict an attack; contemporary technologies like Graph Neural Networks can evaluate real-time network traffic volume. Lack of basic, top-tier dashboards is another challenge security experts can overcome to quickly examine information.

The proposed artificial intelligence-IDS-SOC approach provides a complete end-to-end means of detecting ongoing cyber attacks. Later phases yielded a parser derived from Terraform log warnings for unexpected command patterns discovered in an SQLite database. Flask-SocketIO's real-time dashboard lets specialists rapidly evaluate risk level, keep an eye on events, and grasp links between warnings. The lean way eliminates pointless alarms to help real dangers from relying on expensive technology. For already stretched small to medium-sized security operations centers, this will be quite beneficial.

Many of the current security systems only analyze selected network activity patterns. Actual attacks create even more uncertainty because they enable one to relate desired system-level network activity with either bad instructions or code execution. Fileless attacks and inappropriate use of actual


979-8-3315-8871-7/26/$31.00 ©2026 IEEE

Figure A.2 Front Page of Research Paper

APPENDIX C

PLAGIARISM REPORT

Turnitin Similarity Report Summary:



turnitin Page 2 of 8 - Integrity Overview Submission ID trn:oid:::1:3485434808

4% Overall Similarity

The combined total of all matches, including overlapping sources, for each database.

Filtered from the Report


- Bibliography
- Quoted Text

Match Groups

- 8 Not Cited or Quoted 4%
  Matches with neither in-text citation nor quotation marks
- 0 Missing Quotations 0%
  Matches that are still very similar to source material
- 0 Missing Citation 0%
  Matches that have quotation marks, but no in-text citation
- 0 Cited and Quoted 0%
  Matches with in-text citation present, but no quotation marks

Top Sources

- 1% Internet sources
- 3% Publications
- 2% Submitted works (Student Papers)



turnitin Page 3 of 8 - Integrity Overview Submission ID trn:oid:::1:3485434808

Match Groups

- 8 Not Cited or Quoted 4%
  Matches with neither in-text citation nor quotation marks
- 0 Missing Quotations 0%
  Matches that are still very similar to source material
- 0 Missing Citation 0%
  Matches that have quotation marks, but no in-text citation
- 0 Cited and Quoted 0%
  Matches with in-text citation present, but no quotation marks

Top Sources

1% Internet sources
3% Publications
2% Submitted works (Student Papers)

Top Sources

The sources with the highest number of matches within the submission. Overlapping sources will not be displayed.

1	Publication	
Vyshakh Nair, Kp Yashwin, Annapurani Panaiyappan K. "FOOTHOLDER: Collection...		<1%
2	Publication	
B. Hariharan, R. Siva, S. Sadagopan, Vaibhav Mishra, Yash Raghav. "Malware Dete...		<1%
3	Publication	
Jérémy Billuart, Romain Gemignani, Patrick Perrot. "Chapter 2 ODIP : A State-of-t...		<1%
4	Internet	
gallardorafael.github.io		<1%
5	Publication	
Ahmed A. Abd El-Latif, Mohammed A ElAffendi, Mohamed Ali AlShara, Yassine Ma...		<1%
6	Internet	
www.coursehero.com		<1%
7	Student papers	
SRM University		<1%