

Doctor Appointment Booking System

Step by Step Process to Run the Project

1 Step 1: Set Up the Frontend (React App)

a) Open a terminal and navigate into the client folder:

```
$ cd client
```

b) Install the dependencies (if not installed already):

```
$ npm install
```

c) Once installation is done, start the React development server:

```
$ npm run dev
```

Output in Terminal:

```
VITE v5.0.0 ready in 300 ms
→ Local: http://localhost:5173/
→ Network: use --host to expose
```



The app should now be running on:
<http://localhost:5173>

2 Step 2: Set Up the Backend (Express Server)

a) Open a new terminal tab/window or split the terminal.

b) Navigate into the server folder:

```
$ cd ../server
```

Example:

```
Terminal 1 (Frontend)
$ cd client
$ npm run dev
VITE v5.0.0 ready in 300 ms
→ Local: http://localhost:5173/
→ Network: use --host to expose
```

React App Running on
<http://localhost:5173>

```
Terminal 2 (Backend)
$ cd ../server
$
```

Backend will Run on
<http://localhost:8000>

3 Step 3: Configure Environment Variables

Inside the server folder, create a new file named .env (no file extension).

In that .env file, add your MongoDB connection string:

```
MONGO_URI=mongodb://localhost:27017/doctor
```



Make sure the file name is exactly .env (no .txt or any other extension).

4 Step 4: Start MongoDB

Before running the backend, ensure MongoDB is running.

- If you are using MongoDB locally, start the MongoDB service.
- Verify by opening MongoDB Compass and connecting to:

```
mongodb://localhost:27017
```



If the connection is successful, MongoDB is running.

5 Step 5: Install Backend Packages

In the server folder, install the dependencies (if not installed yet):

```
$ npm install
```



Wait until installation completes.

7 Step 7: Backend Running

You should see output similar to:

```
Server started on port 8000
MongoDB Connected
```



The server should start on:
<http://localhost:8000>

6 Step 6: Start the Backend Server

Inside the same server folder, run the backend server:

```
$ nodemon index.js
```

If nodemon is not installed:

- Install it globally:

```
$ npm install -g nodemon
```

- Or run without installing globally:

```
$ npx nodemon index.js
```

Or if you have in package.json:

```
$ npm run dev
```

8 Step 8: Run Both Together

At this point, you should have two terminals running:

```
Terminal 1 (Frontend)
$ cd client
$ npm run dev
VITE v5.0.0 ready in 300 ms
→ Local: http://localhost:5173/
→ Network: use --host to expose
```

Runs on:
<http://localhost:5173>



```
Terminal 2 (Backend)
$ cd server
$ nodemon index.js
Server started on port 8000
MongoDB Connected
```

Runs on:
<http://localhost:8000>

9 Step 9: Project Structure

```
Doctor-Appointment/
├── client/
│   ├── src/
│   ├── public/
│   └── package.json
└── server/
    ├── controllers/
    ├── models/
    ├── routes/
    ├── middleware/
    ├── node_modules/
    ├── package.json
    ├── index.js
    └── .env
```

10 Step 10: Access the Application



React Frontend
Open in browser
<http://localhost:5173>



Express Backend
API Server
<http://localhost:8000>



MongoDB Database
Database Name: **doctor**
<mongodb://localhost:27017/doctor>