

Create VPC with 2 private and 2 public subnets.

VPC > Your VPCs > Create VPC

Create VPC [Info](#)

A VPC is an isolated portion of the AWS Cloud populated by AWS objects, such as Amazon EC2 instances. Mouse over a resource to highlight the related resource.

VPC settings

Resources to create [Info](#)

Create only the VPC resource or the VPC and other networking resources.

☐ VPC only

☒ VPC and more

Name tag auto-generation [Info](#)

Enter a value for the Name tag. This value will be used to auto-generate Name tags for all resources in the VPC.

☒ Auto-generate

Preview

VPC [Show details](#)

Your AWS virtual network

project-vpc

Su

Sub

us-

A

Your VPCs (2) [Info](#)

Last updated
less than a minute ago

[Actions](#)

[Create VPC](#)

Find VPCs by attribute or tag

☐	Name	VPC ID	State	Encryption c...	Encryption cont
☐	-	vpc-0c750680361361647	Available	-	-
☐	my-vpc-vpc	vpc-0ba04db3a6aec5489	Available	-	-

Route tables (6) [Info](#)

Last updated
6 minutes ago

[Actions](#)

[Create route table](#)

Find route tables by attribute or tag

☐	Name	Route table ID	Explicit subnet associ...	Edge associations	Ma
☐	-	rtb-0eeb9ca56b97018d8	-	-	Yes
☐	my-vpc-rtb-public	rtb-0b7cb732e07bc8456	2 subnets	-	No
☐	my-vpc-rtb-private1-us-east-1a	rtb-0e70449f34e0820f1	subnet-0e3824328e70ffd...	-	No
☐	my-vpc-rtb-private2-us-east-1b	rtb-053bd5471f86c9876	subnet-0bd855ecffd783a...	-	No

for my vpc 2 subnets are associated

✓ You have successfully updated subnet associations for [rtb-0e70449f34e0820f1](#) / [my-vpc-rtb-private1-us-east-1a](#).

Route tables (1/6) [Info](#)

Last updated
1 minute ago

[Actions](#)

[Create route table](#)

Find route tables by attribute or tag

☐	Name	Route table ID	Explicit subnet associ...	Edge associations	Main
☐	-	rtb-0eeb9ca56b97018d8	-	-	Yes
☐	my-vpc-rtb-public	rtb-0b7cb732e07bc8456	2 subnets	-	No
☒	my-vpc-rtb-private1-us-east-1a	rtb-0e70449f34e0820f1	subnet-0bd855ecffd783a...	-	No

[rtb-0e70449f34e0820f1](#) / [my-vpc-rtb-private1-us-east-1a](#)

The subnet association was successfully updated

rtb-0e70449f34e0820f1 / my-vpc-rtb-private1-us-east-1a

Filter routes					< 1 >	
Destination	Target	Status	Propagated	Route Origin		
0.0.0.0/0	nat-194c28e1c7edec...	✓ Active	No	Create Route		
10.0.0.0/16	local	✓ Active	No	Create Route Table		

And we already confirmed both private subnets are associated with this route table

Our VPC setup so far,

VPC 10.0.0.0/16

2 public subnets

2 private subnets

DNS hostnames enabled

Public subnets auto-assign public IPv4

Both public subnets → public route table

Both private subnets → private route table

Public route table → Internet Gateway

Private route table → NAT Gateway

Enable DNS Hostname in VPC.

Create an instance

Instance type: t2.micro

Security group: SSH (22)

HTTP (80):

Public subnet: one of your my-vpc-subnet-public1 or public2

Auto-assign public IP: Enabled

User data - optional | [Info](#)

Upload a file with your user data or enter it in the field.

 **Choose file**

```
#!/bin/bash
dnf update -y
dnf install -y httpd
systemctl enable httpd
systemctl start httpd
echo "Hello from my EC2 server" > /var/www/html/index.html
```

Keep this in user data

Then launch instance

And in the browser type `http://public ip`



That means our EC2 + VPC + Apache setup is working correctly.

So far you have:

VPC created

Public and private subnets created

Route tables configured

Internet Gateway configured

NAT Gateway configured

EC2 launched in your public subnet

Public IP assigned

Security group allows HTTP (80)

Apache installed through User Data

Website accessible in browser

Enable Auto Assign Public IP in 2 public subnets.

Subnet

Subnet ID

 subnet-0671d098997c12ab3

Name

 my-vpc-subnet-public1-us-east-1a

Auto-assign IP settings [Info](#)

Enable AWS to automatically assign a public IPv4 or IPv6 address to a new primary network interface for an instance in this subnet.

☒ Enable auto-assign public IPv4 address [Info](#)

☐ Enable auto-assign customer-owned IPv4 address [Info](#)

Option disabled because no customer owned pools found.

Enabling auto-assign ip settings

Edit subnet settings [Info](#)

Subnet

Subnet ID

 subnet-064c7809b4fc04dc4

Name

 my-vpc-subnet-public2-us-east-1b

Auto-assign IP settings [Info](#)

Enable AWS to automatically assign a public IPv4 or IPv6 address to a new primary network interface for an instance in this subnet.

☒ Enable auto-assign public IPv4 address [Info](#)

☐ Enable auto-assign customer-owned IPv4 address [Info](#)

Option disabled because no customer owned pools found.

Also enable for other subnet

both the subnets are now assigned to auto assign public IPV4 address enabled

Add 2 private subnets in private route table.

Available subnets (2/4)

Filter subnet associations

	Name	Subnet ID	IPv4 CIDR	IPv6 CIDR	Route table ID
☐	my-vpc-subnet-public2-us-east-1b	subnet-064c7809b4fc04dc4	10.0.16.0/20	–	rtb-0b7cb732e07bc8456 / my-vpc-
☐	my-vpc-subnet-public1-us-east-1a	subnet-0671d098997c12ab3	10.0.0.0/20	–	rtb-0b7cb732e07bc8456 / my-vpc-
☒	my-vpc-subnet-private1-us-east-1a	subnet-0e3824328e70ffd80	10.0.128.0/20	–	rtb-0e70449f34e0820f1 / my-vpc-
☒	my-vpc-subnet-private2-us-east-1b	subnet-0bd855ecffd783a97	10.0.144.0/20	–	rtb-0e70449f34e0820f1 / my-vpc-

Selected subnets

subnet-0bd855ecffd783a97 / my-vpc-subnet-private2-us-east-1b 

subnet-0e3824328e70ffd80 / my-vpc-subnet-private1-us-east-1a 

[Cancel](#) [Save associations](#)

Her both the private subnets are now associated with private route table

Add 2 public subnets in public route table.

Available subnets (2/4)

Filter subnet associations

Name

Subnet ID

IPv4 CIDR

IPv6 CIDR

Route table ID

☒

my-vpc-subnet-public2-us-east-1a

subnet-064c7809b4fc04dc4

10.0.16.0/20

-

rtb-0b7cb732e07bc8456 / my-vpc-subnet-public2-us-east-1a

☒

my-vpc-subnet-public1-us-east-1a

subnet-0671d098997c12ab3

10.0.0.0/20

-

rtb-0b7cb732e07bc8456 / my-vpc-subnet-public1-us-east-1a

☐

my-vpc-subnet-private1-us-east-1a

subnet-0e3824328e70ffd80

10.0.128.0/20

-

rtb-0e70449f34e0820f1 / my-vpc-subnet-private1-us-east-1a

☐

my-vpc-subnet-private2-us-east-1a

subnet-0bd855ecffd783a97

10.0.144.0/20

-

rtb-0e70449f34e0820f1 / my-vpc-subnet-private2-us-east-1a

Selected subnets

subnet-0671d098997c12ab3 / my-vpc-subnet-public1-us-east-1a

subnet-064c7809b4fc04dc4 / my-vpc-subnet-public2-us-east-1a

Cancel

Save associations

Both public subnets are correctly associated with the public route table

Public route table will have the routes to internet and local.

rtb-0b7cb732e07bc8456 / my-vpc-rtb-public

Filter routes

Destination

Target

Status

Propagated

Route Origin

0.0.0.0/0

igw-03f538d99c287...

Active

No

Create Route

10.0.0.0/16

local

Active

No

Create Route Table

Create EC2 in public subnet with t2.micro and install PHP.

▼ Network settings [Info](#)

VPC - *required* [Info](#)

vpc-0ba04db3a6aec5489 (my-vpc-vpc)
10.0.0.0/16



User data - *optional* [Info](#)

Upload a file with your user data or enter it in the field.

Choose file

```
#!/bin/bash
dnf update -y
dnf install -y httpd php
systemctl enable httpd
systemctl start httpd
echo "<?php phpinfo(); ?>" > /var/www/html/index.php
```

paste this script in the userdata

Then launch instance

☐	public-php-ser...	i-01eb3eea0376f7910	Running	t3.micro	3/3 checks passed	us-east-1a
--------------------------	-------------------	---------------------	---------	----------	-------------------	------------

PHP Version 8.5.9	
	
System	Linux ip-10-0-3-35.ec2.internal 6.18.44-99.149.amzn2023.x86_64 #2 SMP PREEMPT_DYNAMIC Tue Aug 25 21:16:03 UTC 2026 x86_64
Build Date	Jul 28 2026 13:06:52
Build System	Linux
Build Provider	Amazon Linux
Compiler	gcc (GCC) 11.5.0 20240719 (Red Hat 11.5.0-5)
Architecture	x86_64
Server API	FPM/FastCGI
Virtual Directory Support	disabled
Configuration File (php.ini) Path	/etc
Loaded Configuration File	/etc/php.ini
Scan this dir for additional .ini files	/etc/php.d
Additional .ini files parsed	/etc/php.d/10-opcache.ini, /etc/php.d/20-bz2.ini, /etc/php.d/20-calendar.ini, /etc/php.d/20-ctype.ini, /etc/php.d/20-curl.ini, /etc/php.d/20-dom.ini, /etc/php.d/20-exif.ini, /etc/php.d/20-fileinfo.ini, /etc/php.d/20-ftp.ini, /etc/php.d/20-gettext.ini, /etc/php.d/20-iconv.ini, /etc/php.d/20-mbstring.ini, /etc/php.d/20-pdo.ini, /etc/php.d/20-phar.ini, /etc/php.d/20-posix.ini, /etc/php.d/20-shmop.ini, /etc/php.d/20-simplexml.ini, /etc/php.d/20-sockets.ini, /etc/php.d/20-sodium.ini, /etc/php.d/20-sqlite3.ini, /etc/php.d/20-sysvmsg.ini, /etc/php.d/20-sysvsem.ini, /etc/php.d/20-sysvshm.ini, /etc/php.d/20-tokenizer.ini, /etc/php.d/20-xml.ini, /etc/php.d/20-xmlwriter.ini, /etc/php.d/20-xsl.ini, /etc/php.d/30-pdo_sqlite.ini, /etc/php.d/30-xmlreader.ini
PHP API	20250925
PHP Extension	20250925
Zend Extension	420250925
Zend Extension Build	API420250925.NTS
PHP Extension Build	API20250925.NTS

Configure NAT gateway in public subnet and connect to private instance.

NAT gateways (1) [Info](#)

Find NAT gateways by attribute or tag



Actions

Create NAT gateway

< 1 >

	Name	NAT gateway ID	Connectivity...	State	State message	Availabi
	my-vpc-regional-nat	nat-194c28e1c7edec911	Public	Available	-	Regiona

VPC > Route tables > [rtb-0e70449f34e0820f1](#) > Edit routes

Edit routes: [rtb-0e70449f34e0820f1](#) / my-vpc-rtb-private1-us-east-1a

Destination	Target	Status	Propagated	Route Origin
10.0.0.0/16	local	Active	No	CreateRouteTable
Q 0.0.0.0/0	NAT Gateway	Active	No	CreateRoute
	Q nat-194c28e1c7edec911			

Add route

Cancel

Preview

Save changes

Network settings [Info](#)

VPC - required [Info](#)

vpc-0ba04db3a6aec5489 (my-vpc-vpc)
10.0.0.0/16

Subnet [Info](#)

subnet-0e3824328e70ffd80 my-vpc-subnet-private1-us-east-1a
VPC: vpc-0ba04db3a6aec5489 Owner: 469132170253
Availability Zone: us-east-1a (use1-az1) Zone type: Availability Zone
IP addresses available: 4091 CIDR: 10.0.128.0/20

Auto-assign public IP [Info](#)

Disable

Firewall (security groups) [Info](#)

A security group is a set of firewall rules that control the traffic for your instance. Add rules to allow specific traffic to reach your instance.

Create security group

Select existing security group

Summary

Number of instances [Info](#)

1

Software Image (AMI)

Amazon Linux 2023 AMI 2023.12...[read more](#)
ami-081b0a6eac00b4f53

Virtual server type (instance type)

t3.micro

Firewall (security group)

New security group

Cancel

Launch instance

[Preview code](#)

e (Amazon-private)

Public IPv4 address

-

Instance state

Running

Private IP DNS name (IPv4 only)

Private IPv4 addresses

10.0.131.33

Public DNS

-

```
[ec2-user@ip-10-0-3-35 ~]$ ssh ec2-user@10.0.131.33
The authenticity of host '10.0.131.33 (10.0.131.33)' can't be established.
ED25519 key fingerprint is SHA256:HPUD1vRZfJmUEG/HNiNtRxZbqntyWLQrX99SpquB+Mk.
This key is not known by any other names.
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '10.0.131.33' (ED25519) to the list of known hosts.
ec2-user@10.0.131.33: Permission denied (publickey,gssapi-keyex,gssapi-with-mic).
[ec2-user@ip-10-0-3-35 ~]$
```

Permission denied so were are connecting to private instance

browser

In SSH client

How to connect

Public subnet access

Managed SSH keys

Instance Connect

For instances with public IPs or accessible via standard routing. Requires network connectivity to your instance. Connect using temporary SSH keys managed by AWS.



Private subnet access

Managed SSH keys

EC2 Instance Connect Endpoint

Use for instances in private subnets. Traffic is routed through a VPC endpoint. Connect using temporary SSH keys managed by AWS.



Maximum security

IAM authentication

SSM Session Manager

Uses IAM-based authentication. Without SSH keys, bastion hosts any inbound ports.

Connections

We can see an option to connect endpoint

Edit inbound rules

Inbound rules control the incoming traffic that's allowed to reach the instance.

Security group rule ID	Type	Protocol	Port range	Source	Description - optional	
sgr-0cbec178b55bca372	SSH	TCP	22	Cus...		Delete
-	SSH	TCP	22	Cus...	10.0.3.35/32	Delete
					sg-00af58c799142e568	Delete

After giving permissions in the inbound rules of private instance, we connected now

```
Amazon Linux 2023
https://aws.amazon.com/linux/amazon-linux-2023
[ec2-user@ip-10-0-131-33 ~]$
```

```
[ec2-user@ip-10-0-131-33 ~]$ curl -I https://google.com
HTTP/2 301
location: https://www.google.com/
content-type: text/html; charset=UTF-8
content-security-policy-report-only: object-src 'none';base-uri 'self';script-src 'nonce-B6Ryl_99W6tplhg5RZWF6g' 'strict-dynami
mple' 'unsafe-eval' 'unsafe-inline' https: http:;report-uri https://csp.withgoogle.com/csp/gws/other-hp
date: Wed, 02 Sep 2026 07:51:17 GMT
expires: Fri, 02 Oct 2026 07:51:17 GMT
cache-control: public, max-age=2592000
server: gws
content-length: 220
x-xss-protection: 0
x-frame-options: SAMEORIGIN
alt-svc: h3=":443"; ma=2592000,h3-29=":443"; ma=2592000
```

Private EC2 → Private Subnet → NAT Gateway → Internet is working.

So your NAT Gateway configuration and private route table are correct

Install Apache Tomcat in private EC2 and deploy a sample app.

```
[root@ip-10-0-131-33 ~]# dnf install java-17-amazon-corretto -y
Amazon Linux 2023 Kernel Livepatch repository
Dependencies resolved.
533 kB/s | 69 kB    00:00

=====
Package                                Architecture      Version           Repository        Size
-----
Installing:
java-17-amazon-corretto                x86_64            1:17.0.20+10-1.amzn2023.1  amazonlinux      220 k
Installing dependencies:
alsa-lib                                x86_64            1.2.7.2-1.amzn2023.0.4    amazonlinux      503 k
cairo                                    x86_64            1.18.0-4.amzn2023.0.3     amazonlinux      717 k
dejavu-sans-fonts                       noarch            2.37-16.amzn2023.0.2      amazonlinux      1.3 M
dejavu-sans-mono-fonts                  noarch            2.37-16.amzn2023.0.2      amazonlinux      467 k
dejavu-serif-fonts                      noarch            2.37-16.amzn2023.0.2      amazonlinux      1.0 M
fontconfig                              x86_64            2.13.94-2.amzn2023.0.2    amazonlinux      273 k
fonts-filesystem                        noarch            1:2.0.5-12.amzn2023.0.2   amazonlinux      9.5 k
freetype                                x86_64            2.13.2-5.amzn2023.0.2     amazonlinux      422 k
giflib                                   x86_64            5.2.1-9.amzn2023.0.4      amazonlinux      49 k
google-noto-fonts-common                noarch            20240401-1.amzn2023.0.2   amazonlinux      17 k
```

Install java first

```
[root@ip-10-0-131-33 ~]# java --version
openjdk 17.0.20.1 2026-08-18 LTS
OpenJDK Runtime Environment Corretto-17.0.20.10.1 (build 17.0.20.1+10-LTS)
OpenJDK 64-Bit Server VM Corretto-17.0.20.10.1 (build 17.0.20.1+10-LTS, mixed mode, sharing)
```

```
[root@ip-10-0-131-33 opt]# wget https://archive.apache.org/dist/tomcat/tomcat-9/v9.0.89/bin/apache-tomcat-9.0.89.tar.gz
--2026-09-02 07:58:57-- https://archive.apache.org/dist/tomcat/tomcat-9/v9.0.89/bin/apache-tomcat-9.0.89.tar.gz
Resolving archive.apache.org (archive.apache.org)... 65.108.204.189, 2a01:4f9:1a:a084::2
Connecting to archive.apache.org (archive.apache.org)|65.108.204.189|:443... connected.
HTTP request sent, awaiting response... 200 OK
Length: 11756919 (11M) [application/x-gzip]
Saving to: 'apache-tomcat-9.0.89.tar.gz'

apache-tomcat-9.0.89.tar.gz      37%[=====>] 4.24M 289KB/s
```

```

[root@ip-10-0-131-33 opt]# tar xvf apache-tomcat-9.0.89.tar.gz
apache-tomcat-9.0.89/conf/
apache-tomcat-9.0.89/conf/catalina.policy
apache-tomcat-9.0.89/conf/catalina.properties
apache-tomcat-9.0.89/conf/context.xml
apache-tomcat-9.0.89/conf/jaspic-providers.xml
apache-tomcat-9.0.89/conf/jaspic-providers.xsd
apache-tomcat-9.0.89/conf/logging.properties
apache-tomcat-9.0.89/conf/server.xml
apache-tomcat-9.0.89/conf/tomcat-users.xml
apache-tomcat-9.0.89/conf/tomcat-users.xsd
apache-tomcat-9.0.89/conf/web.xml
apache-tomcat-9.0.89/bin/

[root@ip-10-0-131-33 opt]# mv apache-tomcat-9.0.89 tomcat
[root@ip-10-0-131-33 opt]# cd /opt/tomcat/bin
[root@ip-10-0-131-33 bin]# ./startup.sh
Using CATALINA_BASE:   /opt/tomcat
Using CATALINA_HOME:   /opt/tomcat
Using CATALINA_TMPDIR: /opt/tomcat/temp

[root@ip-10-0-131-33 bin]# cd /opt/tomcat/webapps
[root@ip-10-0-131-33 webapps]# ls
ROOT  docs  examples  host-manager  manager
[root@ip-10-0-131-33 webapps]# curl -I http://localhost:8080/examples/
HTTP/1.1 200
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
Accept-Ranges: bytes
ETag: W/"1126-1714767731000"
Last-Modified: Fri, 03 May 2024 20:22:11 GMT
Content-Type: text/html
Content-Length: 1126
Date: Wed, 02 Sep 2026 08:05:15 GMT

[root@ip-10-0-131-33 webapps]# netstat -na | grep 8080
tcp6      0      0 :::8080          :::*              LISTEN
[root@ip-10-0-131-33 webapps]#

```

Installed Java 17

Installed Apache Tomcat 9

Started Tomcat

Deployed/used the Tomcat Examples sample application

Verified the app returns HTTP 200

Verified Tomcat is listening on port 8080

Apache Tomcat + sample app is working on your private EC2.

Configure VPC flow logs and store the logs in S3 and CloudWatch.

Your VPCs (1/2) [Info](#)

Last updated
less than a minute ago



Actions

Create VPC

Find VPCs by attribute or tag

	Name	VPC ID	State	Encryption c...	Encryption con
☒	my-vpc-vpc	vpc-0ba04db3a6aec5489	Available	-	-
☐	-	vpc-0c750680361361647	Available	-	-

vpc-0ba04db3a6aec5489 / my-vpc-vpc



Details

Resource map

CIDRs

Flow logs

Tags

Related resources

Integrations

Details

VPC ID

State

Block Public Access

DNS hostnames

Go to the vpc dashboard

go to the flowlogs and create flowlog fill the details as mentioned

Flow log settings

Name - *optional*

my-vpc-flow-log

Filter

The type of traffic to capture (accepted traffic only, rejected traffic only, or all traffic).

- ☐ Accept
☐ Reject
☒ All

Maximum aggregation interval [Info](#)

The maximum interval of time during which a flow of packets is captured and aggregated into a flow log record.

- ☐ 10 minutes
☒ 1 minute

Destination

The destination to which to publish the flow log data.

- ☐ Send to CloudWatch Logs
☒ Send to an Amazon S3 bucket
☐ Send to Amazon Data Firehose in the same account

Then create s3 bucket

l bucket settings.

Cancel

Create bucket

We successfully created flowlog

Successfully created bucket "my-vpc-flow-log-jagan-2026"

my-vpc-flow-log-jagan-2026 Info

Objects | Metadata | Properties | Permissions | Metrics | Management | File systems - new | Access Points

Objects (0) Copy S3 URI Copy URL Download Open Delete Actions Create folder Upload

Objects are the fundamental entities stored in Amazon S3. You can use [Amazon S3 inventory](#) to get a list of all objects in your bucket. For others to access your objects, you'll need to explicitly grant them permissions. [Learn more](#)

< 1 >

☐	Name	Type	Last modified	Size	Storage class
--------------------------	------	------	---------------	------	---------------

Successfully created flow log for the following resource:
vpc-0ba04db3a6aec5489

fl-031da33c3c433ea08 / my-vpc-s3-flow-log

Details

Flow Log ID fl-031da33c3c433ea08	Destination Type s3	Traffic Type All	File Format Plain text
Name my-vpc-s3-flow-log	Destination Name my-vpc-flow-log-jagan-2026	Max Aggregation Interval 1 minute	Hive Compatible Partitions Not enabled
State Active	IAM Role -	Log Format Default	Partition Logs Daily
Creation Time Wednesday, September 2, 2026 at 14:14:58 GMT+5:30	Cross Account IAM Role -	Tag field specifications -	

The s3 vpc flowlog is active as you can see

Then create one more flow log for cloudwatch

Create flow log [Info](#)

Flow logs can capture IP traffic flow information for the network interfaces associated with your resources. You can create multiple flow logs to send traffic to different destinations.

Selected resources [Info](#)

Flow logs will only be created for resources in an available state.

Name	Resource ID	State
my-vpc-vpc	vpc-0ba04db3a6aec5489	Available

Flow log settings

Name - *optional*

my-vpc-cloudwatch-flow-log

Successfully created flow log for the following resource:

vpc-0ba04db3a6aec5489

fl-05b3d71bb6ee10f0d / my-vpc-cloudwatch-flow-log

Actions

Details

Flow Log ID fl-05b3d71bb6ee10f0d	Destination Type cloud-watch-logs	Traffic Type All	File Format -
Name my-vpc-cloudwatch-flow-log	Destination Name my-vpc-flow-logs	Max Aggregation Interval 1 minute	Hive Compatible Partitions -
State Active	IAM Role arn:aws:iam::469132170253:role/service-role/VPCFlowLogs-Cloudwatch-1788338795203	Log Format Default	Partition Logs -

my-vpc-flow-log-jagan-2026 [Info](#)

[<](#)

[Objects](#)

Metadata

Properties

Permissions

Metrics

Objects (1)

Copy S3 URI

Copy URL

Download

Open

Create folder

Upload

Objects are the fundamental entities stored in Amazon S3. You can use [Amazon S3 inventory](#) to access your objects, you'll need to explicitly grant them permissions. [Learn more](#)

Find objects by prefix

☐	Name	▲	Type	▼	Last modified	▼
☐	AWSLogs/		Folder		-	

We can see aswlogs folder is created

Object overview

Owner

34db28e00368e85b4c8c75808a23477139dc3274304ab4f79ebd9
67d57a54483

AWS Region

US East (N. Virginia) us-east-1

Last modified

September 2, 2026, 14:22:34 (UTC+05:30)

Size

2.6 KB

Type

gz

Key

 AWSLogs/469132170253/vpcflowlogs/us-east-1/2026/09/0
2/469132170253_vpcflowlogs_us-east-1_fl-031da33c3c433ea08_
20260902T0845Z 3821d407.log.gz

flowlog is created and can see the size, type modified etc.