Assignment 7: Sample Data Insertion

DBMS Assignment Series | Project topic: **Online Food Delivery System (QuickBite)**

Name: **Jagan S** | Roll No.: **2501121240031**

1. Objective

Insert realistic sample data into all six tables so that the database simulates a working food-delivery platform in Bengaluru. Data respects every constraint and relationship defined in Assignments 5 and 6.

2. Insertion order

Parent tables are populated first (*customers, restaurants, delivery_partners*), then *menu_items*, then the transaction tables *orders* and *order_items*. This order guarantees that every foreign key value already exists when it is referenced.

Note: E-mail addresses and phone numbers are fictitious sample values. Premium members get free delivery (fee 0); other orders pay Rs. 30 (Rs. 40 for one restaurant). *order_items.unit_price* copies the menu price at the time of ordering. Reference date: 25-Oct-2026.

3.1 Table: customers (12 rows)

```
INSERT INTO customers (full_name, email, phone, area, signup_date, membership) VALUES
    ('Aditya Rao', 'aditya.rao@example.com', '9811100001', 'Indiranagar', '2025-06-10', 'Regular'),
    ('Nisha Verma', 'nisha.verma@example.com', '9811100002', 'Koramangala', '2025-07-15', 'Regular'),
    ('Rahul Menon', 'rahul.menon@example.com', '9811100003', 'HSR Layout', '2025-08-01', 'Regular'),
    ('Pooja Shetty', 'pooja.shetty@example.com', '9811100004', 'Indiranagar', '2024-11-20', 'Premium'),
    ('Sanjay Kumar', 'sanjay.kumar@example.com', '9811100005', 'Whitefield', '2025-09-05', 'Regular'),
    ('Tara Nair', 'tara.nair@example.com', '9811100006', 'Koramangala', '2025-10-12', 'Regular'),
    ('Harish Gowda', 'harish.gowda@example.com', '9811100007', 'Jayanagar', '2024-05-02', 'Premium'),
    ('Ishita Das', 'ishita.das@example.com', '9811100008', 'HSR Layout', '2026-01-18', 'Regular'),
    ('Mohan Raj', 'mohan.raj@example.com', '9811100009', 'Whitefield', '2026-02-25', 'Regular'),
    ('Fatima Sheikh', 'fatima.sheikh@example.com', '9811100010', 'Jayanagar', '2025-12-09', 'Regular'),
    ('Kiran Hegde', 'kiran.hegde@example.com', '9811100011', 'Indiranagar', '2026-03-14', 'Regular'),
    ('Leela Pillai', 'leela.pillai@example.com', '9811100012', 'Koramangala', '2026-10-21', 'Regular');
```

3.2 Table: restaurants (6 rows)

```
INSERT INTO restaurants (restaurant_name, cuisine, area, rating, is_open) VALUES
    ('Spice Garden', 'North Indian', 'Indiranagar', 4.4, 1),
    ('Dosa Corner', 'South Indian', 'Jayanagar', 4.6, 1),
    ('Pizza Palace', 'Italian', 'Koramangala', 4.1, 1),
    ('Dragon Bowl', 'Chinese', 'HSR Layout', 4.0, 1),
    ('Burger Hub', 'Fast Food', 'Whitefield', 3.9, 1),
    ('Sweet Tooth', 'Desserts', 'Koramangala', 4.5, 0);
```

3.3 Table: delivery_partners (5 rows)

```
INSERT INTO delivery_partners (partner_name, phone, vehicle, availability) VALUES
    ('Ravi Kumar', '9822200001', 'Bike', 'Available'),
    ('Suresh Babu', '9822200002', 'Scooter', 'Available'),
    ('Manju Nath', '9822200003', 'Bike', 'Available'),
    ('Deepak Joshi', '9822200004', 'Cycle', 'Available'),
    ('Anil Reddy', '9822200005', 'Bike', 'Offline');
```

3.4 Table: menu_items (24 rows)

```
INSERT INTO menu_items (restaurant_id, item_name, category, price, is_veg) VALUES
    (1, 'Paneer Tikka', 'Starter', 220, 1),
    (1, 'Butter Chicken', 'Main Course', 320, 0),
    (1, 'Dal Makhani', 'Main Course', 240, 1),
    (1, 'Gulab Jamun', 'Dessert', 90, 1),
    (2, 'Masala Dosa', 'Main Course', 110, 1),
    (2, 'Idli Sambar', 'Starter', 70, 1),
    (2, 'Filter Coffee', 'Beverage', 40, 1),
    (2, 'Chicken Chettinad', 'Main Course', 280, 0),
    (3, 'Margherita Pizza', 'Main Course', 299, 1),
    (3, 'Pepperoni Pizza', 'Main Course', 399, 0),
```

```
    (3, 'Garlic Bread', 'Starter', 129, 1),
    (3, 'Cold Coffee', 'Beverage', 99, 1),
    (4, 'Veg Spring Rolls', 'Starter', 150, 1),
    (4, 'Hakka Noodles', 'Main Course', 210, 1),
    (4, 'Chilli Chicken', 'Starter', 260, 0),
    (4, 'Lemon Iced Tea', 'Beverage', 80, 1),
    (5, 'Classic Veg Burger', 'Main Course', 120, 1),
    (5, 'Chicken Burger', 'Main Course', 180, 0),
    (5, 'French Fries', 'Starter', 99, 1),
    (5, 'Chocolate Shake', 'Beverage', 140, 1),
    (6, 'Chocolate Brownie', 'Dessert', 150, 1),
    (6, 'Ice Cream Sundae', 'Dessert', 170, 1),
    (6, 'Rasmalai', 'Dessert', 130, 1),
    (6, 'Mango Smoothie', 'Beverage', 120, 1);
```

3.5 Table: orders (26 rows)

```
INSERT INTO orders (customer_id, restaurant_id, partner_id, order_date, status, payment_method, delivery_fee) VALUES
    (1, 1, 1, '2026-08-02', 'Delivered', 'UPI', 30),
    (2, 2, 2, '2026-08-05', 'Delivered', 'Cash', 30),
    (3, 3, 3, '2026-08-09', 'Delivered', 'Card', 40),
    (1, 4, 1, '2026-08-14', 'Delivered', 'UPI', 30),
    (4, 1, 2, '2026-08-20', 'Delivered', 'UPI', 0),
    (5, 5, NULL, '2026-08-23', 'Cancelled', 'Card', 30),
    (6, 2, 4, '2026-09-01', 'Delivered', 'UPI', 30),
    (7, 3, 1, '2026-09-04', 'Delivered', 'Card', 0),
    (3, 5, 2, '2026-09-08', 'Delivered', 'Cash', 30),
    (8, 6, 3, '2026-09-12', 'Delivered', 'UPI', 30),
    (1, 2, 1, '2026-09-15', 'Delivered', 'UPI', 30),
    (9, 4, 4, '2026-09-18', 'Delivered', 'Cash', 30),
    (4, 6, 2, '2026-09-22', 'Delivered', 'UPI', 0),
    (10, 1, 3, '2026-09-25', 'Delivered', 'Card', 30),
    (2, 3, 1, '2026-10-01', 'Delivered', 'UPI', 40),
    (5, 2, 2, '2026-10-03', 'Delivered', 'UPI', 30),
    (7, 1, 3, '2026-10-05', 'Delivered', 'Card', 0),
    (11, 5, NULL, '2026-10-07', 'Cancelled', 'Cash', 30),
    (1, 3, 1, '2026-10-09', 'Delivered', 'UPI', 30),
    (6, 4, 4, '2026-10-12', 'Delivered', 'Card', 30),
    (3, 2, 2, '2026-10-14', 'Delivered', 'UPI', 30),
    (4, 5, 3, '2026-10-16', 'Delivered', 'UPI', 0),
    (8, 1, 1, '2026-10-19', 'Delivered', 'Cash', 30),
    (9, 2, 2, '2026-10-22', 'Placed', 'UPI', 30),
    (1, 1, 3, '2026-10-24', 'Placed', 'Card', 30),
    (7, 4, 1, '2026-10-25', 'Placed', 'UPI', 0);
```

3.6 Table: order_items (52 rows)

```
INSERT INTO order_items (order_id, item_id, quantity, unit_price) VALUES
    (1, 1, 1, 220),
    (1, 2, 1, 320),
    (1, 4, 2, 90),
    (2, 5, 2, 110),
    (2, 7, 2, 40),
    (3, 9, 1, 299),
    (3, 11, 1, 129),
    (3, 12, 2, 99),
    (4, 13, 1, 150),
    (4, 14, 2, 210),
    (4, 16, 2, 80),
    (5, 3, 2, 240),
    (5, 2, 1, 320),
    (6, 17, 2, 120),
    (7, 5, 1, 110),
    (7, 6, 1, 70),
    (7, 7, 1, 40),
    (8, 10, 1, 399),
    (8, 9, 1, 299),
    (9, 18, 1, 180),
    (9, 19, 1, 99),
    (9, 20, 1, 140),
    (10, 21, 2, 150),
    (10, 22, 1, 170),
    (11, 5, 2, 110),
    (12, 15, 1, 260),
    (12, 14, 1, 210),
    (13, 23, 2, 130),
```

```
(14, 2, 1, 320),
(14, 3, 1, 240),
(15, 9, 2, 299),
(15, 11, 1, 129),
(16, 5, 1, 110),
(16, 7, 1, 40),
(17, 1, 2, 220),
(17, 3, 1, 240),
(17, 4, 2, 90),
(18, 18, 1, 180),
(19, 10, 1, 399),
(20, 13, 1, 150),
(20, 15, 1, 260),
(21, 6, 2, 70),
(21, 7, 1, 40),
(22, 17, 1, 120),
(22, 19, 2, 99),
(23, 2, 1, 320),
(23, 4, 1, 90),
(24, 5, 1, 110),
(25, 2, 1, 320),
(25, 3, 1, 240),
(26, 13, 2, 150),
(26, 16, 1, 80);
```

After the orders are recorded, partners who have an order in 'Placed' status are marked as busy:

```
UPDATE delivery_partners
SET availability = 'Busy'
WHERE partner_id IN (SELECT partner_id FROM orders
                     WHERE status = 'Placed' AND partner_id IS NOT NULL);
```

4. Verification of the inserted data

4.1 Row count of every table

```
SELECT 'customers' AS table_name, COUNT(*) AS total_rows FROM customers
UNION ALL SELECT 'restaurants', COUNT(*) FROM restaurants
UNION ALL SELECT 'delivery_partners', COUNT(*) FROM delivery_partners
UNION ALL SELECT 'menu_items', COUNT(*) FROM menu_items
UNION ALL SELECT 'orders', COUNT(*) FROM orders
UNION ALL SELECT 'order_items', COUNT(*) FROM order_items;
```

table_name	total_rows
customers	12
restaurants	6
delivery_partners	5
menu_items	24
orders	26
order_items	52

4.2 Restaurants

```
SELECT restaurant_id, restaurant_name, cuisine, area, rating, is_open FROM restaurants;
```

restaurant_id	restaurant_name	cuisine	area	rating	is_open
1	Spice Garden	North Indian	Indiranagar	4.4	1
2	Dosa Corner	South Indian	Jayanagar	4.6	1
3	Pizza Palace	Italian	Koramangala	4.1	1
4	Dragon Bowl	Chinese	HSR Layout	4	1
5	Burger Hub	Fast Food	Whitefield	3.9	1
6	Sweet Tooth	Desserts	Koramangala	4.5	0

4.3 Delivery partners (after the availability update)

```
SELECT partner_id, partner_name, vehicle, availability FROM delivery_partners;
```

partner_id	partner_name	vehicle	availability
1	Ravi Kumar	Bike	Busy
2	Suresh Babu	Scooter	Busy
3	Manju Nath	Bike	Busy
4	Deepak Joshi	Cycle	Available
5	Anil Reddy	Bike	Offline

4.4 Sample from orders (NULL partner_id = cancelled before assignment)

```
SELECT order_id, customer_id, restaurant_id, partner_id, order_date, status, payment_method, delivery_fee
FROM orders ORDER BY order_id LIMIT 10;
```

order_id	customer_id	restaurant_id	partner_id	order_date	status	payment_method	delivery_fee
1	1	1	1	2026-08-02	Delivered	UPI	30
2	2	2	2	2026-08-05	Delivered	Cash	30
3	3	3	3	2026-08-09	Delivered	Card	40
4	1	4	1	2026-08-14	Delivered	UPI	30
5	4	1	2	2026-08-20	Delivered	UPI	0
6	5	5	NULL	2026-08-23	Cancelled	Card	30
7	6	2	4	2026-09-01	Delivered	UPI	30
8	7	3	1	2026-09-04	Delivered	Card	0
9	3	5	2	2026-09-08	Delivered	Cash	30
10	8	6	3	2026-09-12	Delivered	UPI	30

4.5 Sample from order_items (lines of orders 1, 4 and 17)

```
SELECT * FROM order_items WHERE order_id IN (1, 4, 17);
```

order_item_id	order_id	item_id	quantity	unit_price
1	1	1	1	220
2	1	2	1	320
3	1	4	2	90
9	4	13	1	150
10	4	14	2	210
11	4	16	2	80
35	17	1	2	220
36	17	3	1	240
37	17	4	2	90

4.6 Relationship and constraint checks

```
PRAGMA foreign_key_check;
```

Output: (no rows) - every foreign key value in menu_items, orders and order_items refers to an existing parent row.

```
SELECT COUNT(*) AS violations FROM menu_items WHERE price <= 0;
```

violations
0

All inserts were accepted by the DBMS without a constraint error, so the data follows the defined constraints and relationships. The data set (12 customers, 6 restaurants, 5 delivery partners, 24 menu items, 26 orders, 52 order lines) contains delivered, cancelled and in-progress orders, premium and regular customers, a closed restaurant, an offline partner, dishes that were never ordered and customers with no delivered order - enough variety to exercise the queries in Assignments 8 and 9.