

1. app_users

```
create table public.app_users (  
  id uuid not null default gen_random_uuid (),  
  email text not null,  
  name text null,  
  created_at timestamp with time zone null default now(),  
  constraint app_users_pkey primary key (id),  
  constraint app_users_email_key unique (email)  
) TABLESPACE pg_default;
```

2. chapters

```
create table public.chapters (  
  id bigint generated always as identity not null,  
  grade text not null,  
  board text not null,  
  chapter_key text not null,  
  chapter_name text not null,  
  created_at timestamp without time zone null default now(),  
  constraint chapters_pkey primary key (id)  
) TABLESPACE pg_default;
```

3. events

```
create table public.events (  
  id uuid not null default gen_random_uuid (),  
  user_id uuid null,  
  event_type text not null,  
  metadata jsonb null,  
  created_at timestamp with time zone null default now(),  
  constraint events_pkey primary key (id)  
) TABLESPACE pg_default;
```

4. pdf_notes

```
create table public.pdf_notes (  
  id bigint generated always as identity not null,  
  chapter_id bigint null,  
  pdf_url text not null,  
  created_at timestamp without time zone null default now(),  
  constraint pdf_notes_pkey primary key (id),  
  constraint pdf_notes_chapter_id_fkey foreign KEY  
  (chapter_id) references chapters (id) on delete CASCADE  
 ) TABLESPACE pg_default;
```

5. profiles

```
create table public.profiles (  
  id uuid not null,  
  email text null,  
  full_name text null,  
  is_admin boolean null default true,  
  subscription_status text null default 'free'::text,  
  grade text null,  
  board text null,  
  created_at timestamp without time zone null default now(),  
  role text not null default 'student'::text,  
  constraint profiles_pkey primary key (id),  
  constraint profiles_email_key unique (email),  
  constraint profiles_id_fkey foreign KEY (id) references  
  auth.users (id) on delete CASCADE  
 ) TABLESPACE pg_default;
```

6. public_content

```
create table public.public_content (  
  id uuid not null default gen_random_uuid (),  
  title text not null,  
  body text not null,  
  category text null default 'General'::text,  
  is_premium boolean null default false,  
  created_by uuid null,  
  created_at timestamp with time zone null default now(),  
  constraint public_content_pkey primary key (id)  
) TABLESPACE pg_default;  
  
create trigger format_math_before_insert BEFORE INSERT  
or  
update on public_content for EACH row  
execute FUNCTION clean_math_content ();
```

7. settings

```
create table public.settings (  
  key text not null,  
  value text null,  
  id uuid null default gen_random_uuid (),  
  created_at timestamp with time zone null default now(),  
  updated_at timestamp with time zone null default now(),  
  constraint settings_key_unique unique (key)  
) TABLESPACE pg_default;  
  
create trigger update_settings_updated_at BEFORE
```

SUPABASE – MATH_SAAS Database Schema
Jagdev Singh Dosanjh (jagdevsinghdosanjh@gmail.com)
update on settings for EACH row
execute FUNCTION update_updated_at_column ();

8. subscription_payments

```
create table public.subscription_payments (  
  id bigint generated always as identity not null,  
  user_id uuid null,  
  order_id text null,  
  payment_id text null,  
  signature text null,  
  amount integer null,  
  status text null default 'success'::text,  
  created_at timestamp without time zone null default now(),  
  subscription_id uuid null,  
  constraint subscription_payments_pkey primary key (id),  
  constraint fk_subscription_payments_subscription foreign  
KEY (subscription_id) references subscriptions (id) on  
delete CASCADE,  
  constraint subscription_payments_user_id_fkey foreign KEY  
(user_id) references profiles (id)  
) TABLESPACE pg_default;
```

9. subscriptions

```
create table public.subscriptions (  
  id uuid not null default gen_random_uuid (),  
  user_id uuid null,  
  plan text not null,  
  status text not null,  
  started_at timestamp with time zone null default now(),  
  ends_at timestamp with time zone null,  
  plan_code text null,  
  amount integer null,
```

SUPABASE – MATH_SAAS Database Schema

Jagdev Singh Dosanjh (jagdevsinghdosanjh@gmail.com)

```
currency text null,  
razorpay_order_id text null,  
expires_at timestamp with time zone null,  
constraint subscriptions_pkey primary key (id),  
constraint subscriptions_user_id_fkey foreign KEY  
(user_id) references app_users (id) on delete CASCADE  
) TABLESPACE pg_default;
```

10.sync_chapters

```
create table public.sync_chapters (  
    id bigserial not null,  
    grade text not null,  
    board text not null,  
    chapter_title text not null,  
    chapter_url text null,  
    description text null,  
    is_published boolean null default true,  
    created_at timestamp without time zone null default now(),  
    constraint sync_chapters_pkey primary key (id)  
) TABLESPACE pg_default;
```

11.usage_logs

```
create table public.usage_logs (  
    id uuid not null default gen_random_uuid (),  
    user_id uuid null,  
    action text null,  
    grade text null,  
    board text null,  
    chapter_key text null,  
    created_at timestamp without time zone null default now(),  
    bytes_in bigint null default 0,  
    bytes_out bigint null default 0,
```

SUPABASE – MATH_SAAS Database Schema
Jagdev Singh Dosanjh (jagdevsinghdosanjh@gmail.com)
`constraint` usage_logs_pkey `primary` key (id),
`constraint` usage_logs_user_id_fkey `foreign` KEY (user_id)
`references` profiles (id)
) TABLESPACE pg_default;

12. videos

```
create table public.videos (  
    id bigint generated always as identity not null,  
    chapter_id bigint null,  
    video_url text not null,  
    created_at timestamp without time zone null default now(),  
    constraint videos_pkey primary key (id),  
    constraint videos_chapter_id_fkey foreign KEY (chapter_id)  
references chapters (id) on delete CASCADE  
) TABLESPACE pg_default;
```