

```
create table public.app_users (  
    id uuid not null default gen_random_uuid (),  
    email text not null,  
    name text null,  
    created_at timestamp with time zone null default now(),  
    constraint app_users_pkey primary key (id),  
    constraint app_users_email_key unique (email)  
) TABLESPACE pg_default;
```

```
create table public.chapters (  
    id bigint generated always as identity not null,  
    grade text not null,  
    board text not null,  
    chapter_key text not null,  
    chapter_name text not null,  
    created_at timestamp without time zone null default now(),  
    constraint chapters_pkey primary key (id)  
) TABLESPACE pg_default;
```

```
create table public.events (  
    id uuid not null default gen_random_uuid (),  
    user_id uuid null,  
    event_type text not null,  
    metadata jsonb null,
```

```
created_at timestamp with time zone null default now(),  
constraint events_pkey primary key (id)  
) TABLESPACE pg_default;
```

```
create table public.pdf_notes (  
    id bigint generated always as identity not null,  
    chapter_id bigint null,  
    pdf_url text not null,  
    created_at timestamp without time zone null default now(),  
    constraint pdf_notes_pkey primary key (id),  
    constraint pdf_notes_chapter_id_fkey foreign KEY (chapter_id) references chapters (id) on  
delete CASCADE  
) TABLESPACE pg_default;
```

```
create table public.profiles (  
    id uuid not null,  
    email text null,  
    full_name text null,  
    is_admin boolean null default true,  
    subscription_status text null default 'free'::text,  
    grade text null,  
    board text null,  
    created_at timestamp without time zone null default now(),  
    role text not null default 'student'::text,
```

```
constraint profiles_pkey primary key (id),  
constraint profiles_email_key unique (email),  
constraint profiles_id_fkey foreign KEY (id) references auth.users (id) on delete CASCADE  
) TABLESPACE pg_default;
```

```
create table public.public_content (  
  id uuid not null default gen_random_uuid (),  
  title text not null,  
  body text not null,  
  category text null default 'General'::text,  
  is_premium boolean null default false,  
  created_by uuid null,  
  created_at timestamp with time zone null default now(),  
  is_published boolean null default true,  
  constraint public_content_pkey primary key (id)  
) TABLESPACE pg_default;
```

```
create trigger format_math_before_insert BEFORE INSERT  
or  
update on public_content for EACH row  
execute FUNCTION clean_math_content ();
```

```
create table public.settings (  
    key text not null,  
    value text null,  
    id uuid null default gen_random_uuid (),  
    created_at timestamp with time zone null default now(),  
    updated_at timestamp with time zone null default now(),  
    constraint settings_key_unique unique (key)  
) TABLESPACE pg_default;
```

```
create trigger update_settings_updated_at BEFORE  
update on settings for EACH row  
execute FUNCTION update_updated_at_column ();
```

```
create table public.subscription_payments (  
    id bigint generated always as identity not null,  
    user_id uuid null,  
    order_id text null,  
    payment_id text null,  
    signature text null,  
    amount integer null,  
    status text null default 'success'::text,  
    created_at timestamp without time zone null default now(),  
    subscription_id uuid null,  
    constraint subscription_payments_pkey primary key (id),
```

```
constraint fk_subscription_payments_subscription foreign KEY (subscription_id) references
subscriptions (id) on delete CASCADE,

constraint subscription_payments_user_id_fkey foreign KEY (user_id) references profiles (id)
) TABLESPACE pg_default;
```

```
create table public.subscriptions (

id uuid not null default gen_random_uuid (),

user_id uuid null,

plan text not null,

status text not null,

started_at timestamp with time zone null default now(),

ends_at timestamp with time zone null,

plan_code text null,

amount integer null,

currency text null,

razorpay_order_id text null,

expires_at timestamp with time zone null,

created_at timestamp with time zone null default now(),

updated_at timestamp with time zone null default now(),

constraint subscriptions_pkey primary key (id),

constraint subscriptions_user_id_fkey foreign KEY (user_id) references profiles (id) on delete
CASCADE

) TABLESPACE pg_default;
```

```
create unique INDEX IF not exists subscriptions_user_id_unique on public.subscriptions using
btree (user_id) TABLESPACE pg_default;
```

```
create table public.sync_chapters (  
    id bigserial not null,  
    grade text not null,  
    board text not null,  
    chapter_title text not null,  
    chapter_url text null,  
    description text null,  
    is_published boolean null default true,  
    created_at timestamp without time zone null default now(),  
    constraint sync_chapters_pkey primary key (id)  
) TABLESPACE pg_default;
```

```
create table public.usage_logs (  
    id uuid not null default gen_random_uuid (),  
    user_id uuid null,  
    action text null,  
    grade text null,  
    board text null,  
    chapter_key text null,  
    created_at timestamp without time zone null default now(),  
    bytes_in bigint null default 0,  
    bytes_out bigint null default 0,  
    constraint usage_logs_pkey primary key (id),  
    constraint usage_logs_user_id_fkey foreign KEY (user_id) references profiles (id)
```

```
) TABLESPACE pg_default;
```

```
create table public.videos (
```

```
    id bigint generated always as identity not null,
```

```
    chapter_id bigint null,
```

```
    video_url text not null,
```

```
    created_at timestamp without time zone null default now(),
```

```
    constraint videos_pkey primary key (id),
```

```
    constraint videos_chapter_id_fkey foreign KEY (chapter_id) references chapters (id) on delete  
CASCADE
```

```
) TABLESPACE pg_default;
```