

```
1  -- phpMyAdmin SQL Dump
2  -- version 5.2.1
3  -- https://www.phpmyadmin.net/
4  --
5  -- Host: 127.0.0.1:3306
6  -- Generation Time: Jun 10, 2026 at 04:26 PM
7  -- Server version: 9.1.0
8  -- PHP Version: 8.3.14
9
10 SET SQL_MODE = "NO_AUTO_VALUE_ON_ZERO";
11 START TRANSACTION;
12 SET time_zone = "+00:00";
13
14
15 /*!40101 SET @OLD_CHARACTER_SET_CLIENT=@@CHARACTER_SET_CLIENT */;
16 /*!40101 SET @OLD_CHARACTER_SET_RESULTS=@@CHARACTER_SET_RESULTS */;
17 /*!40101 SET @OLD_COLLATION_CONNECTION=@@COLLATION_CONNECTION */;
18 /*!40101 SET NAMES utf8mb4 */;
19
20 --
21 -- Database: `physics_saas`
22 --
23
24 -- -----
25
26 --
27 -- Table structure for table `api_keys`
28 --
29
30 DROP TABLE IF EXISTS `api_keys`;
31 CREATE TABLE IF NOT EXISTS `api_keys` (
32   `id` bigint UNSIGNED NOT NULL AUTO_INCREMENT,
33   `name` varchar(100) COLLATE utf8mb4_unicode_ci NOT NULL,
34   `key_hash` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
35   `created_by` bigint UNSIGNED NOT NULL,
36   `is_active` tinyint(1) NOT NULL DEFAULT '1',
37   `created_at` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP,
38   PRIMARY KEY (`id`),
39   KEY `fk_apikeys_user` (`created_by`)
40 ) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
41
42 -- -----
43
44 --
45 -- Table structure for table `audit_logs`
```

```

46  --
47
48  DROP TABLE IF EXISTS `audit_logs`;
49  CREATE TABLE IF NOT EXISTS `audit_logs` (
50      `id` bigint UNSIGNED NOT NULL AUTO_INCREMENT,
51      `user_id` bigint UNSIGNED DEFAULT NULL,
52      `action` varchar(100) COLLATE utf8mb4_unicode_ci NOT NULL,
53      `entity_type` varchar(100) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
54      `entity_id` bigint UNSIGNED DEFAULT NULL,
55      `meta` json DEFAULT NULL,
56      `ip_address` varchar(45) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
57      `created_at` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP,
58      PRIMARY KEY (`id`),
59      KEY `fk_audit_user` (`user_id`)
60  ) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
61
62  -- -----
63
64  --
65  -- Table structure for table `courses`
66  --
67
68  DROP TABLE IF EXISTS `courses`;
69  CREATE TABLE IF NOT EXISTS `courses` (
70      `id` bigint UNSIGNED NOT NULL AUTO_INCREMENT,
71      `slug` varchar(150) COLLATE utf8mb4_unicode_ci NOT NULL,
72      `title` varchar(200) COLLATE utf8mb4_unicode_ci NOT NULL,
73      `description` text COLLATE utf8mb4_unicode_ci,
74      `level` enum('foundation','11','12','dropper','mixed') COLLATE
75      utf8mb4_unicode_ci DEFAULT NULL,
76      `is_published` tinyint(1) NOT NULL DEFAULT '0',
77      `created_by` bigint UNSIGNED NOT NULL,
78      `created_at` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP,
79      `updated_at` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP ON UPDATE
80      CURRENT_TIMESTAMP,
81      PRIMARY KEY (`id`),
82      UNIQUE KEY `slug` (`slug`),
83      KEY `fk_courses_created_by` (`created_by`)
84  ) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
85
86  -- -----
87
88  -- Table structure for table `enrollments`
89  --

```

```
90 DROP TABLE IF EXISTS `enrollments`;
91 CREATE TABLE IF NOT EXISTS `enrollments` (
92   `id` bigint UNSIGNED NOT NULL AUTO_INCREMENT,
93   `user_id` bigint UNSIGNED NOT NULL,
94   `course_id` bigint UNSIGNED NOT NULL,
95   `source` enum('subscription','manual','promo') COLLATE
utf8mb4_unicode_ci NOT NULL,
96   `subscription_id` bigint UNSIGNED DEFAULT NULL,
97   `enrolled_at` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP,
98   PRIMARY KEY (`id`),
99   UNIQUE KEY `uq_enrollment` (`user_id`,`course_id`),
100   KEY `fk_enrollments_course` (`course_id`),
101   KEY `fk_enrollments_subscription` (`subscription_id`)
102 ) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
103
104 -- -----
105
106 --
107 -- Table structure for table `lessons`
108 --
109
110 DROP TABLE IF EXISTS `lessons`;
111 CREATE TABLE IF NOT EXISTS `lessons` (
112   `id` bigint UNSIGNED NOT NULL AUTO_INCREMENT,
113   `module_id` bigint UNSIGNED NOT NULL,
114   `title` varchar(200) COLLATE utf8mb4_unicode_ci NOT NULL,
115   `slug` varchar(200) COLLATE utf8mb4_unicode_ci NOT NULL,
116   `content_type` enum('video','pdf','quiz','live_class') COLLATE
utf8mb4_unicode_ci NOT NULL,
117   `video_url` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
118   `resource_url` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
119   `duration_sec` int UNSIGNED DEFAULT NULL,
120   `is_free_preview` tinyint(1) NOT NULL DEFAULT '0',
121   `sort_order` int UNSIGNED NOT NULL DEFAULT '1',
122   `created_at` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP,
123   `updated_at` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP ON UPDATE
CURRENT_TIMESTAMP,
124   PRIMARY KEY (`id`),
125   KEY `fk_lessons_module` (`module_id`)
126 ) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
127
128 -- -----
129
130 --
131 -- Table structure for table `lesson_progress`
132 --
```

```
133
134 DROP TABLE IF EXISTS `lesson_progress`;
135 CREATE TABLE IF NOT EXISTS `lesson_progress` (
136   `id` bigint UNSIGNED NOT NULL AUTO_INCREMENT,
137   `user_id` bigint UNSIGNED NOT NULL,
138   `lesson_id` bigint UNSIGNED NOT NULL,
139   `last_position_s` int UNSIGNED DEFAULT NULL,
140   `is_completed` tinyint(1) NOT NULL DEFAULT '0',
141   `completed_at` datetime DEFAULT NULL,
142   `updated_at` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP ON UPDATE
CURRENT_TIMESTAMP,
143   PRIMARY KEY (`id`),
144   UNIQUE KEY `uq_progress` (`user_id`,`lesson_id`),
145   KEY `fk_progress_lesson` (`lesson_id`)
146 ) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
147
148 -- -----
149
150 --
151 -- Table structure for table `modules`
152 --
153
154 DROP TABLE IF EXISTS `modules`;
155 CREATE TABLE IF NOT EXISTS `modules` (
156   `id` bigint UNSIGNED NOT NULL AUTO_INCREMENT,
157   `course_id` bigint UNSIGNED NOT NULL,
158   `title` varchar(200) COLLATE utf8mb4_unicode_ci NOT NULL,
159   `sort_order` int UNSIGNED NOT NULL DEFAULT '1',
160   `created_at` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP,
161   `updated_at` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP ON UPDATE
CURRENT_TIMESTAMP,
162   PRIMARY KEY (`id`),
163   KEY `fk_modules_course` (`course_id`)
164 ) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
165
166 -- -----
167
168 --
169 -- Table structure for table `password_resets`
170 --
171
172 DROP TABLE IF EXISTS `password_resets`;
173 CREATE TABLE IF NOT EXISTS `password_resets` (
174   `id` bigint UNSIGNED NOT NULL AUTO_INCREMENT,
175   `user_id` bigint UNSIGNED NOT NULL,
176   `token` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
```

```
177 `expires_at` datetime NOT NULL,
178 `used_at` datetime DEFAULT NULL,
179 `created_at` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP,
180 PRIMARY KEY (`id`),
181 UNIQUE KEY `token` (`token`),
182 KEY `fk_pwreset_user` (`user_id`)
183 ) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
184
185 -----
186
187 --
188 -- Table structure for table `payments`
189 --
190
191 DROP TABLE IF EXISTS `payments`;
192 CREATE TABLE IF NOT EXISTS `payments` (
193   `id` bigint UNSIGNED NOT NULL AUTO_INCREMENT,
194   `user_id` bigint UNSIGNED NOT NULL,
195   `subscription_id` bigint UNSIGNED DEFAULT NULL,
196   `razorpay_order_id` varchar(100) COLLATE utf8mb4_unicode_ci NOT NULL,
197   `razorpay_payment_id` varchar(100) COLLATE utf8mb4_unicode_ci DEFAULT
198   NULL,
199   `razorpay_signature` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT
200   NULL,
201   `amount_in_paise` int UNSIGNED NOT NULL,
202   `currency` varchar(10) COLLATE utf8mb4_unicode_ci NOT NULL DEFAULT
203   'INR',
204   `status` enum('created','authorized','captured','failed','refunded')
205   COLLATE utf8mb4_unicode_ci NOT NULL,
206   `created_at` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP,
207   `updated_at` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP ON UPDATE
208   CURRENT_TIMESTAMP,
209   PRIMARY KEY (`id`),
210   KEY `fk_payments_user` (`user_id`),
211   KEY `fk_payments_subscription` (`subscription_id`)
212 ) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
213
214 -----
215
216 --
217 -- Table structure for table `plans`
218 --
219
220 DROP TABLE IF EXISTS `plans`;
221 CREATE TABLE IF NOT EXISTS `plans` (
222   `id` bigint UNSIGNED NOT NULL AUTO_INCREMENT,
```

```
218 `code` varchar(50) COLLATE utf8mb4_unicode_ci NOT NULL,
219 `name` varchar(100) COLLATE utf8mb4_unicode_ci NOT NULL,
220 `description` text COLLATE utf8mb4_unicode_ci,
221 `price_in_paise` int UNSIGNED NOT NULL,
222 `billing_period` enum('monthly','quarterly','yearly','lifetime') COLLATE
utf8mb4_unicode_ci NOT NULL,
223 `is_active` tinyint(1) NOT NULL DEFAULT '1',
224 `created_at` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP,
225 `updated_at` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP ON UPDATE
CURRENT_TIMESTAMP,
226 PRIMARY KEY (`id`),
227 UNIQUE KEY `code` (`code`)
228 ) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
229
230 -- -----
231
232 --
233 -- Table structure for table `questions`
234 --
235
236 DROP TABLE IF EXISTS `questions`;
237 CREATE TABLE IF NOT EXISTS `questions` (
238   `id` bigint UNSIGNED NOT NULL AUTO_INCREMENT,
239   `quiz_id` bigint UNSIGNED NOT NULL,
240   `question_text` text COLLATE utf8mb4_unicode_ci NOT NULL,
241   `question_type` enum('mcq_single','mcq_multi','integer','subjective')
COLLATE utf8mb4_unicode_ci NOT NULL,
242   `marks` int UNSIGNED NOT NULL DEFAULT '1',
243   `sort_order` int UNSIGNED NOT NULL DEFAULT '1',
244   `created_at` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP,
245   PRIMARY KEY (`id`),
246   KEY `fk_questions_quiz` (`quiz_id`)
247 ) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
248
249 -- -----
250
251 --
252 -- Table structure for table `question_options`
253 --
254
255 DROP TABLE IF EXISTS `question_options`;
256 CREATE TABLE IF NOT EXISTS `question_options` (
257   `id` bigint UNSIGNED NOT NULL AUTO_INCREMENT,
258   `question_id` bigint UNSIGNED NOT NULL,
259   `option_text` text COLLATE utf8mb4_unicode_ci NOT NULL,
260   `is_correct` tinyint(1) NOT NULL DEFAULT '0',
```

```
261     `sort_order` int UNSIGNED NOT NULL DEFAULT '1',
262     PRIMARY KEY (`id`),
263     KEY `fk_options_question` (`question_id`)
264 ) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
265
266 -----
267
268 --
269 -- Table structure for table `quizzes`
270 --
271
272 DROP TABLE IF EXISTS `quizzes`;
273 CREATE TABLE IF NOT EXISTS `quizzes` (
274     `id` bigint UNSIGNED NOT NULL AUTO_INCREMENT,
275     `lesson_id` bigint UNSIGNED NOT NULL,
276     `title` varchar(200) COLLATE utf8mb4_unicode_ci NOT NULL,
277     `total_marks` int UNSIGNED NOT NULL,
278     `created_at` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP,
279     `updated_at` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP ON UPDATE
280     CURRENT_TIMESTAMP,
281     PRIMARY KEY (`id`),
282     KEY `fk_quizzes_lesson` (`lesson_id`)
283 ) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
284
285 -----
286
287 -- Table structure for table `quiz_answers`
288 --
289
290 DROP TABLE IF EXISTS `quiz_answers`;
291 CREATE TABLE IF NOT EXISTS `quiz_answers` (
292     `id` bigint UNSIGNED NOT NULL AUTO_INCREMENT,
293     `attempt_id` bigint UNSIGNED NOT NULL,
294     `question_id` bigint UNSIGNED NOT NULL,
295     `selected_option_id` bigint UNSIGNED DEFAULT NULL,
296     `answer_text` text COLLATE utf8mb4_unicode_ci,
297     `is_correct` tinyint(1) DEFAULT NULL,
298     `marks_awarded` int DEFAULT NULL,
299     PRIMARY KEY (`id`),
300     KEY `fk_answers_attempt` (`attempt_id`),
301     KEY `fk_answers_question` (`question_id`),
302     KEY `fk_answers_option` (`selected_option_id`)
303 ) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
304
305 -----
```

```
306
307 --
308 -- Table structure for table `quiz_attempts`
309 --
310
311 DROP TABLE IF EXISTS `quiz_attempts`;
312 CREATE TABLE IF NOT EXISTS `quiz_attempts` (
313   `id` bigint UNSIGNED NOT NULL AUTO_INCREMENT,
314   `user_id` bigint UNSIGNED NOT NULL,
315   `quiz_id` bigint UNSIGNED NOT NULL,
316   `started_at` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP,
317   `submitted_at` datetime DEFAULT NULL,
318   `score` int DEFAULT NULL,
319   `status` enum('in_progress','submitted','evaluated') COLLATE
utf8mb4_unicode_ci NOT NULL DEFAULT 'in_progress',
320   PRIMARY KEY (`id`),
321   KEY `fk_attempts_user` (`user_id`),
322   KEY `fk_attempts_quiz` (`quiz_id`)
323 ) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
324
325 -- -----
326
327 --
328 -- Table structure for table `roles`
329 --
330
331 DROP TABLE IF EXISTS `roles`;
332 CREATE TABLE IF NOT EXISTS `roles` (
333   `id` tinyint UNSIGNED NOT NULL AUTO_INCREMENT,
334   `name` varchar(50) COLLATE utf8mb4_unicode_ci NOT NULL,
335   `description` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
336   PRIMARY KEY (`id`),
337   UNIQUE KEY `name` (`name`)
338 ) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
339
340 -- -----
341
342 --
343 -- Table structure for table `sessions`
344 --
345
346 DROP TABLE IF EXISTS `sessions`;
347 CREATE TABLE IF NOT EXISTS `sessions` (
348   `id` bigint UNSIGNED NOT NULL AUTO_INCREMENT,
349   `user_id` bigint UNSIGNED NOT NULL,
350   `refresh_token` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
```

```
351 `user_agent` varchar(255) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
352 `ip_address` varchar(45) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
353 `expires_at` datetime NOT NULL,
354 `created_at` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP,
355 PRIMARY KEY (`id`),
356 KEY `fk_sessions_user` (`user_id`)
357 ) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
358
359 -----
360
361 --
362 -- Table structure for table `subscriptions`
363 --
364
365 DROP TABLE IF EXISTS `subscriptions`;
366 CREATE TABLE IF NOT EXISTS `subscriptions` (
367   `id` bigint UNSIGNED NOT NULL AUTO_INCREMENT,
368   `user_id` bigint UNSIGNED NOT NULL,
369   `plan_id` bigint UNSIGNED NOT NULL,
370   `status` enum('active','expired','cancelled','pending') COLLATE
utf8mb4_unicode_ci NOT NULL DEFAULT 'pending',
371   `starts_at` datetime NOT NULL,
372   `ends_at` datetime NOT NULL,
373   `razorpay_sub_id` varchar(100) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
374   `created_at` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP,
375   `updated_at` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP ON UPDATE
CURRENT_TIMESTAMP,
376   PRIMARY KEY (`id`),
377   KEY `fk_subscriptions_user` (`user_id`),
378   KEY `fk_subscriptions_plan` (`plan_id`)
379 ) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
380
381 -----
382
383 --
384 -- Table structure for table `users`
385 --
386
387 DROP TABLE IF EXISTS `users`;
388 CREATE TABLE IF NOT EXISTS `users` (
389   `id` bigint UNSIGNED NOT NULL AUTO_INCREMENT,
390   `uuid` char(36) COLLATE utf8mb4_unicode_ci NOT NULL,
391   `full_name` varchar(150) COLLATE utf8mb4_unicode_ci NOT NULL,
392   `email` varchar(190) COLLATE utf8mb4_unicode_ci NOT NULL,
393   `phone` varchar(20) COLLATE utf8mb4_unicode_ci DEFAULT NULL,
394   `password_hash` varchar(255) COLLATE utf8mb4_unicode_ci NOT NULL,
```

```
395     `status` enum('active','inactive','banned') COLLATE utf8mb4_unicode_ci
396     DEFAULT 'active',
397     `created_at` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP,
398     `updated_at` datetime NOT NULL DEFAULT CURRENT_TIMESTAMP ON UPDATE
399     CURRENT_TIMESTAMP,
400     PRIMARY KEY (`id`),
401     UNIQUE KEY `uuid` (`uuid`),
402     UNIQUE KEY `email` (`email`)
403 ) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
404
405 --
406 -- Table structure for table `user_roles`
407 --
408
409 DROP TABLE IF EXISTS `user_roles`;
410 CREATE TABLE IF NOT EXISTS `user_roles` (
411     `user_id` bigint UNSIGNED NOT NULL,
412     `role_id` tinyint UNSIGNED NOT NULL,
413     PRIMARY KEY (`user_id`,`role_id`),
414     KEY `fk_user_roles_role` (`role_id`)
415 ) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_unicode_ci;
416
417 --
418 -- Constraints for dumped tables
419 --
420
421 --
422 -- Constraints for table `api_keys`
423 --
424 ALTER TABLE `api_keys`
425     ADD CONSTRAINT `fk_apikeys_user` FOREIGN KEY (`created_by`) REFERENCES
426     `users` (`id`) ON DELETE RESTRICT;
427
428 -- Constraints for table `audit_logs`
429 --
430 ALTER TABLE `audit_logs`
431     ADD CONSTRAINT `fk_audit_user` FOREIGN KEY (`user_id`) REFERENCES
432     `users` (`id`) ON DELETE SET NULL;
433
434 -- Constraints for table `courses`
435 --
436 ALTER TABLE `courses`
```

```
437     ADD CONSTRAINT `fk_courses_created_by` FOREIGN KEY (`created_by`)
REFERENCES `users` (`id`) ON DELETE RESTRICT;
438
439 --
440 -- Constraints for table `enrollments`
441 --
442 ALTER TABLE `enrollments`
443     ADD CONSTRAINT `fk_enrollments_course` FOREIGN KEY (`course_id`)
REFERENCES `courses` (`id`) ON DELETE CASCADE,
444     ADD CONSTRAINT `fk_enrollments_subscription` FOREIGN KEY
(`subscription_id`) REFERENCES `subscriptions` (`id`) ON DELETE SET NULL,
445     ADD CONSTRAINT `fk_enrollments_user` FOREIGN KEY (`user_id`) REFERENCES
`users` (`id`) ON DELETE CASCADE;
446
447 --
448 -- Constraints for table `lessons`
449 --
450 ALTER TABLE `lessons`
451     ADD CONSTRAINT `fk_lessons_module` FOREIGN KEY (`module_id`) REFERENCES
`modules` (`id`) ON DELETE CASCADE;
452
453 --
454 -- Constraints for table `lesson_progress`
455 --
456 ALTER TABLE `lesson_progress`
457     ADD CONSTRAINT `fk_progress_lesson` FOREIGN KEY (`lesson_id`) REFERENCES
`lessons` (`id`) ON DELETE CASCADE,
458     ADD CONSTRAINT `fk_progress_user` FOREIGN KEY (`user_id`) REFERENCES
`users` (`id`) ON DELETE CASCADE;
459
460 --
461 -- Constraints for table `modules`
462 --
463 ALTER TABLE `modules`
464     ADD CONSTRAINT `fk_modules_course` FOREIGN KEY (`course_id`) REFERENCES
`courses` (`id`) ON DELETE CASCADE;
465
466 --
467 -- Constraints for table `password_resets`
468 --
469 ALTER TABLE `password_resets`
470     ADD CONSTRAINT `fk_pwreset_user` FOREIGN KEY (`user_id`) REFERENCES
`users` (`id`) ON DELETE CASCADE;
471
472 --
473 -- Constraints for table `payments`
```

```
474 --
475 ALTER TABLE `payments`
476     ADD CONSTRAINT `fk_payments_subscription` FOREIGN KEY
(`subscription_id`) REFERENCES `subscriptions` (`id`) ON DELETE SET NULL,
477     ADD CONSTRAINT `fk_payments_user` FOREIGN KEY (`user_id`) REFERENCES
`users` (`id`) ON DELETE CASCADE;
478
479 --
480 -- Constraints for table `questions`
481 --
482 ALTER TABLE `questions`
483     ADD CONSTRAINT `fk_questions_quiz` FOREIGN KEY (`quiz_id`) REFERENCES
`quizzes` (`id`) ON DELETE CASCADE;
484
485 --
486 -- Constraints for table `question_options`
487 --
488 ALTER TABLE `question_options`
489     ADD CONSTRAINT `fk_options_question` FOREIGN KEY (`question_id`)
REFERENCES `questions` (`id`) ON DELETE CASCADE;
490
491 --
492 -- Constraints for table `quizzes`
493 --
494 ALTER TABLE `quizzes`
495     ADD CONSTRAINT `fk_quizzes_lesson` FOREIGN KEY (`lesson_id`) REFERENCES
`lessons` (`id`) ON DELETE CASCADE;
496
497 --
498 -- Constraints for table `quiz_answers`
499 --
500 ALTER TABLE `quiz_answers`
501     ADD CONSTRAINT `fk_answers_attempt` FOREIGN KEY (`attempt_id`)
REFERENCES `quiz_attempts` (`id`) ON DELETE CASCADE,
502     ADD CONSTRAINT `fk_answers_option` FOREIGN KEY (`selected_option_id`)
REFERENCES `question_options` (`id`) ON DELETE SET NULL,
503     ADD CONSTRAINT `fk_answers_question` FOREIGN KEY (`question_id`)
REFERENCES `questions` (`id`) ON DELETE CASCADE;
504
505 --
506 -- Constraints for table `quiz_attempts`
507 --
508 ALTER TABLE `quiz_attempts`
509     ADD CONSTRAINT `fk_attempts_quiz` FOREIGN KEY (`quiz_id`) REFERENCES
`quizzes` (`id`) ON DELETE CASCADE;
```

```
510     ADD CONSTRAINT `fk_attempts_user` FOREIGN KEY (`user_id`) REFERENCES
    `users` (`id`) ON DELETE CASCADE;
511
512 --
513 -- Constraints for table `sessions`
514 --
515 ALTER TABLE `sessions`
516     ADD CONSTRAINT `fk_sessions_user` FOREIGN KEY (`user_id`) REFERENCES
    `users` (`id`) ON DELETE CASCADE;
517
518 --
519 -- Constraints for table `subscriptions`
520 --
521 ALTER TABLE `subscriptions`
522     ADD CONSTRAINT `fk_subscriptions_plan` FOREIGN KEY (`plan_id`)
    REFERENCES `plans` (`id`) ON DELETE RESTRICT,
523     ADD CONSTRAINT `fk_subscriptions_user` FOREIGN KEY (`user_id`)
    REFERENCES `users` (`id`) ON DELETE CASCADE;
524
525 --
526 -- Constraints for table `user_roles`
527 --
528 ALTER TABLE `user_roles`
529     ADD CONSTRAINT `fk_user_roles_role` FOREIGN KEY (`role_id`) REFERENCES
    `roles` (`id`) ON DELETE CASCADE,
530     ADD CONSTRAINT `fk_user_roles_user` FOREIGN KEY (`user_id`) REFERENCES
    `users` (`id`) ON DELETE CASCADE;
531 COMMIT;
532
533 /*!40101 SET CHARACTER_SET_CLIENT=@OLD_CHARACTER_SET_CLIENT */;
534 /*!40101 SET CHARACTER_SET_RESULTS=@OLD_CHARACTER_SET_RESULTS */;
535 /*!40101 SET COLLATION_CONNECTION=@OLD_COLLATION_CONNECTION */;
```