

Agenda

- Template engine with express
- jQuery

Using template engines with Express

- A template engine enables you to use static template files in your application.
- At runtime, the template engine replaces variables in a template file with actual values, and transforms the template into an HTML file sent to the client.
- This approach makes it easier to design an HTML page.
- The Express application generator uses Pug as its default, but it also supports Handlebars, and EJS, among others
- To use the template engine (ejs) install the corresponding template engine npm package

```
npm install ejs
```

- To render template files, set the following application setting properties, in the default server.js
 1. views, the directory where the template files are located. Eg: app.set('views', './views'). This defaults to the views directory in the application root directory.
 2. view engine, the template engine to use. For example, to use the ejs template engine: app.set('view engine', 'ejs')

```
app.set('view engine', 'ejs')
```

jQuery

- jQuery is a fast, small, and feature-rich JavaScript library.
- It makes things like HTML document traversal and manipulation, event handling, animation, and Ajax much simpler with an easy-to-use API that works across a multitude of browsers.
- It is a lightweight, "write less, do more", JavaScript library.
- With a combination of versatility and extensibility, jQuery has changed the way that millions of people write JavaScript.
- The jQuery library contains the following features:
 1. HTML/DOM manipulation
 2. CSS manipulation
 3. HTML event methods
 4. Effects and animations
 5. AJAX

Adding jQuery

- The jQuery library is a single JavaScript file, and you reference it with the HTML `<script>` tag

- make sure that the script tag should be inside the head section ``HTML

...

Basic Syntax

- `$(selector).action()`
 - \$ sign to define/access jQuery
 - (selector) to "query (or find)" HTML elements
 - action() to be performed on the element(s)
- Example
 - `$(this).hide()` - hides the current element.
 - `$("p").hide()` - hides all elements.
 - `$(".testclass").hide()` - hides all elements with class="testclass".
 - `$("#testId").hide()` - hides the element with id="testId".

SUNBEAM INFOTECH