

# Database Technologies - Assignment 2

1. Write a query that produces all rows from the Customers table for which the salesperson's number is 1001.

```
D6_96342_Jagdish@localhost>SELECT * FROM CUSTOMERS WHERE snum = 1001;
+-----+-----+-----+-----+-----+
| cnum | cname | city | rating | snum |
+-----+-----+-----+-----+-----+
| 2001 | Hoffman | London | 100 | 1001 |
| 2006 | Clemens | London | 100 | 1001 |
+-----+-----+-----+-----+-----+
2 rows in set (0.001 sec)

D6_96342_Jagdish@localhost>
```

2. Write a select command that produces the rating followed by the name of each customer in San Jose.

```
D6_96342_Jagdish@localhost>SELECT cname, rating FROM customers WHERE city = 'San Jose';
+-----+-----+
| cname | rating |
+-----+-----+
| Liu | 200 |
| Cisneros | 300 |
+-----+-----+
2 rows in set (0.001 sec)
```

3. Write a query that will produce the snum values of all salespeople from the Orders table (with the duplicate values suppressed).

```
[D6_96342_Jagdish@localhost>SELECT DISTINCT snum FROM orders;
```

| snum |
|------|
| 1007 |
| 1001 |
| 1004 |
| 1002 |
| 1003 |

5 rows in set (0.001 sec)

4. Write a query that will display all the orders for amount more than Rs. 1,000.

```
[D6_96342_Jagdish@localhost>SELECT * FROM orders WHERE amt > 1000;
```

| onum | amt     | odate      | cnum | snum |
|------|---------|------------|------|------|
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |

6 rows in set (0.000 sec)

5. Write a query that will give you the names and cities of all salespeople in London with a commission above 0.10.

```
[D6_96342_Jagdish@localhost>SELECT sname, city, comm FROM salespeople WHERE comm > 0.10;
```

| sname  | city      | comm |
|--------|-----------|------|
| Peel   | London    | 0.12 |
| Serres | San Jose  | 0.13 |
| Motika | London    | 0.11 |
| Rifkin | Barcelona | 0.15 |

```
4 rows in set (0.001 sec)
```

6. Write an SQL query that returns all customers who have a rating greater than 100, along with the customers located in Rome regardless of their rating.

```
[D6_96342_Jagdish@localhost>SELECT * FROM customers WHERE rating > 100 OR city = 'Rome';
```

| cnum | cname    | city     | rating | snum |
|------|----------|----------|--------|------|
| 2002 | Giovanni | Rome     | 200    | 1003 |
| 2003 | Liu      | San Jose | 200    | 1002 |
| 2004 | Grass    | Berlin   | 300    | 1002 |
| 2008 | Cisneros | San Jose | 300    | 1007 |
| 2007 | Pereira  | Rome     | 100    | 1004 |

```
5 rows in set (0.001 sec)
```

7. What will be the output from the following query? Select \* from Orders where (amt < 1000 OR NOT (odate = '1990-10-03' AND cnum > 2003));

```
D6_96342_Jagdish@localhost>SELECT * FROM orders WHERE (amt < 1000 OR NOT (odate = '1990-10-03' AND cnum > 2003));
```

| onum | amt     | odate      | cnum | snum |
|------|---------|------------|------|------|
| 3001 | 18.69   | 1990-10-03 | 2008 | 1007 |
| 3003 | 767.19  | 1990-10-03 | 2001 | 1001 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 | 75.75   | 1990-10-04 | 2004 | 1002 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3010 | 309.95  | 1990-10-04 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |

8 rows in set (0.002 sec)

8. What will be the output of the following query? Select \* from Orders where NOT (odate = '1990-10-03' OR snum > 1006) AND amt >= 1500;

```
D6_96342_Jagdish@localhost>SELECT * FROM orders WHERE NOT (odate = '1990-10-03' OR snum > 1006) AND amt >= 1500;
```

| onum | amt     | odate      | cnum | snum |
|------|---------|------------|------|------|
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |

3 rows in set (0.001 sec)

9. What is a simpler way to write this query? Select snum, sname, city, comm from Salespeople Where (comm >= .12 AND comm <= .14);

```
D6_96342_Jagdish@localhost>SELECT snum, sname, city, comm FROM salespeople WHERE (comm >= 0.12 AND comm <= 0.14);
```

| snum | sname  | city     | comm |
|------|--------|----------|------|
| 1001 | Peel   | London   | 0.12 |
| 1002 | Serres | San Jose | 0.13 |

2 rows in set (0.001 sec)

10. Write a query that selects all orders except those with amount less than 100.

```
D6_96342_Jagdish@localhost>SELECT * FROM orders WHERE amt >= 100;
```

| onum | amt     | odate      | cnum | snum |
|------|---------|------------|------|------|
| 3003 | 767.19  | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3010 | 309.95  | 1990-10-04 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |

8 rows in set (0.001 sec)