

Linux assignment VI

Create new directory with the name 18oct and create three directories there. (dir1, dir2, dir3), also create four .txt files (1.txt, 2.txt, 3.txt, 4.txt)

```
[jagdishbutte@Jagdish96342D6 os-sdm % mkdir 18oct  
[jagdishbutte@Jagdish96342D6 os-sdm % mkdir 18oct/dir1 18oct/dir2 18oct/dir3  
[jagdishbutte@Jagdish96342D6 os-sdm % touch 18oct/1.txt 18oct/2.txt 18oct/3.txt 18oct/4.txt
```

Using find command:

1. List only directories from 18oct.

```
[jagdishbutte@Jagdish96342D6 os-sdm % find 18oct -type d  
18oct  
18oct/dir2  
18oct/dir3  
18oct/dir1
```

2. List only files.

```
[jagdishbutte@Jagdish96342D6 os-sdm % find 18oct -type f  
18oct/4.txt  
18oct/3.txt  
18oct/2.txt  
18oct/1.txt
```

3. Make 2.txt executable, now search the files having permission as rwxr-xr-x (755) from 18oct.

```
[jagdishbutte@Jagdish96342D6 os-sdm % chmod 755 18oct/2.txt  
[jagdishbutte@Jagdish96342D6 os-sdm % ls -l 18oct/2.tx  
ls: 18oct/2.tx: No such file or directory  
[jagdishbutte@Jagdish96342D6 os-sdm % ls -l 18oct/2.txt  
-rwxr-xr-x 1 jagdishbutte staff 0 24 May 14:07 18oct/2.txt  
[jagdishbutte@Jagdish96342D6 os-sdm % find 18oct -type f -perm 755  
18oct/2.txt
```

4. Search the file 4.txt.

```
[jagdishbutte@Jagdish96342D6 os-sdm % find 18oct -name "4.txt"  
18oct/4.txt
```