

The Control-M/Server is creating a large number of empty NS*.txt files in the ctm_server/tmp directory after Agent Deployment activities lose the output.

This document contains official content from the BMC Software Knowledge Base. It is automatically updated when the knowledge article is modified.

PRODUCT:

Control-M/Server for UNIX and Microsoft Windows

COMPONENT:

Control-M/Server for UNIX and Microsoft Windows

APPLIES TO:

Control-M/Server 9.0.00, and 9.0.18 prior to Fix Pack 2

PROBLEM:

The Control-M/Server is creating a large number of empty NS*.txt files in the ctm_server/tmp directory after Agent Deployment activities lose the output. These files are created at intervals of 30 minutes.

CAUSE:

CAR00108243: Large amount of empty files in the form of NS*.txt appears at the Control-M/Server temp directory when many agent deployment activities lose their outputs.

SOLUTION:

CAR00108243 has been resolved as part of Control-M/Server 9.0.18.200.

The Control-M/Server is creating a large number of empty NS*.txt files in the ctm_server/tmp directory after Agent Deployment activities lose the output.

Please apply the latest available version of Control-M/Server to resolve.

Alternate option:

1. Open the CCM (Control-M Configuration Manager) and select Manage -> Deployment delete any completed Agent Deployment activities.
2. Decrease the frequency the Control-M/Server attempts to access Control-M/Agent Deploy errors by adding the following line to the file \$HOME/ctm_server/data/config.dat

```
AUTODEPLOY_CACHE_OUTPUT_INTERVAL 1440
```

and run the following command to refresh the Control-M/Server configuration:

```
ctmipc -dest all -msgid cfg
```

NOTE: Once Control-M/Server 9.0.18 Fix Pack 2 or higher is implemented, remove the previously added line in Step 2 and re-run the ctmipc command.

Article Number:

000125852

Article Type:

Solutions to a Product Problem

Looking for additional information? [Search BMC Support](#) or [Browse Knowledge Articles](#)