



CrowdStrike APIs

01/25/2026

1. Vulnerability Management APIs

1.1. About CrowdStrike APIs

1.2. Vulnerability management API overview

- 1.2.1. Required API client scope
- 1.2.2. Validate API data
 - 1.2.2.1. API query syntax
- 1.2.3. Vulnerability management data retention
- 1.2.4. Combined endpoints
- 1.2.5. Task-based endpoints
- 1.2.6. Recommended best practices

1.3. Vulnerability entity properties

- 1.3.1. General vulnerability properties
- 1.3.2. CVE object properties (cve)
- 1.3.3. Host object properties (host_info)
- 1.3.4. Remediation object properties (remediation)
- 1.3.5. Vulnerability evaluation logic properties (evaluation_logic)
- 1.3.6. Installed patches properties (installed_patches)

1.4. Filter vulnerability management APIs

- 1.4.1. Vulnerability management API filter parameters

1.5. Sort vulnerability management APIs

- 1.5.1. Vulnerability management API sort parameters

1.6. HTTP response codes

1.7. Use vulnerability management API endpoints

- 1.7.1. Get vulnerability entities
 - 1.7.1.1. Endpoint
 - 1.7.1.2. Parameters
 - 1.7.1.3. Example request
 - 1.7.1.4. Example response
- 1.7.2. Get vulnerability evaluation logic entities
 - 1.7.2.1. Endpoint
 - 1.7.2.2. Parameters
 - 1.7.2.3. Example request
 - 1.7.2.4. Example response
- 1.7.3. Get remediation details by ID
 - 1.7.3.1. Recommended best practice
 - 1.7.3.2. Endpoint
 - 1.7.3.3. Parameters
 - 1.7.3.4. Example request
 - 1.7.3.5. Example response
- 1.7.4. Get vulnerability evaluation logic IDs by timestamp
 - 1.7.4.1. Endpoint
 - 1.7.4.2. Parameters
 - 1.7.4.3. Example request
 - 1.7.4.4. Example response
- 1.7.5. Get vulnerability evaluation logic details by ID
 - 1.7.5.1. Endpoint
 - 1.7.5.2. Parameters
 - 1.7.5.3. Example request
 - 1.7.5.4. Example response
- 1.7.6. Get Windows patch details for individual assets
 - 1.7.6.1. Endpoint
 - 1.7.6.2. Parameters
 - 1.7.6.3. Example request
 - 1.7.6.4. Example response

Vulnerability Management APIs

Identify, prioritize, and remediate vulnerabilities on your Windows, macOS, and Linux assets.

About CrowdStrike APIs

CrowdStrike provides use cases and example requests and responses for interacting with a specific set of our OAuth2-based APIs. For general info about CrowdStrike APIs, see CrowdStrike OAuth2-Based APIs, which covers these topics:

- Details on getting started, such as authentication and API scopes
- Domains used in base URLs by cloud
- Links to our Swagger API specification by cloud

Vulnerability management API overview

The vulnerability management API features several endpoints. Use these endpoints to find and get detailed info about vulnerabilities in your environment and integrate vulnerability management data into your organization's other ticketing or risk management tools. Vulnerabilities are known security risks in an operating system, application, hardware, firmware, or other part of a computing stack. Falcon tracks vulnerabilities by industry-standard frameworks like Common Vulnerabilities and Exposures (CVE). Falcon identifies and gives info about specific vulnerabilities on your hosts using the Falcon sensor.

For more info about managing vulnerabilities in Falcon, see Vulnerability Management Overview.

Required API client scope

To access the vulnerability management API, your API client must be assigned the **vulnerabilities:read** scope. For more info, see API clients.

Validate API data

The Falcon sensor continuously monitors hosts for any changes and reports them as they occur. Depending on the timing of requests, vulnerability management APIs can return values that are different from those shown by the Falcon console or an external source.

There are other factors that can cause differences between API responses and other data sources.

API query syntax

If an API query doesn't exactly match the query used on the **Vulnerabilities** page, the values might differ. When comparing vulnerability management API responses to external data sources, keep in mind that third-party applications might use different criteria when processing vulnerability data. For example, when calculating the number of hosts vulnerable to a CVE, Falcon searches for unique host IDs. Other applications might search for hostnames, which are not unique identifiers. Different machines can share the same hostname, which can lead to inaccurate host counts.

Vulnerability management data retention

Data is retained for different periods of time, depending on the vulnerability status:

- Open vulnerabilities are reported while the host is active.
- Closed vulnerabilities are removed after 45 days.
- Expired vulnerabilities are removed after 3 days. Vulnerabilities on a deleted host or a host that has been inactive for 45 days are assigned the status of **expired**.

Note: Expired vulnerabilities are not included in the Falcon console or reports. They are only visible in API responses.

An external data source might not use the same data retention policy, which can lead to discrepancies with vulnerability management APIs.

Combined endpoints

The combined endpoints deliver a unified, comprehensive view of your vulnerability data with a single request. Use these endpoints for reporting and maintaining a local copy of vulnerability data.

Endpoint	Description
GET /spotlight/combined/vulnerabilities/v1	Get a current snapshot of complete vulnerability instance data. This endpoint consolidates three task-based vulnerability management endpoints into one.

CrowdStrike APIs

Endpoint	Description
GET /spotlight/combined/evaluation-logic/v1	Query and retrieve evaluation logic for Windows and macOS-based products related to a vulnerability. Note: In the details panel of the Vulnerabilities page, evaluation logic is referred to as vulnerability evidence .
GET /spotlight/combined/installed-patches/v1	Retrieve the installation status for Windows patches on managed assets. Query this endpoint to identify assets that require a restart before they're fully patched.

Task-based endpoints

Get specific types of data using separate task-based endpoints. Use these endpoints for refreshing data about a specific entity, such as getting the details for a specific remediation or vulnerability.

Endpoint	Description
GET /spotlight/entities/remediations/v2	Provide one or more remediation IDs to get detailed remediation info.
GET /spotlight/queries/evaluation-logic/v1	Retrieve evaluation logic IDs for test results that substantiate the existence of a vulnerability.
GET /spotlight/entities/evaluation-logic/v1	Provide one or more evaluation logic IDs to get detailed test results that substantiate the existence of a vulnerability.

Recommended best practices

As the volume of vulnerability data in many environments can be quite large, we recommend pulling data once with the combined vulnerabilities endpoint to create a baseline for your environment, followed by subsequent differential pulls. For more info, see [Get vulnerability entities](#).

Important: To ensure the completeness of returned vulnerabilities, by default, vulnerability management API responses are sorted chronologically based on the last updated timestamp. This ensures the completeness of returned vulnerabilities. Alternative sort parameters should only be applied for use cases other than maintaining a replica of vulnerability data.

The changes include vulnerabilities that have been created or closed, as well as any vulnerability that has had a property change, such as status changing from **closed** to **reopened**. We recommend starting with a once-per-day differential data pull and adjusting the frequency as needed to ensure that you can keep up with the changes within your environment.

Note: The above method does not capture changes to remediation details. If you are trying to maintain a local replica of vulnerability data, we recommend using the remediation endpoint to periodically refresh the remediation details or maintain an up-to-date local cache of remediation info. For more info, see [Get remediation details by ID](#).

Tip: If an API request times out, reduce the number of records in your response by including the **limit** parameter in your request. For more info, see [Parameters](#).

Vulnerability entity properties

The vulnerability entity contains various general attributes as well as host, CVE, remediation, and evaluation logic objects.

General vulnerability properties

The following table defines the vulnerability fields included in the **GET /spotlight/combined/vulnerabilities/v1** response.

Note: For some fields, if there's a null value, the field is not included in the response.

Tip: Timestamps are in Coordinated Universal Time (UTC) format.

Field	Nested field 1	Nested field 2	Description
id			Unique system-assigned ID of the vulnerability.
cid			Unique system-generated customer identifier (CID) of the account. In multi-CID environments:

CrowdStrike APIs

Field	Nested field 1	Nested field 2	Description
			- You can filter by both parent and child CIDs. - If you're in a parent CID and leave this filter empty, the response includes data about the parent CID and all its child CIDs. - If you're in a parent CID and use this filter, the response includes data for only the CIDs you filtered by. - If you're in a non-parent CID, this property only shows data for that CID.
aid			Unique agent identifier (AID) of the sensor where the vulnerability was found. For assets without a Falcon sensor installed, this field matches the asset ID field in asset management. For more info, see Asset Management APIs.
vulnerability_id			CVE ID of the vulnerability. If there's no CVE ID, this is the CrowdStrike or third-party ID of the vulnerability. For more info, see Vulnerability identifiers.
data_providers			Array of vulnerability data provider objects.
	provider		Name of the vulnerability data provider.
	scanner_id		ID of the provider scanner that identified the vulnerability.
	scan_id		ID of the network scan that identified the vulnerability.
	rating		Vulnerability score given by the provider.
	scan_time		Timestamp when the vulnerability was most recently identified by the third-party provider.
	ports		Ports on the host where the vulnerability was found by the provider.
created_timestamp			Timestamp when the vulnerability was created in the CrowdStrike cloud.
closed_timestamp			Timestamp when the vulnerability was closed.
updated_timestamp			Timestamp of the most recent update of the vulnerability. The timestamp updates based on changes to any of these vulnerability properties: status remediation evaluation_logic suppression_info cve Note: For third-party provider vulnerabilities, this is the most recent timestamp when a scan identified the vulnerability on the asset.
status			Vulnerability's current status. One of: open, closed, reopen, or expired. Note: Vulnerabilities in the expired status are visible only through the API. They do not appear in the Falcon console or in reports. The expired status alerts you that a vulnerability will be removed within 3 days. For more info, see Vulnerability management data retention.
apps			Array of details about the products associated with the vulnerability.
	vendor_normalized		Vendor of the product associated with the vulnerability.
	product_name_version		Name and version of the product associated with the vulnerability.
	product_name_normalized		Normalized name of the product associated with the vulnerability.
	sub_status		Status of each product associated with the vulnerability. One of: open , closed , or reopen .
	remediation	ids	Remediation IDs associated with the vulnerability and product.
	evaluation_logic	id	Unique system-assigned ID of the vulnerability evaluation logic.
	remediation_info		

CrowdStrike APIs

Field	Nested field 1	Nested field 2	Description
		recommended_id	Remediation ID of the patch or software version that addresses the most number of vulnerabilities, including this one.
		minimum_ID	Remediation ID of the earliest published patch or software version that remediates the vulnerability.
		patch_publication_date	Timestamp when the minimum remediation was first published.
	patch_publication_date		Timestamp when the minimum remediation was first published.
suppression_info			Details about vulnerability suppression rules associated with the vulnerability.
	is_suppressed		True or false field indicating whether the vulnerability is suppressed by a suppression rule or not.
	reason		Reason selected for the vulnerability suppression rule. One of: ACCEPT_RISK , COMPENSATING_CONTROL , or FALSE_POSITIVE .
services			Details about port protocols and processes.
	port		Port on the host where a vulnerability was found by Falcon EASM or a third-party provider.
	transport		Transport methods recognized by Falcon EASM. Note: This field requires a Falcon Exposure Management or Falcon Surface subscription.
	protocol		Network protocols recognized by Falcon EASM. Note: This field requires a Falcon Exposure Management or Falcon Surface subscription.
confidence			Whether the vulnerability has been confirmed: • confirmed: Clear evidence that vulnerable code, misconfiguration, or other artifact associated with the vulnerability was detected on the asset. • confirmed by prior scan: Identified through a network scan performed before vulnerability coverage was published. • potential: Software versions or configurations associated with a vulnerability were detected on the asset, but the available data lacks sufficient detail to prove a confident finding. Note: For more info about confirmed by prior scan, see Continuous Visibility Network Vulnerabilities.

CVE object properties (cve)

The **cve** object is included in the GET `/spotlight/combined/vulnerabilities/v1` response. This table defines the CVE fields.

Tip: Timestamps are in Coordinated Universal Time (UTC) format.

Field	Nested field	Description
id		Common Vulnerabilities and Exposures (CVE) identifier.
base_score		Base score of the CVE: Decimal value between 1 and 10.
severity		Severity of the CVE. One of: CRITICAL , HIGH , MEDIUM , LOW , UNKNOWN , or NONE .
exploit_status		Numeric value of the most severe known exploit. • 0: UNPROVEN • 30: AVAILABLE • 60: EASILY_ACCESSIBLE • 90: ACTIVELY_USED
exprt_rating		ExPRT rating assigned by CrowdStrike's predictive AI rating system. One of: CRITICAL , HIGH , MEDIUM , LOW , or UNKNOWN .

CrowdStrike APIs

Field	Nested field	Description
remediation_level		CVSS remediation level of the vulnerability: • U: Unavailable. There are no remediations available for open instances of the vulnerability. • 0: Official fix. There is at least one remediation available that can address open instances of this vulnerability. Note: Remediations might not be available for every product or product version affected by the vulnerability. If you apply all available remediations and the vulnerability is still detected in products without a remediation, the remediation level changes from 0 to U.
cisa_info		Cybersecurity and Infrastructure Security Agency (CISA) data.
	is_cisa_kev	Whether the vulnerability is listed in the CISA Known Exploited Vulnerabilities (KEV) catalog: true or false .
	due_date	Date before which CISA mandates subject organizations to patch the vulnerability.
spotlight_published_date		Timestamp when coverage was enabled for the vulnerability.
actors		Adversaries associated with the vulnerability.
name		Vulnerability name, if applicable.
type		Vulnerability type: • Vulnerability: A security flaw that can potentially be used by an adversary to gain unauthorized access to a platform or to perform unauthorized actions on a system. All third-party source results have this vulnerability type. • Misconfiguration: A configuration error that an adversary can leverage to gain access to a platform or perform unauthorized actions on a system. • Unsupported software: A product that no longer receives security updates or advisories and presents an unknown risk to a system. Commonly known as end-of-life (EOL) or end-of-support (EOS) products.
cwes		Unique identifier for a vulnerability from the Common Weakness Enumeration (CWE) list. Note: This field requires a Falcon Exposure Management or Falcon Surface subscription.
description		An explanation of the CVE. Note: This field includes an AI-enhanced description for Falcon Exposure Management subscriptions.
original_description		Original explanation of the CVE. Note: This field requires a Falcon Exposure Management subscription.
published_date		Timestamp when the vendor published the CVE.
vendor_advisory		Link to the vendor page where the CVE was disclosed.
references		Array of URLs providing additional information about the CVE.
exploitability_score		Exploitability score of the CVE: Decimal values from 1–4.
impact_score		Impact score of the CVE: Decimal values from 1–6.
vector		Textual representation of the metric values used to score the vulnerability.

Host object properties (host_info)

The **host_info** object is included in the **GET /spotlight/combined/vulnerabilities/v1** response. This table defines the host info fields.

Field	Nested field	Description
hostname		Hostname of the asset.
local_ip		Device's local IP address.
machine_domain		Active Directory domain name.
os_version		Operating system version.
ou		Active directory organizational unit name.
site_name		Active directory site name.

CrowdStrike APIs

Field	Nested field	Description
system_manufacturer		Name of the system manufacturer.
groups		Array of host group details that the host is assigned to.
	id	Unique identifiers of the host groups that the host is assigned to.
	name	Name of the host group that the host is assigned to.
tags		Array of tags assigned to the host.
platform		Operating system platform.
instance_id		Cloud instance ID of the host.
service_provider_account_id		Cloud service provider account ID for the host.
service_provider		Cloud service provider for the host.
instance_state		Cloud instance status. This field is filterable and case-insensitive. Note: The instance status of terminated is not available in this field.
os_build		Operating system build of the asset
product_type_desc		Asset type: Workstation , Domain Controller , or Server .
asset_criticality		Assigned criticality level of the asset: Critical , High , Noncritical , or Unassigned .
asset_roles		Roles assigned to the host in asset management. Note: Asset roles are only available with Falcon Exposure Management subscriptions.
internet_exposure		Indicates if the asset is exposed to the internet: Yes , No , or Pending .
third_party_asset_ids		Asset IDs assigned to the host by third-party providers in the format: {data_provider}: {data_provider_asset_id}
managed_by		Indicates if the asset has the Falcon sensor installed: Falcon sensor or Unmanaged .
confidence_label		Level of confidence that the asset is associated with your organization as determined by Falcon EASM: • High • Medium • Low • Unknown Tip: For more info, see External asset confidence levels. Note: This field requires a Falcon Exposure Management or Falcon Surface subscription.
subsidiaries		Subsidiary within your organization associated with the host. Note: This field requires a Falcon Exposure Management or Falcon Surface subscription.
host_last_seen_timestamp		Timestamp of asset's most recent connection to the CrowdStrike cloud. A value is only provided for hosts that have been offline for 3 or more days. The timestamp value does not change until the host comes back online, at which point the value resets to null.
has_run_container		Whether the host is running Kubernetes containers: true or false .

Remediation object properties (remediation)

The **remediation** object is included in the **GET /spotlight/combined/vulnerabilities/v1** response. This table defines the remediation fields.

Tip: Timestamps are in Coordinated Universal Time (UTC) format.

Field	Nested field	Description
ids		Unique IDs of remediations associated with the vulnerability.
entities		Array of remediation objects.
	id	Unique ID of the remediation.
	reference	Relevant reference for the remediation that can be used to get additional details for the remediation. For example, a KB number that needs to be installed for a KB_SECURITY_UPDATE.

CrowdStrike APIs

Field	Nested field	Description
	title	Short description of the remediation.
	action	Expanded description of the remediation.
	link	Link to the remediation page for the vendor.
	vendor_url	Link to the vendor advisory. Note: This field is populated if there are extra steps that are required to complete the remediation.
	recommendation_type	Classification of the remediation: minimum or recommended Tip: Minimum remediations can help address vulnerable assets that aren't compatible with the recommended remediations.
	patch_publication_date	Timestamp when the remediation was first published.

Vulnerability evaluation logic properties (evaluation_logic)

These fields are available for the **evaluation_logic** parameter for products related to a vulnerability.

Note: Evaluation logic is only available for vulnerabilities with a status of **open** or **reopen**.

Tip: Timestamps are in Coordinated Universal Time (UTC) format.

Field	Nested field 1	Nested field 2	Description
id			Unique system-assigned ID of the vulnerability evaluation logic.
cid			Unique system-generated customer identifier (CID) of the account.
aid			Identifier of the asset where the vulnerability was found. If you have access to asset management, this field matches the asset ID field. For more info, see Asset Management APIs.
scanner_id			For third-party vulnerability data providers, the ID of the scanner used to identify the vulnerability.
data_provider			Name of the vulnerability data provider associated with the evaluation logic.
created_timestamp			Timestamp when the evaluation logic evaluation was first performed.
updated_timestamp			Timestamp of the most recent update of evaluation logic.
logic			Evaluation tests used to assess the vulnerability.
	id		Unique system-assigned ID of the vulnerability evaluation test. Note: This attribute is not included in exported reports.
	title		Description of the evaluation test. For example: Check if the version of Java Runtime Environment 64 bit is less than 1.9.0 (9.0.0)
	type		Type of evaluation test: inventory: Typically checks if a product is installed or not. vulnerability: Checks for specific product versions or files related to the product. external: Evaluated by third-party vulnerability data provider. Note: Inventory evaluation tests are labeled as notable in the Falcon console.
	negate		In most cases, if an evaluation fulfills the test title, the test result is positive in support of the vulnerability's existence. For example, if the title is "Check if the version of application.exe is less than 3.1" and the version on the evaluated host is 3.0, the test result is positive. When a test is negated, the opposite is true. If a host does not fulfill the test title, the test result is positive evidence that the vulnerability exists. For example, if a negated test title is "Check if UEFI is enabled" and UEFI is disabled on the evaluated host, it's a positive test result in support of the vulnerability's existence. Possible values:

CrowdStrike APIs

Field	Nested field 1	Nested field 2	Description
			• true: Test is negated. If the host does not meet the threshold in the test title, the test result is positive. • false: Test is not negated. If the host meets the threshold in the test title, the test result is positive.
	existence_check		Testing parameters that must match with items found on the asset to validate the vulnerability. Possible values: • at_least_one_exists • all_exist • any_exist • none_exist • only_one_exists
	comparison_check		Number of state comparison checks required to validate the vulnerability. Possible values: • all • at least one • none satisfy • only one
	determined_by_comparison		Indicates whether comparison testing was performed: • true: Comparison and existence checks • false: Existence check only
	comparisons		Tests performed on items collected from the host: • state_operator: Describes how the state_comparisons are evaluated. For AND, the item must pass all state comparison tests. For OR, the item must pass any state comparison test. • state_comparisons: Array of state comparison tests. Each test includes one or more entity comparison tests. • entity_operators: If entity comparisons are included, describes how the entity comparisons are evaluated. For AND, the item must pass all entity comparison tests. For OR, the item must pass any entity comparison test. • entity_comparison: Array of entity comparison tests • actual_value_field: A field from the items attribute used in the comparison test. • expected_value: Value used to compare with actual_value_field. • operation: Type of comparison used in the test. • value_datatype: Data type used in the comparison. For example: <pre>"entity_comparisons": [{ actual_value_field": "version", expected_value": "10.0.17763.4010", operation": "less than", value_datatype": "version" }]</pre> This entity comparison checks the version value in the items attribute. If the value is less than 10.0.17763.4010, then it passes the comparison test, which is evidence of the vulnerability.
	items		Array of objects collected from the host involved in the evaluation logic test. Each item includes these attributes: • comparison_result: If determined_by_comparison is true, then this value is true or false. If determined_by_comparison is false, then this value is not evaluated. • item_type: Item from host that was evaluated, such as registry_item or file_item. Additional attributes depend on the item type. Typically, the file path of the item is defined by one of these attributes. For example, for registry_item, the file path is included in the key attribute.

CrowdStrike APIs

Field	Nested field 1	Nested field 2	Description
	description		Description of the evaluation logic item.
simplified_logic			Array of evaluation tests that identify a vulnerability parsed in a human-readable format.
	id		Unique identifier of the simplified evaluation.
	title		Description of the evaluation test.
	negate		Indicates if the evaluation logic described in the title is inverted. In most cases, if a test result fulfills the title, it's positive evidence in support of a vulnerability's existence. For example, if the title is "Check if the version of application.exe is less than 3.1" and the version on the evaluated asset is 3.0, the test result is positive. When a test is negated, the inverse is true. If an evaluation does not fulfill the title, it's positive evidence that the vulnerability exists. For example, if a negated test title is "Check if UEFI is enabled" and UEFI is disabled on the evaluated asset, it's a positive result in support of the vulnerability's existence.
	checks		Checks performed for the test.
	match_required		Threshold of positive checks required for a positive test result.
	found		Evidence gathered from the asset that's evaluated in checks.
	data		Evidence sources.
asset_info			Contains asset IDs associated with the asset. Multiple asset IDs might occur if third-party vulnerability evaluation records exist for the same physical asset.
	entities_matched		An array of asset IDs that includes the aid , as well as any asset IDs of records for the same physical asset.
		asset_id	Asset ID assigned to the asset. This field is filterable.

Installed patches properties (installed_patches)

In GET `/spotlight/combined/installed-patches/v1` endpoint responses, these fields are included.

Field 1	Field 2	Definition
aid		Unique identifier for the asset.
hostname		Hostname of the asset.
reboot_required		Indicates whether the asset requires a reboot to complete the installation of pending patches. Possible values are true or false .
device_type		Asset type: Workstation , Domain Controller , or Server .
active_patches		Number of installed patches that are active on the asset.
pending_patches		Number of installed patches on the asset that require a reboot to become active.
last_patch_confirmed		Timestamp when the most recent patch was installed on the asset. Timestamps are in Coordinated Universal Time (UTC) format.
installed_patches		Array of installed patch details.
	id	Unique identifier for the installed patch.
	status	Status of the installed patch: active or pending.
	published_date	When the patch was published by the vendor.
	type	Classification of the installed patch, such as Security Update or Critical Update .
	description	Brief description of the patch.

Field 1	Field 2	Definition
	<code>detail_url</code>	Link to the related Microsoft Knowledge Base article.

Filter vulnerability management APIs

In certain requests, you can pass Falcon Query Language (FQL) filters to limit the vulnerabilities returned to specific properties. FQL filters follow a standard syntax of **filter=** followed by the filter name and a colon, appended with a value. Each value must be enclosed in single quotes and placed immediately after the colon with no space. For more info, see [Filtering with FQL](#).

Syntax: `filter=<parameter_name>:'<value>'`

Example: `filter=cve.severity:'LOW'`

Vulnerability management API filter parameters

The following table lists available API filters with examples.

Name	Description	Example
<code>aid</code>	Unique agent identifier (AID) of the sensor where the vulnerability was found. For assets without a Falcon sensor installed, this field matches the asset ID field in asset management. For more info, see Asset Management APIs .	Get vulnerabilities for a specific AID: <code>filter=aid:'abcde6b9a3427d8c4a1af416424d6231'</code>
<code>apps.remediation.ids</code>	Unique identifier of a remediation. This filter supports multiple values and negation.	Get the vulnerability ID for a specific remediation ID: <code>filter=apps.remediation.ids:'7bba2e543744a92962be7afeb6484858'</code> Get vulnerabilities for multiple remediation IDs: <code>filter=apps.remediation.ids:['ID1','ID2','ID3']</code>
<code>cid</code>	Unique system-generated customer identifier (CID) of the account. In multi-CID environments: - You can filter by both parent and child CIDs. - If you're in a parent CID and leave this filter empty, the response includes data about the parent CID and all its child CIDs. - If you're in a parent CID and use this filter, the response includes data for only the CIDs you filtered by. - If you're in a non-parent CID, this property only shows data for that CID.	Get vulnerabilities for a specific CID: <code>filter=cid:'0123456789ABCDEF GHIJKLMNOPQRSTU V'</code>
<code>closed_timestamp</code>	Date and time a vulnerability was set to a status of CLOSED	Get vulnerabilities that were marked as closed after June 25, 2021 at 10:32 UTC: <code>filter=closed_timestamp:>'2021-06-25T10:32'</code> Get vulnerabilities that were marked as closed before October 18, 2021: <code>filter=closed_timestamp:<'2021-10-18'</code>
<code>confidence</code>	Whether or not the vulnerability has been confirmed:	Get vulnerabilities with a potential confidence level:

CrowdStrike APIs

Name	Description	Example
	- confirmed - potential	<code>filter=confidence:<'potential'</code>
<code>created_timestamp</code>	Date and time when this vulnerability was found in your environment. Tip: Use this filter to get only the vulnerabilities created after the timestamp you last pulled data on.	Get vulnerabilities created before September 30, 2021 at 13:22 UTC: <code>filter=created_timestamp:<'2021-09-25T13:22'</code> Get vulnerabilities created after February 12, 2021: <code>filter=created_timestamp:>'2021-02-12'</code>
<code>cve.base_score</code>	Base score of the CVE: Decimal value between 1 and 10.	Get vulnerabilities with CVE base scores greater than 7.5: <code>filter=cve.base_score:>'7.5'</code>
<code>cve.cwes</code>	Unique identifier for a vulnerability from the Common Weakness Enumeration (CWE) list	<code>filter=cve.cwes:>['CWE-787','CWE-699']</code>
<code>cve.exploit_status</code>	Numeric value of the most severe known exploit. This filter supports multiple values and negation. Possible values: 0 : Unproven. No known exploits. 30 : Available - Medium. At least one known piece of code developed to take advantage of the vulnerability. 60 : Easily accessible - High. An exploit that is packaged and easily available in an exploit framework. 90 : Actively used - Critical. An exploit that has been used in at least one attack.	Get vulnerabilities with an exploit status of 60: <code>filter=cve.exploit_status:'60'</code> Get vulnerabilities with an exploit status of 30, 60, or 90: <code>filter=cve.exploit_status:!'0'</code> or <code>filter=cve.exploit_status:['30','60','90']</code>
<code>cve.exprt_rating</code>	ExPRT rating assigned by CrowdStrike's predictive AI rating system. The value must be entered in all caps. This filter supports multiple values and negation. Possible values:	Get vulnerabilities with an ExPRT rating of high: <code>filter=cve.exprt_rating:'HIGH'</code> Get vulnerabilities with an ExPRT rating of high or critical: <code>filter=cve.exprt_rating:['HIGH','CRITICAL']</code> Get vulnerabilities with any ExPRT rating other than unknown: <code>filter=cve.exprt_rating:!'UNKNOWN'</code>

CrowdStrike APIs

Name	Description	Example
	UNKNOWN : The CVE Metadata lacks some required properties or a technical/temporary problem. LOW : Score is < ~50% Percentile OR it does not have an Exploit prediction. MEDIUM : Score is > ~50% percentile. HIGH : Exploit Status = Easily Accessible Exploit OR it fits in the ~ [80,95]% ExPRT Scores. CRITICAL : Exploit Status = Actively Used Exploit OR it fits in the top 5% ExpRT Scores.	
cve.id Tip: For case-insensitive filtering, add .insensitive to the field name in the filter parameters.	Unique identifier for a vulnerability as cataloged in the National Vulnerability Database (NVD). This filter supports multiple values and negation. Note: All values must be enclosed in brackets, including single values.	Get vulnerabilities with a specific single CVE ID: filter=cve.id:['CVE-2022-1234'] Get vulnerabilities for multiple CVE IDs: filter=cve.id:['CVE-2022-1234','CVE-2023-1234'] Get vulnerabilities that do not contain either of 2 specific CVE IDs: filter=cve.id:['CVE-2022-1234','CVE-2023-1234']
cve.is_cisa_kev	Filter for vulnerabilities that are in the CISA Known Exploited Vulnerabilities (KEV) catalog: true or false This filter supports negation.	Get vulnerabilities that are in the CISA KEV catalog: filter=cve.is_cisa_kev:true
cve.remediation_level	CVSS remediation level of the vulnerability. This filter supports multiple values and negation.	Get vulnerabilities with an official fix: filter=cve.remediation_level:'0' Get vulnerabilities no available fix: filter=cve.remediation_level:'U'
cve.severity	CVSS severity rating of the vulnerability. The value must be entered in all caps. This filter supports multiple values and negation. Possible values:	Get vulnerabilities with a CVE severity of LOW: filter=cve.severity:'LOW' Get vulnerabilities with any CVE severity but UNKNOWN: filter=cve.severity:['UNKNOWN'] Get vulnerabilities with a CVE severity of LOW and MEDIUM: filter=cve.severity:['LOW','MEDIUM']

CrowdStrike APIs

Name	Description	Example
	• UNKNOWN : A severity that's not defined • NONE : No severity provided • LOW : A low severity computed out of the base score • MEDIUM : A medium severity computed out of the base score • HIGH : A high severity computed out of the base score • CRITICAL : a critical severity computed out of the base score	
cve.types	Vulnerability type: • Vulnerability • Misconfiguration • Unsupported software	filter=cve.types:! 'Misconfiguration'
data_providers.ports	Ports on the host where the vulnerability was found by the third-party provider	Get vulnerabilities found on port 53: data_providers.ports: '53' Get vulnerabilities found on any port: filter=data_providers.ports:! '0'
data_providers.provider	Name of the data provider	Get vulnerabilities for a specific third-party provider: filter=data_providers.provider: '{provider name}'
data_providers.rating	Possible values: • UNKNOWN : A severity that's not defined • NONE : No severity provided • LOW : A low severity computed out of the base score • MEDIUM : A medium severity computed out of the base score • HIGH : A high severity computed out of the base score • CRITICAL : a critical severity computed out of the base score	Get vulnerabilities with a third-party rating of CRITICAL: filter=data_providers.rating: 'CRITICAL'
data_providers.scan_time	UTC date and time when the vulnerability was most recently identified by the third-party provider	Get vulnerabilities scanned by a third-party provider after August 3, 2023: filter=data_providers.scan_time:> '023-08-03'

CrowdStrike APIs

Name	Description	Example
<code>data_providers.scanner_id</code>	ID of the third-party scanner that identified the vulnerability	Get vulnerabilities found by a specific scanner: <code>filter=data_providers.scanner_id:'{scanner id}'</code>
<code>host_info.asset_criticality</code>	Assigned criticality level of the asset Possible values: • <code>Critical</code> • <code>High</code> • <code>Noncritical</code> • <code>Unassigned</code>	Get vulnerabilities on hosts with high and critical levels of asset criticality: <code>filter=host_info.asset_criticality:['Critical','High']</code> Get vulnerabilities on hosts without an assigned asset criticality level: <code>filter=host_info.asset_criticality:! 'Unassigned'</code>
<code>host_info.groups</code>	Unique system-assigned ID of a host group. Retrieve the host group ID from Host Group APIs. For more info, see Host and Host Group Management APIs. This filter supports multiple values and negation. Note: All values must be enclosed in brackets, including single values.	Get vulnerabilities on hosts in a specific host group ID: <code>filter=host_info.groups:['03f0b54af2692e99c4cec945818fbef7']</code> Get vulnerabilities on hosts in all host groups except a specific host group ID: <code>filter=host_info.groups:! ['03f0b54af2692e99c4cec945818fbef7']</code> Get vulnerabilities on hosts in multiple host group IDs: <code>filter=host_info.groups:['03f0b54af2692e99c4cec945818fbef7' , '1676624bb307f5054406a3c343d40212']</code>
<code>host_info.has_run_container</code>	Whether or not the host is running Kubernetes containers: <code>true</code> or <code>false</code>	Get vulnerabilities on hosts running Kubernetes containers: <code>filter=host_info.has_run_container:'true'</code>
<code>host_info.instance_state</code>	Cloud instance status. Note: This filter is case insensitive.	Get vulnerabilities on running cloud instances: <code>filter=host_info.instance_state:'Running'</code>
<code>host_info.internet_exposure</code>	Whether or not the asset is internet-facing: • <code>Yes</code> • <code>No</code> • <code>Pending</code>	Get vulnerabilities on internet-exposed hosts: <code>filter=host_info.internet_exposure:'Yes'</code>
<code>host_info.managed_by</code>	Indicates if the asset has the Falcon sensor installed: • <code>Falcon sensor</code> • <code>Unmanaged</code> This filter supports multiple values and negation.	Get vulnerabilities on assets without a Falcon sensor installed: <code>filter=host_info.managed_by:'Unmanaged'</code>
<code>host_info.platform_name</code>	Operating system platform. This filter supports negation. Possible values: • <code>Windows</code> • <code>Mac</code> • <code>Linux</code>	Get Windows OS vulnerabilities: <code>filter=host_info.platform_name:'Windows'</code> Get Windows OS and macOS vulnerabilities: <code>filter=host_info.platform_name:! 'Linux'</code>
<code>host_info.product_type_desc</code>	Type of host a sensor is running on. This filter supports multiple	Get vulnerabilities on workstation hosts: <code>filter=host_info.product_type_desc:'Workstation'</code>

CrowdStrike APIs

Name	Description	Example
Tip: For case-insensitive filtering, add .insensitive to the field name in the filter parameters.	values and negation. Enter values as shown with the first letter capitalized. Possible values: • Workstation • Server • Domain Controller	Get vulnerabilities on server and domain controller hosts: filter=host_info.product_type_desc:!'Workstation' or filter=host_info.product_type_desc:['Domain Controller','Server']
host_info.tags	Name of a tag assigned to a host. Retrieve tags from Host Tags APIs. For more info, see Host and Host Group Management APIs. This filter supports multiple values and negation. Note: All values must be enclosed in brackets, including single values.	Get vulnerabilities on hosts tagged with “ephemeral”: filter=host_info.tags:['ephemeral'] Get vulnerabilities on hosts with any tag but “search” or “ephemeral”: filter=host_info.tags:!['search','ephemeral'] Get vulnerabilities on hosts tagged with “workstation” or “main”: filter=host_info.tags:['workstation','main']
host_info.third_party_asset_ids	Asset IDs assigned to the host by third-party providers in the format: {data_provider}: {data_provider_asset_id} This filter supports multiple values and negation.	Get vulnerabilities for a specific third-party asset: filter=host_info.third_party_asset_ids:'{data_provider}:{data_provider_asset_id}'
last_seen_within	Filter for vulnerabilities based on the number of days since a host last connected to Falcon. Enter a numeric value from 3 to 45 to indicate the number of days you want to look back. All active hosts seen up to the specified number of days are returned with a host_last_seen_timestamp response field populated as follows: • A UTC timestamp of the most recent connection displays for hosts that were last seen online more than 3 days ago • Null for hosts that have been online in the last 3 days Possible values: • Integer, from 3–45 Note: Values less than 3 and greater than 45 are not supported and will result in an error.	Get vulnerabilities for hosts that last connected to Falcon within the last 10 days: filter=last_seen_within:'10' The host_last_seen_timestamp in the response shows: • A timestamp for last host activity detected on days 4-10 • Null for last host activity detected on days 1-3
services.port	Port on the host where a vulnerability was found by Falcon EASM or a third-party provider	filter=services.port:'443'

CrowdStrike APIs

Name	Description	Example
<code>services.protocol</code>	Network protocols recognized by Falcon EASM	<code>filter=services.protocol:'pop3'</code>
<code>services.transport</code>	Transport methods recognized by Falcon EASM	<code>filter=services.transport:'tcp'</code>
<code>status</code>	Status of a vulnerability. The value must be entered in all lowercase letters. This filter supports multiple values and negation. Possible values: open: Vulnerabilities that are currently open. A vulnerability is automatically assigned the open status upon creation. closed: Vulnerabilities that are closed. You can close a vulnerability from the open or reopen status. reopen: Vulnerabilities that are currently reopened after previously being closed. expired: Vulnerabilities on decommissioned hosts that are set to be deleted. The expired status appears 3 days before a vulnerability is deleted from the system. Note that vulnerabilities in the expired status are visible only through the API. They do not appear in the Falcon console or in reports.	Get vulnerabilities with a status of open: <code>filter=status:'open'</code> Get vulnerabilities with any status except closed: <code>filter=status:!'closed'</code> Get vulnerabilities with a status of open or reopen: <code>filter=status:['open','reopen']</code> or <code>filter=status:!'closed','expired']</code>
<code>suppression_info.is_suppressed</code>	Indicates if the vulnerability is suppressed by a suppression rule or not	Get suppressed vulnerabilities: <code>filter=suppression_info.is_suppressed:true</code>
<code>suppression_info.reason</code>	Attribute assigned to a suppression rule. One of ACCEPT_RISK, COMPENSATING_CONTROL, or FALSE_POSITIVE. This filter supports multiple values and negation. Note: All values must be enclosed in brackets, including single values.	Get suppressed vulnerabilities where the reason for the rule is "accept risk": <code>filter=suppression_info.reason:['ACCEPT_RISK']</code> Get suppressed vulnerabilities where the reason for the rule is anything except "false positive": <code>filter=suppression_info.reason:!'FALSE_POSITIVE']</code> Get suppressed vulnerabilities where the reason for the rule is "compensating control" or "false positive": <code>filter=suppression_info.reason:['COMPENSATING_CONTROL','FALSE_POSITIVE']</code>
<code>updated_timestamp</code>	UTC date and time of the last update made on a vulnerability	Get vulnerabilities that were last updated before October 20, 2021 at 10:36 PM UTC: <code>filter=updated_timestamp:<'2021-10-20T22:36'</code> Get vulnerabilities that were last updated after September 15, 2021: <code>filter=updated_timestamp:>'2021-09-15'</code>

CrowdStrike APIs

Name	Description	Example
vulnerability_id Tip: For case-insensitive filtering, add .insensitive to the field name in the filter parameters.	CVE ID of the vulnerability. If there's no CVE ID, this is the CrowdStrike or third-party ID of the vulnerability For more info, see Asset Management APIs. This filter supports multiple values and negation.	Get vulnerabilities with a specific single CVE ID: filter=vulnerability_id:['CVE-2022-1234'] Get vulnerabilities for multiple CVE IDs: filter=vulnerability_id:['CVE-2022-1234','CVE-2023-4321'] Get vulnerabilities that do not contain either of 2 specific CVE IDs: filter=vulnerability_id:['CVE-2022-1234','CVE-2023-4321']

Sort vulnerability management APIs

The **sort** parameter defines criteria for ordering the result set in **GET** requests. This field uses a standard list of enum values in ascending and descending order. Ascending order arranges vulnerabilities with the oldest timestamp at the top of the list, while descending places the vulnerability with the most recent timestamp at the top. You can use no more than one **sort** value per request. For more info, see Sorting with FQL.

Vulnerability management API sort parameters

Parameter	Description and Example
created_timestamp.asc created_timestamp.desc	Lists vulnerabilities in ascending or descending order by the created_timestamp field sort=created_timestamp.asc
closed_timestamp.asc closed_timestamp.desc	Lists vulnerabilities with a closed status in ascending or descending order by the closed_timestamp field sort=closed_timestamp.asc
updated_timestamp.asc updated_timestamp.desc	Lists vulnerabilities in ascending or descending order by the updated_timestamp field sort=updated_timestamp.asc

HTTP response codes

The vulnerability management API uses the HTTP status codes below to indicate the success or failure of API requests.

HTTP code	Description
200 OK	The request was completed without any issues or errors.
400 Bad Request	This error can occur when a filter or sort parameter is invalid or improperly formatted, such as an extra space or the use of quotes. It can also occur if a filter is required and there isn't one in your request. Check your request parameters and resend it.
401 Unauthorized	The OAuth2 access token is missing or invalid. Verify your API client ID and secret and send your request again.
403 Forbidden	Your access token does not have permission to perform the request. Verify that your API client is assigned the vulnerabilities:read scope and that your organization has the appropriate subscription.
404 Not found Note: This message displays with a 200 OK header and the 404 code under errors in the response body.	An invalid ID is in the request or there are too many records in the response. Verify the IDs and resend the request. or Your after pagination token has expired. Tokens expire 120 seconds after a call is made.

HTTP code	Description
	Tip: Reduce the number of records in your response by including the limit parameter in your request. For more info, see Parameters .
429 Too Many Requests	The allowed rate limit has been reached.
500 Internal Server Error	The server encountered an unexpected error that prevented your request from being completed.

Use vulnerability management API endpoints

Get vulnerability entities

Get complete vulnerability instance data, including remediation, host, and CVE details. This endpoint combines three vulnerability management endpoints to provide filtering, querying, and data gathering in one. Among other purposes, this endpoint is especially useful for establishing a baseline and staying up to date with changes.

To run this request, you must provide at least one FQL filter in the query string. Successful requests return an HTTP 200 code and an array of vulnerability entities that match the query criteria.

Endpoint

GET `/spotlight/combined/vulnerabilities/v1`

Parameters

Each request requires at least one **filter** parameter. Join multiple filters with an encoded `+`. Use the `&` operator between multiple parameters.

Name	In	Type	Description
filter <i>required</i>	query	string	FQL filter expression used to limit the results. For more info, see Vulnerability management API filter parameters . Filter fields include:

CrowdStrike APIs

Name	In	Type	Description
			• aid • apps.remediation.ids • closed_timestamp • confidence • created_timestamp • cve_cwes • cve.exploit_status • cve.exprt_rating • cve.id • cve.is_cisa_kev • cve.remediation_level • cve.severity • cve.types • data_providers.ports • data_providers.provider • data_providers.rating • data_providers.scan_time • data_providers.scanner_id • host_info.asset_criticality • host_info.groups • host_info.internet_exposure • host_info.managed_by • host_info.platform_name • host_info.product_type_desc • host_info.tags • host_info.third_party_asset_ids • last_seen_within • services.port • services.protocol • services.transport • status • suppression_info.is_suppressed • suppression_info.reason • updated_timestamp • vulnerability_id
facet <i>optional</i>	query	string	Type of data to be returned for each vulnerability entity. The facet filter allows you to limit the response to just the information you want. For example, the CVE description and severity are the same for every instance of that CVE, and you might prefer to cache a copy of that information rather than have it included. Possible values: • host_info • remediation • cve • evaluation_logic Note: Requests that do not include the cve or evaluation_logic facets still return the CVE and evaluation_logic IDs in the response.
limit <i>optional</i>	query	integer	Maximum number of items to return: 1-5000. Default is 100. Use with the after parameter to manage pagination of results.
after <i>optional</i>	query	string	Token used with the limit parameter to manage pagination of results. On your first request, don't provide an after token. On subsequent requests, provide the after token from the previous response to continue from that place in the results. Tokens expire 120 seconds after a call is made.
sort <i>optional</i>	query	string	Property used to sort the results. For more info, see Vulnerability management API sort parameters. Available sort parameters: • created_timestamp • closed_timestamp • updated_timestamp

Example request

Get vulnerabilities that meet these conditions:

- "Open" status
- "High" CVE severity level
- Include "host_info", "cve", and "remediation" facets

The response returns up to two matching vulnerability entities with complete host, CVE, and remediation details, sorted in descending order by created timestamp.

```
curl -X GET "https://api.crowdstrike.com/spotlight/combined/vulnerabilities/v1?
filter=status:'open'+cve.severity:'HIGH'&facet=host_info&facet=cve&facet=remediation&sort=created_timestamp.desc" \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer eyJhbGciOi..xYg1NNI'
```

Example response

```
{
  "meta": {
    "query_time": 0.054128435,
    "powered_by": "spapi",
    "trace_id": "1446bcxxxba7747a4ed"
  },
  "resources": [
    {
      "id": "280f4d789bcexxxxxxxxx9abcc3811914f",
      "cid": "0123456789ABCDEFGHIJKLMN0PQRSTUW-WX",
      "aid": "280f4d...2a7f7bbd",
      "vulnerability_id": "CVE-2025-26633",
      "data_providers": [
        {
          "provider": "Falcon sensor"
        }
      ],
      "created_timestamp": "2025-06-03T00:38:46Z",
      "updated_timestamp": "2025-06-06T00:10:34Z",
      "status": "open",
      "apps": [
        {
          "vendor_normalized": "Microsoft",
          "product_name_version": "Windows Server 2012 R2",
          "product_name_normalized": "Windows Server 2012 R2",
          "sub_status": "open",
          "remediation": {
            "ids": [
              "91b4ee1abe763150a74150dfddf93840"
            ]
          },
          "evaluation_logic": {
            "id": "9b022daf26493769863d5a22be528b9b"
          },
          "remediation_info": {
            "recommended_id": "91b4ee1abe763150a74150dfddf93840",
            "minimum_id": "ec48482667043f9e9578742143ed29bf",
            "patch_publication_date": "2025-03-11T00:00:00Z"
          },
          "patch_publication_date": "2025-03-11T00:00:00Z"
        }
      ],
      "suppression_info": {
        "is_suppressed": false
      },
      "confidence": "confirmed",
      "app": {
        "vendor_normalized": "Microsoft",
        "product_name_version": "Windows Server 2012 R2",
        "product_name_normalized": "Windows Server 2012 R2"
      },
      "cve": {
        "id": "CVE-2025-26633",
        "base_score": 7,
        "severity": "HIGH",
        "exploit_status": 90,
        "exprt_rating": "CRITICAL",
        "remediation_level": "0",
        "cisa_info": {
          "is_cisa_key": true,
          "due_date": "2025-04-01T00:00:00Z"
        }
      }
    }
  ]
}
```

```

"spotlight_published_date": "2025-03-12T17:23:00Z",
"name": "MSC EvilTwin",
"types": [
  "Vulnerability"
],
"cwes": [
  ""
],
"original_description": "Improper neutralization in Microsoft Management Console allows an unauthorized attacker to bypass a security feature locally.\n",
"description": "Summary\n\n\nCVE-2025-26633 is a security feature bypass vulnerability (CWE-1023) in Microsoft Management Console due to improper neutralization of input. This vulnerability allows an attacker to bypass security features when a user is tricked into performing specific actions, potentially leading to unauthorized access with high confidentiality, integrity, and availability impacts on Windows workstations and servers.\n\n\nExploitability\n\n\n\nLocal exploitation requires user interaction\n\n\nNo public exploit code has been identified\n\n\n\nAttack Requirements\n\n\n\n\nAttacker must have local access to the target system\n\n\nRequires user interaction to open or interact with malicious content\n\n\nExploitation requires high attack complexity, suggesting specific conditions must be met for successful exploitation\n\n\n\nAffected Products\n\n\n\n\nMicrosoft Management Console (version unknown)\n\n\nMicrosoft Windows (version unknown)\n\n\n\nMitigations\n\n\n\n\nReview any recommended remediations",
"published_date": "2025-03-11T07:00:00Z",
"vendor_advisory": [
  "https://msrc.microsoft.com/update-guide/en-us/vulnerability/CVE-2025-26633",
  "https://msrc.microsoft.com/update-guide/vulnerability/CVE-2025-26633"
],
"references": [
  "https://www.vicarius.io/vsociety/posts/cve-2025-26633-security-feature-bypass-in-microsoft-management-console-detection-script",
  "https://www.vicarius.io/vsociety/posts/cve-2025-26633-security-feature-bypass-in-microsoft-management-console-mitigation-script"
],
"exploitability_score": 1,
"impact_score": 5.9,
"vector": "CVSS:3.1/AV:L/AC:H/PR:N/UI:R/S:U/C:H/I:H/A:H"
},
"host_info": {
  "hostname": "CsFlows_win_280f4d789bce47a28e3769052a7f7bbd",
  "local_ip": "222.116.81.67",
  "machine_domain": "nelsonosborn.com",
  "os_version": "Windows 10",
  "ou": "chase79",
  "site_name": "desktop-66.maxwell.org",
  "system_manufacturer": "CsFlows System Manufacturer Inc",
  "groups": [
    {
      "id": "7023064081fa41578f00c5f6f8aaeba0",
      "name": "CsFlows_win"
    }
  ],
  "tags": [
    "SensorGroupingTags/main/tags",
    "SensorGroupingTags/wp-content/explore"
  ],
  "platform": "Windows",
  "os_build": "17134",
  "product_type_desc": "Workstation",
  "asset_criticality": "Unassigned",
  "internet_exposure": "No",
  "managed_by": "Falcon sensor",
  "host_last_seen_timestamp": "2025-06-03T00:00:00Z"
},
"remediation": {
  "ids": [
    "ec48482667043f9e9578742143ed29bf",
    "91b4ee1abe763150a74150dfddf93840"
  ],
  "entities": [
    {
      "id": "ec48482667043f9e9578742143ed29bf",
      "reference": "KB5053887",
      "title": "Update Microsoft Windows Server 2012 R2 9600",
      "action": "Install patch for Microsoft Windows Server 2012 R2 9600 (Server): Monthly Rollup KB5053887",
      "link": "https://catalog.update.microsoft.com/v7/site/Search.aspx?q=KB5053887",
      "vendor_url": "",
      "recommendation_type": "minimum",
      "patch_publication_date": "2025-03-11T00:00:00Z"
    },
    {
      "id": "91b4ee1abe763150a74150dfddf93840",
      "reference": "KB5061018",
      "title": "Update Microsoft Windows Server 2012 R2",
      "action": "Install patch for Microsoft Windows Server 2012 R2 9600 (Server): Monthly Rollup KB5061018",
      "link": "https://catalog.update.microsoft.com/v7/site/Search.aspx?q=KB5061018",
      "vendor_url": "",
      "recommendation_type": "recommended",
      "patch_publication_date": "2025-06-10T00:00:00Z"
    }
  ]
}

```

```

    }
  }
}
}

```

Get vulnerability evaluation logic entities

Get details on evaluation logic for products related to a vulnerability.

Endpoint

GET /spotlight/combined/evaluation-logic/v1

Parameters

Each request requires at least one **filter** parameter. Join multiple filters with an encoded **+**. Use the **&** operator between multiple parameters.

Name	In	Type	Description
filter <i>required</i>	query	string	FQL filter expression used to limit the results. For more info, see Vulnerability management API filter parameters . Filter fields include: • aid • created_timestamp • updated_timestamp
limit <i>optional</i>	query	integer	Maximum number of items to return: 1-5000. Default is 100.
after <i>optional</i>	query	string	Use with the limit parameter to manage pagination of results. On first request, don't provide an after token. On subsequent requests, provide the after token from the previous response to continue from that place in the results. Tokens expire 120 seconds after a call is made.
sort <i>optional</i>	query	string	Property used to sort the results. For more info, see Vulnerability management API sort parameters . Available sort parameters: • created_timestamp • updated_timestamp

Example request

Get 2 vulnerability evaluation logic entities that meet these conditions:

- Vulnerability evaluation logic last updated after August 3, 2023

The response returns 2 matching vulnerability evaluation logic entities with host and evaluation test details, sorted in descending order by created timestamp.

```

curl -X GET "https://api.crowdstrike.com/spotlight/combined/evaluation-logic/v1?filter=updated_timestamp:>'2023-08-03'&limit=2&sort=created_timestamp.desc" \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer eyJhbGciOi...xYg1NNI'

```

Example response

```

{
  "meta": {
    "query_time": 0.390429212,
    "pagination": {
      "limit": 2,

```



```

"total": 59982,
"after": "WzE20TE1MzxxxxxxxxxxxxxxxxxxxxxxxxxxxxQ4MGYy0GE00WYwZTc5YzJlIl0="
},
"powered_by": "spapi",
"trace_id": "e5545045-xxxx-xxxx-xxxx-d2e7befc75fa"
},
"resources": [
{
  "id": "23119xxxxxxxxxxxx4477ec729413",
  "cid": "5ddbxxxxxxxxxxxx975f17979a1f",
  "aid": "c118xxxxxxxxxxxx4f168711bbd19",
  "data_provider": "CrowdStrike Spotlight",
  "created_timestamp": "2023-08-08T22:13:25Z",
  "updated_timestamp": "2023-08-08T22:13:25Z",
  "logic": [
    {
      "id": 6275119961371159115,
      "title": "Check if Windows Server 2019 is installed",
      "type": "inventory",
      "description": "",
      "negate": false,
      "existence_check": "at_least_one_exists",
      "comparison_check": "all",
      "determined_by_comparison": true,
      "comparisons": {
        "state_operator": "AND",
        "state_comparisons": [
          {
            "entity_operator": "AND",
            "entity_comparisons": [
              {
                "actual_value_field": "value",
                "expected_value": "^[a-zA-Z0-9\\(\\)\\s\\-]*[Ss][Ee][Rr][Vv][Ee][Rr] 2019[a-zA-Z0-9\\(\\)\\s]*$",
                "operation": "pattern match",
                "value_datatype": "string"
              }
            ]
          }
        ]
      }
    }
  ],
  "items": [
    {
      "comparison_result": "true",
      "hive": "HKEY_LOCAL_MACHINE",
      "item_type": "registry_item",
      "key": "SOFTWARE\\Microsoft\\Windows NT\\CurrentVersion",
      "name": "ProductName",
      "type": "reg_sz",
      "value": [
        "Windows Server 2019 Datacenter"
      ],
      "windows_view": "64_bit"
    }
  ]
},
{
  "id": 14679234622762726800,
  "title": "a version of Windows for the x64 architecture is installed",
  "type": "inventory",
  "description": "",
  "negate": false,
  "existence_check": "at_least_one_exists",
  "comparison_check": "at least one",
  "determined_by_comparison": true,
  "comparisons": {
    "state_operator": "AND",
    "state_comparisons": [
      {
        "entity_operator": "AND",
        "entity_comparisons": [
          {
            "actual_value_field": "value",
            "expected_value": "amd64",
            "operation": "case insensitive equals",
            "value_datatype": "string"
          }
        ]
      }
    ]
  }
},
{
  "comparison_result": "true",
  "hive": "HKEY_LOCAL_MACHINE",

```

```

    "item_type": "registry_item",
    "key": "SYSTEM\\CurrentControlSet\\Control\\Session Manager\\Environment",
    "name": "PROCESSOR_ARCHITECTURE",
    "type": "reg_sz",
    "value": [
      "AMD64"
    ],
    "windows_view": "64_bit"
  }
}
},
{
  "id": 8639067719954618847,
  "title": "Check if the version of netlogon.dll is less than 10.0.17763.4644",
  "type": "vulnerability",
  "description": "",
  "negate": false,
  "existence_check": "at_least_one_exists",
  "comparison_check": "all",
  "determined_by_comparison": true,
  "comparisons": {
    "state_operator": "AND",
    "state_comparisons": [
      {
        "entity_operator": "AND",
        "entity_comparisons": [
          {
            "actual_value_field": "version",
            "expected_value": "10.0.17763.4644",
            "operation": "less than",
            "value_datatype": "version"
          }
        ]
      }
    ]
  }
},
{
  "items": [
    {
      "comparison_result": "true",
      "filename": "netlogon.dll",
      "filepath": "C:\\Windows\\System32\\netlogon.dll",
      "item_type": "file_item",
      "product_name": "Microsoft® Windows® Operating System",
      "product_version": "10.0.17763.4252",
      "version": "10.0.17763.4252",
      "windows_view": "64_bit"
    }
  ]
},
{
  "host_info": {
    "entities_matched": []
  }
},
{
  "id": "bc4603bbxxxxxxxxxxxx9f0e79c2e",
  "cid": "5ddb040xxxxxxxxxxxx5f17979a1f",
  "aid": "c118065xxxxxxxxxxxx8711bbd19",
  "data_provider": "CrowdStrike Spotlight",
  "created_timestamp": "2023-08-08T22:13:24Z",
  "updated_timestamp": "2023-08-08T22:13:24Z",
  "logic": [
    {
      "id": 3616443169600178112,
      "title": "Check if Windows Server 2019 is installed",
      "type": "inventory",
      "description": "",
      "negate": false,
      "existence_check": "at_least_one_exists",
      "comparison_check": "all",
      "determined_by_comparison": true,
      "comparisons": {
        "state_operator": "AND",
        "state_comparisons": [
          {
            "entity_operator": "AND",
            "entity_comparisons": [
              {
                "actual_value_field": "value",
                "expected_value": "^[a-zA-Z0-9\\(\\)\\s\\-]*[Ss][Ee][Rr][Vv][Ee][Rr] 2019[a-zA-Z0-9\\(\\)\\s]*$",
                "operation": "pattern match",
                "value_datatype": "string"
              }
            ]
          }
        ]
      }
    }
  ]
}

```

```

    }
  ],
  "items": [
    {
      "comparison_result": "true",
      "hive": "HKEY_LOCAL_MACHINE",
      "item_type": "registry_item",
      "key": "SOFTWARE\\Microsoft\\Windows NT\\CurrentVersion",
      "name": "ProductName",
      "type": "reg_sz",
      "value": [
        "Windows Server 2019 Datacenter"
      ],
      "windows_view": "64_bit"
    }
  ],
  {
    "id": 3839094395306265009,
    "title": "a version of Windows for the x64 architecture is installed",
    "type": "inventory",
    "description": "",
    "negate": false,
    "existence_check": "at_least_one_exists",
    "comparison_check": "at least one",
    "determined_by_comparison": true,
    "comparisons": {
      "state_operator": "AND",
      "state_comparisons": [
        {
          "entity_operator": "AND",
          "entity_comparisons": [
            {
              "actual_value_field": "value",
              "expected_value": "amd64",
              "operation": "case insensitive equals",
              "value_datatype": "string"
            }
          ]
        }
      ]
    }
  ],
  "items": [
    {
      "comparison_result": "true",
      "hive": "HKEY_LOCAL_MACHINE",
      "item_type": "registry_item",
      "key": "SYSTEM\\CurrentControlSet\\Control\\Session Manager\\Environment",
      "name": "PROCESSOR_ARCHITECTURE",
      "type": "reg_sz",
      "value": [
        "AMD64"
      ],
      "windows_view": "64_bit"
    }
  ],
  {
    "id": 10639554875801557792,
    "title": "Check if the version of kerberos.dll is less than 10.0.17763.4644",
    "type": "vulnerability",
    "description": "",
    "negate": false,
    "existence_check": "at_least_one_exists",
    "comparison_check": "all",
    "determined_by_comparison": true,
    "comparisons": {
      "state_operator": "AND",
      "state_comparisons": [
        {
          "entity_operator": "AND",
          "entity_comparisons": [
            {
              "actual_value_field": "version",
              "expected_value": "10.0.17763.4644",
              "operation": "less than",
              "value_datatype": "version"
            }
          ]
        }
      ]
    }
  ],
  "items": [

```

```
{
  "comparison_result": "true",
  "filename": "kerberos.dll",
  "filepath": "C:\\Windows\\System32\\kerberos.dll",
  "item_type": "file_item",
  "product_name": "Microsoft® Windows® Operating System",
  "product_version": "10.0.17763.4252",
  "version": "10.0.17763.4252",
  "windows_view": "64_bit"
}
]
```

Get remediation details by ID

Retrieve remediation details for a specific ID. This request takes one or more remediation IDs returned in **GET /spotlight/combined/vulnerabilities/v1**. Successful requests return an HTTP 200 code and an array of remediation objects for the specified IDs, listed in the order they were provided in the request.

Recommended best practice

CrowdStrike recommends maintaining a local cache for joining and look up purposes, and refreshing this cache infrequently. These values are frequently repeated, and excessive calls to the remediation API can cause you to hit your API rate limit. It's recommended to refresh these remediations every few days.

Endpoint

GET /spotlight/entities/remediations/v2

Parameters

Name	In	Type	Description
ids <i>required</i>	query	string	Unique ID of the remediation. Separate multiple IDs using &. Example: ids=111111&ids=222222 Note: Maximum number of IDs is 400.

Example request

Get the details of 2 remediation IDs.

```
curl -X GET 'https://api.crowdstrike.com/spotlight/entities/remediations/v2?ids=23619c5342xxxxxx0531594531136f&ids=14d2xxxxxx16198e647307c6a2a54' \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer eyJhbGciOi..xYg1NNI'
```

Example response

```
{
  "meta": {
    "query_time": 0.000292109,
    "powered_by": "spapi",
    "trace_id": "940501ef-c431-4b7f-b65f-1bdac8a3fbd"
  },
  "resources": [
    {
      "id": "23619c5342x0531594xxxxxx531136f",
      "reference": "3.0.12",
      "title": "Update VideoLAN VLC Media Player",
    }
  ]
}
```

CrowdStrike APIs

```
{
  "action": "Update Videolan Vlc Media Player to version 3.0.12 or newer",
  "link": ""
},
{
  "id": "14d2ac933036xxxxxx47307c6a2a54",
  "reference": "KB6750043",
  "title": "Update Microsoft Windows Server 2009 R2",
  "action": "Install patch for Microsoft Windows Server 2009 R2 SP1 x64 (Server): Monthly Rollup KB6750043",
  "link": "https://catalog.update.microsoft.com/v7/site/Search.aspx?q=KB6750043"
}
]
```

Get vulnerability evaluation logic IDs by timestamp

Retrieve evaluation logic IDs for products related to a vulnerability.

Endpoint

GET /spotlight/queries/evaluation-logic/v1

Parameters

Each request requires at least one **filter** parameter. Join multiple filters with an encoded **+**. Use the **&** operator between multiple parameters.

Name	In	Type	Description
filter <i>optional</i>	query	string	FQL filter expression used to limit the results. For more info, see Vulnerability management API filter parameters. Filter fields include: aid created_timestamp updated_timestamp
limit <i>optional</i>	query	integer	Maximum number of items to return: 1-5000. Default is 100.
after <i>optional</i>	query	string	Use with the limit parameter to manage pagination of results. On first request, don't provide an after token. On subsequent requests, provide the after token from the previous response to continue from that place in the results. Tokens expire 120 seconds after a call is made.
sort <i>optional</i>	query	string	Property used to sort the results. For more info, see Vulnerability management API sort parameters. Available sort parameters: created_timestamp updated_timestamp

Example request

Get vulnerability evaluation logic IDs filtered by timestamp:

- Vulnerability evaluation logic created after 03/01/2022

The response returns matching vulnerability evaluation logic IDs.

```
curl -X GET "https://api.crowdstrike.com/spotlight/queries/evaluation-logic/v1?filter=created_timestamp:>'2022-03-01'" \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer eyJhbGciOi...xYg1NNI'
```

Example response

```
{
  "meta": {
    "query_time": 0.034870655,
    "pagination": {
      "limit": 100,
      "total": 8,
      "after": "WyIxNWlYyWI50Tc30WQzZGIzYjA4ZmNhYzg2ODQ1MTlmZCJd"
    },
    "powered_by": "spapi",
    "trace_id": "2591c5cb-5fbd-48b5-8e01-0836bfe37942"
  },
  "resources": [
    "f7d305f68fxxx19230db73e017403a",
    "e2e2ec622xxxx15ab1c8803bc3f9a27",
    "c820d1xxxx13168aefc327431a476ed",
    "c09a97dxxxx3f7b86649947b059322f",
    "baf53axxxa31c1a82e5d4a499749e4",
    "6c9ba80fxxx3ad18c011d4cc4148669",
    "230ff55b6xxx75a9ba83031d502e400",
    "15b2ab9xxxx3db3b08fcac8684519fd"
  ]
}
```

Get vulnerability evaluation logic details by ID

Retrieve evaluation logic details for specific evaluation logic IDs.

Endpoint

GET /spotlight/entities/evaluation-logic/v1

Parameters

Name	In	Type	Description
ids <i>required</i>	query	string	Unique evaluation logic ID for the product associated with a vulnerability. Separate multiple IDs using &. Example: ids=111111&ids=222222 Note: Maximum number of IDs is 400.

Example request

Get evaluation logic details for 2 vulnerability evaluation logic entities.

```
curl -X GET 'https://api.crowdstrike.com/spotlight/entities/evaluation-logic/v1?ids=d7c33ae71bd430d0xxxxxb6d3b9653ad&ids=f7d30xxxxx7236e19230db73e017403a'
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer eyJhbGciOi..xYg1NNI'
```

Example response

```
{
  "meta": {
    "query_time": 0.003611339,
    "powered_by": "spapi",
    "trace_id": "e00e4bf8-e6e9-40d2-9d57-13bdb9b07c77"
  },
  "resources": [
    {
      "id": "d7c33ae71bdxxxxx86553b6d3b9653ad",
      "cid": "0123456789ABCDEFGHJKLMNOPQRSTUVWXYZ",
      "aid": "abc123def456ghi789jkl012mno345pq",
      "created_timestamp": "2022-02-23T19:04:03Z",
      "updated_timestamp": "2022-02-23T19:04:03Z",
      "logic": [
        {

```

```

        "id": 4419377731929302500,
        "title": "Check if the version of Mozilla Firefox is less than 97",
        "type": "vulnerability"
    },
    {
        "id": 12507900159687447000,
        "title": "Mozilla Firefox (64 bit) is installed",
        "type": "inventory"
    }
]
},
{
    "id": "f7d305f68fxxxxx19230db73e017403a",
    "cid": "0123456789ABCDEFGHIJKLMNQRSTUUV",
    "aid": "abc123def456ghi789jkl012mno345pq",
    "created_timestamp": "2022-03-02T12:50:25Z",
    "updated_timestamp": "2022-03-02T12:50:25Z",
    "logic": [
        {
            "id": 10091058424124630000,
            "title": "the installed operating system is part of the Microsoft Windows family",
            "type": "inventory"
        },
        {
            "id": 65280237291851250,
            "title": "Check if Windows Server 2019 is installed",
            "type": "inventory"
        },
        {
            "id": 13939724348614779000,
            "title": "a version of Windows for the x64 architecture is installed",
            "type": "inventory"
        },
        {
            "id": 4318554134395734500,
            "title": "Check if the Authenticode signature verification feature is enabled",
            "type": "vulnerability"
        }
    ]
}
]
}
}

```

Get Windows patch details for individual assets

Retrieve the installation status for Windows patches on managed assets.

Endpoint

GET /spotlight/combined/installed-patches/v1

Parameters

Name	In	Type	Description
filter <i>optional</i>	query	string	Filter fields include: • aid • cid • reboot_required • hostname Note: These filters support multiple, comma-separated values: aid , hostname . For example: filter=hostname:['Laptop-ABC', 'Workstation-123'] .
limit <i>optional</i>	query	integer	Maximum number of items to return is 400. Combine with the after parameter to manage pagination of results. Default limit is 100.
after <i>optional</i>	query	string	Maximum number of assets in a response is 400. To retrieve assets that continue beyond the response limit, include the after token from the response in the next query. For example: after=WyIxNWlYxxxxxxxxxxxxxYjA4ZmNhYzg2ODQ1MTlmZCJd Tokens expire 120 seconds after a call is made.
sort <i>optional</i>	query	string	Sort results by hostname . For example: sort=hostname.asc

CrowdStrike APIs

Example request

Get patch installation details for 2 specific assets by aid.

```
curl -X GET "https://api.crowdstrike.com/spotlight/combined/installed-patches/v1?filter=aid:
['c118xxxxxxxxxxxx4f168711bbd19','br45xxxxxxxxxxxx4f16871f834bn']" \-H 'Content-Type: application/json' \-H 'Authorization: Bearer
eyJhbGciOi4uLWY1N1I'
```

Example response

```
{
  "meta": {
    "query_time": 0.113925668,
    "pagination": {
      "limit": 100,
      "total": 2,
      "after": ""
    },
    "powered_by": "spapi",
    "trace_id": "a3113f4fa8004d478de5b981a2cf76ed"
  },
  "resources": [
    {
      "aid": "c118xxxxxxxxxxxx4f168711bbd19",
      "hostname": "SERVER-ABC",
      "reboot_required": true,
      "device_type": "Server",
      "active_patches": 4,
      "pending_patches": 1,
      "last_patch_confirmed": "2023-07-11T10:12:50Z",
      "installed_patches": [
        {
          "id": "3033929",
          "status": "active",
          "published_date": "2015-03-10T00:00:00Z",
          "type": "Security Updates",
          "description": "Provides a link to Microsoft Security Advisory 3033929: Availability of SHA-2 Code Signing Support for Windows 7 and Windows Server 2008 R2. Microsoft has released a security advisory for IT professionals about SHA-2 code signing support. The security advisory announces the availability of a security update and contains additional security-related information. To view the security advisory, go to the following Microsoft website: https://technet.microsoft.com/en-us/library/security/3033929",
          "detail_url": "https://www.catalog.update.microsoft.com/Search.aspx?q=3033929"
        },
        {
          "id": "3063858",
          "status": "pending",
          "published_date": "2015-06-09T00:00:00Z",
          "type": "Security Updates",
          "description": "Microsoft has released security bulletin MS15-063. To learn more about this security bulletin: Home users:https://www.microsoft.com/security/pc-security/updates.aspxSkip the details: Download the updates for your home computer or laptop from the Microsoft Update website now:https://update.microsoft.com/microsoftupdate/IT professionals:https://technet.microsoft.com/library/security/MS15-063How to obtain help and support for this security updateHelp installing updates:Support for Microsoft UpdateSecurity solutions for IT professionals:TechNet Security Troubleshooting and SupportHelp protect your Windows-based computer from viruses and malware:Virus Solution and Security CenterLocal support according to your country:International Support",
          "detail_url": "https://support.microsoft.com/help/kb/KB3063858"
        },
        {
          "id": "976902",
          "status": "active"
        },
        {
          "id": "976932",
          "status": "active"
        },
        {
          "id": "976933",
          "status": "active"
        }
      ]
    },
    {
      "aid": "br45xxxxxxxxxxxx4f16871f834bn",
      "hostname": "SERVER-DEF",
      "reboot_required": false,
      "device_type": "Server",
      "active_patches": 5,
      "pending_patches": 0,
      "last_patch_confirmed": "2023-07-11T10:12:50Z",
      "installed_patches": [
        {
          "id": "3033929",
```



```

    "status": "active",
    "published_date": "2015-03-10T00:00:00Z",
    "type": "Security Updates",
    "description": "Provides a link to Microsoft Security Advisory 3033929: Availability of SHA-2 Code Signing Support for Windows 7
and Windows Server 2008 R2. Microsoft has released a security advisory for IT professionals about SHA-2 code signing support. The security
advisory announces the availability of a security update and contains additional security-related information. To view the security advisory,
go to the following Microsoft website: https://technet.microsoft.com/en-us/library/security/3033929",
    "detail_url": "https://www.catalog.update.microsoft.com/Search.aspx?q=3033929"
  },
  {
    "id": "3063858",
    "status": "active",
    "published_date": "2015-06-09T00:00:00Z",
    "type": "Security Updates",
    "description": "Microsoft has released security bulletin MS15-063. To learn more about this security bulletin:Home
users:https://www.microsoft.com/security/pc-security/updates.aspxSkip the details: Download the updates for your home computer or laptop from
the Microsoft Update website now:https://update.microsoft.com/microsoftupdate/IT
professionals:https://technet.microsoft.com/library/security/MS15-063How to obtain help and support for this security updateHelp installing
updates:Support for Microsoft UpdateSecurity solutions for IT professionals:TechNet Security Troubleshooting and SupportHelp protect your
Windows-based computer from viruses and malware:Virus Solution and Security CenterLocal support according to your country:International
Support",
    "detail_url": "https://support.microsoft.com/help/kb/KB3063858"
  },
  {
    "id": "976902",
    "status": "active"
  },
  {
    "id": "976932",
    "status": "active"
  },
  {
    "id": "976933",
    "status": "active"
  }
}
]
}
}

```