

SONARAY



LED Flood Light

DASCOM LED LIGHTING (JIANGMEN) CO., LTD.

Add.: No.399, Jinxing Road, Jianghai District, Jiangmen,
Guangdong, P. R. China

Tel.: 400-810-9998 800-810-9998

E-mail: info@dascomlighting.com

Website: <http://www.sonarayled.com>




FL-001-A




CE CQC IP65




Power Consumption: 130W
 LED Luminous Flux: 10472 lm (5000K)
 Luminous Efficacy: 81lm/w
 CCT: 3000K / 5000K
 CRI: ≥65
 Light Source: 9 LEDs
 Beam Angle: 60°/ 90°/ 120°
 Power Supply: Built-in
 Power Requirement: AC 100~240V, 50 / 60Hz
 Power Factor: ≥0.9
 Housing: Aluminum
 Weight: 1.2kg
 Operation Temperature : -25℃ ~ +45℃
 Average Lifetime : ≥35000hrs



Illuminance Distribution



Light Distribution Map






FL-001-B

CE CQC IP65



Power Consumption: 40W
 LED Luminous Flux: 2900 lm (3000K) , 3400(5000K)
 Luminous Efficacy: 73lm/w (3000K), 86lm/w (3000K)
 CCT: 3000K / 5000K
 CRI : ≥ 65
 Light Source: 5 LEDs
 Beam Angle: 60°/ 90°/ 120°
 Power Supply: Built-in
 Power Requirement: AC 100~240V,50 / 60Hz
 Power Factor: ≥ 0.9
 Housing: Aluminum
 Operation Temperature: -25°C ~ +45°C
 Average Lifetime: ≥ 35000 hrs






FL-001-D


CE CQC IP65




Power Consumption: 60W
 LED Luminous Flux: 5245 lm (5000K)
 Luminous Efficacy: 87lm/w
 CCT: 3000K / 5000K
 CRI: ≥65
 Light Source: 5 LEDs
 Beam Angle: 60°/ 90°/ 120°
 Power Supply: Built-in
 Power Requirement: AC 100~240V, 50 / 60Hz
 Power Factor: ≥0.9
 Housing 外壳: Aluminum
 Weight: 4kg
 Operation Temperature: -25℃ ~ +45℃
 Average Lifetime: ≥35000hrs




Illuminance Distribution



Isolux(Floor)



Light Distribution Map






FL-001-E


CE CQC IP65

Power Consumption: 250W
 LED Luminous Flux: 19983 lm (5000K)
 Luminous Efficacy: 80lm/w
 CCT: 3000K / 5000K
 CRI: ≥65
 Light Source: 8 LEDs
 Beam Angle: 90°
 Power Supply: Built-in
 Power Requirement: AC 100~240V,50 / 60Hz
 Power Factor: ≥0.9
 Housing: Aluminum
 Weight: 9.13kg
 Operation Temperature: -25℃ ~ +45℃
 Average Lifetime: ≥35000hrs


Illuminance Distribution of 1m Heighy



Isolux (Floor)



Light Distribution Map






FL-001-F


CE CQC IP65



Power Consumption: 520W
 LED Luminous Flux: 44502 lm (5000K)
 Luminous Efficacy: 86lm/w
 CCT: 3000K / 5000K
 CRI: ≥65
 Light Source: 12 LEDs
 Beam Angle: 75°
 Power Supply: Built-in
 Power Requirement: AC 100~240V,50 / 60Hz
 Power Factor: ≥0.9
 Housing: Aluminum
 Weight: 23kg
 Operation Temperature: -25℃ ~ +45℃
 Average Lifetime: ≥35000hrs



Light Distribution Map



Illuminance Distribution

FL-001-F (5000K 75°)

Height(m)	E(lx)	Diameter(cm)
3	3982	405
6	995	811
9	442	1216
12	249	1622
15	159	2028