

LED LIGHTING FOR INDUSTRIAL USE

A photograph of an industrial facility, likely a port or refinery, viewed through a large window with a black grid pattern. The scene includes cranes, storage tanks, and a body of water reflecting the structures. The sky is a mix of blue and orange, suggesting dawn or dusk. The window frame is prominent, with thick black vertical and horizontal bars.


SONARAY



The distinguish feature of SONARAY High Bay Lighting is its superior quality and the professional technical method applied in product design and production. This range of product emphasizes on the luminaire exterior design as well as exhibiting internal technical advantage of CITED.

Besides providing solution to traditional lighting. SONARAY products determines to exploit the limitless boundaries of lighting application base on the advance technical characteristics of CITED. Its application environment includes all interior settings in the building industry. The emphasis is on improving the interior environment, and not just on photometric effect of the luminaire design.





High Quality CITILED LED from Citizen of Japan

High Quality, maximum light output with advance technologies.

LM-80

Certified compliance with IES-LM80

Official standard with Illuminating Engineering Society of North America (IESNA) 70% lumens maintained after 35,000 hours of operation



Complies to Photo-Biological Safety Standards EN62471:2008

Do not emit radiation causing harm to the human eyes and skin

CCT

Complies with American National Standards Institute ANSI C78.377

Correspond to "3-steps MacAdam Ellipses (Chromaticity control standard) where the chromaticity range is narrower than 11%



High Colour Rendering

CITILED has a colour rendering index of Ra90, close to natural daylight, bringing out the original colour of an object



Energy Saving

SONARAY LED lighting achieved energy savings of 40% - 80% compare to traditional lighting



Kerry Logistics
Food Warehouse





There's 1000 Series LED High Bay Light, a revolutionary concept within High Bay lighting that redefines what you can get with an intact product. Not only does the line offer a sleek, industrial design that blends in with any décor, it is available in multiple power options under two dimensions, offering a wide range of applications.

LED HIGH BAY LIGHT 1000 SERIES





HB-1025

Power: 25W
Luminous Flux: 2200lm
Lamp Luminous Efficacy: 88lm/w
Color Temperature: 5000K
(Options: 2700K/3000K/3500K/4000K)
CRI: ≥ 65
Beam Angle: 40°
Material: Aluminum+Iron
Housing Color: Silver Gray
Power Supply: Built-in
Input Voltage: AC100-240V , 50/60Hz
Power Factor: ≥ 0.9
Weight: 2.5kg
Average Lifetime: ≥ 35000 hrs



HB-1100

Power: 100W
Luminous Flux: 8500lm
Lamp Luminous Efficacy: 85lm/w
Color Temperature: 5000K
(Options: 2700K/3000K/3500K/4000K)
CRI: ≥ 65
Beam Angle: 40°
Material: Aluminum+Iron
Housing Color: Silver Gray
Power Supply: Built-in
Input Voltage: AC100-240V , 50/60Hz
Power Factor: ≥ 0.9
Weight: 5kg
Average Lifetime: ≥ 35000 hrs



HB-1025 (5000K)

Height	Eavg,Emax	Beam Angle40°	Diameter
1m	656/2600lx		75cm
2m	165/650lx		150cm
3m	73/285lx		220cm
4m	40/160lx		300cm

HB-1100 (5000K)

Height	Eavg,Emax	Beam Angle40°	Diameter
3m	263/1190lx		225cm
6m	66/295lx		450cm
9m	30/130lx		675cm
12m	16/74lx		900cm



Shanghai Merchants Logistics
Warehouse





SONARAY latest 2000 series High Bay Lighting is a range of high efficiency energy saving product. It projects uniform brightness and colour temperature. It is especially suitable in wide area and high ceilings. Ideal application includes manufacturing plant, warehouse, supermarket, exhibition hall and meeting hall.

LED HIGH BAY LIGHT 2000 SERIES





HB-A-2025

Power: 25W
Luminous Flux: 2202lm
Lamp Luminous Efficacy: 88lm/w
Color Temperature: 5000K
(Options: 2700K/3000K/3500K/4000K)
CRI: ≥ 80
Beam Angle: 35°
Material: Aluminum
Housing Color: Silver
Power Supply: Built-in
Input Voltage: AC100-240V, 50/60Hz
Power Factor: ≥ 0.9
Weight: 2.7kg
Average Lifetime: ≥ 35000 hrs





HB-A-2035

Power: 35W
Luminous Flux: 2923lm
Lamp Luminous Efficacy: 84lm/w
Color Temperature: 5000K
(Options: 2700K/3000K/3500K/4000K)
CRI: ≥ 80
Beam Angle: 35°
Material: Aluminum
Housing Color: Silver
Power Supply: Built-in
Input Voltage: AC100-240V, 50/60Hz
Power Factor: ≥ 0.9
Weight: 2.7kg
Average Lifetime: ≥ 35000 hrs





HB-A-2045

Power: 45W
Luminous Flux: 3150lm
Lamp Luminous Efficacy: 70lm/w
Color Temperature: 5000K
(Options: 2700K/3000K/3500K/4000K)
CRI: ≥ 80
Beam Angle: 35°
Material: Aluminum
Housing Color: Silver
Power Supply: Built-in
Input Voltage: AC100-240V, 50/60Hz
Power Factor: ≥ 0.9
Weight: 3.5kg
Average Lifetime: ≥ 35000 hrs



HB-A-2065

Power: 65W
Luminous Flux: 5028lm
Lamp Luminous Efficacy: 77lm/w
Color Temperature: 5000K
(Options: 2700K/3000K/3500K/4000K)
CRI: ≥ 80
Beam Angle: 35°
Material: Aluminum
Housing Color: Silver
Power Supply: Built-in
Input Voltage: AC100-240V, 50/60Hz
Power Factor: ≥ 0.9
Weight: 3.5kg
Average Lifetime: ≥ 35000 hrs



HB-A-2025 (5000K)			
Height	Eavg,Emax	Beam Angle35°	Diameter
1m	2939/4458lx		58cm
2m	710/1115lx		117cm
3m	315/495lx		175cm
4m	177/279lx		233cm
5m	113/178lx		292cm

HB-A-2035 (5000K)			
Height	Eavg,Emax	Beam Angle35°	Diameter
1m	3703/5839lx		61cm
2m	925/1460lx		122cm
3m	411/648lx		183cm
4m	231/365lx		244cm
5m	148/233lx		306cm

HB-A-2045 (5000K)			
Height	Eavg,Emax	Beam Angle35°	Diameter
1m	4305/6845lx		59cm
2m	1076/1711lx		117cm
3m	447/760lx		176cm
4m	269/428lx		234cm
5m	172/274lx		293cm



HB-A-2065 (5000K)			
Height	Eavg,Emax	Beam Angle35°	Diameter
1m	5368/8750lx		60cm
2m	1342/2188lx		119cm
3m	596/972lx		179cm
4m	335/547lx		238cm
5m	153/250lx		298cm

LED HIGH BAY LIGHT 2000 SERIES





HB-AD-2035

Power: 35W
Luminous Flux: 2777lm
Lamp Luminous Efficacy: 79lm/w
Color Temperature: 5000K
(Options: 2700K/3000K/3500K/4000K)
CRI: ≥ 80
Beam Angle: 52°
Material: Aluminum
Housing Color: Silver
Power Supply: Built-in
Input Voltage: AC100-240V , 50/60Hz
Power Factor: ≥ 0.9
Weight: 3kg
Average Lifetime: ≥ 35000 hrs



HB-AD-2065

Power: 65W
Luminous Flux: 4418lm
Lamp Luminous Efficacy: 70lm/w
Color Temperature: 5000K
(Options: 2700K/3000K/3500K/4000K)
CRI: ≥ 80
Beam Angle: 48°
Material: Aluminum
Housing Color: Silver
Power Supply: Built-in
Input Voltage: AC100-240V , 50/60Hz
Power Factor: ≥ 0.9
Weight: 3.8kg
Average Lifetime: ≥ 35000 hrs



HB-AD-2035 (5000K)				
Height	Eavg,Emax	Beam Angle52°	Diameter	
1m	721/2265lx		99cm	
2m	180/566lx		198cm	
3m	80/252lx		296cm	
4m	45/142lx		395cm	
5m	29/91lx		494cm	

HB-AD-2065 (5000K)				
Height	Eavg,Emax	Beam Angle48°	Diameter	
1m	3465/4116lx		89cm	
2m	646/1029lx		178cm	
3m	273/457lx		267cm	
4m	154/257lx		356cm	
5m	98/164lx		445cm	



Shenyang Merchants Logistics
Warehouse





SONARAY stress on using CITILED single LED light source to prevent the issue of shadowing, produced by using the multiple LEDs approach by mass majority of lighting product in the market. By adopting a single LED light source it generates a natural illumination effect with wide-angle coverage, thereby ensuring lighting balance.

HB-B-2025





Power: 25W
Luminous Flux: 2398lm
Lamp Luminous Efficacy: 96lm/w
Color Temperature: 5000K
(Options: 2700K/3000K/3500K/4000K)
CRI: ≥80
Beam Angle: 70°
Material: Aluminum
Housing Color: Silver
Power Supply: Built-in
Input Voltage: AC100-240V , 50/60Hz
Power Factor: ≥0.9
Weight: 3.1kg
Average Lifetime: ≥35000hrs



HB-B-2035





Power: 35W
Luminous Flux: 3011lm
Lamp Luminous Efficacy: 86lm/w
Color Temperature: 5000K
(Options: 2700K/3000K/3500K/4000K)
CRI: ≥80
Beam Angle: 70°
Material: Aluminum
Housing Color: Silver
Power Supply: Built-in
Input Voltage: AC100-240V , 50/60Hz
Power Factor: ≥0.9
Weight: 3.1kg
Average Lifetime: ≥35000hrs



HB-B-2065





Power: 65W
Luminous Flux: 5311lm
Lamp Luminous Efficacy: 82lm/w
Color Temperature: 5000K
(Options: 2700K/3000K/3500K/4000K)
CRI: ≥80
Beam Angle: 70°
Material: Aluminum
Housing Color: Silver
Power Supply: Built-in
Input Voltage: AC100-240V , 50/60Hz
Power Factor: ≥0.9
Weight: 3.95kg
Average Lifetime: ≥35000hrs



HB-BD-2065 (With Diffuser)



Power: 65W
Luminous Flux: 4325lm
Lamp Luminous Efficacy: 66lm/w
Color Temperature: 5000K
(Options: 2700K/3000K/3500K/4000K)
CRI: ≥80
Beam Angle: 90°
Material: Aluminum
Housing Color: Silver
Power Supply: Built-in
Input Voltage: AC100-240V , 50/60Hz
Power Factor: ≥0.9
Weight: 4.45kg
Average Lifetime: ≥35000hrs



HB-B-2025 (5000K)

1m	815/1307lx	125cm
2m	203/326lx	251cm
3m	90/145lx	375cm
4m	51/82lx	501cm
5m	32/52lx	624cm

Height Eavg,Emax Beam Angle70° Diameter

HB-B-2035 (5000K)

1m	1009/1952lx	131cm
2m	252/487lx	262cm
3m	112/217lx	393cm
4m	63/122lx	524cm
5m	40/78lx	656cm

Height Eavg,Emax Beam Angle70° Diameter

HB-B-2065 (5000K)

1m	1484/3048lx	149cm
2m	371/762lx	298cm
3m	165/339lx	447cm
4m	93/199lx	595cm
5m	59/122lx	744cm

Height Eavg,Emax Beam Angle70° Diameter

HB-BD-2065 (5000K)

1m	743/1822lx	202cm
2m	186/455lx	405cm
3m	82/202lx	607cm
4m	46/119lx	810cm
5m	29/73lx	1013cm



Height Eavg,Emax Beam Angle90° Diameter

LED HIGH BAY LIGHT 2000 SERIES





HB-B-2085

Power: 85W
Luminous Flux: 7410lm
Lamp Luminous Efficacy: 87lm/w
Color Temperature: 5000K
(Options: 2700K/3000K/3500K/4000K)
CRI: ≥ 80
Beam Angle: 80°
Material: Aluminum
Housing Color: Silver
Power Supply: Built-in
Input Voltage: AC100-240V, 50/60Hz
Power Factor: ≥ 0.9
Weight: 5kg
Average Lifetime: ≥ 35000 hrs





HB-BD-2085 (With Diffuser)

Power: 85W
Luminous Flux: 6587lm
Lamp Luminous Efficacy: 77lm/w
Color Temperature: 5000K
(Options: 2700K/3000K/3500K/4000K)
CRI: ≥ 80
Beam Angle: 90°
Material: Aluminum
Housing Color: Silver
Power Supply: Built-in
Input Voltage: AC100-240V, 50/60Hz
Power Factor: ≥ 0.9
Weight: 5.5kg
Average Lifetime: ≥ 35000 hrs









HB-B-2100

Power: 100W
Luminous Flux: 8796lm
Lamp Luminous Efficacy: 88lm/w
Color Temperature: 5000K
(Options: 2700K/3000K/3500K/4000K)
CRI: ≥ 80
Beam Angle: 80°
Material: Aluminum
Housing Color: Silver
Power Supply: Built-in
Input Voltage: AC100-240V, 50/60Hz
Power Factor: ≥ 0.9
Weight: 5kg
Average Lifetime: ≥ 35000 hrs



HB-BD-2100 (With Diffuser)

Power: 100W
Luminous Flux: 7680lm
Lamp Luminous Efficacy: 77lm/w
Color Temperature: 5000K
(Options: 2700K/3000K/3500K/4000K)
CRI: ≥ 80
Beam Angle: 90°
Material: Aluminum
Housing Color: Silver
Power Supply: Built-in
Input Voltage: AC100-240V, 50/60Hz
Power Factor: ≥ 0.9
Weight: 5.5kg
Average Lifetime: ≥ 35000 hrs





Changi Airport Group





We research thoroughly upon the basic foundation of architectural design and conceived this range of High Bay Lighting series. Employing advance LED light engine, it caters to unique light setting requirements. The stress on details motivated SONARAY's designers and engineers to device a complete lighting solution, integrating intelligently to the wide application of current indoor light settings.





HB-C-2045

Power: 45W
Luminous Flux: 3375lm
Lamp Luminous Efficacy: 74lm/w
Color Temperature: 5000K
(Options: 2700K/3000K/3500K/4000K)
CRI: ≥ 80
Beam Angle: 53°
Material: Aluminum+PC
Housing Color: Silver
Power Supply: Built-in
Input Voltage: AC100-240V, 50/60Hz
Power Factor: ≥ 0.9
Weight: 3.9kg
Average Lifetime: ≥ 35000 hrs





HB-C-2085

Power: 85W
Luminous Flux: 7526lm
Lamp Luminous Efficacy: 88lm/w
Color Temperature: 5000K
(Options: 2700K/3000K/3500K/4000K)
CRI: ≥ 80
Beam Angle: 72°
Material: Aluminum+PC
Housing Color: Silver
Power Supply: Built-in
Input Voltage: AC100-240V, 50/60Hz
Power Factor: ≥ 0.9
Weight: 5.8kg
Average Lifetime: ≥ 35000 hrs





HB-CD-2085 (With Diffuser)

Power: 85W
Luminous Flux: 7523lm
Lamp Luminous Efficacy: 88lm/w
Color Temperature: 5000K
(Options: 2700K/3000K/3500K/4000K)
CRI: ≥ 80
Beam Angle: 72°
Material: Aluminum+PC
Housing Color: Silver
Power Supply: Built-in
Input Voltage: AC100-240V, 50/60Hz
Power Factor: ≥ 0.9
Weight: 6.5kg
Average Lifetime: ≥ 35000 hrs



HB-C-2100

Power: 100W
Luminous Flux: 7917lm
Lamp Luminous Efficacy: 79lm/w
Color Temperature: 5000K
(Options: 2700K/3000K/3500K/4000K)
CRI: ≥ 80
Beam Angle: 72°
Material: Aluminum+PC
Housing Color: Silver
Power Supply: Built-in
Input Voltage: AC100-240V, 50/60Hz
Power Factor: ≥ 0.9
Weight: 5.8kg
Average Lifetime: ≥ 35000 hrs



HB-C-2045 (5000K)

3m	126/239lx	298cm
6m	32/60lx	597cm
9m	14/27lx	595cm
12m	8/15lx	1193cm
15m	5/9lx	1492cm

Height Eavg,Emax Beam Angle 53° Diameter

HB-C-2085 (5000K)

3m	311/457lx	432cm
6m	78/114lx	869cm
9m	35/51lx	1303cm
12m	17/29lx	1737cm
15m	12/18lx	2172cm

Height Eavg,Emax Beam Angle 72° Diameter

HB-CD-2085 (5000K)

3m	313/362lx	269cm
6m	78/91lx	537cm
9m	35/40lx	806cm
12m	20/23lx	1075cm
15m	13/15lx	1343cm

Height Eavg,Emax Beam Angle 48° Diameter

HB-C-2100 (5000K)

3m	393/488lx	350cm
6m	98/122lx	701cm
9m	44/54lx	1051cm
12m	25/31lx	1402cm
15m	16/20lx	1753cm

Height Eavg,Emax Beam Angle 72° Diameter

LED HIGH BAY LIGHT 1000 SERIES



Order Direction

Model	Power	Dimension	Color Temperature	CRI	Beam Angle	Dimming	Appearance	Part Number
	(W)	(mm)	(K)		(°)			
HB-1025	25W	Φ255×222	5000K	65	40	NO	Silver Gray	HB255040CAG1
	25W	Φ255×222	5000K	80	40	NO	Silver Gray	HB255040BAG1
	25W	Φ255×222	4000K	80	40	NO	Silver Gray	HB254040BAG1
	25W	Φ255×222	3500K	80	40	NO	Silver Gray	HB253540BAG1
	25W	Φ255×222	3000K	80	40	NO	Silver Gray	HB253040BAG1
	25W	Φ255×222	2700K	80	40	NO	Silver Gray	HB252740BAG1
HB-1100	100W	Φ365×284	5000K	65	40	NO	Silver Gray	HBJ05040CAG1
	100W	Φ365×284	5000K	80	40	NO	Silver Gray	HBJ05040BAG1
	100W	Φ365×284	4000K	80	40	NO	Silver Gray	HBJ04040BAG1
	100W	Φ365×284	3500K	80	40	NO	Silver Gray	HBJ03540BAG1
	100W	Φ365×284	3000K	80	40	NO	Silver Gray	HBJ03040BAG1
	100W	Φ365×284	2700K	80	40	NO	Silver Gray	HBJ02740BAG1

LED HIGH BAY LIGHT 2000 SERIES



Order Direction

Model	Power	Dimension	Color Temperature	CRI	Beam Angle	Dimming	Appearance	Part Number
	(W)	(mm)	(K)		(°)			
HB-A-2025	25W	Φ338×380	5000K	65	35°	NO	Bell-shaped Lampshade	HB255035CGB1
	25W	Φ338×380	5000K	80	35°	NO	Bell-shaped Lampshade	HB255035BGB1
	25W	Φ338×380	4000K	80	35°	NO	Bell-shaped Lampshade	HB254035BGB1
	25W	Φ338×380	3500K	80	35°	NO	Bell-shaped Lampshade	HB253535BGB1
	25W	Φ338×380	3000K	80	35°	NO	Bell-shaped Lampshade	HB253035BGB1
	25W	Φ338×380	2700K	80	35°	NO	Bell-shaped Lampshade	HB252735BGB1
HB-B-2025	25W	Φ510×310	5000K	65	70°	NO	Large Empire Lampshade	HB255070CGB1
	25W	Φ510×310	5000K	80	70°	NO	Large Empire Lampshade	HB255070BGB1
	25W	Φ510×310	4000K	80	70°	NO	Large Empire Lampshade	HB254070BGB1
	25W	Φ510×310	3500K	80	70°	NO	Large Empire Lampshade	HB253570BGB1
	25W	Φ510×310	3000K	80	70°	NO	Large Empire Lampshade	HB253070BGB1
	25W	Φ510×310	2700K	80	70°	NO	Large Empire Lampshade	HB252770BGB1
HB-A-2035	35W	Φ338×380	5000K	65	35°	NO	Bell-shaped Lampshade	HB355035CGB1
	35W	Φ338×380	5000K	80	35°	NO	Bell-shaped Lampshade	HB355035BGB1
	35W	Φ338×380	4000K	80	35°	NO	Bell-shaped Lampshade	HB354035BGB1
	35W	Φ338×380	3500K	80	35°	NO	Bell-shaped Lampshade	HB353535BGB1
	35W	Φ338×380	3000K	80	35°	NO	Bell-shaped Lampshade	HB353035BGB1
	35W	Φ338×380	2700K	80	35°	NO	Bell-shaped Lampshade	HB352735BGB1
HB-B-2035	35W	Φ510×310	5000K	65	70°	NO	Large Empire Lampshade	HB355070CGB1
	35W	Φ510×310	5000K	80	70°	NO	Large Empire Lampshade	HB355070BGB1
	35W	Φ510×310	4000K	80	70°	NO	Large Empire Lampshade	HB354070BGB1
	35W	Φ510×310	3500K	80	70°	NO	Large Empire Lampshade	HB353570BGB1
	35W	Φ510×310	3000K	80	70°	NO	Large Empire Lampshade	HB353070BGB1
	35W	Φ510×310	2700K	80	70°	NO	Large Empire Lampshade	HB352770BGB1
HB-A-2045	45W	Φ338×450	5000K	65	35°	NO	Bell-shaped Lampshade	HB455035CGB1
	45W	Φ338×450	5000K	80	35°	NO	Bell-shaped Lampshade	HB455035BGB1
	45W	Φ338×450	4000K	80	35°	NO	Bell-shaped Lampshade	HB454035BGB1
	45W	Φ338×450	3500K	80	35°	NO	Bell-shaped Lampshade	HB453535BGB1
	45W	Φ338×450	3000K	80	35°	NO	Bell-shaped Lampshade	HB453035BGB1
	45W	Φ338×450	2700K	80	35°	NO	Bell-shaped Lampshade	HB452735BGB1
HB-B-2045	45W	Φ510×387	5000K	65	70°	NO	Large Empire Lampshade	HB455070CGB1
	45W	Φ510×387	5000K	80	70°	NO	Large Empire Lampshade	HB455070BGB1
	45W	Φ510×387	4000K	80	70°	NO	Large Empire Lampshade	HB454070BGB1
	45W	Φ510×387	3500K	80	70°	NO	Large Empire Lampshade	HB453570BGB1
	45W	Φ510×387	3000K	80	70°	NO	Large Empire Lampshade	HB453070BGB1
	45W	Φ510×387	2700K	80	70°	NO	Large Empire Lampshade	HB452770BGB1
HB-A-2065	65W	Φ338×450	5000K	65	35°	NO	Bell-shaped Lampshade	HB655035CGB1
	65W	Φ338×450	5000K	80	35°	NO	Bell-shaped Lampshade	HB655035BGB1
	65W	Φ338×450	4000K	80	35°	NO	Bell-shaped Lampshade	HB654035BGB1
	65W	Φ338×450	3500K	80	35°	NO	Bell-shaped Lampshade	HB653535BGB1
	65W	Φ338×450	3000K	80	35°	NO	Bell-shaped Lampshade	HB653035BGB1
	65W	Φ338×450	2700K	80	35°	NO	Bell-shaped Lampshade	HB652735BGB1
HB-B-2065	65W	Φ510×387	5000K	65	70°	NO	Large Empire Lampshade	HB655070CGB1
	65W	Φ510×387	5000K	80	70°	NO	Large Empire Lampshade	HB655070BGB1
	65W	Φ510×387	4000K	80	70°	NO	Large Empire Lampshade	HB654070BGB1
	65W	Φ510×387	3500K	80	70°	NO	Large Empire Lampshade	HB653570BGB1
	65W	Φ510×387	3000K	80	70°	NO	Large Empire Lampshade	HB653070BGB1
	65W	Φ510×387	2700K	80	70°	NO	Large Empire Lampshade	HB652770BGB1
HB-B-2085	85W	Φ510×420	5000K	65	80°	NO	Large Empire Lampshade	HB855080CGB1
	85W	Φ510×420	5000K	80	80°	NO	Large Empire Lampshade	HB855080BGB1
	85W	Φ510×420	4000K	80	80°	NO	Large Empire Lampshade	HB854080BGB1
	85W	Φ510×420	3500K	80	80°	NO	Large Empire Lampshade	HB853580BGB1
	85W	Φ510×420	3000K	80	80°	NO	Large Empire Lampshade	HB853080BGB1
	85W	Φ510×420	2700K	80	80°	NO	Large Empire Lampshade	HB852780BGB1
HB-B-2100	100W	Φ510×420	5000K	65	80°	NO	Large Empire Lampshade	HBJ05080CGB1
	100W	Φ510×420	5000K	80	80°	NO	Large Empire Lampshade	HBJ05080BGB1
	100W	Φ510×420	4000K	80	80°	NO	Large Empire Lampshade	HBJ04080BGB1
	100W	Φ510×420	3500K	80	80°	NO	Large Empire Lampshade	HBJ03580BGB1
	100W	Φ510×420	3000K	80	80°	NO	Large Empire Lampshade	HBJ03080BGB1
	100W	Φ510×420	2700K	80	80°	NO	Large Empire Lampshade	HBJ02780BGB1
HB-C-2025	25W	Φ357×356	5000K	80	53°	NO	Transparent Lampshade	HB255000CGB1
HB-C-2035	35W	Φ357×356	5000K	80	53°	NO	Transparent Lampshade	HB355000CGB1
HB-C-2045	45W	Φ430×356	5000K	80	53°	NO	Transparent Lampshade	HB455000BGB1
HB-C-2085	85W	Φ557×410	5000K	80	72°	NO	Transparent Lampshade	HB855000BGB1
HB-C-2100	100W	Φ557×410	5000K	80	72°	NO	Transparent Lampshade	HBJ05000BGB1

Contact us

- **China**

Add.: No.399,Jinxing Road,Jianghai District,Jiangmen,
Guangdong,P.R.China
Tel.: 400-810-9998
800-810-9998

- **United States**

DASCOM AMERICAS CORPORATION
421 West Main Street
Waynesboro
Virginia 22980-3606
USA
Tel.: +1 877 434-1377

- **Germany**

DASCOM Europe GmbH
Heuweg 3, D-89079 Ulm
Tel.: +49(0)731.2075.543

- **Hongkong**

Room 1811-1816A
Nan Fung Centre
264-298 Castle Peak Road
Tsuen Wan, New Territories, Hong Kong
Tel.: 852 2498 1507

- **Singapore**

DASCOM AP Pte. Ltd.
21 Bukit Batok Crescent
29-81 WCEGA Tower
Singapore 658065
Tel.: +65 6760.8833

For more information of SONARAY Products, Please read the catalogue of *COMPANY PROFILE* and *LIGHTING FOR COMMERCIAL USE*.

