10 Linux commands:

```
ubuntu@ip-172-31-1-182:~$ count=1
ubuntu@ip-172-31-1-182:~$ echo "$count"
1
ubuntu@ip-172-31-1-182:~$ if [ "$count" -eq 1 ]; then echo yes; fi
yes
ubuntu@ip-172-31-1-182:~$ for name in a b c; do echo "$name"; done
a
b
c
ubuntu@ip-172-31-1-182:~$ for f in ~/linux-lab/*.txt; do echo "$f"; done
/home/ubuntu/linux-lab/file1.txt
/home/ubuntu/linux-lab/file2.txt
/home/ubuntu/linux-lab/notes.txt
/home/ubuntu/linux-lab/output.txt
ubuntu@ip-172-31-1-182:~$ test -f ~/linux-lab/output.txt && echo exists
exists
ubuntu@ip-172-31-1-182:~$ test -d ~/linux-lab && echo exists
exists
ubuntu@ip-172-31-1-182:~$ case "$count" in 1) echo one;; *) echo other;; esac
one
ubuntu@ip-172-31-1-182:~$ read -r answer
echo "$answer"
Hello!
Hello!
ubuntu@ip-172-31-1-182:~$ ls -l ~/linux-lab
echo "count=$count, answer=$answer"
total 4
-rw-rw-r-- 1 ubuntu ubuntu  0 Oct 26 18:34 file1.txt
-rw-rw-r-- 1 ubuntu ubuntu  0 Oct 26 18:34 file2.txt
-rw-rw-r-- 1 ubuntu ubuntu  0 Oct 26 18:34 notes.txt
-rw-rw-r-- 1 ubuntu ubuntu 15 Oct 26 18:34 output.txt
count=1, answer=Hello!
```

`count=1` – Creates a shell variable named `count` and assigns it the value `1`.

`echo "$count"` – Displays the value stored in the `count` variable.

`if [ "$count" -eq 1 ]; then echo yes; fi` – Checks whether `count` equals 1 and prints `yes` if true.

`for name in a b c; do echo "$name"; done` – Loops through the values `a`, `b`, and `c` and prints each one.

`for f in ~/linux-lab/*.txt; do echo "$f"; done` – Loops through and prints the paths of all matching `.txt` files in the directory.

`test -f ~/linux-lab/output.txt && echo exists` – Prints `exists` if `output.txt` exists as a regular file.

`test -d ~/linux-lab && echo exists` – Prints `exists` if the `linux-lab` directory exists.

`case "$count" in 1) echo one;; *) echo other;; esac` – Prints `one` if `count` is 1; otherwise, prints `other`.

`read -r answer` – Reads a line of user input and stores it in the `answer` variable.

Review – Practise variables, conditions, loops, and quoting before writing a complete shell script.