

Fit Force

Frontend Source Code

Generated 2026-08-16 • 42 files

package.json

```
1  {
2    "name": "@workspace/fit-force",
3    "version": "0.0.0",
4    "private": true,
5    "main": "expo-router/entry",
6    "scripts": {
7      "dev": "EXPO_PACKAGER_PROXY_URL=https://$REPLIT_EXPO_DEV_DOMAIN EXPO_PUBLIC_DOMAIN=$REPLIT_DEV_DOMAIN
EXPO_PUBLIC_REPL_ID=$REPL_ID REACT_NATIVE_PACKAGER_HOSTNAME=$REPLIT_DEV_DOMAIN pnpm exec expo start --localhost --
port $PORT",
8      "build": "node scripts/build.js",
9      "serve": "node server/serve.js",
10     "typecheck": "tsc -p tsconfig.json --noEmit"
11   },
12   "devDependencies": {
13     "@babel/core": "^7.25.2",
14     "@expo-google-fonts/inter": "^0.4.0",
15     "@expo/cli": "54.0.23",
16     "@expo/ngrok": "^4.1.0",
17     "@expo/vector-icons": "^15.0.3",
18     "@react-native-async-storage/async-storage": "2.2.0",
19     "@stardazed/streams-text-encoding": "^1.0.2",
20     "@tanstack/react-query": "catalog:",
21     "@types/react": "~19.1.10",
22     "@types/react-dom": "~19.1.7",
23     "@ungap/structured-clone": "^1.3.0",
24     "babel-plugin-react-compiler": "^19.0.0-beta-e993439-20250117",
25     "pdfkit": "^0.19.1",
26     "expo": "54.0.25",
27     "expo-blur": "~15.0.8",
28     "expo-constants": "~18.0.11",
29     "expo-document-picker": "~14.0.8",
30     "expo-file-system": "~19.0.23",
31     "expo-font": "~14.0.10",
32     "expo-glass-effect": "~0.1.4",
33     "expo-haptics": "~15.0.8",
34     "expo-image": "~3.0.11",
35     "expo-image-picker": "~17.0.9",
36     "expo-linear-gradient": "~15.0.8",
37     "expo-linking": "~8.0.10",
38     "expo-location": "~19.0.8",
39     "expo-router": "6.0.17",
40     "expo-sharing": "~14.0.8",
41     "expo-splash-screen": "~31.0.12",
42     "expo-status-bar": "~3.0.9",
43     "expo-symbols": "~1.0.8",
44     "expo-system-ui": "~6.0.9",
45     "expo-web-browser": "~15.0.10",
46     "react": "catalog:",
47     "react-dom": "catalog:",
48     "react-native": "0.81.5",
49     "react-native-gesture-handler": "~2.28.0",
50     "react-native-keyboard-controller": "1.18.5",
51     "react-native-reanimated": "~4.1.1",
52     "react-native-safe-area-context": "~5.6.0",
53     "react-native-screens": "~4.16.0",
54     "react-native-svg": "15.12.1",
55     "react-native-web": "^0.21.0",
56     "react-native-worklets": "0.5.1",
57     "typescript": "~5.9.2",
58     "zod": "catalog:",
59     "zod-validation-error": "^3.4.0"
60   },
61   "packageManager": "pnpm@11.20.0+sha512.9a6f330a95b66446ea088faf1521405a8a01f07fde7124cc9958dfed52d4bb43673
7e65b08f85f37b46fcb375092558ac51262b816844b22f63406ed166bfee"
62 }
63
```

app.json

```
1  {
2    "expo": {
3      "name": "Fit Force",
4      "slug": "fit-force",
5      "version": "1.0.0",
6      "orientation": "portrait",
7      "icon": "./assets/images/icon.png",
8      "scheme": "fit-force",
9      "userInterfaceStyle": "dark",
10     "newArchEnabled": true,
11     "splash": {
12       "image": "./assets/images/icon.png",
13       "resizeMode": "contain",
14       "backgroundColor": "#1B5E3B"
15     },
16     "ios": {
17       "supportsTablet": false
18     },
19     "android": {},
20     "web": {
21       "favicon": "./assets/images/icon.png"
22     },
23     "plugins": [
24       [
25         "expo-router",
26         {
27           "origin": "https://replit.com/"
28         }
29       ],
30       "expo-font",
31       "expo-web-browser"
32     ],
33     "experiments": {
34       "typedRoutes": true,
35       "reactCompiler": true
36     }
37   }
38 }
39
```

babel.config.js

```
1 module.exports = function (api) {
2   api.cache(true);
3   return {
4     presets: [['babel-preset-expo', { unstable_transformImportMeta: true }]],
5   };
6 };
7
```

metro.config.js

```
1  const { getDefaultConfig } = require('expo/metro-config');
2
3  module.exports = getDefaultConfig(__dirname);
4
```

tsconfig.json

```
1  {
2    "extends": "expo/tsconfig.base",
3    "compilerOptions": {
4      "ignoreDeprecations": "6.0",
5      "baseUrl": ".",
6      "strict": true,
7      "paths": {
8        "@/*": [
9          ".*/*"
10       ]
11     }
12   },
13   "include": [
14     "**/*.ts",
15     "**/*.tsx",
16     ".expo/types/**/*.ts",
17     "expo-env.d.ts"
18   ],
19   "references": [
20     {
21       "path": "../../lib/api-client-react"
22     }
23   ]
24 }
25
```

lib/alert.ts

```
1 import { Platform, Alert as RNAlert } from 'react-native';
2
3 export interface AlertButton {
4   text: string;
5   onPress?: () => void;
6   style?: 'default' | 'cancel' | 'destructive';
7 }
8
9 /**
10  * react-native-web's Alert.alert() is a complete no-op on web – it shows
11  * nothing and never calls any button's onPress. That silently breaks every
12  * confirm dialog (Approve, Delete, ...) and every "OK to continue" flow
13  * (e.g. navigating back after a save) whenever the app runs in a browser,
14  * with no error or warning to say so. This wraps Alert.alert so native
15  * platforms keep the real dialog, while web falls back to window.alert /
16  * window.confirm so the button actions this app depends on actually run.
17  */
18 export function showAlert(title: string, message?: string, buttons?: AlertButton[]): void {
19   if (Platform.OS !== 'web') {
20     RNAlert.alert(title, message, buttons as any);
21     return;
22   }
23
24   const list = buttons && buttons.length > 0 ? buttons : [{ text: 'OK' } as AlertButton];
25   const text = [title, message].filter(Boolean).join('\n\n');
26
27   if (list.length === 1) {
28     window.alert(text);
29     list[0].onPress?.();
30     return;
31   }
32
33   const cancelBtn = list.find(b => b.style === 'cancel');
34   const actionBtn = list.find(b => b.style !== 'cancel') ?? list[list.length - 1];
35
36   if (window.confirm(text)) {
37     actionBtn.onPress?.();
38   } else {
39     cancelBtn?.onPress?.();
40   }
41 }
42
```

lib/api.ts

```
1 import { Platform } from 'react-native';
2 import Constants from 'expo-constants';
3
4 const API_PORT = 4000;
5
6 /**
7  * Figures out where the shared data server is, without hardcoding an IP.
8  * On web, the browser's own address bar already has the right LAN IP (or
9  * "localhost") – reuse it. On native (Expo Go), Constants exposes the
10 * host:port the JS bundle was loaded from, which lives on the same
11 * machine as the data server; swap its port for the data server's.
12 */
13 function resolveApiBase(): string {
14   if (Platform.OS === 'web' && typeof window !== 'undefined' && window.location?.hostname) {
15     return `http://${window.location.hostname}:${API_PORT}`;
16   }
17   const hostUri =
18     Constants.expoConfig?.hostUri ??
19     (Constants as any).expoGoConfig?.hostUri ??
20     (Constants as any).manifest2?.extra?.expoClient?.hostUri;
21   const host = hostUri ? String(hostUri).split(':')[0] : 'localhost';
22   return `http://${host}:${API_PORT}`;
23 }
24
25 export const API_BASE = resolveApiBase();
26
```

```
1 import type { User, Soldier, PTPlan, IPFTResult, IPFTSchedule, Notification, Report } from './types';
2
3 export const SEED_USERS: User[] = [
4   {
5     id: 'co-001', email: 'co@gmail.com', password: 'co123', role: 'co',
6     name: 'Lt Col Shahid Hasan', rank: 'Lt Col', ba: 'BA-6556',
7     phone: '01711-334455', bloodGroup: 'B+', medicalCategory: 'Category A',
8     height: 178, weight: 82, age: 45,
9   },
10  {
11    id: '2ic-001', email: '2ic@gmail.com', password: '2ic123', role: '2ic',
12    name: 'Maj Aminul Haque', rank: 'Maj', ba: 'BA-8823',
13    phone: '01712-556677', bloodGroup: 'O+', medicalCategory: 'Category A',
14    height: 175, weight: 78, age: 38,
15  },
16  {
17    id: 'adjt-001', email: 'adjt@gmail.com', password: 'adjt123', role: 'adjutant',
18    name: 'Capt Tasnim Akhter', rank: 'Capt', ba: 'BA-20211',
19    phone: '01713-778899', bloodGroup: 'A+', medicalCategory: 'Category A',
20    height: 165, weight: 60, age: 30,
21  },
22  {
23    id: 'coy-a-001', email: 'acoycomd@gmail.com', password: 'coya123', role: 'coy_comd',
24    name: 'Maj Jannat Ara', rank: 'Maj', ba: 'BA-202116', company: 'A',
25    phone: '01714-223344', bloodGroup: 'AB+', medicalCategory: 'Category A',
26    height: 162, weight: 58, age: 36,
27  },
28  {
29    id: 'coy-b-001', email: 'bcoycomd@gmail.com', password: 'coyb123', role: 'coy_comd',
30    name: 'Maj Faizul Hasan', rank: 'Maj', ba: 'BA-193045', company: 'B',
31    phone: '01715-445566', bloodGroup: 'B+', medicalCategory: 'Category A',
32    height: 174, weight: 80, age: 37,
33  },
34  {
35    id: 'coy-c-001', email: 'ccoycomd@gmail.com', password: 'coyc123', role: 'coy_comd',
36    name: 'Maj Rezaul Karim', rank: 'Maj', ba: 'BA-185674', company: 'C',
37    phone: '01716-667788', bloodGroup: 'O-', medicalCategory: 'Category A',
38    height: 172, weight: 75, age: 39,
39  },
40  {
41    id: 'coy-d-001', email: 'dcoycomd@gmail.com', password: 'coyd123', role: 'coy_comd',
42    name: 'Maj Kabirul Islam', rank: 'Maj', ba: 'BA-201234', company: 'D',
43    phone: '01717-889900', bloodGroup: 'A-', medicalCategory: 'Category A',
44    height: 176, weight: 82, age: 40,
45  },
46  {
47    id: 'clerk-001', email: 'clerk@gmail.com', password: 'clerk123', role: 'clerk',
48    name: 'Cpl Mizanur Rahman', rank: 'Cpl', ba: 'BA-301122',
49    phone: '01718-112233', bloodGroup: 'B+', medicalCategory: 'Category A',
50    height: 170, weight: 72, age: 28,
51  },
52  {
53    id: 'sol-a-001', email: 'jahangir@gmail.com', password: 'soldier123', role: 'soldier',
54    name: 'Jahangir Alam', rank: 'Snk', ba: 'BD-11001', company: 'A',
55    phone: '01911-001001', bloodGroup: 'A+', medicalCategory: 'Category A',
56    height: 170, weight: 68, age: 22, serviceNumber: 'BD-11001',
57  },
58  {
59    id: 'sol-a-002', email: 'rafiq@gmail.com', password: 'soldier123', role: 'soldier',
60    name: 'Rafiq Uddin', rank: 'LCpl', ba: 'BD-11002', company: 'A',
61    phone: '01911-001002', bloodGroup: 'B+', medicalCategory: 'Category B',
62    height: 168, weight: 85, age: 24, serviceNumber: 'BD-11002',
63  },
64  {
65    id: 'sol-a-003', email: 'kamal@gmail.com', password: 'soldier123', role: 'soldier',
66    name: 'Kamal Hossain', rank: 'Cpl', ba: 'BD-11003', company: 'A',
67    phone: '01911-001003', bloodGroup: 'O+', medicalCategory: 'Category A',
68    height: 172, weight: 70, age: 26, serviceNumber: 'BD-11003',
69  },
70  {
71    id: 'sol-a-004', email: 'arif@gmail.com', password: 'soldier123', role: 'soldier',
72    name: 'Ariful Islam', rank: 'Snk', ba: 'BD-11004', company: 'A',
73    phone: '01911-001004', bloodGroup: 'AB+', medicalCategory: 'Category A',
74    height: 165, weight: 62, age: 21, serviceNumber: 'BD-11004',
75  },
76  {
77    id: 'sol-b-001', email: 'rahim@gmail.com', password: 'soldier123', role: 'soldier',
78    name: 'Rahim Mia', rank: 'Snk', ba: 'BD-12001', company: 'B',
79    phone: '01911-002001', bloodGroup: 'A+', medicalCategory: 'Category A',
80    height: 169, weight: 66, age: 22, serviceNumber: 'BD-12001',
81  },
82  {
83    id: 'sol-b-002', email: 'selim@gmail.com', password: 'soldier123', role: 'soldier',
```

```

84     name: 'Selim Khan', rank: 'LCpl', ba: 'BD-12002', company: 'B',
85     phone: '01911-002002', bloodGroup: 'AB+', medicalCategory: 'Category A',
86     height: 173, weight: 71, age: 25, serviceNumber: 'BD-12002',
87 },
88 {
89     id: 'sol-b-003', email: 'monir@gmail.com', password: 'soldier123', role: 'soldier',
90     name: 'Monir Hossain', rank: 'Cpl', ba: 'BD-12003', company: 'B',
91     phone: '01911-002003', bloodGroup: 'B-', medicalCategory: 'Category B',
92     height: 166, weight: 88, age: 27, serviceNumber: 'BD-12003',
93 },
94 {
95     id: 'sol-c-001', email: 'babu@gmail.com', password: 'soldier123', role: 'soldier',
96     name: 'Babu Mia', rank: 'Snk', ba: 'BD-13001', company: 'C',
97     phone: '01911-003001', bloodGroup: 'B-', medicalCategory: 'Category A',
98     height: 167, weight: 64, age: 21, serviceNumber: 'BD-13001',
99 },
100 {
101     id: 'sol-c-002', email: 'jamal@gmail.com', password: 'soldier123', role: 'soldier',
102     name: 'Jamal Uddin', rank: 'LCpl', ba: 'BD-13002', company: 'C',
103     phone: '01911-003002', bloodGroup: 'O+', medicalCategory: 'Category A',
104     height: 171, weight: 69, age: 24, serviceNumber: 'BD-13002',
105 },
106 {
107     id: 'sol-c-003', email: 'habib@gmail.com', password: 'soldier123', role: 'soldier',
108     name: 'Habibur Rahman', rank: 'Sgt', ba: 'BD-13003', company: 'C',
109     phone: '01911-003003', bloodGroup: 'A-', medicalCategory: 'Category A',
110     height: 174, weight: 76, age: 30, serviceNumber: 'BD-13003',
111 },
112 {
113     id: 'sol-d-001', email: 'faruk@gmail.com', password: 'soldier123', role: 'soldier',
114     name: 'Faruk Ahmed', rank: 'Snk', ba: 'BD-14001', company: 'D',
115     phone: '01911-004001', bloodGroup: 'A+', medicalCategory: 'Category A',
116     height: 168, weight: 65, age: 22, serviceNumber: 'BD-14001',
117 },
118 {
119     id: 'sol-d-002', email: 'nurul@gmail.com', password: 'soldier123', role: 'soldier',
120     name: 'Nurul Islam', rank: 'LCpl', ba: 'BD-14002', company: 'D',
121     phone: '01911-004002', bloodGroup: 'B+', medicalCategory: 'Category B',
122     height: 166, weight: 90, age: 25, serviceNumber: 'BD-14002',
123 },
124 {
125     id: 'sol-d-003', email: 'sultan@gmail.com', password: 'soldier123', role: 'soldier',
126     name: 'Sultan Mahmud', rank: 'WO', ba: 'BD-14003', company: 'D',
127     phone: '01911-004003', bloodGroup: 'O-', medicalCategory: 'Category A',
128     height: 176, weight: 80, age: 35, serviceNumber: 'BD-14003',
129 },
130 ];
131
132 export const SEED_SOLDIERS: Soldier[] = [
133   { id: 'sol-a-001', userId: 'sol-a-001', serviceNumber: 'BD-11001', name: 'Jahangir Alam', rank: 'Snk',
company: 'A', email: 'jahangir@gmail.com', bloodGroup: 'A+', height: 170, weight: 68, age: 22, medicalCategory:
'Category A', phone: '01911-001001', isApproved: true, isOverweight: false, ptStatus: 'fit' },
134   { id: 'sol-a-002', userId: 'sol-a-002', serviceNumber: 'BD-11002', name: 'Rafiq Uddin', rank: 'LCpl',
company: 'A', email: 'rafiq@gmail.com', bloodGroup: 'B+', height: 168, weight: 85, age: 24, medicalCategory:
'Category B', phone: '01911-001002', isApproved: true, isOverweight: true, ptStatus: 'unfit' },
135   { id: 'sol-a-003', userId: 'sol-a-003', serviceNumber: 'BD-11003', name: 'Kamal Hossain', rank: 'Cpl',
company: 'A', email: 'kamal@gmail.com', bloodGroup: 'O+', height: 172, weight: 70, age: 26, medicalCategory:
'Category A', phone: '01911-001003', isApproved: true, isOverweight: false, ptStatus: 'fit' },
136   { id: 'sol-a-004', userId: 'sol-a-004', serviceNumber: 'BD-11004', name: 'Ariful Islam', rank: 'Snk',
company: 'A', email: 'arif@gmail.com', bloodGroup: 'AB+', height: 165, weight: 62, age: 21, medicalCategory:
'Category A', phone: '01911-001004', isApproved: true, isOverweight: false, ptStatus: 'pending' },
137   { id: 'sol-b-001', userId: 'sol-b-001', serviceNumber: 'BD-12001', name: 'Rahim Mia', rank: 'Snk',
company: 'B', email: 'rahim@gmail.com', bloodGroup: 'A+', height: 169, weight: 66, age: 22, medicalCategory:
'Category A', phone: '01911-002001', isApproved: true, isOverweight: false, ptStatus: 'fit' },
138   { id: 'sol-b-002', userId: 'sol-b-002', serviceNumber: 'BD-12002', name: 'Selim Khan', rank: 'LCpl',
company: 'B', email: 'selim@gmail.com', bloodGroup: 'AB+', height: 173, weight: 71, age: 25, medicalCategory:
'Category A', phone: '01911-002002', isApproved: true, isOverweight: false, ptStatus: 'fit' },
139   { id: 'sol-b-003', userId: 'sol-b-003', serviceNumber: 'BD-12003', name: 'Monir Hossain', rank: 'Cpl',
company: 'B', email: 'monir@gmail.com', bloodGroup: 'B-', height: 166, weight: 88, age: 27, medicalCategory:
'Category B', phone: '01911-002003', isApproved: true, isOverweight: true, ptStatus: 'unfit' },
140   { id: 'sol-c-001', userId: 'sol-c-001', serviceNumber: 'BD-13001', name: 'Babu Mia', rank: 'Snk',
company: 'C', email: 'babu@gmail.com', bloodGroup: 'B-', height: 167, weight: 64, age: 21, medicalCategory:
'Category A', phone: '01911-003001', isApproved: true, isOverweight: false, ptStatus: 'fit' },
141   { id: 'sol-c-002', userId: 'sol-c-002', serviceNumber: 'BD-13002', name: 'Jamal Uddin', rank: 'LCpl',
company: 'C', email: 'jamal@gmail.com', bloodGroup: 'O+', height: 171, weight: 69, age: 24, medicalCategory:
'Category A', phone: '01911-003002', isApproved: true, isOverweight: false, ptStatus: 'fit' },
142   { id: 'sol-c-003', userId: 'sol-c-003', serviceNumber: 'BD-13003', name: 'Habibur Rahman', rank: 'Sgt',
company: 'C', email: 'habib@gmail.com', bloodGroup: 'A-', height: 174, weight: 76, age: 30, medicalCategory:
'Category A', phone: '01911-003003', isApproved: true, isOverweight: false, ptStatus: 'unfit' },
143   { id: 'sol-d-001', userId: 'sol-d-001', serviceNumber: 'BD-14001', name: 'Faruk Ahmed', rank: 'Snk',
company: 'D', email: 'faruk@gmail.com', bloodGroup: 'A+', height: 168, weight: 65, age: 22, medicalCategory:
'Category A', phone: '01911-004001', isApproved: true, isOverweight: false, ptStatus: 'fit' },
144   { id: 'sol-d-002', userId: 'sol-d-002', serviceNumber: 'BD-14002', name: 'Nurul Islam', rank: 'LCpl',
company: 'D', email: 'nurul@gmail.com', bloodGroup: 'B+', height: 166, weight: 90, age: 25, medicalCategory:
'Category B', phone: '01911-004002', isApproved: true, isOverweight: true, ptStatus: 'unfit' },

```

```

145   { id: 'sol-d-003', userId: 'sol-d-003', serviceNumber: 'BD-14003', name: 'Sultan Mahmud', rank: 'WO',
company: 'D', email: 'sultan@gmail.com', bloodGroup: 'O-', height: 176, weight: 80, age: 35, medicalCategory:
'Category A', phone: '01911-004003', isApproved: true, isOverweight: false, ptStatus: 'fit' },
146 ];
147
148 export const SEED_PT_PLANS: PTPlan[] = [
149   {
150     id: 'plan-001', title: 'Standard Fitness Week Plan', type: 'fit',
151     description: 'Weekly PT plan for soldiers who passed IPFT. Maintain peak physical condition.',
152     createdBy: '2ic-001', createdByName: 'Maj Aminul Haque', weekNumber: 29,
153     createdAt: '2026-07-10T08:00:00Z',
154     days: [
155       { day: 'Saturday', focus: 'Cardio & Speed', exercises: [{ name: '3km Run', target: 'Complete in 12
min', notes: 'Maintain steady pace' }, { name: 'Sprints 100m', target: '10 sets', notes: '30s rest between
sets' }, { name: 'Jump Rope', target: '15 min continuous' } ] },
156       { day: 'Sunday', focus: 'Upper Body Strength', exercises: [{ name: 'Push-ups', target: '3 sets x 40
reps' }, { name: 'Pull-ups', target: '3 sets x 10 reps' }, { name: 'Dips', target: '3 sets x 15 reps' }, { name:
'Plank', target: '3 sets x 60 sec' } ] },
157       { day: 'Monday', focus: 'Lower Body & Core', exercises: [{ name: 'Squats', target: '4 sets x 30
reps' }, { name: 'Lunges', target: '3 sets x 20 reps each leg' }, { name: 'Sit-ups', target: '4 sets x 35
reps' }, { name: 'Calf Raises', target: '3 sets x 25 reps' } ] },
158       { day: 'Tuesday', focus: 'REST / Recovery', exercises: [{ name: 'Light Stretching', target: '20
min' }, { name: 'Walking', target: '2km easy pace' } ] },
159       { day: 'Wednesday', focus: 'Endurance Run', exercises: [{ name: '5km Run', target: 'Complete in 25
min' }, { name: 'Stair Climbing', target: '10 flights x 5 sets' } ] },
160       { day: 'Thursday', focus: 'Full Body Circuit', exercises: [{ name: 'Burpees', target: '4 sets x 15
reps' }, { name: 'Mountain Climbers', target: '3 sets x 30 reps' }, { name: 'Box Jumps', target: '3 sets x 12
reps' }, { name: 'Push-ups', target: '3 sets x 30 reps' } ] },
161       { day: 'Friday', focus: 'Parade & Drill', exercises: [{ name: 'Parade Drill', target: '1 hour' },
{ name: 'Formation Run', target: '2km' } ] },
162     ],
163   },
164   {
165     id: 'plan-002', title: 'Rehabilitation PT Plan (Unfit)', type: 'unfit',
166     description: 'Progressive recovery plan for soldiers who failed IPFT. Focus on gradual improvement.',
167     createdBy: '2ic-001', createdByName: 'Maj Aminul Haque', weekNumber: 29,
168     createdAt: '2026-07-10T08:30:00Z',
169     days: [
170       { day: 'Saturday', focus: 'Light Cardio', exercises: [{ name: '2km Walk/Jog', target: 'Complete in 20
min', notes: 'No pressure, keep moving' }, { name: 'Deep Breathing', target: '10 min' } ] },
171       { day: 'Sunday', focus: 'Basic Strength', exercises: [{ name: 'Modified Push-ups', target: '3 sets x
15 reps', notes: 'Knee push-ups allowed' }, { name: 'Sit-ups', target: '3 sets x 15 reps' }, { name: 'Plank',
target: '3 sets x 20 sec' } ] },
172       { day: 'Monday', focus: 'Mobility & Flexibility', exercises: [{ name: 'Full Body Stretching', target:
'30 min' }, { name: 'Yoga Basics', target: '20 min' }, { name: 'Light Squats', target: '3 sets x 10 reps' } ] },
173       { day: 'Tuesday', focus: 'REST', exercises: [{ name: 'Rest & Recovery', target: 'Full rest day' } ] },
174       { day: 'Wednesday', focus: 'Progressive Run', exercises: [{ name: 'Walk 3min / Jog 2min', target:
'Repeat 5 times = 25 min', notes: 'Interval training' } ] },
175       { day: 'Thursday', focus: 'Light Circuit', exercises: [{ name: 'Jumping Jacks', target: '3 sets x 20
reps' }, { name: 'Modified Burpees', target: '3 sets x 8 reps' }, { name: 'Wall Sit', target: '3 sets x 20
sec' } ] },
176       { day: 'Friday', focus: 'BMI Awareness & Diet', exercises: [{ name: 'Diet Counseling', target:
'Review meal plan' }, { name: 'Light Walk', target: '30 min' } ] },
177     ],
178   },
179 ];
180
181 export const SEED_IPFT_RESULTS: IPFTResult[] = [
182   {
183     id: 'result-001', soldierId: 'sol-a-001', soldierName: 'Jahangir Alam', soldierRank: 'Snk',
184     serviceNumber: 'BD-11001', company: 'A', date: '2026-06-15', overallStatus: 'pass',
185     recordedBy: 'clerk-001', recordedByName: 'Cpl Mizanur Rahman', bmi: 23.5,
186     items: [
187       { name: '1.6km Run', target: '< 9 min', achieved: '8:20', status: 'pass' },
188       { name: '3.2km Run', target: '< 24 min', achieved: '22:40', status: 'pass' },
189       { name: 'Push-ups', target: '"e 35 reps/2min', achieved: '42', status: 'pass' },
190       { name: 'Sit-ups', target: '"e 30 reps/2min', achieved: '38', status: 'pass' },
191       { name: 'Pull-ups', target: '"e 6 reps', achieved: '8', status: 'pass' },
192     ],
193   },
194   {
195     id: 'result-002', soldierId: 'sol-a-002', soldierName: 'Rafiq Uddin', soldierRank: 'LCpl',
196     serviceNumber: 'BD-11002', company: 'A', date: '2026-06-15', overallStatus: 'fail',
197     recordedBy: 'clerk-001', recordedByName: 'Cpl Mizanur Rahman', bmi: 30.1,
198     items: [
199       { name: '1.6km Run', target: '< 9 min', achieved: '10:15', status: 'fail' },
200       { name: '3.2km Run', target: '< 24 min', achieved: '27:30', status: 'fail' },
201       { name: 'Push-ups', target: '"e 35 reps/2min', achieved: '22', status: 'fail' },
202       { name: 'Sit-ups', target: '"e 30 reps/2min', achieved: '18', status: 'fail' },
203       { name: 'Pull-ups', target: '"e 6 reps', achieved: '3', status: 'fail' },
204     ],
205   },
206   {
207     id: 'result-003', soldierId: 'sol-b-001', soldierName: 'Rahim Mia', soldierRank: 'Snk',
208     serviceNumber: 'BD-12001', company: 'B', date: '2026-06-15', overallStatus: 'pass',

```

```

209     recordedBy: 'clerk-001', recordedByName: 'Cpl Mizanur Rahman', bmi: 23.1,
210     items: [
211       { name: '1.6km Run', target: '< 9 min', achieved: '8:35', status: 'pass' },
212       { name: '3.2km Run', target: '< 24 min', achieved: '23:10', status: 'pass' },
213       { name: 'Push-ups', target: '"e 35 reps/2min', achieved: '38', status: 'pass' },
214       { name: 'Sit-ups', target: '"e 30 reps/2min', achieved: '33', status: 'pass' },
215       { name: 'Pull-ups', target: '"e 6 reps', achieved: '7', status: 'pass' },
216     ],
217   },
218 ];
219
220 export const SEED_IPFT_SCHEDULE: IPFTSchedule = {
221   id: 'ipft-sched-001',
222   proposedDate: '2026-07-28',
223   proposedBy: 'adjt-001',
224   proposedByName: 'Capt Tasnim Akhter',
225   status: 'approved',
226   approvedBy: 'co-001',
227   createdAt: '2026-07-10T09:00:00Z',
228 };
229
230 export const SEED_NOTIFICATIONS: Notification[] = [
231   { id: 'notif-001', title: 'IPFT Date Confirmed', body: 'Next IPFT will be held on 28 July 2026. All
companies must ensure 100% readiness.', type: 'ipft_approved', read: false, createdAt: '2026-07-11T10:00:00Z' },
232   { id: 'notif-002', targetCompany: 'A', title: 'Overweight Soldier Alert', body: 'LCpl Rafiq Uddin
(BD-11002) is overweight. BMI: 30.1. Rehabilitation plan assigned.', type: 'overweight', read: false, createdAt:
'2026-07-10T08:00:00Z' },
233   { id: 'notif-003', title: 'New PT Plans Published', body: 'Week 29 PT plans have been published by 2IC.
Check your assigned plan.', type: 'new_plan', read: true, createdAt: '2026-07-09T07:30:00Z' },
234   { id: 'notif-004', targetUserId: 'sol-a-002', title: 'IPFT Failed - Action Required', body: 'You have
failed the last IPFT. Unfit PT plan assigned. 8 days remaining for next IPFT.', type: 'new_result', read: false,
createdAt: '2026-06-16T09:00:00Z' },
235   { id: 'notif-005', targetCompany: 'B', title: 'Overweight Soldier - Coy B', body: 'Cpl Monir Hossain
(BD-12003) is overweight. BMI: 31.9. Immediate action required.', type: 'overweight', read: false, createdAt:
'2026-07-10T08:00:00Z' },
236 ];
237
238 export const SEED_REPORTS: Report[] = [
239   {
240     id: 'report-001', fromId: 'clerk-001', fromName: 'Cpl Mizanur Rahman', fromRole: 'clerk',
241     toId: 'adjt-001', toRole: 'adjutant', title: 'IPFT Result Report - June 2026',
242     content: 'Total soldiers tested: 13\nPassed: 9 (69.2%)\nFailed: 4 (30.8%)\nOverweight soldiers:
3\n\nCompany-wise breakdown:\nA Coy: 3 Pass, 1 Fail\nB Coy: 2 Pass, 1 Fail\nC Coy: 3 Pass, 0 Fail\nD Coy: 1 Pass,
2 Fail',
243     attachmentLabel: 'IPFT_Result_June2026.pdf', read: false, createdAt: '2026-06-16T14:00:00Z',
244   },
245   {
246     id: 'report-002', fromId: 'clerk-001', fromName: 'Cpl Mizanur Rahman', fromRole: 'clerk',
247     toId: 'adjt-001', toRole: 'adjutant', title: 'Total Strength Report - July 2026',
248     content: 'Overall Unit Strength:\nA Coy: 4 soldiers (3 Fit, 1 Unfit)\nB Coy: 3 soldiers (2 Fit, 1
Unfit)\nC Coy: 3 soldiers (2 Fit, 1 Unfit)\nD Coy: 3 soldiers (1 Fit, 2 Unfit)\n\nTotal Strength: 13\nTotal Fit:
8\nTotal Unfit: 5',
249     attachmentLabel: 'Total_Strength_July2026.pdf', read: true, createdAt: '2026-07-01T09:00:00Z',
250   },
251 ];
252

```

[illegible]

```
83   const soldiers = await getSoldiers();  
84   return soldiers.find(s => s.id === id) ?? null;  
85 }  
86  
87 export async function updateSoldier(id: string, updates: Partial<Soldier>): Promise<void> {  
88   const soldiers = await getSoldiers();  
89   const idx = soldiers.findIndex(s => s.id === id);  
90   if (idx >= 0) {  
91     soldiers[idx] = { ...soldiers[idx], ...updates };  
92     await setAll(KEYS.SOLDIERS, soldiers);  
93   }  
94 }  
95  
96 export async function deleteSoldier(id: string): Promise<void> {  
97   const soldiers = await getSoldiers();  
98   await setAll(KEYS.SOLDIERS, soldiers.filter(s => s.id !== id));  
99 }  
100  
101 export async function addSoldier(soldier: Soldier): Promise<void> {  
102   const soldiers = await getSoldiers();  
103   soldiers.push(soldier);  
104   await setAll(KEYS.SOLDIERS, soldiers);  
105 }  
106  
107 // % PT Plans % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
108 export async function getPTPlans(): Promise<PTPlan[]> { return getAll<PTPlan>(KEYS.PT_PLANS); }  
109  
110 export async function addPTPlan(plan: PTPlan): Promise<void> {  
111   const plans = await getPTPlans();  
112   plans.unshift(plan);  
113   await setAll(KEYS.PT_PLANS, plans);  
114 }  
115  
116 // % IPFT Results % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
117 export async function getIPFTResults(): Promise<IPFTResult[]> { return  
getAll<IPFTResult>(KEYS.IPFT_RESULTS); }  
118  
119 export async function getIPFTResultsBySoldier(soldierId: string): Promise<IPFTResult[]> {  
120   const results = await getIPFTResults();  
121   return results.filter(r => r.soldierId === soldierId).sort((a, b) => b.date.localeCompare(a.date));  
122 }  
123  
124 export async function addIPFTResult(result: IPFTResult): Promise<void> {  
125   const results = await getIPFTResults();  
126   results.unshift(result);  
127   await setAll(KEYS.IPFT_RESULTS, results);  
128 }  
129  
130 // % IPFT Schedule % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
131 export async function getIPFTSchedule(): Promise<IPFTSchedule | null> {  
132   return getItem<IPFTSchedule>(KEYS.IPFT_SCHEDULE);  
133 }  
134  
135 export async function saveIPFTSchedule(schedule: IPFTSchedule): Promise<void> {  
136   await setItem(KEYS.IPFT_SCHEDULE, schedule);  
137 }  
138  
139 // % Notifications % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
140 export async function getNotifications(): Promise<Notification[]> { return  
getAll<Notification>(KEYS.NOTIFICATIONS); }  
141  
142 export async function addNotification(notif: Notification): Promise<void> {  
143   const notif = await getNotifications();  
144   notif.unshift(notif);  
145   await setAll(KEYS.NOTIFICATIONS, notif);  
146 }  
147  
148 export async function markNotificationRead(id: string): Promise<void> {  
149   const notif = await getNotifications();  
150   const idx = notif.findIndex(n => n.id === id);  
151   if (idx >= 0) { notif[idx].read = true; await setAll(KEYS.NOTIFICATIONS, notif); }  
152 }  
153  
154 export async function markAllNotificationsRead(): Promise<void> {  
155   const notif = await getNotifications();  
156   notif.forEach(n => { n.read = true; });  
157   await setAll(KEYS.NOTIFICATIONS, notif);  
158 }  
159  
160 // % Messages % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % % %  
161 export async function getMessages(): Promise<Message[]> { return getAll<Message>(KEYS.MESSAGES); }  
162  
163 export async function addMessage(msg: Message): Promise<void> {  
164   const msgs = await getMessages();  
165   msgs.unshift(msg);
```

[illegible]

```
1 export type UserRole = 'co' | '2ic' | 'coy_comd' | 'adjutant' | 'clerk' | 'soldier';
2 export type Company = 'A' | 'B' | 'C' | 'D';
3 export type SoldierRank = 'Snk' | 'LCpl' | 'Cpl' | 'Sgt' | 'WO' | 'SWO';
4 export type PTStatus = 'fit' | 'unfit' | 'pending';
5 export type BloodGroup = 'A+' | 'A-' | 'B+' | 'B-' | 'AB+' | 'AB-' | 'O+' | 'O-';
6
7 export interface User {
8   id: string;
9   email: string;
10  password: string;
11  role: UserRole;
12  name: string;
13  rank: string;
14  ba: string;
15  company?: Company;
16  phone?: string;
17  bloodGroup?: BloodGroup;
18  medicalCategory?: string;
19  height?: number;
20  weight?: number;
21  age?: number;
22  address?: string;
23  serviceNumber?: string;
24  /** false only for newly self-registered soldiers awaiting Adjutant approval */
25  isApproved?: boolean;
26 }
27
28 export interface Soldier {
29   id: string;
30   serviceNumber: string;
31   name: string;
32   rank: SoldierRank;
33   company: Company;
34   email: string;
35   bloodGroup: BloodGroup;
36   height: number;
37   weight: number;
38   age: number;
39   medicalCategory: string;
40   phone: string;
41   address?: string;
42   isApproved: boolean;
43   isOverweight: boolean;
44   ptStatus: PTStatus;
45   userId: string;
46 }
47
48 export interface PTExercise {
49   name: string;
50   target: string;
51   notes?: string;
52 }
53
54 export interface PTPlanDay {
55   day: string;
56   focus: string;
57   exercises: PTExercise[];
58 }
59
60 export interface PTPlan {
61   id: string;
62   title: string;
63   type: 'fit' | 'unfit';
64   description: string;
65   createdBy: string;
66   createdByName: string;
67   weekNumber: number;
68   days: PTPlanDay[];
69   createdAt: string;
70 }
71
72 export interface IPFTResultItem {
73   name: string;
74   target: string;
75   achieved: string;
76   status: 'pass' | 'fail';
77 }
78
79 export interface IPFTResult {
80   id: string;
81   soldierId: string;
82   soldierName: string;
83   soldierRank: string;
```

```

84     serviceNumber: string;
85     company: Company;
86     date: string;
87     items: IPFTResultItem[];
88     overallStatus: 'pass' | 'fail';
89     recordedBy: string;
90     recordedByName: string;
91     bmi?: number;
92     /** Which half-year IPFT cycle this result belongs to. */
93     biannual?: '1st' | '2nd';
94     /** True for a result the soldier reported from a previous unit at registration, not one recorded by a
Clerk here. */
95     selfReported?: boolean;
96 }
97
98 export interface IPFTSchedule {
99     id: string;
100     proposedDate: string;
101     proposedBy: string;
102     proposedByName: string;
103     status: 'pending' | 'approved' | 'rejected';
104     approvedBy?: string;
105     rejectionNote?: string;
106     alternateDate?: string;
107     createdAt: string;
108 }
109
110 /** Free-form chat between staff roles (co, 2ic, coy_comd, adjutant, clerk). Soldiers do not use messaging.
*/
111 export interface Message {
112     id: string;
113     fromId: string;
114     fromName: string;
115     fromRole: UserRole;
116     toId: string;
117     toRole: UserRole;
118     subject: string;
119     content: string;
120     read: boolean;
121     createdAt: string;
122 }
123
124 export interface Notification {
125     id: string;
126     targetRole?: UserRole;
127     targetCompany?: Company;
128     targetUserId?: string;
129     title: string;
130     body: string;
131     type: 'ipft_approved' | 'ipft_proposed' | 'ipft_rejected' | 'new_result' | 'overweight' | 'new_plan' |
'general';
132     read: boolean;
133     createdAt: string;
134 }
135
136 export interface Report {
137     id: string;
138     fromId: string;
139     fromName: string;
140     fromRole: UserRole;
141     toId: string;
142     toRole: UserRole;
143     title: string;
144     content: string;
145     /** Display filename, e.g. "IPFT_Report_July2026.pdf" */
146     attachmentLabel?: string;
147     /** Relative URL to download the file from the shared data server, e.g. "/files/abc-name.pdf" */
148     attachmentUrl?: string;
149     attachmentMimeType?: string;
150     company?: Company;
151     read: boolean;
152     createdAt: string;
153 }
154

```

lib/upload.ts

```
1 import { Platform } from 'react-native';
2 import * as FileSystem from 'expo-file-system/legacy';
3 import { API_BASE } from './api';
4
5 export interface PickedDocument {
6   uri: string;
7   name: string;
8   mimeType?: string | null;
9   file?: any; // browser File object, present on web only
10 }
11
12 export interface UploadedFile {
13   url: string;
14   name: string;
15   mimeType: string;
16   size?: number;
17 }
18
19 function readWebFileAsBase64(file: File): Promise<string> {
20   return new Promise((resolve, reject) => {
21     const reader = new FileReader();
22     reader.onload = () => {
23       const result = reader.result as string;
24       resolve(result.split(',')[1] ?? '');
25     };
26     reader.onerror = () => reject(reader.error);
27     reader.readAsDataURL(file);
28   });
29 }
30
31 /** Uploads a document picked via expo-document-picker to the shared data server. */
32 export async function uploadDocument(doc: PickedDocument): Promise<UploadedFile> {
33   const base64 = Platform.OS === 'web' && doc.file
34     ? await readWebFileAsBase64(doc.file)
35     : await FileSystem.readAsStringAsync(doc.uri, { encoding: FileSystem.EncodingType.Base64 });
36
37   const res = await fetch(`${API_BASE}/upload`, {
38     method: 'POST',
39     headers: { 'Content-Type': 'application/json' },
40     body: JSON.stringify({ name: doc.name, mimeType: doc.mimeType ?? 'application/octet-stream', base64 }),
41   });
42   if (!res.ok) throw new Error('Upload failed');
43   return res.json();
44 }
45
46 export function fileDownloadUrl(relativeUrl: string): string {
47   return `${API_BASE}${relativeUrl}`;
48 }
49
```

hooks/useColors.ts

```
1 import colors from '@constants/colors';
2
3 /**
4  * Always returns the dark palette regardless of each device's OS theme setting.
5  * The app previously followed each device's system dark/light preference via
6  * useColorScheme(), which made the background (and everything else) look
7  * different across a phone and a laptop whenever their OS themes differed.
8  * Forcing one palette keeps the app visually identical on every device.
9  */
10 export function useColors() {
11   return { ...colors.dark, radius: colors.radius };
12 }
13
```

context/AuthContext.tsx

```
1 import React, { createContext, useContext, useState, useEffect, ReactNode } from 'react';
2 import AsyncStorage from '@react-native-async-storage/async-storage';
3 import { findUserByEmail, initStorage, getUsers, getSoldiers } from '@lib/storage';
4 import type { User } from '@lib/types';
5
6 interface AuthContextType {
7   user: User | null;
8   isLoading: boolean;
9   login: (email: string, password: string) => Promise<{ success: boolean; error?: string }>;
10  logout: () => Promise<void>;
11  refreshUser: () => Promise<void>;
12 }
13
14 const AuthContext = createContext<AuthContextType | null>(null);
15
16 const SESSION_KEY = 'fitforce:session_user_id';
17
18 export function AuthProvider({ children }: { children: ReactNode }) {
19   const [user, setUser] = useState<User | null>(null);
20   const [isLoading, setIsLoading] = useState(true);
21
22   useEffect(() => {
23     (async () => {
24       try {
25         await initStorage();
26         const savedId = await AsyncStorage.getItem(SESSION_KEY);
27         if (savedId) {
28           const users = await getUsers();
29           const found = users.find(u => u.id === savedId);
30           if (found) setUser(found);
31         }
32       } catch (_) {}
33       setIsLoading(false);
34     })();
35   }, []);
36
37   const login = async (email: string, password: string): Promise<{ success: boolean; error?: string }> => {
38     const found = await findUserByEmail(email);
39     if (!found) return { success: false, error: 'No account found with this email.' };
40     if (found.password !== password) return { success: false, error: 'Incorrect password.' };
41
42     // For self-registered soldiers, check Adjutant approval
43     if (found.role === 'soldier') {
44       // Check isApproved on the User record (false = pending approval)
45       if (found.isApproved === false) {
46         // Double-check the Soldier record too
47         const soldiers = await getSoldiers();
48         const soldierRecord = soldiers.find(s => s.userId === found.id);
49         if (!soldierRecord || !soldierRecord.isApproved) {
50           return {
51             success: false,
52             error: 'Your account is pending approval by the Adjutant. Please wait for approval before signing in.',
53           };
54         }
55       }
56     }
57
58     setUser(found);
59     await AsyncStorage.setItem(SESSION_KEY, found.id);
60     return { success: true };
61   };
62
63   const logout = async () => {
64     setUser(null);
65     await AsyncStorage.removeItem(SESSION_KEY);
66   };
67
68   const refreshUser = async () => {
69     const savedId = await AsyncStorage.getItem(SESSION_KEY);
70     if (!savedId) return;
71     const users = await getUsers();
72     const found = users.find(u => u.id === savedId);
73     if (found) setUser(found);
74   };
75
76   return (
77     <AuthContext.Provider value={{ user, isLoading, login, logout, refreshUser }}>
78       {children}
79     </AuthContext.Provider>
80   );
81 }
82
```

```
83 export function useAuth() {  
84   const ctx = useContext(AuthContext);  
85   if (!ctx) throw new Error('useAuth must be used within AuthProvider');  
86   return ctx;  
87 }  
88
```

constants/colors.ts

```
1  const colors = {
2    light: {
3      text: '#1A1A1A',
4      tint: '#1B5E3B',
5
6      background: '#F4F5F0',
7      foreground: '#1A1A1A',
8
9      card: '#FFFFFF',
10     cardForeground: '#1A1A1A',
11
12     primary: '#1B5E3B',
13     primaryForeground: '#FFFFFF',
14
15     secondary: '#E8EDE5',
16     secondaryForeground: '#2D4A3A',
17
18     muted: '#EEF0EB',
19     mutedForeground: '#6B7A6D',
20
21     accent: '#C5A028',
22     accentForeground: '#1A1A1A',
23
24     destructive: '#C62828',
25     destructiveForeground: '#FFFFFF',
26
27     success: '#2E7D32',
28     successForeground: '#FFFFFF',
29
30     warning: '#E65100',
31     warningForeground: '#FFFFFF',
32
33     border: '#D5D9D0',
34     input: '#D5D9D0',
35
36     roleColors: {
37       co: '#1B3A4B',
38       '2ic': '#1B5E3B',
39       coy_comd: '#4A1B5E',
40       adjutant: '#5E3A1B',
41       clerk: '#1B4A5E',
42       soldier: '#2E5E1B',
43     } as Record<string, string>,
44   },
45
46   dark: {
47     text: '#ECEEE9',
48     tint: '#4CAF70',
49
50     background: '#0D1810',
51     foreground: '#ECEEE9',
52
53     card: '#1A2D1E',
54     cardForeground: '#ECEEE9',
55
56     primary: '#4CAF70',
57     primaryForeground: '#0D1810',
58
59     secondary: '#1E3025',
60     secondaryForeground: '#B8D4BE',
61
62     muted: '#1E3025',
63     mutedForeground: '#8AA890',
64
65     accent: '#D4A830',
66     accentForeground: '#0D1810',
67
68     destructive: '#EF5350',
69     destructiveForeground: '#FFFFFF',
70
71     success: '#66BB6A',
72     successForeground: '#0D1810',
73
74     warning: '#FF7043',
75     warningForeground: '#FFFFFF',
76
77     border: '#2A4030',
78     input: '#2A4030',
79
80     roleColors: {
81       co: '#3A7A9C',
82       '2ic': '#4CAF70',
83       coy_comd: '#9C5ABF',
```

```
84         adjutant: '#BF8A5A',
85         clerk: '#5A9CBF',
86         soldier: '#6ABF4C',
87     } as Record<string, string>,
88 },
89
90     radius: 10,
91 };
92
93 export default colors;
94
```

components/AppHeader.tsx

```
1 import React from 'react';
2 import { View, Text, Image, StyleSheet, Platform } from 'react-native';
3 import { useSafeAreaInsets } from 'react-native-safe-area-context';
4 import { useColors } from '@hooks/useColors';
5
6 export function AppHeader() {
7   const colors = useColors();
8   const insets = useSafeAreaInsets();
9   const isWeb = Platform.OS === 'web';
10  // On web: account for 67px Replit preview bar overlay
11  // On native: account for device status bar (insets.top)
12  const topPad = isWeb ? 67 : insets.top;
13
14  return (
15    <View style={[styles.container, { backgroundColor: colors.primary, paddingTop: topPad }]}>
16      <View style={styles.inner}>
17        <View style={[styles.logowrap, { borderColor: colors.accent }]}>
18          <Image
19            source={require('@assets/images/fitforce-logo.jpg')}
20            style={styles.logo}
21            resizeMode="cover"
22          />
23        </View>
24        <View style={styles.textWrap}>
25          <Text style={styles.title}>Fit Force</Text>
26          <Text style={styles.subtitle}>Soldier Fitness Assessment System</Text>
27        </View>
28      </View>
29    </View>
30  );
31 }
32
33 const styles = StyleSheet.create({
34   container: {
35     width: '100%',
36   },
37   inner: {
38     flexDirection: 'row',
39     alignItems: 'center',
40     paddingHorizontal: 14,
41     paddingVertical: 10,
42     gap: 12,
43     height: 68,
44   },
45   logowrap: {
46     width: 52,
47     height: 52,
48     borderRadius: 26,
49     borderWidth: 2.5,
50     overflow: 'hidden',
51   },
52   logo: {
53     width: '100%',
54     height: '100%',
55   },
56   textWrap: {
57     flex: 1,
58     gap: 2,
59   },
60   title: {
61     fontSize: 19,
62     fontFamily: 'Inter_700Bold',
63     color: 'FFFFFF',
64     letterSpacing: 0.5,
65   },
66   subtitle: {
67     fontSize: 11,
68     fontFamily: 'Inter_400Regular',
69     color: 'rgba(255,255,255,0.75)',
70     letterSpacing: 0.3,
71   },
72 });
73
```

components/BarChart.tsx

```
1  import React from 'react';
2  import { View, Text, StyleSheet } from 'react-native';
3
4  export interface BarDatum {
5    label: string;
6    value: number;
7    color: string;
8    sublabel?: string;
9  }
10
11 interface BarChartProps {
12   data: BarDatum[];
13   maxValue?: number;
14   height?: number;
15   unit?: string;
16   labelColor: string;
17   subColor: string;
18   trackColor: string;
19 }
20
21 export function BarChart({ data, maxValue, height = 120, unit = '', labelColor, subColor, trackColor }:
BarChartProps) {
22   const max = maxValue ?? Math.max(1, ...data.map(d => d.value));
23   return (
24     <View style={styles.wrap}>
25       {data.map((d, i) => {
26         const pct = d.value > 0 ? Math.max(4, Math.round((d.value / max) * 100)) : 0;
27         return (
28           <View key={i} style={styles.col}>
29             <Text style={[styles.value, { color: d.color }]} numberOfLines={1}>{d.value}{unit}</Text>
30             <View style={[styles.track, { height, backgroundColor: trackColor }]}>
31               <View style={styles.bar, { height: `${pct}%`, backgroundColor: d.color }} />
32             </View>
33             <Text style={styles.label, { color: labelColor }} numberOfLines={1}>{d.label}</Text>
34             {d.sublabel ? <Text style={styles.sublabel, { color: subColor }} numberOfLines={1}
>{d.sublabel}</Text> : null}
35           </View>
36         );
37       })}
38     </View>
39   );
40 }
41
42 const styles = StyleSheet.create({
43   wrap: { flexDirection: 'row', alignItems: 'flex-end', justifyContent: 'space-around', gap: 8 },
44   col: { alignItems: 'center', flex: 1, gap: 6 },
45   value: { fontSize: 11, fontFamily: 'Inter_700Bold' },
46   track: { width: '68%', maxWidth: 36, borderRadius: 8, justifyContent: 'flex-end', overflow: 'hidden' },
47   bar: { width: '100%', borderRadius: 8 },
48   label: { fontSize: 10, fontFamily: 'Inter_600SemiBold', marginTop: 2 },
49   sublabel: { fontSize: 9, fontFamily: 'Inter_400Regular' },
50 });
51
```

components/Calendar.tsx

```
1  import React, { useState } from 'react';
2  import { View, Text, StyleSheet, TouchableOpacity } from 'react-native';
3  import { Feather } from '@expo/vector-icons';
4  import * as Haptics from 'expo-haptics';
5
6  const WEEKDAY_LABELS = ['S', 'M', 'T', 'W', 'T', 'F', 'S'];
7  const MONTH_NAMES = [
8    'January', 'February', 'March', 'April', 'May', 'June',
9    'July', 'August', 'September', 'October', 'November', 'December',
10 ];
11
12 function toISODate(y: number, m: number, d: number): string {
13   return `${y}-${String(m + 1).padStart(2, '0')}-${String(d).padStart(2, '0')}`;
14 }
15
16 interface CalendarProps {
17   value: string;
18   onChange: (date: string) => void;
19   minDate?: string;
20   colors: {
21     foreground: string;
22     mutedForeground: string;
23     primary: string;
24     border: string;
25     card: string;
26     muted: string;
27   };
28 }
29
30 export function Calendar({ value, onChange, minDate, colors }: CalendarProps) {
31   const initial = value ? new Date(value + 'T00:00:00') : new Date();
32   const [viewYear, setViewYear] = useState(initial.getFullYear());
33   const [viewMonth, setViewMonth] = useState(initial.getMonth());
34
35   const min = minDate ? new Date(minDate + 'T00:00:00') : null;
36
37   const firstOfMonth = new Date(viewYear, viewMonth, 1);
38   const startWeekday = firstOfMonth.getDay();
39   const daysInMonth = new Date(viewYear, viewMonth + 1, 0).getDate();
40
41   const cells: (number | null)[] = [
42     ...Array(startWeekday).fill(null),
43     ...Array.from({ length: daysInMonth }, (_, i) => i + 1),
44   ];
45   while (cells.length % 7 !== 0) cells.push(null);
46
47   const goPrevMonth = () => {
48     Haptics.selectionAsync();
49     if (viewMonth === 0) { setViewMonth(11); setViewYear(viewYear - 1); } else { setViewMonth(viewMonth -
50 1); }
51   };
52   const goNextMonth = () => {
53     Haptics.selectionAsync();
54     if (viewMonth === 11) { setViewMonth(0); setViewYear(viewYear + 1); } else { setViewMonth(viewMonth +
55 1); }
56   };
57
58   return (
59     <View style={[styles.wrap, { borderColor: colors.border, backgroundColor: colors.card }]}>
60       <View style={styles.header}>
61         <TouchableOpacity onPress={goPrevMonth} style={styles.navBtn} hitSlop={8}>
62           <Feather name="chevron-left" size={18} color={colors.foreground} />
63         </TouchableOpacity>
64         <Text style={[styles.headerText, { color: colors.foreground }]}>{MONTH_NAMES[viewMonth]} {viewYear}</Text>
65         <TouchableOpacity onPress={goNextMonth} style={styles.navBtn} hitSlop={8}>
66           <Feather name="chevron-right" size={18} color={colors.foreground} />
67         </TouchableOpacity>
68       </View>
69
70       <View style={styles.weekRow}>
71         {WEEKDAY_LABELS.map((w, i) => (
72           <Text key={i} style={[styles.weekdayLabel, { color: colors.mutedForeground }]}>{w}</Text>
73         ))}
74       </View>
75
76       <View style={styles.grid}>
77         {cells.map((day, i) => {
78           if (day === null) return <View key={i} style={styles.cell} />;
79           const iso = toISODate(viewYear, viewMonth, day);
80           const isSelected = iso === value;
81           const cellDate = new Date(viewYear, viewMonth, day);
82           const isDisabled = min ? cellDate < min : false;
94       </View>
83     </View>
84   );
85 }
```

```

81         return (
82             <TouchableOpacity
83                 key={i}
84                 style={[styles.cell, styles.dayCell, isSelected && { backgroundColor: colors.primary }]}
85                 disabled={isDisabled}
86                 onPress={() => { Haptics.selectionAsync(); onChange(iso); }}
87                 activeOpacity={0.7}
88             >
89                 <Text style={[
90                     styles.dayText,
91                     { color: isSelected ? '#FFF' : isDisabled ? colors.mutedForeground : colors.foreground },
92                     isDisabled && { opacity: 0.35 },
93                 ]}>
94                     {day}
95                 </Text>
96             </TouchableOpacity>
97         );
98     }
99 </View>
100 </View>
101 );
102 }
103
104 const styles = StyleSheet.create({
105     wrap: { borderWidth: 1, borderRadius: 12, padding: 12 },
106     header: { flexDirection: 'row', alignItems: 'center', justifyContent: 'space-between', marginBottom: 10 },
107     headerText: { fontSize: 14, fontFamily: 'Inter_700Bold' },
108     navBtn: { padding: 4 },
109     weekRow: { flexDirection: 'row', marginBottom: 4 },
110     weekdayLabel: { flex: 1, textAlign: 'center', fontSize: 11, fontFamily: 'Inter_600SemiBold' },
111     grid: { flexDirection: 'row', flexWrap: 'wrap' },
112     cell: { width: `${100 / 7}%`, aspectRatio: 1, alignItems: 'center', justifyContent: 'center' },
113     dayCell: { borderRadius: 8 },
114     dayText: { fontSize: 13, fontFamily: 'Inter_500Medium' },
115 });
116

```

components/ErrorMessage.tsx

```
1 import React, { Component, ComponentType, PropsWithChildren } from 'react';
2 import { ErrorFallback, ErrorFallbackProps } from '@components/ErrorFallback';
3
4 export type ErrorBoundaryProps = PropsWithChildren<{
5   fallbackComponent?: ComponentType<ErrorFallbackProps>;
6   onError?: (error: Error, stackTrace: string) => void;
7 }>;
8
9 type ErrorBoundaryState = { error: Error | null };
10
11 export class ErrorBoundary extends Component<ErrorBoundaryProps, ErrorBoundaryState> {
12   state: ErrorBoundaryState = { error: null };
13
14   static defaultProps: { fallbackComponent: ComponentType<ErrorFallbackProps> } = {
15     fallbackComponent: ErrorFallback,
16   };
17
18   static getDerivedStateFromError(error: Error): ErrorBoundaryState {
19     return { error };
20   }
21
22   componentDidCatch(error: Error, info: { componentStack: string }): void {
23     if (typeof this.props.onError === 'function') {
24       this.props.onError(error, info.componentStack);
25     }
26   }
27
28   resetError = (): void => {
29     this.setState({ error: null });
30   };
31
32   render() {
33     const { fallbackComponent } = this.props;
34     return this.state.error && fallbackComponent ? (
35       <fallbackComponent error={this.state.error} resetError={this.resetError} />
36     ) : (
37       this.props.children
38     );
39   }
40 }
41
```

components/ErrorFallback.tsx

```
1 import React, { useState } from 'react';
2 import { Modal, Platform, Pressable, ScrollView, StyleSheet, Text, View } from 'react-native';
3 import { useSafeAreaInsets } from 'react-native-safe-area-context';
4 import { useColors } from '@hooks/useColors';
5 import { Feather } from '@expo/vector-icons';
6 import { reloadAppAsync } from 'expo';
7
8 export type ErrorFallbackProps = {
9   error: Error;
10  resetError: () => void;
11 };
12
13 export function ErrorFallback({ error, resetError }: ErrorFallbackProps) {
14   const colors = useColors();
15   const insets = useSafeAreaInsets();
16   const [isModalVisible, setIsModalVisible] = useState(false);
17
18   const handleRestart = async () => {
19     try {
20       await reloadAppAsync();
21     } catch (restartError) {
22       console.error('Failed to restart app:', restartError);
23       resetError();
24     }
25   };
26
27   const formatErrorDetails = (): string => {
28     let details = `Error: ${error.message}\n\n`;
29     if (error.stack) details += `Stack Trace:\n${error.stack}`;
30     return details;
31   };
32
33   const monoFont = Platform.select({ ios: 'Menlo', android: 'monospace', default: 'monospace' });
34
35   return (
36     <View style={[styles.container, { backgroundColor: colors.background }]}>
37       {__DEV__ ? (
38         <Pressable onPress={() => setIsModalVisible(true)} style={({ pressed }) => [styles.topButton,
39 { top: insets.top + 16, backgroundColor: colors.card, opacity: pressed ? 0.8 : 1 }]}>
40           <Feather name="alert-circle" size={20} color={colors.foreground} />
41         </Pressable>
42       ) : null}
43       <View style={styles.content}>
44         <Text style={[styles.title, { color: colors.foreground }]}>Something went wrong</Text>
45         <Text style={[styles.message, { color: colors.mutedForeground }]}>Please reload the app to
46 continue.</Text>
47         <Pressable onPress={handleRestart} style={({ pressed }) => [styles.button, { backgroundColor:
48 colors.primary, opacity: pressed ? 0.9 : 1 }]}>
49           <Text style={[styles.buttonText, { color: colors.primaryForeground }]}>Try Again</Text>
50         </Pressable>
51       </View>
52       {__DEV__ ? (
53         <Modal visible={isModalVisible} animationType="slide" transparent onRequestClose={() =>
54 setIsModalVisible(false)}>
55           <View style={styles.modalOverlay}>
56             <View style={[styles.modalContainer, { backgroundColor: colors.background }]}>
57               <View style={[styles.modalHeader, { borderBottomColor: colors.border }]}>
58                 <Text style={[styles.modalTitle, { color: colors.foreground }]}>Error Details</Text>
59                 <Pressable onPress={() => setIsModalVisible(false)} style={({ pressed }) =>
60 [styles.closeButton, { opacity: pressed ? 0.6 : 1 }]}>
61                   <Feather name="x" size={24} color={colors.foreground} />
62                 </Pressable>
63               </View>
64               <ScrollView style={styles.modalScrollView} contentContainerStyle={[styles.modalScrollContent,
65 { paddingBottom: insets.bottom + 16 }]}>
66                 <View style={[styles.errorContainer, { backgroundColor: colors.card }]}>
67                   <Text style={[styles.errorText, { color: colors.foreground, fontFamily: monoFont }]}
68 selectable>{formatErrorDetails()}</Text>
69                 </View>
70               </ScrollView>
71             </View>
72           </Modal>
73         ) : null}
74     </View>
75   );
76 }
77
78 const styles = StyleSheet.create({
79   container: { flex: 1, width: '100%', height: '100%', justifyContent: 'center', alignItems: 'center',
80 padding: 24 },
81   content: { alignItems: 'center', justifyContent: 'center', gap: 16, width: '100%', maxWidth: 600 },
82   title: { fontSize: 28, fontWeight: '700', textAlign: 'center', lineHeight: 40 },
83   message: {
84     color: colors.mutedForeground,
85     text-align: 'center',
86     font-family: monoFont,
87     line-height: 1.5,
88     padding: 0 16,
89     margin: 16 0,
90   },
91   button: {
92     width: 120,
93     height: 32,
94     borderRadius: 16,
95     backgroundColor: colors.primary,
96     opacity: 0.9,
97     margin: 16 0,
98   },
99   buttonText: {
100    color: colors.primaryForeground,
101    text-align: 'center',
102    font-weight: '700',
103    line-height: 1,
104  },
105   topButton: {
106    width: 40,
107    height: 40,
108    borderRadius: 20,
109    backgroundColor: colors.card,
110    opacity: 0.8,
111    margin: 0 auto,
112  },
113   modalOverlay: {
114    width: '100%',
115    height: '100%',
116    backgroundColor: 'transparent',
117    position: 'relative',
118  },
119   modalContainer: {
120    width: '100%',
121    height: '100%',
122    backgroundColor: colors.background,
123    position: 'relative',
124  },
125   modalHeader: {
126    width: '100%',
127    height: 40,
128    borderBottomColor: colors.border,
129    position: 'relative',
130  },
131   modalTitle: {
132    color: colors.foreground,
133    font-weight: '700',
134    text-align: 'center',
135    line-height: 1,
136    padding: 0 16,
137  },
138   closeButton: {
139    width: 40,
140    height: 40,
141    borderRadius: 20,
142    backgroundColor: colors.card,
143    opacity: 0.6,
144    margin: 0 auto,
145  },
146   modalScrollView: {
147    width: '100%',
148    height: '100%',
149    padding: 0 16,
150  },
151   modalScrollContent: {
152    width: '100%',
153    height: '100%',
154  },
155   errorContainer: {
156    width: '100%',
157    height: 100,
158    backgroundColor: colors.card,
159    position: 'relative',
160  },
161   errorText: {
162    color: colors.foreground,
163    font-family: monoFont,
164    line-height: 1.5,
165    padding: 16 16 0 16,
166  },
167 });
```

```
76   message: { fontSize: 16, textAlign: 'center', lineHeight: 24 },
77   topButton: { position: 'absolute', right: 16, width: 44, height: 44, borderRadius: 8, flexDirection:
'row', alignItems: 'center', justifyContent: 'center', zIndex: 10 },
78   button: { paddingVertical: 16, borderRadius: 8, paddingHorizontal: 24, minWidth: 200 },
79   buttonText: { fontWeight: '600', textAlign: 'center', fontSize: 16 },
80   modalOverlay: { flex: 1, backgroundColor: 'rgba(0,0,0,0.5)', justifyContent: 'flex-end' },
81   modalContainer: { width: '100%', height: '90%', borderTopLeftRadius: 16, borderTopRightRadius: 16 },
82   modalHeader: { flexDirection: 'row', justifyContent: 'space-between', alignItems: 'center',
paddingHorizontal: 16, paddingTop: 16, paddingBottom: 12, borderBottomWidth: 1 },
83   modalTitle: { fontSize: 20, fontWeight: '600' },
84   closeButton: { width: 44, height: 44, alignItems: 'center', justifyContent: 'center' },
85   modalScrollView: { flex: 1 },
86   modalScrollContent: { padding: 16 },
87   errorContainer: { width: '100%', borderRadius: 8, overflow: 'hidden', padding: 16 },
88   errorText: { fontSize: 12, lineHeight: 18, width: '100%' },
89 });
90
```

components/KeyboardAwareScrollViewCompat.tsx

```
1 import { Platform, ScrollView, ScrollViewProps } from 'react-native';
2 import { KeyboardAwareScrollView, KeyboardAwareScrollViewProps } from 'react-native-keyboard-controller';
3
4 type Props = KeyboardAwareScrollViewProps & ScrollViewProps;
5
6 export function KeyboardAwareScrollViewCompat({ children, keyboardShouldPersistTaps =
'handled', ...props }: Props) {
7   if (Platform.OS === 'web') {
8     return (
9       <ScrollView keyboardShouldPersistTaps={keyboardShouldPersistTaps} {...props}>
10         {children}
11       </ScrollView>
12     );
13   }
14   return (
15     <KeyboardAwareScrollView keyboardShouldPersistTaps={keyboardShouldPersistTaps} {...props}>
16       {children}
17     </KeyboardAwareScrollView>
18   );
19 }
20
```

app/_layout.tsx

```
1 import React, { useEffect } from 'react';
2 import { QueryClient, QueryClientProvider } from '@tanstack/react-query';
3 import { GestureHandlerRootView } from 'react-native-gesture-handler';
4 import { KeyboardProvider } from 'react-native-keyboard-controller';
5 import { SafeAreaProvider } from 'react-native-safe-area-context';
6 import { ErrorBoundary } from '@components/ErrorBoundary';
7 import {
8   Inter_400Regular,
9   Inter_500Medium,
10  Inter_600SemiBold,
11  Inter_700Bold,
12  useFonts,
13 } from '@expo-google-fonts/inter';
14 import { Ionicons, Feather, MaterialCommunityIcons } from '@expo/vector-icons';
15 import { Stack } from 'expo-router';
16 import * as SplashScreen from 'expo-splash-screen';
17 import { StatusBar } from 'expo-status-bar';
18 import { AuthProvider } from '@context/AuthContext';
19
20 SplashScreen.preventAutoHideAsync();
21
22 const queryClient = new QueryClient();
23
24 function RootLayoutNav() {
25   return (
26     <Stack screenOptions={{ headerShown: false }}>
27       <Stack.Screen name="index" />
28       <Stack.Screen name="(auth)" />
29       <Stack.Screen name="(tabs)" />
30       <Stack.Screen name="soldier/[id]" options={{ headerShown: false }} />
31       <Stack.Screen name="plan/[id]" options={{ headerShown: false }} />
32       <Stack.Screen name="plan/new" options={{ headerShown: false }} />
33       <Stack.Screen name="result/new" options={{ headerShown: false }} />
34     </Stack>
35   );
36 }
37
38 export default function RootLayout() {
39   const [fontsLoaded, fontError] = useFonts({
40     Inter_400Regular,
41     Inter_500Medium,
42     Inter_600SemiBold,
43     Inter_700Bold,
44     // Preload icon fonts so they render on native devices
45     ...Ionicons.font,
46     ...Feather.font,
47     ...MaterialCommunityIcons.font,
48   });
49
50   useEffect(() => {
51     if (fontsLoaded || fontError) {
52       SplashScreen.hideAsync();
53     }
54   }, [fontsLoaded, fontError]);
55
56   if (!fontsLoaded && !fontError) return null;
57
58   return (
59     <SafeAreaProvider>
60       <ErrorBoundary>
61         <QueryClientProvider client={queryClient}>
62           <AuthProvider>
63             <GestureHandlerRootView style={{ flex: 1 }}>
64               <KeyboardProvider>
65                 <StatusBar style="light" />
66                 <RootLayoutNav />
67               </KeyboardProvider>
68             </GestureHandlerRootView>
69           </AuthProvider>
70         </QueryClientProvider>
71       </ErrorBoundary>
72     </SafeAreaProvider>
73   );
74 }
75
```

app/(auth)/_layout.tsx

```
1 import { Stack } from 'expo-router';
2
3 export default function AuthLayout() {
4   return <Stack screenOptions={{ headerShown: false }} />;
5 }
6
```

app/auth/login.tsx

```
1  import React, { useState } from 'react';
2  import {
3    View, Text, StyleSheet, TextInput, TouchableOpacity,
4    ScrollView, Platform, Modal, FlatList, ActivityIndicator, Image,
5  } from 'react-native';
6  import { useSafeAreaInsets } from 'react-native-safe-area-context';
7  import { router } from 'expo-router';
8  import { Ionicons, MaterialCommunityIcons } from '@expo/vector-icons';
9  import * as Haptics from 'expo-haptics';
10 import { useAuth } from '@context/AuthContext';
11 import { useColors } from '@hooks/useColors';
12 import type { UserRole } from '@lib/types';
13
14 interface RoleOption {
15   role: UserRole;
16   label: string;
17   email: string;
18   password: string;
19   description: string;
20   icon: string;
21 }
22
23 const ROLE_OPTIONS: RoleOption[] = [
24   { role: 'co', label: 'Commanding Officer (CO)', email: 'co@gmail.com', password: 'co123', description:
25 'Lt Col – Battalion Commander', icon: 'shield-star' },
26   { role: '2ic', label: 'Second in Command (2IC)', email: '2ic@gmail.com', password: '2ic123', description:
27 'Maj – Deputy Commander', icon: 'shield-half-full' },
28   { role: 'coy_comd', label: 'Company Commander (Coy Comd)', email: '', password: '', description: 'Maj – A/
29 B/C/D Company', icon: 'account-group' },
30   { role: 'adjutant', label: 'Adjutant', email: 'adjt@gmail.com', password: 'adjt123', description: 'Capt –
31 Administration Officer', icon: 'file-document' },
32   { role: 'clerk', label: 'Clerk', email: 'clerk@gmail.com', password: 'clerk123', description: 'Cpl –
33 Record Keeper', icon: 'clipboard-text' },
34   { role: 'soldier', label: 'Soldier', email: '', password: 'soldier123', description: 'Snk/LCpl/Cpl/Sgt –
35 Rank & File', icon: 'run' },
36 ];
37
38 const COY_CMD_OPTIONS = [
39   { label: 'A Coy Commander', email: 'acoycomd@gmail.com', password: 'coya123' },
40   { label: 'B Coy Commander', email: 'bcoycomd@gmail.com', password: 'coyb123' },
41   { label: 'C Coy Commander', email: 'ccoycomd@gmail.com', password: 'coyc123' },
42   { label: 'D Coy Commander', email: 'dcoycomd@gmail.com', password: 'coyd123' },
43 ];
44
45 export default function LoginScreen() {
46   const colors = useColors();
47   const insets = useSafeAreaInsets();
48   const { login } = useAuth();
49   const isWeb = Platform.OS === 'web';
50
51   const [selectedRole, setSelectedRole] = useState<RoleOption | null>(null);
52   const [email, setEmail] = useState('');
53   const [password, setPassword] = useState('');
54   const [showPassword, setShowPassword] = useState(false);
55   const [roleModalVisible, setRoleModalVisible] = useState(false);
56   const [coyModalVisible, setCoyModalVisible] = useState(false);
57   const [isLoading, setIsLoading] = useState(false);
58   const [error, setError] = useState('');
59
60   const handleRoleSelect = (option: RoleOption) => {
61     Haptics.impactAsync(Haptics.ImpactFeedbackStyle.Light);
62     setSelectedRole(option);
63     setRoleModalVisible(false);
64     setError('');
65     if (option.role === 'coy_comd') {
66       setCoyModalVisible(true);
67       setEmail('');
68       setPassword('');
69     } else if (option.role === 'soldier') {
70       setEmail('');
71       setPassword('soldier123');
72     } else {
73       setEmail(option.email);
74       setPassword(option.password);
75     }
76   };
77
78   const handleCoySelect = (coy: typeof COY_CMD_OPTIONS[0]) => {
79     Haptics.impactAsync(Haptics.ImpactFeedbackStyle.Light);
80     setEmail(coy.email);
81     setPassword(coy.password);
82     setCoyModalVisible(false);
83   };
84 }
```

```

78
79 const handleLogin = async () => {
80   if (!email.trim() || !password.trim()) {
81     setError('Please enter email and password.');
```

```

82     return;
83   }
84   setIsLoading(true);
85   setError('');
86   Haptics.impactAsync(Haptics.ImpactFeedbackStyle.Medium);
87   const result = await login(email.trim().toLowerCase(), password.trim());
88   setIsLoading(false);
89   if (result.success) {
90     router.replace('/(tabs)');
```

```

91   } else {
92     setError(result.error ?? 'Login failed.');
```

```

93     Haptics.notificationAsync(Haptics.NotificationFeedbackType.Error);
94   }
95 };
96
97 const paddingTop = isWeb ? 67 + insets.top + 12 : insets.top + 20;
98
99 return (
100   <View style={[styles.root, { backgroundColor: colors.background }]}>
101     <ScrollView contentContainerStyle={[styles.container, { paddingTop, paddingBottom: isWeb ? 34 :
insets.bottom + 24 }]} keyboardShouldPersistTaps="handled">
102       {/* % % Logo Header % % */}
103       <View style={styles.header}>
104         <View style={[styles.logoCircle, { borderColor: colors.accent, shadowColor: colors.primary }]}>
105           <Image
106             source={require('@assets/images/fitforce-logo.jpg')}
107             style={styles.logoImg}
108             resizeMode="cover"
109           />
110         </View>
111         <Text style={[styles.appName, { color: colors.foreground }]}>FIT FORCE</Text>
112         <Text style={[styles.tagline, { color: colors.mutedForeground }]}>Soldier Fitness Assessment
System</Text>
113         <View style={[styles.divider, { backgroundColor: colors.accent }]} />
114       </View>
115
116       {/* % % Form % % */}
117       <View style={[styles.form, { backgroundColor: colors.card }]}>
118         {/* Role picker */}
119         <Text style={[styles.sectionLabel, { color: colors.mutedForeground }]}>ROLE</Text>
120         <TouchableOpacity style={[styles.roleSelector, { borderColor: colors.border, backgroundColor:
colors.background }]} onPress={() => setRoleModalVisible(true)} activeOpacity={0.8}>
121           <MaterialCommunityIcons name={{selectedRole?.icon ?? 'shield-outline'} as any} size={20}
color={selectedRole ? colors.accent : colors.mutedForeground} />
122           <Text style={[styles.roleSelectorText, { color: selectedRole ? colors.foreground :
colors.mutedForeground }]}>
123             {selectedRole ? selectedRole.label : 'Select your role'}
124           </Text>
125           <Ionicons name="chevron-down" size={18} color={colors.mutedForeground} />
126           </TouchableOpacity>
127           {selectedRole && <Text style={[styles.roleDesc, { color: colors.accent }]}
>{selectedRole.description}</Text>}
128         </View>
129
130         {/* Email */}
131         <Text style={[styles.sectionLabel, { color: colors.mutedForeground, marginTop: 20 }]}>EMAIL</Text>
132         <View style={[styles.inputWrapper, { borderColor: colors.border, backgroundColor:
colors.background }]}>
133           <Ionicons name="mail-outline" size={18} color={colors.mutedForeground}
style={styles.inputIcon} />
134           <TextInput
135             style={styles.input, { color: colors.foreground }}
136             value={email} onChangeText={t => { setEmail(t); setError(''); }}
137             placeholder="Enter email address" placeholderTextColor={colors.mutedForeground}
138             keyboardType="email-address" autoCapitalize="none" autoCorrect={false}
139           />
140         </View>
141
142         {/* Password */}
143         <Text style={[styles.sectionLabel, { color: colors.mutedForeground, marginTop: 16 }]}>PASSWORD</
Text>
144         <View style={[styles.inputWrapper, { borderColor: colors.border, backgroundColor:
colors.background }]}>
145           <Ionicons name="lock-closed-outline" size={18} color={colors.mutedForeground}
style={styles.inputIcon} />
146           <TextInput
147             style={styles.input, { flex: 1, color: colors.foreground }}
148             value={password} onChangeText={t => { setPassword(t); setError(''); }}
149             placeholder="Enter password" placeholderTextColor={colors.mutedForeground}
150             secureTextEntry={!showPassword}
151           />

```

```

152         <TouchableOpacity onPress={() => setShowPassword(v => !v)} style={styles.eyeBtn}>
153             <Icons name={showPassword ? 'eye-off-outline' : 'eye-outline'} size={18}
color={colors.mutedForeground} />
154         </TouchableOpacity>
155     </View>
156
157     {/* Error */}
158     {!!error && (
159         <View style={[styles.errorBox, { backgroundColor: colors.destructive + '18' }]}>
160             <Icons name="alert-circle" size={16} color={colors.destructive} />
161             <Text style={[styles.errorText, { color: colors.destructive }]}>{error}</Text>
162         </View>
163     )}
164
165     {/* Sign In Button */}
166     <TouchableOpacity
167         style={styles.loginBtn, { backgroundColor: colors.primary, shadowColor: colors.primary },
isLoading && { opacity: 0.7 }}
168         onPress={handleLogin} disabled={isLoading} activeOpacity={0.85}>
169         {isLoading ? <ActivityIndicator color="#FFF" /> : (
170             <>
171                 <Icons name="log-in-outline" size={20} color="#FFF" />
172                 <Text style={styles.loginBtnText}>SIGN IN</Text>
173             </>
174         )}
175     </TouchableOpacity>
176 </View>
177
178     {/* % % Register Link % % */}
179     <TouchableOpacity style={styles.registerLinkWrap} onPress={() => router.push('/(auth)/register')}
activeOpacity={0.7}>
180         <Text style={[styles.registerLinkText, { color: colors.mutedForeground }]}>
181             New soldier?{' '}
182             <Text style={[styles.registerLinkBold, { color: colors.primary }]}>Register here</Text>
183         </Text>
184     </TouchableOpacity>
185
186     <Text style={[styles.footer, { color: colors.mutedForeground }]}>Bangladesh Army – Fitness
Monitoring System</Text>
187 </ScrollView>
188
189     {/* Role Modal */}
190     <Modal visible={roleModalVisible} transparent animationType="slide" onRequestClose={() =>
setRoleModalVisible(false)}>
191         <TouchableOpacity style={styles.modalOverlay} onPress={() => setRoleModalVisible(false)}
activeOpacity={1}>
192             <View style={[styles.modalSheet, { backgroundColor: colors.card, paddingBottom: insets.bottom +
16 }]}>
193                 <View style={styles.modalHandle} />
194                 <Text style={[styles.modalTitle, { color: colors.foreground }]}>Select Role</Text>
195                 <FlatList
196                     data={ROLE_OPTIONS} keyExtractor={i => i.role}
197                     renderItem={({ item }) => (
198                         <TouchableOpacity style={[styles.roleItem, { borderBottomColor: colors.border }]}
onPress={() => handleRoleSelect(item)} activeOpacity={0.75}>
199                             <View style={[styles.roleItemIcon, { backgroundColor: colors.muted }]}>
200                                 <MaterialCommunityIcons name={item.icon as any} size={22} color={colors.primary} />
201                             </View>
202                             <View style={{ flex: 1 }}>
203                                 <Text style={[styles.roleItemLabel, { color: colors.foreground }]}>{item.label}</Text>
204                                 <Text style={[styles.roleItemDesc, { color: colors.mutedForeground }]}>
>{item.description}</Text>
205                             </View>
206                             {selectedRole?.role === item.role && <Icons name="checkmark-circle" size={20}
color={colors.primary} />}
207                         </TouchableOpacity>
208                     )}
209                 </>
210             </View>
211         </TouchableOpacity>
212     </Modal>
213
214     {/* Coy Modal */}
215     <Modal visible={coyModalVisible} transparent animationType="slide" onRequestClose={() =>
setCoyModalVisible(false)}>
216         <TouchableOpacity style={styles.modalOverlay} onPress={() => setCoyModalVisible(false)}
activeOpacity={1}>
217             <View style={[styles.modalSheet, { backgroundColor: colors.card, paddingBottom: insets.bottom +
16 }]}>
218                 <View style={styles.modalHandle} />
219                 <Text style={[styles.modalTitle, { color: colors.foreground }]}>Select Company</Text>
220                 {COY_CMD_OPTIONS.map(coy => (
221                     <TouchableOpacity key={coy.email} style={styles.roleItem, { borderBottomColor:
colors.border }]} onPress={() => handleCoySelect(coy)} activeOpacity={0.75}>
222                     <View style={[styles.roleItemIcon, { backgroundColor: colors.muted }]}>

```

```

223         <MaterialCommunityIcons name="flag" size={22} color={colors.accent} />
224     </View>
225     <Text style={[styles.roleItemLabel, { color: colors.foreground }]}>{coy.label}</Text>
226     </TouchableOpacity>
227   )}}
228 </View>
229 </TouchableOpacity>
230 </Modal>
231 </View>
232 );
233 }
234
235 const styles = StyleSheet.create({
236   root: { flex: 1 },
237   container: { flexGrow: 1, paddingHorizontal: 24 },
238   header: { alignItems: 'center', marginBottom: 28 },
239   logoCircle: {
240     width: 110, height: 110, borderRadius: 55,
241     borderWidth: 3, overflow: 'hidden',
242     marginBottom: 14,
243     shadowOffset: { width: 0, height: 6 }, shadowOpacity: 0.35, shadowRadius: 14, elevation: 10,
244   },
245   logoImg: { width: '100%', height: '100%' },
246   appName: { fontSize: 30, fontFamily: 'Inter_700Bold', letterSpacing: 6, marginBottom: 4 },
247   tagline: { fontSize: 13, fontFamily: 'Inter_400Regular', letterSpacing: 1.5 },
248   divider: { height: 2, width: 60, marginTop: 16, borderRadius: 1 },
249   form: { borderRadius: 18, padding: 20, shadowColor: '#000', shadowOffset: { width: 0, height: 2 },
shadowOpacity: 0.08, shadowRadius: 8, elevation: 3, marginBottom: 16 },
250   sectionLabel: { fontSize: 11, fontFamily: 'Inter_600SemiBold', letterSpacing: 1.5, marginBottom: 8 },
251   roleSelector: { flexDirection: 'row', alignItems: 'center', gap: 10, borderWidth: 1, borderRadius: 10,
paddingHorizontal: 14, paddingVertical: 13 },
252   roleSelectorText: { flex: 1, fontSize: 15, fontFamily: 'Inter_500Medium' },
253   roleDesc: { fontSize: 12, fontFamily: 'Inter_400Regular', marginTop: 6 },
254   inputWrapper: { flexDirection: 'row', alignItems: 'center', borderWidth: 1, borderRadius: 10,
paddingHorizontal: 12 },
255   inputIcon: { marginRight: 8 },
256   input: { flex: 1, fontSize: 15, fontFamily: 'Inter_400Regular', paddingVertical: 13 },
257   eyeBtn: { padding: 4 },
258   errorBox: { flexDirection: 'row', alignItems: 'center', gap: 6, borderRadius: 8, padding: 10, marginTop:
12 },
259   errorText: { fontSize: 13, fontFamily: 'Inter_400Regular', flex: 1 },
260   loginBtn: { flexDirection: 'row', alignItems: 'center', justifyContent: 'center', gap: 8, borderRadius:
10, paddingVertical: 15, marginTop: 20, shadowOffset: { width: 0, height: 4 }, shadowOpacity: 0.3, shadowRadius:
8, elevation: 4 },
261   loginBtnText: { fontSize: 15, fontFamily: 'Inter_700Bold', color: '#FFF', letterSpacing: 2 },
262   registerLinkWrap: { alignItems: 'center', paddingVertical: 12 },
263   registerLinkText: { fontSize: 14, fontFamily: 'Inter_400Regular' },
264   registerLinkBold: { fontFamily: 'Inter_600SemiBold' },
265   footer: { textAlign: 'center', fontSize: 12, fontFamily: 'Inter_400Regular', marginTop: 8, marginBottom:
8 },
266   modalOverlay: { flex: 1, backgroundColor: 'rgba(0,0,0,0.5)', justifyContent: 'flex-end' },
267   modalSheet: { borderTopLeftRadius: 20, borderTopRightRadius: 20, paddingHorizontal: 16, paddingTop: 12,
maxHeight: '80%' },
268   modalHandle: { width: 40, height: 4, backgroundColor: '#ccc', borderRadius: 2, alignSelf: 'center',
marginBottom: 16 },
269   modalTitle: { fontSize: 16, fontFamily: 'Inter_700Bold', marginBottom: 12, textAlign: 'center' },
270   roleItem: { flexDirection: 'row', alignItems: 'center', gap: 12, paddingVertical: 13, borderBottomWidth:
1 },
271   roleItemIcon: { width: 42, height: 42, borderRadius: 21, alignItems: 'center', justifyContent: 'center' },
272   roleItemLabel: { fontSize: 14, fontFamily: 'Inter_600SemiBold' },
273   roleItemDesc: { fontSize: 12, fontFamily: 'Inter_400Regular', marginTop: 1 },
274 });
275

```

app/auth/register.tsx

```
1  import React, { useState } from 'react';
2  import {
3    View, Text, StyleSheet, ScrollView, TouchableOpacity,
4    TextInput, Modal, ActivityIndicator,
5    Platform, Image,
6  } from 'react-native';
7  import { useSafeAreaInsets } from 'react-native-safe-area-context';
8  import { router } from 'expo-router';
9  import { Ionicons, MaterialCommunityIcons } from '@expo/vector-icons';
10 import * as Haptics from 'expo-haptics';
11 import { useColors } from '@/hooks/useColors';
12 import { showAlert } from '@lib/alert';
13 import { getUsers, addUser, addSoldier, addIPFTResult, addNotification, genId, calcAge } from '@lib/storage';
14 import type { UserRole, SoldierRank, Company, BloodGroup } from '@lib/types';
15
16 const RANKS: SoldierRank[] = ['Snk', 'LCpl', 'Cpl', 'Sgt', 'WO', 'SWO'];
17 const COMPANIES: Company[] = ['A', 'B', 'C', 'D'];
18 const BLOOD_GROUPS: BloodGroup[] = ['A+', 'A-', 'B+', 'B-', 'AB+', 'AB-', 'O+', 'O-'];
19 const MED_CATS = ['Category A', 'Category B', 'Category C'];
20 const PREVIOUS_RESULT_OPTIONS = ['Not Applicable (First Time)', 'Pass', 'Fail'];
21 const BIENNIAL_OPTIONS = ['1st Biannual', '2nd Biannual'];
22
23 type Colors = ReturnType<typeof useColors>;
24
25 /**
26  * These field components live OUTSIDE the screen component on purpose.
27  * When they were defined inside RegisterScreen, every keystroke triggered a
28  * re-render that recreated them as brand-new component types, so React
29  * unmounted and remounted the underlying TextInput on every character -
30  * dropping keyboard focus after each letter/word. Hoisting them keeps their
31  * identity stable across renders so focus is preserved while typing.
32  */
33 function SelectField({
34   colors, label, value, placeholder, onPress, icon,
35 }: { colors: Colors; label: string; value: string; placeholder: string; onPress: () => void; icon:
string }) {
36   return (
37     <View style={styles.fieldWrap}>
38       <Text style={[styles.fieldLabel, { color: colors.mutedForeground }]}>{label}</Text>
39       <TouchableOpacity style={[styles.selectBtn, { borderColor: colors.border, backgroundColor:
colors.background }]} onPress={onPress} activeOpacity={0.8}>
40         <MaterialCommunityIcons name={icon as any} size={18} color={value ? colors.primary :
colors.mutedForeground} />
41         <Text style={[styles.selectText, !value && { color: colors.mutedForeground }, !!value && { color:
colors.foreground }]}>
42           {value || placeholder}
43         </Text>
44         <Ionicons name="chevron-down" size={16} color={colors.mutedForeground} />
45       </TouchableOpacity>
46     </View>
47   );
48 }
49
50 function InputField({
51   colors, label, value, onChange, placeholder, keyboardType, secure, showToggle, icon, multiline,
showPassword, onToggleShowPassword,
52 }: {
53   colors: Colors; label: string; value: string; onChange: (v: string) => void; placeholder: string;
54   keyboardType?: any; secure?: boolean; showToggle?: boolean; icon: string; multiline?: boolean;
55   showPassword?: boolean; onToggleShowPassword?: () => void;
56 }) {
57   return (
58     <View style={styles.fieldWrap}>
59       <Text style={[styles.fieldLabel, { color: colors.mutedForeground }]}>{label}</Text>
60       <View style={[styles.inputWrap, { borderColor: colors.border, backgroundColor: colors.background }]}>
61         <MaterialCommunityIcons name={icon as any} size={18} color={colors.mutedForeground}
style={{ marginRight: 8 }} />
62         <TextInput
63           style={[styles.textInput, { color: colors.foreground, flex: 1 }]}
64           value={value} onChangeText={onChange} placeholder={placeholder}
65           placeholderTextColor={colors.mutedForeground}
66           keyboardType={keyboardType ?? 'default'}
67           secureTextEntry={secure && !showPassword}
68           multiline={multiline}
69           autoCapitalize={keyboardType === 'email-address' ? 'none' : 'words'}
70           autoCorrect={false}
71         />
72         {showToggle && (
73           <TouchableOpacity onPress={onToggleShowPassword}>
74             <Ionicons name={showPassword ? 'eye-off-outline' : 'eye-outline'} size={18}
color={colors.mutedForeground} />
75           </TouchableOpacity>
76         )}
77       </View>
78     </View>
79   );
80 }
```

```

76     })
77   </View>
78 </View>
79 );
80 }
81
82 function SimpleModal({
83   colors, insetsBottom, visible, title, options, onSelect, onClose,
84   v: string) => void; onClose: () => void }) {
85   return (
86     <Modal visible={visible} transparent animationType="slide" onRequestClose={onClose}>
87       <TouchableOpacity style={styles.modalOverlay} onPress={onClose} activeOpacity={1}>
88         <View style={[styles.modalSheet, { backgroundColor: colors.card, paddingBottom: insetsBottom +
16 }]}>
89           <View style={styles.modalHandle} />
90           <Text style={[styles.modalTitle, { color: colors.foreground }]}>{title}</Text>
91           {options.map(opt => (
92             <TouchableOpacity key={opt} style={styles.optionRow, { borderBottomColor: colors.border }}>
93               <Text style={styles.optionText, { color: colors.foreground }}>{opt}</Text>
94             </TouchableOpacity>
95           ))}
96         </View>
97       </TouchableOpacity>
98     </Modal>
99   );
100 }
101
102 export default function RegisterScreen() {
103   const colors = useColors();
104   const insets = useSafeAreaInsets();
105   const isWeb = Platform.OS === 'web';
106
107   const [name, setName] = useState('');
108   const [rank, setRank] = useState<SoldierRank | ''>('');
109   const [company, setCompany] = useState<Company | ''>('');
110   const [serviceNumber, setServiceNumber] = useState('');
111   const [email, setEmail] = useState('');
112   const [password, setPassword] = useState('');
113   const [confirmPassword, setConfirmPassword] = useState('');
114   const [phone, setPhone] = useState('');
115   const [address, setAddress] = useState('');
116   const [bloodGroup, setBloodGroup] = useState<BloodGroup | ''>('');
117   const [height, setHeight] = useState('');
118   const [weight, setWeight] = useState('');
119   const [dob, setDob] = useState('');
120   const [medCat, setMedCat] = useState('Category A');
121   const [previousResult, setPreviousResult] = useState(PREVIOUS_RESULT_OPTIONS[0]);
122   const [biannual, setBiannual] = useState('');
123   const [showPassword, setShowPassword] = useState(false);
124   const [isSaving, setIsSaving] = useState(false);
125   const [errors, setErrors] = useState<string[]>([]);
126
127   // Picker states
128   const [rankModal, setRankModal] = useState(false);
129   const [companyModal, setCompanyModal] = useState(false);
130   const [bloodModal, setBloodModal] = useState(false);
131   const [medModal, setMedModal] = useState(false);
132   const [previousResultModal, setPreviousResultModal] = useState(false);
133   const [biannualModal, setBiannualModal] = useState(false);
134
135   const validate = (): string[] => {
136     const errs: string[] = [];
137     if (!name.trim()) errs.push('Full name is required.');
```

```

158     errs.push('Select which biannual period the previous IPFT result is from.');
```

159

}

return errs;

};

162

const handleRegister = async () => {

164 const errs = validate();

165 if (errs.length > 0) { setErrors(errs); return; }

166 setErrors([]);

167 setIsSaving(true);

168 Haptics.impactAsync(Haptics.ImpactFeedbackStyle.Medium);

169

170 try {

171 const existingUsers = await getUsers();

172 const emailTaken = existingUsers.find(u => u.email.toLowerCase() === email.trim().toLowerCase());

173 if (emailTaken) {

174 setErrors(['This email is already registered.']);

175 setIsSaving(false);

176 return;

177 }

178 const svcTaken = existingUsers.find(u => u.ba === serviceNumber.trim().toUpperCase());

179 if (svcTaken) {

180 setErrors(['This service number is already registered.']);

181 setIsSaving(false);

182 return;

183 }

184

185 const userId = genId();

186 const soldierId = genId();

187 const svcNum = serviceNumber.trim().toUpperCase();

188 const age = calcAge(dob.trim());

189

190 await addUser({

191 id: userId,

192 email: email.trim().toLowerCase(),

193 password: password.trim(),

194 role: 'soldier' as UserRole,

195 name: name.trim(),

196 rank: rank,

197 ba: svcNum,

198 company: company as Company,

199 phone: phone.trim() || undefined,

200 address: address.trim(),

201 bloodGroup: bloodGroup as BloodGroup,

202 height: Number(height),

203 weight: Number(weight),

204 age: Number(age),

205 medicalCategory: medCat,

206 serviceNumber: svcNum,

207 isApproved: false,

208 });

209

210 await addSoldier({

211 id: soldierId,

212 userId,

213 serviceNumber: svcNum,

214 name: name.trim(),

215 rank: rank as SoldierRank,

216 company: company as Company,

217 email: email.trim().toLowerCase(),

218 bloodGroup: bloodGroup as BloodGroup,

219 height: Number(height),

220 weight: Number(weight),

221 age: Number(age),

222 medicalCategory: medCat,

223 phone: phone.trim() || '',

224 address: address.trim(),

225 isApproved: false,

226 isOverweight: false,

227 ptStatus: 'pending',

228 });

229

230 // Keep any previous unit's IPFT result on record, so it shows in this

231 // soldier's history – it does not affect their pending status here,

232 // since the new unit still needs to test them itself.

233 if (previousResult !== PREVIOUS_RESULT_OPTIONS[0]) {

234 const status = previousResult.toLowerCase() as 'pass' | 'fail';

235 await addIPFTResult({

236 id: genId(), soldierId, soldierName: name.trim(), soldierRank: rank as SoldierRank,

237 serviceNumber: svcNum, company: company as Company,

238 date: new Date().toISOString().slice(0, 10),

239 items: [{ name: 'Previous Unit IPFT (Self-Reported)', target: 'N/A', achieved: previousResult,

status }],

240 overallStatus: status,

241 recordedBy: userId, recordedByName: `\${name.trim()} (self-reported at registration)`,

```

242         biannual: biannual.startsWith('1st') ? '1st' : '2nd',
243         selfReported: true,
244     });
245 }
246
247 // Send approval notification to Adjutant
248 await addNotification({
249     id: genId(),
250     targetRole: 'adjutant',
251     title: 'New Soldier Registration',
252     body: `${rank} ${name.trim()} (${svcNum}) from ${company} Company has registered and requires
approval.` ,
253     type: 'general',
254     read: false,
255     createdAt: new Date().toISOString(),
256 });
257
258 setIsSaving(false);
259 Haptics.notificationAsync(Haptics.NotificationFeedbackType.Success);
260 showAlert(
261     'Registration Submitted',
262     'Your registration has been submitted. Please wait for Adjutant approval before signing in.',
263     [{ text: 'Go to Sign In', onPress: () => router.replace('/(auth)/login') }]
264 );
265 } catch (e) {
266     setIsSaving(false);
267     setErrors(['Registration failed. Please try again.']);
268 }
269 };
270
271 const paddingTop = isWeb ? (67 + insets.top) : insets.top + 16;
272
273 return (
274     <ScrollView style={[styles.root, { backgroundColor: colors.background }]}
275     <contentContainerStyle={[styles.content, { paddingTop, paddingBottom: isWeb ? 34 : insets.bottom +
24 ]]}
276     keyboardShouldPersistTaps="handled">
277
278     /* Logo header */
279     <View style={styles.logoRow}>
280         <View style={[styles.logoCircle, { borderColor: colors.accent }]}>
281             <Image source={require('@assets/images/fitforce-logo.jpg')} style={styles.logoImg}
resizeMode="cover" />
282         </View>
283         <View style={{ flex: 1 }}>
284             <Text style={styles.appName, { color: colors.foreground }}>Fit Force</Text>
285             <Text style={styles.appSub, { color: colors.mutedForeground }}>Soldier Fitness Assessment
System</Text>
286         </View>
287     </View>
288
289     <Text style={styles.screenTitle, { color: colors.foreground }}>Soldier Registration</Text>
290     <Text style={styles.screenSubtitle, { color: colors.mutedForeground }}>Your account will be
activated after Adjutant approval.</Text>
291
292     {errors.length > 0 && (
293         <View style={[styles.errorBox, { backgroundColor: colors.destructive + '12', borderColor:
colors.destructive }]}>
294             {errors.map((e, i) => <Text key={i} style={styles.errorText, { color: colors.destructive }}>•
{e}</Text>)}
295         </View>
296     )}
297
298     <View style={[styles.card, { backgroundColor: colors.card, borderColor: colors.border }]}>
299         <Text style={styles.cardTitle, { color: colors.foreground }}>Personal Information</Text>
300
301         <InputField colors={colors} label="Full Name *" value={name} onChange={setName} placeholder="e.g.
Kamal Hossain" icon="account-outline" />
302         <SelectField colors={colors} label="Rank *" value={rank} placeholder="Select rank" onPress={() =>
setRankModal(true)} icon="chevron-down-circle-outline" />
303         <SelectField colors={colors} label="Company *" value={company ? `${company} Company` : ''}
placeholder="Select company" onPress={() => setCompanyModal(true)} icon="flag-outline" />
304         <InputField colors={colors} label="Service Number *" value={serviceNumber}
onChange={setServiceNumber}
305             placeholder="e.g. BD-11010" icon="identifier" keyboardType="default" />
306         <InputField colors={colors} label="Date of Birth *" value={dob} onChange={setDob} placeholder="e.g.
2001-05-14 (YYYY-MM-DD)" icon="cake-variant-outline" />
307         <SelectField colors={colors} label="Blood Group *" value={bloodGroup} placeholder="Select blood
group" onPress={() => setBloodModal(true)} icon="water-outline" />
308         <SelectField colors={colors} label="Medical Category *" value={medCat} placeholder="Select
category" onPress={() => setMedModal(true)} icon="medical-bag" />
309         <InputField colors={colors} label="Phone" value={phone} onChange={setPhone} placeholder="e.g.
01711-123456" icon="phone-outline" keyboardType="phone-pad" />
310         <InputField colors={colors} label="Address *" value={address} onChange={setAddress}
placeholder="e.g. House 12, Road 5, Dhaka" icon="map-marker-outline" multiline />

```

```

311     </View>
312
313     <View style={{[styles.card, { backgroundColor: colors.card, borderColor: colors.border }]}>
314         <Text style={{[styles.cardTitle, { color: colors.foreground }]}>Previous IPFT Record</Text>
315         <Text style={{[styles.cardHint, { color: colors.mutedForeground }]}>If you have a result from a
previous unit, add it here – it will show on your profile history. Otherwise leave as "Not Applicable".</Text>
316         <SelectField colors={colors} label="Previous IPFT Result" value={previousResult}
placeholder="Select result" onPress={() => setPreviousResultModal(true)} icon="clipboard-text-outline" />
317         {previousResult !== PREVIOUS_RESULT_OPTIONS[0] && (
318             <SelectField colors={colors} label="Biannual Period *" value={biannual} placeholder="Select
biannual period" onPress={() => setBiannualModal(true)} icon="calendar-range" />
319         )}
320     </View>
321
322     <View style={{[styles.card, { backgroundColor: colors.card, borderColor: colors.border }]}>
323         <Text style={{[styles.cardTitle, { color: colors.foreground }]}>Physical Metrics</Text>
324         <InputField colors={colors} label="Height (cm) *" value={height} onChange={setHeight}
placeholder="e.g. 170" icon="human-male-height" keyboardType="numeric" />
325         <InputField colors={colors} label="Weight (kg) *" value={weight} onChange={setWeight}
placeholder="e.g. 68" icon="weight-kilogram" keyboardType="numeric" />
326     </View>
327
328     <View style={{[styles.card, { backgroundColor: colors.card, borderColor: colors.border }]}>
329         <Text style={{[styles.cardTitle, { color: colors.foreground }]}>Account Credentials</Text>
330         <InputField colors={colors} label="Email *" value={email} onChange={setEmail} placeholder="e.g.
kamel@gmail.com" icon="email-outline" keyboardType="email-address" />
331         <InputField colors={colors} label="Password *" value={password} onChange={setPassword}
placeholder="Min. 6 characters" icon="lock-outline" secure showToggle showPassword={showPassword}
onToggleShowPassword={() => setShowPassword(v => !v)} />
332         <InputField colors={colors} label="Confirm Password *" value={confirmPassword}
onChange={setConfirmPassword} placeholder="Re-enter password" icon="lock-check-outline" secure showToggle
showPassword={showPassword} onToggleShowPassword={() => setShowPassword(v => !v)} />
333     </View>
334
335     <TouchableOpacity
336         style={{[styles.registerBtn, { backgroundColor: colors.primary }, isSaving && { opacity: 0.7 }]}
337         onPress={handleRegister} disabled={isSaving} activeOpacity={0.85}>
338         {isSaving ? <ActivityIndicator color="#FFF" /> : (
339             <>
340                 <MaterialCommunityIcons name="account-plus" size={20} color="#FFF" />
341                 <Text style={styles.registerBtnText}>SUBMIT REGISTRATION</Text>
342             </>
343         )}
344     </TouchableOpacity>
345
346     <TouchableOpacity style={styles.loginLink} onPress={() => router.back()}>
347         <Text style={{[styles.loginLinkText, { color: colors.mutedForeground }]}>
348             Already have an account? <Text style={{ color: colors.primary, fontFamily: 'Inter_600SemiBold' }}
>Sign In</Text>
349         </Text>
350     </TouchableOpacity>
351
352     <SimpleModal colors={colors} insetsBottom={insets.bottom} visible={rankModal} title="Select Rank"
options={RANKS} onSelect={v => setRank(v as SoldierRank)} onClose={() => setRankModal(false)} />
353     <SimpleModal colors={colors} insetsBottom={insets.bottom} visible={companyModal} title="Select
Company" options={COMPANIES.map(c => `${c} Company`)} onSelect={v => setCompany(v[0] as Company)} onClose={() =>
setCompanyModal(false)} />
354     <SimpleModal colors={colors} insetsBottom={insets.bottom} visible={bloodModal} title="Select Blood
Group" options={BLOOD_GROUPS} onSelect={v => setBloodGroup(v as BloodGroup)} onClose={() =>
setBloodModal(false)} />
355     <SimpleModal colors={colors} insetsBottom={insets.bottom} visible={medModal} title="Medical Category"
options={MED_CATS} onSelect={v => setMedCat(v)} onClose={() => setMedModal(false)} />
356     <SimpleModal colors={colors} insetsBottom={insets.bottom} visible={previousResultModal}
title="Previous IPFT Result" options={PREVIOUS_RESULT_OPTIONS}
357         onSelect={v => { setPreviousResult(v); if (v === PREVIOUS_RESULT_OPTIONS[0]) setBiannual(''); }}
onClose={() => setPreviousResultModal(false)} />
358     <SimpleModal colors={colors} insetsBottom={insets.bottom} visible={biannualModal} title="Biannual
Period" options={BIANNUAL_OPTIONS} onSelect={v => setBiannual(v)} onClose={() => setBiannualModal(false)} />
359     </ScrollView>
360 );
361 }
362
363 const styles = StyleSheet.create({
364     root: { flex: 1 },
365     content: { paddingHorizontal: 16, gap: 14 },
366     logoRow: { flexDirection: 'row', alignItems: 'center', gap: 14, marginBottom: 6 },
367     logoCircle: { width: 80, height: 80, borderRadius: 40, borderWidth: 3, overflow: 'hidden' },
368     logoImg: { width: '100%', height: '100%' },
369     appName: { fontSize: 22, fontFamily: 'Inter_700Bold' },
370     appSub: { fontSize: 12, fontFamily: 'Inter_400Regular', letterSpacing: 0.3, marginTop: 2 },
371     screenTitle: { fontSize: 24, fontFamily: 'Inter_700Bold' },
372     screenSubtitle: { fontSize: 13, fontFamily: 'Inter_400Regular', lineHeight: 19, marginTop: -6 },
373     errorBox: { borderRadius: 10, borderWidth: 1, padding: 12, gap: 4 },
374     errorText: { fontSize: 12, fontFamily: 'Inter_400Regular' },
375     card: { borderRadius: 14, borderWidth: 1, padding: 16, gap: 12 },

```

```

376   cardTitle: { fontSize: 14, fontFamily: 'Inter_700Bold', marginBottom: 2 },
377   cardHint: { fontSize: 11, fontFamily: 'Inter_400Regular', lineHeight: 16, marginTop: -6 },
378   fieldWrap: { gap: 5 },
379   fieldLabel: { fontSize: 11, fontFamily: 'Inter_600SemiBold', letterSpacing: 1 },
380   inputWrap: { flexDirection: 'row', alignItems: 'center', borderWidth: 1, borderRadius: 10,
paddingHorizontal: 12, paddingVertical: 11 },
381   textInput: { fontSize: 14, fontFamily: 'Inter_400Regular' },
382   selectBtn: { flexDirection: 'row', alignItems: 'center', gap: 10, borderWidth: 1, borderRadius: 10,
paddingHorizontal: 12, paddingVertical: 12 },
383   selectText: { flex: 1, fontSize: 14, fontFamily: 'Inter_400Regular' },
384   registerBtn: { flexDirection: 'row', alignItems: 'center', justifyContent: 'center', gap: 10,
borderRadius: 12, paddingVertical: 16, marginTop: 4 },
385   registerBtnText: { fontSize: 15, fontFamily: 'Inter_700Bold', color: '#FFF', letterSpacing: 1.5 },
386   loginLink: { alignItems: 'center', paddingVertical: 8 },
387   loginLinkText: { fontSize: 14, fontFamily: 'Inter_400Regular' },
388   modalOverlay: { flex: 1, backgroundColor: 'rgba(0,0,0,0.5)', justifyContent: 'flex-end' },
389   modalSheet: { borderTopLeftRadius: 20, borderTopRightRadius: 20, paddingHorizontal: 16, paddingTop: 12 },
390   modalHandle: { width: 40, height: 4, borderRadius: 2, backgroundColor: '#ccc', alignSelf: 'center',
marginBottom: 16 },
391   modalTitle: { fontSize: 16, fontFamily: 'Inter_700Bold', marginBottom: 10, textAlign: 'center' },
392   optionRow: { paddingVertical: 14, borderBottomWidth: 1 },
393   optionText: { fontSize: 15, fontFamily: 'Inter_500Medium' },
394 });
395

```

app/(tabs)/_layout.tsx

```
1 import React from 'react';
2 import { Platform, StyleSheet, View } from 'react-native';
3 import { useColors } from '@/hooks/useColors';
4 import { Feather, MaterialCommunityIcons } from '@expo/vector-icons';
5 import { BlurView } from 'expo-blur';
6 import { Tabs } from 'expo-router';
7 import { useAuth } from '@/context/AuthContext';
8 import { AppHeader } from '@/components/AppHeader';
9 import type { UserRole } from '@/lib/types';
10
11 function canSeeTab(tab: string, role: UserRole): boolean {
12   const map: Record<string, UserRole[]> = {
13     index: ['co', '2ic', 'coy_comd', 'adjutant', 'clerk', 'soldier'],
14     soldiers: ['co', '2ic', 'coy_comd', 'adjutant', 'clerk'],
15     plan: ['2ic', 'adjutant', 'clerk', 'soldier'],
16     reports: ['co', '2ic', 'coy_comd', 'adjutant', 'clerk'],
17     messages: ['co', '2ic', 'coy_comd', 'adjutant', 'clerk'],
18     notifications: ['co', '2ic', 'coy_comd', 'adjutant', 'clerk', 'soldier'],
19     profile: ['co', '2ic', 'coy_comd', 'adjutant', 'clerk', 'soldier'],
20   };
21   return (map[tab] ?? []).includes(role);
22 }
23
24 export default function TabLayout() {
25   const colors = useColors();
26   const isDark = true;
27   const isIOS = Platform.OS === 'ios';
28   const isWeb = Platform.OS === 'web';
29   const { user } = useAuth();
30   const role: UserRole = user?.role ?? 'soldier';
31
32   const tabBarStyle = {
33     position: 'absolute' as const,
34     backgroundColor: isIOS ? 'transparent' : colors.background,
35     borderTopWidth: isWeb ? 1 : 0,
36     borderTopColor: colors.border,
37     elevation: 0,
38     ...(isWeb ? { height: 84 } : {}),
39     paddingBottom: isIOS ? 6 : 4,
40     paddingTop: 4,
41   };
42
43   const tabBg = () =>
44     isIOS ? (
45       <BlurView intensity={100} tint={isDark ? 'dark' : 'light'} style={StyleSheet.absoluteFill} />
46     ) : isWeb ? (
47       <View style={[StyleSheet.absoluteFill, { backgroundColor: colors.background }]}/>
48     ) : null;
49
50   return (
51     <View style={{ flex: 1, backgroundColor: colors.background }}>
52       <AppHeader />
53       <Tabs
54         screenOptions={{
55           tabBarActiveTintColor: colors.primary,
56           tabBarInactiveTintColor: colors.mutedForeground,
57           headerShown: false,
58           tabBarStyle,
59           tabBarBackground: tabBg,
60           tabBarLabelStyle: { fontSize: 11, fontFamily: 'Inter_600SemiBold' },
61         }}
62       >
63         <Tabs.Screen
64           name="index"
65           options={{
66             title: 'Dashboard',
67             href: canSeeTab('index', role) ? undefined : null,
68             tabBarIcon: ({ color }) => <Feather name="home" size={26} color={color} />,
69           }}
70         />
71         <Tabs.Screen
72           name="soldiers"
73           options={{
74             title: 'Soldiers',
75             href: canSeeTab('soldiers', role) ? undefined : null,
76             tabBarIcon: ({ color }) => <MaterialCommunityIcons name="account-group" size={28}
77               color={color} />,
78           }}
79         />
80         <Tabs.Screen
81           name="plan"
82           options={{
83             title: role === '2ic' ? 'Plans' : 'My Plan',
```

```

83         href: canSeeTab('plan', role) ? undefined : null,
84         tabBarIcon: ({ color }) => <Feather name="calendar" size={26} color={color} />,
85     }}
86 />
87 <Tabs.Screen
88   name="reports"
89   options={{
90     title: 'Reports',
91     href: canSeeTab('reports', role) ? undefined : null,
92     tabBarIcon: ({ color }) => <Feather name="file-text" size={26} color={color} />,
93   }}
94 />
95 <Tabs.Screen
96   name="messages"
97   options={{
98     title: 'Messages',
99     href: canSeeTab('messages', role) ? undefined : null,
100     tabBarIcon: ({ color }) => <Feather name="message-square" size={26} color={color} />,
101   }}
102 />
103 <Tabs.Screen
104   name="notifications"
105   options={{
106     title: 'Alerts',
107     href: canSeeTab('notifications', role) ? undefined : null,
108     tabBarIcon: ({ color }) => <Feather name="bell" size={26} color={color} />,
109   }}
110 />
111 <Tabs.Screen
112   name="profile"
113   options={{
114     title: 'Profile',
115     href: canSeeTab('profile', role) ? undefined : null,
116     tabBarIcon: ({ color }) => <Feather name="user" size={26} color={color} />,
117   }}
118 />
119 </Tabs>
120 </View>
121 );
122 }
123

```

```

1  import React, { useState, useEffect, useCallback } from 'react';
2  import {
3    View, Text, StyleSheet, ScrollView, TouchableOpacity,
4    Platform, RefreshControl,
5  } from 'react-native';
6  import { useSafeAreaInsets } from 'react-native-safe-area-context';
7  import { Feather, MaterialCommunityIcons } from '@expo/vector-icons';
8  import { router, useFocusEffect } from 'expo-router';
9  import { useColors } from '@/hooks/useColors';
10 import { useAuth } from '@/context/AuthContext';
11 import {
12   getSoldiers, getIPFTResults, getIPFTSchedule,
13   getNotifications, getPTPlans, getReports, calcBMI, getIPFTResultsBySoldier,
14 } from '@/lib/storage';
15 import type { Soldier, IPFTResult, IPFTSchedule } from '@/lib/types';
16 import { BarChart } from '@/components/BarChart';
17
18 export default function DashboardScreen() {
19   const colors = useColors();
20   const insets = useSafeAreaInsets();
21   const { user } = useAuth();
22   const [refreshing, setRefreshing] = useState(false);
23   const [data, setData] = useState<any>({});
24   const isWeb = Platform.OS === 'web';
25
26   const load = useCallback(async () => {
27     if (!user) return;
28     const [soldiers, results, schedule, notifications, plans, reports] = await Promise.all([
29       getSoldiers(), getIPFTResults(), getIPFTSchedule(), getNotifications(), getPTPlans(), getReports(),
30     ]);
31
32     const approvedSoldiers = soldiers.filter(s => s.isApproved);
33
34     const mySoldiers = user.role === 'coy_comd'
35       ? approvedSoldiers.filter(s => s.company === user.company)
36       : approvedSoldiers;
37
38     const unreadNotifs = notifications.filter(n => !n.read).length;
39     const overweight = mySoldiers.filter(s => s.isOverweight);
40     const fit = mySoldiers.filter(s => s.ptStatus === 'fit');
41     const unfit = mySoldiers.filter(s => s.ptStatus === 'unfit');
42
43     let ipftDaysLeft: number | null = null;
44     if (schedule?.proposedDate && schedule.status === 'approved') {
45       const target = new Date(schedule.proposedDate);
46       const now = new Date();
47       const diff = Math.ceil((target.getTime() - now.getTime()) / (1000 * 60 * 60 * 24));
48       ipftDaysLeft = Math.max(0, diff);
49     }
50
51     let soldierResults: IPFTResult[] = [];
52     let soldierBMI: number | null = null;
53     let myPlan = null;
54     if (user.role === 'soldier') {
55       const mySol = soldiers.find(s => s.userId === user.id);
56       if (mySol) {
57         soldierResults = await getIPFTResultsBySoldier(mySol.id);
58         soldierBMI = calcBMI(mySol.weight, mySol.height);
59         myPlan = plans.find(p => p.type === (mySol.ptStatus === 'unfit' ? 'unfit' : 'fit'));
60       }
61     }
62
63     const companyBreakdown: Record<string, { total: number; fit: number; unfit: number }> = {};
64     ['A', 'B', 'C', 'D'].forEach(c => {
65       const cs = approvedSoldiers.filter(s => s.company === c);
66       companyBreakdown[c] = {
67         total: cs.length,
68         fit: cs.filter(s => s.ptStatus === 'fit').length,
69         unfit: cs.filter(s => s.ptStatus === 'unfit').length,
70       };
71     });
72
73     setData({ soldiers: mySoldiers, allSoldiers: soldiers, approvedSoldiers, results, schedule,
74       ipftDaysLeft, unreadNotifs, overweight, fit, unfit, soldierResults, soldierBMI, myPlan, companyBreakdown, plans,
75       reports });
76     }, [user]);
77
78   useFocusEffect(useCallback(() => { load(); }, [load]));
79
80   const onRefresh = async () => { setRefreshing(true); await load(); setRefreshing(false); };
81
82   const formatDate = (d: string) => new Date(d).toLocaleDateString('en-BD', { day: '2-digit', month:
83     'long', year: 'numeric' });

```

```

81
82   if (!user) return null;
83
84   const StatCard = ({ label, value, icon, color, onPress }: { label: string; value: string | number; icon:
string; color: string; onPress?: () => void }) => (
85     <TouchableOpacity style={[styles.statCard, { backgroundColor: colors.card, borderColor:
colors.border }]} onPress={onPress} activeOpacity={onPress ? 0.75 : 1}>
86       <View style={[styles.statIcon, { backgroundColor: color + '20' }]}>
87         <MaterialCommunityIcons name={icon as any} size={22} color={color} />
88       </View>
89       <Text style={[styles.statValue, { color: colors.foreground }]}>{value}</Text>
90       <Text style={[styles.statLabel, { color: colors.mutedForeground }]}>{label}</Text>
91     </TouchableOpacity>
92   );
93
94   const SectionHeader = ({ title }: { title: string }) => (
95     <Text style={[styles.sectionHeader, { color: colors.foreground }]}>{title}</Text>
96   );
97
98   const renderIPFTBanner = () => {
99     const s = data.schedule as IPFTSchedule | null;
100     if (!s) return null;
101     const statusColor = s.status === 'approved' ? colors.success : s.status === 'rejected' ?
colors.destructive : colors.accent;
102     const statusLabel = s.status === 'approved' ? 'CONFIRMED' : s.status === 'rejected' ? 'REJECTED' :
'PENDING CO APPROVAL';
103     return (
104       <View style={[styles.ipftBanner, { backgroundColor: statusColor + '15', borderColor: statusColor }]}>
105         <MaterialCommunityIcons name="calendar-check" size={24} color={statusColor} />
106         <View style={{ flex: 1 }}>
107           <Text style={[styles.ipftBannerTitle, { color: statusColor }]}>Next IPFT – {statusLabel}</Text>
108           <Text style={[styles.ipftBannerDate, { color: colors.foreground }]}>{formatDate(s.proposedDate)}</
Text>
109           {data.ipftDaysLeft !== null && <Text style={[styles.ipftCountdown, { color: statusColor }]}
>{data.ipftDaysLeft} days remaining</Text>}
110         </View>
111       </View>
112     );
113   };
114
115   const paddingTop = 16;
116   const paddingBottom = isWeb ? 34 : insets.bottom + 90;
117
118   if (user.role === 'co') {
119     return (
120       <ScrollView style={[styles.root, { backgroundColor: colors.background }]}
121         contentContainerStyle={[styles.content, { paddingTop, paddingBottom }]}
122         refreshControl={<RefreshControl refreshing={refreshing} onRefresh={onRefresh}
tintColor={colors.primary} />}>
123         <View style={styles.greetRow}>
124           <View>
125             <Text style={[styles.greetSmall, { color: colors.mutedForeground }]}>Commanding Officer</Text>
126             <Text style={[styles.greetName, { color: colors.foreground }]}>{user.name}</Text>
127             <Text style={[styles.greetBA, { color: colors.mutedForeground }]}>{user.ba} · {user.rank}</Text>
128           </View>
129           <View style={[styles.roleBadge, { backgroundColor: colors.primary }]}>
130             <Text style={styles.roleBadgeText}>CO</Text>
131           </View>
132         </View>
133         {renderIPFTBanner()}
134         <SectionHeader title="Unit Strength" />
135         <View style={styles.statsGrid}>
136           <StatCard label="Total" value={data.approvedSoldiers?.length ?? 0} icon="account-group"
color={colors.primary} onPress={() => router.push('/(tabs)/soldiers')} />
137           <StatCard label="Fit" value={data.approvedSoldiers?.filter((s: Soldier) => s.ptStatus ===
'fit').length ?? 0} icon="check-circle" color={colors.success} />
138           <StatCard label="Unfit" value={data.approvedSoldiers?.filter((s: Soldier) => s.ptStatus ===
'unfit').length ?? 0} icon="close-circle" color={colors.destructive} />
139           <StatCard label="Overweight" value={data.approvedSoldiers?.filter((s: Soldier) =>
s.isOverweight).length ?? 0} icon="alert" color={colors.warning} />
140         </View>
141         <SectionHeader title="IPFT Pass Rate by Company" />
142         <View style={[styles.chartCard, { backgroundColor: colors.card, borderColor: colors.border }]}>
143           <BarChart
144             unit="%"
145             height={110}
146             maxValue={100}
147             labelColor={colors.foreground}
148             subColor={colors.mutedForeground}
149             trackColor={colors.muted}
150             data={['A', 'B', 'C', 'D'].map(c => {
151               const cb = data.companyBreakdown?.[c];
152               const passRate = cb && cb.total > 0 ? Math.round((cb.fit / cb.total) * 100) : 0;
153               return { label: `${c} Coy`, value: passRate, color: passRate >= 70 ? colors.success :
passRate > 0 ? colors.destructive : colors.mutedForeground };

```

```

154     }}}
155     />
156   </View>
157   <SectionHeader title="Company Breakdown" />
158   [[ 'A', 'B', 'C', 'D' ].map(c => {
159     const cb = data.companyBreakdown?.[c];
160     if (!cb) return null;
161     const passRate = cb.total > 0 ? Math.round((cb.fit / cb.total) * 100) : 0;
162     return (
163       <View key={c} style={{[styles.companyRow, { backgroundColor: colors.card, borderColor:
colors.border } ]}}>
164         <View style={{[styles.companyBadge, { backgroundColor: colors.primary } ]}}>
165           <Text style={styles.companyBadgeText}>{c}</Text>
166         </View>
167         <View style={{ flex: 1 }}>
168           <Text style={{[styles.companyLabel, { color: colors.foreground } ]}}>{c} Company</Text>
169           <Text style={{[styles.companyStats, { color: colors.mutedForeground } ]}}>{cb.total} soldiers
· {cb.fit} fit · {cb.unfit} unfit</Text>
170         </View>
171         <Text style={{[styles.passRate, { color: passRate >= 70 ? colors.success :
colors.destructive } ]}}>{passRate}%</Text>
172       </View>
173     );
174   } ] ] }
175   </ScrollView>
176   );
177 }
178
179 if (user.role === '2ic') {
180   return (
181     <ScrollView style={{[styles.root, { backgroundColor: colors.background } ]}}
182       contentContainerStyle={{[styles.content, { paddingTop, paddingBottom } ]}}
183       refreshControl={<RefreshControl refreshing={refreshing} onRefresh={onRefresh}
tintColor={colors.primary} />}>
184       <View style={styles.greetRow}>
185         <View>
186           <Text style={{[styles.greetSmall, { color: colors.mutedForeground } ]}}>Second in Command</Text>
187           <Text style={{[styles.greetName, { color: colors.foreground } ]}}>{user.name}</Text>
188           <Text style={{[styles.greetBA, { color: colors.mutedForeground } ]}}>{user.ba}</Text>
189         </View>
190         <View style={{[styles.roleBadge, { backgroundColor: colors.primary } ]}}>
191           <Text style={styles.roleBadgeText}>2IC</Text>
192         </View>
193       </View>
194       {renderIPFTBanner()}
195       <SectionHeader title="Unit Overview" />
196       <View style={styles.statsGrid}>
197         <StatCard label="Total Soldiers" value={data.approvedSoldiers?.length ?? 0} icon="account-group"
color={colors.primary} />
198         <StatCard label="Fit" value={data.approvedSoldiers?.filter((s: Soldier) => s.ptStatus ===
'fit').length ?? 0} icon="check-circle" color={colors.success} />
199         <StatCard label="Unfit" value={data.approvedSoldiers?.filter((s: Soldier) => s.ptStatus ===
'unfit').length ?? 0} icon="close-circle" color={colors.destructive} />
200         <StatCard label="PT Plans" value={data.plans?.length ?? 0} icon="dumbbell" color={colors.accent} /
>
201       </View>
202       <SectionHeader title="PT Plans" />
203       <TouchableOpacity style={{[styles.newPlanBtn, { backgroundColor: colors.primary } ]}} onPress={() =>
router.push('/plan/new')}>
204         <Feather name="plus-circle" size={20} color="#FFF" />
205         <Text style={styles.newPlanBtnText}>Create New PT Plan</Text>
206       </TouchableOpacity>
207       {data.plans?.map((plan: any) => (
208         <TouchableOpacity key={plan.id} style={{[styles.planCard, { backgroundColor: colors.card,
borderColor: plan.type === 'fit' ? colors.success : colors.warning } ]}}
209         onPress={() => router.push('/plan/${plan.id}')} activeOpacity={0.75}>
210         <View style={{[styles.planType, { backgroundColor: plan.type === 'fit' ? colors.success :
colors.warning } ]}}>
211           <Text style={styles.planTypeText}>{plan.type === 'fit' ? 'FIT' : 'UNFIT'}</Text>
212         </View>
213         <View style={{ flex: 1 }}>
214           <Text style={{[styles.planTitle, { color: colors.foreground } ]}}>{plan.title}</Text>
215           <Text style={{[styles.planMeta, { color: colors.mutedForeground } ]}}>Week {plan.weekNumber} ·
{plan.days.length} days</Text>
216         </View>
217         <Feather name="chevron-right" size={18} color={colors.mutedForeground} />
218       </TouchableOpacity>
219     ) ) }
220   </ScrollView>
221   );
222 }
223
224 if (user.role === 'coy_comd') {
225   const comp = user.company ?? 'A';
226   const mySoldiers = data.soldiers ?? [];

```

```

227     const passRate = mySoldiers.length > 0 ? Math.round(((data.fit?.length ?? 0) / mySoldiers.length) *
100) : 0;
228     return (
229       <ScrollView style={[styles.root, { backgroundColor: colors.background }]}
230         contentContainerStyle={[styles.content, { paddingTop, paddingBottom }]}
231         refreshControl={<RefreshControl refreshing={refreshing} onRefresh={onRefresh}
tintColor={colors.primary} />}
232         <View style={styles.greetRow}>
233           <View>
234             <Text style={[styles.greetSmall, { color: colors.mutedForeground }]}>{comp} Company Commander</
Text>
235             <Text style={[styles.greetName, { color: colors.foreground }]}>{user.name}</Text>
236             <Text style={[styles.greetBA, { color: colors.mutedForeground }]}>{user.ba}</Text>
237           </View>
238           <View style={[styles.roleBadge, { backgroundColor: colors.primary }]}>
239             <Text style={styles.roleBadgeText}>{comp} COY</Text>
240           </View>
241         </View>
242         {renderIPFTBanner()}
243         <SectionHeader title={`{comp} Company Strength`} />
244         <View style={styles.statsGrid}>
245           <StatCard label="Total" value={mySoldiers.length} icon="account-group" color={colors.primary}
onPress={() => router.push('/(tabs)/soldiers')} />
246           <StatCard label="Fit" value={data.fit?.length ?? 0} icon="check-circle" color={colors.success} />
247           <StatCard label="Unfit" value={data.unfit?.length ?? 0} icon="close-circle"
color={colors.destructive} />
248           <StatCard label="Overweight" value={data.overweight?.length ?? 0} icon="alert"
color={colors.warning} />
249         </View>
250         <View style={[styles.passRateCard, { backgroundColor: colors.primary + '15', borderColor:
colors.primary }]}>
251           <Text style={[styles.passRateTitle, { color: colors.primary }]}>PT Pass Rate</Text>
252           <Text style={[styles.passRateBig, { color: passRate >= 70 ? colors.success :
colors.destructive }]}>{passRate}%</Text>
253           <Text style={[styles.passRateSub, { color: colors.mutedForeground }]}>{data.fit?.length ?? 0} of
{mySoldiers.length} soldiers</Text>
254         </View>
255         <SectionHeader title="IPFT Result Breakdown" />
256         <View style={[styles.chartCard, { backgroundColor: colors.card, borderColor: colors.border }]}>
257           <BarChart
258             height={100}
259             labelColor={colors.foreground}
260             subColor={colors.mutedForeground}
261             trackColor={colors.muted}
262             data={[
263               { label: 'Fit', value: data.fit?.length ?? 0, color: colors.success },
264               { label: 'Unfit', value: data.unfit?.length ?? 0, color: colors.destructive },
265               { label: 'Overweight', value: data.overweight?.length ?? 0, color: colors.warning },
266             ]}
267           />
268         </View>
269         {(data.overweight?.length ?? 0) > 0 && (
270           <
271             <SectionHeader title="Overweight Soldiers" />
272             {data.overweight?.map((s: Soldier) => (
273               <TouchableOpacity key={s.id} style={[styles.alertCard, { backgroundColor: colors.warning +
'10', borderColor: colors.warning }]}
274               onPress={() => router.push(`/soldier/${s.id}`)} activeOpacity={0.75}>
275                 <MaterialCommunityIcons name="alert" size={20} color={colors.warning} />
276                 <View style={{ flex: 1 }}>
277                   <Text style={[styles.alertName, { color: colors.foreground }]}>{s.rank} {s.name}</Text>
278                   <Text style={[styles.alertSub, { color: colors.mutedForeground }]}>{s.serviceNumber} ·
BMI: {calcBMI(s.weight, s.height)}</Text>
279                 </View>
280                 <Feather name="chevron-right" size={16} color={colors.mutedForeground} />
281               </TouchableOpacity>
282             )]}
283           </>
284         )}
285       </ScrollView>
286     );
287   }
288
289   if (user.role === 'adjutant') {
290     const pending = data.allSoldiers?.filter((s: Soldier) => !s.isApproved) ?? [];
291     const unreadReports = data.reports?.filter((r: any) => !r.read && r.toRole === 'adjutant') ?? [];
292     return (
293       <ScrollView style={[styles.root, { backgroundColor: colors.background }]}
294         contentContainerStyle={[styles.content, { paddingTop, paddingBottom }]}
295         refreshControl={<RefreshControl refreshing={refreshing} onRefresh={onRefresh}
tintColor={colors.primary} />}
296         <View style={styles.greetRow}>
297           <View>
298             <Text style={[styles.greetSmall, { color: colors.mutedForeground }]}>Adjutant</Text>
299             <Text style={[styles.greetName, { color: colors.foreground }]}>{user.name}</Text>

```

```

300         <Text style=[[styles.greetBA, { color: colors.mutedForeground }]]>{user.ba}</Text>
301     </View>
302     <View style=[[styles.roleBadge, { backgroundColor: colors.primary }]]>
303         <Text style={styles.roleBadgeText}>ADJT</Text>
304     </View>
305 </View>
306 {renderIPFTBanner()}
307 <View style={styles.statsGrid}>
308     <StatCard label="Total Soldiers" value={data.approvedSoldiers?.length ?? 0} icon="account-group"
color={colors.primary} onPress={() => router.push('/(tabs)/soldiers')} />
309     <StatCard label="Pending Approval" value={pending.length} icon="account-clock"
color={colors.warning} />
310     <StatCard label="New Reports" value={unreadReports.length} icon="file-alert"
color={colors.accent} onPress={() => router.push('/(tabs)/reports')} />
311     <StatCard label="Unfit Soldiers" value={data.approvedSoldiers?.filter((s: Soldier) => s.ptStatus
=== 'unfit').length ?? 0} icon="close-circle" color={colors.destructive} />
312 </View>
313     <TouchableOpacity style=[[styles.newPlanBtn, { backgroundColor: colors.accent }]] onPress={() =>
router.push('/(tabs)/notifications')}>
314         <Feather name="send" size={20} color="#FFF" />
315         <Text style={styles.newPlanBtnText}>Propose IPFT Date to CO</Text>
316     </TouchableOpacity>
317     <SectionHeader title="IPFT Schedule Status" />
318     {data.schedule ? (
319         <View style=[[styles.scheduleCard, { backgroundColor: colors.card, borderColor: colors.border }]]>
320             <Text style=[[styles.scheduleDateLabel, { color: colors.mutedForeground }]]>Proposed Date</Text>
321             <Text style={styles.scheduleDate, { color: colors.foreground }}>
>{formatDate(data.schedule.proposedDate)}</Text>
322             <View style=[[styles.scheduleStatus, { backgroundColor: data.schedule.status === 'approved' ?
colors.success + '20' : data.schedule.status === 'rejected' ? colors.destructive + '20' : colors.warning +
'20' }]]>
323                 <Text style={{ fontSize: 12, fontFamily: 'Inter_600SemiBold', color: data.schedule.status ===
'approved' ? colors.success : data.schedule.status === 'rejected' ? colors.destructive : colors.warning }}>
324                     {data.schedule.status.toUpperCase()}
325                 </Text>
326             </View>
327         </View>
328     ) : (
329         <Text style={styles.noSchedule, { color: colors.mutedForeground }}>No IPFT date proposed yet.</
Text>
330     )}
331 </ScrollView>
332 );
333 }
334
335 if (user.role === 'clerk') {
336     return (
337         <ScrollView style=[[styles.root, { backgroundColor: colors.background }]]
338             contentContainerStyle={styles.content, { paddingTop, paddingBottom }}
339             refreshControl={<RefreshControl refreshing={refreshing} onRefresh={onRefresh}
tintColor={colors.primary} />}>
340             <View style={styles.greetRow}>
341                 <View>
342                     <Text style=[[styles.greetSmall, { color: colors.mutedForeground }]]>Clerk</Text>
343                     <Text style=[[styles.greetName, { color: colors.foreground }]]>{user.name}</Text>
344                     <Text style=[[styles.greetBA, { color: colors.mutedForeground }]]>{user.ba}</Text>
345                 </View>
346                 <View style={styles.roleBadge, { backgroundColor: colors.primary }}>
347                     <Text style={styles.roleBadgeText}>CLERK</Text>
348                 </View>
349             </View>
350             {renderIPFTBanner()}
351             <View style={styles.statsGrid}>
352                 <StatCard label="Total Soldiers" value={data.approvedSoldiers?.length ?? 0} icon="account-group"
color={colors.primary} onPress={() => router.push('/(tabs)/soldiers')} />
353                 <StatCard label="Results Logged" value={data.results?.length ?? 0} icon="clipboard-check"
color={colors.success} />
354                 <StatCard label="Overweight" value={data.approvedSoldiers?.filter((s: Soldier) =>
s.isOverweight).length ?? 0} icon="alert" color={colors.warning} />
355                 <StatCard label="Unfit" value={data.approvedSoldiers?.filter((s: Soldier) => s.ptStatus ===
'unfit').length ?? 0} icon="close-circle" color={colors.destructive} />
356             </View>
357             <TouchableOpacity style=[[styles.newPlanBtn, { backgroundColor: colors.primary }]] onPress={() =>
router.push('/result/new')}>
358                 <Feather name="plus-circle" size={20} color="#FFF" />
359                 <Text style={styles.newPlanBtnText}>Record IPFT Result</Text>
360             </TouchableOpacity>
361             <TouchableOpacity style=[[styles.newPlanBtn, { backgroundColor: colors.accent, marginTop: 8 }]]
onPress={() => router.push('/(tabs)/reports')}>
362                 <Feather name="file-text" size={20} color="#FFF" />
363                 <Text style={styles.newPlanBtnText}>Send Report</Text>
364             </TouchableOpacity>
365         </ScrollView>
366     );
367 }

```

```

368
369   if (user.role === 'soldier') {
370     const mySol = data.allSoldiers?.find((s: Soldier) => s.userId === user.id);
371     const latestResult = data.soldierResults?.[0];
372     const failedItems = latestResult?.items.filter((i: any) => i.status === 'fail') ?? [];
373     const bmi = data.soldierBMI;
374     const bmiOk = bmi ? bmi < 25 : true;
375
376     return (
377       <ScrollView style={{[styles.root, { backgroundColor: colors.background }]}
378         contentContainerStyle={{[styles.content, { paddingTop, paddingBottom }]}
379         refreshControl={<RefreshControl refreshing={refreshing} onRefresh={onRefresh}
tintColor={colors.primary} />}>
380         <View style={styles.greetRow}>
381           <View>
382             <Text style={{[styles.greetSmall, { color: colors.mutedForeground }]}>{user.rank} .
{mySol?.company ?? ''} Company</Text>
383             <Text style={{[styles.greetName, { color: colors.foreground }]}>{user.name}</Text>
384             <Text style={{[styles.greetBA, { color: colors.mutedForeground }]}>{user.ba}</Text>
385           </View>
386           <View style={{[styles.roleBadge, { backgroundColor: mySol?.ptStatus === 'fit' ? colors.success :
mySol?.ptStatus === 'unfit' ? colors.destructive : colors.muted }]}>
387             <Text style={styles.roleBadgeText}>{mySol?.ptStatus?.toUpperCase() ?? 'PENDING'}</Text>
388           </View>
389         </View>
390         {data.schedule?.status === 'approved' && (
391           <View style={{[styles.countdownCard, { backgroundColor: colors.primary }]}>
392             <Text style={styles.countdownLabel}>Next IPFT</Text>
393             <Text style={styles.countdownDate}>{formatDate(data.schedule.proposedDate)}</Text>
394             <View style={styles.countdownDaysRow}>
395               <Text style={styles.countdownDays}>{data.ipftDaysLeft ?? '-'}</Text>
396               <Text style={styles.countdownDaysLabel}>days remaining</Text>
397             </View>
398           </View>
399         )}
400         {mySol?.isOverweight && (
401           <View style={{[styles.alertBanner, { backgroundColor: colors.warning + '15', borderColor:
colors.warning }]}>
402             <MaterialCommunityIcons name="alert" size={20} color={colors.warning} />
403             <Text style={{[styles.alertBannerText, { color: colors.warning }]}>You are currently OVERWEIGHT.
BMI: {bmi}. Follow your assigned rehabilitation plan.</Text>
404           </View>
405         )}
406         {failedItems.length > 0 && (
407           <View style={{[styles.alertBanner, { backgroundColor: colors.destructive + '10', borderColor:
colors.destructive }]}>
408             <Feather name="x-circle" size={20} color={colors.destructive} />
409             <View style={{ flex: 1 }}>
410               <Text style={{[styles.alertBannerText, { color: colors.destructive }]}>Failed IPFT Items:</
Text>
411               {failedItems.map((item: any, i: number) => (
412                 <Text key={i} style={{[styles.failedItem, { color: colors.destructive }]}>• {item.name}
{item.achieved} / target: {item.target}</Text>
413               ))}
414             </View>
415           </View>
416         )}
417         <View style={styles.statsGrid}>
418           {bmi && <StatCard label="BMI" value={bmi} icon={bmiOk ? 'check-circle' : 'alert'} color={bmiOk ?
colors.success : colors.warning} />}
419           <StatCard label="IPFT Records" value={data.soldierResults?.length ?? 0} icon="history"
color={colors.primary} />
420           <StatCard label="Height" value={mySol ? `${mySol.height}cm` : '-'} icon="human-male-height"
color={colors.mutedForeground} />
421           <StatCard label="Weight" value={mySol ? `${mySol.weight}kg` : '-'} icon="weight-kilogram"
color={colors.mutedForeground} />
422         </View>
423         {(data.soldierResults?.length ?? 0) > 1 && (
424           <>
425             <SectionHeader title="IPFT Trend" />
426             <View style={{[styles.chartCard, { backgroundColor: colors.card, borderColor: colors.border }]}>
427               <BarChart
428                 height={90}
429                 maxValue={Math.max(...data.soldierResults.map((r: IPFTResult) => r.items.length))}
430                 labelColor={colors.foreground}
431                 subColor={colors.mutedForeground}
432                 trackColor={colors.muted}
433                 data={[...data.soldierResults].reverse().slice(-6).map((r: IPFTResult) => ({
434                   label: new Date(r.date).toLocaleDateString('en-BD', { day: '2-digit', month: 'short' }),
435                   value: r.items.filter(i => i.status === 'pass').length,
436                   color: r.overallStatus === 'pass' ? colors.success : colors.destructive,
437                   sublabel: `${r.items.filter(i => i.status === 'pass').length}/${r.items.length}`,
438                 })]}
439               />
440             </View>

```

```

441         </>
442     })
443     {latestResult && (
444         <>
445             <SectionHeader title="Last IPFT Result" />
446             <View style={[styles.resultCard, { backgroundColor: latestResult.overallStatus === 'pass' ?
colors.success + '10' : colors.destructive + '10', borderColor: latestResult.overallStatus === 'pass' ?
colors.success : colors.destructive }]}>
447                 <View style={styles.resultHeader}>
448                     <Text style={[styles.resultDate, { color: colors.foreground }]}>{latestResult.date}</Text>
449                     <View style={[styles.resultBadge, { backgroundColor: latestResult.overallStatus ===
'pass' ? colors.success : colors.destructive }]}>
450                         <Text style={styles.resultBadgeText}>{latestResult.overallStatus.toUpperCase()}</Text>
451                     </View>
452                 </View>
453                 {latestResult.items.map((item: any, i: number) => (
454                     <View key={i} style={styles.resultItem}>
455                         <Text style={[styles.resultItemName, { color: colors.foreground }]}>{item.name}</Text>
456                         <View style={styles.resultItemRight}>
457                             <Text style={[styles.resultItemVal, { color: item.status === 'pass' ? colors.success :
colors.destructive }]}>{item.achieved}</Text>
458                             <MaterialCommunityIcons name={item.status === 'pass' ? 'check-circle' : 'close-circle'}
size={16} color={item.status === 'pass' ? colors.success : colors.destructive} />
459                         </View>
460                     </View>
461                 )))
462             </View>
463         </>
464     })
465     {data.myPlan && (
466         <>
467             <SectionHeader title="My PT Plan" />
468             <TouchableOpacity style={[styles.planCard, { backgroundColor: colors.card, borderColor:
colors.border }]}
469                 onPress={() => router.push(`/plan/${data.myPlan.id}`)} activeOpacity={0.75}>
470                 <View style={[styles.planType, { backgroundColor: data.myPlan.type === 'fit' ?
colors.success : colors.warning }]}>
471                     <Text style={styles.planTypeText}>{data.myPlan.type === 'fit' ? 'FIT' : 'REHAB'}</Text>
472                 </View>
473                 <View style={{ flex: 1 }}>
474                     <Text style={[styles.planTitle, { color: colors.foreground }]}>{data.myPlan.title}</Text>
475                     <Text style={[styles.planMeta, { color: colors.mutedForeground }]}>Week
{data.myPlan.weekNumber} · Tap to view</Text>
476                 </View>
477                 <Feather name="chevron-right" size={18} color={colors.mutedForeground} />
478             </TouchableOpacity>
479         </>
480     })
481 </ScrollView>
482 );
483 }
484
485 return null;
486 }
487
488 const styles = StyleSheet.create({
489     root: { flex: 1 },
490     content: { paddingHorizontal: 16, gap: 8 },
491     greetRow: { flexDirection: 'row', alignItems: 'flex-start', justifyContent: 'space-between',
marginBottom: 8 },
492     greetSmall: { fontSize: 12, fontFamily: 'Inter_400Regular', marginBottom: 2 },
493     greetName: { fontSize: 20, fontFamily: 'Inter_700Bold' },
494     greetBA: { fontSize: 12, fontFamily: 'Inter_400Regular', marginTop: 2 },
495     roleBadge: { borderRadius: 8, paddingHorizontal: 12, paddingVertical: 6 },
496     roleBadgeText: { fontSize: 11, fontFamily: 'Inter_700Bold', color: '#FFF', letterSpacing: 1 },
497     sectionHeader: { fontSize: 15, fontFamily: 'Inter_700Bold', marginTop: 8, marginBottom: 4 },
498     statsGrid: { flexDirection: 'row', flexWrap: 'wrap', gap: 10, marginBottom: 4 },
499     statCard: { flex: 1, minWidth: '45%', borderRadius: 12, padding: 14, gap: 6, alignItems: 'center',
borderWidth: 1 },
500     statIcon: { width: 44, height: 44, borderRadius: 22, alignItems: 'center', justifyContent: 'center' },
501     statValue: { fontSize: 22, fontFamily: 'Inter_700Bold' },
502     statLabel: { fontSize: 11, fontFamily: 'Inter_400Regular', textAlign: 'center' },
503     ipftBanner: { flexDirection: 'row', alignItems: 'center', gap: 12, padding: 14, borderRadius: 12,
borderWidth: 1.5, marginBottom: 8 },
504     ipftBannerTitle: { fontSize: 11, fontFamily: 'Inter_700Bold', letterSpacing: 1 },
505     ipftBannerDate: { fontSize: 16, fontFamily: 'Inter_700Bold', marginTop: 2 },
506     ipftCountdown: { fontSize: 12, fontFamily: 'Inter_500Medium', marginTop: 1 },
507     chartCard: { borderRadius: 14, borderWidth: 1, padding: 16, paddingTop: 18, marginBottom: 8 },
508     companyRow: { flexDirection: 'row', alignItems: 'center', gap: 12, padding: 14, borderRadius: 12,
borderWidth: 1, marginBottom: 8 },
509     companyBadge: { width: 38, height: 38, borderRadius: 19, alignItems: 'center', justifyContent: 'center' },
510     companyBadgeText: { fontSize: 14, fontFamily: 'Inter_700Bold', color: '#FFF' },
511     companyLabel: { fontSize: 14, fontFamily: 'Inter_600SemiBold' },
512     companyStats: { fontSize: 12, fontFamily: 'Inter_400Regular', marginTop: 2 },
513     passRate: { fontSize: 18, fontFamily: 'Inter_700Bold' },

```

```

514   passRateCard: { borderRadius: 14, padding: 20, alignItems: 'center', borderWidth: 1.5, marginBottom: 8,
gap: 4 },
515   passRateTitle: { fontSize: 11, fontFamily: 'Inter_600SemiBold', letterSpacing: 1.5 },
516   passRateBig: { fontSize: 44, fontFamily: 'Inter_700Bold' },
517   passRateSub: { fontSize: 13, fontFamily: 'Inter_400Regular' },
518   alertCard: { flexDirection: 'row', alignItems: 'center', gap: 12, padding: 12, borderRadius: 12,
borderWidth: 1, marginBottom: 8 },
519   alertName: { fontSize: 14, fontFamily: 'Inter_600SemiBold' },
520   alertSub: { fontSize: 12, fontFamily: 'Inter_400Regular', marginTop: 1 },
521   scheduleCard: { borderRadius: 12, padding: 16, borderWidth: 1, gap: 6 },
522   scheduleDateLabel: { fontSize: 11, fontFamily: 'Inter_400Regular' },
523   scheduleDate: { fontSize: 18, fontFamily: 'Inter_700Bold' },
524   scheduleStatus: { borderRadius: 20, paddingHorizontal: 12, paddingVertical: 4, alignSelf: 'flex-start' },
525   noSchedule: { fontSize: 14, fontFamily: 'Inter_400Regular', fontStyle: 'italic' },
526   newPlanBtn: { flexDirection: 'row', alignItems: 'center', justifyContent: 'center', gap: 8, borderRadius:
12, paddingVertical: 14, marginBottom: 8 },
527   newPlanBtnText: { fontSize: 15, fontFamily: 'Inter_600SemiBold', color: '#FFF' },
528   planCard: { flexDirection: 'row', alignItems: 'center', gap: 12, padding: 14, borderRadius: 12,
borderWidth: 1.5, marginBottom: 8 },
529   planType: { borderRadius: 6, paddingHorizontal: 8, paddingVertical: 4 },
530   planTypeText: { fontSize: 10, fontFamily: 'Inter_700Bold', color: '#FFF', letterSpacing: 0.5 },
531   planTitle: { fontSize: 14, fontFamily: 'Inter_600SemiBold' },
532   planMeta: { fontSize: 12, fontFamily: 'Inter_400Regular', marginTop: 2 },
533   countdownCard: { borderRadius: 16, padding: 24, alignItems: 'center', gap: 4, marginBottom: 8 },
534   countdownLabel: { fontSize: 11, fontFamily: 'Inter_600SemiBold', color: 'rgba(255,255,255,0.7)',
letterSpacing: 1.5 },
535   countdownDate: { fontSize: 16, fontFamily: 'Inter_600SemiBold', color: '#FFF' },
536   countdownDaysRow: { flexDirection: 'row', alignItems: 'baseline', gap: 6, marginTop: 4 },
537   countdownDays: { fontSize: 48, fontFamily: 'Inter_700Bold', color: '#FFF' },
538   countdownDaysLabel: { fontSize: 14, fontFamily: 'Inter_400Regular', color: 'rgba(255,255,255,0.8)' },
539   alertBanner: { flexDirection: 'row', gap: 10, padding: 12, borderRadius: 12, borderWidth: 1,
marginBottom: 8, alignItems: 'flex-start' },
540   alertBannerText: { fontSize: 13, fontFamily: 'Inter_600SemiBold', flex: 1 },
541   failedItem: { fontSize: 12, fontFamily: 'Inter_400Regular', marginTop: 2 },
542   resultCard: { borderRadius: 12, padding: 14, borderWidth: 1.5, marginBottom: 8, gap: 10 },
543   resultHeader: { flexDirection: 'row', alignItems: 'center', justifyContent: 'space-between' },
544   resultDate: { fontSize: 14, fontFamily: 'Inter_600SemiBold' },
545   resultBadge: { borderRadius: 6, paddingHorizontal: 8, paddingVertical: 4 },
546   resultBadgeText: { fontSize: 10, fontFamily: 'Inter_700Bold', color: '#FFF' },
547   resultItem: { flexDirection: 'row', alignItems: 'center', justifyContent: 'space-between' },
548   resultItemName: { fontSize: 13, fontFamily: 'Inter_400Regular', flex: 1 },
549   resultItemRight: { flexDirection: 'row', alignItems: 'center', gap: 4 },
550   resultItemVal: { fontSize: 13, fontFamily: 'Inter_600SemiBold' },
551 });
552

```

app/(tabs)/messages.tsx

```
1  import React, { useState, useCallback } from 'react';
2  import {
3    View, Text, StyleSheet, FlatList, TouchableOpacity,
4    Platform, RefreshControl, TextInput, Modal, ScrollView,
5  } from 'react-native';
6  import { useSafeAreaInsets } from 'react-native-safe-area-context';
7  import { Feather } from '@expo/vector-icons';
8  import * as Haptics from 'expo-haptics';
9  import { useFocusEffect } from 'expo-router';
10 import { useColors } from '@hooks/useColors';
11 import { useAuth } from '@context/AuthContext';
12 import { showAlert } from '@lib/alert';
13 import { getMessages, addMessage, markMessageRead, getUsers, genId } from '@lib/storage';
14 import type { Message, User } from '@lib/types';
15
16 const ROLE_LABELS: Record<string, string> = {
17   co: 'CO', '2ic': '2IC', coy_comd: 'Coy Comd', adjutant: 'Adjutant', clerk: 'Clerk', soldier: 'Soldier',
18 };
19
20 export default function MessagesScreen() {
21   const colors = useColors();
22   const insets = useSafeAreaInsets();
23   const { user } = useAuth();
24   const isWeb = Platform.OS === 'web';
25
26   const [messages, setMessages] = useState<Message[]>([]);
27   const [contacts, setContacts] = useState<User[]>([]);
28   const [refreshing, setRefreshing] = useState(false);
29   const [composeVisible, setComposeVisible] = useState(false);
30   const [selectedMsg, setSelectedMsg] = useState<Message | null>(null);
31   const [recipientPicker, setRecipientPicker] = useState(false);
32   const [recipient, setRecipient] = useState<User | null>(null);
33   const [subject, setSubject] = useState('');
34   const [content, setContent] = useState('');
35
36   const load = useCallback(async () => {
37     if (!user) return;
38     const [all, users] = await Promise.all([getMessages(), getUsers()]);
39     const mine = all.filter(m => m.fromId === user.id || m.toId === user.id);
40     setMessages(mine);
41     setContacts(users.filter(u => u.role !== 'soldier' && u.id !== user.id));
42   }, [user]);
43
44   useFocusEffect(useCallback(() => { load(); }, [load]));
45
46   const onRefresh = async () => { setRefreshing(true); await load(); setRefreshing(false); };
47
48   const resetCompose = () => {
49     setRecipient(null);
50     setSubject('');
51     setContent('');
52   };
53
54   const handleSend = async () => {
55     if (!recipient) { showAlert('Error', 'Please select a recipient.');
```

```
return; }
56     if (!subject.trim() || !content.trim()) { showAlert('Error', 'Please fill in subject and message.');
```

```
return; }
57     Haptics.impactAsync(Haptics.ImpactFeedbackStyle.Medium);
58     await addMessage({
59       id: genId(), fromId: user!.id, fromName: user!.name, fromRole: user!.role,
60       toId: recipient.id, toRole: recipient.role,
61       subject: subject.trim(), content: content.trim(),
62       read: false, createdAt: new Date().toISOString(),
63     });
64     setComposeVisible(false);
65     resetCompose();
66     await load();
67     Haptics.notificationAsync(Haptics.NotificationFeedbackType.Success);
68   };
69
70   const formatDate = (d: string) => new Date(d).toLocaleDateString('en-BD', { day: '2-digit', month:
'short', hour: '2-digit', minute: '2-digit' });
71
72   const renderItem = ({ item }: { item: Message }) => {
73     const isFrom = item.fromId === user?.id;
74     return (
75       <TouchableOpacity
76         style={[styles.msgCard, { backgroundColor: colors.card, borderColor: item.read || isFrom ?
colors.border : colors.primary }]}
77         onPress={async () => { if (!isFrom) await markMessageRead(item.id); setSelectedMsg(item); await
load(); }}
78         activeOpacity={0.75}
79       >
```

```

80         <View style={styles.msgHeader}>
81             <View style={styles.msgMeta}>
82                 {!item.read && !isFrom && <View style={[styles.unreadDot, { backgroundColor:
colors.primary }]} />}
83                 <Text style={[styles.msgSubject, { color: colors.foreground }]} numberOfLines={1}>{item.subject}
</Text>
84             </View>
85             <Text style={[styles.msgDate, { color: colors.mutedForeground }]}>{formatDate(item.createdAt)}</
Text>
86         </View>
87         <Text style={[styles.msgFrom, { color: colors.mutedForeground }]}>
88             {isFrom ? `To: ${item.fromName === item.toId ? '' : ''}${ROLE_LABELS[item.toRole] ?? item.toRole}
` : `From: ${item.fromName} · ${ROLE_LABELS[item.fromRole] ?? item.fromRole}`}
89         </Text>
90         <Text style={[styles.msgPreview, { color: colors.mutedForeground }]} numberOfLines={2}
>{item.content}</Text>
91     </TouchableOpacity>
92     );
93 };
94
95     const paddingTop = 16;
96     const paddingBottom = isWeb ? 34 : insets.bottom + 90;
97
98     if (user?.role === 'soldier') return null;
99
100    return (
101        <View style={[styles.root, { backgroundColor: colors.background }]}>
102            <View style={[styles.header, { paddingTop, backgroundColor: colors.background }]}>
103                <Text style={[styles.title, { color: colors.foreground }]}>Messages</Text>
104                <TouchableOpacity style={[styles.composeBtn, { backgroundColor: colors.primary }]} onPress={() =>
{ resetCompose(); setComposeVisible(true); }}>
105                    <Feather name="edit-3" size={16} color="#FFF" />
106                    <Text style={styles.composeBtnText}>New Message</Text>
107                </TouchableOpacity>
108            </View>
109
110            <FlatList
111                data={messages}
112                keyExtractor={i => i.id}
113                renderItem={renderItem}
114                contentContainerStyle={[styles.list, { paddingBottom }]}
115                refreshControl={<RefreshControl refreshing={refreshing} onRefresh={onRefresh}
tintColor={colors.primary} />}
116                ItemSeparatorComponent={() => <View style={{ height: 8 }} />}
117                ListEmptyComponent={
118                    <View style={styles.empty}>
119                        <Feather name="message-square" size={48} color={colors.border} />
120                        <Text style={[styles.emptyText, { color: colors.mutedForeground }]}>No messages yet</Text>
121                        <Text style={[styles.emptySubtext, { color: colors.mutedForeground }]}>Start a conversation
with anyone on staff.</Text>
122                    </View>
123                }
124            />
125
126            {/* Compose modal */}
127            <Modal visible={composeVisible} transparent animationType="slide" onRequestClose={() =>
setComposeVisible(false)}>
128                <View style={styles.modalOverlay}>
129                    <View style={[styles.modalSheet, { backgroundColor: colors.card, paddingBottom: insets.bottom +
20, maxHeight: '88%' }]}>
130                        <View style={styles.modalHandle} />
131                        <ScrollView keyboardShouldPersistTaps="handled">
132                            <Text style={[styles.modalTitle, { color: colors.foreground }]}>New Message</Text>
133
134                            <Text style={[styles.modalLabel, { color: colors.mutedForeground }]}>To</Text>
135                            <TouchableOpacity style={[styles.recipientBtn, { borderColor: colors.border, backgroundColor:
colors.background }]} onPress={() => setRecipientPicker(true)}>
136                                <Text style={[styles.recipientText, recipient ? { color: colors.foreground } : { color:
colors.mutedForeground }]}>
137                                    {recipient ? `${recipient.name} · ${ROLE_LABELS[recipient.role] ?? recipient.role}` :
'Select recipient...'}
138                                </Text>
139                                <Feather name="chevron-down" size={16} color={colors.mutedForeground} />
140                            </TouchableOpacity>
141
142                            <Text style={[styles.modalLabel, { color: colors.mutedForeground }]}>Subject</Text>
143                            <TextInput style={[styles.modalInput, { borderColor: colors.border, color: colors.foreground,
backgroundColor: colors.background }]}
144                                value={subject} onChangeText={setSubject} placeholder="Subject..."
placeholderTextColor={colors.mutedForeground} />
145
146                            <Text style={[styles.modalLabel, { color: colors.mutedForeground }]}>Message</Text>
147                            <TextInput style={[styles.modalInput, { borderColor: colors.border, color: colors.foreground,
backgroundColor: colors.background, height: 110, textAlignVertical: 'top' }]}
148                                value={content} onChangeText={setContent} placeholder="Write your message..."

```

```

placeholderTextColor={colors.mutedForeground} multiline />
149
150         <TouchableOpacity style={[styles.sendBtn, { backgroundColor: colors.primary }]}
onPress={handleSend}>
151             <Feather name="send" size={18} color="#FFF" />
152             <Text style={styles.sendBtnText}>Send</Text>
153         </TouchableOpacity>
154         <TouchableOpacity style={[styles.cancelBtn, { borderColor: colors.border }]} onPress={() =>
setComposeVisible(false)}>
155             <Text style={[styles.cancelBtnText, { color: colors.mutedForeground }]}>Cancel</Text>
156         </TouchableOpacity>
157     </ScrollView>
158 </View>
159 </View>
160 </Modal>
161
162     {/* Recipient picker */}
163     <Modal visible={recipientPicker} transparent animationType="slide" onRequestClose={() =>
setRecipientPicker(false)}>
164         <TouchableOpacity style={styles.modalOverlay} activeOpacity={1} onPress={() =>
setRecipientPicker(false)}>
165             <View style={[styles.modalSheet, { backgroundColor: colors.card, paddingBottom: insets.bottom +
16, maxHeight: '75%' }]}>
166                 <View style={styles.modalHandle} />
167                 <Text style={[styles.modalTitle, { color: colors.foreground }]}>Select Recipient</Text>
168                 <FlatList
169                     data={contacts}
170                     keyExtractor={i => i.id}
171                     style={{ maxHeight: 380 }}
172                     renderItem={({ item }) => (
173                         <TouchableOpacity style={[styles.contactRow, { borderBottomColor: colors.border }]}
174                             onPress={() => { setRecipient(item); setRecipientPicker(false);
Haptics.selectionAsync(); }}>
175                             <View style={[styles.contactAvatar, { backgroundColor: colors.primary + '20' }]}>
176                                 <Text style={[styles.contactAvatarText, { color: colors.primary }]}>{item.name.slice(0,
2)}.toUpperCase()</Text>
177                             </View>
178                             <View style={{ flex: 1 }}>
179                                 <Text style={[styles.contactName, { color: colors.foreground }]}>{item.name}</Text>
180                                 <Text style={[styles.contactRole, { color: colors.mutedForeground }]}>
181                                     {ROLE_LABELS[item.role] ?? item.role}{item.company ? ` · ${item.company} Coy` : ''}
182                                 </Text>
183                             </View>
184                         </TouchableOpacity>
185                     )}
186                     ListEmptyComponent={<Text style={{ color: colors.mutedForeground, textAlign: 'center',
paddingVertical: 20 }}>No contacts available</Text>}
187                 </View>
188             </View>
189         </TouchableOpacity>
190     </Modal>
191
192     {/* Message detail modal */}
193     <Modal visible={!selectedMsg} transparent animationType="slide" onRequestClose={() =>
setSelectedMsg(null)}>
194         <View style={styles.modalOverlay}>
195             <View style={[styles.modalSheet, { backgroundColor: colors.card, paddingBottom: insets.bottom +
20, maxHeight: '80%' }]}>
196                 <View style={styles.modalHandle} />
197                 <ScrollView>
198                     <Text style={[styles.modalTitle, { color: colors.foreground }]}>{selectedMsg?.subject}</Text>
199                     <Text style={[styles.modalLabel, { color: colors.mutedForeground }]}>From:
{selectedMsg?.fromName} · {formatDate(selectedMsg?.createdAt ?? '')}</Text>
200                     <Text style={[styles.modalBody, { color: colors.foreground }]}>{selectedMsg?.content}</Text>
201                 </ScrollView>
202                 <TouchableOpacity style={[styles.cancelBtn, { borderColor: colors.border, marginTop: 12 }]}
onPress={() => setSelectedMsg(null)}>
203                     <Text style={[styles.cancelBtnText, { color: colors.mutedForeground }]}>Close</Text>
204                 </TouchableOpacity>
205             </View>
206         </View>
207     </Modal>
208 </View>
209 );
210 }
211
212 const styles = StyleSheet.create({
213     root: { flex: 1 },
214     header: { flexDirection: 'row', alignItems: 'center', justifyContent: 'space-between', paddingHorizontal:
16, paddingBottom: 12 },
215     title: { fontSize: 24, fontFamily: 'Inter_700Bold' },
216     composeBtn: { flexDirection: 'row', alignItems: 'center', gap: 6, borderRadius: 10, paddingHorizontal:
12, paddingVertical: 8 },
217     composeBtnText: { fontSize: 13, fontFamily: 'Inter_600SemiBold', color: '#FFF' },
218     list: { paddingHorizontal: 16, paddingTop: 4 },

```

```

219 msgCard: { borderRadius: 12, borderWidth: 1.5, padding: 14, gap: 4 },
220 msgHeader: { flexDirection: 'row', alignItems: 'center', justifyContent: 'space-between', gap: 8 },
221 msgMeta: { flexDirection: 'row', alignItems: 'center', gap: 6, flex: 1 },
222 unreadDot: { width: 8, height: 8, borderRadius: 4 },
223 msgSubject: { fontSize: 14, fontFamily: 'Inter_600SemiBold', flex: 1 },
224 msgDate: { fontSize: 10, fontFamily: 'Inter_400Regular' },
225 msgFrom: { fontSize: 11, fontFamily: 'Inter_400Regular' },
226 msgPreview: { fontSize: 13, fontFamily: 'Inter_400Regular', lineHeight: 18 },
227 empty: { alignItems: 'center', paddingVertical: 60, gap: 8 },
228 emptyText: { fontSize: 15, fontFamily: 'Inter_400Regular' },
229 emptySubtext: { fontSize: 12, fontFamily: 'Inter_400Regular' },
230 modalOverlay: { flex: 1, backgroundColor: 'rgba(0,0,0,0.5)', justifyContent: 'flex-end' },
231 modalSheet: { borderTopLeftRadius: 20, borderTopRightRadius: 20, paddingHorizontal: 20, paddingTop: 12 },
232 modalHandle: { width: 40, height: 4, borderRadius: 2, backgroundColor: '#ccc', alignSelf: 'center',
marginBottom: 16 },
233 modalTitle: { fontSize: 18, fontFamily: 'Inter_700Bold', marginBottom: 16 },
234 modalLabel: { fontSize: 12, fontFamily: 'Inter_500Medium', marginBottom: 6 },
235 modalInput: { borderWidth: 1, borderRadius: 8, padding: 12, fontSize: 14, fontFamily: 'Inter_400Regular',
marginBottom: 12 },
236 modalBody: { fontSize: 14, fontFamily: 'Inter_400Regular', lineHeight: 22, marginBottom: 16 },
237 recipientBtn: { flexDirection: 'row', alignItems: 'center', justifyContent: 'space-between', borderWidth:
1, borderRadius: 8, padding: 12, marginBottom: 12 },
238 recipientText: { fontSize: 14, fontFamily: 'Inter_400Regular', flex: 1 },
239 contactRow: { flexDirection: 'row', alignItems: 'center', gap: 12, paddingVertical: 12,
borderBottomWidth: 1 },
240 contactAvatar: { width: 38, height: 38, borderRadius: 19, alignItems: 'center', justifyContent:
'center' },
241 contactAvatarText: { fontSize: 12, fontFamily: 'Inter_700Bold' },
242 contactName: { fontSize: 14, fontFamily: 'Inter_600SemiBold' },
243 contactRole: { fontSize: 12, fontFamily: 'Inter_400Regular', marginTop: 1 },
244 sendBtn: { flexDirection: 'row', alignItems: 'center', justifyContent: 'center', gap: 8, borderRadius:
10, paddingVertical: 13, marginBottom: 8, marginTop: 4 },
245 sendBtnText: { fontSize: 15, fontFamily: 'Inter_600SemiBold', color: '#FFF' },
246 cancelBtn: { borderWidth: 1, borderRadius: 10, paddingVertical: 12, alignItems: 'center' },
247 cancelBtnText: { fontSize: 14, fontFamily: 'Inter_500Medium' },
248 });
249

```

app/(tabs)/notifications.tsx

```
1  import React, { useState, useEffect, useCallba ck } from 'react';
2  import { View, Text, StyleSheet, FlatList, TouchableOpacity, Platform, RefreshControl, TextInput, Modal,
ScrollView } from 'react-native';
3  import { useSafeAreaInsets } from 'react-native-safe-area-context';
4  import { Feather, MaterialCommunityIcons } from '@expo/vector-icons';
5  import * as Haptics from 'expo-haptics';
6  import { useFocusEffect } from 'expo-router';
7  import { useColors } from '@/hooks/useColors';
8  import { useAuth } from '@/context/AuthContext';
9  import { showAlert } from '@/lib/alert';
10 import { getNotifications, markNotificationRead, markAllNotificationsRead, getIPFTSchedule,
saveIPFTSchedule, getUsers, addNotification, genId } from '@/lib/storage';
11 import type { Notification, IPFTSchedule } from '@/lib/types';
12 import { Calendar } from '@/components/Calendar';
13
14 const TODAY = new Date().toISOString().slice(0, 10);
15
16 function notifIcon(type: Notification['type']): { name: string; color: (c: any) => string } {
17   switch (type) {
18     case 'ipft_approved': return { name: 'calendar-check', color: c => c.success };
19     case 'ipft_proposed': return { name: 'calendar-clock', color: c => c.accent };
20     case 'ipft_rejected': return { name: 'calendar-remove', color: c => c.destructive };
21     case 'new_result': return { name: 'clipboard-check', color: c => c.primary };
22     case 'overweight': return { name: 'alert', color: c => c.warning };
23     case 'new_plan': return { name: 'dumbbell', color: c => c.primary };
24     default: return { name: 'bell', color: c => c.mutedForeground };
25   }
26 }
27
28 export default function NotificationsScreen() {
29   const colors = useColors();
30   const insets = useSafeAreaInsets();
31   const { user } = useAuth();
32   const isWeb = Platform.OS === 'web';
33
34   const [notifs, setNotifs] = useState<Notification[]>([]);
35   const [refreshing, setRefreshing] = useState(false);
36   const [schedule, setSchedule] = useState<IPFTSchedule | null>(null);
37   const [proposeVisible, setProposeVisible] = useState(false);
38   const [proposedDate, setProposedDate] = useState('');
39   const [rejectVisible, setRejectVisible] = useState(false);
40   const [rejectionNote, setRejectionNote] = useState('');
41   const [altDate, setAltDate] = useState('');
42
43   const load = useCallba ck(async () => {
44     if (!user) return;
45     const [all, sched] = await Promise.all([getNotifications(), getIPFTSchedule()]);
46     const mine = all.filter(n => {
47       // Personal notices (targetUserId) always win, regardless of role.
48       if (n.targetUserId) return n.targetUserId === user.id;
49       // Soldiers never see company-wide or role-targeted staff alerts about
50       // other soldiers (e.g. "so-and-so is overweight") – only their own
51       // notices (handled above) and true all-hands broadcasts with no
52       // targeting at all (e.g. "IPFT date confirmed").
53       if (user.role === 'soldier') return !n.targetCompany && !n.targetRole;
54       if (n.targetCompany && n.targetCompany !== user.company) return false;
55       if (n.targetRole && n.targetRole !== user.role) return false;
56       return true;
57     });
58     setNotifs(mine);
59     setSchedule(sched);
60   }, [user]);
61
62   useFocusEffect(useCallba ck(() => { load(); }, [load]));
63
64   const onRefresh = async () => { setRefreshing(true); await load(); setRefreshing(false); };
65
66   const handleMarkAll = async () => {
67     Haptics.impactAsync(Haptics.ImpactFeedbackStyle.Light);
68     await markAllNotificationsRead();
69     await load();
70   };
71
72   const handleRead = async (id: string) => {
73     await markNotificationRead(id);
74     await load();
75   };
76
77   const handlePropose = async () => {
78     if (!proposedDate) { showAlert('Error', 'Please pick a date on the calendar. '); return; }
79     Haptics.impactAsync(Haptics.ImpactFeedbackStyle.Medium);
80     const sched: IPFTSchedule = {
81       id: genId(), proposedDate: proposedDate.trim(),
```

```

82     proposedBy: user!.id, proposedByName: user!.name,
83     status: 'pending', createdAt: new Date().toISOString(),
84   };
85   await saveIPFTSchedule(sched);
86   await addNotification({
87     id: genId(), targetRole: 'co', title: 'New IPFT Date Proposed',
88     body: `Adjutant has proposed IPFT on ${proposedDate.trim()}. Your approval is required.`,
89     type: 'ipft_proposed', read: false, createdAt: new Date().toISOString(),
90   });
91   setProposeVisible(false);
92   setProposedDate('');
93   await load();
94   Haptics.notificationAsync(Haptics.NotificationFeedbackType.Success);
95   showAlert('Sent', 'IPFT date proposal has been sent to CO.');
```

```

96 };
97
98 const handleApprove = async () => {
99   if (!schedule) return;
100   Haptics.impactAsync(Haptics.ImpactFeedbackStyle.Medium);
101   await saveIPFTSchedule({ ...schedule, status: 'approved', approvedBy: user!.id });
102   await addNotification({
103     id: genId(), title: 'IPFT Date Confirmed',
104     body: `Next IPFT confirmed for ${schedule.proposedDate}. All companies must prepare.`,
105     type: 'ipft_approved', read: false, createdAt: new Date().toISOString(),
106   });
107   await load();
108   showAlert('Approved', 'IPFT date approved and unit notified.');
```

```

109 };
110
111 const handleReject = async () => {
112   if (!schedule) return;
113   if (!rejectionNote.trim() && !altDate.trim()) { showAlert('Error', 'Please provide a reason or
alternate date.');
```

```

114   return; }
115   await saveIPFTSchedule({ ...schedule, status: 'rejected', rejectionNote: rejectionNote.trim(),
alternateDate: altDate.trim() || undefined });
116   await addNotification({
117     id: genId(), targetRole: 'adjutant', title: 'IPFT Date Rejected',
118     body: `Proposed date ${schedule.proposedDate} was rejected.${rejectionNote ? ' Reason: ' +
rejectionNote : ''}${altDate ? ' Alternate date suggested: ' + altDate : ''}`,
119     type: 'ipft_rejected', read: false, createdAt: new Date().toISOString(),
120   });
121   setRejectVisible(false);
122   setRejectionNote('');
123   setAltDate('');
124   await load();
125   showAlert('Rejected', 'Rejection sent to Adjutant.');
```

```

126 };
127
128 const unread = notifs.filter(n => !n.read).length;
129 const formatDate = (d: string) => new Date(d).toLocaleDateString('en-BD', { day: '2-digit', month:
'short', year: 'numeric' });
130
131 const renderItem = ({ item }: { item: Notification }) => {
132   const icon = notifIcon(item.type);
133   const iconColor = icon.color(colors);
134   const fmtTime = (d: string) => new Date(d).toLocaleDateString('en-BD', { day: '2-digit', month:
'short', hour: '2-digit', minute: '2-digit' });
135   return (
136     <TouchableOpacity
137       style={[styles.card, { backgroundColor: item.read ? colors.card : colors.primary + '08',
borderColor: item.read ? colors.border : colors.primary }]}
138       onPress={() => handleRead(item.id)}
139       activeOpacity={0.75}
140     >
141       <View style={[styles.iconWrap, { backgroundColor: iconColor + '20' }]}>
142         <MaterialCommunityIcons name={icon.name as any} size={22} color={iconColor} />
143       </View>
144       <View style={styles.content}>
145         <View style={styles.topRow}>
146           <Text style={[styles.notifTitle, { color: colors.foreground }]}>{item.title}</Text>
147           <View style={[styles.dot, { backgroundColor: colors.primary }]} />
148         </View>
149         <Text style={[styles.notifBody, { color: colors.mutedForeground }]}>{item.body}</Text>
150         <Text style={[styles.notifDate, { color: colors.mutedForeground }]}>{fmtTime(item.createdAt)}</
Text>
151         {user?.role === 'co' && item.type === 'ipft_proposed' && schedule?.status === 'pending' && (
152           <View style={styles.actionRow}>
153             <TouchableOpacity style={[styles.approveActionBtn, { backgroundColor: colors.success }]}
onPress={handleApprove}>
154               <Feather name="check" size={16} color="#FFF" />
155               <Text style={styles.actionBtnText}>Approve</Text>
156             </TouchableOpacity>
157             <TouchableOpacity style={[styles.approveActionBtn, { backgroundColor: colors.destructive }]}
onPress={() => setRejectVisible(true)}>
158               <Feather name="x" size={16} color="#FFF" />

```

```

158         <Text style={styles.actionBtnText}>Reject</Text>
159     </TouchableOpacity>
160 </View>
161 }}
162 </View>
163 </TouchableOpacity>
164 );
165 };
166
167 const paddingTop = 16;
168 const paddingBottom = isWeb ? 34 : insets.bottom + 90;
169
170 return (
171     <View style={[styles.root, { backgroundColor: colors.background }]}>
172         <View style={[styles.header, { paddingTop, backgroundColor: colors.background }]}>
173             <View>
174                 <Text style={[styles.title, { color: colors.foreground }]}>Notifications</Text>
175                 {unread > 0 && <Text style={[styles.badge, { color: colors.primary }]}>{unread} unread</Text>}
176             </View>
177             {unread > 0 && (
178                 <TouchableOpacity style={[styles.markAllBtn, { borderColor: colors.border }]}
onPress={handleMarkAll}>
179                 <Feather name="check-square" size={16} color={colors.mutedForeground} />
180                 <Text style={[styles.markAllText, { color: colors.mutedForeground }]}>Mark All Read</Text>
181             </TouchableOpacity>
182             )}
183         </View>
184
185         {user?.role === 'adjutant' && (
186             <TouchableOpacity style={[styles.proposeBtn, { backgroundColor: colors.accent, marginHorizontal:
16 }]} onPress={() => setProposeVisible(true)}>
187                 <Feather name="calendar" size={16} color={colors.accentForeground ?? '#000'} />
188                 <Text style={[styles.proposeBtnText, { color: colors.accentForeground ?? '#000' }]}>Propose IPFT
Date to C0</Text>
189             </TouchableOpacity>
190         )}
191
192         {schedule && (
193             <View style={[styles.schedBanner, { backgroundColor: schedule.status === 'approved' ?
colors.success + '15' : schedule.status === 'rejected' ? colors.destructive + '15' : colors.accent + '15',
borderColor: schedule.status === 'approved' ? colors.success : schedule.status === 'rejected' ?
colors.destructive : colors.accent, marginHorizontal: 16 }]}>
194                 <Text style={[styles.schedLabel, { color: schedule.status === 'approved' ? colors.success :
schedule.status === 'rejected' ? colors.destructive : colors.accent }]}>
195                     IPFT Proposed: {schedule.proposedDate} - {schedule.status.toUpperCase()}
196                 </Text>
197             </View>
198         )}
199
200         <FlatList
201             data={notifs}
202             keyExtractor={i => i.id}
203             renderItem={renderItem}
204             contentContainerStyle={[styles.list, { paddingBottom }]}
205             refreshControl={<RefreshControl refreshing={refreshing} onRefresh={onRefresh}
tintColor={colors.primary} />}
206             ItemSeparatorComponent={() => <View style={{ height: 8 }} />}
207             ListEmptyComponent={
208                 <View style={styles.empty}>
209                     <Feather name="bell-off" size={48} color={colors.border} />
210                     <Text style={[styles.emptyText, { color: colors.mutedForeground }]}>No notifications</Text>
211                 </View>
212             }
213         />
214
215         {/* Propose date modal */}
216         <Modal visible={proposeVisible} transparent animationType="slide" onRequestClose={() =>
setProposeVisible(false)}>
217             <View style={styles.modalOverlay}>
218                 <View style={[styles.modalSheet, { backgroundColor: colors.card, paddingBottom: insets.bottom +
20, maxHeight: '90%' }]}>
219                     <View style={styles.modalHandle} />
220                     <ScrollView keyboardShouldPersistTaps="handled">
221                         <Text style={[styles.modalTitle, { color: colors.foreground }]}>Propose IPFT Date</Text>
222                         <Text style={[styles.modalLabel, { color: colors.mutedForeground }]}>Tap a date on the
calendar</Text>
223                         <Calendar value={proposedDate} onChange={setProposedDate} minDate={TODAY} colors={colors} />
224                         {proposedDate ? (
225                             <Text style={[styles.selectedDateText, { color: colors.primary }]}>Selected: {proposedDate}
</Text>
226                         ) : null}
227                         <TouchableOpacity style={[styles.sendBtn, { backgroundColor: colors.primary, marginTop:
14 }]} onPress={handlePropose}>
228                             <Feather name="send" size={18} color="#FFF" />
229                             <Text style={styles.sendBtnText}>Send to C0</Text>

```

```

230         </TouchableOpacity>
231         <TouchableOpacity style={[styles.cancelBtn, { borderColor: colors.border }]} onPress={() =>
setProposeVisible(false)}>
232             <Text style={[styles.cancelBtnText, { color: colors.mutedForeground }]}>Cancel</Text>
233         </TouchableOpacity>
234     </ScrollView>
235 </View>
236 </View>
237 </Modal>
238
239     /* Reject modal */
240     <Modal visible={rejectVisible} transparent animationType="slide" onRequestClose={() =>
setRejectVisible(false)}>
241         <View style={styles.modalOverlay}>
242             <View style={[styles.modalSheet, { backgroundColor: colors.card, paddingBottom: insets.bottom +
20, maxHeight: '90%' }]}>
243                 <View style={styles.modalHandle} />
244                 <ScrollView keyboardShouldPersistTaps="handled">
245                     <Text style={[styles.modalTitle, { color: colors.foreground }]}>Reject IPFT Date</Text>
246                     <Text style={[styles.modalLabel, { color: colors.mutedForeground }]}>Reason for rejection</
Text>
247                     <TextInput style={[styles.modalInput, { borderColor: colors.border, color: colors.foreground,
backgroundColor: colors.background }]} value={rejectionNote} onChangeText={setRejectionNote} placeholder="Enter
reason..." placeholderTextColor={colors.mutedForeground} multiline />
248                     <Text style={[styles.modalLabel, { color: colors.mutedForeground, marginTop: 4 }]}>Suggest a
new date (optional) – tap the calendar</Text>
249                     <Calendar value={altDate} onChange={setAltDate} minDate={TODAY} colors={colors} />
250                     {altDate ? (
251                         <Text style={[styles.selectedDateText, { color: colors.destructive }]}>Suggested: {altDate}
</Text>
252                     ) : null}
253                     <TouchableOpacity style={[styles.sendBtn, { backgroundColor: colors.destructive, marginTop:
14 }]} onPress={handleReject}>
254                         <Text style={styles.sendBtnText}>Send Rejection</Text>
255                     </TouchableOpacity>
256                     <TouchableOpacity style={[styles.cancelBtn, { borderColor: colors.border }]} onPress={() =>
setRejectVisible(false)}>
257                         <Text style={[styles.cancelBtnText, { color: colors.mutedForeground }]}>Cancel</Text>
258                     </TouchableOpacity>
259                 </ScrollView>
260             </View>
261         </View>
262     </Modal>
263 </View>
264 );
265 }
266
267 const styles = StyleSheet.create({
268     root: { flex: 1 },
269     header: { flexDirection: 'row', alignItems: 'center', justifyContent: 'space-between', paddingHorizontal:
16, paddingBottom: 12 },
270     title: { fontSize: 24, fontFamily: 'Inter_700Bold' },
271     badge: { fontSize: 12, fontFamily: 'Inter_500Medium', marginTop: 2 },
272     markAllBtn: { flexDirection: 'row', alignItems: 'center', gap: 6, borderRadius: 8, paddingHorizontal: 10,
paddingVertical: 7, borderWidth: 1 },
273     markAllText: { fontSize: 12, fontFamily: 'Inter_500Medium' },
274     proposeBtn: { flexDirection: 'row', alignItems: 'center', justifyContent: 'center', gap: 8, borderRadius:
10, paddingVertical: 11, marginBottom: 10 },
275     proposeBtnText: { fontSize: 13, fontFamily: 'Inter_600SemiBold' },
276     schedBanner: { borderRadius: 10, padding: 10, borderWidth: 1, marginBottom: 10 },
277     schedLabel: { fontSize: 12, fontFamily: 'Inter_600SemiBold' },
278     list: { paddingHorizontal: 16, paddingTop: 4 },
279     card: { flexDirection: 'row', gap: 12, padding: 14, borderRadius: 12, borderWidth: 1.5, alignItems: 'flex-
start' },
280     iconWrap: { width: 44, height: 44, borderRadius: 22, alignItems: 'center', justifyContent: 'center' },
281     content: { flex: 1, gap: 4 },
282     topRow: { flexDirection: 'row', alignItems: 'center', justifyContent: 'space-between' },
283     notifTitle: { fontSize: 14, fontFamily: 'Inter_600SemiBold', flex: 1 },
284     dot: { width: 8, height: 8, borderRadius: 4 },
285     notifBody: { fontSize: 13, fontFamily: 'Inter_400Regular', lineHeight: 19 },
286     notifDate: { fontSize: 11, fontFamily: 'Inter_400Regular' },
287     empty: { alignItems: 'center', paddingVertical: 60, gap: 12 },
288     emptyText: { fontSize: 15, fontFamily: 'Inter_400Regular' },
289     modalOverlay: { flex: 1, backgroundColor: 'rgba(0,0,0,0.5)', justifyContent: 'flex-end' },
290     modalSheet: { borderTopLeftRadius: 20, borderTopRightRadius: 20, paddingHorizontal: 20, paddingTop: 12 },
291     modalHandle: { width: 40, height: 4, borderRadius: 2, backgroundColor: '#ccc', alignSelf: 'center',
marginBottom: 16 },
292     modalTitle: { fontSize: 18, fontFamily: 'Inter_700Bold', marginBottom: 16 },
293     modalLabel: { fontSize: 12, fontFamily: 'Inter_500Medium', marginBottom: 6 },
294     modalInput: { borderWidth: 1, borderRadius: 8, padding: 12, fontSize: 14, fontFamily: 'Inter_400Regular',
marginBottom: 12 },
295     selectedDateText: { fontSize: 12, fontFamily: 'Inter_600SemiBold', marginTop: 8, textAlign: 'center' },
296     sendBtn: { flexDirection: 'row', alignItems: 'center', justifyContent: 'center', gap: 8, borderRadius:
10, paddingVertical: 13, marginBottom: 8 },
297     sendBtnText: { fontSize: 15, fontFamily: 'Inter_600SemiBold', color: '#FFF' },

```

```
298   cancelBtn: { borderWidth: 1, borderRadius: 10, paddingVertical: 12, alignItems: 'center' },
299   cancelBtnText: { fontSize: 14, fontFamily: 'Inter_500Medium' },
300   actionRow: { flexDirection: 'row', gap: 10, marginTop: 8 },
301   approveActionBtn: { flex: 1, flexDirection: 'row', alignItems: 'center', justifyContent: 'center', gap:
6, borderRadius: 8, paddingVertical: 10 },
302   actionBtnText: { fontSize: 13, fontFamily: 'Inter_600SemiBold', color: '#FFF' },
303 });
304
```

```

1  import React, { useState, useEffect, useCallback } from 'react';
2  import { View, Text, StyleSheet, FlatList, TouchableOpacity, Platform, RefreshControl } from 'react-native';
3  import { useSafeAreaInsets } from 'react-native-safe-area-context';
4  import { Feather } from '@expo/vector-icons';
5  import { router } from 'expo-router';
6  import { useColors } from '@hooks/useColors';
7  import { useAuth } from '@context/AuthContext';
8  import { getPTPlans, getSoldiers } from '@lib/storage';
9  import type { PTPlan, Soldier } from '@lib/types';
10
11 export default function PlanScreen() {
12   const colors = useColors();
13   const insets = useSafeAreaInsets();
14   const { user } = useAuth();
15   const isWeb = Platform.OS === 'web';
16
17   const [plans, setPlans] = useState<PTPlan[]>([]);
18   const [mySoldier, setMySoldier] = useState<Soldier | null>(null);
19   const [refreshing, setRefreshing] = useState(false);
20
21   const load = useCallback(async () => {
22     const allPlans = await getPTPlans();
23     setPlans(allPlans);
24     if (user?.role === 'soldier') {
25       const all = await getSoldiers();
26       setMySoldier(all.find(s => s.userId === user.id) ?? null);
27     }
28   }, [user]);
29
30   useEffect(() => { load(); }, [load]);
31
32   const onRefresh = async () => { setRefreshing(true); await load(); setRefreshing(false); };
33
34   const visiblePlans = user?.role === 'soldier' && mySoldier
35     ? plans.filter(p => p.type === (mySoldier.ptStatus === 'unfit' ? 'unfit' : 'fit'))
36     : plans;
37
38   const renderPlan = ({ item }: { item: PTPlan }) => {
39     const accent = item.type === 'fit' ? colors.success : colors.warning;
40     return (
41       <TouchableOpacity
42         style={[styles.card, { backgroundColor: colors.card, borderColor: accent }]}
43         onPress={() => router.push(`/plan/${item.id}`)}
44         activeOpacity={0.75}
45       >
46         <View style={[styles.typeTag, { backgroundColor: accent }]}>
47           <Text style={styles.typeTagText}>{item.type === 'fit' ? 'FIT' : 'REHABILITATION'}</Text>
48         </View>
49         <Text style={[styles.cardTitle, { color: colors.foreground }]}>{item.title}</Text>
50         <Text style={[styles.cardMeta, { color: colors.mutedForeground }]}>Week {item.weekNumber} .
51         {item.days.length} days · by {item.createdByName}</Text>
52         <Text style={[styles.cardDesc, { color: colors.mutedForeground }]} numberOfLines={2}
53         >{item.description}</Text>
54         <View style={styles.footer}>
55           <View style={styles.daysRow}>
56             {item.days.map((d, i) => (
57               <View key={i} style={[styles.dayDot, { backgroundColor: accent + '30', borderColor: accent }]}
58               <Text style={[styles.dayDotText, { color: accent }]}>{d.day.slice(0, 2)}</Text>
59             </View>
60             ))}
61           </View>
62           <Feather name="chevron-right" size={18} color={colors.mutedForeground} />
63         </View>
64       </TouchableOpacity>
65     );
66   };
67
68   const paddingTop = 16;
69   const paddingBottom = isWeb ? 34 : insets.bottom + 90;
70
71   return (
72     <View style={[styles.root, { backgroundColor: colors.background }]}>
73       <View style={[styles.header, { paddingTop, backgroundColor: colors.background }]}>
74         <Text style={[styles.title, { color: colors.foreground }]}>
75           {user?.role === '2ic' ? 'All PT Plans' : 'My PT Plan'}
76         </Text>
77         {user?.role === '2ic' && (
78           <TouchableOpacity style={[styles.createBtn, { backgroundColor: colors.primary }]} onPress={() =>
79             router.push('/plan/new')}>
80             <Feather name="plus" size={18} color="#FFF" />
81             <Text style={styles.createBtnText}>New Plan</Text>
82           </TouchableOpacity>
83         )}
84       </View>
85       <FlatList
86         data={visiblePlans}
87         renderItem={renderPlan}
88         keyExtractor={item => item.id}
89       />
90     </View>
91   );

```

```

80     })
81   </View>
82   <FlatList
83     data={visiblePlans}
84     keyExtractor={i => i.id}
85     renderItem={renderPlan}
86     contentContainerStyle={[styles.list, { paddingBottom }]}
87     refreshControl={<RefreshControl refreshing={refreshing} onRefresh={onRefresh}
tintColor={colors.primary} />}
88     ItemSeparatorComponent={() => <View style={{ height: 12 }} />}
89     ListEmptyComponent={
90       <View style={styles.empty}>
91         <Feather name="calendar" size={48} color={colors.border} />
92         <Text style={[styles.emptyText, { color: colors.mutedForeground }]}>No PT plans available</Text>
93       </View>
94     }
95   />
96 </View>
97 );
98 }
99
100 const styles = StyleSheet.create({
101   root: { flex: 1 },
102   header: { flexDirection: 'row', alignItems: 'center', justifyContent: 'space-between', paddingHorizontal:
16, paddingBottom: 12 },
103   title: { fontSize: 24, fontFamily: 'Inter_700Bold' },
104   createBtn: { flexDirection: 'row', alignItems: 'center', gap: 6, borderRadius: 10, paddingHorizontal: 14,
paddingVertical: 8 },
105   createBtnText: { fontSize: 14, fontFamily: 'Inter_600SemiBold', color: '#FFF' },
106   list: { paddingHorizontal: 16, paddingTop: 8 },
107   card: { borderRadius: 14, borderWidth: 1.5, padding: 16, gap: 8 },
108   typeTag: { alignSelf: 'flex-start', borderRadius: 6, paddingHorizontal: 10, paddingVertical: 4 },
109   typeTagText: { fontSize: 10, fontFamily: 'Inter_700Bold', color: '#FFF', letterSpacing: 1 },
110   cardTitle: { fontSize: 16, fontFamily: 'Inter_700Bold' },
111   cardMeta: { fontSize: 12, fontFamily: 'Inter_400Regular' },
112   cardDesc: { fontSize: 13, fontFamily: 'Inter_400Regular', lineHeight: 1.9 },
113   footer: { flexDirection: 'row', alignItems: 'center', justifyContent: 'space-between', marginTop: 4 },
114   daysRow: { flexDirection: 'row', gap: 4 },
115   dayDot: { borderRadius: 4, paddingHorizontal: 5, paddingVertical: 3, borderWidth: 1 },
116   dayDotText: { fontSize: 9, fontFamily: 'Inter_600SemiBold' },
117   empty: { alignItems: 'center', paddingVertical: 60, gap: 12 },
118   emptyText: { fontSize: 15, fontFamily: 'Inter_400Regular' },
119 });
120

```

app/(tabs)/profile.tsx

```
1  import React, { useEffect, useState } from 'react';
2  import { View, Text, StyleSheet, ScrollView, TouchableOpacity, Platform, Modal, TextInput } from 'react-native';
3  import { useSafeAreaInsets } from 'react-native-safe-area-context';
4  import { Feather, MaterialCommunityIcons, Ionicons } from '@expo/vector-icons';
5  import * as Haptics from 'expo-haptics';
6  import { router } from 'expo-router';
7  import { useColors } from '@/hooks/useColors';
8  import { useAuth } from '@/context/AuthContext';
9  import { calcBMI, getSoldiers, getUsers, updateSoldier, updateUser, addNotification, genId } from '@/lib/storage';
10 import type { Company } from '@/lib/types';
11
12 const ROLE_LABELS: Record<string, string> = {
13   co: 'Commanding Officer', '2ic': 'Second in Command',
14   coy_comd: 'Company Commander', adjutant: 'Adjutant',
15   clerk: 'Clerk', soldier: 'Soldier',
16 };
17
18 const COMPANIES: Company[] = ['A', 'B', 'C', 'D'];
19
20 const EDITABLE_FIELD_LABELS: Record<string, string> = {
21   email: 'email',
22   phone: 'phone number',
23   company: 'company',
24   height: 'height',
25   weight: 'weight',
26   age: 'age',
27   address: 'address',
28 };
29
30 export default function ProfileScreen() {
31   const colors = useColors();
32   const insets = useSafeAreaInsets();
33   const { user, logout, refreshUser } = useAuth();
34   const isWeb = Platform.OS === 'web';
35
36   const [editVisible, setEditVisible] = useState(false);
37   const [companyModal, setCompanyModal] = useState(false);
38   const [isSaving, setIsSaving] = useState(false);
39   const [email, setEmail] = useState('');
40   const [phone, setPhone] = useState('');
41   const [company, setCompany] = useState<Company | ''>('');
42   const [height, setHeight] = useState('');
43   const [weight, setWeight] = useState('');
44   const [age, setAge] = useState('');
45   const [address, setAddress] = useState('');
46   const [errors, setErrors] = useState<string[]>([]);
47
48   const handleLogout = () => {
49     Haptics.impactAsync(Haptics.ImpactFeedbackStyle.Medium);
50     void logout();
51   };
52
53   useEffect(() => {
54     if (!user) {
55       router.replace('/(auth)/login');
56     }
57   }, [user]);
58
59   if (!user) return null;
60
61   const bmi = user.height && user.weight ? calcBMI(user.weight, user.height) : null;
62   const bmiStatus = bmi ? (bmi < 18.5 ? 'Underweight' : bmi < 25 ? 'Normal' : bmi < 30 ? 'Overweight' : 'Obese') : null;
63   const bmiColor = bmi ? (bmi < 25 ? colors.success : bmi < 30 ? colors.warning : colors.destructive) : colors.mutedForeground;
64
65   const openEdit = () => {
66     setEmail(user.email ?? '');
67     setPhone(user.phone ?? '');
68     setCompany(user.company ?? '');
69     setHeight(user.height ? String(user.height) : '');
70     setWeight(user.weight ? String(user.weight) : '');
71     setAge(user.age ? String(user.age) : '');
72     setAddress(user.address ?? '');
73     setErrors([]);
74     setEditVisible(true);
75   };
76
77   const handleSaveEdit = async () => {
78     const errs: string[] = [];
79     if (!email.trim() || !email.includes('@')) errs.push('Valid email is required.');
```

```

80     if (!height || isNaN(Number(height))) errs.push('Valid height (cm) is required.');
```

```

81     if (!weight || isNaN(Number(weight))) errs.push('Valid weight (kg) is required.');
```

```

82     if (!age || isNaN(Number(age))) errs.push('Valid age is required.');
```

```

83     if (!address.trim()) errs.push('Address is required.');
```

```

84
```

```

85     const normalizedEmail = email.trim().toLowerCase();
```

```

86     if (errs.length === 0 && normalizedEmail !== user.email.toLowerCase()) {
```

```

87         const users = await getUsers();
```

```

88         if (users.some(u => u.id !== user.id && u.email.toLowerCase() === normalizedEmail)) {
```

```

89             errs.push('This email is already used by another account.');
```

```

90         }
```

```

91     }
```

```

92     if (errs.length > 0) { setErrors(errs); return; }
```

```

93     setErrors([]);
```

```

94
```

```

95     const newValues: Record<string, any> = {
```

```

96         email: normalizedEmail,
```

```

97         phone: phone.trim() || undefined,
```

```

98         company: company || undefined,
```

```

99         height: Number(height),
```

```

100        weight: Number(weight),
```

```

101        age: Number(age),
```

```

102        address: address.trim(),
```

```

103    };
```

```

104
```

```

105    const changedFields: string[] = [];
```

```

106    (Object.keys(newValues) as (keyof typeof newValues)[]).forEach(key => {
```

```

107        if ((user as any)[key] !== newValues[key]) changedFields.push(key);
```

```

108    });
```

```

109
```

```

110    if (changedFields.length === 0) { setEditVisible(false); return; }
```

```

111
```

```

112    setIsSaving(true);
```

```

113    Haptics.impactAsync(Haptics.ImpactFeedbackStyle.Medium);
```

```

114
```

```

115    await updateUser(user.id, newValues);
```

```

116
```

```

117    if (user.role === 'soldier') {
```

```

118        const soldiers = await getSoldiers();
```

```

119        const soldier = soldiers.find(s => s.userId === user.id);
```

```

120        if (soldier) {
```

```

121            const isOverweight = calcBMI(newValues.weight, newValues.height) > 25;
```

```

122            await updateSoldier(soldier.id, {
```

```

123                email: newValues.email,
```

```

124                phone: newValues.phone ?? '',
```

```

125                company: newValues.company,
```

```

126                height: newValues.height,
```

```

127                weight: newValues.weight,
```

```

128                age: newValues.age,
```

```

129                address: newValues.address,
```

```

130                isOverweight,
```

```

131            });
```

```

132        }
```

```

133        const changedLabels = changedFields.map(f => EDITABLE_FIELD_LABELS[f] ?? f).join(', ');
```

```

134        await addNotification({
```

```

135            id: genId(), targetRole: 'clerk',
```

```

136            title: 'Soldier Profile Updated',
```

```

137            body: `${user.rank} ${user.name} updated their profile: ${changedLabels}.`,
```

```

138            type: 'general', read: false, createdAt: new Date().toISOString(),
```

```

139        });
```

```

140    }
```

```

141
```

```

142    await refreshUser();
```

```

143    setIsSaving(false);
```

```

144    setEditVisible(false);
```

```

145    Haptics.notificationAsync(Haptics.NotificationFeedbackType.Success);
```

```

146};
```

```

147
```

```

148    const InfoRow = ({ label, value, icon }: { label: string; value: string; icon: string }) => (
```

```

149        <View style={[[styles.infoRow, { borderBottomColor: colors.border }]]}>
```

```

150            <View style={styles.infoLeft}>
```

```

151                <MaterialCommunityIcons name={icon as any} size={18} color={colors.mutedForeground} />
```

```

152                <Text style={[[styles.infoLabel, { color: colors.mutedForeground }]]}>{label}</Text>
```

```

153            </View>
```

```

154            <Text style={[[styles.infoValue, { color: colors.foreground }]]} numberOfLines={2}>{value}</Text>
```

```

155        </View>
```

```

156    );
```

```

157
```

```

158    const paddingTop = 16;
```

```

159    const paddingBottom = isWeb ? 24 : insets.bottom + 170;
```

```

160
```

```

161    return (
```

```

162        <View style={[[styles.root, { backgroundColor: colors.background }]]}>
```

```

163            <ScrollView
```

```

164                style={styles.scroll}
```

```

165         contentContainerStyle=[{styles.content, { paddingTop, paddingBottom }}]
166     >
167     <View style={[[styles.headerCard, { backgroundColor: colors.primary }]]>
168         <View style={styles.avatarCircle}>
169             <Text style={styles.avatarText}>{user.name.split(' ').map(n => n[0]).join('').slice(0,
2).toUpperCase()}</Text>
170         </View>
171         <Text style={styles.profileName}>{user.name}</Text>
172         <Text style={styles.profileRole}>{ROLE_LABELS[user.role] ?? user.role}</Text>
173         <View style={styles.badgesRow}>
174             {user.rank && <View style={styles.profileBadge}><Text style={styles.profileBadgeText}>{user.rank}</Text></View>}
175             {user.ba && <View style={styles.profileBadge}><Text style={styles.profileBadgeText}>{user.ba}</Text></View>}
176             {user.company && <View style={styles.profileBadge}><Text style={styles.profileBadgeText}>
>{user.company} Company</Text></View>}
177         </View>
178     </View>
179
180     <TouchableOpacity
181         style={[[styles.editBtn, { borderColor: colors.primary, backgroundColor: colors.card }]]}
182         onPress={openEdit}
183         activeOpacity={0.8}
184     >
185         <Feather name="edit-2" size={18} color={colors.primary} />
186         <Text style={[[styles.editText, { color: colors.primary }]]>Edit Profile</Text>
187     </TouchableOpacity>
188
189     <TouchableOpacity
190         style={[[styles.logoutBtn, { borderColor: colors.destructive, backgroundColor: colors.card }]]}
191         onPress={handleLogout}
192         activeOpacity={0.8}
193     >
194         <Feather name="log-out" size={18} color={colors.destructive} />
195         <Text style={[[styles.logoutText, { color: colors.destructive }]]>Sign Out</Text>
196     </TouchableOpacity>
197
198     {bmi && (
199         <View style={[[styles.bmiCard, { backgroundColor: colors.card, borderColor: bmiColor }]]>
200             <View style={styles.bmiLeft}>
201                 <Text style={[[styles.bmiTitle, { color: colors.foreground }]]>Body Mass Index</Text>
202                 <Text style={[[styles.bmiStatus, { color: bmiColor }]]>{bmiStatus}</Text>
203             </View>
204             <Text style={[[styles.bmiBig, { color: bmiColor }]]>{bmi}</Text>
205         </View>
206     )}
207
208     <View style={[[styles.section, { backgroundColor: colors.card, borderColor: colors.border }]]>
209         <Text style={[[styles.sectionTitle, { color: colors.foreground }]]>Personal Information</Text>
210         <InfoRow label="Email" value={user.email} icon="email-outline" />
211         {user.phone && <InfoRow label="Phone" value={user.phone} icon="phone-outline" />}
212         {user.company && <InfoRow label="Company" value={` ${user.company} Company `} icon="flag-outline" />}
213         {user.age && <InfoRow label="Age" value={` ${user.age} years`} icon="cake-variant" />}
214         {user.address && <InfoRow label="Address" value={user.address} icon="map-marker-outline" />}
215     </View>
216
217     {(user.height || user.weight) && (
218         <View style={[[styles.section, { backgroundColor: colors.card, borderColor: colors.border }]]>
219             <Text style={[[styles.sectionTitle, { color: colors.foreground }]]>Physical Metrics</Text>
220             {user.height && <InfoRow label="Height" value={` ${user.height} cm`} icon="human-male-height" />}
221             {user.weight && <InfoRow label="Weight" value={` ${user.weight} kg`} icon="weight-kilogram" />}
222         </View>
223     )}
224
225 </ScrollView>
226
227 {/ * Edit profile modal */}
228 <Modal visible={editVisible} transparent animationType="slide" onRequestClose={() =>
setEditVisible(false)}>
229     <View style={styles.modalOverlay}>
230         <View style={[[styles.modalSheet, { backgroundColor: colors.card, paddingBottom: insets.bottom +
20, maxHeight: '88%' }]]>
231             <View style={styles.modalHandle} />
232             <ScrollView keyboardShouldPersistTaps="handled">
233                 <Text style={[[styles.modalTitle, { color: colors.foreground }]]>Edit Profile</Text>
234
235                 {errors.length > 0 && (
236                     <View style={[[styles.errorBox, { backgroundColor: colors.destructive + '12', borderColor:
colors.destructive }]]>
237                         {errors.map((e, i) => <Text key={i} style={[[styles.errorText, { color:
colors.destructive }]]>• {e}</Text>)}
238                     </View>
239                 )}
240
241                 <Text style={[[styles.modalLabel, { color: colors.mutedForeground }]]>Email</Text>

```

```

242         <TextInput style={[[styles.modalInput, { borderColor: colors.border, color: colors.foreground,
backgroundColor: colors.background }]]}
243             value={email} onChangeText={setEmail} placeholder="e.g. name@gmail.com"
placeholderTextColor={colors.mutedForeground} keyboardType="email-address" autoCapitalize="none" />
244
245         <Text style={[[styles.modalLabel, { color: colors.mutedForeground }]]}>Phone</Text>
246         <TextInput style={[[styles.modalInput, { borderColor: colors.border, color: colors.foreground,
backgroundColor: colors.background }]]}
247             value={phone} onChangeText={setPhone} placeholder="e.g. 01711-123456"
placeholderTextColor={colors.mutedForeground} keyboardType="phone-pad" />
248
249         <Text style={[[styles.modalLabel, { color: colors.mutedForeground }]]}>Company (Coy)</Text>
250         <TouchableOpacity style={[[styles.selectBtn, { borderColor: colors.border, backgroundColor:
colors.background }]]} onPress={() => setCompanyModal(true)}>
251             <Text style={[[styles.selectText, { color: company ? colors.foreground :
colors.mutedForeground }]]}>{company ? `${company} Company` : 'Select company'}</Text>
252             <Ionicons name="chevron-down" size={16} color={colors.mutedForeground} />
253         </TouchableOpacity>
254
255         <Text style={[[styles.modalLabel, { color: colors.mutedForeground }]]}>Height (cm)</Text>
256         <TextInput style={[[styles.modalInput, { borderColor: colors.border, color: colors.foreground,
backgroundColor: colors.background }]]}
257             value={height} onChangeText={setHeight} placeholder="e.g. 170"
placeholderTextColor={colors.mutedForeground} keyboardType="numeric" />
258
259         <Text style={[[styles.modalLabel, { color: colors.mutedForeground }]]}>Weight (kg)</Text>
260         <TextInput style={[[styles.modalInput, { borderColor: colors.border, color: colors.foreground,
backgroundColor: colors.background }]]}
261             value={weight} onChangeText={setWeight} placeholder="e.g. 68"
placeholderTextColor={colors.mutedForeground} keyboardType="numeric" />
262
263         <Text style={[[styles.modalLabel, { color: colors.mutedForeground }]]}>Age</Text>
264         <TextInput style={[[styles.modalInput, { borderColor: colors.border, color: colors.foreground,
backgroundColor: colors.background }]]}
265             value={age} onChangeText={setAge} placeholder="e.g. 22"
placeholderTextColor={colors.mutedForeground} keyboardType="numeric" />
266
267         <Text style={[[styles.modalLabel, { color: colors.mutedForeground }]]}>Address</Text>
268         <TextInput style={[[styles.modalInput, { borderColor: colors.border, color: colors.foreground,
backgroundColor: colors.background, height: 70, textAlignVertical: 'top' }]]}
269             value={address} onChangeText={setAddress} placeholder="e.g. House 12, Road 5, Dhaka"
placeholderTextColor={colors.mutedForeground} multiline />
270
271         {user.role === 'soldier' && (
272             <View style={[[styles.noticeBox, { backgroundColor: colors.accent + '15', borderColor:
colors.accent }]]}>
273                 <Feather name="info" size={14} color={colors.accent} />
274                 <Text style={[[styles.noticeText, { color: colors.accent }]]}>The Clerk will be notified
when you update your profile.</Text>
275             </View>
276         )}
277
278         <TouchableOpacity style={[[styles.saveBtn, { backgroundColor: colors.primary }, isSaving &&
{ opacity: 0.7 }]]} onPress={handleSaveEdit} disabled={isSaving}>
279             <Feather name="check" size={18} color="#FFF" />
280             <Text style={styles.saveBtnText}>{isSaving ? 'Saving...' : 'Save Changes'}</Text>
281         </TouchableOpacity>
282         <TouchableOpacity style={[[styles.cancelBtn, { borderColor: colors.border }]]} onPress={() =>
setEditVisible(false)}>
283             <Text style={[[styles.cancelBtnText, { color: colors.mutedForeground }]]}>Cancel</Text>
284         </TouchableOpacity>
285     </ScrollView>
286 </View>
287 </View>
288 </Modal>
289
290     /* Company picker */
291     <Modal visible={companyModal} transparent animationType="slide" onRequestClose={() =>
setCompanyModal(false)}>
292         <TouchableOpacity style={styles.modalOverlay} activeOpacity={1} onPress={() =>
setCompanyModal(false)}>
293             <View style={[[styles.modalSheet, { backgroundColor: colors.card, paddingBottom: insets.bottom +
16 }]]}>
294                 <View style={styles.modalHandle} />
295                 <Text style={[[styles.modalTitle, { color: colors.foreground }]]}>Select Company</Text>
296                 {COMPANIES.map(opt => (
297                     <TouchableOpacity key={opt} style={[[styles.optionRow, { borderBottomColor: colors.border }]]}
onPress={() => { setCompany(opt); setCompanyModal(false); Haptics.selectionAsync(); }}>
298                     <Text style={[[styles.optionText, { color: colors.foreground }]]}>{opt} Company</Text>
299                 </TouchableOpacity>
300             )]}
301             </View>
302         </TouchableOpacity>
303     </Modal>
304
305

```

```

306     </View>
307   );
308 }
309
310 const styles = StyleSheet.create({
311   root: { flex: 1 },
312   scroll: { flex: 1 },
313   content: { paddingHorizontal: 16, gap: 14 },
314   headerCard: { borderRadius: 20, padding: 28, alignItems: 'center', gap: 6 },
315   avatarCircle: { width: 80, height: 80, borderRadius: 40, backgroundColor: 'rgba(255,255,255,0.25)',
alignItems: 'center', justifyContent: 'center', marginBottom: 4 },
316   avatarText: { fontSize: 28, fontFamily: 'Inter_700Bold', color: '#FFF' },
317   profileName: { fontSize: 22, fontFamily: 'Inter_700Bold', color: '#FFF', textAlign: 'center' },
318   profileRole: { fontSize: 14, fontFamily: 'Inter_400Regular', color: 'rgba(255,255,255,0.8)' },
319   badgesRow: { flexDirection: 'row', flexWrap: 'wrap', gap: 8, marginTop: 8, justifyContent: 'center' },
320   profileBadge: { backgroundColor: 'rgba(255,255,255,0.2)', borderRadius: 20, paddingHorizontal: 12,
paddingVertical: 5 },
321   profileBadgeText: { fontSize: 12, fontFamily: 'Inter_600SemiBold', color: '#FFF' },
322   bmiCard: { flexDirection: 'row', alignItems: 'center', justifyContent: 'space-between', borderRadius: 14,
padding: 18, borderWidth: 2 },
323   bmiLeft: { gap: 4 },
324   bmiTitle: { fontSize: 16, fontFamily: 'Inter_600SemiBold' },
325   bmiStatus: { fontSize: 14, fontFamily: 'Inter_500Medium' },
326   bmiBig: { fontSize: 42, fontFamily: 'Inter_700Bold' },
327   section: { borderRadius: 14, borderWidth: 1, overflow: 'hidden' },
328   sectionTitle: { fontSize: 14, fontFamily: 'Inter_700Bold', padding: 14, paddingBottom: 8 },
329   infoRow: { flexDirection: 'row', alignItems: 'center', justifyContent: 'space-between',
paddingHorizontal: 14, paddingVertical: 12, borderBottomWidth: 1, gap: 10 },
330   infoLeft: { flexDirection: 'row', alignItems: 'center', gap: 8 },
331   infoLabel: { fontSize: 13, fontFamily: 'Inter_400Regular' },
332   infoValue: { fontSize: 14, fontFamily: 'Inter_500Medium', flex: 1, textAlign: 'right' },
333   editBtn: { flexDirection: 'row', alignItems: 'center', justifyContent: 'center', gap: 8, borderRadius:
14, paddingVertical: 15, borderWidth: 1.5, marginTop: 14 },
334   editText: { fontSize: 16, fontFamily: 'Inter_600SemiBold' },
335   logoutBtn: { flexDirection: 'row', alignItems: 'center', justifyContent: 'center', gap: 8, borderRadius:
14, paddingVertical: 15, borderWidth: 1.5 },
336   logoutText: { fontSize: 16, fontFamily: 'Inter_600SemiBold' },
337   modalOverlay: { flex: 1, backgroundColor: 'rgba(0,0,0,0.5)', justifyContent: 'flex-end' },
338   modalSheet: { borderTopLeftRadius: 20, borderTopRightRadius: 20, paddingHorizontal: 20, paddingTop: 12 },
339   modalHandle: { width: 40, height: 4, borderRadius: 2, backgroundColor: '#ccc', alignSelf: 'center',
marginBottom: 16 },
340   modalTitle: { fontSize: 18, fontFamily: 'Inter_700Bold', marginBottom: 16, textAlign: 'center' },
341   modalLabel: { fontSize: 12, fontFamily: 'Inter_500Medium', marginBottom: 6 },
342   modalInput: { borderWidth: 1, borderRadius: 8, padding: 12, fontSize: 14, fontFamily: 'Inter_400Regular',
marginBottom: 12 },
343   selectBtn: { flexDirection: 'row', alignItems: 'center', justifyContent: 'space-between', borderWidth: 1,
borderRadius: 8, padding: 12, marginBottom: 12 },
344   selectText: { fontSize: 14, fontFamily: 'Inter_400Regular', flex: 1 },
345   optionRow: { paddingVertical: 14, borderBottomWidth: 1 },
346   optionText: { fontSize: 15, fontFamily: 'Inter_500Medium' },
347   errorBox: { borderRadius: 10, borderWidth: 1, padding: 12, gap: 4, marginBottom: 12 },
348   errorText: { fontSize: 12, fontFamily: 'Inter_400Regular' },
349   noticeBox: { flexDirection: 'row', alignItems: 'center', gap: 8, borderRadius: 8, borderWidth: 1,
padding: 10, marginBottom: 12 },
350   noticeText: { fontSize: 12, fontFamily: 'Inter_500Medium', flex: 1 },
351   saveBtn: { flexDirection: 'row', alignItems: 'center', justifyContent: 'center', gap: 8, borderRadius:
10, paddingVertical: 13, marginBottom: 8, marginTop: 4 },
352   saveBtnText: { fontSize: 15, fontFamily: 'Inter_600SemiBold', color: '#FFF' },
353   cancelBtn: { borderWidth: 1, borderRadius: 10, paddingVertical: 12, alignItems: 'center' },
354   cancelBtnText: { fontSize: 14, fontFamily: 'Inter_500Medium' },
355 });
356

```

app/(tabs)/reports.tsx

```
1  import React, { useState, useEffect, useCallback } from 'react';
2  import {
3    View, Text, StyleSheet, FlatList, TouchableOpacity,
4    Platform, RefreshControl, TextInput, Modal, ScrollView, ActivityIndicator, Linking,
5  } from 'react-native';
6  import { useSafeAreaInsets } from 'react-native-safe-area-context';
7  import { Feather } from '@expo/vector-icons';
8  import * as Haptics from 'expo-haptics';
9  import * as DocumentPicker from 'expo-document-picker';
10 import { useFocusEffect } from 'expo-router';
11 import { useColors } from '@/hooks/useColors';
12 import { useAuth } from '@/context/AuthContext';
13 import { showAlert } from '@/lib/alert';
14 import { getReports, addReport, markReportRead, getUsers, genId } from '@/lib/storage';
15 import { uploadDocument, fileDownloadUrl } from '@/lib/upload';
16 import type { Report, User } from '@/lib/types';
17
18 const DOCUMENT_MIME_TYPES = [
19   'application/pdf',
20   'application/msword',
21   'application/vnd.openxmlformats-officedocument.wordprocessingml.document',
22 ];
23
24 const ROLE_LABELS: Record<string, string> = {
25   co: 'CO', '2ic': '2IC', coy_comd: 'Coy Comd', adjutant: 'Adjutant', clerk: 'Clerk', soldier: 'Soldier',
26 };
27 const REPORT_RECIPIENT_ROLES = ['co', '2ic', 'coy_comd', 'adjutant'];
28
29 export default function ReportsScreen() {
30   const colors = useColors();
31   const insets = useSafeAreaInsets();
32   const { user } = useAuth();
33   const isWeb = Platform.OS === 'web';
34
35   const [reports, setReports] = useState<Report[]>([]);
36   const [recipients, setRecipients] = useState<User[]>([]);
37   const [refreshing, setRefreshing] = useState(false);
38   const [composeVisible, setComposeVisible] = useState(false);
39   const [recipientPicker, setRecipientPicker] = useState(false);
40   const [recipient, setRecipient] = useState<User | null>(null);
41   const [selectedReport, setSelectedReport] = useState<Report | null>(null);
42   const [title, setTitle] = useState('');
43   const [content, setContent] = useState('');
44   const [attachment, setAttachment] = useState<{ name: string; url: string; mimeType: string } |
45   null>(null);
46   const [isUploading, setIsUploading] = useState(false);
47
48   const load = useCallback(async () => {
49     if (!user) return;
50     const [all, users] = await Promise.all([getReports(), getUsers()]);
51     const mine = all.filter(r => r.fromId === user.id || r.toId === user.id || r.toRole === user.role ||
52   r.fromRole === user.role);
53     setReports(mine);
54     setRecipients(users.filter(u => REPORT_RECIPIENT_ROLES.includes(u.role) && u.id !== user.id));
55   }, [user]);
56
57   useFocusEffect(useCallback(() => { load(); }, [load]));
58
59   const onRefresh = async () => { setRefreshing(true); await load(); setRefreshing(false); };
60
61   const handlePickFile = async () => {
62     const result = await DocumentPicker.getDocumentAsync({
63       type: [...DOCUMENT_MIME_TYPES, 'application/octet-stream'],
64       copyToCacheDirectory: true,
65     });
66     if (result.canceled || !result.assets?.[0]) return;
67     const asset = result.assets[0];
68     setIsUploading(true);
69     try {
70       const uploaded = await uploadDocument({ uri: asset.uri, name: asset.name, mimeType: asset.mimeType,
71   file: (asset as any).file });
72       setAttachment(uploaded);
73     } catch (e) {
74       showAlert('Error', 'Could not upload the file. Please try again.');
```

```

80     Haptics.impactAsync(Haptics.ImpactFeedbackStyle.Medium);
81     await addReport({
82       id: genId(), fromId: user!.id, fromName: user!.name, fromRole: user!.role,
83       toId: recipient.id, toRole: recipient.role,
84       title: title.trim(), content: content.trim(),
85       attachmentLabel: attachment?.name,
86       attachmentUrl: attachment?.url,
87       attachmentMimeType: attachment?.mimeType,
88       read: false, createdAt: new Date().toISOString(),
89     });
90     setComposeVisible(false);
91     setRecipient(null);
92     setTitle('');
93     setContent('');
94     setAttachment(null);
95     await load();
96     Haptics.notificationAsync(Haptics.NotificationFeedbackType.Success);
97     showAlert('Sent', 'Report has been sent.');
```

```

98   };
99
100   const openAttachment = (report: Report) => {
101     if (!report.attachmentUrl) return;
102     Linking.openURL(fileDownloadUrl(report.attachmentUrl));
103   };
104
105   const formatDate = (d: string) => new Date(d).toLocaleDateString('en-BD', { day: '2-digit', month:
'short', year: 'numeric' });
106
107   const renderItem = ({ item }: { item: Report }) => {
108     const isOwn = item.fromId === user?.id;
109     return (
110       <TouchableOpacity
111         style={[styles.card, { backgroundColor: colors.card, borderColor: item.read || isOwn ?
colors.border : colors.accent }]}
112         onPress={async () => { await markReportRead(item.id); setSelectedReport(item); await load(); }}
113         activeOpacity={0.75}
114       >
115         <View style={styles.cardHeader}>
116           <Text style={styles.cardTitle, { color: colors.foreground }}>{item.title}</Text>
117           {item.read && !isOwn && <View style={styles.unreadDot, { backgroundColor: colors.accent }} />}
118         </View>
119         <Text style={styles.cardFrom, { color: colors.mutedForeground }}>
120           {isOwn ? `To: ${ROLE_LABELS[item.toRole] ?? item.toRole}` : `From: ${item.fromName} .
${ROLE_LABELS[item.fromRole] ?? item.fromRole}`} · {formatDate(item.createdAt)}
121         </Text>
122         <Text style={styles.cardPreview, { color: colors.mutedForeground }} numberOfLines={2}
>{item.content}</Text>
123         {item.attachmentLabel && (
124           <TouchableOpacity
125             style={styles.attachRow, { backgroundColor: colors.muted }}
126             onPress={item.attachmentUrl ? () => openAttachment(item) : undefined}
127             disabled={!item.attachmentUrl}
128           >
129             <Feather name={item.attachmentUrl ? 'download' : 'paperclip'} size={12}
color={colors.mutedForeground} />
130             <Text style={styles.attachText, { color: colors.mutedForeground }}>{item.attachmentLabel}</
Text>
131           </TouchableOpacity>
132         )}
133       </TouchableOpacity>
134     );
135   };
136
137   const paddingTop = 16;
138   const paddingBottom = isWeb ? 34 : insets.bottom + 90;
139
140   return (
141     <View style={styles.root, { backgroundColor: colors.background }}>
142       <View style={styles.header, { paddingTop, backgroundColor: colors.background }}>
143         <Text style={styles.title, { color: colors.foreground }}>Reports</Text>
144         {user?.role === 'clerk' && (
145           <TouchableOpacity style={styles.sendBtn, { backgroundColor: colors.primary }} onPress={() =>
setComposeVisible(true)}>
146             <Feather name="plus" size={16} color="#FFF" />
147             <Text style={styles.sendBtnText}>New Report</Text>
148           </TouchableOpacity>
149         )}
150       </View>
151       <FlatList
152         data={reports}
153         keyExtractor={i => i.id}
154         renderItem={renderItem}
155         contentContainerStyle={styles.list, { paddingBottom }}
156         refreshControl={<RefreshControl refreshing={refreshing} onRefresh={onRefresh}
tintColor={colors.primary} />}

```

```

157     ItemSeparatorComponent={() => <View style={{ height: 10 }} />}
158     ListEmptyComponent={
159         <View style={styles.empty}>
160             <Feather name="file-text" size={48} color={colors.border} />
161             <Text style={[styles.emptyText, { color: colors.mutedForeground }]}>No reports yet</Text>
162         </View>
163     }
164 />
165
166     <Modal visible={composeVisible} transparent animationType="slide" onRequestClose={() =>
setComposeVisible(false)}>
167         <View style={styles.modalOverlay}>
168             <View style={[styles.modalSheet, { backgroundColor: colors.card, paddingBottom: insets.bottom +
20, maxHeight: '88%' }]}>
169                 <View style={styles.modalHandle} />
170                 <ScrollView keyboardShouldPersistTaps="handled">
171                     <Text style={[styles.modalTitle, { color: colors.foreground }]}>New Report</Text>
172                     <Text style={[styles.modalLabel, { color: colors.mutedForeground }]}>Send To</Text>
173                     <TouchableOpacity style={[styles.recipientBtn, { borderColor: colors.border, backgroundColor:
colors.background }]} onPress={() => setRecipientPicker(true)}>
174                         <Text style={[styles.recipientText, recipient ? { color: colors.foreground } : { color:
colors.mutedForeground }]}>
175                             {recipient ? `${recipient.name} · ${ROLE_LABELS[recipient.role] ?? recipient.role}` :
'Select recipient...'}
176                         </Text>
177                         <Feather name="chevron-down" size={16} color={colors.mutedForeground} />
178                     </TouchableOpacity>
179                     <Text style={[styles.modalLabel, { color: colors.mutedForeground }]}>Title</Text>
180                     <TextInput style={[styles.modalInput, { borderColor: colors.border, color: colors.foreground,
backgroundColor: colors.background }]} value={title} onChangeText={setTitle} placeholder="Report title..."
placeholderTextColor={colors.mutedForeground} />
181                     <Text style={[styles.modalLabel, { color: colors.mutedForeground }]}>Content</Text>
182                     <TextInput style={[styles.modalInput, { borderColor: colors.border, color: colors.foreground,
backgroundColor: colors.background, height: 120, textAlignVertical: 'top' }]} value={content}
onChangeText={setContent} placeholder="Report content..." placeholderTextColor={colors.mutedForeground}
multiline />
183                     <Text style={[styles.modalLabel, { color: colors.mutedForeground }]}>Attach a PDF or Word
document (optional)</Text>
184                     <TouchableOpacity
185                         style={[styles.attachPickBtn, { borderColor: colors.border, backgroundColor:
colors.background }]}
186                         onPress={handlePickFile}
187                         disabled={isUploading}
188                     >
189                         {isUploading ? (
190                             <>
191                                 <ActivityIndicator size="small" color={colors.primary} />
192                                 <Text style={[styles.attachPickText, { color: colors.mutedForeground }]}>Uploading...</
Text>
193                             </>
194                         ) : attachment ? (
195                             <>
196                                 <Feather name="file-text" size={16} color={colors.primary} />
197                                 <Text style={[styles.attachPickText, { color: colors.foreground, flex: 1 }]}
numberOfLines={1}>{attachment.name}</Text>
198                                 <TouchableOpacity onPress={() => setAttachment(null)} hitSlop={8}>
199                                     <Feather name="x" size={16} color={colors.mutedForeground} />
200                                 </TouchableOpacity>
201                             </>
202                         ) : (
203                             <>
204                                 <Feather name="paperclip" size={16} color={colors.mutedForeground} />
205                                 <Text style={[styles.attachPickText, { color: colors.mutedForeground }]}>Tap to choose
a file</Text>
206                             </>
207                         )}
208                     </TouchableOpacity>
209                     <TouchableOpacity style={[styles.submitBtn, { backgroundColor: colors.primary }]}
onPress={handleSend}>
210                         <Feather name="send" size={18} color="#FFF" />
211                         <Text style={styles.submitBtnText}>Send Report</Text>
212                     </TouchableOpacity>
213                     <TouchableOpacity style={[styles.cancelBtn, { borderColor: colors.border }]} onPress={() =>
setComposeVisible(false)}>
214                         <Text style={[styles.cancelBtnText, { color: colors.mutedForeground }]}>Cancel</Text>
215                     </TouchableOpacity>
216                 </ScrollView>
217             </View>
218         </View>
219     </Modal>
220
221     /* Recipient picker */
222     <Modal visible={recipientPicker} transparent animationType="slide" onRequestClose={() =>
setRecipientPicker(false)}>
223         <TouchableOpacity style={styles.modalOverlay} activeOpacity={1} onPress={() =>

```

```

setRecipientPicker(false))>
224     <View style={{[styles.modalSheet, { backgroundColor: colors.card, paddingBottom: insets.bottom +
16, maxHeight: '75%' } ]}}>
225         <View style={styles.modalHandle} />
226         <Text style={{[styles.modalTitle, { color: colors.foreground } ]}}>Select Recipient</Text>
227         <FlatList
228             data={recipients}
229             keyExtractor={i => i.id}
230             style={{ maxHeight: 380 }}
231             renderItem={({ item }) => (
232                 <TouchableOpacity style={{[styles.contactRow, { borderBottomColor: colors.border } ]}}
233                     onPress={() => { setRecipient(item); setRecipientPicker(false);
Haptics.selectionAsync(); }}>
234                     <View style={{ flex: 1 }}>
235                         <Text style={{[styles.contactName, { color: colors.foreground } ]}}>{item.name}</Text>
236                         <Text style={{[styles.contactRole, { color: colors.mutedForeground } ]}}>
237                             {ROLE_LABELS[item.role] ?? item.role}{item.company ? ` · ${item.company} Coy` : ''}
238                         </Text>
239                     </View>
240                 </TouchableOpacity>
241             )}
242             ListEmptyComponent={<Text style={{ color: colors.mutedForeground, textAlign: 'center',
paddingVertical: 20 }}>No recipients available</Text>}
243         />
244     </View>
245 </TouchableOpacity>
246 </Modal>
247
248     <Modal visible={!selectedReport} transparent animationType="slide" onRequestClose={() =>
setSelectedReport(null)}>
249         <View style={styles.modalOverlay}>
250             <View style={{[styles.modalSheet, { backgroundColor: colors.card, paddingBottom: insets.bottom +
20, maxHeight: '85%' } ]}}>
251                 <View style={styles.modalHandle} />
252                 <ScrollView>
253                     <Text style={{[styles.modalTitle, { color: colors.foreground } ]}}>{selectedReport?.title}</Text>
254                     <Text style={{[styles.modalLabel, { color: colors.mutedForeground } ]}}>From:
{selectedReport?.fromName} · {formatDate(selectedReport?.createdAt ?? '')}</Text>
255                     <Text style={{[styles.reportBody, { color: colors.foreground } ]}}>{selectedReport?.content}</
Text>
256                     {selectedReport?.attachmentLabel && (
257                         <TouchableOpacity
258                             style={{[styles.attachRow, { backgroundColor: colors.muted, marginTop: 12 } ]}}
259                             onPress={selectedReport.attachmentUrl ? () => openAttachment(selectedReport) : undefined}
260                             disabled={!selectedReport.attachmentUrl}
261                         >
262                             <Feather name={selectedReport.attachmentUrl ? 'download' : 'paperclip'} size={14}
color={colors.mutedForeground} />
263                             <Text style={{[styles.attachText, { color: colors.mutedForeground } ]}}
>{selectedReport.attachmentLabel}</Text>
264                         </TouchableOpacity>
265                     )}
266                 </ScrollView>
267                 <TouchableOpacity style={{[styles.cancelBtn, { borderColor: colors.border, marginTop: 12 } ]}}
onPress={() => setSelectedReport(null)}>
268                     <Text style={{[styles.cancelBtnText, { color: colors.mutedForeground } ]}}>Close</Text>
269                 </TouchableOpacity>
270             </View>
271         </View>
272     </Modal>
273 </View>
274 );
275 }
276
277 const styles = StyleSheet.create({
278     root: { flex: 1 },
279     header: { flexDirection: 'row', alignItems: 'center', justifyContent: 'space-between', paddingHorizontal:
16, paddingBottom: 12 },
280     title: { fontSize: 24, fontFamily: 'Inter_700Bold' },
281     sendBtn: { flexDirection: 'row', alignItems: 'center', gap: 6, borderRadius: 10, paddingHorizontal: 12,
paddingVertical: 8 },
282     sendBtnText: { fontSize: 13, fontFamily: 'Inter_600SemiBold', color: '#FFF' },
283     list: { paddingHorizontal: 16, paddingTop: 4 },
284     card: { borderRadius: 12, borderWidth: 1.5, padding: 14, gap: 6 },
285     cardHeader: { flexDirection: 'row', alignItems: 'center', justifyContent: 'space-between' },
286     cardTitle: { fontSize: 15, fontFamily: 'Inter_600SemiBold', flex: 1 },
287     unreadDot: { width: 8, height: 8, borderRadius: 4 },
288     cardFrom: { fontSize: 11, fontFamily: 'Inter_400Regular' },
289     cardPreview: { fontSize: 13, fontFamily: 'Inter_400Regular', lineHeight: 18 },
290     attachRow: { flexDirection: 'row', alignItems: 'center', gap: 6, borderRadius: 6, paddingHorizontal: 8,
paddingVertical: 5, alignSelf: 'flex-start' },
291     attachText: { fontSize: 11, fontFamily: 'Inter_400Regular' },
292     empty: { alignItems: 'center', paddingVertical: 60, gap: 12 },
293     emptyText: { fontSize: 15, fontFamily: 'Inter_400Regular' },
294     modalOverlay: { flex: 1, backgroundColor: 'rgba(0,0,0,0.5)', justifyContent: 'flex-end' },

```

```

295     modalSheet: { borderTopLeftRadius: 20, borderTopRightRadius: 20, paddingHorizontal: 20, paddingTop: 12 },
296     modalHandle: { width: 40, height: 4, borderRadius: 2, backgroundColor: '#ccc', alignSelf: 'center',
marginBottom: 16 },
297     modalTitle: { fontSize: 18, fontFamily: 'Inter_700Bold', marginBottom: 12 },
298     modalLabel: { fontSize: 12, fontFamily: 'Inter_500Medium', marginBottom: 6 },
299     modalInput: { borderWidth: 1, borderRadius: 8, padding: 12, fontSize: 14, fontFamily: 'Inter_400Regular',
marginBottom: 12 },
300     reportBody: { fontSize: 14, fontFamily: 'Inter_400Regular', lineHeight: 22, marginBottom: 8, marginTop:
8 },
301     attachPickBtn: { flexDirection: 'row', alignItems: 'center', gap: 8, borderWidth: 1, borderRadius: 8,
padding: 12, marginBottom: 12 },
302     attachPickText: { fontSize: 13, fontFamily: 'Inter_500Medium' },
303     recipientBtn: { flexDirection: 'row', alignItems: 'center', justifyContent: 'space-between', borderWidth:
1, borderRadius: 8, padding: 12, marginBottom: 12 },
304     recipientText: { fontSize: 14, fontFamily: 'Inter_400Regular', flex: 1 },
305     contactRow: { flexDirection: 'row', alignItems: 'center', gap: 12, paddingVertical: 12,
borderBottomWidth: 1 },
306     contactName: { fontSize: 14, fontFamily: 'Inter_600SemiBold' },
307     contactRole: { fontSize: 12, fontFamily: 'Inter_400Regular', marginTop: 1 },
308     submitBtn: { flexDirection: 'row', alignItems: 'center', justifyContent: 'center', gap: 8, borderRadius:
10, paddingVertical: 13, marginBottom: 8 },
309     submitBtnText: { fontSize: 15, fontFamily: 'Inter_600SemiBold', color: '#FFF' },
310     cancelBtn: { borderWidth: 1, borderRadius: 10, paddingVertical: 12, alignItems: 'center' },
311     cancelBtnText: { fontSize: 14, fontFamily: 'Inter_500Medium' },
312 });
313

```

app/(tabs)/soldiers.tsx

```
1  import React, { useState, useEffect, useCallback } from 'react';
2  import {
3    View, Text, StyleSheet, FlatList, TouchableOpacity,
4    TextInput, Platform, RefreshControl,
5  } from 'react-native';
6  import { useSafeAreaInsets } from 'react-native-safe-area-context';
7  import { Feather, MaterialCommunityIcons } from '@expo/vector-icons';
8  import { router, useFocusEffect } from 'expo-router';
9  import * as Haptics from 'expo-haptics';
10 import { useColors } from '@hooks/useColors';
11 import { useAuth } from '@context/AuthContext';
12 import { showAlert } from '@lib/alert';
13 import { getSoldiers, updateSoldier, updateUser, deleteSoldier, deleteUser, calcBMI, addNotification,
14   genId } from '@lib/storage';
15 import type { Soldier, Company } from '@lib/types';
16
17 const COMPANIES: (Company | 'ALL')[] = ['ALL', 'A', 'B', 'C', 'D'];
18 const STATUS_FILTERS = ['ALL', 'fit', 'unfit', 'pending'];
19 // "pending" here is ptStatus (not yet taken an IPFT test), which is a
20 // different thing from a registration awaiting Adjutant approval – the chip
21 // is labeled differently from the raw value to avoid the two "pending"s
22 // being read as the same thing.
23 const STATUS_LABELS: Record<string, string> = { ALL: 'ALL', fit: 'FIT', unfit: 'UNFIT', pending: 'AWAITING
24   TEST' };
25
26 export default function SoldiersScreen() {
27   const colors = useColors();
28   const insets = useSafeAreaInsets();
29   const { user } = useAuth();
30   const isWeb = Platform.OS === 'web';
31
32   const [soldiers, setSoldiers] = useState<Soldier[]>([]);
33   const [filtered, setFiltered] = useState<Soldier[]>([]);
34   const [search, setSearch] = useState('');
35   const [companyFilter, setCompanyFilter] = useState<Company | 'ALL'>('ALL');
36   const [statusFilter, setStatusFilter] = useState('ALL');
37   const [refreshing, setRefreshing] = useState(false);
38
39   const load = useCallback(async () => {
40     const all = await getSoldiers();
41     const visible = user?.role === 'coy_comd'
42       ? all.filter(s => s.company === user.company)
43       : all;
44     setSoldiers(visible);
45   }, [user]);
46
47   useFocusEffect(useCallback(() => { load(); }, [load]));
48
49   useEffect(() => {
50     let result = [...soldiers];
51     if (companyFilter !== 'ALL') result = result.filter(s => s.company === companyFilter);
52     if (statusFilter !== 'ALL') result = result.filter(s => s.ptStatus === statusFilter);
53     if (search.trim()) {
54       const q = search.trim().toLowerCase();
55       result = result.filter(s =>
56         s.name.toLowerCase().includes(q) ||
57         s.serviceNumber.toLowerCase().includes(q) ||
58         s.rank.toLowerCase().includes(q)
59       );
60     }
61     setFiltered(result);
62   }, [soldiers, search, companyFilter, statusFilter]);
63
64   const onRefresh = async () => { setRefreshing(true); await load(); setRefreshing(false); };
65
66   const handleApprove = async (soldier: Soldier) => {
67     if (user?.role !== 'adjutant') return;
68     Haptics.impactAsync(Haptics.ImpactFeedbackStyle.Medium);
69     showAlert('Approve Soldier', `Approve ${soldier.rank} ${soldier.name}`, [
70       { text: 'Cancel', style: 'cancel' },
71       {
72         text: 'Approve', onPress: async () => {
73           // Reflect the approval immediately instead of waiting on the
74           // network round trip to the shared server, so the row (and the
75           // dashboard's pending/total counts) update the instant you tap
76           // Approve rather than only after load() resolves.
77           setSoldiers(prev => prev.map(s => s.id === soldier.id ? { ...s, isApproved: true, ptStatus:
78             'pending' } : s));
79           try {
80             await updateSoldier(soldier.id, { isApproved: true, ptStatus: 'pending' });
81             await updateUser(soldier.userId, { isApproved: true });
82             await addNotification({
83               id: genId(), targetUserId: soldier.userId, title: 'Account Approved',
```

```

81         body: 'Your soldier account has been approved by Adjutant.', type: 'general', read: false,
createdAt: new Date().toISOString(),
82     });
83     Haptics.notificationAsync(Haptics.NotificationFeedbackType.Success);
84   } catch (e) {
85     showAlert('Error', 'Could not approve the soldier – check your connection and try again.');
```

```

86   } finally {
87     await load();
88   }
89 },
90 },
91 ]);
92 };
93
94 // Used both to reject a pending registration and to let the Adjutant
95 // delete any already-approved soldier's account from the roster.
96 const handleDeleteSoldier = (soldier: Soldier) => {
97   if (user?.role !== 'adjutant') return;
98   Haptics.impactAsync(Haptics.ImpactFeedbackStyle.Medium);
99   const title = soldier.isApproved ? 'Delete Soldier' : 'Delete Registration';
100  const message = soldier.isApproved
101    ? `Permanently delete ${soldier.rank} ${soldier.name} (${soldier.serviceNumber})? This removes their
account and cannot be undone.`
102    : `Delete the registration for ${soldier.rank} ${soldier.name}? This cannot be undone.`;
103  showAlert(title, message, [
104    { text: 'Cancel', style: 'cancel' },
105    {
106      text: 'Delete', style: 'destructive', onPress: async () => {
107        setSoldiers(prev => prev.filter(s => s.id !== soldier.id));
108        try {
109          await deleteSoldier(soldier.id);
110          await deleteUser(soldier.userId);
111          Haptics.notificationAsync(Haptics.NotificationFeedbackType.Success);
112        } catch (e) {
113          showAlert('Error', 'Could not delete the record – check your connection and try again.');
```

```

114        } finally {
115          await load();
116        }
117      },
118    },
119  ]);
120 };
121
122 const ptColor = (status: string) => {
123   if (status === 'fit') return colors.success;
124   if (status === 'unfit') return colors.destructive;
125   return colors.muted;
126 };
127
128 const ptTextColor = (status: string) => {
129   if (status === 'fit') return colors.success;
130   if (status === 'unfit') return colors.destructive;
131   return colors.mutedForeground;
132 };
133
134 const renderItem = ({ item }: { item: Soldier }) => {
135   const bmi = calcBMI(item.weight, item.height);
136   return (
137     <TouchableOpacity
138       style={[styles.card, { backgroundColor: colors.card, borderColor: colors.border }]}
139       onPress={() => router.push(`/soldier/${item.id}`)}
140       activeOpacity={0.75}
141     >
142       <View style={styles.cardLeft}>
143         <View style={[styles.avatar, { backgroundColor: colors.primary + '20' }]}>
144           <Text style={[styles.avatarText, { color: colors.primary }]}>
145             {item.name.split(' ').map(n => n[0]).join('').slice(0, 2).toUpperCase()}
146           </Text>
147         </View>
148       </View>
149       <View style={styles.cardMiddle}>
150         <Text style={[styles.name, { color: colors.foreground }]}>{item.rank} {item.name}</Text>
151         <Text style={[styles.meta, { color: colors.mutedForeground }]}>{item.serviceNumber} .
{item.company} Coy</Text>
152         <View style={styles.tagsRow}>
153           <View style={[styles.tag, { backgroundColor: ptColor(item.ptStatus) + '15' }]}>
154             <Text style={[styles.tagText, { color: ptTextColor(item.ptStatus) }]}>
>{item.ptStatus.toUpperCase()}</Text>
155           </View>
156           {item.isOverweight && (
157             <View style={[styles.tag, { backgroundColor: colors.warning + '15' }]}>
158               <MaterialCommunityIcons name="alert" size={10} color={colors.warning} />
159               <Text style={[styles.tagText, { color: colors.warning }]}>OVERWEIGHT</Text>
160             </View>
161           )}

```

```

162         {!item.isApproved && (
163             <View style={styles.tag, { backgroundColor: colors.accent + '15' }}>
164                 <Text style={styles.tagText, { color: colors.accent }}>PENDING</Text>
165             </View>
166         )}
167     </View>
168 </View>
169 <View style={styles.cardRight}>
170     <Text style={styles.bmiLabel, { color: colors.mutedForeground }}>BMI</Text>
171     <Text style={styles.bmiValue, { color: bmi > 25 ? colors.warning : colors.success }}>{bmi}</
Text>
172     {user?.role === 'adjutant' && !item.isApproved ? (
173         <View style={styles.pendingActions}>
174             <TouchableOpacity style={styles.approveBtn, { backgroundColor: colors.success }}
onPress={() => handleApprove(item)}>
175                 <Text style={styles.approveBtnText}>Approve</Text>
176             </TouchableOpacity>
177             <TouchableOpacity style={styles.approveBtn, { backgroundColor: colors.destructive }}
onPress={() => handleDeleteSoldier(item)}>
178                 <Text style={styles.approveBtnText}>Delete</Text>
179             </TouchableOpacity>
180         </View>
181     ) : user?.role === 'adjutant' ? (
182         <View style={styles.approvedActions}>
183             <TouchableOpacity onPress={() => handleDeleteSoldier(item)} hitSlop={8}>
184                 <Feather name="trash-2" size={16} color={colors.destructive} />
185             </TouchableOpacity>
186             <Feather name="chevron-right" size={18} color={colors.mutedForeground} />
187         </View>
188     ) : (
189         <Feather name="chevron-right" size={18} color={colors.mutedForeground} />
190     )}
191 </View>
192 </TouchableOpacity>
193 );
194 };
195
196 const paddingTop = 16;
197 const paddingBottom = isWeb ? 34 : insets.bottom + 90;
198
199 return (
200     <View style={styles.root, { backgroundColor: colors.background }}>
201         <View style={styles.header, { paddingTop, backgroundColor: colors.background }}>
202             <Text style={styles.title, { color: colors.foreground }}>Soldiers</Text>
203             <Text style={styles.subtitle, { color: colors.mutedForeground }}>{filtered.length} of
{soldiers.length} shown</Text>
204         </View>
205         <View style={styles.searchBar, { backgroundColor: colors.card, borderColor: colors.border }}>
206             <Feather name="search" size={16} color={colors.mutedForeground} />
207             <TextInput
208                 style={styles.searchInput, { color: colors.foreground }}
209                 placeholder="Search name, service no, rank..."
210                 placeholderTextColor={colors.mutedForeground}
211                 value={search}
212                 onChangeText={setSearch}
213             />
214             {!!search && (
215                 <TouchableOpacity onPress={() => setSearch('')}>
216                     <Feather name="x" size={16} color={colors.mutedForeground} />
217                 </TouchableOpacity>
218             )}
219         </View>
220
221         {user?.role !== 'coy_comd' && (
222             <FlatList
223                 horizontal showsHorizontalScrollIndicator={false}
224                 data={COMPANIES}
225                 keyExtractor={i => i}
226                 contentContainerStyle={{ gap: 8, paddingBottom: 8 }}
227                 renderItem={({ item }) => (
228                     <TouchableOpacity
229                         style={styles.filterChip, { backgroundColor: companyFilter === item ? colors.primary :
colors.card, borderColor: companyFilter === item ? colors.primary : colors.border }}
230                         onPress={() => { Haptics.selectionAsync(); setCompanyFilter(item as Company | 'ALL'); }}
231                     >
232                         <Text style={styles.filterChipText, { color: companyFilter === item ? '#FFF' :
colors.mutedForeground }}>{item}</Text>
233                     </TouchableOpacity>
234                 )}
235             />
236         )}
237
238         <FlatList
239             horizontal showsHorizontalScrollIndicator={false}
240             data={STATUS_FILTERS}

```

```

241         keyExtractor={i => i}
242         contentContainerStyle={{ gap: 8, paddingBottom: 8 }}
243         renderItem={({ item }) => (
244             <TouchableOpacity
245                 style={[styles.filterChip, { backgroundColor: statusFilter === item ? colors.accent :
colors.card, borderColor: statusFilter === item ? colors.accent : colors.border }]}
246                 onPress={() => { Haptics.selectionAsync(); setStatusFilter(item); }}
247             >
248                 <Text style={[styles.filterChipText, { color: statusFilter === item ? '#000' :
colors.mutedForeground }]}>{STATUS_LABELS[item] ?? item.toUpperCase()}</Text>
249             </TouchableOpacity>
250         )}
251     />
252 </View>
253
254     <FlatList
255         data={filtered}
256         keyExtractor={i => i.id}
257         renderItem={renderItem}
258         contentContainerStyle={[styles.list, { paddingBottom }]}
259         refreshControl={<RefreshControl refreshing={refreshing} onRefresh={onRefresh}
tintColor={colors.primary} />}
260         ListEmptyComponent={
261             <View style={styles.empty}>
262                 <MaterialCommunityIcons name="account-off" size={48} color={colors.border} />
263                 <Text style={[styles.emptyText, { color: colors.mutedForeground }]}>No soldiers found</Text>
264             </View>
265         }
266         ItemSeparatorComponent={() => <View style={{ height: 8 }} />}
267     />
268 </View>
269 );
270 }
271
272 const styles = StyleSheet.create({
273     root: { flex: 1 },
274     header: { paddingHorizontal: 16, paddingBottom: 4 },
275     title: { fontSize: 24, fontFamily: 'Inter_700Bold', marginBottom: 2 },
276     subtitle: { fontSize: 12, fontFamily: 'Inter_400Regular', marginBottom: 12 },
277     searchBar: { flexDirection: 'row', alignItems: 'center', gap: 8, borderWidth: 1, borderRadius: 10,
paddingHorizontal: 12, paddingVertical: 10, marginBottom: 10 },
278     searchInput: { flex: 1, fontSize: 14, fontFamily: 'Inter_400Regular' },
279     filterChip: { borderRadius: 20, paddingHorizontal: 14, paddingVertical: 6, borderWidth: 1 },
280     filterChipText: { fontSize: 12, fontFamily: 'Inter_600SemiBold' },
281     list: { paddingHorizontal: 16, paddingTop: 8 },
282     card: { flexDirection: 'row', alignItems: 'center', gap: 12, padding: 14, borderRadius: 12, borderWidth:
1 },
283     cardLeft: {},
284     cardMiddle: { flex: 1, gap: 3 },
285     cardRight: { alignItems: 'center', gap: 4 },
286     avatar: { width: 44, height: 44, borderRadius: 22, alignItems: 'center', justifyContent: 'center' },
287     avatarText: { fontSize: 14, fontFamily: 'Inter_700Bold' },
288     name: { fontSize: 14, fontFamily: 'Inter_600SemiBold' },
289     meta: { fontSize: 12, fontFamily: 'Inter_400Regular' },
290     tagsRow: { flexDirection: 'row', flexWrap: 'wrap', gap: 4 },
291     tag: { flexDirection: 'row', alignItems: 'center', gap: 3, borderRadius: 4, paddingHorizontal: 6,
paddingVertical: 2 },
292     tagText: { fontSize: 9, fontFamily: 'Inter_700Bold', letterSpacing: 0.5 },
293     bmiLabel: { fontSize: 9, fontFamily: 'Inter_600SemiBold', letterSpacing: 1 },
294     bmiValue: { fontSize: 16, fontFamily: 'Inter_700Bold' },
295     pendingActions: { gap: 4 },
296     approvedActions: { flexDirection: 'row', alignItems: 'center', gap: 10 },
297     approveBtn: { borderRadius: 6, paddingHorizontal: 8, paddingVertical: 5, minWidth: 58, alignItems:
'center' },
298     approveBtnText: { fontSize: 10, fontFamily: 'Inter_600SemiBold', color: '#FFF' },
299     empty: { alignItems: 'center', paddingVertical: 48, gap: 12 },
300     emptyText: { fontSize: 15, fontFamily: 'Inter_400Regular' },
301 });
302

```

app/+not-found.tsx

```
1 import { Link, Stack } from 'expo-router';
2 import { StyleSheet, Text, View } from 'react-native';
3 import { useColors } from '@hooks/useColors';
4
5 export default function NotFoundScreen() {
6   const colors = useColors();
7   return (
8     <
9       <Stack.Screen options={{ title: 'Oops!' }} />
10      <View style={[styles.container, { backgroundColor: colors.background }]}>
11        <Text style={[styles.title, { color: colors.foreground }]}>This screen doesn't exist.</Text>
12        <Link href="/" style={styles.link}>
13          <Text style={[styles.linkText, { color: colors.primary }]}>Go to home screen!</Text>
14        </Link>
15      </View>
16    </>
17  );
18 }
19
20 const styles = StyleSheet.create({
21   container: { flex: 1, alignItems: 'center', justifyContent: 'center', padding: 20 },
22   title: { fontSize: 20, fontWeight: 'bold' },
23   link: { marginTop: 15, paddingVertical: 15 },
24   linkText: { fontSize: 14 },
25 });
26
```

app/index.tsx

```
1 import { Redirect } from 'expo-router';
2 import { useAuth } from '@context/AuthContext';
3 import { View, ActivityIndicator } from 'react-native';
4 import { useColors } from '@hooks/useColors';
5
6 export default function Index() {
7   const { user, isLoading } = useAuth();
8   const colors = useColors();
9
10  if (isLoading) {
11    return (
12      <View style={{ flex: 1, alignItems: 'center', justifyContent: 'center', backgroundColor:
colors.background }}>
13        <ActivityIndicator size="large" color={colors.primary} />
14      </View>
15    );
16  }
17
18  if (!user) return <Redirect href="/(auth)/login" />;
19  return <Redirect href="/(tabs)" />;
20 }
21
```

app/plan/[id].tsx

```
1 import React, { useState, useEffect } from 'react';
2 import { View, Text, StyleSheet, ScrollView, TouchableOpacity, Platform, ActivityIndicator } from 'react-native';
3 import { useSafeAreaInsets } from 'react-native-safe-area-context';
4 import { useLocalSearchParams, router } from 'expo-router';
5 import { Feather, MaterialCommunityIcons } from '@expo/vector-icons';
6 import * as FileSystem from 'expo-file-system/legacy';
7 import * as Sharing from 'expo-sharing';
8 import * as Haptics from 'expo-haptics';
9 import { useColors } from '@hooks/useColors';
10 import { showAlert } from '@lib/alert';
11 import { getPTPlans } from '@lib/storage';
12 import { API_BASE } from '@lib/api';
13 import type { PTPlan, PTPlanDay } from '@lib/types';
14
15 /**
16  * The plan PDF is generated on the shared server (server/pdf.js) rather than
17  * via expo-print, because expo-print's web implementation has no real
18  * "generate a PDF file" capability – printToFileAsync just calls
19  * window.print() on web, which always opens the browser's print dialog. A
20  * server-generated PDF lets both web and native do a genuine one-tap
21  * download with no dialog in between.
22  */
23 async function downloadPlanPdf(plan: PTPlan): Promise<{ url: string; name: string }> {
24   const res = await fetch(`${API_BASE}/generate-plan-pdf`, {
25     method: 'POST',
26     headers: { 'Content-Type': 'application/json' },
27     body: JSON.stringify(plan),
28   });
29   if (!res.ok) throw new Error('PDF generation failed');
30   return res.json();
31 }
32
33 export default function PlanDetailScreen() {
34   const colors = useColors();
35   const insets = useSafeAreaInsets();
36   const { id } = useLocalSearchParams<{ id: string }>();
37   const isWeb = Platform.OS === 'web';
38
39   const [plan, setPlan] = useState<PTPlan | null>(null);
40   const [loading, setLoading] = useState(true);
41   const [expandedDay, setExpandedDay] = useState<number | null>(0);
42   const [isExporting, setIsExporting] = useState(false);
43
44   useEffect(() => {
45     (async () => {
46       const plans = await getPTPlans();
47       setPlan(plans.find(p => p.id === id) ?? null);
48       setLoading(false);
49     })();
50   }, [id]);
51
52   if (loading) return <View style={[styles.center, { backgroundColor: colors.background }]}
53 ><ActivityIndicator size="large" color={colors.primary} /></View>;
54   if (!plan) return <View style={[styles.center, { backgroundColor: colors.background }]}><Text
55 style={{ color: colors.mutedForeground }}>Plan not found</Text></View>;
56
57   const handleExport = async () => {
58     setIsExporting(true);
59     Haptics.impactAsync(Haptics.ImpactFeedbackStyle.Medium);
60     try {
61       const { url, name } = await downloadPlanPdf(plan);
62       const fileUrl = `${API_BASE}${url}?download=1`;
63       if (isWeb) {
64         // Plain browser download – no print dialog, no new tab.
65         const link = document.createElement('a');
66         link.href = fileUrl;
67         link.download = name;
68         document.body.appendChild(link);
69         link.click();
70         document.body.removeChild(link);
71       } else {
72         const localUri = FileSystem.cacheDirectory + name;
73         const { uri } = await FileSystem.downloadAsync(fileUrl, localUri);
74         if (await Sharing.isAvailableAsync()) {
75           await Sharing.shareAsync(uri, { mimeType: 'application/pdf', dialogTitle: plan.title });
76         } else {
77           showAlert('Downloaded', `PDF saved to: ${uri}`);
78         }
79       }
80     } catch (e) {
81       showAlert('Error', 'Could not download the PDF. Please try again.');
```

```

81     setIsExporting(false);
82   }
83 };
84
85 const accent = plan.type === 'fit' ? colors.success : colors.warning;
86 const paddingTop = (isWeb ? 67 : 0) + insets.top + 16;
87 const paddingBottom = isWeb ? 34 : insets.bottom + 24;
88
89 return (
90   <ScrollView style={[styles.root, { backgroundColor: colors.background }]}
91     containerViewStyle={[styles.content, { padding: paddingTop, padding: paddingBottom }]}>
92     <View style={styles.topRow}>
93       <TouchableOpacity onPress={() => router.back()} style={styles.backBtn}>
94         <Feather name="arrow-left" size={20} color={colors.foreground} />
95         <Text style={styles.backText, { color: colors.foreground }}>Back</Text>
96       </TouchableOpacity>
97       <TouchableOpacity
98         style={[styles.exportBtn, { backgroundColor: colors.primary }, { opacity: 0.7 }]}
99         onPress={handleExport} disabled={isExporting} activeOpacity={0.85}
100       >
101         {isExporting ? <ActivityIndicator size="small" color="#FFF" /> : <Feather name="download"
size={15} color="#FFF" />}
102         <Text style={styles.exportBtnText}>{isExporting ? 'Preparing...' : 'Download PDF'}</Text>
103       </TouchableOpacity>
104     </View>
105
106     <View style={[styles.heroCard, { backgroundColor: accent + '15', borderColor: accent }]}>
107       <View style={styles.typeTag, { backgroundColor: accent }}>
108         <Text style={styles.typeTagText}>{plan.type === 'fit' ? 'FIT PLAN' : 'REHABILITATION PLAN'}</Text>
109       </View>
110       <Text style={styles.heroTitle, { color: colors.foreground }}>{plan.title}</Text>
111       <Text style={styles.heroDesc, { color: colors.mutedForeground }}>{plan.description}</Text>
112       <View style={styles.heroMetaRow}>
113         <View style={styles.metaPill}>
114           <Feather name="calendar" size={12} color={colors.mutedForeground} />
115           <Text style={styles.metaText, { color: colors.mutedForeground }}>Week {plan.weekNumber}</Text>
116         </View>
117         <View style={styles.metaPill}>
118           <MaterialCommunityIcons name="dumbbell" size={12} color={colors.mutedForeground} />
119           <Text style={styles.metaText, { color: colors.mutedForeground }}>{plan.days.length} days</
Text>
120         </View>
121         <View style={styles.metaPill}>
122           <Feather name="user" size={12} color={colors.mutedForeground} />
123           <Text style={styles.metaText, { color: colors.mutedForeground }}>{plan.createdByName}</Text>
124         </View>
125       </View>
126
127       <Text style={styles.sectionLabel, { color: colors.foreground }}>Weekly Schedule</Text>
128       {plan.days.map((day: PTPlanDay, idx: number) => {
129         const isExpanded = expandedDay === idx;
130         return (
131           <View key={idx} style={styles.dayCard, { backgroundColor: colors.card, borderColor: isExpanded ?
accent : colors.border }}>
132             <TouchableOpacity style={styles.dayHeader} onPress={() => setExpandedDay(isExpanded ? null :
idx)} activeOpacity={0.75}>
133               <View style={styles.dayNumber, { backgroundColor: accent }}>
134                 <Text style={styles.dayNumberText}>{idx + 1}</Text>
135               </View>
136               <View style={{ flex: 1 }}>
137                 <Text style={styles.dayName, { color: colors.foreground }}>{day.day}</Text>
138                 <Text style={styles.dayFocus, { color: accent }}>{day.focus}</Text>
139               </View>
140               <View style={styles.exerciseCount}>
141                 <Text style={styles.exerciseCountText, { color: colors.mutedForeground }}>
>{day.exercises.length} exercises</Text>
142               </View>
143               <Feather name={isExpanded ? 'chevron-up' : 'chevron-down'} size={18}
color={colors.mutedForeground} />
144             </TouchableOpacity>
145             {isExpanded && (
146               <View style={styles.exerciseList, { borderTopColor: colors.border }}>
147                 {day.exercises.map((ex, ei) => (
148                   <View key={ei} style={styles.exerciseItem, { borderBottomColor: colors.border }}>
149                     <View style={styles.exerciseBullet, { backgroundColor: accent }} />
150                     <View style={{ flex: 1 }}>
151                       <Text style={styles.exerciseName, { color: colors.foreground }}>{ex.name}</Text>
152                       <Text style={styles.exerciseTarget, { color: colors.primary }}>{ex.target}</Text>
153                       {ex.notes && <Text style={styles.exerciseNotes, { color: colors.mutedForeground }}>
>{ex.notes}</Text>
154                     </View>
155                   </View>
156                 ))}
157               </View>
158             )}

```

```

159         })
160     </View>
161     );
162     })}
163 </ScrollView>
164 );
165 }
166
167 const styles = StyleSheet.create({
168     root: { flex: 1 },
169     content: { paddingHorizontal: 16, gap: 12 },
170     center: { flex: 1, alignItems: 'center', justifyContent: 'center' },
171     topRow: { flexDirection: 'row', alignItems: 'center', justifyContent: 'space-between', marginBottom: 4,
gap: 10 },
172     backBtn: { flexDirection: 'row', alignItems: 'center', gap: 6 },
173     exportBtn: { flexDirection: 'row', alignItems: 'center', gap: 7, borderRadius: 8, paddingHorizontal: 12,
paddingVertical: 8 },
174     exportBtnText: { fontSize: 12, fontFamily: 'Inter_600SemiBold', color: '#FFF' },
175     backText: { fontSize: 15, fontFamily: 'Inter_500Medium' },
176     heroCard: { borderRadius: 16, padding: 18, borderWidth: 1.5, gap: 8 },
177     typeTag: { alignSelf: 'flex-start', borderRadius: 6, paddingHorizontal: 10, paddingVertical: 4 },
178     typeTagText: { fontSize: 10, fontFamily: 'Inter_700Bold', color: '#FFF', letterSpacing: 1 },
179     heroTitle: { fontSize: 20, fontFamily: 'Inter_700Bold' },
180     heroDesc: { fontSize: 13, fontFamily: 'Inter_400Regular', lineHeight: 20 },
181     heroMetaRow: { flexDirection: 'row', flexWrap: 'wrap', gap: 8 },
182     metaPill: { flexDirection: 'row', alignItems: 'center', gap: 4 },
183     metaText: { fontSize: 12, fontFamily: 'Inter_400Regular' },
184     sectionLabel: { fontSize: 15, fontFamily: 'Inter_700Bold' },
185     dayCard: { borderRadius: 12, borderWidth: 1.5, overflow: 'hidden' },
186     dayHeader: { flexDirection: 'row', alignItems: 'center', gap: 12, padding: 14 },
187     dayNumber: { width: 32, height: 32, borderRadius: 16, alignItems: 'center', justifyContent: 'center' },
188     dayNumberText: { fontSize: 14, fontFamily: 'Inter_700Bold', color: '#FFF' },
189     dayName: { fontSize: 15, fontFamily: 'Inter_600SemiBold' },
190     dayFocus: { fontSize: 12, fontFamily: 'Inter_500Medium', marginTop: 1 },
191     exerciseCount: {},
192     exerciseCountText: { fontSize: 11, fontFamily: 'Inter_400Regular' },
193     exerciseList: { borderTopWidth: 1 },
194     exerciseItem: { flexDirection: 'row', gap: 12, padding: 14, borderBottomWidth: 1, alignItems: 'flex-
start' },
195     exerciseBullet: { width: 6, height: 6, borderRadius: 3, marginTop: 6 },
196     exerciseName: { fontSize: 14, fontFamily: 'Inter_500Medium' },
197     exerciseTarget: { fontSize: 13, fontFamily: 'Inter_600SemiBold', marginTop: 2 },
198     exerciseNotes: { fontSize: 12, fontFamily: 'Inter_400Regular', marginTop: 2, fontStyle: 'italic' },
199 });
200

```

```

1  import React, { useState } from 'react';
2  import {
3    View, Text, StyleSheet, ScrollView, TouchableOpacity, TextInput,
4    Platform, ActivityIndicator,
5  } from 'react-native';
6  import { useSafeAreaInsets } from 'react-native-safe-area-context';
7  import { router } from 'expo-router';
8  import { Feather } from '@expo/vector-icons';
9  import * as Haptics from 'expo-haptics';
10 import { useColors } from '@hooks/useColors';
11 import { useAuth } from '@context/AuthContext';
12 import { showAlert } from '@lib/alert';
13 import { addPTPlan, addNotification, genId } from '@lib/storage';
14 import type { PTPlan, PTPlanDay, PTEExercise } from '@lib/types';
15
16 const DAYS = ['Saturday', 'Sunday', 'Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday'];
17
18 interface ExerciseForm {
19   name: string;
20   target: string;
21   notes: string;
22 }
23
24 interface DayForm {
25   focus: string;
26   exercises: ExerciseForm[];
27 }
28
29 export default function NewPlanScreen() {
30   const colors = useColors();
31   const insets = useSafeAreaInsets();
32   const { user } = useAuth();
33   const isWeb = Platform.OS === 'web';
34
35   const [title, setTitle] = useState('');
36   const [type, setType] = useState<'fit' | 'unfit'>('fit');
37   const [description, setDescription] = useState('');
38   const [weekNumber, setWeekNumber] = useState('');
39   const [days, setDays] = useState<DayForm[]>(
40     DAYS.map(() => ({ focus: '', exercises: [{ name: '', target: '', notes: '' }] })))
41   );
42   const [isSaving, setIsSaving] = useState(false);
43
44   const updateDay = (di: number, field: keyof DayForm, value: string) => {
45     setDays(prev => prev.map((d, i) => i === di ? { ...d, [field]: value } : d));
46   };
47
48   const updateExercise = (di: number, ei: number, field: keyof ExerciseForm, value: string) => {
49     setDays(prev => prev.map((d, i) => {
50       if (i !== di) return d;
51       return { ...d, exercises: d.exercises.map((e, j) => j === ei ? { ...e, [field]: value } : e) };
52     }));
53   };
54
55   const addExercise = (di: number) => {
56     setDays(prev => prev.map((d, i) => i === di ? { ...d, exercises: [...d.exercises, { name: '', target:
57   '', notes: '' }] } : d));
58   };
59
60   const removeExercise = (di: number, ei: number) => {
61     setDays(prev => prev.map((d, i) => {
62       if (i !== di || d.exercises.length <= 1) return d;
63       return { ...d, exercises: d.exercises.filter((_, j) => j !== ei) };
64     }));
65   };
66
67   const handleSave = async () => {
68     if (!title.trim()) { showAlert('Error', 'Plan title is required.');
```

```

82     if (planDays.length === 0) { showAlert('Error', 'Add at least one exercise.');
```

```

return; }
83
84     const plan: PTPlan = {
85         id: genId(), title: title.trim(), type, description: description.trim(),
86         createdBy: user!.id, createdByName: user!.name,
87         weekNumber: Number(weekNumber), days: planDays,
88         createdAt: new Date().toISOString(),
89     };
90     await addPTPlan(plan);
91     await addNotification({
92         id: genId(), title: 'New PT Plan Published',
93         body: `Week ${weekNumber} ${type === 'fit' ? 'Fit' : 'Rehabilitation'} PT Plan has been published.`,
94         type: 'new_plan', read: false, createdAt: new Date().toISOString(),
95     });
96     setIsSaving(false);
97     Haptics.notificationAsync(Haptics.NotificationFeedbackType.Success);
98     showAlert('Success', 'PT Plan created and published!', [{ text: 'OK', onPress: () => router.back() }]);
99 };
100
101     const paddingTop = (isWeb ? 67 : 0) + insets.top + 16;
102     const paddingBottom = isWeb ? 34 : insets.bottom + 24;
103
104     return (
105         <ScrollView style={[styles.root, { backgroundColor: colors.background }]}
106             contentContainerStyle={[styles.content, { paddingTop, paddingBottom }]}
107             keyboardShouldPersistTaps="handled">
108             <TouchableOpacity onPress={() => router.back()} style={styles.backBtn}>
109                 <Feather name="x" size={20} color={colors.foreground} />
110                 <Text style={[styles.backText, { color: colors.foreground }]}>Cancel</Text>
111             </TouchableOpacity>
112
113             <Text style={[styles.screenTitle, { color: colors.foreground }]}>Create PT Plan</Text>
114
115             <View style={[styles.card, { backgroundColor: colors.card, borderColor: colors.border }]}>
116                 <Text style={[styles.fieldLabel, { color: colors.mutedForeground }]}>PLAN TYPE</Text>
117                 <View style={styles.typeRow}>
118                     {[['fit', 'unfit'] as const}.map(t => (
119                         <TouchableOpacity key={t} style={[styles.typeBtn, { backgroundColor: type === t ? (t ===
'fit' ? colors.success : colors.warning) : colors.muted }]}
120                             onPress={() => setType(t)} activeOpacity={0.75}>
121                             <Text style={[styles.typeBtnText, { color: type === t ? '#FFF' : colors.mutedForeground }]}>
122                                 {t === 'fit' ? 'FIT' : 'REHABILITATION'}
123                             </Text>
124                         </TouchableOpacity>
125                     ))}
126                 </View>
127
128                 <Text style={[styles.fieldLabel, { color: colors.mutedForeground }]}>TITLE</Text>
129                 <TextInput style={[styles.input, { borderColor: colors.border, color: colors.foreground,
backgroundColor: colors.background }]}
130                     value={title} onChangeText={setTitle} placeholder="e.g. Week 30 Fitness Plan"
131                     placeholderTextColor={colors.mutedForeground} />
132                 <Text style={[styles.fieldLabel, { color: colors.mutedForeground }]}>WEEK NUMBER</Text>
133                 <TextInput style={[styles.input, { borderColor: colors.border, color: colors.foreground,
backgroundColor: colors.background }]}
134                     value={weekNumber} onChangeText={setWeekNumber} placeholder="e.g. 30"
135                     placeholderTextColor={colors.mutedForeground}
136                     keyboardType="numeric" />
137                 <Text style={[styles.fieldLabel, { color: colors.mutedForeground }]}>DESCRIPTION</Text>
138                 <TextInput style={[styles.input, { borderColor: colors.border, color: colors.foreground,
backgroundColor: colors.background, height: 80, textAlignVertical: 'top' }]}
139                     value={description} onChangeText={setDescription} placeholder="Brief description..."
140                     placeholderTextColor={colors.mutedForeground} multiline />
141             </View>
142
143             <Text style={[styles.daysTitle, { color: colors.foreground }]}>Daily Schedule</Text>
144
145             {DAYS.map((dayName, di) => {
146                 const day = days[di];
147                 return (
148                     <View key={dayName} style={[styles.dayCard, { backgroundColor: colors.card, borderColor:
colors.border }]}>
149                         <Text style={[styles.dayTitle, { color: colors.foreground }]}>{dayName}</Text>
150                         <TextInput
151                             style={[styles.input, { borderColor: colors.border, color: colors.foreground,
backgroundColor: colors.background }]}
152                             value={day.focus} onChangeText={v => updateDay(di, 'focus', v)}
153                             placeholder="Focus (e.g. Cardio, Strength...)" placeholderTextColor={colors.mutedForeground}
154                             />
155                         {day.exercises.map((ex, ei) => (
156                             <View key={ei} style={[styles.exerciseBlock, { borderColor: colors.border }]}>

```

```

157         <Text style={[styles.exerciseBlockTitle, { color: colors.mutedForeground }]}>Exercise {ei
+ 1}</Text>
158         {day.exercises.length > 1 && (
159             <TouchableOpacity onPress={() => removeExercise(di, ei)}>
160                 <Feather name="minus-circle" size={16} color={colors.destructive} />
161             </TouchableOpacity>
162         )}
163     </View>
164     <TextInput style={[styles.input, { borderColor: colors.border, color: colors.foreground,
backgroundColor: colors.background }]}
165         value={ex.name} onChangeText={v => updateExercise(di, ei, 'name', v)}
placeholder="Exercise name" placeholderTextColor={colors.mutedForeground} />
166     <TextInput style={[styles.input, { borderColor: colors.border, color: colors.foreground,
backgroundColor: colors.background }]}
167         value={ex.target} onChangeText={v => updateExercise(di, ei, 'target', v)}
placeholder="Target (e.g. 3 sets x 20 reps)" placeholderTextColor={colors.mutedForeground} />
168     <TextInput style={[styles.input, { borderColor: colors.border, color: colors.foreground,
backgroundColor: colors.background }]}
169         value={ex.notes} onChangeText={v => updateExercise(di, ei, 'notes', v)}
placeholder="Notes (optional)" placeholderTextColor={colors.mutedForeground} />
170     </View>
171     )}
172     <TouchableOpacity style={[styles.addExBtn, { borderColor: colors.primary }]} onPress={() =>
addExercise(di)}>
173         <Feather name="plus" size={14} color={colors.primary} />
174         <Text style={[styles.addExText, { color: colors.primary }]}>Add Exercise</Text>
175     </TouchableOpacity>
176 </View>
177 );
178 }}}
179
180 <TouchableOpacity style={[styles.saveBtn, { backgroundColor: colors.primary }, isSaving && { opacity:
0.7 }]}
181     onPress={handleSave} disabled={isSaving} activeOpacity={0.85}>
182     {isSaving ? <ActivityIndicator color="#FFF" /> : (
183         <>
184             <Feather name="check-circle" size={20} color="#FFF" />
185             <Text style={styles.saveBtnText}>Publish PT Plan</Text>
186         </>
187     )}
188 </TouchableOpacity>
189 </ScrollView>
190 );
191 }
192
193 const styles = StyleSheet.create({
194     root: { flex: 1 },
195     content: { paddingHorizontal: 16, gap: 14 },
196     backBtn: { flexDirection: 'row', alignItems: 'center', gap: 6 },
197     backText: { fontSize: 15, fontFamily: 'Inter_500Medium' },
198     screenTitle: { fontSize: 24, fontFamily: 'Inter_700Bold' },
199     card: { borderRadius: 14, borderWidth: 1, padding: 16, gap: 10 },
200     fieldLabel: { fontSize: 11, fontFamily: 'Inter_600SemiBold', letterSpacing: 1.2 },
201     typeRow: { flexDirection: 'row', gap: 10 },
202     typeBtn: { flex: 1, borderRadius: 8, paddingVertical: 10, alignItems: 'center' },
203     typeBtnText: { fontSize: 12, fontFamily: 'Inter_700Bold', letterSpacing: 0.5 },
204     input: { borderWidth: 1, borderRadius: 8, padding: 12, fontSize: 14, fontFamily: 'Inter_400Regular' },
205     daysTitle: { fontSize: 16, fontFamily: 'Inter_700Bold' },
206     dayCard: { borderRadius: 14, borderWidth: 1, padding: 14, gap: 10 },
207     dayTitle: { fontSize: 15, fontFamily: 'Inter_700Bold' },
208     exerciseBlock: { borderWidth: 1, borderRadius: 10, padding: 12, gap: 8 },
209     exerciseBlockHeader: { flexDirection: 'row', alignItems: 'center', justifyContent: 'space-between' },
210     exerciseBlockTitle: { fontSize: 12, fontFamily: 'Inter_500Medium' },
211     addExBtn: { flexDirection: 'row', alignItems: 'center', justifyContent: 'center', gap: 6, borderWidth: 1,
borderRadius: 8, paddingVertical: 9, borderStyle: 'dashed' },
212     addExText: { fontSize: 13, fontFamily: 'Inter_500Medium' },
213     saveBtn: { flexDirection: 'row', alignItems: 'center', justifyContent: 'center', gap: 8, borderRadius:
12, paddingVertical: 16 },
214     saveBtnText: { fontSize: 16, fontFamily: 'Inter_700Bold', color: '#FFF' },
215 });
216

```

```

1  import React, { useState, useEffect, useCallback } from 'react';
2  import {
3    View, Text, StyleSheet, ScrollView, TouchableOpacity, TextInput,
4    Platform, ActivityIndicator, FlatList,
5  } from 'react-native';
6  import { useSafeAreaInsets } from 'react-native-safe-area-context';
7  import { router } from 'expo-router';
8  import { Feather, MaterialCommunityIcons } from '@expo/vector-icons';
9  import * as Haptics from 'expo-haptics';
10 import { useColors } from '@/hooks/useColors';
11 import { useAuth } from '@/context/AuthContext';
12 import { showAlert } from '@/lib/alert';
13 import { getSoldiers, addIPFTResult, updateSoldier, addNotification, calcBMI, genId } from '@/lib/storage';
14 import type { Soldier, IPFTResult, IPFTResultItem } from '@/lib/types';
15
16 /**
17  * Pass/fail for every item is now a direct choice by the clerk instead of
18  * something parsed out of free text (e.g. "8:20" for a run time). The old
19  * version tried to parse the run fields as MM:SS and silently marked the
20  * item FAIL whenever that parse didn't match, which is why runs always came
21  * back failed regardless of what was typed. Recording it as an explicit tap
22  * also matches how these items are actually graded on the ground – pass/fail
23  * per obstacle/event, not a formula.
24  */
25 const DEFAULT_ITEMS = [
26   { name: '1.6km Run', target: '< 9 min' },
27   { name: '3.2km Run', target: '< 24 min' },
28   { name: 'Push-ups', target: '"e 35 reps/2min' },
29   { name: 'Sit-ups', target: '"e 30 reps/2min' },
30   { name: 'Pull-ups', target: '"e 6 reps' },
31   { name: 'Swimming', target: 'Complete the swimming test' },
32   { name: 'Beam', target: 'Cross the beam' },
33   { name: 'Knee Bending', target: 'Complete knee bending' },
34   { name: 'Horizontal Rope', target: 'Cross the horizontal rope' },
35   { name: 'Fireman's Lift', target: 'Complete fireman's carry' },
36   { name: 'Wall', target: 'Clear the wall obstacle' },
37 ];
38
39 type Grade = 'pass' | 'fail' | null;
40
41 export default function NewResultScreen() {
42   const colors = useColors();
43   const insets = useSafeAreaInsets();
44   const { user } = useAuth();
45   const isWeb = Platform.OS === 'web';
46
47   const [soldiers, setSoldiers] = useState<Soldier[]>([]);
48   const [selectedSoldier, setSelectedSoldier] = useState<Soldier | null>(null);
49   const [searchSoldier, setSearchSoldier] = useState('');
50   const [showPicker, setShowPicker] = useState(false);
51   const [date, setDate] = useState(new Date().toISOString().slice(0, 10));
52   const [achieved, setAchieved] = useState<string[]>(DEFAULT_ITEMS.map(() => ''));
53   const [grades, setGrades] = useState<Grade[]>(DEFAULT_ITEMS.map(() => null));
54   const [isSaving, setIsSaving] = useState(false);
55
56   const load = useCallback(async () => {
57     const all = await getSoldiers();
58     setSoldiers(all.filter(s => s.isApproved));
59   }, []);
60
61   useEffect(() => { load(); }, [load]);
62
63   const filteredSoldiers = searchSoldier.trim()
64     ? soldiers.filter(s => s.name.toLowerCase().includes(searchSoldier.toLowerCase()) ||
65       s.serviceNumber.toLowerCase().includes(searchSoldier.toLowerCase()))
66     : soldiers;
67
68   const gradedCount = grades.filter(g => g !== null).length;
69   const overallPass = gradedCount > 0 && grades.every(g => g === null || g === 'pass');
70
71   const handleSave = async () => {
72     if (!selectedSoldier) { showAlert('Error', 'Please select a soldier.');
```

```

83         achieved: achieved[i].trim() || (grades[i] === 'pass' ? 'Pass' : 'Fail'),
84         status: grades[i] as 'pass' | 'fail',
85     }));
86     const overallStatus: 'pass' | 'fail' = overallPass ? 'pass' : 'fail';
87     const failedNames = items.filter(it => it.status === 'fail').map(it => it.name);
88     const bmi = calcBMI(selectedSoldier.weight, selectedSoldier.height);
89     const isOverweight = bmi > 25;
90
91     const result: IPFTResult = {
92         id: genId(), soldierId: selectedSoldier.id, soldierName: selectedSoldier.name,
93         soldierRank: selectedSoldier.rank, serviceNumber: selectedSoldier.serviceNumber,
94         company: selectedSoldier.company, date, items, overallStatus,
95         recordedBy: user!.id, recordedByName: user!.name, bmi,
96     };
97     // Previous results for this soldier are never overwritten – addIPFTResult
98     // adds this as a new record, so their full IPFT history stays on their profile.
99     await addIPFTResult(result);
100    await updateSoldier(selectedSoldier.id, {
101        ptStatus: overallStatus === 'pass' ? 'fit' : 'unfit',
102        isOverweight,
103    });
104
105    const planNote = overallStatus === 'pass'
106        ? 'You have been declared FIT.'
107        : `You have been declared UNFIT and assigned the Unfit/Rehabilitation PT plan.${failedNames.length ? '
Weak in: ${failedNames.join(', ')}.' : ''}`;
108    await addNotification({
109        id: genId(), targetUserId: selectedSoldier.userId,
110        title: `IPFT Result: ${overallStatus.toUpperCase()}`,
111        body: `Your IPFT result on ${date} is ${overallStatus.toUpperCase()}.${planNote}${isOverweight ? '
You are classified as overweight (BMI: ' + bmi + ').': ''}`,
112        type: 'new_result', read: false, createdAt: new Date().toISOString(),
113    });
114    if (isOverweight) {
115        await addNotification({
116            id: genId(), targetCompany: selectedSoldier.company,
117            title: 'Overweight Soldier Alert',
118            body: `${selectedSoldier.rank} ${selectedSoldier.name} (${selectedSoldier.serviceNumber}) is
overweight. BMI: ${bmi}.`,
119            type: 'overweight', read: false, createdAt: new Date().toISOString(),
120        });
121    }
122
123    setIsSaving(false);
124    Haptics.notificationAsync(Haptics.NotificationFeedbackType.Success);
125    showAlert('Saved', `IPFT result recorded. Status: ${overallStatus.toUpperCase()}`, [{ text: 'OK',
onPress: () => router.back() }]);
126    };
127
128    const paddingTop = (isWeb ? 67 : 0) + insets.top + 16;
129    const paddingBottom = isWeb ? 34 : insets.bottom + 24;
130
131    return (
132        <ScrollView style={[styles.root, { backgroundColor: colors.background }]}
133        <View style={[styles.card, { backgroundColor: colors.card, borderColor: colors.border }]}>
134            <Text style={[styles.fieldLabel, { color: colors.mutedForeground }]}>SOLDIER</Text>
135            <TouchableOpacity style={[styles.pickerBtn, { borderColor: colors.border, backgroundColor:
colors.background }]}
136                onPress={() => setShowPicker(true)} activeOpacity={0.75}>
137                <View style={styles.pickerSelected}>
138                    <View style={[styles.pickerAvatar, { backgroundColor: colors.primary + '20' }]}>
139                        <Text style={[styles.pickerAvatarText, { color: colors.primary }]}>
140                            {selectedSoldier.name.slice(0, 2).toUpperCase()}</Text>
141                        </View>
142                        <View>
143                            <Text style={[styles.pickerName, { color: colors.foreground }]}>{selectedSoldier.rank}
{selectedSoldier.name}</Text>
144                            <Text style={[styles.pickerMeta, { color: colors.mutedForeground }]}>
145                                {selectedSoldier.serviceNumber} · {selectedSoldier.company} Coy</Text>
146                        </View>
147                    </View>
148                ) : (
149                    <Text style={[styles.pickerPlaceholder, { color: colors.mutedForeground }]}>Select soldier...</
Text>
150                )
151            )
152        )
153    )
154
155    )
156
157    )
158

```

```

159         <Feather name="chevron-down" size={18} color={colors.mutedForeground} />
160     </TouchableOpacity>
161 </View>
162
163     {showPicker && (
164         <View style={[styles.pickerDropdown, { backgroundColor: colors.card, borderColor: colors.border }]}>
165             <TextInput style={[styles.searchInput, { borderColor: colors.border, color: colors.foreground,
backgroundColor: colors.background }]}
166                 value={searchSoldier} onChangeText={setSearchSoldier} placeholder="Search..."
placeholderTextColor={colors.mutedForeground} />
167             <FlatList
168                 data={filteredSoldiers} keyExtractor={i => i.id} style={{ maxHeight: 200 }}
169                 renderItem={({ item }) => (
170                     <TouchableOpacity style={[styles.pickerItem, { borderBottomColor: colors.border }]}
171                         onPress={() => { setSelectedSoldier(item); setShowPicker(false); setSearchSoldier(''); }}
activeOpacity={0.75}>
172                         <Text style={[styles.pickerItemName, { color: colors.foreground }]}>{item.rank} {item.name}</Text>
173                         <Text style={[styles.pickerItemMeta, { color: colors.mutedForeground }]}
>{item.serviceNumber} · {item.company}</Text>
174                     </TouchableOpacity>
175                 )}
176             />
177         </View>
178     )}
179
180     <View style={[styles.card, { backgroundColor: colors.card, borderColor: colors.border }]}>
181         <Text style={[styles.fieldLabel, { color: colors.mutedForeground }]}>DATE (YYYY-MM-DD)</Text>
182         <TextInput style={[styles.input, { borderColor: colors.border, color: colors.foreground,
backgroundColor: colors.background }]}
183             value={date} onChangeText={setDate} placeholder="2026-07-28"
placeholderTextColor={colors.mutedForeground} />
184     </View>
185
186     <View style={[styles.card, { backgroundColor: colors.card, borderColor: colors.border }]}>
187         <Text style={[styles.sectionTitle, { color: colors.foreground }]}>IPFT Results</Text>
188         <Text style={[styles.sectionHint, { color: colors.mutedForeground }]}>Mark each item Pass or Fail.
Notes are optional.</Text>
189         {DEFAULT_ITEMS.map((item, i) => {
190             const grade = grades[i];
191             return (
192                 <View key={item.name} style={[styles.resultRow, { borderColor: grade === 'pass' ?
colors.success : grade === 'fail' ? colors.destructive : colors.border }]}>
193                     <View style={styles.resultRowHeader}>
194                         <Text style={[styles.resultName, { color: colors.foreground }]}>{item.name}</Text>
195                         <Text style={[styles.resultTarget, { color: colors.mutedForeground }]}>Target: {item.target}</Text>
196                     </View>
197                     <View style={styles.gradeRow}>
198                         <TouchableOpacity
199                             style={[styles.gradeBtn, { borderColor: colors.success, backgroundColor: grade ===
'pass' ? colors.success : 'transparent' }]}
200                             onPress={() => { const g = [...grades]; g[i] = 'pass'; setGrades(g);
Haptics.selectionAsync(); }}
201                             activeOpacity={0.8}
202                         >
203                             <MaterialCommunityIcons name="check-circle" size={16} color={grade === 'pass' ? '#FFF' :
colors.success} />
204                             <Text style={[styles.gradeBtnText, { color: grade === 'pass' ? '#FFF' : colors.success }]}
>PASS</Text>
205                         </TouchableOpacity>
206                         <TouchableOpacity
207                             style={[styles.gradeBtn, { borderColor: colors.destructive, backgroundColor: grade ===
'fail' ? colors.destructive : 'transparent' }]}
208                             onPress={() => { const g = [...grades]; g[i] = 'fail'; setGrades(g);
Haptics.selectionAsync(); }}
209                             activeOpacity={0.8}
210                         >
211                             <MaterialCommunityIcons name="close-circle" size={16} color={grade === 'fail' ? '#FFF' :
colors.destructive} />
212                             <Text style={[styles.gradeBtnText, { color: grade === 'fail' ? '#FFF' :
colors.destructive }]}>FAIL</Text>
213                         </TouchableOpacity>
214                     </View>
215                     <TextInput
216                         style={[styles.resultInput, { borderColor: colors.border, color: colors.foreground,
backgroundColor: colors.background }]}
217                         value={achieved[i]} onChangeText={v => { const a = [...achieved]; a[i] = v;
setAchieved(a); }}
218                         placeholder={item.name.includes('Run') ? 'Note (optional), e.g. 8:20' : 'Note (optional),
e.g. 40 reps'}
219                         placeholderTextColor={colors.mutedForeground}
220                     />
221                 </View>
222             );

```

```

223     }}}
224 </View>
225
226     {selectedSoldier && gradedCount > 0 && (
227         <View style={[styles.previewCard, {
228             backgroundColor: overallPass ? colors.success + '10' : colors.destructive + '10',
229             borderColor: overallPass ? colors.success : colors.destructive,
230         }]}>
231             <Text style={[styles.previewTitle, { color: overallPass ? colors.success : colors.destructive }]}>
232                 Overall: {overallPass ? 'PASS' : 'FAIL'}
233             </Text>
234             <Text style={[styles.previewSub, { color: colors.mutedForeground }]}>{gradedCount} of
235 {DEFAULT_ITEMS.length} items graded</Text>
236         </View>
237     )}
238     <TouchableOpacity style={[styles.saveBtn, { backgroundColor: colors.primary }, isSaving && { opacity:
0.7 }]}
239         onPress={handleSave} disabled={isSaving} activeOpacity={0.85}>
240         {isSaving ? <ActivityIndicator color="#FFF" /> : (
241             <>
242                 <Feather name="save" size={20} color="#FFF" />
243                 <Text style={styles.saveBtnText}>Save Result</Text>
244             </>
245         )}
246     </TouchableOpacity>
247 </ScrollView>
248 );
249 }
250
251 const styles = StyleSheet.create({
252     root: { flex: 1 },
253     content: { paddingHorizontal: 16, gap: 14 },
254     backBtn: { flexDirection: 'row', alignItems: 'center', gap: 6 },
255     backText: { fontSize: 15, fontFamily: 'Inter_500Medium' },
256     screenTitle: { fontSize: 24, fontFamily: 'Inter_700Bold' },
257     card: { borderRadius: 14, borderWidth: 1, padding: 16, gap: 10 },
258     fieldLabel: { fontSize: 11, fontFamily: 'Inter_600SemiBold', letterSpacing: 1.2 },
259     input: { borderWidth: 1, borderRadius: 8, padding: 12, fontSize: 14, fontFamily: 'Inter_400Regular' },
260     pickerBtn: { flexDirection: 'row', alignItems: 'center', justifyContent: 'space-between', borderWidth: 1,
borderRadius: 10, padding: 12 },
261     pickerSelected: { flexDirection: 'row', alignItems: 'center', gap: 10 },
262     pickerAvatar: { width: 36, height: 36, borderRadius: 18, alignItems: 'center', justifyContent: 'center' },
263     pickerAvatarText: { fontSize: 12, fontFamily: 'Inter_700Bold' },
264     pickerName: { fontSize: 14, fontFamily: 'Inter_600SemiBold' },
265     pickerMeta: { fontSize: 11, fontFamily: 'Inter_400Regular' },
266     pickerPlaceholder: { fontSize: 14, fontFamily: 'Inter_400Regular' },
267     pickerDropdown: { borderRadius: 12, borderWidth: 1, overflow: 'hidden' },
268     searchInput: { borderWidth: 1, borderRadius: 0, padding: 12, fontSize: 14, fontFamily:
'Inter_400Regular' },
269     pickerItem: { padding: 14, borderBottomWidth: 1 },
270     pickerItemName: { fontSize: 14, fontFamily: 'Inter_500Medium' },
271     pickerItemMeta: { fontSize: 12, fontFamily: 'Inter_400Regular', marginTop: 2 },
272     sectionTitle: { fontSize: 15, fontFamily: 'Inter_700Bold' },
273     sectionHint: { fontSize: 12, fontFamily: 'Inter_400Regular', marginTop: -6 },
274     resultRow: { borderRadius: 10, borderWidth: 1.5, padding: 12, gap: 8 },
275     resultRowHeader: {},
276     resultName: { fontSize: 14, fontFamily: 'Inter_600SemiBold' },
277     resultTarget: { fontSize: 12, fontFamily: 'Inter_400Regular', marginTop: 1 },
278     gradeRow: { flexDirection: 'row', gap: 8 },
279     gradeBtn: { flex: 1, flexDirection: 'row', alignItems: 'center', justifyContent: 'center', gap: 6,
borderWidth: 1.5, borderRadius: 8, paddingVertical: 9 },
280     gradeBtnText: { fontSize: 12, fontFamily: 'Inter_700Bold', letterSpacing: 0.5 },
281     resultInput: { borderWidth: 1, borderRadius: 8, padding: 10, fontSize: 13, fontFamily:
'Inter_400Regular' },
282     previewCard: { borderRadius: 12, borderWidth: 2, padding: 16, alignItems: 'center', gap: 4 },
283     previewTitle: { fontSize: 18, fontFamily: 'Inter_700Bold', letterSpacing: 2 },
284     previewSub: { fontSize: 12, fontFamily: 'Inter_400Regular' },
285     saveBtn: { flexDirection: 'row', alignItems: 'center', justifyContent: 'center', gap: 8, borderRadius:
12, paddingVertical: 16 },
286     saveBtnText: { fontSize: 16, fontFamily: 'Inter_700Bold', color: '#FFF' },
287 });
288

```

app/soldier/[id].tsx

```
1  import React, { useState, useEffect } from 'react';
2  import { View, Text, StyleSheet, ScrollView, TouchableOpacity, Platform, ActivityIndicator } from 'react-native';
3  import { useSafeAreaInsets } from 'react-native-safe-area-context';
4  import { useLocalSearchParams, router } from 'expo-router';
5  import { Feather, MaterialCommunityIcons } from '@expo/vector-icons';
6  import { useColors } from '@hooks/useColors';
7  import { getSoldierById, getIPFTResultsBySoldier, calcBMI } from '@lib/storage';
8  import type { Soldier, IPFTResult } from '@lib/types';
9
10 export default function SoldierDetailScreen() {
11   const colors = useColors();
12   const insets = useSafeAreaInsets();
13   const { id } = useLocalSearchParams<{ id: string }>();
14   const isWeb = Platform.OS === 'web';
15
16   const [soldier, setSoldier] = useState<Soldier | null>(null);
17   const [results, setResults] = useState<IPFTResult[]>([]);
18   const [loading, setLoading] = useState(true);
19
20   useEffect(() => {
21     (async () => {
22       if (!id) return;
23       const [s, r] = await Promise.all([getSoldierById(id), getIPFTResultsBySoldier(id)]);
24       setSoldier(s);
25       setResults(r);
26       setLoading(false);
27     })();
28   }, [id]);
29
30   if (loading) return <View style={[styles.center, { backgroundColor: colors.background }]}
><ActivityIndicator size="large" color={colors.primary} /></View>;
31   if (!soldier) return <View style={[styles.center, { backgroundColor: colors.background }]}><Text
style={{ color: colors.mutedForeground }}>Soldier not found</Text></View>;
32
33   const bmi = calcBMI(soldier.weight, soldier.height);
34   const bmiStatus = bmi < 18.5 ? 'Underweight' : bmi < 25 ? 'Normal' : bmi < 30 ? 'Overweight' : 'Obese';
35   const bmiColor = bmi < 25 ? colors.success : bmi < 30 ? colors.warning : colors.destructive;
36   const ptColor = soldier.ptStatus === 'fit' ? colors.success : soldier.ptStatus === 'unfit' ?
colors.destructive : colors.muted;
37
38   const paddingTop = (isWeb ? 67 : 0) + insets.top + 16;
39   const paddingBottom = isWeb ? 34 : insets.bottom + 20;
40
41   return (
42     <ScrollView style={[styles.root, { backgroundColor: colors.background }]}
43       contentContainerStyle={[styles.content, { paddingTop, paddingBottom }]}>
44       <TouchableOpacity onPress={() => router.back()} style={styles.backBtn}>
45         <Feather name="arrow-left" size={20} color={colors.foreground} />
46         <Text style={[styles.backText, { color: colors.foreground }]}>Back</Text>
47       </TouchableOpacity>
48
49       <View style={[styles.heroCard, { backgroundColor: colors.primary }]}>
50         <View style={styles.heroAvatar}>
51           <Text style={styles.heroAvatarText}>{soldier.name.split(' ').map(n => n[0]).join('').slice(0, 2)}
52         </View>
53         <Text style={styles.heroName}>{soldier.rank} {soldier.name}</Text>
54         <Text style={styles.heroService}>{soldier.serviceNumber}</Text>
55         <View style={styles.heroBadgesRow}>
56           <View style={[styles.heroBadge, { backgroundColor: ptColor }]}>
57             <Text style={styles.heroBadgeText}>{soldier.ptStatus.toUpperCase()}</Text>
58           </View>
59           <View style={styles.heroBadge}>
60             <Text style={styles.heroBadgeText}>{soldier.company} Company</Text>
61           </View>
62           {soldier.isOverweight && (
63             <View style={[styles.heroBadge, { backgroundColor: colors.warning }]}>
64               <MaterialCommunityIcons name="alert" size={10} color="#FFF" />
65               <Text style={styles.heroBadgeText}>OVERWEIGHT</Text>
66             </View>
67           )}
68         </View>
69       </View>
70
71       <View style={[styles.bmiCard, { backgroundColor: colors.card, borderColor: bmiColor }]}>
72         <View>
73           <Text style={[styles.bmiLabel, { color: colors.foreground }]}>BMI</Text>
74           <Text style={[styles.bmiStatus, { color: bmiColor }]}>{bmiStatus}</Text>
75         </View>
76         <Text style={[styles.bmiBig, { color: bmiColor }]}>{bmi}</Text>
77       </View>
78     )
  }
```

```

79     <View style={[styles.section, { backgroundColor: colors.card, borderColor: colors.border }]}>
80       <Text style={[styles.sectionTitle, { color: colors.foreground }]}>Personal Details</Text>
81       [[
82         { icon: 'email-outline', label: 'Email', value: soldier.email },
83         { icon: 'phone-outline', label: 'Phone', value: soldier.phone },
84         { icon: 'water', label: 'Blood Group', value: soldier.bloodGroup },
85         { icon: 'medical-bag', label: 'Medical Category', value: soldier.medicalCategory },
86         { icon: 'cake-variant', label: 'Age', value: `${soldier.age} years` },
87         { icon: 'human-male-height', label: 'Height', value: `${soldier.height} cm` },
88         { icon: 'weight-kilogram', label: 'Weight', value: `${soldier.weight} kg` },
89         ...(soldier.address ? [{ icon: 'map-marker-outline', label: 'Address', value:
soldier.address }] : []),
90       ].map(({ icon, label, value }) => (
91         <View key={label} style={[styles.infoRow, { borderBottomColor: colors.border }]}>
92           <View style={styles.infoLeft}>
93             <MaterialCommunityIcons name={icon as any} size={16} color={colors.mutedForeground} />
94             <Text style={[styles.infoLabel, { color: colors.mutedForeground }]}>{label}</Text>
95           </View>
96           <Text style={[styles.infoValue, { color: colors.foreground }]}>{value}</Text>
97         </View>
98       )])
99     </View>
100
101     <Text style={[styles.historyTitle, { color: colors.foreground }]}>IPFT History ({results.length}
records)</Text>
102     {results.length === 0 ? (
103       <View style={[styles.emptyHistory, { backgroundColor: colors.card, borderColor: colors.border }]}>
104         <Feather name="clipboard" size={32} color={colors.border} />
105         <Text style={[styles.emptyHistoryText, { color: colors.mutedForeground }]}>No IPFT results
recorded</Text>
106       </View>
107     ) : (
108       results.map(result => (
109         <View key={result.id} style={[styles.resultCard, { backgroundColor: result.overallStatus ===
'pass' ? colors.success + '08' : colors.destructive + '08', borderColor: result.overallStatus === 'pass' ?
colors.success : colors.destructive }]}>
110           <View style={styles.resultHeader}>
111             <Text style={[styles.resultDate, { color: colors.foreground }]}>{result.date}</Text>
112             <View style={styles.resultBadgeRow}>
113               {result.biannual && (
114                 <View style={[styles.biannualBadge, { borderColor: colors.border }]}>
115                   <Text style={[styles.biannualBadgeText, { color: colors.mutedForeground }]}
>{result.biannual} Biannual</Text>
116                 </View>
117               )}
118               <View style={[styles.resultBadge, { backgroundColor: result.overallStatus === 'pass' ?
colors.success : colors.destructive }]}>
119                 <Text style={styles.resultBadgeText}>{result.overallStatus.toUpperCase()}</Text>
120               </View>
121             </View>
122             {result.selfReported && <Text style={[styles.selfReportedNote, { color:
colors.mutedForeground }]}>Self-reported at registration (previous unit)</Text>}
124             {result.bmi && <Text style={[styles.resultBmi, { color: colors.mutedForeground }]}>BMI:
{result.bmi}</Text>}
125             {result.items.map((item, i) => (
126               <View key={i} style={styles.resultItem}>
127                 <MaterialCommunityIcons name={item.status === 'pass' ? 'check-circle' : 'close-circle'}
size={16} color={item.status === 'pass' ? colors.success : colors.destructive} />
128                 <View style={{ flex: 1 }}>
129                   <Text style={[styles.resultItemName, { color: colors.foreground }]}>{item.name}</Text>
130                   <Text style={[styles.resultItemMeta, { color: colors.mutedForeground }]}>Achieved:
{item.achieved} · Target: {item.target}</Text>
131                 </View>
132               </View>
133             )])
134             <Text style={[styles.resultBy, { color: colors.mutedForeground }]}>Recorded by
{result.recordedBy}</Text>
135           </View>
136         )}
137       )}
138     </ScrollView>
139   );
140 }
141
142 const styles = StyleSheet.create({
143   root: { flex: 1 },
144   content: { paddingHorizontal: 16, gap: 14 },
145   center: { flex: 1, alignItems: 'center', justifyContent: 'center' },
146   backBtn: { flexDirection: 'row', alignItems: 'center', gap: 6, marginBottom: 8 },
147   backText: { fontSize: 15, fontFamily: 'Inter_500Medium' },
148   heroCard: { borderRadius: 20, padding: 28, alignItems: 'center', gap: 6 },
149   heroAvatar: { width: 72, height: 72, borderRadius: 36, backgroundColor: 'rgba(255,255,255,0.25)',
alignItems: 'center', justifyContent: 'center', marginBottom: 4 },
150   heroAvatarText: { fontSize: 24, fontFamily: 'Inter_700Bold', color: '#FFF' },

```

```

151   heroName: { fontSize: 20, fontFamily: 'Inter_700Bold', color: '#FFF', textAlign: 'center' },
152   heroService: { fontSize: 13, fontFamily: 'Inter_400Regular', color: 'rgba(255,255,255,0.75)' },
153   heroBadgesRow: { flexDirection: 'row', flexWrap: 'wrap', gap: 6, marginTop: 8, justifyContent: 'center' },
154   heroBadge: { flexDirection: 'row', alignItems: 'center', gap: 4, borderRadius: 20, paddingHorizontal: 10,
paddingVertical: 4, backgroundColor: 'rgba(255,255,255,0.2)' },
155   heroBadgeText: { fontSize: 10, fontFamily: 'Inter_700Bold', color: '#FFF', letterSpacing: 0.5 },
156   bmiCard: { flexDirection: 'row', alignItems: 'center', justifyContent: 'space-between', borderRadius: 14,
padding: 16, borderWidth: 2 },
157   bmiLabel: { fontSize: 15, fontFamily: 'Inter_600SemiBold' },
158   bmiStatus: { fontSize: 13, fontFamily: 'Inter_500Medium', marginTop: 2 },
159   bmiBig: { fontSize: 40, fontFamily: 'Inter_700Bold' },
160   section: { borderRadius: 14, borderWidth: 1, overflow: 'hidden' },
161   sectionTitle: { fontSize: 14, fontFamily: 'Inter_700Bold', padding: 14, paddingBottom: 8 },
162   infoRow: { flexDirection: 'row', alignItems: 'center', justifyContent: 'space-between',
paddingHorizontal: 14, paddingVertical: 12, borderBottomWidth: 1 },
163   infoLeft: { flexDirection: 'row', alignItems: 'center', gap: 8 },
164   infoLabel: { fontSize: 13, fontFamily: 'Inter_400Regular' },
165   infoValue: { fontSize: 13, fontFamily: 'Inter_500Medium' },
166   historyTitle: { fontSize: 15, fontFamily: 'Inter_700Bold' },
167   emptyHistory: { borderRadius: 12, borderWidth: 1, padding: 24, alignItems: 'center', gap: 8 },
168   emptyHistoryText: { fontSize: 13, fontFamily: 'Inter_400Regular' },
169   resultCard: { borderRadius: 12, borderWidth: 1.5, padding: 14, gap: 10 },
170   resultHeader: { flexDirection: 'row', alignItems: 'center', justifyContent: 'space-between' },
171   resultDate: { fontSize: 14, fontFamily: 'Inter_600SemiBold' },
172   resultBadgeRow: { flexDirection: 'row', alignItems: 'center', gap: 6 },
173   biannualBadge: { borderRadius: 6, borderWidth: 1, paddingHorizontal: 8, paddingVertical: 4 },
174   biannualBadgeText: { fontSize: 10, fontFamily: 'Inter_600SemiBold' },
175   selfReportedNote: { fontSize: 11, fontFamily: 'Inter_400Regular', fontStyle: 'italic' },
176   resultBadge: { borderRadius: 6, paddingHorizontal: 8, paddingVertical: 4 },
177   resultBadgeText: { fontSize: 10, fontFamily: 'Inter_700Bold', color: '#FFF' },
178   resultBmi: { fontSize: 12, fontFamily: 'Inter_400Regular' },
179   resultItem: { flexDirection: 'row', alignItems: 'flex-start', gap: 8 },
180   resultItemName: { fontSize: 13, fontFamily: 'Inter_500Medium' },
181   resultItemMeta: { fontSize: 12, fontFamily: 'Inter_400Regular', marginTop: 1 },
182   resultBy: { fontSize: 11, fontFamily: 'Inter_400Regular', fontStyle: 'italic' },
183 });
184

```

server/api-server.js

```
1 // Shared data server for Fit Force.
2 //
3 // The app used to store everything (users, soldiers, messages, ...) in
4 // per-device AsyncStorage, so a soldier registering on a phone was
5 // invisible to the Adjutant approving accounts on a laptop, and messages
6 // never reached anyone on a different device. This server holds the one
7 // shared copy of that data so every device reads and writes the same
8 // state, over the same LAN the Expo dev server already uses.
9 //
10 // It exposes a tiny key/value API that mirrors AsyncStorage's own
11 // getItem/setItem shape, so lib/storage.ts only had to change how it reads
12 // and writes a value, not the data model itself. It also exposes a small
13 // file upload/download API so Reports can carry a real PDF/DOC attachment
14 // instead of just a filename label.
15
16 const http = require('http');
17 const fs = require('fs');
18 const path = require('path');
19
20 const {
21   SEED_USERS, SEED_SOLDIERS, SEED_PT_PLANS, SEED_IPFT_RESULTS,
22   SEED_IPFT_SCHEDULE, SEED_NOTIFICATIONS, SEED_REPORTS,
23 } = require('./seed-data');
24 const { renderPlanPdf } = require('./pdf');
25
26 const PORT = 4000;
27 const DATA_FILE = path.join(__dirname, 'data-store.json');
28 const UPLOAD_DIR = path.join(__dirname, 'uploads');
29 const MAX_UPLOAD_BYTES = 15 * 1024 * 1024; // 15MB, comfortably covers a scanned PDF/DOC
30
31 if (!fs.existsSync(UPLOAD_DIR)) fs.mkdirSync(UPLOAD_DIR, { recursive: true });
32
33 const INITIAL_STORE = {
34   'fitforce:users': SEED_USERS,
35   'fitforce:soldiers': SEED_SOLDIERS,
36   'fitforce:pt_plans': SEED_PT_PLANS,
37   'fitforce:ipft_results': SEED_IPFT_RESULTS,
38   'fitforce:ipft_schedule': SEED_IPFT_SCHEDULE,
39   'fitforce:notifications': SEED_NOTIFICATIONS,
40   'fitforce:messages': [],
41   'fitforce:reports': [],
42 };
43
44 function loadStore() {
45   if (fs.existsSync(DATA_FILE)) {
46     try {
47       return JSON.parse(fs.readFileSync(DATA_FILE, 'utf8'));
48     } catch (e) {
49       console.error('Failed to parse data-store.json, reseeding.', e);
50     }
51   }
52   fs.writeFileSync(DATA_FILE, JSON.stringify(INITIAL_STORE, null, 2));
53   return { ...INITIAL_STORE };
54 }
55
56 let store = loadStore();
57 let saveTimer = null;
58
59 function persist() {
60   clearTimeout(saveTimer);
61   saveTimer = setTimeout(() => {
62     fs.writeFile(DATA_FILE, JSON.stringify(store, null, 2), err => {
63       if (err) console.error('Failed to persist data-store.json', err);
64     });
65   }, 150);
66 }
67
68 function setCors(res) {
69   res.setHeader('Access-Control-Allow-Origin', '*');
70   res.setHeader('Access-Control-Allow-Methods', 'GET, PUT, POST, OPTIONS');
71   res.setHeader('Access-Control-Allow-Headers', 'Content-Type');
72 }
73
74 function readJsonBody(req, maxBytes) {
75   return new Promise((resolve, reject) => {
76     let body = '';
77     let bytes = 0;
78     req.on('data', chunk => {
79       bytes += chunk.length;
80       if (maxBytes && bytes > maxBytes) {
81         reject(new Error('Payload too large'));
82         req.destroy();
83       }
84     });
85     return;
86   });
87 }
```

```

84     }
85     body += chunk;
86   });
87   req.on('end', () => {
88     try {
89       resolve(body ? JSON.parse(body) : null);
90     } catch (e) {
91       reject(e);
92     }
93   });
94   req.on('error', reject);
95 });
96 }
97
98 const server = http.createServer(async (req, res) => {
99   setCors(res);
100
101   if (req.method === 'OPTIONS') {
102     res.writeHead(204);
103     res.end();
104     return;
105   }
106
107   const url = new URL(req.url, `http://${req.headers.host}`);
108
109   if (url.pathname === '/health') {
110     res.writeHead(200, { 'Content-Type': 'application/json' });
111     res.end(JSON.stringify({ ok: true }));
112     return;
113   }
114
115   // % % File upload: client sends { name, mimeType, base64 } as JSON % %
116   if (req.method === 'POST' && url.pathname === '/upload') {
117     try {
118       const payload = await readJsonBody(req, MAX_UPLOAD_BYTES * 1.4); // base64 inflates ~33%
119       if (!payload || !payload.base64 || !payload.name) {
120         res.writeHead(400, { 'Content-Type': 'application/json' });
121         res.end(JSON.stringify({ error: 'name and base64 are required' }));
122         return;
123       }
124       const buffer = Buffer.from(payload.base64, 'base64');
125       if (buffer.length > MAX_UPLOAD_BYTES) {
126         res.writeHead(413, { 'Content-Type': 'application/json' });
127         res.end(JSON.stringify({ error: 'File too large (max 15MB)' }));
128         return;
129       }
130       const safeName = String(payload.name).replace(/^[a-zA-Z0-9_.-]/g, '_').slice(-100);
131       const storedName = `${Date.now().toString(36)}-${Math.random().toString(36).slice(2, 8)}-${safeName}`;
132       fs.writeFileSync(path.join(UPLOAD_DIR, storedName), buffer);
133       res.writeHead(200, { 'Content-Type': 'application/json' });
134       res.end(JSON.stringify({
135         url: `/files/${storedName}`,
136         name: safeName,
137         mimeType: payload.mimeType || 'application/octet-stream',
138         size: buffer.length,
139       }));
140     } catch (e) {
141       res.writeHead(400, { 'Content-Type': 'application/json' });
142       res.end(JSON.stringify({ error: 'Upload failed' }));
143     }
144     return;
145   }
146
147   // % % Generate a PT plan PDF: client sends the plan JSON, gets back a URL % %
148   if (req.method === 'POST' && url.pathname === '/generate-plan-pdf') {
149     try {
150       const plan = await readJsonBody(req, 2 * 1024 * 1024);
151       if (!plan || !plan.title) {
152         res.writeHead(400, { 'Content-Type': 'application/json' });
153         res.end(JSON.stringify({ error: 'A plan object is required' }));
154         return;
155       }
156       const buffer = await renderPlanPdf(plan);
157       const safeName = `${String(plan.title).replace(/^[a-zA-Z0-9_.-]/g, '_').slice(0, 60)}.pdf`;
158       const storedName = `${Date.now().toString(36)}-${Math.random().toString(36).slice(2, 8)}-${safeName}`;
159       fs.writeFileSync(path.join(UPLOAD_DIR, storedName), buffer);
160       res.writeHead(200, { 'Content-Type': 'application/json' });
161       res.end(JSON.stringify({ url: `/files/${storedName}`, name: safeName, mimeType: 'application/pdf',
size: buffer.length }));
162     } catch (e) {
163       res.writeHead(500, { 'Content-Type': 'application/json' });
164       res.end(JSON.stringify({ error: 'Could not generate PDF' }));
165     }
166     return;
167   }

```

```

168
169 // % % File download % %
170 const fileMatch = url.pathname.match(/^\/files\/([^\+]*)$/);
171 if (req.method === 'GET' && fileMatch) {
172   const storedName = decodeURIComponent(fileMatch[1]);
173   const filePath = path.join(UPLOAD_DIR, storedName);
174   if (!filePath.startsWith(UPLOAD_DIR) || !fs.existsSync(filePath)) {
175     res.writeHead(404, { 'Content-Type': 'application/json' });
176     res.end(JSON.stringify({ error: 'Not found' }));
177     return;
178   }
179   const displayName = storedName.replace(/^[a-z0-9]+-[a-z0-9]+-/, '');
180   const forceDownload = url.searchParams.get('download') === '1';
181   const contentType = displayName.toLowerCase().endsWith('.pdf') ? 'application/pdf' : 'application/octet-
stream';
182   res.writeHead(200, {
183     'Content-Type': contentType,
184     'Content-Disposition': `${forceDownload ? 'attachment' : 'inline'}; filename="${displayName}"`,
185   });
186   fs.createReadStream(filePath).pipe(res);
187   return;
188 }
189
190 // % % Key/value store (everything else) % %
191 const kvMatch = url.pathname.match(/^\/kv\/(.+)$/);
192 if (!kvMatch) {
193   res.writeHead(404, { 'Content-Type': 'application/json' });
194   res.end(JSON.stringify({ error: 'Not found' }));
195   return;
196 }
197
198 const key = decodeURIComponent(kvMatch[1]);
199
200 if (req.method === 'GET') {
201   res.writeHead(200, { 'Content-Type': 'application/json' });
202   res.end(JSON.stringify(store[key] ?? null));
203   return;
204 }
205
206 if (req.method === 'PUT') {
207   try {
208     const parsed = await readJsonBody(req);
209     store[key] = parsed;
210     persist();
211     res.writeHead(200, { 'Content-Type': 'application/json' });
212     res.end(JSON.stringify({ ok: true }));
213   } catch (e) {
214     res.writeHead(400, { 'Content-Type': 'application/json' });
215     res.end(JSON.stringify({ error: 'Invalid JSON body' }));
216   }
217   return;
218 }
219
220 res.writeHead(405, { 'Content-Type': 'application/json' });
221 res.end(JSON.stringify({ error: 'Method not allowed' }));
222 });
223
224 server.listen(PORT, '0.0.0.0', () => {
225   console.log(`Fit Force data server listening on http://0.0.0.0:${PORT}`);
226   console.log(`Data file: ${DATA_FILE}`);
227   console.log(`Uploads dir: ${UPLOAD_DIR}`);
228 });
229

```

```
1 // Renders a PT plan into a real, text-based PDF (not a screenshot) using
2 // pdfkit, so plans can be downloaded directly instead of going through the
3 // browser's print dialog (which is all expo-print can do on web).
4
5 const PDFDocument = require('pdfkit');
6
7 function renderPlanPdf(plan) {
8   return new Promise((resolve, reject) => {
9     const doc = new PDFDocument({ margin: 48, size: 'A4' });
10    const chunks = [];
11    doc.on('data', chunk => chunks.push(chunk));
12    doc.on('end', () => resolve(Buffer.concat(chunks)));
13    doc.on('error', reject);
14
15    const accent = plan.type === 'fit' ? '#2E7D32' : '#E65100';
16
17    doc.fontSize(10).fillColor(accent)
18      .text(plan.type === 'fit' ? 'FIT PLAN' : 'REHABILITATION PLAN', { characterSpacing: 1 });
19    doc.moveDown(0.3);
20    doc.fontSize(20).fillColor('#1A1A1A').text(plan.title);
21    doc.moveDown(0.2);
22    doc.fontSize(10).fillColor('#555555')
23      .text(`Week ${plan.weekNumber} • ${plan.days.length} days • Prepared by ${plan.createdByName}`);
24    doc.moveDown(0.6);
25    doc.fontSize(11).fillColor('#333333').text(plan.description, { lineGap: 3 });
26    doc.moveDown(1);
27
28    plan.days.forEach((day, i) => {
29      if (i > 0) doc.moveDown(0.8);
30
31      const titleY = doc.y;
32      doc.fontSize(13).fillColor('#1A1A1A').text(day.day, { continued: true });
33      doc.fontSize(13).fillColor('#777777').text(` - ${day.focus}`);
34      doc.moveTo(48, doc.y + 2).lineTo(547, doc.y + 2).strokeColor(accent).lineWidth(1.5).stroke();
35      doc.moveDown(0.4);
36
37      day.exercises.forEach(ex => {
38        doc.fontSize(10.5).fillColor('#1A1A1A').text(ex.name, { continued: true, indent: 8 });
39        doc.fontSize(10.5).fillColor(accent).text(` - ${ex.target}`);
40        if (ex.notes) {
41          doc.fontSize(9.5).fillColor('#777777').text(ex.notes, { indent: 8 });
42        }
43        doc.moveDown(0.25);
44      });
45    });
46
47    doc.end();
48  });
49 }
50
51 module.exports = { renderPlanPdf };
52
```

server/seed-data.js

```
1 // Plain-JS mirror of ../lib/seedData.ts, used to seed the shared data server
2 // the first time it starts (no existing data-store.json on disk yet).
3
4 const SEED_USERS = [
5   {
6     id: 'co-001', email: 'co@gmail.com', password: 'co123', role: 'co',
7     name: 'Lt Col Shahid Hasan', rank: 'Lt Col', ba: 'BA-6556',
8     phone: '01711-334455', bloodGroup: 'B+', medicalCategory: 'Category A',
9     height: 178, weight: 82, age: 45,
10  },
11  {
12    id: '2ic-001', email: '2ic@gmail.com', password: '2ic123', role: '2ic',
13    name: 'Maj Aminul Haque', rank: 'Maj', ba: 'BA-8823',
14    phone: '01712-556677', bloodGroup: 'O+', medicalCategory: 'Category A',
15    height: 175, weight: 78, age: 38,
16  },
17  {
18    id: 'adjt-001', email: 'adjt@gmail.com', password: 'adjt123', role: 'adjutant',
19    name: 'Capt Tasnim Akhter', rank: 'Capt', ba: 'BA-20211',
20    phone: '01713-778899', bloodGroup: 'A+', medicalCategory: 'Category A',
21    height: 165, weight: 60, age: 30,
22  },
23  {
24    id: 'coy-a-001', email: 'acoycomd@gmail.com', password: 'coya123', role: 'coy_comd',
25    name: 'Maj Jannat Ara', rank: 'Maj', ba: 'BA-202116', company: 'A',
26    phone: '01714-223344', bloodGroup: 'AB+', medicalCategory: 'Category A',
27    height: 162, weight: 58, age: 36,
28  },
29  {
30    id: 'coy-b-001', email: 'bcoycomd@gmail.com', password: 'coyb123', role: 'coy_comd',
31    name: 'Maj Faizul Hasan', rank: 'Maj', ba: 'BA-193045', company: 'B',
32    phone: '01715-445566', bloodGroup: 'B+', medicalCategory: 'Category A',
33    height: 174, weight: 80, age: 37,
34  },
35  {
36    id: 'coy-c-001', email: 'ccoycomd@gmail.com', password: 'coyc123', role: 'coy_comd',
37    name: 'Maj Rezaul Karim', rank: 'Maj', ba: 'BA-185674', company: 'C',
38    phone: '01716-667788', bloodGroup: 'O-', medicalCategory: 'Category A',
39    height: 172, weight: 75, age: 39,
40  },
41  {
42    id: 'coy-d-001', email: 'dcoycomd@gmail.com', password: 'coyd123', role: 'coy_comd',
43    name: 'Maj Kabirul Islam', rank: 'Maj', ba: 'BA-201234', company: 'D',
44    phone: '01717-889900', bloodGroup: 'A-', medicalCategory: 'Category A',
45    height: 176, weight: 82, age: 40,
46  },
47  {
48    id: 'clerk-001', email: 'clerk@gmail.com', password: 'clerk123', role: 'clerk',
49    name: 'Cpl Mizanur Rahman', rank: 'Cpl', ba: 'BA-301122',
50    phone: '01718-112233', bloodGroup: 'B+', medicalCategory: 'Category A',
51    height: 170, weight: 72, age: 28,
52  },
53  {
54    id: 'sol-a-001', email: 'jahangir@gmail.com', password: 'soldier123', role: 'soldier',
55    name: 'Jahangir Alam', rank: 'Snk', ba: 'BD-11001', company: 'A',
56    phone: '01911-001001', bloodGroup: 'A+', medicalCategory: 'Category A',
57    height: 170, weight: 68, age: 22, serviceNumber: 'BD-11001',
58  },
59  {
60    id: 'sol-a-002', email: 'rafiq@gmail.com', password: 'soldier123', role: 'soldier',
61    name: 'Rafiq Uddin', rank: 'LCpl', ba: 'BD-11002', company: 'A',
62    phone: '01911-001002', bloodGroup: 'B+', medicalCategory: 'Category B',
63    height: 168, weight: 85, age: 24, serviceNumber: 'BD-11002',
64  },
65  {
66    id: 'sol-a-003', email: 'kamal@gmail.com', password: 'soldier123', role: 'soldier',
67    name: 'Kamal Hossain', rank: 'Cpl', ba: 'BD-11003', company: 'A',
68    phone: '01911-001003', bloodGroup: 'O+', medicalCategory: 'Category A',
69    height: 172, weight: 70, age: 26, serviceNumber: 'BD-11003',
70  },
71  {
72    id: 'sol-a-004', email: 'arif@gmail.com', password: 'soldier123', role: 'soldier',
73    name: 'Ariful Islam', rank: 'Snk', ba: 'BD-11004', company: 'A',
74    phone: '01911-001004', bloodGroup: 'AB+', medicalCategory: 'Category A',
75    height: 165, weight: 62, age: 21, serviceNumber: 'BD-11004',
76  },
77  {
78    id: 'sol-b-001', email: 'rahim@gmail.com', password: 'soldier123', role: 'soldier',
79    name: 'Rahim Mia', rank: 'Snk', ba: 'BD-12001', company: 'B',
80    phone: '01911-002001', bloodGroup: 'A+', medicalCategory: 'Category A',
81    height: 169, weight: 66, age: 22, serviceNumber: 'BD-12001',
82  },
83  ]
```

```

84     id: 'sol-b-002', email: 'selim@gmail.com', password: 'soldier123', role: 'soldier',
85     name: 'Selim Khan', rank: 'LCpl', ba: 'BD-12002', company: 'B',
86     phone: '01911-002002', bloodGroup: 'AB+', medicalCategory: 'Category A',
87     height: 173, weight: 71, age: 25, serviceNumber: 'BD-12002',
88   },
89   {
90     id: 'sol-b-003', email: 'monir@gmail.com', password: 'soldier123', role: 'soldier',
91     name: 'Monir Hossain', rank: 'Cpl', ba: 'BD-12003', company: 'B',
92     phone: '01911-002003', bloodGroup: 'B-', medicalCategory: 'Category B',
93     height: 166, weight: 88, age: 27, serviceNumber: 'BD-12003',
94   },
95   {
96     id: 'sol-c-001', email: 'babu@gmail.com', password: 'soldier123', role: 'soldier',
97     name: 'Babu Mia', rank: 'Snk', ba: 'BD-13001', company: 'C',
98     phone: '01911-003001', bloodGroup: 'B-', medicalCategory: 'Category A',
99     height: 167, weight: 64, age: 21, serviceNumber: 'BD-13001',
100  },
101  {
102    id: 'sol-c-002', email: 'jamal@gmail.com', password: 'soldier123', role: 'soldier',
103    name: 'Jamal Uddin', rank: 'LCpl', ba: 'BD-13002', company: 'C',
104    phone: '01911-003002', bloodGroup: 'O+', medicalCategory: 'Category A',
105    height: 171, weight: 69, age: 24, serviceNumber: 'BD-13002',
106  },
107  {
108    id: 'sol-c-003', email: 'habib@gmail.com', password: 'soldier123', role: 'soldier',
109    name: 'Habibur Rahman', rank: 'Sgt', ba: 'BD-13003', company: 'C',
110    phone: '01911-003003', bloodGroup: 'A-', medicalCategory: 'Category A',
111    height: 174, weight: 76, age: 30, serviceNumber: 'BD-13003',
112  },
113  {
114    id: 'sol-d-001', email: 'faruk@gmail.com', password: 'soldier123', role: 'soldier',
115    name: 'Faruk Ahmed', rank: 'Snk', ba: 'BD-14001', company: 'D',
116    phone: '01911-004001', bloodGroup: 'A+', medicalCategory: 'Category A',
117    height: 168, weight: 65, age: 22, serviceNumber: 'BD-14001',
118  },
119  {
120    id: 'sol-d-002', email: 'nurul@gmail.com', password: 'soldier123', role: 'soldier',
121    name: 'Nurul Islam', rank: 'LCpl', ba: 'BD-14002', company: 'D',
122    phone: '01911-004002', bloodGroup: 'B+', medicalCategory: 'Category B',
123    height: 166, weight: 90, age: 25, serviceNumber: 'BD-14002',
124  },
125  {
126    id: 'sol-d-003', email: 'sultan@gmail.com', password: 'soldier123', role: 'soldier',
127    name: 'Sultan Mahmud', rank: 'WO', ba: 'BD-14003', company: 'D',
128    phone: '01911-004003', bloodGroup: 'O-', medicalCategory: 'Category A',
129    height: 176, weight: 80, age: 35, serviceNumber: 'BD-14003',
130  },
131 ];
132
133 const SEED_SOLDIERS = [
134   { id: 'sol-a-001', userId: 'sol-a-001', serviceNumber: 'BD-11001', name: 'Jahangir Alam', rank: 'Snk',
company: 'A', email: 'jahangir@gmail.com', bloodGroup: 'A+', height: 170, weight: 68, age: 22, medicalCategory:
'Category A', phone: '01911-001001', isApproved: true, isOverweight: false, ptStatus: 'fit' },
135   { id: 'sol-a-002', userId: 'sol-a-002', serviceNumber: 'BD-11002', name: 'Rafiq Uddin', rank: 'LCpl',
company: 'A', email: 'rafiq@gmail.com', bloodGroup: 'B+', height: 168, weight: 85, age: 24, medicalCategory:
'Category B', phone: '01911-001002', isApproved: true, isOverweight: true, ptStatus: 'unfit' },
136   { id: 'sol-a-003', userId: 'sol-a-003', serviceNumber: 'BD-11003', name: 'Kamal Hossain', rank: 'Cpl',
company: 'A', email: 'kamal@gmail.com', bloodGroup: 'O+', height: 172, weight: 70, age: 26, medicalCategory:
'Category A', phone: '01911-001003', isApproved: true, isOverweight: false, ptStatus: 'fit' },
137   { id: 'sol-a-004', userId: 'sol-a-004', serviceNumber: 'BD-11004', name: 'Ariful Islam', rank: 'Snk',
company: 'A', email: 'arif@gmail.com', bloodGroup: 'AB+', height: 165, weight: 62, age: 21, medicalCategory:
'Category A', phone: '01911-001004', isApproved: true, isOverweight: false, ptStatus: 'pending' },
138   { id: 'sol-b-001', userId: 'sol-b-001', serviceNumber: 'BD-12001', name: 'Rahim Mia', rank: 'Snk',
company: 'B', email: 'rahim@gmail.com', bloodGroup: 'A+', height: 169, weight: 66, age: 22, medicalCategory:
'Category A', phone: '01911-002001', isApproved: true, isOverweight: false, ptStatus: 'fit' },
139   { id: 'sol-b-002', userId: 'sol-b-002', serviceNumber: 'BD-12002', name: 'Selim Khan', rank: 'LCpl',
company: 'B', email: 'selim@gmail.com', bloodGroup: 'AB+', height: 173, weight: 71, age: 25, medicalCategory:
'Category A', phone: '01911-002002', isApproved: true, isOverweight: false, ptStatus: 'fit' },
140   { id: 'sol-b-003', userId: 'sol-b-003', serviceNumber: 'BD-12003', name: 'Monir Hossain', rank: 'Cpl',
company: 'B', email: 'monir@gmail.com', bloodGroup: 'B-', height: 166, weight: 88, age: 27, medicalCategory:
'Category B', phone: '01911-002003', isApproved: true, isOverweight: true, ptStatus: 'unfit' },
141   { id: 'sol-c-001', userId: 'sol-c-001', serviceNumber: 'BD-13001', name: 'Babu Mia', rank: 'Snk',
company: 'C', email: 'babu@gmail.com', bloodGroup: 'B-', height: 167, weight: 64, age: 21, medicalCategory:
'Category A', phone: '01911-003001', isApproved: true, isOverweight: false, ptStatus: 'fit' },
142   { id: 'sol-c-002', userId: 'sol-c-002', serviceNumber: 'BD-13002', name: 'Jamal Uddin', rank: 'LCpl',
company: 'C', email: 'jamal@gmail.com', bloodGroup: 'O+', height: 171, weight: 69, age: 24, medicalCategory:
'Category A', phone: '01911-003002', isApproved: true, isOverweight: false, ptStatus: 'fit' },
143   { id: 'sol-c-003', userId: 'sol-c-003', serviceNumber: 'BD-13003', name: 'Habibur Rahman', rank: 'Sgt',
company: 'C', email: 'habib@gmail.com', bloodGroup: 'A-', height: 174, weight: 76, age: 30, medicalCategory:
'Category A', phone: '01911-003003', isApproved: true, isOverweight: false, ptStatus: 'unfit' },
144   { id: 'sol-d-001', userId: 'sol-d-001', serviceNumber: 'BD-14001', name: 'Faruk Ahmed', rank: 'Snk',
company: 'D', email: 'faruk@gmail.com', bloodGroup: 'A+', height: 168, weight: 65, age: 22, medicalCategory:
'Category A', phone: '01911-004001', isApproved: true, isOverweight: false, ptStatus: 'fit' },
145   { id: 'sol-d-002', userId: 'sol-d-002', serviceNumber: 'BD-14002', name: 'Nurul Islam', rank: 'LCpl',
company: 'D', email: 'nurul@gmail.com', bloodGroup: 'B+', height: 166, weight: 90, age: 25, medicalCategory:

```

```

'Category B', phone: '01911-004002', isApproved: true, isOverweight: true, ptStatus: 'unfit' },
146   { id: 'sol-d-003', userId: 'sol-d-003', serviceNumber: 'BD-14003', name: 'Sultan Mahmud', rank: 'WO',
company: 'D', email: 'sultan@gmail.com', bloodGroup: 'O-', height: 176, weight: 80, age: 35, medicalCategory:
'Category A', phone: '01911-004003', isApproved: true, isOverweight: false, ptStatus: 'fit' },
147 ];
148
149 const SEED_PT_PLANS = [
150   {
151     id: 'plan-001', title: 'Standard Fitness Week Plan', type: 'fit',
152     description: 'Weekly PT plan for soldiers who passed IPFT. Maintain peak physical condition.',
153     createdBy: '2ic-001', createdByName: 'Maj Aminul Haque', weekNumber: 29,
154     createdAt: '2026-07-10T08:00:00Z',
155     days: [
156       { day: 'Saturday', focus: 'Cardio & Speed', exercises: [{ name: '3km Run', target: 'Complete in 12
min', notes: 'Maintain steady pace' }, { name: 'Sprints 100m', target: '10 sets', notes: '30s rest between
sets' }, { name: 'Jump Rope', target: '15 min continuous' } ] },
157       { day: 'Sunday', focus: 'Upper Body Strength', exercises: [{ name: 'Push-ups', target: '3 sets x 40
reps' }, { name: 'Pull-ups', target: '3 sets x 10 reps' }, { name: 'Dips', target: '3 sets x 15 reps' }, { name:
'Plank', target: '3 sets x 60 sec' } ] },
158       { day: 'Monday', focus: 'Lower Body & Core', exercises: [{ name: 'Squats', target: '4 sets x 30
reps' }, { name: 'Lunges', target: '3 sets x 20 reps each leg' }, { name: 'Sit-ups', target: '4 sets x 35
reps' }, { name: 'Calf Raises', target: '3 sets x 25 reps' } ] },
159       { day: 'Tuesday', focus: 'REST / Recovery', exercises: [{ name: 'Light Stretching', target: '20
min' }, { name: 'Walking', target: '2km easy pace' } ] },
160       { day: 'Wednesday', focus: 'Endurance Run', exercises: [{ name: '5km Run', target: 'Complete in 25
min' }, { name: 'Stair Climbing', target: '10 flights x 5 sets' } ] },
161       { day: 'Thursday', focus: 'Full Body Circuit', exercises: [{ name: 'Burpees', target: '4 sets x 15
reps' }, { name: 'Mountain Climbers', target: '3 sets x 30 reps' }, { name: 'Box Jumps', target: '3 sets x 12
reps' }, { name: 'Push-ups', target: '3 sets x 30 reps' } ] },
162       { day: 'Friday', focus: 'Parade & Drill', exercises: [{ name: 'Parade Drill', target: '1 hour' },
{ name: 'Formation Run', target: '2km' } ] },
163     ],
164   },
165   {
166     id: 'plan-002', title: 'Rehabilitation PT Plan (Unfit)', type: 'unfit',
167     description: 'Progressive recovery plan for soldiers who failed IPFT. Focus on gradual improvement.',
168     createdBy: '2ic-001', createdByName: 'Maj Aminul Haque', weekNumber: 29,
169     createdAt: '2026-07-10T08:30:00Z',
170     days: [
171       { day: 'Saturday', focus: 'Light Cardio', exercises: [{ name: '2km Walk/Jog', target: 'Complete in 20
min', notes: 'No pressure, keep moving' }, { name: 'Deep Breathing', target: '10 min' } ] },
172       { day: 'Sunday', focus: 'Basic Strength', exercises: [{ name: 'Modified Push-ups', target: '3 sets x
15 reps', notes: 'Knee push-ups allowed' }, { name: 'Sit-ups', target: '3 sets x 15 reps' }, { name: 'Plank',
target: '3 sets x 20 sec' } ] },
173       { day: 'Monday', focus: 'Mobility & Flexibility', exercises: [{ name: 'Full Body Stretching', target:
'30 min' }, { name: 'Yoga Basics', target: '20 min' }, { name: 'Light Squats', target: '3 sets x 10 reps' } ] },
174       { day: 'Tuesday', focus: 'REST', exercises: [{ name: 'Rest & Recovery', target: 'Full rest day' } ] },
175       { day: 'Wednesday', focus: 'Progressive Run', exercises: [{ name: 'Walk 3min / Jog 2min', target:
'Repeat 5 times = 25 min', notes: 'Interval training' } ] },
176       { day: 'Thursday', focus: 'Light Circuit', exercises: [{ name: 'Jumping Jacks', target: '3 sets x 20
reps' }, { name: 'Modified Burpees', target: '3 sets x 8 reps' }, { name: 'Wall Sit', target: '3 sets x 20
sec' } ] },
177       { day: 'Friday', focus: 'BMI Awareness & Diet', exercises: [{ name: 'Diet Counseling', target:
'Review meal plan' }, { name: 'Light Walk', target: '30 min' } ] },
178     ],
179   },
180 ];
181
182 const SEED_IPFT_RESULTS = [
183   {
184     id: 'result-001', soldierId: 'sol-a-001', soldierName: 'Jahangir Alam', soldierRank: 'Snk',
185     serviceNumber: 'BD-11001', company: 'A', date: '2026-06-15', overallStatus: 'pass',
186     recordedBy: 'clerk-001', recordedByName: 'Cpl Mizanur Rahman', bmi: 23.5,
187     items: [
188       { name: '1.6km Run', target: '< 9 min', achieved: '8:20', status: 'pass' },
189       { name: '3.2km Run', target: '< 24 min', achieved: '22:40', status: 'pass' },
190       { name: 'Push-ups', target: '"e 35 reps/2min', achieved: '42', status: 'pass' },
191       { name: 'Sit-ups', target: '"e 30 reps/2min', achieved: '38', status: 'pass' },
192       { name: 'Pull-ups', target: '"e 6 reps', achieved: '8', status: 'pass' },
193     ],
194   },
195   {
196     id: 'result-002', soldierId: 'sol-a-002', soldierName: 'Rafiq Uddin', soldierRank: 'LCpl',
197     serviceNumber: 'BD-11002', company: 'A', date: '2026-06-15', overallStatus: 'fail',
198     recordedBy: 'clerk-001', recordedByName: 'Cpl Mizanur Rahman', bmi: 30.1,
199     items: [
200       { name: '1.6km Run', target: '< 9 min', achieved: '10:15', status: 'fail' },
201       { name: '3.2km Run', target: '< 24 min', achieved: '27:30', status: 'fail' },
202       { name: 'Push-ups', target: '"e 35 reps/2min', achieved: '22', status: 'fail' },
203       { name: 'Sit-ups', target: '"e 30 reps/2min', achieved: '18', status: 'fail' },
204       { name: 'Pull-ups', target: '"e 6 reps', achieved: '3', status: 'fail' },
205     ],
206   },
207   {
208     id: 'result-003', soldierId: 'sol-b-001', soldierName: 'Rahim Mia', soldierRank: 'Snk',

```

```

209     serviceNumber: 'BD-12001', company: 'B', date: '2026-06-15', overallStatus: 'pass',
210     recordedBy: 'clerk-001', recordedByName: 'Cpl Mizanur Rahman', bmi: 23.1,
211     items: [
212         { name: '1.6km Run', target: '< 9 min', achieved: '8:35', status: 'pass' },
213         { name: '3.2km Run', target: '< 24 min', achieved: '23:10', status: 'pass' },
214         { name: 'Push-ups', target: '"e 35 reps/2min', achieved: '38', status: 'pass' },
215         { name: 'Sit-ups', target: '"e 30 reps/2min', achieved: '33', status: 'pass' },
216         { name: 'Pull-ups', target: '"e 6 reps', achieved: '7', status: 'pass' },
217     ],
218 },
219 ];
220
221 const SEED_IPFT_SCHEDULE = {
222     id: 'ipft-sched-001',
223     proposedDate: '2026-07-28',
224     proposedBy: 'adjt-001',
225     proposedByName: 'Capt Tasnim Akhter',
226     status: 'approved',
227     approvedBy: 'co-001',
228     createdAt: '2026-07-10T09:00:00Z',
229 };
230
231 const SEED_NOTIFICATIONS = [
232     { id: 'notif-001', title: 'IPFT Date Confirmed', body: 'Next IPFT will be held on 28 July 2026. All
companies must ensure 100% readiness.', type: 'ipft_approved', read: false, createdAt: '2026-07-11T10:00:00Z' },
233     { id: 'notif-002', targetCompany: 'A', title: 'Overweight Soldier Alert', body: 'LCpl Rafiq Uddin
(BD-11002) is overweight. BMI: 30.1. Rehabilitation plan assigned.', type: 'overweight', read: false, createdAt:
'2026-07-10T08:00:00Z' },
234     { id: 'notif-003', title: 'New PT Plans Published', body: 'Week 29 PT plans have been published by 2IC.
Check your assigned plan.', type: 'new_plan', read: true, createdAt: '2026-07-09T07:30:00Z' },
235     { id: 'notif-004', targetUserId: 'sol-a-002', title: 'IPFT Failed - Action Required', body: 'You have
failed the last IPFT. Unfit PT plan assigned. 8 days remaining for next IPFT.', type: 'new_result', read: false,
createdAt: '2026-06-16T09:00:00Z' },
236     { id: 'notif-005', targetCompany: 'B', title: 'Overweight Soldier - Coy B', body: 'Cpl Monir Hossain
(BD-12003) is overweight. BMI: 31.9. Immediate action required.', type: 'overweight', read: false, createdAt:
'2026-07-10T08:00:00Z' },
237 ];
238
239 const SEED_REPORTS = [
240     {
241         id: 'report-001', fromId: 'clerk-001', fromName: 'Cpl Mizanur Rahman', fromRole: 'clerk',
242         toId: 'adjt-001', toRole: 'adjutant', title: 'IPFT Result Report - June 2026',
243         content: 'Total soldiers tested: 13\nPassed: 9 (69.2%)\nFailed: 4 (30.8%)\nOverweight soldiers:
3\n\nCompany-wise breakdown:\nA Coy: 3 Pass, 1 Fail\nB Coy: 2 Pass, 1 Fail\nC Coy: 3 Pass, 0 Fail\nD Coy: 1 Pass,
2 Fail',
244         attachmentLabel: 'IPFT_Result_June2026.pdf', read: false, createdAt: '2026-06-16T14:00:00Z',
245     },
246     {
247         id: 'report-002', fromId: 'clerk-001', fromName: 'Cpl Mizanur Rahman', fromRole: 'clerk',
248         toId: 'adjt-001', toRole: 'adjutant', title: 'Total Strength Report - July 2026',
249         content: 'Overall Unit Strength:\nA Coy: 4 soldiers (3 Fit, 1 Unfit)\nB Coy: 3 soldiers (2 Fit, 1
Unfit)\nC Coy: 3 soldiers (2 Fit, 1 Unfit)\nD Coy: 3 soldiers (1 Fit, 2 Unfit)\n\nTotal Strength: 13\nTotal Fit:
8\nTotal Unfit: 5',
250         attachmentLabel: 'Total_Strength_July2026.pdf', read: true, createdAt: '2026-07-01T09:00:00Z',
251     },
252 ];
253
254 module.exports = {
255     SEED_USERS, SEED_SOLDIERS, SEED_PT_PLANS, SEED_IPFT_RESULTS,
256     SEED_IPFT_SCHEDULE, SEED_NOTIFICATIONS, SEED_REPORTS,
257 };
258

```

```
1  /**
2   * Standalone production server for Expo static builds.
3   *
4   * Serves the output of build.js (static-build/) with two special routes:
5   * - GET / or /manifest with expo-platform header !' platform manifest JSON
6   * - GET / without expo-platform !' landing page HTML
7   * Everything else falls through to static file serving from ./static-build/.
8   *
9   * Zero external dependencies – uses only Node.js built-ins (http, fs, path).
10  */
11
12  const http = require('http');
13  const fs = require('fs');
14  const path = require('path');
15
16  const STATIC_ROOT = path.resolve(__dirname, '..', 'static-build');
17  const TEMPLATE_PATH = path.resolve(__dirname, 'templates', 'landing-page.html');
18  const basePath = (process.env.BASE_PATH || '/').replace(/\/+$/, '');
19
20  const MIME_TYPES = {
21    '.html': 'text/html; charset=utf-8',
22    '.js': 'application/javascript; charset=utf-8',
23    '.json': 'application/json; charset=utf-8',
24    '.css': 'text/css; charset=utf-8',
25    '.png': 'image/png',
26    '.jpg': 'image/jpeg',
27    '.jpeg': 'image/jpeg',
28    '.gif': 'image/gif',
29    '.svg': 'image/svg+xml',
30    '.ico': 'image/x-icon',
31    '.woff': 'font/woff',
32    '.woff2': 'font/woff2',
33    '.ttf': 'font/ttf',
34    '.otf': 'font/otf',
35    '.map': 'application/json',
36  };
37
38  function getAppName() {
39    try {
40      const appJsonPath = path.resolve(__dirname, '..', 'app.json');
41      const appJson = JSON.parse(fs.readFileSync(appJsonPath, 'utf-8'));
42      return appJson.expo?.name || 'App Landing Page';
43    } catch {
44      return 'App Landing Page';
45    }
46  }
47
48  function serveManifest(platform, res) {
49    const manifestPath = path.join(STATIC_ROOT, platform, 'manifest.json');
50
51    if (!fs.existsSync(manifestPath)) {
52      res.writeHead(404, { 'content-type': 'application/json' });
53      res.end(
54        JSON.stringify({ error: `Manifest not found for platform: ${platform}` })
55      );
56      return;
57    }
58
59    const manifest = fs.readFileSync(manifestPath, 'utf-8');
60    res.writeHead(200, {
61      'content-type': 'application/json',
62      'expo-protocol-version': '1',
63      'expo-sfv-version': '0',
64    });
65    res.end(manifest);
66  }
67
68  function serveLandingPage(req, res, landingPageTemplate, appName) {
69    const forwardedProto = req.headers['x-forwarded-proto'];
70    const protocol = forwardedProto || 'https';
71    const host = req.headers['x-forwarded-host'] || req.headers['host'];
72    const baseUrl = `${protocol}://${host}`;
73    const expsUrl = `${host}`;
74
75    const html = landingPageTemplate
76      .replace(/BASE_URL_PLACEHOLDER/g, baseUrl)
77      .replace(/EXPS_URL_PLACEHOLDER/g, expsUrl)
78      .replace(/APP_NAME_PLACEHOLDER/g, appName);
79
80    res.writeHead(200, { 'content-type': 'text/html; charset=utf-8' });
81    res.end(html);
82  }
83
```

```

84 function serveStaticFile(urlPath, res) {
85   const safePath = path.normalize(urlPath).replace(/^(\\.\\.\\.\\|\\$))+/, '');
86   const filePath = path.join(STATIC_ROOT, safePath);
87
88   if (!filePath.startsWith(STATIC_ROOT)) {
89     res.writeHead(403);
90     res.end('Forbidden');
91     return;
92   }
93
94   if (!fs.existsSync(filePath) || fs.statSync(filePath).isDirectory()) {
95     res.writeHead(404);
96     res.end('Not Found');
97     return;
98   }
99
100  const ext = path.extname(filePath).toLowerCase();
101  const contentType = MIME_TYPES[ext] || 'application/octet-stream';
102  const content = fs.readFileSync(filePath);
103  res.writeHead(200, { 'content-type': contentType });
104  res.end(content);
105 }
106
107 const landingPageTemplate = fs.readFileSync(TEMPLATE_PATH, 'utf-8');
108 const appName = getAppName();
109
110 const server = http.createServer((req, res) => {
111   const url = new URL(req.url || '/', `http://${req.headers.host}`);
112   let pathname = url.pathname;
113
114   if (basePath && pathname.startsWith(basePath)) {
115     pathname = pathname.slice(basePath.length) || '/';
116   }
117
118   if (pathname === '/' || pathname === '/manifest') {
119     const platform = req.headers['expo-platform'];
120     if (platform === 'ios' || platform === 'android') {
121       return serveManifest(platform, res);
122     }
123
124     if (pathname === '/') {
125       return serveLandingPage(req, res, landingPageTemplate, appName);
126     }
127   }
128
129   serveStaticFile(pathname, res);
130 });
131
132 const port = parseInt(process.env.PORT || '3000', 10);
133 server.listen(port, '0.0.0.0', () => {
134   console.log(`Serving static Expo build on port ${port}`);
135 });
136

```


