Introduction to Communication Engineering SSY121, Lecture # 9

Fredrik Brännström
Fredrik.Brannstrom@chalmers.se

Communication Systems Group
Department of Electrical Engineering
Chalmers University of Technology
Göteborg, Sweden

Wed Sept 20, 2023

Information

Computer lab

For working on the project, you can use the computer lab (room 5225) or for example rooms ES61, ES62, and ES63 on floor 6 in Linsen in the EDIT house. The computer lab (room 5225) is booked Mon–Fri at 17-21 in study week 5, 6, and 7.

Project Quiz, Wed Oct 11, at 10:00-10:20 (first part of the last lecture)

10 questions (10 points) is answered individually. The quiz is 20 minutes long, and it is composed of 10 multiple choice questions which evaluate the understanding of the scientific base of the project.

Sign up for exam

The exam is on Mon Oct 23 at 14:00-18:00. Please remember to register for the exam. Chalmers' rule is that if you have not registered for the exam, you will not be allowed to take the exam.
The last day to register for the exam is Sun Oct 8!

Outline

Part I

Review and Some Definitions

Review and Some Definitions
Pairwise error probability
Error probabilities

The AWGN channel
Review of the vector channel model for the AWGN channel
Some Definitions

A very nice property of the AWGN

If $n(t)$ is a white Gaussian random process with PSD $N_0/2$, then the random variables n_i, the projections of $n(t)$ onto **any** set of orthonormal basis functions, are i.i.d. Gaussian random variables with zero mean and variance $N_0/2$. (Theorem 2.5-1 in [Anderson])

The continuous-time AWGN channel in signal space

- If $n(t)$ is AWGN with PSD $N_0/2$, the continuous time channel $y(t) = s(t) + n(t)$, can be replaced by a vectorial channel model

$$y = s + n,$$

  where $s = [s_1, \ldots, s_N]$ is the transmitted symbol, $n = [n_1, \ldots, n_N]$ is the noise, and $y = [y_1, \ldots, y_N]$ is the received signal.

- The components of the noise vector n_i for $i = 1, \ldots, N$ are i.i.d. zero-mean Gaussian random variables with variance $N_0/2$.

Review and Some Definitions | The AWGN channel
Pairwise error probability | Review of the vector channel model for the AWGN channel
Error probabilities | Some Definitions

The vector channel model for the AWGN channel

Review and Some Definitions
Pairwise error probability
Error probabilities

The AWGN channel
Review of the vector channel model for the AWGN channel
Some Definitions

Definitions (see also L_2)

- M: Number of symbols
- l: Number of bits per symbol
- R_s: Symbol rate (T_s: symbol period)
- R_b: Bit rate (T_b: bit period). $R_b = lR_s$
- E_s: Average symbol energy:

$$E_s = \sum_{i=1}^{M} \mathbb{P}\left[\mathsf{S} = \mathsf{s}_i\right] \|\mathsf{s}_i\|^2$$

- E_b: Average bit energy. $E_b = E_s/l$
- Signal to noise-ratio: SNR=E_s/N_0
- Decibel: logarithmic measure of the ratio between two power or energies. For example $\text{SNR}_{dB} = 10 \log_{10}(E_s/N_0)$

Review and Some Definitions   The AWGN channel
Pairwise error probability   Review of the vector channel model for the AWGN channel
Error probabilities   Some Definitions

Example (what can you do after this lecture?)

Consider equally likely 4-PAM transmission where $\mathsf{s} \in \{-3A, -A, A, 3A\}$.

- Compute A such that $E_s = 1$
- Compute the relation between E_s and E_b
- Draw the constellation and the decision regions
- Compute the SNR in dB if $N_0 = 0.5$
- Compute the conditional PDF $f_{Y|S}(y|S = -3A)$ for SNR$= 3$ dB, for SNR$= -3$ dB, and for SNR$= 10$ dB
- Compute the probability of mistaking the transmitted symbol $\mathsf{s} = -3A$ by the symbol $-A$, A, and $+3A$ for the three SNR values

Pairwise error probability (PEP) definition

The PEP is simply the probability of mistaking the symbol s_i by s_j, i.e.,

$$\mathrm{PEP}^{(i,j)} = \mathbb{P}\left[||\mathsf{Y}-\mathsf{s}_j|| \leq ||\mathsf{Y}-\mathsf{s}_i|| \big| \mathsf{S}=\mathsf{s}_i\right]$$

PEP in 1D for an AWGN channel

$$\begin{aligned}
\mathrm{PEP}^{(i,j)} &= \mathbb{P}\left[||\mathsf{Y}-\mathsf{s}_j|| < ||\mathsf{Y}-\mathsf{s}_i|| \big| \mathsf{S}=\mathsf{s}_i\right] \\
&= \int_{y_0}^{\infty} f_{\mathsf{Y}|\mathsf{S}}(\mathsf{y}|\mathsf{s}_i)d\mathsf{y} = \mathrm{Q}\left(\frac{y_0-\mathsf{s}_i}{\sigma}\right) \\
&= \mathrm{Q}\left(\frac{\mathsf{s}_i+\mathsf{s}_j-2\mathsf{s}_i}{2\sqrt{N_0/2}}\right) = \mathrm{Q}\left(\sqrt{\frac{D_{i,j}^2}{2N_0}}\right),
\end{aligned}$$

where $y_0 = (\mathsf{s}_i+\mathsf{s}_j)/2$ is halfway between the signals, $\sigma^2 = N_0/2$ the variance of the noise, and $D_{i,j}^2$ is the squared Euclidean distance between s_i and s_j, i.e., $D_{i,j}^2 = \|\mathsf{s}_j-\mathsf{s}_i\|^2$ (see also L_7).

PEP in 2D: Still the same (Why?)

$$\mathrm{PEP}^{(i,j)} = \mathrm{Q}\left(\sqrt{\frac{D_{i,j}^2}{2N_0}}\right).$$

2D Conditional Gaussian densities

PEP in N dimensions

Still the same! (Why?)

$$\text{PEP}^{(i,j)} = Q\left(\sqrt{\frac{D_{i,j}^2}{2N_0}}\right).$$

What we need to know?

- The squared Euclidean distance between the two points $D_{i,j}^2$
- The noise variance $N_0/2$

The "border" (decision region)

- In 1D, the "border" is a point
- In 2D, the "border" is a line
- In 3D, the "border" is a plane
- In 4D, ...

Review and Some Definitions
Pairwise error probability
Error probabilities

The average error probability
The union bound and a high SNR approximation
Bit Error probability and Gray code

A general error probability formula

The error probability when s_i is transmitted is

$$\mathbb{P}\left[\text{error}|\mathsf{S}=\mathsf{s}_i\right] = \mathbb{P}\left[\mathsf{Y}\notin\mathcal{R}_i|\mathsf{S}=\mathsf{s}_i\right] = \sum_{j\neq i}\mathbb{P}\left[\mathsf{Y}\in\mathcal{R}_j|\mathsf{S}=\mathsf{s}_i\right]$$

The **exact** average error probability P_{e} is

$$P_{\mathrm{e}} = \sum_{i=1}^{M}\mathbb{P}\left[\text{error}|\mathsf{S}=\mathsf{s}_i\right]\mathbb{P}\left[\mathsf{S}=\mathsf{s}_i\right]$$

$$= \sum_{i=1}^{M}\mathbb{P}\left[\mathsf{S}=\mathsf{s}_i\right]\sum_{j\neq i}\mathbb{P}\left[\mathsf{Y}\in\mathcal{R}_j|\mathsf{S}=\mathsf{s}_i\right]$$

And what is the problem with this?

In general, we do not know how to compute $\mathbb{P}\left[\mathsf{Y}\in\mathcal{R}_j|\mathsf{S}=\mathsf{s}_i\right]$ 🙁

Review and Some Definitions
Pairwise error probability
Error probabilities

The average error probability
The union bound and a high SNR approximation
Bit Error probability and Gray code

An exception to the rule...

For binary transmission ($M = 2$), we do know how to compute the exact P_{e}, since $\mathbb{P}\left[\mathsf{Y} \in \mathcal{R}_j | \mathsf{S} = \mathsf{s}_i\right] = \mathrm{PEP}^{(1,2)}$.

For the particular case of $M = 2$ and equally likely symbols

For binary modulation ($M = 2$), the exact average error probability P_{e} can be written in terms of the PEP

$$
\begin{aligned}
P_{\mathrm{e}} &= \mathbb{P}\left[\mathsf{S} = \mathsf{s}_1\right] \mathrm{PEP}^{(1,2)} + \mathbb{P}\left[\mathsf{S} = \mathsf{s}_2\right] \mathrm{PEP}^{(2,1)} \\
&= \frac{1}{2} \mathrm{Q}\left(\sqrt{\frac{D_{1,2}^2}{2N_0}}\right) + \frac{1}{2} \mathrm{Q}\left(\sqrt{\frac{D_{2,1}^2}{2N_0}}\right) \\
&= \mathrm{Q}\left(\sqrt{\frac{D_{1,2}^2}{2N_0}}\right)
\end{aligned}
$$

Review and Some Definitions
Pairwise error probability
Error probabilities

The average error probability
The union bound and a high SNR approximation
Bit Error probability and Gray code

The union bound (UB)

A good **approximation** of the average error probability P_{e} is

$$P_{\mathrm{e}} = \sum_{i=1}^{M} \mathbb{P}\left[\mathsf{S} = \mathsf{s}_i\right] \sum_{j \neq i} \mathbb{P}\left[\mathsf{Y} \in \mathcal{R}_j | \mathsf{S} = \mathsf{s}_i\right]$$

$$\leq \sum_{i=1}^{M} \mathbb{P}\left[\mathsf{S} = \mathsf{s}_i\right] \sum_{j \neq i} \mathrm{PEP}^{(i,j)} = \sum_{i=1}^{M} \mathbb{P}\left[\mathsf{S} = \mathsf{s}_i\right] \sum_{j \neq i} \mathrm{Q}\left(\sqrt{\frac{D_{i,j}^2}{2N_0}}\right)$$

The UB for equally likely symbols

$$P_{\mathrm{e}} \leq \frac{1}{M} \sum_{i=1}^{M} \sum_{j \neq i} \mathrm{Q}\left(\sqrt{\frac{D_{i,j}^2}{2N_0}}\right)$$

The previous approximation...

- It is actually **not** an approximation (it is exact) for $M = 2$

Review and Some Definitions
Pairwise error probability
Error probabilities

The average error probability
The union bound and a high SNR approximation
Bit Error probability and Gray code

Can we simplify it even more?

- The Q-functions decrease very fast when the argument increases
- For large arguments (high SNR), one of the Q-functions will dominate

Definition (High-SNR approximation)

For sufficiently high SNR, the average error probability can be approximated by

$$P_{\mathrm{e}} = \sum_{i=1}^{M} \mathbb{P}\left[\mathsf{S} = \mathsf{s}_i\right] \sum_{j \neq i} \mathbb{P}\left[\mathsf{Y} \in \mathcal{R}_j | \mathsf{S} = \mathsf{s}_i\right]$$

$$\leq \frac{1}{M} \sum_{i=1}^{M} \sum_{j \neq i} \mathrm{Q}\left(\sqrt{\frac{D_{i,j}^2}{2N_0}}\right) \approx \frac{2K}{M} \cdot \mathrm{Q}\left(\sqrt{\frac{D_{\min}^2}{2N_0}}\right),$$

where $D_{\min} = \min_{i \neq j}\{D_{i,j}\}$ is the *minimum distance* of the constellation, and K is the number of signal pairs at minimum distance (section 2.6 in [Andersson])

Review and Some Definitions
Pairwise error probability
Error probabilities

The average error probability
The union bound and a high SNR approximation
Bit Error probability and Gray code

Example (Error probability of OOK and BPSK)

Which modulation scheme is better in terms of error probability, OOK or BPSK?

- Normalize both constellations to unit energy
- For a given N_0, find the PEP
- Plot both of them using Matlab

Homeworks!

Compute and plot error probabilities (bounds/approximations) for OOK, BPSK, 4-PAM, 8-PAM, QPSK, 16-QAM, 8-PSK, etc.

Review and Some Definitions   The average error probability
Pairwise error probability   The union bound and a high SNR approximation
Error probabilities   **Bit Error probability and Gray code**

Symbol error probability and bit error probability

- The relation between symbol error probability and bit error probability is in general not simple
- It depends on the binary labeling
- The "best" we could do is to have one bit-error for each symbol error
- For the high-SNR approximation, we would like to use a binary labeling such that symbols at $D_{\min}$ differ in only one bit
- How: Gray Code

Review and Some Definitions   The average error probability
Pairwise error probability   The union bound and a high SNR approximation
Error probabilities   **Bit Error probability and Gray code**

Gray code for 4-PAM and 64-QAM

Review and Some Definitions   The average error probability
Pairwise error probability   The union bound and a high SNR approximation
Error probabilities   **Bit Error probability and Gray code**

Today's Summary

- Vector channel model for the AWGN channel.
- Pairwise error probability (PEP), exact average error probability, union bound, and high-SNR approximation.
- Symbol error probability vs. bit error probability and Gray Code.