Project 8C C17 integrated chassis design review
Revision: C17 Rev 0 / generated 2026-10-11
STATUS: CONCEPT / DESIGN REVIEW / ENGINEERING HOLD

Architecture
- Image-led triangulated spaceframe: paired lower/upper rails, repeated side-bay diagonals,
- Cabin floor crossmembers, a provisional shear panel, side-door diagonals and shared X-02 c
- The supplied 108-solid C18 front reference, 199-solid Probox reference and 21-solid C11 ca
- Rear Probox packaging is represented by a replaceable RHS cradle around the actual donor e
- Firewall at X=950 and cockpit aft edge X=889.83 remain the visible X-01 conflict pending t

Fixed / derived parameters
- Body width 2100 mm (F); body length 6110.17 mm (D); wheelbase 3559.32 mm (D).
- Rear axle X=0 (F); front axle X=3559.32 (D); +X front, +Y vehicle-left, +Z up.
- Toyota donor geometry is not scaled; donor interfaces are P/M proxies.

Design assessment
- C11 is retained as a spatial reference and strengthened with 60x80x4 lap rails and diagona
- C16 front study is reorganized into paired continuous rails, four crossmembers, wheel outr
- Probox Rev01 is retained as a packaging reference; rear-drive transaxle feasibility, mount
- Scaled central shell station loft is reference geometry only; validated fenders are absent

Engineering limitations
- No donor drilling, weld specification, material certificate, fatigue result, FEA, kinemati
- Bracket drilling schedule is a HOLD. Fabrication requires closure of C17 gates G01-G11 and