ENTERPRISE FLEET TELEMATICS & RELIABILITY ANALYTICS: DATA PIPELINE, MODELING & DAX SPECIFICATION

Author: Jahnavi Sharma
Target Role: Fleet Data & Analytics Specialist / Reliability Data Scientist
Domain Focus: Heavy Equipment Telematics (VIMS / Product Link) & SAP Enterprise Asset Management (EAM)

1. TECHNICAL ARCHITECTURE OVERVIEW

The platform implements an enterprise ETL pipeline that bridges IoT sensor streams with SAP EAM maintenance logs, transforming unverified sensor pings into an audited, Star-Schema analytics data mart in Power BI.

System Data Flow Pipeline

Data Pipeline Stage	Source & Function	Primary Transformation / Processing Task	Target Output / Layer
1. Raw Extraction	IoT Telematics Streams & SAP Work Orders	Ingestion of raw sensor CSVs (`fact_fleet_telematics`) and maintenance logs (`fact_sap_work_orders`).	Raw Staging Layer
2. Python Engineering	Pandas & NumPy Processing Engine	Cleansing -999 signal loss, metric unit conversions (°F → °C, PSI → Bar), and interval matching via `merge_asof`.	Cleansed Data Mart (`_clean`)
3. Analytics Modeling	Power BI Engine & Enterprise Star-Schema	1:∗ Relationship alignment across `Dim_Calendar` and `dim_equipment` with dynamic DAX evaluation.	Executive Dashboards & Predictive Tools

2. DATA SCHEMAS & GOVERNANCE RULES

2.1 Table Schemas Specification

Table Name	Entity Type	Field Name	Data Type	Primary / Foreign Key	Key Description & Constraints
fact_fleet_telematics_clean	Fact (IoT Stream)	equipment_id	VARCHAR	Foreign Key	Associated machine identifier (e.g., EQ-CAT-390F-01).
		timestamp	DATETIME	Composite Key	High-frequency sensor ping timestamp.
		engine_temp_c	FLOAT	Attributes	Cleansed engine coolant temperature in Celsius (°C).
		hydraulic_pressure_bar	FLOAT	Attributes	Cleansed hydraulic line pressure in Bar.
		fuel_burn_rate_lhr	FLOAT	Attributes	Fuel consumption rate (Liters/Hour).
		discrepancy_flag	INTEGER	Audit Flag	1 = Active fuel burn during open SAP WO; 0 = Verified.
fact_sap_work_orders_clean	Fact (EAM Maintenance)	work_order_id	VARCHAR	Primary Key	Unique SAP Work Order number.
		equipment_id	VARCHAR	Foreign Key	Foreign key referencing master asset.
		work_order_type	VARCHAR	Attributes	Maintenance type (Planned vs. Unplanned).
		start_timestamp	DATETIME	Attributes	Official repair check-in time.
		end_timestamp	DATETIME	Attributes	Official repair closure time.
		downtime_hours	FLOAT	Metric	Total duration out of service.
		parsed_component_catego…	VARCHAR	Attributes	System category (Engine, Hydraulic, Drivetrain, Inspection).
dim_equipment	Dimension (Asset Master)	equipment_id	VARCHAR	Primary Key	Master asset key.
		asset_model	VARCHAR	Attributes	Machine classification (Cat 390F, Cat 797F, Cat 994K, Cat D11).

Table Name	Entity Type	Field Name	Data Type	Primary / Foreign Key	Key Description & Constraints
		`site_location`	VARCHAR	Attributes	Mine site (`Fort Hills`, `Kearl Oil Sands`, `Red Chris`, `Highvale`).

2.2 Data Quality & Governance Transformation Rules

Governance Layer	Rule Description	Technical Implementation	Impact on Business Analysis
Signal Validation	Rejection of -999 transmission error codes.	Linear interpolation via Pandas `.replace(-999, np.nan)` & `.interpolate()`.	Prevents corrupted temperature and pressure spikes in operational baselines.
Unit Normalization	Standardization of °F → °C and PSI → Bar.	`engine_temp_c = (engine_temp_f - 32) * 5/9hydraulic_pressure_bar = hydraulic_pressure_psi * 0.0689476`	Aligns telematics metrics across international site locations and machine models.
Reconciliation Audit	Flags active fuel burn (> 5 L/hr) during active SAP work orders.	Interval matching using `pd.merge_asof()`.	Isolates false equipment availability figures and identifies delayed SAP work order closures.

3. PYTHON ETL & DATASET DESIGN METHODOLOGY

3.1 Objective of Dataset Construction

The core objective of constructing this custom ETL pipeline was to simulate real-world mining telematics conditions—bridging the gap between raw, unstructured IoT sensor streams and structured Enterprise Asset Management logs. By pairing synthetic telematics pings with official SAP work orders, the pipeline creates an environment to test data governance, audit cross-system discrepancies, and validate predictive failure thresholds under realistic operating conditions.

3.2 Brainstorming & Architecture Thought Process

- **"How do I represent realistic sensor failure modes without corrupting model logic?"** Real-world telemetry feeds suffer from intermittent transmission dropouts and regional unit discrepancies. The dataset needed to contain intentional sensor dropouts and mixed engineering units to test automated cleansing scripts.
- **"How do I audit operational compliance across two independent databases?"** Telematics feeds and SAP maintenance logs record data at different frequencies. To catch "ghost fleet" activity (machinery burning fuel while marked as "In Maintenance"), the ETL pipeline needed to perform backward time-series alignment (`pd.merge_asof`).

- **"How do I establish realistic predictive failure thresholds?"** Component failures rarely occur in a vacuum. To model thermal-hydraulic fatigue, synthetic anomalies were introduced where elevated engine temperatures (> 90.2 °C) coincided with extreme hydraulic pressure spikes (> 192.3 Bar).

3.3 Noise Injection & Technical Solutions

Anomaly / Error Mode Introduced	Operational & Technical Cause	ETL Solution & Resolution Logic
Sensor Signal Loss (-999 Codes)	Network dropouts, satellite jitter, and physical sensor disconnects in remote pits.	Programmatically replaced -999 values with `NaN` and applied linear interpolation (`.interpolate()`) to restore smooth time-series baselines.
Unit Inconsistencies (°F / PSI vs. Metric)	Legacy asset configurations and mixed Caterpillar Product Link firmware defaults.	Enforced automated vector transformations to standardize all engineering metrics to °C and Bar prior to database loading.
Work Order Timestamp Lags ("Ghost Downtime")	Technicians completing maintenance work but delaying the digital closure of SAP work orders.	Implemented `pd.merge_asof()` interval logic. Telemetry pings registering active fuel burn (> 5 L/hr) during an open SAP repair window are automatically flagged with `discrepancy_flag = 1`.

4. STAR-SCHEMA DATA MODELING & COMPLETE DAX MEASURE LIBRARY

4.1 Data Model Architecture

The data model implements a *1: Star-Schema structure** centered around two core fact tables (`fact_fleet_telematics_clean` and `fact_sap_work_orders_clean`) linked to shared dimension tables (`dim_equipment` and `Dim_Calendar`).

- **Filter:** Slicers selected on `Dim_Calendar` or `dim_equipment` filter both telemetry pings and work order records simultaneously, ensuring seamless cross-filtering across KPI cards, scatter plots, and Pareto charts.

4.2 Complete DAX Measure Library

Measure Name	Business Purpose & Description	Production DAX Formulation
Fleet Physical Availability (%)	Evaluates net machine operating hours against total available calendar hours.	`Fleet_Physical_Availability_% =VAR Total_Available_Hours = COUNTROWS('Dim_Calendar') * 24VAR Total_Downtime_Hours = SUM('fact_sap_work_orders_clean'[downtime_hours])VAR Operating_Hours = Total_Available_Hours - Total_Downtime_HoursRETURN DIVIDE(Operating_Hours, Total_Available_Hours, 0) * 100`
Mean Time Between Failures (MTBF)	Measures average operating runtime (in hours) achieved between unplanned breakdown events.	`MTBF_Hours =VAR Total_Operating_Hours = (COUNTROWS('Dim_Calendar') * 24) - SUM('fact_sap_work_orders_clean'[downtime_hours])VAR Unplanned_Failures = CALCULATE(COUNTROWS('fact_sap_work_orders_clean'), 'fact_sap_work_orders_clean'[work_order_type] = "Unplanned")RETURN DIVIDE(Total_Operating_Hours, Unplanned_Failures, 0)`
Mean Time To Repair (MTTR)	Measures average shop repair duration (in hours) required to resolve unplanned failure events.	`MTTR_Hours =VAR Total_Unplanned_Downtime = CALCULATE(SUM('fact_sap_work_orders_clean'[downtime_hours]), 'fact_sap_work_orders_clean'[work_order_type] = "Unplanned")VAR Unplanned_Failures =`

Measure Name	Business Purpose & Description	Production DAX Formulation
		`CALCULATE(COUNTROWS('fact_sap_work_orders_clean'), 'fact_sap_work_orders_clean'[work_order_type] = "Unplanned")RETURN DIVIDE(Total_Unplanned_Downtime, Unplanned_Failures, 0)`
Data Integrity Score (%)	Audits data governance compliance by measuring the ratio of verified telemetry pings against flagged discrepancies.	`Data_Integrity_Score_% =VAR Total_Telemetry_Pings = COUNTROWS('fact_fleet_telematics_clean')VAR Flagged_Discrepancy_Pings = CALCULATE(COUNTROWS('fact_fleet_telematics_clean'), 'fact_fleet_telematics_clean'[discrepancy_flag] = 1)RETURN DIVIDE(Total_Telemetry_Pings - Flagged_Discrepancy_Pings, Total_Telemetry_Pings, 1) * 100`

5. TECHNICAL ROADMAP & FUTURE TOOL ENHANCEMENTS

To scale this platform from a prototype to an enterprise production analytics suite, several cloud, engineering, and machine learning tool integrations are planned across the architecture:

Platform Layer	Target Enterprise Tool / Technology	Technical Integration Purpose & Enhancements	Target Business Impact
Data Orchestration	**n8n / Apache Airflow**	Replace manual Python staging with automated workflow orchestration. Schedule automated trigger jobs to pull raw VIMS/Product Link telemetry and SAP API logs on an hourly cadence.	Eliminates manual ETL execution; ensures real-time telemetry availability for operational dispatch teams.

Platform Layer	Target Enterprise Tool / Technology	Technical Integration Purpose & Enhancements	Target Business Impact
Cloud Storage & Warehousing	**Microsoft Azure / PostgreSQL / Snowflake**	Migrate flat CSV files into a centralized SQL data warehouse on Azure Synapse / Snowflake using star-schema staging.	Enables sub-second SQL queries across billions of telemetry rows and enforces strict database role-based access security.
Predictive Machine Learning	**Python (Scikit-Learn / Azure ML / XGBoost)**	Implement multivariate classification models (Logistic Regression / XGBoost) trained on historical thermal-hydraulic boundaries to assign continuous "Failure Probability Scores" per machine.	Moves beyond fixed static limits (> 90.2 °C) to dynamic multi-sensor failure probability predictions.
Bi-directional Sync	**SAP EAM Webhooks & Power Automate**	Build automated Power Automate alerts and webhook calls to push "High Risk Anomaly" alerts directly back into SAP as draft Work Requests.	Automates work order creation before field equipment experiences physical component failure.
Advanced BI Features	**Power BI Tabular Editor & Field Parameters**	Implement Field Parameters, Calculation Groups, and incremental refresh in Power BI Desktop / Service.	Enables dynamic measure selection and optimizes dataset memory usage for fast report load times.