

C0 2 – ASSESSMENT TOOL 3 – SOLUTION

NAME : R S JAHNAVI

REGISTER NO : 192371056

COURSE CODE : CSA1717

COURSE NAME : ARTIFICIAL INTELLIGENCE

Question 1: Dry Run of A* Search Algorithm

Graph Summary

Edge	Co st
A–B	2
A–C	4
B–C	3
B–D	7
B–E	2
D–E	2
D–G	2
E–G	2

Heuristic values $h(n)$:

Node	$h(n)$
A	7
B	6
C	4
D	3
E	2
G	0

Formula: $f(n) = g(n) + h(n)$, where $g(n)$ = actual cost from start to n ,
 $h(n)$ = estimated cost from n to goal.

Iteration-by-Iteration Trace

Iteration 1

- **Current Node:** A
- **Open List:** [A]
- **Closed List:** []
- $g(A) = 0$, $h(A) = 7$, **$f(A) = 7$**

Expand A $\rightarrow$ neighbors B (cost 2), C (cost 4)

- $g(B) = 0 + 2 = 2$, $h(B) = 6$, $f(B) = 8$
- $g(C) = 0 + 4 = 4$, $h(C) = 4$, $f(C) = 8$

Move A to Closed List.

Iteration 2

- **Open List:** [B(f=8), C(f=8)]
- **Closed List:** [A]

Both B and C have $f = 8$ (tie). By convention, pick alphabetically/first inserted → **Current Node: B**

- $g(B) = 2$, $h(B) = 6$, **$f(B) = 8$**

Expand B → neighbors A(visited), C, D, E

- $g(C)$ via B = $2 + 3 = 5$ → worse than existing $g(C)=4$, **discard**
- $g(D) = 2 + 7 = 9$, $h(D) = 3$, $f(D) = 12$
- $g(E) = 2 + 2 = 4$, $h(E) = 2$, $f(E) = 6$

Move B to Closed List.

Iteration 3

- **Open List:** [E(f=6), C(f=8), D(f=12)]
- **Closed List:** [A, B]
- **Current Node:** E (lowest f)
- $g(E) = 4$, $h(E) = 2$, **$f(E) = 6$**

Expand E → neighbors B(visited), C, D, G

- $g(C)$ via E = $4 + 3 = 7$ → worse than 4, discard
- $g(D)$ via E = $4 + 2 = 6$ → better than 9! Update: $g(D) = 6$, $f(D) = 6 + 3 = 9$
- $g(G) = 4 + 2 = 6$, $h(G) = 0$, $f(G) = 6$

Move E to Closed List.

Iteration 4

- **Open List:** [G(f=6), C(f=8), D(f=9)]
- **Closed List:** [A, B, E]
- **Current Node:** G (lowest f)
- $g(G) = 6, h(G) = 0, f(G) = 6$

G is the goal node → stop.

Summary Table

Iteration Current g(n) h(n) f(n) Open List Closed List

1	A	0	7	7	[A]	{ }
2	B	2	6	8	[B, C]	{A}
3	E	4	2	6	[E, C, D]	{A, B}
4	G	6	0	6	[G, C, D]	{A, B, E}

Result

Optimal Path: $A \rightarrow B \rightarrow E \rightarrow G$


Cost breakdown: $A \rightarrow B (2) + B \rightarrow E (2) + E \rightarrow G (2)$

Total Path Cost = $2 + 2 + 2 = 6$

This matches $f(G) = 6$, confirming the path is optimal (since $h(G) = 0$, $g(G)$ at goal = actual total cost).

Question 2: Dry Run of Minimax with Alpha-Beta Pruning

Tree Structure



Initial call: $\text{alphabeta}(\text{MAX}, \alpha = -\infty, \beta = +\infty)$

Step-by-Step Evaluation (Left to Right)

Branch 1: MIN1 (children 3, 5, 6)

MIN1 starts with $\alpha = -\infty, \beta = +\infty$

Leaf 3: value = 3 $\rightarrow$ MIN1's current best (β) = $\min(+\infty, 3) = 3$

- Check pruning: $\beta(3) \leq \alpha(-\infty)$? No $\rightarrow$ continue

Leaf 5: value = 5 $\rightarrow$ MIN1's value = $\min(3, 5) = 3$ (no change, 5 is worse for MIN)

- β stays 3
- Check pruning: $\beta(3) \leq \alpha(-\infty)$? No $\rightarrow$ continue

Leaf 6: value = 6 $\rightarrow$ MIN1's value = $\min(3, 6) = 3$ (no change)

- β stays 3

MIN1 finishes all children $\rightarrow$ MIN1 = 3

Back at MAX: $\alpha = \max(-\infty, 3) = 3$

Branch 2: MIN2 (children 9, 1, 2)

MIN2 starts with $\alpha = 3$ (inherited from MAX), $\beta = +\infty$

Leaf 9: value = 9 $\rightarrow$ MIN2's value = $\min(+\infty, 9) = 9$

- Check pruning: $\beta(9) \leq \alpha(3)$? No $\rightarrow$ continue

Leaf 1: value = 1 $\rightarrow$ MIN2's value = $\min(9, 1) = 1$

- β updates to 1
- Check pruning: $\beta(1) \leq \alpha(3)$? **YES!** $\rightarrow$ **PRUNE remaining child (leaf value 2)**
- MIN2 stops here since MIN will never let this branch exceed 1, and MAX already has a guaranteed 3 elsewhere — so this branch is worthless to explore further.

MIN2 = 1 (final value, leaf "2" is never evaluated)

Back at MAX: $\alpha = \max(3, 1) = 3$ (no change, 3 is still better for MAX)

Alpha-Beta Table

Node	α (start)	β (start)	Value Computed	α (end)	β (end)	Pruned?
MIN1	$-\infty$	$+\infty$	$\min(3,5,6) = 3$	$-\infty$	3	No
MAX (after MIN1)	$-\infty$	$+\infty$	—	3	$+\infty$	—
MIN2	3	$+\infty$	9 $\rightarrow$ 1 (pruned after)	3	1	Yes
MAX (final)	3	$+\infty$	$\max(3, 1) = 3$	3	$+\infty$	—

Why the Pruning Happened

At MIN2, after seeing leaf **1**, MIN2's value can only stay at 1 or go lower (MIN always picks the smallest). Since MAX already has a guaranteed score of **3** from MIN1, and MIN2 can never produce anything higher than 1 at this point, there is **no way MAX would ever choose MIN2's branch** over MIN1. So exploring the third leaf (value **2**) under MIN2 is pointless — it's pruned.

This is a classic **beta cutoff**: $\beta \leq \alpha$ triggered inside a MIN node.

Result

- **Best Move for MAX:** Choose the **MIN1 branch** (value = 3)
- **Final Minimax Value:** 3
- **Pruned Nodes:** Leaf value **2** (the third child of MIN2) — never evaluated due to alpha-beta cutoff