Free Fire Legal Headshot Panel — HTML Code

Copy the code below into a file named **index.html** and open it in a browser. This is a standalone settings helper; it does not modify Free Fire or guarantee headshots.

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<title>FF Headshot Settings Panel</title>
<style>
* { box-sizing: border-box; }
body {
  margin: 0; padding: 20px; font-family: Arial, sans-serif;
  background: #10131c; color: white;
}
.panel {
  max-width: 450px; margin: auto; padding: 22px;
  background: #1c2230; border: 1px solid #ff4d4d;
  border-radius: 16px;
}
h1 { text-align: center; color: #ff5757; font-size: 24px; }
.subtitle { text-align: center; color: #c6cad4; font-size: 13px; }
.setting { margin: 22px 0; }
.setting label {
  display: flex; justify-content: space-between;
  margin-bottom: 12px; font-weight: bold;
}
input[type="range"] { width: 100%; accent-color: #ff4d4d; }
button {
  width: 100%; padding: 13px; margin-top: 10px; border: none;
  border-radius: 8px; background: #ff4545; color: white;
  font-size: 16px; font-weight: bold; cursor: pointer;
}
.secondary { background: #30394b; }
.status { margin-top: 15px; color: #8cffb0; text-align: center; }
.note { margin-top: 20px; color: #c6cad4; font-size: 12px; line-height: 1.6; }
</style>
</head>
<body>
<div class="panel">
<h1>HEADSHOT PANEL</h1>
<p class="subtitle">FREE FIRE LEGAL SETTINGS TOOL</p>
<div id="settings"></div>
<button onclick="saveSettings()">SAVE SETTINGS</button>
<button class="secondary" onclick="resetSettings()">RESET DEFAULTS</button>
<p class="status" id="status"></p>
<p class="note">This is a standalone settings helper. It does not modify Free Fire or guarantee headshots. Adjust settings manually inside the
</div>
<script>
const defaults = {
  general: 190, redDot: 185, scope2x: 175,
  scope4x: 160, sniper: 100, freeLook: 150
};
const labels = {
  general: "General Sensitivity", redDot: "Red Dot",
  scope2x: "2x Scope", scope4x: "4x Scope",
  sniper: "Sniper Scope", freeLook: "Free Look"
};
function renderSettings(values) {
  const container = document.getElementById("settings");
  container.innerHTML = "";
  Object.keys(defaults).forEach(key => {
    const value = values[key] ?? defaults[key];
    const div = document.createElement("div");
    div.className = "setting";
    const label = document.createElement("label");
    label.htmlFor = key;
    label.textContent = labels[key];
    const number = document.createElement("span");
    number.id = key + "Value";
    number.textContent = value;
    label.appendChild(number);
    const slider = document.createElement("input");
    slider.type = "range"; slider.id = key;
    slider.min = 0; slider.max = 200; slider.value = value;
    slider.addEventListener("input", () => {
      number.textContent = slider.value;
    });
    div.appendChild(label); div.appendChild(slider);
    container.appendChild(div);
  });
}
function saveSettings() {
  const values = {};
  Object.keys(defaults).forEach(key => {
    values[key] = Number(document.getElementById(key).value);
  });
  localStorage.setItem("ffLegalSettings", JSON.stringify(values));
  document.getElementById("status").textContent =
    "Settings saved successfully!";
}
function resetSettings() {
```

```
  renderSettings(defaults);
  document.getElementById("status").textContent =
    "Defaults restored. Tap Save Settings to keep them.";
}
let saved = {};
try {
  saved = JSON.parse(localStorage.getItem("ffLegalSettings") || "{}") || {};
} catch (error) { saved = {}; }
renderSettings({...defaults, ...saved});
</script>
</body>
</html>
```