

# GE23131-Programming Using C-2024





```
1 |#includekstaio.n>
    #include<string.h>
 3 v int main(){
4
       char str[1000];
5
       scanf("%s",str);
6
       int arr[10]={0},temp;
       for(int i=0;str[i]!='\0';i++){
7 ,
 8
           temp=str[i]-'0';
           if(temp<=9&&temp>=0){
 9 ,
10
               arr[temp]++;
11
12
13
       for(int i=0;i<10;i++){
14
           printf("%d ",arr[i]);
15
16 }
```

	Input	Ехре	ect	ed						G	ot									
<b>~</b>	a11472o5t6	0 2	1 6	0 1	1	1	1	0	0	0	2	1	0	1	1	1	1	0	0	~
<b>~</b>	lw4n88j12n1	0 2	1 6	0 1	0	0	0	2	0	0	2	1	0	1	0	0	0	2	0	~
<b>~</b>	1v888861256338ar0ekk	1 1	1 2	2 0	1	2	0	5	0	1	1	1	2	0	1	2	0	5	0	~

Passed all tests! <

# Question **2**Correct

Marked out of 1.00

Flag question

Today, Monk went for a walk in a garden. There are many trees in the garden and each tree has an English alphabet on it. While Monk was walking, he noticed that all trees with vowels on it are not in good state. He decided to take care of them. So, he asked you to tell him the count of such trees in the garden.

Note: The following letters are vowels: 'A', 'E', 'I', 'O', 'U', 'a', 'e', 'i', 'o' and 'u'.

# Input:

The first line consists of an integer T denoting the number of test cases.

Each test case consists of only one string, each character of string denoting the alphabet (may be lowercase or uppercase) on a tree in the garden.

# Output:

For each test case, print the count in a new line.

### Constraints:

```
1 \le T \le 10

1 \le length of string \le 10^5
```

#### SAMPLE INPUT

```
2
nBBZLaosnm
JHklsnZtTL
SAMPLE OUTPUT
2
Explanation
In test case 1, a and o are the only vowels. So, count=2
Answer: (penalty regime: 0 %)
   1 #include<stdio.h>
   2
      #include<string.h>
   3 v int main(){
          int T;
          scanf("%d",&T);
          while(T--){
   7
             int count=0;
   8
              char str[100];
   9
              scanf("%s",str);
              for(int i=0;str[i]!='\0';i++){
   10
                 char ch=str[i];
   11
                 if(ch=='A'||ch=='E'||ch=='I'||ch=='0'||ch=='U'||ch=='a'||ch=='e'||ch=='i'||ch=='o'||ch=='u')
   12
  13
                 count+=1;
  14
   15
              printf("%d\n",count);
   16
   17 }
```

	Input	Expected	Got	
~	2 nBBZLaosnm JHkIsnZtTL	2	2	~
~	2 nBBZLaosnm JHkIsnZtTL	2	2	~

Passed all tests! 🗸

Question **3**Correct
Marked out of 1.00

₹ Flag question

Given a sentence, s, print each word of the sentence in a new line.

Input Format

The first and only line contains a sentence, s. Constraints  $1 \le len(s) \le 1000$ **Output Format** Print each word of the sentence in a new line. Sample Input 0 This is C

# Sample Output 0

This is

C

# Explanation 0

In the given string, there are three words ["This", "is", "C"]. We have to print each of these words in a new line.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
8
9
      printf("\n");
10
11
    return 0;
12 }
```

	Input	Expected	Got	
~	This is C	This	This	~
		is	is	
		С	С	

~	Learning C is fun	Learning C is fun	Learning C is fun	~
Danco	fall tests!			

Question 4
Correct
Marked out of 1.00
Flag question

# **Input Format**

You are given two strings, **a** and **b**, separated by a new line. Each string will consist of lower case Latin characters ('a'-'z').

#### **Output Format**

In the first line print two space-separated integers, representing the length of  $\boldsymbol{a}$  and  $\boldsymbol{b}$  respectively.

In the second line print the string produced by concatenating  $\boldsymbol{a}$  and  $\boldsymbol{b}$  ( $\boldsymbol{a} + \boldsymbol{b}$ ).

In the third line print two strings separated by a space, a' and b'. a' and b' are the same as a and b, respectively, except that their first characters are swapped.

# Sample Input

abcd

ef

#### Sample Output

42

abcdef

ebcd af

# Explanation

```
a = "abcd"
```

b = "ef"

|a| = 4

|b| = 2

a + b = "abcdef"

a' = "ebcd"

b' = "af"

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
#include<string.h>
int main(){
    char str1[100],t;
    char str2[100];
    scanf("%s",str1);
```

	Input	Expected	Got	
~	abcd ef	4 2 abcdef ebcd af	4 2 abcdef ebcd af	<b>~</b>

Passed all tests! 🗸

Finish review