

Cadence SKILL Language Reference

**Product Version IC23.1
January 2024**

© 2024 Cadence Design Systems, Inc.
Printed in the United States of America.

Cadence Design Systems, Inc. (Cadence), 2655 Seely Ave., San Jose, CA 95134, USA.

Open SystemC, Open SystemC Initiative, OSCI, SystemC, and SystemC Initiative are trademarks or registered trademarks of Open SystemC Initiative, Inc. in the United States and other countries and are used with permission.

Trademarks: Trademarks and service marks of Cadence Design Systems, Inc. contained in this document are attributed to Cadence with the appropriate symbol. For queries regarding Cadence's trademarks, contact the corporate legal department at the address shown above or call 800.862.4522. All other trademarks are the property of their respective holders.

Restricted Permission: This publication is protected by copyright law and international treaties and contains trade secrets and proprietary information owned by Cadence. Unauthorized reproduction or distribution of this publication, or any portion of it, may result in civil and criminal penalties. Except as specified in this permission statement, this publication may not be copied, reproduced, modified, published, uploaded, posted, transmitted, or distributed in any way, without prior written permission from Cadence. Unless otherwise agreed to by Cadence in writing, this statement grants Cadence customers permission to print one (1) hard copy of this publication subject to the following conditions:

1. The publication may be used only in accordance with a written agreement between Cadence and its customer.
2. The publication may not be modified in any way.
3. Any authorized copy of the publication or portion thereof must include all original copyright, trademark, and other proprietary notices and this permission statement.
4. The information contained in this document cannot be used in the development of like products or software, whether for internal or external use, and shall not be used for the benefit of any other party, whether or not for consideration.

Disclaimer: Information in this publication is subject to change without notice and does not represent a commitment on the part of Cadence. Except as may be explicitly set forth in such agreement, Cadence does not, and expressly disclaims, any representations or warranties as to the completeness, accuracy or usefulness of the information contained in this document. Cadence does not warrant that use of such information will not infringe any third party rights, nor does Cadence assume any liability for damages or costs of any kind that may result from use of such information.

Cadence is committed to using respectful language in our code and communications. We are also active in the removal and replacement of inappropriate language from existing content. This product documentation may however contain material that is no longer considered appropriate but still reflects long-standing industry terminology. Such content will be addressed at a time when the related software can be updated without end-user impact.

Restricted Rights: Use, duplication, or disclosure by the Government is subject to restrictions as set forth in FAR52.227-14 and DFAR252.227-7013 et seq. or its successor

Contents

1

| | |
|---|----|
| List Functions | 19 |
| <u>append</u> | 20 |
| <u>append1</u> | 22 |
| <u>caar, caaar, caadr, cadr, caddr, cdar, cddr, ...</u> | 23 |
| <u>car</u> | 25 |
| <u>cdr</u> | 26 |
| <u>cons</u> | 27 |
| <u>constar</u> | 29 |
| <u>copy</u> | 31 |
| <u>dtpr</u> | 33 |
| <u>last</u> | 34 |
| <u>lconc</u> | 35 |
| <u>length</u> | 36 |
| <u>index</u> | 38 |
| <u>list</u> | 39 |
| <u>listp</u> | 40 |
| <u>nconc</u> | 41 |
| <u>ncons</u> | 43 |
| <u>nth</u> | 44 |
| <u>nthcdr</u> | 46 |
| <u>nthelem</u> | 47 |
| <u>pairp</u> | 48 |
| <u>range</u> | 49 |
| <u>remd</u> | 50 |
| <u>remdq</u> | 52 |
| <u>remove</u> | 53 |
| <u>removeListDuplicates</u> | 55 |
| <u>remq</u> | 56 |
| <u>reverse</u> | 57 |
| <u>rplaca</u> | 58 |

Cadence SKILL Language Reference

| | |
|---------------|----|
| <u>rplacd</u> | 59 |
| <u>setcar</u> | 60 |
| <u>setcdr</u> | 61 |
| <u>subst</u> | 62 |
| <u>tailp</u> | 63 |
| <u>tconc</u> | 65 |
| <u>xcons</u> | 67 |
| <u>xCoord</u> | 68 |
| <u>yCoord</u> | 69 |

2

Data Structures 71

| | |
|--------------------------|----|
| <u>arrayp</u> | 72 |
| <u>arrayref</u> | 73 |
| <u>assoc, assq, assv</u> | 74 |
| <u>declare</u> | 76 |
| <u>defprop</u> | 78 |
| <u>defstruct</u> | 79 |
| <u>defstructp</u> | 81 |
| <u>defvar</u> | 82 |
| <u>makeTable</u> | 83 |
| <u>makeVector</u> | 85 |
| <u>setarray</u> | 86 |
| <u>tablep</u> | 88 |
| <u>type, typep</u> | 89 |
| <u>vector</u> | 91 |
| <u>vectorp</u> | 92 |

3

Data Operator Functions 93

| | |
|--------------------------|-----|
| <u>alphaNumCmp</u> | 94 |
| <u>concat</u> | 96 |
| <u>copy <name></u> | 98 |
| <u>copyDefstructDeep</u> | 99 |
| <u>get</u> | 101 |

Cadence SKILL Language Reference

| | |
|----------------------------|-----|
| <u>getSG</u> | 103 |
| <u>getq</u> | 104 |
| <u>getqq</u> | 106 |
| <u>importSkillVar</u> | 108 |
| <u>integerp</u> | 110 |
| <u>make <name></u> | 111 |
| <u>otherp</u> | 112 |
| <u>plist</u> | 113 |
| <u>popf</u> | 114 |
| <u>postArrayDec</u> | 115 |
| <u>postArrayInc</u> | 117 |
| <u>postArraySet</u> | 119 |
| <u>postdecrement</u> | 121 |
| <u>postincrement</u> | 122 |
| <u>preArrayDec</u> | 123 |
| <u>preArrayInc</u> | 124 |
| <u>preArraySet</u> | 125 |
| <u>predecrement</u> | 127 |
| <u>preincrement</u> | 128 |
| <u>pushf</u> | 129 |
| <u>putprop</u> | 130 |
| <u>putpropq</u> | 131 |
| <u>putpropqq</u> | 133 |
| <u>quote</u> | 135 |
| <u>remprop</u> | 136 |
| <u>rotatef</u> | 137 |
| <u>set</u> | 138 |
| <u>setf</u> | 140 |
| <u>setf <helper></u> | 142 |
| <u>setguard</u> | 143 |
| <u>setplist</u> | 146 |
| <u>setq</u> | 148 |
| <u>setSG</u> | 150 |
| <u>symbolp</u> | 151 |
| <u>symeval</u> | 152 |
| <u>symstrp</u> | 153 |

4

| | |
|---|-----|
| <u>Type Conversion Functions</u> | 155 |
| <u>charToInt</u> | 156 |
| <u>intToChar</u> | 157 |
| <u>listToVector</u> | 158 |
| <u>stringToFunction</u> | 159 |
| <u>stringToSymbol</u> | 161 |
| <u>stringToTime</u> | 162 |
| <u>symbolToString</u> | 163 |
| <u>tableToList</u> | 164 |
| <u>timeToString</u> | 165 |
| <u>timeToTm</u> | 166 |
| <u>tmToTime</u> | 168 |
| <u>vectorToList</u> | 170 |

5

| | |
|--------------------------------------|-----|
| <u>String Functions</u> | 171 |
| <u>blankstrp</u> | 172 |
| <u>buildString</u> | 173 |
| <u>getchar</u> | 175 |
| <u>index</u> | 177 |
| <u>lowerCase</u> | 179 |
| <u>lsprintf</u> | 180 |
| <u>nindex</u> | 181 |
| <u>outstringp</u> | 182 |
| <u>parseString</u> | 183 |
| <u>pcreCompile</u> | 186 |
| <u>pcreExecute</u> | 189 |
| <u>pcreGenCompileOptBits</u> | 191 |
| <u>pcreGenExecOptBits</u> | 195 |
| <u>pcreGetRecursionLimit</u> | 198 |
| <u>pcreListCompileOptBits</u> | 199 |
| <u>pcreListExecOptBits</u> | 200 |
| <u>pcreMatchAssocList</u> | 201 |

Cadence SKILL Language Reference

| | |
|-----------------------------|-----|
| <u>pcrMatchList</u> | 203 |
| <u>pcrMatchp</u> | 205 |
| <u>pcrObjectp</u> | 207 |
| <u>pcrPrintLastMatchErr</u> | 208 |
| <u>pcrReplace</u> | 210 |
| <u>pcrSetRecursionLimit</u> | 212 |
| <u>pcrSubpatCount</u> | 213 |
| <u>pcrSubstitute</u> | 214 |
| <u>readstring</u> | 217 |
| <u>rexCompile</u> | 219 |
| <u>rexExecute</u> | 222 |
| <u>rexMagic</u> | 224 |
| <u>rexMatchAssocList</u> | 226 |
| <u>rexMatchList</u> | 228 |
| <u>rexMatchp</u> | 230 |
| <u>rexReplace</u> | 232 |
| <u>rexSubstitute</u> | 234 |
| <u>rindex</u> | 236 |
| <u>sprintf</u> | 237 |
| <u>strcat</u> | 239 |
| <u>strcmp</u> | 241 |
| <u>stringp</u> | 243 |
| <u>strlen</u> | 244 |
| <u>strncat</u> | 245 |
| <u>strncmp</u> | 247 |
| <u>strpbrk</u> | 249 |
| <u>substring</u> | 251 |
| <u>upperCase</u> | 253 |

6

| | |
|-----------------------------|-----|
| <u>Arithmetic Functions</u> | 255 |
| <u>abs</u> | 256 |
| <u>add1</u> | 257 |
| <u>atof</u> | 258 |
| <u>atoi</u> | 260 |

Cadence SKILL Language Reference

| | |
|-------------------------|-----|
| <u>ceiling</u> | 262 |
| <u>defMathConstants</u> | 263 |
| <u>difference</u> | 266 |
| <u>evenp</u> | 267 |
| <u>exp</u> | 268 |
| <u>expt</u> | 269 |
| <u>fix</u> | 270 |
| <u>fixp</u> | 272 |
| <u>fix2</u> | 274 |
| <u>float</u> | 275 |
| <u>floatp</u> | 276 |
| <u>floor</u> | 277 |
| <u>int</u> | 278 |
| <u>isInfinity</u> | 279 |
| <u>isNaN</u> | 280 |
| <u>leftshift</u> | 281 |
| <u>log</u> | 282 |
| <u>log10</u> | 283 |
| <u>max</u> | 284 |
| <u>min</u> | 285 |
| <u>minus</u> | 286 |
| <u>minusp</u> | 287 |
| <u>mod</u> | 288 |
| <u>modf</u> | 289 |
| <u>modulo</u> | 290 |
| <u>nearlyEqual</u> | 292 |
| <u>negativep</u> | 294 |
| <u>oddp</u> | 295 |
| <u>onep</u> | 296 |
| <u>plus</u> | 297 |
| <u>plusp</u> | 298 |
| <u>quotient</u> | 299 |
| <u>random</u> | 300 |
| <u>realp</u> | 301 |
| <u>remainder</u> | 302 |
| <u>rightshift</u> | 304 |

Cadence SKILL Language Reference

| | |
|--------------------|-----|
| <u>round</u> | 305 |
| <u>round2</u> | 306 |
| <u>sort</u> | 307 |
| <u>sortcar</u> | 309 |
| <u>sqrt</u> | 311 |
| <u>srandom</u> | 312 |
| <u>sub1</u> | 313 |
| <u>times</u> | 314 |
| <u>truncate</u> | 315 |
| <u>xdifference</u> | 316 |
| <u>xplus</u> | 317 |
| <u>xquotient</u> | 318 |
| <u>xtimes</u> | 319 |
| <u>zerop</u> | 320 |
| <u>zxttd</u> | 321 |

7

Bitwise Operator Functions 323

| | |
|----------------------|-----|
| <u>band</u> | 324 |
| <u>bitfield</u> | 325 |
| <u>bitfield1</u> | 326 |
| <u>bband</u> | 327 |
| <u>bnor</u> | 328 |
| <u>bnot</u> | 329 |
| <u>bor</u> | 330 |
| <u>bxnor</u> | 331 |
| <u>bxor</u> | 332 |
| <u>setqbitfield</u> | 333 |
| <u>setqbitfield1</u> | 335 |

8

Trigonometric Functions 337

| | |
|-------------|-----|
| <u>acos</u> | 338 |
| <u>asin</u> | 339 |
| <u>atan</u> | 340 |

Cadence SKILL Language Reference

| | |
|--------------|-----|
| <u>atan2</u> | 341 |
| <u>cos</u> | 343 |
| <u>sin</u> | 344 |
| <u>tan</u> | 345 |

9

Logical and Relational Functions 347

| | |
|---------------------------|-----|
| <u>alphalessp</u> | 348 |
| <u>and</u> | 350 |
| <u>compareTime</u> | 352 |
| <u>eq</u> | 353 |
| <u>equal</u> | 355 |
| <u>eqv</u> | 357 |
| <u>geqp</u> | 359 |
| <u>greaterp</u> | 361 |
| <u>leqp</u> | 363 |
| <u>lessp</u> | 365 |
| <u>member, memq, memv</u> | 367 |
| <u>neq</u> | 369 |
| <u>nequal</u> | 371 |
| <u>null</u> | 373 |
| <u>numberp</u> | 374 |
| <u>or</u> | 375 |
| <u>sxtd</u> | 377 |

10

Flow Control Functions 379

| | |
|----------------|-----|
| <u>case</u> | 380 |
| <u>caseq</u> | 383 |
| <u>catch</u> | 385 |
| <u>cond</u> | 387 |
| <u>decode</u> | 389 |
| <u>do</u> | 391 |
| <u>exists</u> | 394 |
| <u>existss</u> | 396 |

Cadence SKILL Language Reference

| | |
|----------------------|-----|
| <u>for</u> | 398 |
| <u>fors</u> | 400 |
| <u>forall</u> | 402 |
| <u>foralls</u> | 404 |
| <u>foreach</u> | 406 |
| <u>foreachs</u> | 409 |
| <u>if</u> | 412 |
| <u>go</u> | 414 |
| <u>map</u> | 416 |
| <u>mapc</u> | 418 |
| <u>mapcan</u> | 420 |
| <u>mapcar</u> | 422 |
| <u>mapcon</u> | 424 |
| <u>mapinto</u> | 426 |
| <u>maplist</u> | 428 |
| <u>not</u> | 430 |
| <u>regExitAfter</u> | 431 |
| <u>regExitBefore</u> | 432 |
| <u>remExitProc</u> | 434 |
| <u>return</u> | 435 |
| <u>setof</u> | 437 |
| <u>setofs</u> | 439 |
| <u>throw</u> | 441 |
| <u>unless</u> | 442 |
| <u>when</u> | 444 |
| <u>while</u> | 446 |

11

Input Output Functions 447

| | |
|-----------------|-----|
| <u>close</u> | 448 |
| <u>compress</u> | 449 |
| <u>display</u> | 450 |
| <u>drain</u> | 451 |
| <u>ed</u> | 453 |
| <u>edi</u> | 454 |

Cadence SKILL Language Reference

| | |
|------------------------------|-----|
| <u>edit</u> | 455 |
| <u>edl</u> | 457 |
| <u>encrypt</u> | 458 |
| <u>expandMacroDeep</u> | 460 |
| <u>fileLength</u> | 461 |
| <u>fileSeek</u> | 462 |
| <u>fileTell</u> | 464 |
| <u>fileTimeModified</u> | 466 |
| <u>fprintf</u> | 467 |
| <u>fscanf, scanf, sscanf</u> | 471 |
| <u>get_filename</u> | 474 |
| <u>getc</u> | 475 |
| <u>getDirFiles</u> | 476 |
| <u>getOutstring</u> | 477 |
| <u>gets</u> | 478 |
| <u>include</u> | 480 |
| <u>infile</u> | 481 |
| <u>info</u> | 483 |
| <u>inportp</u> | 484 |
| <u>instring</u> | 485 |
| <u>isExecutable</u> | 486 |
| <u>isFile</u> | 488 |
| <u>isFileEncrypted</u> | 490 |
| <u>isFileName</u> | 491 |
| <u>IsLargeFile</u> | 493 |
| <u>isLink</u> | 495 |
| <u>isPortAtEOF</u> | 496 |
| <u>isReadable</u> | 497 |
| <u>isWritable</u> | 499 |
| <u>lineread</u> | 501 |
| <u>linereadstring</u> | 503 |
| <u>load</u> | 504 |
| <u>loadi</u> | 506 |
| <u>loadPort</u> | 508 |
| <u>loadstring</u> | 510 |
| <u>makeTempFileName</u> | 512 |

Cadence SKILL Language Reference

| | |
|-------------------------------|-----|
| <u>newline</u> | 514 |
| <u>numOpenFiles</u> | 515 |
| <u>openportp</u> | 516 |
| <u>outfile</u> | 517 |
| <u>outportp</u> | 519 |
| <u>outstring</u> | 520 |
| <u>portp</u> | 521 |
| <u>pprint</u> | 522 |
| <u>print</u> | 523 |
| <u>printf</u> | 524 |
| <u>printlev</u> | 526 |
| <u>println</u> | 528 |
| <u>putc</u> | 529 |
| <u>read</u> | 530 |
| <u>readTable</u> | 532 |
| <u>renameFile</u> | 534 |
| <u>simplifyFilename</u> | 536 |
| <u>simplifyFilenameUnique</u> | 538 |
| <u>truename</u> | 539 |
| <u>which</u> | 541 |
| <u>write</u> | 543 |
| <u>writeTable</u> | 544 |

12

Core Functions 545

| | |
|-----------------|-----|
| <u>arglist</u> | 546 |
| <u>assert</u> | 547 |
| <u>atom</u> | 549 |
| <u>bcdp</u> | 550 |
| <u>booleanp</u> | 551 |
| <u>boundp</u> | 552 |
| <u>describe</u> | 554 |
| <u>fdoc</u> | 555 |
| <u>gc</u> | 556 |
| <u>gensym</u> | 558 |

Cadence SKILL Language Reference

| | |
|--------------------------|-----|
| <u>getMuffleWarnings</u> | 559 |
| <u>getSkillVersion</u> | 560 |
| <u>get_pname</u> | 561 |
| <u>get_string</u> | 562 |
| <u>getVersion</u> | 563 |
| <u>getWarn</u> | 565 |
| <u>help</u> | 567 |
| <u>inScheme</u> | 569 |
| <u>inSkill</u> | 570 |
| <u>isVarImported</u> | 571 |
| <u>makeSymbol</u> | 572 |
| <u>measureTime</u> | 574 |
| <u>muffleWarnings</u> | 576 |
| <u>needNCells</u> | 577 |
| <u>restoreFloat</u> | 578 |
| <u>saveFloat</u> | 579 |
| <u>schemeTopLevelEnv</u> | 580 |
| <u>setPrompts</u> | 581 |
| <u>sstatus</u> | 583 |
| <u>status</u> | 590 |
| <u>theEnvironment</u> | 591 |
| <u>unbindVar</u> | 594 |

13

Function and Program Structure 595

| | |
|--------------------------|-----|
| <u>addDefstructClass</u> | 596 |
| <u>alias</u> | 598 |
| <u>apply</u> | 599 |
| <u>argc</u> | 601 |
| <u>argv</u> | 603 |
| <u>begin</u> | 605 |
| <u>clearExitProcs</u> | 607 |
| <u>declareLambda</u> | 608 |
| <u>declareNLambda</u> | 609 |
| <u>declareSQNLambda</u> | 610 |

Cadence SKILL Language Reference

| | |
|---------------------------|-----|
| <u>defdynamic</u> | 611 |
| <u>defglobalfun</u> | 612 |
| <u>define</u> | 614 |
| <u>define syntax</u> | 616 |
| <u>defmacro</u> | 617 |
| <u>defsetf</u> | 618 |
| <u>defun</u> | 620 |
| <u>defUserInitProc</u> | 622 |
| <u>destructuringBind</u> | 624 |
| <u>dynamic</u> | 626 |
| <u>dynamicLet</u> | 627 |
| <u>err</u> | 629 |
| <u>error</u> | 631 |
| <u>errset</u> | 633 |
| <u>errsetstring</u> | 635 |
| <u>eval</u> | 637 |
| <u>evalstring</u> | 639 |
| <u>expandMacro</u> | 641 |
| <u>fboundp</u> | 642 |
| <u>flet</u> | 643 |
| <u>funcall</u> | 644 |
| <u>getd</u> | 646 |
| <u>getFnWriteProtect</u> | 647 |
| <u>getFunType</u> | 648 |
| <u>getVarWriteProtect</u> | 649 |
| <u>globalProc</u> | 650 |
| <u>isCallable</u> | 652 |
| <u>isMacro</u> | 653 |
| <u>labels</u> | 654 |
| <u>lambda</u> | 655 |
| <u>let</u> | 656 |
| <u>letrec</u> | 659 |
| <u>letseq</u> | 661 |
| <u>mprocedure</u> | 663 |
| <u>nlambda</u> | 665 |
| <u>nprocedure</u> | 667 |

Cadence SKILL Language Reference

| | |
|---------------------------|-----|
| <u>procedure</u> | 669 |
| <u>procedurep</u> | 673 |
| <u>prog</u> | 674 |
| <u>prog1</u> | 676 |
| <u>prog2</u> | 677 |
| <u>progn</u> | 678 |
| <u>putd</u> | 680 |
| <u>setf_dynamic</u> | 682 |
| <u>setFnWriteProtect</u> | 683 |
| <u>setVarWriteProtect</u> | 684 |
| <u>unalias</u> | 686 |
| <u>unwindProtect</u> | 687 |
| <u>warn</u> | 689 |

14

Environment Functions 691

| | |
|-------------------------|-----|
| <u>cdsGetInstPath</u> | 692 |
| <u>cdsGetToolsPath</u> | 693 |
| <u>cdsPlat</u> | 694 |
| <u>changeWorkingDir</u> | 695 |
| <u>cputime</u> | 697 |
| <u>createDir</u> | 698 |
| <u>createDirHier</u> | 699 |
| <u>csH</u> | 701 |
| <u>deleteDir</u> | 702 |
| <u>deleteFile</u> | 704 |
| <u>exit</u> | 706 |
| <u>getCurrentTime</u> | 708 |
| <u>getInstallPath</u> | 709 |
| <u>getLogin</u> | 710 |
| <u>getPrompts</u> | 711 |
| <u>getShellEnvVar</u> | 712 |
| <u>getSkillPath</u> | 714 |
| <u>getTempDir</u> | 715 |
| <u>getWorkingDir</u> | 716 |

Cadence SKILL Language Reference

| | |
|---------------------------|-----|
| <u>isDir</u> | 717 |
| <u>prependInstallPath</u> | 719 |
| <u>setShellEnvVar</u> | 721 |
| <u>setSkillPath</u> | 723 |
| <u>sh, shell</u> | 725 |
| <u>system</u> | 726 |
| <u>unsetShellEnvVar</u> | 727 |
| <u>vi, vii, vil</u> | 729 |

15

Namespace Functions 731

| | |
|-----------------------------|-----|
| <u>makeNamespace</u> | 732 |
| <u>findNamespace</u> | 733 |
| <u>useNamespace</u> | 734 |
| <u>unuseNamespace</u> | 735 |
| <u>importSymbol</u> | 736 |
| <u>findSymbol</u> | 737 |
| <u>addToExportList</u> | 738 |
| <u>getSymbolNamespace</u> | 739 |
| <u>removeFromExportList</u> | 740 |
| <u>addToNamespace</u> | 741 |
| <u>shadow</u> | 742 |
| <u>shadowImport</u> | 744 |
| <u>removeShadowImport</u> | 745 |
| <u>unimportSymbol</u> | 746 |

16

Scheme/SKILL++ Equivalents Tables 747

| | |
|--------------------------|-----|
| <u>Lexical Structure</u> | 748 |
| <u>Expressions</u> | 749 |
| <u>Functions</u> | 750 |

17

| | |
|---|-----|
| <u>Mapping Symbols to Values</u> | 757 |
| <u>Reader-Writer Correspondence</u> | 757 |
| <u>Using the Infix Operator</u> | 757 |
| <u>Evaluating Arguments</u> | 758 |
| <u>Working with Lists</u> | 759 |
| <u>Working with Symbols</u> | 759 |
| <u>Working with Hash Tables</u> | 759 |

18

| | |
|------------------------------------|-----|
| <u>setf Helper Functions</u> | 761 |
|------------------------------------|-----|

19

| | |
|---|-----|
| <u>Type Introspection Functions</u> | 765 |
|---|-----|

20

| | |
|--|-----|
| <u>The Standalone skill Program</u> | 769 |
| <u>Syntax</u> | 769 |
| <u>Examples</u> | 770 |
| <u>Use skill as a Script</u> | 770 |
| <u>Identifiers Used to Denote Data Types</u> | 771 |

List Functions

A SKILL list is an ordered collection of SKILL data objects. The list data structure is central to SKILL and is used in many ways. Following are the list functions.

| | | |
|-----------------------------|----------------|---|
| <u>append</u> | <u>append1</u> | <u>caar, caaar, caadr, cadr, caddr, cdar, cddr, ...</u> |
| <u>car</u> | <u>cdr</u> | <u>cons</u> |
| <u>constar</u> | <u>copy</u> | <u>dtpr</u> |
| <u>last</u> | <u>lconc</u> | <u>length</u> |
| <u>lindex</u> | <u>list</u> | <u>listp</u> |
| <u>nconc</u> | <u>nth</u> | <u>nthcdr</u> |
| <u>nthelem</u> | <u>pairp</u> | <u>range</u> |
| <u>remd</u> | <u>remdq</u> | <u>remove</u> |
| <u>removeListDuplicates</u> | <u>remq</u> | <u>reverse</u> |
| <u>rplaca</u> | <u>rplacd</u> | <u>setcar</u> |
| <u>setcdr</u> | <u>subst</u> | <u>tailp</u> |
| <u>tconc</u> | <u>xcons</u> | <u>xCoord</u> |
| <u>yCoord</u> | | |

append

```
append(  
    l_list1  
    l_list2  
)  
=> l_result  
  
append(  
    o_table  
    g_assoc  
)  
=> o_table  
  
append(  
    o_table1  
    o_table2  
)  
=> o_newTable
```

Description

Creates a list containing the elements of *l_list1* followed by the elements of *l_list2* or returns the original association table including new entries.

The top-level list cells of *l_list1* are duplicated and the *cdr* of the last duplicated list cell is set to point to *l_list2*; therefore, this is a time-consuming operation if *l_list1* is a long list.

This is a slow operation and the functions *tconc*, *lconc*, and *nconc* can be used instead for adding an element or a list to the end of a list. The command *cons* is even better if the new list elements can be added to the beginning of the list.

The *append* function can also be used with association tables as shown in the second syntax statement. Key/value pairs are added to the original association table (not to a copy of the table). This function should be used mainly in converting existing association lists or disembodied property lists to an association table.

Arguments

| | |
|----------------|---|
| <i>l_list1</i> | List of elements to be added to a list. |
| <i>l_list2</i> | List of elements to be added. |
| <i>o_table</i> | Association table to be updated. |

Cadence SKILL Language Reference

List Functions

g_assoc Key/value pairs to be added to the association table.

Value Returned

l_result A list containing elements of *l_list1* followed by elements of *l_list2*.

o_table The original association table including the new entries.

Examples

```
/* List Example */
append( '(1 2) '(3 4) )
=> (1 2 3 4)

/* Association Table Example */
myTable = makeTable("myAssocTable")
=> table:myAssocTable
myTable['a] = 1
=> 1
append(myTable '((b 2) (c 3)))
=> table:myAssocTable

/* Check the contents of the assoc table */
tableToList(myTable)
=> ((a 1) (b 2) (c 3))
```

Related Topics

[tconc](#)

[lconc](#)

[nconc](#)

[append1](#)

[cons](#)

[Association Table](#)

append1

```
append1(  
    l_list  
    g_arg  
)  
=> l_result
```

Description

Adds new arguments to the end of a list.

Returns a list just like *l_list* with *g_arg* added as the last element of the list.

This is a slow operation and the functions `tconc`, `lconc`, and `nconc` can be used instead for adding an element or a list to the end of a list. The command `cons` is even better if the new list elements can be added to the beginning of the list.

Arguments

| | |
|---------------|--|
| <i>l_list</i> | List to which <i>g_arg</i> is added. |
| <i>g_arg</i> | Argument to be added to the end of <i>l_list</i> . |

Value Returned

| | |
|-----------------|--|
| <i>l_result</i> | A copy of <i>l_list</i> with <i>g_arg</i> attached to the end. |
|-----------------|--|

Examples

Similar to `append`, `append1` duplicates the top-level list cells of *l_list*.

```
append1(' (1 2 3) 4)  
=> (1 2 3 4)
```

Related Topics

[append](#)

caar, caaar, caadr, cadr, caddr, cdar, cddr, ...

```
ca|d[ a | d ][ a | d ][ a | d ] r(  
    l_list  
)  
=> g_result
```

Description

Performs operations on a list using repeated applications of `car` and `cdr`. For example, `caaar` is equivalent to `car(car(car(l_list)))`. The possible combinations are `caaar`, `caadr`, `caadar`, `caaddr`, `caar`, `caddr`, `caddr`, `cadr`, `cdaaar`, `cdaadr`, `cdaar`, `cdadar`, `cdaddr`, `cdadr`, `cdar`, `cdbaar`, `cddadr`, `cddar`, `cdddar`, `cdddr`, `cddr`, `caaar`, `caadr`, `cadar`, `caddr`, `cdadr`, `cadaar`, `cadadr`, `caddar`, `caddr`, `cdaaar`, `cdaadr`, `cdadar`, `cdaddr`, `cdbaar`, `cddadr`, `cdddar`, and `cdddr`.

The `cadr(l_list)` expression, for example, applies `cdr` to get the tail of the list and then applies `car` to get the first element of the tail, in effect extracting the second element from the list. SKILL implements all `c . . . r` functions with any combination of `a` and `d` up to four characters.

Arguments

| | |
|---------------|-------------------|
| <i>l_list</i> | List of elements. |
|---------------|-------------------|

Value Returned

| | |
|-----------------|---------------------------------------|
| <i>g_result</i> | The value of the specified operation. |
|-----------------|---------------------------------------|

Examples

`caaar` is equivalent to `car(car(car(l_list)))`.

```
caaar('((1 2 3)(4 5 6))(7 8 9))  
=> 1
```

Equivalent to `car(car(cdr(l_list)))`.

```
caadr('((1 2 3)(4 5 6))(7 8 9))  
=> 7
```

Equivalent to `car(car(l_list))`.

```
caar('((1 2 3)(4 5 6))(7 8 9))
```

Cadence SKILL Language Reference

List Functions

```
=> (1 2 3)
```

Equivalent to `car(cdr(l_list))`.

```
z = '(1 2 3)
```

```
=> (1 2 3)
```

```
cadr(z)
```

```
=> 2
```

Related Topics

[car](#)

[cdr](#)

Cadence SKILL Language Reference

List Functions

car

```
car(  
    l_list  
)  
=> g_result
```

Description

Returns the first element of a list. `car` is nondestructive, meaning that it returns the first element of a list but does not modify the list that was its argument.

The functions `car` and `cdr` are typically used to take a list of objects apart, whereas the `cons` function is usually used to build up a list of objects. `car` was a machine language instruction on the first machine to run Lisp. `car` stands for *contents of the address register*.

Arguments

| | |
|---------------------|---------------------|
| <code>l_list</code> | A list of elements. |
|---------------------|---------------------|

Value Returned

| | |
|-----------------------|------------------------------|
| <code>g_result</code> | The first element in a list. |
|-----------------------|------------------------------|

Examples

```
car( '(a b c) )  
=> a  
z = '(1 2 3)  
=> (1 2 3)  
y = car(z)  
=> 1  
y  
=> 1  
z  
=> (1 2 3)  
car(nil)  
=> nil
```

Related Topics

[cdr](#)

[cons](#)

Cadence SKILL Language Reference

List Functions

cdr

```
cdr(  
    l_list  
)  
=> l_result
```

Description

Returns the tail of the list, that is, the list without its first element.

The expression `cdr(nil)` returns `nil`. `cdr` was a machine language instruction on the first machine to run Lisp. `cdr` stands for *contents of the decrement register*.

Arguments

| | |
|---------------------|-------------------|
| <code>l_list</code> | List of elements. |
|---------------------|-------------------|

Value Returned

| | |
|-----------------------|---|
| <code>l_result</code> | The end of a list, or the list minus the first element. |
|-----------------------|---|

Examples

```
cdr(' (a b c) ) => (b c)  
z = '(1 2 3)  
cdr(z)          => (2 3)
```

Note: `cdr` always returns a list. Therefore, `cdr(' (2 3))` returns the `list (3)` rather than the integer 3.

Related Topics

[caar, caaar, caadr, cadr, caddr, cdar, cddr, ...](#)

Cadence SKILL Language Reference

List Functions

cons

```
cons(  
    g_element  
    l_list  
)  
=> l_result
```

Description

Adds an element to the beginning of a list. Thus the *car* of *l_result* is *g_element* and the *cdr* of *l_result* is *l_list*. *l_list* can be *nil*, in which case a new list containing the single element is created.

Arguments

| | |
|------------------|---|
| <i>g_element</i> | Element to be added to the beginning of <i>l_list</i> . |
| <i>l_list</i> | List that can be <i>nil</i> . |

Value Returned

| | |
|-----------------|--|
| <i>l_result</i> | List whose first element is <i>g_element</i> and whose <i>cdr</i> is <i>l_list</i> . |
|-----------------|--|

Examples

```
cons(1 nil)  
=> (1)  
cons('a '(b c))  
=> (a b c)
```

The following example shows how to efficiently build a list from 1 to 100. You can reverse the list if necessary.

```
x = nil  
for( i 1 100 x = cons( i x ) )  
=> t  
x  
=> (100 99 98 .. 2 1)  
x = reverse( x )  
=> (1 2 3 .. 100)
```

Cadence SKILL Language Reference

List Functions

Related Topics

[car](#)

[cdr](#)

[append](#)

[append1](#)

constar

```
constar(  
    [ g_arg1 ... ]  
    l_list  
)  
=> l_result
```

Description

Adds elements to the beginning of a list.

This function is equivalent to `cons*()` and should be used instead.

The last argument, *l_list*, must be a list. *l_list* can be `nil`, in which case a new list containing the elements is created. The `car` of *l_result* is the first argument passed to `constar()` and the `cdr` of *l_result* is rest of the elements of the newly created list (including *l_list*).

Arguments

| | |
|-----------------------|---|
| [<i>g_arg1</i> ...] | Elements to be added to the beginning of <i>l_list</i> . |
| <i>l_list</i> | The last argument that must be a list (which can be <code>nil</code>). |

Value Returned

| | |
|-----------------|---|
| <i>l_result</i> | List whose first element is the first argument and whose <code>cdr</code> is rest of the elements of the newly created list (including <i>l_list</i>). |
|-----------------|---|

Examples

The first element of the newly created list is the first argument while `cdr` is rest of the elements (including *l_list*):

```
newList = constar( '(a b) '("hello") 1 2.3 '(x y) )  
=> ((a b) ("hello") 1 2.3 x y z)  
car( newList ) => (a b)  
cdr( newList ) => (("hello") 1 2.3 x y z)
```

The last argument can be `nil`:

```
constar( 1 2 3 nil ) => (1 2 3)
```

Cadence SKILL Language Reference

List Functions

The last argument must be a list:

```
constar( 'x 1 2 )
```

```
*Error* constar: the last arg must be a list - 2
```

`constar()` is cleaner and more efficient in adding multiple elements to the beginning of a list than `cons()`:

```
cons(1 cons(2 cons(3 '(a b c)))) => (1 2 3 a b c)
```

```
constar( 1 2 3 '(a b c)) => (1 2 3 a b c)
```

Related Topics

[car](#)

[cdr](#)

[append](#)

[append1](#)

Cadence SKILL Language Reference

List Functions

copy

```
copy(  
    l_arg  
)  
=> l_result
```

Description

Returns a copy of a list, that is, a list with all the top-level cells duplicated.

Because list structures in SKILL are typically shared, it is necessary to pass around pointers to lists. If, however, any function that modifies a list destructively is used, `copy` is often used to create new copies of a list so that the original is not inadvertently modified by those functions. This call is costly so its use should be limited. This function only duplicates the top-level list cells, all lower level objects are still shared.

Arguments

| | |
|--------------|-------------------|
| <i>l_arg</i> | List of elements. |
|--------------|-------------------|

Value Returned

| | |
|-----------------|--------------------------|
| <i>l_result</i> | A copy of <i>l_arg</i> . |
|-----------------|--------------------------|

Examples

```
z = '(1 (2 3) 4)  
=> (1 (2 3) 4)
```

```
x = copy(z)  
=> (1 (2 3) 4)
```

z and *x* have the same value.

```
equal(z x)  
=> t
```

z and *x* are not the same list.

```
eq(z x)  
=> nil
```

Cadence SKILL Language Reference

List Functions

Related Topics

[car](#)

[cdr](#)

[append](#)

[append1](#)

dtpr

```
dtpr(  
    g_value  
)  
=> t / nil
```

Description

Checks whether an object is a non-empty list.

`dtpr` is a predicate function that is equivalent to `pairp`.

Arguments

| | |
|----------------|------------|
| <i>g_value</i> | An object. |
|----------------|------------|

Value Returned

| | |
|------------------|--|
| <code>t</code> | Object is a non-empty list. |
| <code>nil</code> | The specified object is an empty list. |

Example

```
dtpr( 1 )  
=> nil  
dtpr( list(1) )  
=> t
```

Related Topics

[listp](#)

[pairp](#)

last

```
last(  
    l_arg  
)  
=> l_result
```

Description

Returns the last list cell in a list.

Arguments

l_arg List of elements.

Value Returned

l_result Last list cell (not the last element) in *l_arg*.

Examples

```
last( ' (a b c) )  
=> (c)  
  
z = ' (1 2 3)  
last(z)  
=> (3)  
  
last( ' (a b c (d e f)) )  
=> ((d e f))
```

Related Topics

[car](#)

[cdr](#)

[list](#)

[listp](#)

lconc

```
lconc(  
    l_tconc  
    l_list  
)  
=> l_result
```

Description

Uses a `tconc` structure to efficiently splice a list to the end of another list.

Arguments

| | |
|----------------------|--|
| <code>l_tconc</code> | A <code>tconc</code> structure that must initially be created using the <code>tconc</code> function. |
| <code>l_list</code> | List to be spliced onto the end of the <code>tconc</code> structure. |

Value Returned

| | |
|-----------------------|---|
| <code>l_result</code> | Returns <code>l_tconc</code> , which must be a <code>tconc</code> structure, with the list <code>l_list</code> spliced in at the end. |
|-----------------------|---|

Examples

```
x = tconc(nil 1)      ; x is initialized ((1) 1)  
lconc(x '(2 3 4))    ; x is now ((1 2 3 4) 4)  
lconc(x nil)         ; Nothing is added to x.  
lconc(x '(5))        ; x is now ((1 2 3 4 5) 5)  
x = car( x )         ; x is now (1 2 3 4 5)
```

Related Topics

[append](#)

[tconc](#)

Cadence SKILL Language Reference

List Functions

length

```
length(  
    laot_arg  
)  
=> x_result / 0
```

Description

Determines the length of a list, array, association table, or string.

The time taken to compute the length depends on the type of object. For example,

| | |
|-------------------|---|
| List | Time taken to compute the length of a list is proportional to the number of items in the list. |
| Array | Time taken to compute the length of an array is constant. |
| Association table | Time taken to compute the length of an association table is constant. |
| String | Time taken to compute the length of a string is proportional to the number of characters in the string. |

Arguments

| | |
|-----------------|--|
| <i>laot_arg</i> | SKILL list, array, association table, or string. |
|-----------------|--|

Value Returned

| | |
|-----------------|--|
| <i>x_result</i> | Length of the <i>laot_arg</i> object. (The length is either the number of elements in the list, string, or array or the number of key/value pairs in the association table). |
| 0 | <i>laot_arg</i> is nil or an empty array or table. |

Examples

```
length( '(a b c d) )  
=> 4  
  
z = '(1 2 3)  
=> (1 2 3)  
  
length( z )  
=> 3
```

Cadence SKILL Language Reference

List Functions

```
length("hello")
=> 5

declare(a[11])
length( a )
=> 11

myTable = makeTable( "atable" 0)
=> table:atable

myTable[ 'one] = "blue"
=> "blue"

myTable[ "two"] = '(red)
=> (r e d)

length(myTable)
=> 2
```

Related Topics

[list](#)

lindex

```
lindex(  
    l_list  
    g_element  
    [ ?all g_all ]  
)  
=> x_result / l_result / nil
```

Description

Returns the index number of the given element in *l_list*.

Arguments

| | |
|-------------------|---|
| <i>l_list</i> | A list of elements. |
| <i>g_element</i> | The element to be searched in <i>l_list</i> . |
| ?all <i>g_all</i> | Specifies whether to print the index number for all occurrences of <i>g_element</i> . |

Value Returned

| | |
|-----------------|---|
| <i>x_result</i> | The index number of <i>g_element</i> in <i>l_list</i> when ?all is either nil or not specified. |
| <i>l_result</i> | The list of index numbers for all occurrences of <i>g_element</i> in <i>l_list</i> when ?all is set to t. |
| nil | When the given element is not found in <i>l_list</i> . |

Examples

```
lindex(' (1 2 3 4) 2)  
=> 2  
  
lindex(' (1 4 6 7 4 8 4) 4 ?all t)  
=> (2 5 7)  
  
lindex(' (1 4 6 7 4 8 4) 4 ?all nil)  
=> 2
```

Related Topics

[list](#)

Cadence SKILL Language Reference

List Functions

list

```
list(  
    [ g_arg1 g_arg2 ... ]  
)  
=> l_result / nil
```

Description

Creates a list with the given elements.

Arguments

| | |
|---------------|---|
| <i>g_arg1</i> | Element to be added to a list. |
| <i>g_arg2</i> | Additional elements to be added to a list |

Value Returned

| | |
|-----------------|--|
| <i>l_result</i> | List whose elements are <i>g_arg1</i> , <i>g_arg2</i> , and so on. |
| <i>nil</i> | No arguments are given. |

Examples

```
list(1 2 3)  
=> (1 2 3)  
list('a 'b 'c)  
=> (a b c)
```

Related Topics

[car](#)

[cdr](#)

[cons](#)

[listp](#)

[tconc](#)

listp

```
listp(  
    g_value  
)  
=> t / nil
```

Description

Checks whether the specified object is a list.

The suffix *p* is usually added to the name of a function to indicate that it is a predicate function.

Arguments

| | |
|----------------|----------------|
| <i>g_value</i> | A data object. |
|----------------|----------------|

Value Returned

| | |
|------------|--|
| <i>t</i> | If <i>g_value</i> is a list, a data type whose internal name is also <code>list.listp(nil)</code> returns <i>t</i> . |
| <i>nil</i> | The specified object is not a list. |

Examples

```
listp(' (1 2 3))  
=> t  
  
listp( nil )  
=> t  
  
listp( 1 )  
=> nil
```

Related Topics

[list](#)

nconc

```
nconc(  
    l_arg1  
    l_arg2  
    [ l_arg3 ... ]  
)  
=> l_result
```

Description

Equivalent to a destructive `append` where the first argument is modified.

This results in `nconc` being much faster than `append` but not as fast as `tconc` and `lconc`. Thus `nconc` returns a list consisting of the elements of `l_arg1`, followed by the elements of `l_arg2`, followed by the elements of `l_arg3`, and so on. The `cdr` of the last list cell of `l_argi` is modified to point to `l_argi+1`. Thus caution must be taken because if `nconc` is called with the `l_argi` two consecutive times it can form an infinite structure where the `cdr` of the last list cell of `l_argi` points to the `car` of `l_argi`.

Use the `nconc` function principally to reduce the amount of memory consumed. A call to `append` would normally duplicate the first argument whereas `nconc` does not duplicate any of its arguments, thereby reducing memory consumption.

Arguments

| | |
|---------------------|---|
| <code>l_arg1</code> | List of elements. |
| <code>l_arg2</code> | List elements concatenated to <code>l_arg1</code> . |
| <code>l_arg3</code> | Additional lists. |

Value Returned

| | |
|-----------------------|---|
| <code>l_result</code> | The modified value of <code>l_arg1</code> . |
|-----------------------|---|

Examples

The following example forms an infinite list structure (a b c d e f g a b c d e f g ...).

```
x = '(a b c)  
nconc( x '(d))      ; x is now (a b c d)
```

Cadence SKILL Language Reference

List Functions

```
nconc( x '(e f g) ) ; x is now the list (a b c d e f g)
nconc( x x )        ; Forms an infinite structure.
```

Related Topics

[lconc](#)

[tconc](#)

Cadence SKILL Language Reference

List Functions

ncons

```
ncons(  
    g_element  
)  
=> l_result
```

Description

Builds a list containing an element. This function is equivalent to `cons(g_element nil)`.

Arguments

| | |
|------------------|--|
| <i>g_element</i> | Element to be added to the beginning of an empty list. |
|------------------|--|

Value Returned

| | |
|-----------------|---|
| <i>l_result</i> | A list with <i>g_element</i> as its only element. |
|-----------------|---|

Examples

```
ncons( 'a )  
=> (a)  
  
z = '(1 2 3)  
=> (1 2 3)  
  
ncons( z )  
=> ((1 2 3))
```

Related Topics

[list](#)

nth

```
nth(  
    x_index0  
    l_list  
)  
=> g_result / nil
```

Description

Returns an index-selected element of a list, assuming a zero-based index.

Thus, `nth(0 l_list)` is the same as `car(l_list)`. The value `nil` is returned if *x_index0* is negative or is greater than or equal to the length of the list.

Arguments

| | |
|-----------------|--|
| <i>x_index0</i> | Index of the list element you want to be returned. |
| <i>l_list</i> | List of elements. |

Value Returned

| | |
|------------------|---|
| <i>g_result</i> | Indexed element of <i>l_list</i> , assuming a zero-based index |
| <code>nil</code> | If <i>x_index0</i> is negative or is greater than or equal to the length of the list. |

Examples

```
nth( 1 '(a b c) )  
=> b  
  
z = '(1 2 3)  
=> (1 2 3)  
  
nth(2 z)  
=> 3  
  
nth(3 z)  
=> nil
```

Related Topics

[list](#)

Cadence SKILL Language Reference

List Functions

nthcdr

nthelem

nthcdr

```
nthcdr(  
    x_count  
    l_list  
)  
=> l_result
```

Description

Applies `cdr` to a list a given number of times.

Arguments

| | |
|----------------|--|
| <i>x_count</i> | Number of times to apply <code>cdr</code> to <i>l_list</i> . |
| <i>l_list</i> | List of elements. |

Value Returned

| | |
|-----------------|--|
| <i>l_result</i> | Result of applying <code>cdr</code> to <i>l_list</i> , <i>x_count</i> number of times. |
|-----------------|--|

Examples

```
nthcdr( 3 '(a b c d))  
=> (d)  
  
z = '(1 2 3)  
nthcdr(2 z)  
=> (3)  
  
nthcdr(-1 z)  
=> (nil 1 2 3)
```

If *x_count* is less than 0, then `cons(nil l_list)` is returned.

Related Topics

[nth](#)

nthelem

```
nthelem(  
    x_index1  
    l_list  
)  
=> g_result / nil
```

Description

Returns the indexed element of the list, assuming a one-based index.

Thus `nthelem(1 l_list)` is the same as `car(l_list)`.

Arguments

| | |
|-----------------|--|
| <i>x_index1</i> | Index of the element of <i>l_list</i> you want returned. |
| <i>l_list</i> | List of elements. |

Value Returned

| | |
|-----------------|--|
| <i>g_result</i> | The <i>x_index1</i> element of <i>l_list</i> . |
| nil | If <i>x_index1</i> is less than or equal to 0 or is greater than the length of the list. |

Examples

```
nthelem( 1 '(a b c) )  
=> a  
  
z = '(1 2 3)  
nthelem(2 z)  
=> 2
```

Related Topics

[nth](#)

pairp

```
pairp(  
    g_obj  
)  
=> t / nil
```

Description

Checks if an object is a `cons` object, that is, a non-empty list. This function is equivalent to `dtpr`.

The suffix `p` is usually added to the name of a function to indicate that it is a predicate function.

Arguments

| | |
|--------------|-------------------|
| <i>g_obj</i> | Any SKILL object. |
|--------------|-------------------|

Value Returned

| | |
|------------|---|
| <i>t</i> | <i>g_obj</i> is a <code>cons</code> object. |
| <i>nil</i> | <i>g_obj</i> is not a <code>cons</code> object. |

Examples

```
(pairp nil)  
=> nil  
(pairp 123)  
=> nil  
(pairp '(1 2))  
=> t
```

Related Topics

[listp](#)

Cadence SKILL Language Reference

List Functions

range

```
range(  
    n_num1  
    n_num2  
)  
=> l_result
```

Description

Returns a list whose first element is *n_num1* and whose tail is *n_num2*. This function is a prefix form of the `:` operator.

Arguments

| | |
|---------------|----------------------------|
| <i>n_num1</i> | First element of the list. |
| <i>n_num2</i> | Tail of the list. |

Value Returned

| | |
|-----------------|--------------------------|
| <i>l_result</i> | Result of the operation. |
|-----------------|--------------------------|

Examples

```
L = range(1 2)  
=> (1 2)  
car(L)  
=> 1  
cdr(L)  
=> (2)  
L = range(1.1 3.3)  
=> (1.1 3.3)  
car(L)  
=> 1.1  
cdr(L)  
=> (3.3)
```

Related Topics

[list](#)

[listp](#)

Cadence SKILL Language Reference

List Functions

remd

```
remd(  
    g_x  
    l_arg  
)  
=> l_result
```

Description

Removes all top-level elements `equal` to a SKILL object from a list. This is a destructive removal, which means that the original list itself is modified. Therefore, any other reference to that list will also see the changes.

`remd` uses `equal` for comparison.

Arguments

| | |
|--------------|---|
| <i>g_x</i> | Any SKILL object to be removed from the list. |
| <i>l_arg</i> | List from which to remove <i>g_x</i> . |

Value Returned

| | |
|-----------------|---|
| <i>l_result</i> | Returns <i>l_arg</i> modified so that all top-level elements equal to <i>g_x</i> are removed. |
|-----------------|---|

Examples

```
y = '("a" "b" "x" "d" "f")  
=> ("a" "b" "x" "d" "f")  
  
remd("x" y)  
=> ("a" "b" "d" "f")  
  
y  
=> ("a" "b" "d" "f")
```

The first element from the original list will not be modified in-place.

```
y = '("a" "b" "d" "f")  
=> ("a" "b" "d" "f")  
  
remd("a" y)  
=> ("b" "d" "f")  
  
y  
=> ("a" "b" "d" "f")
```

Cadence SKILL Language Reference

List Functions

Note the original list, `y`, is not modified.

In order to remove the first element from the original list, use the same variable (that holds the original list) to hold the updated list.

```
y = ' ("a" "b" "d" "f")  
=>  ("a" "b" "d" "f")
```

```
y=remd("a" y)  
=>  ("b" "d" "f")
```

```
y  
=>  ("b" "d" "f")
```

Related Topics

[remdq](#)

[remove](#)

[remq](#)

Cadence SKILL Language Reference

List Functions

remdq

```
remdq(  
    g_x  
    l_arg  
)  
=> l_result
```

Description

Removes all top-level elements that are identical to a SKILL object using `eq` from a list. This is a destructive removal, which means that the original list itself is modified. Therefore, any other reference to that list will also see the changes.

`remdq` uses `eq` instead of `equal` for comparison.

Arguments

| | |
|--------------|---|
| <i>g_x</i> | Any SKILL object to be removed from the list. |
| <i>l_arg</i> | List from which to remove <i>g_x</i> . |

Value Returned

| | |
|-----------------|---|
| <i>l_result</i> | Returns <i>l_arg</i> modified so that all top-level elements <code>eq</code> to <i>g_x</i> are removed. |
|-----------------|---|

Examples

```
y = '(a b x d f x g)  
=> (a b x d f x g)  
  
remdq('x y)  
=> (a b d f g)  
  
y  
=> (a b d f g)
```

Related Topics

[remd](#)

[remove](#)

[remq](#)

remove

```
remove (
    g_x
    l_arg
)
=> l_result

remove (
    g_key
    o_table
)
=> g_value
```

Description

Returns a copy of a list with all top-level elements `equal` to a SKILL object removed. Can also be used to remove an entry from an association table, in which case the removal is destructive, that is, any other reference to the table will also see the changes. `remove` uses `equal` for comparison. `remove` can also be used with an association table to identify and remove an entry corresponding to the key specified in the function.

Arguments

| | |
|----------------|---|
| <i>g_x</i> | Any SKILL object to be removed from the list. |
| <i>l_arg</i> | List from which to remove <i>g_x</i> . |
| <i>g_key</i> | Key or first element of the key/value pair. |
| <i>o_table</i> | Association table containing the key/value pairs to be processed. |

Value Returned

| | |
|-----------------|---|
| <i>l_result</i> | Copy of <i>l_arg</i> with all top-level elements equal to <i>g_x</i> removed. |
| <i>g_value</i> | Value associated with the key that is removed. |

Examples

```
remove ( "x" '("a" "b" "x" "d" "f"))
=> ("a" "b" "d" "f")

myTable = makeTable("myTable" -1)
=> table:myTable           ;default is -1
```

Cadence SKILL Language Reference

List Functions

```
myTable["two"]=2
=> 2

remove("two" myTable)
=> 2 ; permanently removed from table

myTable["two"]
=> -1 ; the default value
```

Related Topics

[remd](#)

[remove](#)

[remq](#)

removeListDuplicates

```
removeListDuplicates(  
    l_list  
)  
=> l_newList
```

Description

Removes duplicate entries from a SKILL list and returns a new list with the duplicates removed.

Arguments

| | |
|---------------|---------------|
| <i>l_list</i> | A SKILL list. |
|---------------|---------------|

Value Returned

| | |
|------------------|--|
| <i>l_newList</i> | Copy of <i>l_list</i> with all duplicates removed. |
|------------------|--|

Examples

```
removeListDuplicates("a" 1 "a" 2 "a" 3 "a" 4)  
=> ("a" 1 2 3 4)
```

Related Topics

[remd](#)

[remove](#)

[remq](#)

Cadence SKILL Language Reference

List Functions

remq

```
remq(  
    g_x  
    l_arg  
)  
=> l_result
```

Description

Returns a copy of a list with all top-level elements that are identical to a SKILL object removed. Uses `eq`.

Arguments

| | |
|--------------|---|
| <i>g_x</i> | Any SKILL object to be removed from the list. |
| <i>l_arg</i> | List from which to remove <i>g_x</i> . |

Value Returned

| | |
|-----------------|---|
| <i>l_result</i> | A copy of <i>l_arg</i> with all top-level elements <i>eq</i> to <i>g_x</i> removed. |
|-----------------|---|

Examples

```
remq('x '(a b x d f x g))  
=> (a b d f g)
```

Related Topics

[remd](#)

[remove](#)

reverse

```
reverse(  
    l_arg  
)  
=> l_result
```

Description

Returns a copy of the given list with the elements in reverse order.

Because this function copies the list, it uses a lot of memory for large lists.

Arguments

| | |
|--------------|---------|
| <i>l_arg</i> | A list. |
|--------------|---------|

Value Returned

| | |
|-----------------|---|
| <i>l_result</i> | A new list with the elements at the top level in reverse order. |
|-----------------|---|

Examples

```
reverse( ' (1 2 3) )  
=> (3 2 1)  
  
reverse( ' (a b (c d) e) )  
=> ' (e (c d) b a)
```

Related Topics

[rplaca](#)

[rplacd](#)

rplaca

```
rplaca(  
    l_arg1  
    g_arg2  
)  
=> l_result
```

Description

Replaces the first element of a list with an object. This function does not create a new list; it alters the input list, in the same way as `setcar`. This is a destructive operation, meaning that any other reference to the list will also see the change.

Arguments

| | |
|---------------|-------------------|
| <i>l_arg1</i> | A list. |
| <i>g_arg2</i> | Any SKILL object. |

Value Returned

| | |
|-----------------|---|
| <i>l_result</i> | Modified <i>l_arg1</i> with the <i>car</i> of <i>l_arg1</i> replaced by <i>g_arg2</i> . |
|-----------------|---|

Examples

```
x = '(a b c)  
rplaca( x 'd )  
=> (d b c)  
  
x  
=> (d b c)
```

The `car` of `x` is replaced by the second argument.

Related Topics

[rplacd](#)

[setcar](#)

[setcdr](#)

rplacd

```
rplacd(  
    l_arg1  
    l_arg2  
)  
=> l_result
```

Description

Replaces the tail of a list with the elements of a second list. This function does not create a new list; it alters the input list in the same way as `setcdr`. This is a destructive operation, meaning that any other reference to the list will also see the changes.

Arguments

| | |
|---------------|--|
| <i>l_arg1</i> | List that is modified. |
| <i>l_arg2</i> | List that replaces the <code>cdr</code> of <i>l_arg1</i> . |

Value Returned

| | |
|-----------------|--|
| <i>l_result</i> | Modified <i>l_arg1</i> with the <code>cdr</code> of the list <i>l_arg1</i> replaced with <i>l_arg2</i> . |
|-----------------|--|

Examples

```
x = '(a b c)  
rplacd( x '(d e f))  
=> (a d e f)  
  
x  
=> (a d e f)
```

The `cdr` of `x` is replaced by the second argument.

Related Topics

[rplaca](#)

[setcar](#)

[setcdr](#)

Cadence SKILL Language Reference

List Functions

setcar

```
setcar(  
    l_arg1  
    g_arg2  
)  
=> l_result
```

Description

Replaces the first element of a list with an object in the same way as `rplaca`. This is a destructive operation, meaning that any other reference to the list will also see the change.

Arguments

| | |
|---------------|-------------------------|
| <i>l_arg1</i> | This is a list. |
| <i>g_arg2</i> | This is a SKILL object. |

Value Returned

| | |
|-----------------|---|
| <i>l_result</i> | Modified <i>l_arg1</i> with the <i>car</i> of <i>l_arg1</i> replaced by <i>g_arg2</i> . |
|-----------------|---|

Examples

```
x = '(a b c)  
=> (a b c)  
setcar( x 'd )  
=> (d b c)  
x  
=> (d b c)
```

The `car` of `x` is replaced by the second argument.

Related Topics

[rplacd](#)

[rplaca](#)

[setcdr](#)

Cadence SKILL Language Reference

List Functions

setcdr

```
setcdr(  
    l_arg1  
    l_arg2  
)  
=> l_result
```

Description

Replaces the tail of a list with the elements of a second list in the same way as `rplacd`. This is a destructive operation, meaning that any other reference to the list will also see the change.

Arguments

| | |
|---------------|--|
| <i>l_arg1</i> | List that is modified. |
| <i>l_arg2</i> | List that replaces the <code>cdr</code> of <i>l_arg1</i> . |

Value Returned

| | |
|-----------------|--|
| <i>l_result</i> | Modified <i>l_arg1</i> with the <code>cdr</code> of the list <i>l_arg1</i> replaced with <i>l_arg2</i> . |
|-----------------|--|

Examples

```
x = '(a b c)  
setcdr( x '(d e f))  
=> (a d e f)  
  
x  
=> (a d e f)
```

The `cdr` of `x` is replaced by the second argument.

Related Topics

[rplacd](#)

[rplaca](#)

[setcar](#)

subst

```
subst (
    g_x
    g_y
    l_arg
)
=> l_result
```

Description

Substitutes one object for another object in a list.

Arguments

| | |
|--------------|-------------------------|
| <i>g_x</i> | Object substituted. |
| <i>g_y</i> | Object substituted for. |
| <i>l_arg</i> | A list. |

Value Returned

| | |
|-----------------|--|
| <i>l_result</i> | Result of substituting <i>g_x</i> for all <code>equal</code> occurrences of <i>g_y</i> at all levels in <i>l_arg</i> . |
|-----------------|--|

Examples

```
subst( 'a 'b '(a b c) )
=> (a a c)
subst('x 'y '(a b y (d y (e y))))
=> (a b x (d x (e x)))
```

Related Topics

[remd](#)

tailp

```
tailp(  
    l_arg1  
    l_arg2  
)  
=> l_arg1 / nil
```

Description

Returns *arg1* if a list cell *eq* to *arg1* is found by *cdr* down *arg2* zero or more times. It returns *nil* otherwise. Because *eq* is being used for comparison *l_arg1* must point to a tail list in *l_arg2* for this predicate to return a non-*nil* value.

The suffix *p* is usually added to the name of a function to indicate that it is a predicate function.

Arguments

| | |
|---------------|--|
| <i>l_arg1</i> | A list. |
| <i>l_arg2</i> | Another list, which can contain <i>l_arg1</i> as its tail. |

Value Returned

| | |
|--------------|---|
| <i>l_arg</i> | If a list cell <i>eq</i> to <i>l_arg1</i> is found by <i>cdr</i> down <i>l_arg2</i> zero or more times. |
| <i>nil</i> | If a list cell <i>eq</i> to <i>l_arg1</i> is not found by <i>cdr</i> down <i>l_arg2</i> zero or more times. |

Examples

```
y = '(b c)  
z = cons( 'a y )  
=> (a b c)  
tailp( y z )  
=> (b c)  
tailp( '(b c) z )  
=> nil
```

nil was returned because *'(b c)* is not *eq* the *cdr*(*z*).

Cadence SKILL Language Reference

List Functions

Related Topics

tconc

Cadence SKILL Language Reference

List Functions

tconc

```
tconc(  
    l_ptr  
    g_x  
)  
=> l_result
```

Description

Creates a list cell whose `car` points to a list of the elements being constructed and whose `cdr` points to the last list cell of the list being constructed.

A `tconc` structure is a special type of list that allows efficient addition of objects to the end of a list. It consists of a list cell whose `car` points to a list of the elements being constructed with `tconc` and whose `cdr` points to the last list cell of the list being constructed. If `l_ptr` is `nil`, a new `tconc` structure is automatically created. To obtain the list under construction, take the `car` of the `tconc` structure.

`tconc` and `lconc` are much faster than `append` when adding new elements to the end of a list. The `append` function is much slower, because it traverses and copies the list to reach the end, whereas `tconc` and `lconc` only manipulate pointers.

Arguments

| | |
|--------------------|---|
| <code>l_ptr</code> | A <code>tconc</code> structure. Must be initialized to <code>nil</code> to create a new <code>tconc</code> structure. |
| <code>g_x</code> | Element to add to the end of the list. |

Value Returned

| | |
|-----------------------|---|
| <code>l_result</code> | Returns <code>l_ptr</code> , which must be a <code>tconc</code> structure or <code>nil</code> , with <code>g_x</code> added to the end. |
|-----------------------|---|

Examples

```
x = tconc(nil 1)      ; x is now ((1) 1)  
tconc(x 2)           ; x is now ((1 2) 2)  
tconc(x 3)           ; x is now ((1 2 3) 3)  
x = car(x)           ; x is now (1 2 3)
```

`x` now equals `(1 2 3)`, the desired result.

Cadence SKILL Language Reference

List Functions

Related Topics

lconc

Cadence SKILL Language Reference

List Functions

xcons

```
xcons(  
    l_list  
    g_element  
)  
=> l_result
```

Description

Adds an element to the beginning of a list. Equivalent to `cons` but the order of the arguments is reversed.

Arguments

| | |
|------------------|---|
| <i>l_list</i> | A list, which can be <code>nil</code> . |
| <i>g_element</i> | Element to be added to the beginning of <i>l_list</i> . |

Value Returned

| | |
|-----------------|-----------------|
| <i>l_result</i> | Returns a list. |
|-----------------|-----------------|

Examples

```
xcons( '(b c) 'a )  
=> ( a b c )
```

Related Topics

[append1](#)

[lconc](#)

[list](#)

[ncons](#)

[tconc](#)

xCoord

```
xCoord(  
    l_list  
)  
=> g_result
```

Description

Returns the first element of a list. Does not modify the argument list.

The `xCoord` and `yCoord` functions are aliases for the `car` and `cadr` functions.

Arguments

| | |
|---------------|---------------------|
| <i>l_list</i> | A list of elements. |
|---------------|---------------------|

Value Returned

| | |
|-----------------|------------------------------|
| <i>g_result</i> | The first element in a list. |
|-----------------|------------------------------|

Examples

```
xValue = 300  
yValue = 400  
aCoordinate = xValue:yValue  
=> ( 300 400 )  
  
xCoord( aCoordinate )  
=> 300  
  
yCoord( aCoordinate )  
=> 400
```

Related Topics

[yCoord](#)

[car](#)

[caar, caaar, caadr, cadr, caddr, cdar, cddr, ...](#)

yCoord

```
yCoord(  
    l_list  
)  
=> g_result
```

Description

Returns the tail of the list, that is, the list without its first element.

The `xCoord` and `yCoord` functions are aliases for the `car` and `cadr` functions

Arguments

| | |
|---------------------|---------------------|
| <code>l_list</code> | A list of elements. |
|---------------------|---------------------|

Value Returned

| | |
|-----------------------|---|
| <code>g_result</code> | Returns the end of a list, or the list minus the first element. |
|-----------------------|---|

Examples

```
xValue = 300  
yValue = 400  
aCoordinate = xValue:yValue  
=> ( 300 400 )  
  
xCoord( aCoordinate )  
=> 300  
  
yCoord( aCoordinate )  
=> 400
```

Related Topics

[xCoord](#)

[car](#)

[caar, caaar, caadr, cadr, caddr, cdar, cddr, ...](#)

Cadence SKILL Language Reference
List Functions

Data Structures

This topic lists the SKILL functions for operations related to data structures.

| | | |
|--|---------------------------------|--|
| <u>arrayp</u> | <u>arrayref</u> | <u>assoc</u> , <u>assq</u> , <u>assv</u> |
| <u>declare</u> | <u>defprop</u> | <u>defstruct</u> |
| <u>defstructp</u> | <u>defvar</u> | <u>makeTable</u> |
| <u>makeVector</u> | <u>setarray</u> | <u>tablep</u> |
| <u>type</u> , <u>typep</u> | <u>vector</u> | <u>vectorp</u> |

arrayp

```
arrayp(  
    g_value  
)  
=> t / nil
```

Description

Checks if an object is an array.

The suffix *p* is usually added to the name of a function to indicate that it is a predicate function.

Arguments

| | |
|----------------|------------------|
| <i>g_value</i> | Any data object. |
|----------------|------------------|

Value Returned

| | |
|------------|---------------------------------------|
| <i>t</i> | If <i>g_value</i> is an array object. |
| <i>nil</i> | When it is not an array object. |

Examples

```
declare(x[10])  
arrayp(x)  
=> t  
  
arrayp('x')  
=> nil
```

Related Topics

[declare](#)

arrayref

```
arrayref(  
    g_collection  
    g_index  
)  
=> g_element
```

Description

Returns the element in a collection that is in an array or a table of the given index.

This function is usually called implicitly using the [] syntax.

The syntax `a[i] = b`, referred to as the setarray function.

Arguments

| | |
|---------------------|---|
| <i>g_collection</i> | An array or a table. |
| <i>g_index</i> | An integer for indexing an array. An arbitrary object for indexing a table. |

Value Returned

| | |
|------------------|--|
| <i>g_element</i> | The element selected by the given index in the given collection. |
|------------------|--|

Examples

```
a[3]  
=> 100           ;if the fourth element of the array is 100  
(arrayref a 3 )  
=> 100           ;same as a[3]
```

Related Topics

[setarray](#)

assoc, assq, assv

```
assv(  
    g_key  
    l_alist  
)  
=> l_association / nil
```

Description

The `assoc`, `assq`, and `assv` functions find the first list in `l_alist` whose `car` field is `g_key` and return that list. `assq` uses `eq` to compare `g_key` with the `car` fields of the lists in `alist`. `assoc` uses `equal`. `assv` uses `eqv`.

The association list, `l_alist`, must be a list of lists. An association list is a standard data structure that has the form `((key1 value1) (key2 value2) (key3 value3) ...)`. These functions find the first list in `l_alist` whose `car` field is `g_key` and return that list. `assq` uses `eq` to compare `g_key` with the `car` fields of the lists in `l_alist`. `assv` uses `eqv`. `assoc` uses `equal`.

Arguments

| | |
|----------------------|--|
| <code>g_key</code> | An arbitrary object as the search key. |
| <code>l_alist</code> | Association list. Must be a list of lists. |

Value Returned

| | |
|----------------------------|---|
| <code>l_association</code> | The returned list is always an element of <code>l_alist</code> . |
| <code>nil</code> | If no list in <code>l_alist</code> has <code>g_key</code> , as its <code>car</code> . |

Examples

```
e = '((a 1) (b 2) (c 3))  
(assq 'a e)  
=> (a 1)  
(assq 'b e)  
=> (b 2)  
(assq 'd e)  
=> nil  
(assq (list 'a) '(((a)) ((b)) ((c))))  
=> nil
```

Cadence SKILL Language Reference

Data Structures

```
(assoc (list 'a) '(((a)) ((b)) ((c))))  
=> ((a))  
  
(assv 5 '((2 3) (5 7) (11 13)))  
=> (5 7)
```

Related Topics

[eq](#)

[equal](#)

[eqv](#)

declare

```
declare(  
    s_arrayName  
    [ x_sizeOfArray ]  
)  
=> a_newArray
```

Description

Creates an array with a specified number of elements. This is a syntax form. All elements of the array are initialized to `unbound`.

Arguments

| | |
|----------------------|---|
| <i>s_arrayName</i> | Name of the array. There must be no white space between the name of an array and the opening bracket containing the size. |
| <i>x_sizeOfArray</i> | Size of the array as an integer. |

Value Returned

| | |
|-------------------|------------------------|
| <i>a_newArray</i> | Returns the new array. |
|-------------------|------------------------|

Examples

When the name of an array appears on the right side of an assignment statement, only a pointer to the array is used in the assignment; the values stored in the array are not copied. It is therefore possible for an array to be accessible by different names. Indexes are used to specify elements of an array and always start with 0; that is, the first element of an array is element 0. SKILL checks for an out of bounds array index with each array access.

```
declare(a[10])  
a[0] = 1  
a[1] = 2.0  
a[2] = a[0] + a[1]
```

Creates an array of 10 elements. *a* is the name of the array, with indexes ranging from 0 to 9. Assigns the integer 1 to element 0, the float 2.0 to element 1, and the float 3.0 to element 2.

```
b = a
```

b now also refers to the same array as *a*.

```
declare(c[10])
```

Declares another array of 10 elements.

```
declare(d[2])
```

Declares `d` as array of 2 elements.

```
d[0] = b
```

`d[0]` now refers to the array pointed to by `b` and `a`.

```
d[1] = c
```

`d[1]` is the array referred to by `c`.

```
d[0][2]
```

Accesses element 2 of the array referred to by `d[0]`. This is the same element as `a[2]`.

Brackets (`[]`) are used in this instance to represent array references and are part of the statement syntax.

Related Topics

[makeVector](#)

defprop

```
defprop(  
    s_id  
    g_value  
    s_name  
)  
=> g_value
```

Description

Adds properties to symbols but none of its arguments are evaluated. This is a syntax form.

The same as `putprop` except that none of its arguments are evaluated.

Arguments

| | |
|----------------|------------------------------|
| <i>s_id</i> | Symbol to add property to. |
| <i>g_value</i> | Value of the named property. |
| <i>s_name</i> | Named property. |

Value Returned

| | |
|----------------|------------------------------|
| <i>g_value</i> | Value of the named property. |
|----------------|------------------------------|

Examples

Sets property `x` on symbol `s` to 3.

```
defprop(s 3 x)  
=> 3
```

Sets property `x` on symbol `s` to the unevaluated expression `1+2`.

```
defprop(s 1+2 x)  
=> (1+2)
```

Related Topics

[get](#)

[putprop](#)

defstruct

```
defstruct (  
    s_name  
    s_slot1 [ s_slot2...]  
)  
=> t
```

Description

Creates a `defstruct`, a named structure that is a collection of one or more variables.

`Defstructs` can have slots of different types that are grouped together under a single name for handling purposes. They are the equivalent of structs in C. The `defstruct` form also creates an instantiation function, named `make_<name>` where `name` is the structure name supplied to `defstruct`. This constructor function takes keyword arguments: one for each slot in the structure. Once created, structures behave just like disembodied property lists.

Note: Just like disembodied property lists, structures can have new slots added at any time. However these dynamic slots are less efficient than the statically declared slots, both in access time and space utilization.

Structures can contain instances of other structures; therefore one needs to be careful about structure sharing. If sharing is not desired, a special copy function can be used to generate a copy of the structure being inserted. The `defstruct` form also creates a function for the given `defstruct` called `copy_<name>`. This function takes one argument, an instance of the `defstruct`. It creates and returns a copy of the given instance. An example appears after the description of the other `defstruct` functions.

Arguments

| | |
|----------------------|--|
| <code>s_name</code> | A structure name. |
| <code>s_slot1</code> | Name of the first slot in structure <code>s_name</code> . |
| <code>s_slot2</code> | Name of the second slot in structure <code>s_name</code> . |

Value Returned

| | |
|----------------|---------------------------------|
| <code>t</code> | Always returns <code>t</code> . |
|----------------|---------------------------------|

Examples

Returns the value associated with a slot of an instance.

```
defstruct(myStruct slot1 slot2 slot3)
struct = make_myStruct(?slot1 "one" ?slot2 "two" ?slot3 "three")
=>t

struct->slot1
=> "one"
```

Modifies the value associated with a slot of an instance.

```
struct->slot1 = "new"
=> "new"
```

Returns a list of the slot names associated with an instance.

```
struct->?
=> (slot3 slot2 slot1)
```

Returns a property list (not a disembodied property list) containing the slot names and values associated with an instance.

```
struct->??
=> (slot3 "three" slot2 "two" slot1 "new")
```

Related Topics

[defstruct](#)

[printstruct](#)

defstructp

```
defstructp(  
    g_object  
    [ S_name ]  
)  
=> t / nil
```

Description

Checks if an object is an instance of a particular `defstruct`.

If the optional second argument is given, it is used as the `defstruct` name to check against. The suffix `p` is usually added to the name of a function to indicate that it is a predicate function.

Arguments

| | |
|-----------------|---|
| <i>g_object</i> | A data object. |
| <i>S_name</i> | Name of the structure to be tested for. |

Value Returned

| | |
|------------|---|
| <i>t</i> | If <i>g_object</i> is an instance of <code>defstruct</code> <i>S_name</i> . |
| <i>nil</i> | The object is not an instance of the <code>defstruct</code> . |

Examples

```
defstruct(myStruct slot1 slot2 slot3)  
=> t  
struct = _myStruct(?slot1 "one" ?slot2 "two" ?slot3 "three")  
=> array[5]:3555552  
defstructp( "myDefstruct")  
=> nil  
defstructp(struct 'myStruct)  
=> t
```

Related Topics

[defstruct](#)

[printstruct](#)

defvar

```
defvar(  
    s_varName  
    [ g_value ]  
)  
=> g_value / nil
```

Description

Defines a variable and assign it a value. The variable defined follows the scoping rule.

Arguments

| | |
|------------------|--|
| <i>s_varName</i> | Name of the variable to be defined. |
| <i>g_value</i> | Value to assign to the variable. If <i>g_value</i> is not given, <code>nil</code> is assigned to the variable. |

Value Returned

| | |
|------------------|------------------------------------|
| <i>g_value</i> | The value of the defined variable. |
| <code>nil</code> | The variable is not defined. |

Examples

The following example assigns `x` a value of 3.

```
defvar(x 3)  
=> 3
```

Related Topics

[defprop](#)

[set](#)

[setq](#)

[Contrast Variable Scoping](#)

makeTable

```
makeTable(  
    S_name  
    [ g_default_value ]  
)  
=> o_table
```

Description

Creates an empty association table.

Arguments

| | |
|------------------------|--|
| <i>S_name</i> | Print name (either a string or symbol) of the new table. |
| <i>g_default_value</i> | Default value to be returned when references are made to keys that are not in the table. If no default value is given, the system returns <code>unbound</code> if the key is not defined in the table. |

Value Returned

| | |
|----------------|----------------------------|
| <i>o_table</i> | The new association table. |
|----------------|----------------------------|

Examples

If you specify a default value when you create the table, the default value is returned if a nonexistent key is accessed.

```
myTable = makeTable("atable1" 0)  
=> table:atable1  
  
myTable[1]  
=> 0
```

If you do not specify a default value when you create the table, the symbol `unbound` is returned if an undefined key is accessed.

```
myTable2 = makeTable("atable2")  
=> table:atable2  
  
myTable2[1]  
=> unbound
```

You can refer to and set the contents of an association table with the standard syntax for accessing array elements

Cadence SKILL Language Reference

Data Structures

```
myTable[1] = "blue"
=> blue

myTable["two"] = '(r e d)
=> (r e d)

myTable['three] = 'green
=> green

myTable['three]
=> green
```

Related Topics

[declare](#)

[Association Tables](#)

makeVector

```
makeVector(  
    x_size  
    [ g_init_val ]  
)  
=> a_vectorArray
```

Description

Creates an array (vector) with the specified number of elements, and optionally initializes each entry.

Allocates a vector of *x_size* number of entries. *Vector* initializes each entry in the vector with *g_init_val*. The default value of *g_init_val* is the symbol *unbound*.

Arguments

| | |
|-------------------|--|
| <i>x_size</i> | Size of the vector to be allocated. |
| <i>g_init_val</i> | Initial value of each entry of the vector to be allocated. |

Value Returned

| | |
|----------------------|--------------------------|
| <i>a_vectorArray</i> | Array of the given size. |
|----------------------|--------------------------|

Examples

```
V = makeVector( 3 0 )  
=> array[3]:1955240  
  
V[0]  
=> 0  
  
V[1]  
=> 0  
  
V[2]  
=> 0
```

Related Topics

[vector](#)

[vectorp](#)

setarray

```
setarray(  
    a_array  
    x_index  
    g_value  
)  
=> g_value  
  
setarray(  
    o_table  
    g_key  
    g_value  
)  
=> g_value
```

Description

Assigns the given value to the specified element of an array or to the specified key of a table. Normally this function is invoked implicitly using the array-subscription syntax, such as, `x[i] = v`.

Assigns *g_value* to the *x_index* element of *a_array*, or adds the association of *g_value* with *g_key* to *o_table*, and returns *g_value*. Normally this function is invoked implicitly using the array-subscription syntax, such as, `x[i] = v`.

Arguments

| | |
|----------------|---|
| <i>a_array</i> | An array object. |
| <i>x_index</i> | Index of the array element to assign a value to. Must be between 0 and one less than the size of the array. |
| <i>g_key</i> | Any SKILL value. |
| <i>g_value</i> | Value to be assigned to the specified array element or table entry. |

Value Returned

| | |
|----------------|---|
| <i>g_value</i> | Value assigned to the specified array element or table entry. |
|----------------|---|

Examples

```
declare(myar[8])  
=> array[8]:3895304
```

Cadence SKILL Language Reference

Data Structures

```
myar[0]
=> unbound
setarray(myar 0 5)
=> 5
myar[0]
=> 5
setarray(myar 8 'hi)
```

Signals an array bounds error.

```
setarray(myar
          (plus 1 2)           ; assigns element 3 the value 8.
          (plus 3 5))
=> 8

mytab = makeTable('myTable)
=> table:myTable

setarray(mytab 8 4)
=> 4
mytab[8]
=> 4
mytab[9] = 3
=> 3      ; same as setarray(mytab 9 3)
mytab[9]
=> 3
```

Related Topics

[arrayref](#)

[declare](#)

tablep

```
tablep(  
    g_object  
)  
=> t / nil
```

Description

Checks if an object is an association table.

The suffix *p* is usually added to the name of a function to indicate that it is a predicate function.

Arguments

| | |
|-----------------|-----------------|
| <i>g_object</i> | A SKILL object. |
|-----------------|-----------------|

Value Returned

| | |
|------------|---|
| <i>t</i> | If <i>g_object</i> is an association table. |
| <i>nil</i> | If <i>g_object</i> is not an association table. |

Examples

```
myTable = makeTable("atable1" 0)  
=> table:atable1  
tablep(myTable)  
=> t  
tablep(9)  
=> nil
```

Related Topics

[makeTable](#)

type, typep

```
type (
    s_object
)
=> s_type

typep (
    s_object
)
=> s_type
```

Description

Returns a symbol that indicates the type of a SKILL object. The functions `type` and `typep` are identical. The suffix `p` is usually added to the name of a function to indicate that it is a predicate function.

Arguments

| | |
|-----------------|-----------------|
| <i>s_object</i> | A SKILL object. |
|-----------------|-----------------|

Value Returned

| | |
|---------------|---|
| <i>s_type</i> | Symbol indicating the type of <i>s_object</i> . |
|---------------|---|

Examples

```
type( 'foo )
=> symbol

typep( "foo" )
=> string

type( 12 )
=> fixnum

typep( "12" )
=> string
```

Related Topics

[fixp](#)

[floatp](#)

Cadence SKILL Language Reference

Data Structures

numberp

portp

stringp

symbolp

vector

```
vector(  
    g_value ...  
)  
=> a_vectorArray
```

Description

Returns a vector or array, filled with the arguments in the given order. The `vector` function is analogous to the `list` function.

A vector is implemented as a SKILL array.

Arguments

| | |
|----------------|--|
| <i>g_value</i> | Ordered list of values to be placed in an array. |
|----------------|--|

Value Returned

| | |
|----------------------|---|
| <i>a_vectorArray</i> | Array filled with the arguments in the given order. |
|----------------------|---|

Examples

```
V = vector( 1 2 3 4 )  
=> array[4]:33394440  
  
V[0]  
=> 1  
  
V[3]  
=> 4
```

Related Topics

[declare](#)

[list](#)

[makeVector](#)

vectorp

```
vectorp(  
    g_value  
)  
=> t / nil
```

Description

Checks whether the specified object is a vector. The behavior of this SKILL function is the same as `arrayp`.

The suffix `p` is usually added to the name of a function to indicate that it is a predicate function.

Arguments

| | |
|----------------|------------------|
| <i>g_value</i> | Any data object. |
|----------------|------------------|

Value Returned

| | |
|------------|---|
| <i>t</i> | If <i>g_value</i> is a vector object. |
| <i>nil</i> | If <i>g_value</i> is not a vector object. |

Examples

```
declare(x[10])  
arrayp(x)  
=> t  
  
arrayp('x')  
=> nil
```

Related Topics

[declare](#)

[arrayp](#)

Data Operator Functions

This topic lists the SKILL functions related to data operators.

| | | |
|--------------------------|---------------------------|-----------------------------|
| <u>alphaNumCmp</u> | <u>concat</u> | <u>copy_ <name></u> |
| <u>copyDefstructDeep</u> | <u>get</u> | <u>getSG</u> |
| <u>getq</u> | <u>getqq</u> | <u>importSkillVar</u> |
| <u>integerp</u> | <u>make_ <name></u> | <u>otherp</u> |
| <u>plist</u> | <u>popf</u> | <u>postArrayDec</u> |
| <u>postArrayInc</u> | <u>postArraySet</u> | <u>postdecrement</u> |
| <u>postincrement</u> | <u>preArrayDec</u> | <u>preArrayInc</u> |
| <u>preArraySet</u> | <u>predecrement</u> | <u>preincrement</u> |
| <u>pushf</u> | <u>putprop</u> | <u>putpropq</u> |
| <u>quote</u> | <u>remprop</u> | <u>rotatef</u> |
| <u>set</u> | <u>setf</u> | <u>setf_ <helper></u> |
| <u>setguard</u> | <u>setplist</u> | <u>setq</u> |
| <u>setSG</u> | <u>symbolp</u> | <u>symeval</u> |
| <u>symstrp</u> | | |

alphaNumCmp

```
alphaNumCmp (
    S_arg1
    S_arg2
    [ g_arg3 ]
)
=> 1 / 0 / -1
```

Description

Compares two string or symbol names alphanumerically or numerically.

If the third optional argument is non-`nil` and the first two arguments are strings holding purely numeric values, then a numeric comparison is performed on the numeric representation of the strings.

Arguments

| | |
|---------------|---|
| <i>S_arg1</i> | First string or symbol to compare. |
| <i>S_arg2</i> | String or symbol to compare against <i>S_arg1</i> . |
| <i>g_arg3</i> | If non- <code>nil</code> , can cause a numeric comparison of <i>S_arg1</i> and <i>S_arg2</i> depending whether those arguments are strings holding purely numeric values. |

Value Returned

| | |
|----|---|
| 1 | If <i>S_arg1</i> is alphanumerically greater than <i>S_arg2</i> |
| 0 | If <i>S_arg1</i> is alphanumerically identical to <i>S_arg2</i> . |
| -1 | If <i>S_arg2</i> is alphanumerically greater than <i>S_arg1</i> . |

Examples

```
alphaNumCmp ( "a" "b" )
=> -1
alphaNumCmp ( "b" "a" )
=> 1
alphaNumCmp ( "name12" "name12" )
=> 0
alphaNumCmp ( "name23" "name12" )
=> 1
```

Cadence SKILL Language Reference

Data Operator Functions

```
alphaNumCmp ( "00.09" "9.0E-2" t)  
=> 0
```

Related Topics

[strcmp](#)

[strncmp](#)

concat

```
concat(  
    Sx_arg1  
    [ Sx_arg2 ... ]  
)  
=> s_result
```

Description

Concatenates strings, symbols, or integers into a single symbol.

This function is useful for converting strings to symbols. To concatenate several strings and have a single string returned, use the `strcat` function. Symbol names are limited to 255 characters.

Symbol functions such as `eq`, `memq`, and `caseq` are much faster than their siblings `equal`, `member`, and `case` because they compare pointers rather than data. You can use `concat` to convert a string to a symbol before performing `memq` on large lists for increased speed.

Arguments

| | |
|----------------|--|
| <i>Sx_arg1</i> | String, symbol, or integer to be concatenated. |
| <i>Sx_arg2</i> | Zero or more strings, symbols, or integers to be concatenated. |

Value Returned

| | |
|-----------------|---|
| <i>s_result</i> | Returns a symbol whose print name is the result of concatenating the printed representation of the argument or arguments. |
|-----------------|---|

Examples

This demonstrates using `concat` to take advantage of the faster functions such as `memq`.

```
concat("string")  
=> string  
concat("ab" 123 'xy)  
=> ab123xy  
memq( concat( "c" ) '(a b c d e))  
=> (c d e)
```


Related Topics

strcat

member, memq, memv

copy_<name>

```
copy_<name>(
    r_defstruct
)
=> r_defstruct
```

Description

Creates and returns a copy of a structure. This function is created by the `defstruct` function where *name* is the name of the defstruct.

Structures can contain instances of other structures; therefore you need to be careful about structure sharing. If sharing is not desired, use the `copyDefstructDeep` function to generate a copy of the structure and its sub-elements.

Arguments

| | |
|--------------------|-----------------------------|
| <i>r_defstruct</i> | An instance of a defstruct. |
|--------------------|-----------------------------|

Value Returned

| | |
|--------------------|-----------------------------|
| <i>r_defstruct</i> | Copy of the given instance. |
|--------------------|-----------------------------|

Examples

```
defstruct(myStruct a b c)
=> t

m1 = _myStruct(?a 3 ?b 2 ?c 1)
=> array[x]:xxxx

m2 = copy_myStruct(m1)
=> array[x]:xxxx
```

Related Topics

[copyDefstructDeep](#)

[make_<name>](#)

[printstruct](#)

copyDefstructDeep

```
copyDefstructDeep(  
    r_object  
)  
=> r_defstruct
```

Description

Performs a deep or recursive copy on defstructs with other defstructs as sub-elements, making copies of all the defstructs encountered.

The various `copy_<name>` functions are called to create copies for the various defstructs encountered in the deep copy.

Only defstruct sub-elements are recursively copied. Other data types, like lists, are still shared.

Arguments

| | |
|-----------------------|-----------------------------|
| <code>r_object</code> | An instance of a defstruct. |
|-----------------------|-----------------------------|

Value Returned

| | |
|--------------------------|------------------------------------|
| <code>r_defstruct</code> | A deep copy of the given instance. |
|--------------------------|------------------------------------|

Examples

```
defstruct(myStruct a b c) => t ;creates a function _myStruct  
  
m1 = _myStruct(?a 3 ?b 2 ?c 1)  
=> array[5]:3873024  
  
m2 = _myStruct(?a m1 ?b '(a b c) ?c 5)  
=> array[5]:3873208 ; m1 is m2's sub-element  
  
m3 = copyDefstructDeep(m2)  
=> array[5]:3873056 ; uses deep copy  
  
m3->a  
=> array[5]:3873344 ; a new object  
  
eq(m3->a m2->a) => nil ; eq checks object identity
```

Cadence SKILL Language Reference

Data Operator Functions

```
m2->b
=> (a b c)

eq(m3->b m2->b)
=> t                                ; still sharing the same object because
                                    ; the sub-element b is not a defstruct

m4 = copy_myStruct(m2)
=> array[5]:3873376                 ; uses shallow copy

m4->a => array[5]:3873024
eq(m4->a m2->a) => t                 ; share identical substructure
eq(m4->b m2->b) => t                 ; the same object
```

Related Topics

copy_<name>

printstruct

get

```
get (
    sl_id
    S_name
)
=> g_result / nil
```

Description

Returns the value of a property in a property list (including disembodied property list), association table, structure, database object, and a standard object (instance of a user-defined subclass of standardObject). `get` has no infix operator syntax.

Used in conjunction with `putprop`, where `putprop` stores the property and `get` retrieves it.

Arguments

| | |
|---------------|---|
| <i>sl_id</i> | Symbol or disembodied property list. |
| <i>S_name</i> | Name of the property you want the value of. |

Value Returned

| | |
|-----------------|---|
| <i>g_result</i> | Value of <i>S_name</i> in the <i>sl_id</i> property list. |
| nil | The named property does not exist. |

Examples

```
putprop( 'chip 8 'pins )
=> 8
```

Assigns the property pins to a value of 8 to the symbol chip.

```
get( 'chip 'pins )
=> 8
chip.pins
=> 8

x = '(nil a 3 b 4)           ;a disembodied property list
x->a
=> 3
get(x 'a)
=> 3
```

Related Topics

[plist](#)

[putprop](#)

getSG

```
getSG(  
    g_obj  
    S_prop  
)  
=> g_propValue
```

Description

Evaluates and then retrieves the value of the specified attribute or property. It is a lambda implementation of `getSGq()`.

Arguments

| | |
|---------------|--|
| <i>g_obj</i> | Specifies the name of an object |
| <i>S_prop</i> | Specifies the name of the attribute or property for which you want to retrieve the value |

Value Returned

| | |
|--------------------|---------------------------|
| <i>g_propValue</i> | The value of the property |
|--------------------|---------------------------|

Examples

In the following example, `getSG()` evaluates the `tbl_list` argument and then retrieves its value.

```
tbl_list = list( (Table 'a nil)  
    Table( 'b nil)  
    Table( 'c nil))  
setSG( tbl_list 41 'x)  
=> '(41 41 41)  
  
getSG( tbl_list 'x)  
=> '(41 41 41)
```

Related Topics

[get](#)

getq

```
getq(  
    sl_id  
    S_name  
)  
=> g_result / nil  
  
    sl_id->S_name  
=> g_result / nil
```

Description

Returns the value of a property in a property list. Same as `get` except that the second argument is not evaluated. This is a syntax form.

`getq` corresponds to `->` as an LHS infix operator. So, `obj->prop` is equivalent to `getq(obj prop)`.

Used in conjunction with `putprop`, where `putprop` stores the property and `getq` retrieves it.

Arguments

| | |
|---------------|---|
| <i>sl_id</i> | Symbol or disembodied property list. |
| <i>S_name</i> | Name of the property you want the value of. |

Value Returned

| | |
|-----------------|---|
| <i>g_result</i> | Value of <i>S_name</i> in the <i>sl_id</i> property list. |
| <i>nil</i> | The named property does not exist. |

Examples

```
putprop( 'chip 8 'pins )  
=> 8
```

Assigns the property `pins` to a value of 8 to the symbol `chip`.

```
getq( 'chip pins )  
=> 8  
  
chip.pins  
=> 8  
  
chip1 = list(nil 'pins 10)  
=> (nil pins 10)
```


Cadence SKILL Language Reference

Data Operator Functions

```
chip1->pins  
=> 10
```

Related Topics

[get](#)

[getqq](#)

[plist](#)

[putprop](#)

[Mapping Symbols to Values](#)

getqq

```
getqq(  
    s_id  
    S_name  
)  
=> g_result / nil  
  
    sl_id.S_name  
=> g_result / nil
```

Description

Returns the value of a property in a symbol's property list. Same as `get` except that neither argument is evaluated. This is a syntax form.

`getqq` corresponds to `.` as an LHS infix operator. So, `obj.prop` is equivalent to `getqq(obj prop)`.

Used in conjunction with `putprop`, where `putprop` stores the property and `getqq` retrieves it.

Arguments

| | |
|---------------|---|
| <i>s_id</i> | Symbol to get a property from. |
| <i>S_name</i> | Name of the property you want the value of. |

Value Returned

| | |
|-----------------|---|
| <i>g_result</i> | Value of the property <i>S_name</i> in the property list of <i>s_id</i> . |
| <i>nil</i> | The named property does not exist. |

Examples

```
putprop( 'chip 8 'pins )  
=> 8
```

Assigns the property `pins` to a value of 8 to the symbol `chip`.

```
getqq( chip pins )  
=> 8  
chip.pins  
=> 8
```

Cadence SKILL Language Reference

Data Operator Functions

Related Topics

[get](#)

[getqq](#)

[plist](#)

[putprop](#)

[Mapping Symbols to Values](#)

importSkillVar

```
importSkillVar(  
    s_variable ...  
)  
=> t / nil
```

Description

(SKILL++ mode) Tells the compiler that the given variable names should be treated as SKILL global variables in SKILL++ code.

All global SKILL functions are automatically accessible from SKILL++ code, but not the SKILL variables. This form tells the compiler that the given variable names should be treated as SKILL global variables in SKILL++ code.

This function returns `nil` if there is already a SKILL++ global variable of the same name defined. Also remember that local variables can use the same name and always take precedence.

This only means that the variables will be accessed as SKILL globals, *NOT* that they will follow SKILL's dynamic scope rule in SKILL++ code.

Arguments

| | |
|-------------------|---|
| <i>s_variable</i> | Variable to be treated as SKILL global variables in SKILL++ code. |
|-------------------|---|

Value Returned

| | |
|------------------|---|
| <code>t</code> | All variables were imported successfully. |
| <code>nil</code> | One or more variables failed to import. |

Note: If the variables are not imported, a warning message displays.

Examples

The following example shows assigning a value to the global variable `q` in SKILL mode and then importing the variable into SKILL++.

```
> q = 1  
=> 1
```

Cadence SKILL Language Reference

Data Operator Functions

```
> toplevel 'ils
ILS-<2> q
*Error* eval: unbound variable - q
ILS-<2> importSkillVar( q )
=> 1

ILS-<2> q
=> 1
```

Related Topics

[get](#)

integerp

```
integerp(  
    g_obj  
)  
=> t / nil
```

Description

Checks if an object is an integer. This function is the same as `fixp`.

The suffix `p` is usually added to the name of a function to indicate that it is a predicate function.

Arguments

| | |
|--------------------|-------------------|
| <code>g_obj</code> | Any SKILL object. |
|--------------------|-------------------|

Value Returned

| | |
|------------------|-------------------------------------|
| <code>t</code> | The given object is an integer. |
| <code>nil</code> | The given object is not an integer. |

Examples

```
(integerp 123)  
=> t  
(integerp "123")  
=> nil
```

Related Topics

[fixp](#)

make_<name>

```
make_<name>(
    ...
)
=> r_defstruct
```

Description

Creates an instance of a *defstruct* specified by *name*.

Arguments

... Initial values for structure elements (slots).

Value Returned

r_defstruct Copy of the given instance

Examples

```
defstruct(myStruct a b c)
=> t

m1 = make_myStruct(?a 3 ?b 2 ?c 1)
=> array[5]:3436504

m2 = copy_myStruct(m1)
=> array[5]:3436168
```

Related Topics

[copy_<name>](#)

[copyDefstructDeep](#)

[printstruct](#)

otherp

```
otherp(  
    g_value  
)  
=> t / nil
```

Description

Checks if an object is a user type object, such as an association table or a window.

The suffix `p` is usually added to the name of a function to indicate that it is a predicate function.

Arguments

| | |
|----------------|----------------|
| <i>g_value</i> | A data object. |
|----------------|----------------|

Value Returned

| | |
|------------------|--|
| <code>t</code> | If <i>g_value</i> is a user type object. |
| <code>nil</code> | If <i>g_value</i> is not a user type object. |

Examples

```
otherp(3.0)  
=> nil  
otherp( makeTable("table1" nil))  
=> t
```

Related Topics

[plist](#)

plist

```
plist(  
    s_symbolName  
)  
=> l_propertyList / nil
```

Description

Returns the property list associated with a symbol.

From time to time, it is useful to print the entire property list attached to a given symbol and see what properties have been assigned to the symbol.

Arguments

| | |
|---------------------|---------------------|
| <i>s_symbolName</i> | Name of the symbol. |
|---------------------|---------------------|

Value Returned

| | |
|-----------------------|--|
| <i>l_propertyList</i> | Property list for the named symbol. |
| <i>nil</i> | If there is no property list for the named symbol. |

Examples

Prints the property list attached to the symbol `a`. Returns `nil`, the result of `println`. Notice that a single quote is used in this example. You can think of this as passing in the name of the symbol rather than its value.

```
a.x = 10  
a.y = 20  
println(plist('a'))  
(y 20 x 10)  
=> nil
```

Related Topics

[putprop](#)

[setplist](#)

popf

```
popf(  
    g_place  
)  
=> g_result
```

Description

A pop that uses the `setf` function. It returns the value for *g_place* that is removed.

Arguments

| | |
|----------------|-----------------------|
| <i>g_place</i> | Place to be modified. |
|----------------|-----------------------|

Value Returned

| | |
|-----------------|---|
| <i>g_result</i> | The value for <i>g_place</i> that is removed. |
|-----------------|---|

Examples

```
a = '((4 1) 2 3)  
popf(car(a) )  
=> 4  
a == '((1) 2 3)
```

Related Topics

[setf](#)

[pushf](#)

postArrayDec

```
postArrayDec(  
    g_array  
    g_index  
)  
=> n_oldValue
```

Description

Takes an array or an associated table element with an index *g_index*, decrements its value by one, stores the new value back into the array, and returns the original value. This function is a prefix form of *s--*.

If the associated table element is not a number or *g_index* is not valid, it returns an error.

Arguments

| | |
|----------------|---|
| <i>g_array</i> | An array or an associated table. |
| <i>g_index</i> | An index in the array or an associated table. |

Value Returned

| | |
|-------------------|--------------------------------|
| <i>n_oldValue</i> | Original value of the element. |
|-------------------|--------------------------------|

Examples

```
a = vector(1 2 34)  
array@0x8382028  
postArrayDec(a 2)  
=> 34  
  
postArrayDec(a -4)  
*Error* setarray: array index out of bounds -  
postArrayDec(a -4)
```

Related Topics

[postArrayInc](#)

[postArraySet](#)

[postArrayDec](#)

Cadence SKILL Language Reference

Data Operator Functions

preArrayInc

preArraySet

postArrayInc

```
postArrayInc(  
    g_array  
    g_index  
)  
=> n_oldValue
```

Description

Takes an array or an associated table element with an index *g_index*, increments its value by one, stores the new value back into the array, and returns the original value. This function is a prefix form of `s++`.

If the associated table element is not a number or *g_index* is not valid, it returns an error.

Arguments

| | |
|----------------|---|
| <i>g_array</i> | An array or an associated table. |
| <i>g_index</i> | An index in the array or an associated table. |

Value Returned

| | |
|-------------------|--------------------------------|
| <i>n_oldValue</i> | Original value of the element. |
|-------------------|--------------------------------|

Examples

```
a = vector(1 2 34)  
array@0x8382028  
postArrayInc(a 2)  
=> 34  
  
a[2]  
=> 35  
  
postArrayInc(a -4)  
*Error* setarray: array index out of bounds -  
postArrayInc(a -4)
```

Related Topics

[postArrayDec](#)

[postArraySet](#)

Cadence SKILL Language Reference

Data Operator Functions

preArrayDec

preArrayInc

preArraySet

postArraySet

```
postArraySet (
    g_array
    g_index
    n_modifier
)
=> n_oldValue
```

Description

Takes an array or an associated table element with an index *g_index*, adds an *n_modifier* value to its original value, stores the new value back into the array, and returns the original value.

If the associated table element is not a number or *g_index* is not valid, it returns an error.

Arguments

| | |
|-------------------|---|
| <i>g_array</i> | An array or an associated table. |
| <i>g_index</i> | An index in the array or an associated table. |
| <i>n_modifier</i> | Value that should be added to the element. |

Value Returned

| | |
|-------------------|--------------------------------|
| <i>n_oldValue</i> | Original value of the element. |
|-------------------|--------------------------------|

Examples

```
a = vector(1 2 34)
array@0x8382028
postArraySet(a 2 3)
=> 34

postArraySet(a -4 9)
*Error* setarray: array index out of bounds -
postArraySet(a -4 9)
```

Related Topics

[postArrayDec](#)

[postArrayInc](#)

Cadence SKILL Language Reference

Data Operator Functions

preArrayDec

preArrayInc

preArraySet

postdecrement

```
postdecrement (
    s_var
)
=> n_result
```

Description

Takes a variable, decrements its value by one, stores the new value back into the variable, and returns the original value. This function is a prefix form of `s--`. The name of the variable must be a symbol and the value must be a number.

Arguments

| | |
|--------------|---------------------------------|
| <i>s_var</i> | Variable representing a number. |
|--------------|---------------------------------|

Value Returned

| | |
|-----------------|---------------------------------|
| <i>n_result</i> | Original value of the variable. |
|-----------------|---------------------------------|

Examples

```
s = 2
postdecrement( s )
=> 2
s
=> 1

s = 2.2
postdecrement( s )
=> 2.2
s
=> 1.2
```

Related Topics

[postincrement](#)

[predecrement](#)

[preincrement](#)

postincrement

```
postincrement(  
    s_var  
)  
=> n_result
```

Description

Takes a variable, increments its value by one, stores the new value back into the variable, and returns the original value. This function is a prefix form of `s++`. The name of the variable must be a symbol and the value must be a number.

Arguments

| | |
|--------------|---------------------------------|
| <i>s_var</i> | Variable representing a number. |
|--------------|---------------------------------|

Value Returned

| | |
|-----------------|---------------------------------|
| <i>n_result</i> | Original value of the variable. |
|-----------------|---------------------------------|

Examples

```
s = 2  
postincrement( s )  
=> 2  
s  
=> 3  
s = 2.2  
postincrement( s )  
=> 2.2  
s  
=> 3.2
```

Related Topics

[postdecrement](#)

[predecrement](#)

[preincrement](#)

preArrayDec

```
preArrayDec (
    g_array
    g_index
)
=> n_newValue
```

Description

Takes an array or an associated table element with an index *g_index*, decrements its value by one, stores the new value back into the array, and returns the updated value. This function is a prefix form of `--s`.

If the associated table element is not a number or *g_index* is not valid, it returns an error.

Arguments

| | |
|----------------|---|
| <i>g_array</i> | An array or an associated table. |
| <i>g_index</i> | An index in the array or an associated table. |

Value Returned

| | |
|-------------------|---------------------------|
| <i>n_newValue</i> | New value of the element. |
|-------------------|---------------------------|

Examples

```
a = vector(1 2 34)
array@0x8382028
preArrayDec(a 2)
=> 33

preArrayDec(a -4)
*Error* setarray: array index out of bounds -
preArrayDec(a -4)
```

Related Topics

[postdecrement](#)

[predecrement](#)

[preincrement](#)

preArrayInc

```
preArrayInc(  
    g_array  
    g_index  
)  
=> n_newValue
```

Description

Takes an array or an associated table element with an index *g_index*, increments its value by one, stores the new value back into the array, and returns the updated value. This function is a prefix form of `++s`.

If the associated table element is not a number or *g_index* is not valid, it returns an error.

Arguments

| | |
|----------------|---|
| <i>g_array</i> | An array or an associated table. |
| <i>g_index</i> | An index in the array or an associated table. |

Value Returned

| | |
|-------------------|---------------------------|
| <i>n_newValue</i> | New value of the element. |
|-------------------|---------------------------|

Examples

```
a = vector(1 2 34)  
array@0x8382028  
preArrayInc(a 2)  
=> 35  
  
preArrayInc(a -4)  
*Error* setarray: array index out of bounds -  
preArrayInc(a -4)
```

Related Topics

[postdecrement](#)

[predecrement](#)

[preincrement](#)

preArraySet

```
preArraySet (  
    g_array  
    g_index  
    n_modifier  
)  
=> n_newValue
```

Description

Takes array or an associated table element with an index *g_index*, adds an *n_modifier* value to its original value, stores the new value back into the array, and returns the updated value.

If the associated table element is not a number or *g_index* is not valid, it returns an error.

Arguments

| | |
|-------------------|--|
| <i>g_array</i> | An array or an associated table. |
| <i>g_index</i> | An index in the array or an associated table. |
| <i>n_modifier</i> | The value that should be added to the element. |

Value Returned

| | |
|-------------------|---|
| <i>n_newValue</i> | New value of the element i.e, (<i>g_array</i> [<i>g_index</i>] + <i>n_modifier</i>) |
|-------------------|---|

Examples

```
a = vector(1 2 34)  
array@0x8382028  
preArraySet(a 2 3)  
=> 37  
  
preArraySet(a -4 9)  
*Error* setarray: array index out of bounds -  
preArraySet(a -4 9)
```

Related Topics

[postdecrement](#)

Cadence SKILL Language Reference

Data Operator Functions

predecrement

preincrement

predecrement

```
predecrement (
    s_var
)
=> n_result
```

Description

Takes a variable, decrements its value by one, stores the new value back into the variable, and returns the new value. This function is a prefix form of `--s`. The name of the variable must be a symbol and the value must be a number.

Arguments

| | |
|--------------|---------------------------------|
| <i>s_var</i> | Variable representing a number. |
|--------------|---------------------------------|

Value Returned

| | |
|-----------------|----------------------------------|
| <i>n_result</i> | Decrement value of the variable. |
|-----------------|----------------------------------|

Examples

```
s = 2
predecrement( s )
=> 1
s => 1

s = 2.2
predecrement( s )
=> 1.2
s => 1.2
```

Related Topics

[postdecrement](#)

[predecrement](#)

[preincrement](#)

preincrement

```
preincrement(  
    s_var  
)  
=> n_result
```

Description

Takes a variable, increments its value by one, stores the new value back into the variable, and returns the new value. This function is a prefix form of `++s`. The name of the variable must be a symbol and the value must be a number.

Arguments

| | |
|--------------|---------------------------------|
| <i>s_var</i> | Variable representing a number. |
|--------------|---------------------------------|

Value Returned

| | |
|-----------------|------------------------------------|
| <i>n_result</i> | Incremented value of the variable. |
|-----------------|------------------------------------|

Examples

```
s = 2  
preincrement( s )  
=> 3  
s => 3  
  
s = 2.2  
preincrement( s )  
=> 3.2  
s => 3.2
```

Related Topics

[postdecrement](#)

[predecrement](#)

pushf

```
pushf(  
    g_obj  
    g_place  
)  
=> g_newPlaceValue
```

Description

A push that uses the `setf` function. It modifies the contents of the original storage location.

Arguments

| | |
|----------------|--|
| <i>g_obj</i> | New value to be pushed. |
| <i>g_place</i> | Place to be modified with the new value. |

Value Returned

| | |
|------------------------|------------|
| <i>g_newPlaceValue</i> | New value. |
|------------------------|------------|

Examples

```
a = list((list 1) 2 3)  
pushf(4 (car a))  
=> a == '((4 1) 2 3)
```

Related Topics

[setf](#)

[popf](#)

putprop

```
putprop(  
    sl_id  
    g_value  
    S_name  
)  
=> g_value
```

Description

Adds properties to symbols or disembodied property lists.

If the property already exists, the old value is replaced with a new one. The `putprop` function is a `lambda` function, which means all of its arguments are evaluated. However, `putprop` has no infix operator syntax.

Arguments

| | |
|----------------|--------------------------------------|
| <i>sl_id</i> | Symbol or disembodied property list. |
| <i>g_value</i> | Value of the named property. |
| <i>S_name</i> | Name of the property. |

Value Returned

| | |
|----------------|----------------------------------|
| <i>g_value</i> | The value of the named property. |
|----------------|----------------------------------|

Examples

Sets the property `x` on symbol `s` to 3.

```
putprop('s 1+2 'x)  
=> 3
```

Related Topics

[get](#)

[putpropq](#)

[putpropqq](#)

putpropq

```
putpropq(  
    sl_id  
    g_value  
    S_name  
)  
=> g_value  
  
    sl_id->S_name = g_value  
=> g_value
```

Description

Adds properties to symbols or disembodied property lists. Identical to `putprop` except that *S_name* is not evaluated. If the property already exists, the old value is replaced with a new one.

`putpropq` corresponds to `-> =` as an assignment operator. So, `obj->prop = value` is equivalent to `putpropq(obj value prop)`.

Arguments

| | |
|----------------|--------------------------------------|
| <i>sl_id</i> | Symbol or disembodied property list. |
| <i>g_value</i> | Value of the named property. |
| <i>S_name</i> | Name of the property. |

Value Returned

| | |
|----------------|------------------------------|
| <i>g_value</i> | Value of the named property. |
|----------------|------------------------------|

Examples

Both examples are equivalent expressions that set the property `x` on symbol `s` to 3.

```
putpropq('s 1+2 x)  
=> 3  
  
y = 'x  
=> x  
  
y->x = 1+2  
=> 3
```

Related Topics

[get](#)

[putpropq](#)

[putpropqq](#)

[Mapping Symbols to Values](#)

putpropqq

```
putpropqq(  
    s_id  
    g_value  
    S_name  
)  
=> g_value  
  
    s_id.S_name = g_value  
=> g_value
```

Description

Adds properties to symbols. Identical to `putprop` except that *sl_id* and *S_name* are not evaluated. If the property already exists, the old value is replaced with a new one.

`putpropqq` corresponds to `. =` as an assignment operator. So, `obj.prop = value` is equivalent to `putpropqq(obj value prop)`.

Arguments

| | |
|----------------|------------------------------|
| <i>s_id</i> | Can only be a symbol. |
| <i>g_value</i> | Value of the named property. |
| <i>S_name</i> | Name of the property. |

Value Returned

| | |
|----------------|------------------------------|
| <i>g_value</i> | Value of the named property. |
|----------------|------------------------------|

Examples

Both examples are equivalent expressions that set the property `x` on symbol `s` to 3.

```
putpropqq(s 1+2 x)  
=> 3  
  
s.x = 1+2  
=> 3
```

Related Topics

[get](#)

[putpropq](#)

[putpropq](#)

[Mapping Symbols to Values](#)

quote

```
quote(  
    g_expr  
)  
=> g_result
```

Description

Returns the name of the variable or the expression. This function is a prefix form of the ' operator. Quoting is used to prevent expressions from being evaluated.

Arguments

| | |
|---------------|-------------------------|
| <i>g_expr</i> | Variable or expression. |
|---------------|-------------------------|

Value Returned

| | |
|-----------------|-------------------------------------|
| <i>g_result</i> | Name of the variable or expression. |
|-----------------|-------------------------------------|

Examples

```
(quote a)  
=> a  
(quote (f a b))  
=> (f a b)
```

Related Topics

[get](#)

remprop

```
remprop(  
    sl_id  
    S_name  
)  
=> l_result / nil
```

Description

Removes a property from a property list and returns the property's former value.

Arguments

| | |
|---------------|--------------------------------------|
| <i>sl_id</i> | Symbol or disembodied property list. |
| <i>S_name</i> | Property name. |

Value Returned

| | |
|-----------------|--|
| <i>l_result</i> | Former value of the property as a single element list. |
| nil | The property does not exist. |

Examples

Assigns the property pins to chip.

```
putprop( 'chip 8 'pins )  
=> 8
```

Removes the property pins from chip.

```
get( 'chip 'pins )  
=> 8  
remprop( 'chip 'pins )  
=> (8)  
get( 'chip 'pins )  
=> nil
```

Related Topics

[get](#)

[putprop](#)

rotatef

```
rotatef(  
    [ gplace1 ]  
    [ gplace2 ]  
    .....  
    [ gplacen ]  
)  
=> g_newPlaceValues
```

Description

Modifies the value of each place by rotating the values from one place to another in a cyclic order.

Arguments

gplace1...gplacen

Values to be rotated.

Value Returned

g_newPlaceValues New values.

Examples

```
a=1 b=2 c=3  
rotatef(a b c)  
=> a=b b=c c=a,
```

Now,

```
a=2 b=3 c=1
```

Related Topics

[get](#)

set

```
set (
    s_variableName
    g_newValue
    [ e_environment ]
)
=> g_result
```

Description

Sets a variable to a new value. Similar to `setq` but the first argument for `set` is evaluated.

The `set` function is similar to the `setq` function, but unlike `setq`, the first argument for `set` is evaluated. This argument must evaluate to a symbol, whose value is then set to `g_newValue`.

Arguments

| | |
|-----------------------|--|
| <i>s_variableName</i> | Symbol that is evaluated. |
| <i>g_newValue</i> | Value to set symbol to. |
| <i>e_environment</i> | If this argument is given, SKILL++ semantics is assumed. The forms entered will be evaluated within the given (lexical) environment. |

Value Returned

| | |
|-----------------|-----------------------------|
| <i>g_result</i> | Returns <i>g_newValue</i> . |
|-----------------|-----------------------------|

Examples

```
y = 'a
=> a      ; Sets y to the constant a.
```

```
set (y 5)
=> 5      ; Sets the value of y to 5.
```

```
y
=> a
```

```
a
=> 5
```

Related Topics

[setq](#)

setf

```
setf(  
    g_place  
    g_value  
)  
=> g_result  
  
setf(  
    g_place := g_value  
=> g_result
```

Description

Assigns a new value to an existing storage location, destroying the value that was previously in that location. `setf` is the same as the assignment (`:=`) operator. This is a syntax form.

The `setf` function uses special expander functions, defined as `setf_<helper>`.

Arguments

| | |
|----------------|--------------------------------|
| <i>g_place</i> | Specifies the storage location |
| <i>g_value</i> | Specifies the new value |

Value Returned

| | |
|-----------------|----------------------------|
| <i>g_result</i> | Returns the updated result |
|-----------------|----------------------------|

Examples

```
x = '(a b c d e)  
setf( (car x) 42);; here x changes to (42 b c d e)  
=> (42 b c d e)  
  
x = '(a b c d e)  
(car x) := 42  
x  
=> (42 b c d e)
```

Related Topics

[pushf](#)

[popf](#)

Cadence SKILL Language Reference

Data Operator Functions

setf Helper Functions

setf_<helper>

```
setf_<helper>(
    g_new
    [ g_cell ]
)
=> g_result
```

Description

An expander function for `setf`, which returns the result of the corresponding `setf` operation. In the function, replace *helper* with the expander name.

Arguments

| | |
|---------------|---|
| <i>g_new</i> | New value to be set for <i>g_cell</i> . |
| <i>g_cell</i> | Cell to be modified. |

Value Returned

| | |
|-----------------|--|
| <i>g_result</i> | Result of the corresponding <code>setf</code> operation. |
|-----------------|--|

Examples

The following is an example of the helper function for `getSkillPath`:

```
defun(setf_getSkillPath (new)
    if(listp(new)
        setSkillPath(new)
        setSkillPath(list(new))) ; alters the skill path with setf
setf(getSkillPath() "/home/user/temp") ; now skill path changed to "/home/user/
temp"
```

Related Topics

[setf](#)

[setf Helper Functions](#)

setguard

```
setguard(  
    s_symbol  
    g_guard  
)  
=> u_guard
```

Description

Mainly enforces disciplined use of a symbol as a global variable by associating it with a guarding function that is either a symbol that identifies the name of the guarding function or a lambda form (just like the first argument to the `apply` function). If the guarding function is `nil`, the symbol is unguarded. The guarding function is called with two arguments whenever a new value is assigned to the symbol: the symbol and the value to be assigned to it. The result of the guarding function determines the `setguard` return value that gets assigned to the symbol.

The guarding function associated with a guarded symbol is triggered whenever a new value is assigned to that symbol by way of the `setq` (or `set`) function. Neither a lambda binding nor a `let` binding will cause the guarding function to be called (see examples below).

Arguments

| | |
|-----------------|---|
| <i>s_symbol</i> | Symbol to be associated with the guarding function. |
| <i>g_guard</i> | Guarding function to be associated with the symbol. |

Value Returned

| | |
|----------------|---|
| <i>u_guard</i> | Either a symbol that identifies the name of the guarding function or a function object. |
|----------------|---|

Examples

```
> procedure( myPortGuard(varName newValue)  
    if( portp(newValue)  
    then  
        newValue  
    else  
        printf("Only port values can be assigned to `%s'\n" varName)  
        symeval(varName)  
    )  
)  
myPortGuard
```

Cadence SKILL Language Reference

Data Operator Functions

```
> setguard('poport 'myPortGuard)
myPortGuard
> poport = nil
Only port values can be assigned to `poport'
port:"*stdout*"
> poport = 123
Only port values can be assigned to `poport'
port:"*stdout*"
> setguard( 'myStringVar
    lambda((varName newValue)
        if(stringp(newValue)
            then
                newValue
            else
                printf("Only strings can be assigned to `%s'\n" varName)
                symeval(varName)
        )
    ) ; lambda
) ; setguard
> myStringVar = "default"
"default"
> myStringVar = 123
Only strings can be assigned to `myStringVar'
"default"
> myStringVar = nil
Only strings can be assigned to `myStringVar'
"default"

;; A lambda binding will not trigger the guard
> ((lambda (myStringVar) (println 'hello)) nil)
hello
nil

;; A let binding will also not trigger the guard
> let( ((myStringVar 123))
    println(myStringVar)
)
123
nil

;; This is the symbol `myStringVar' unguarded
> setguard('myStringVar nil)
nil
> myStringVar = 123
123
```

Related Topics

[apply](#)

[lambda](#)

[let](#)

[set](#)

Cadence SKILL Language Reference

Data Operator Functions

setq

setplist

```
setplist(  
    s_atom  
    l_plist  
)  
=> l_plist
```

Description

Sets the property list of an object to a new property list; the old property list attached to the object is lost.



Users are strongly discouraged from using setplist because it might remove vital properties being used by the system or other applications.

Arguments

| | |
|----------------------|--|
| <code>s_atom</code> | A symbol. |
| <code>l_plist</code> | New property list to attach to <code>s_atom</code> . |

Value Returned

| | |
|----------------------|--|
| <code>l_plist</code> | New property list for <code>s_atom</code> ; the old property list is lost. |
|----------------------|--|

Examples

```
setplist( 'chip ' (pins 8 power 5) )  
=> (pins 8 power 5)  
plist( 'chip ' )  
=> (pins 8 power 5)  
chip.power  
=> 5
```

Related Topics

[getq](#)

[getqq](#)

Cadence SKILL Language Reference

Data Operator Functions

plist

putpropq

putpropqq

remprop

setq

```
setq(  
    s_variableName  
    g_newValueExp  
)  
=> g_result  
  
setq(  
    s_variableName = g_newValue  
)  
=> g_result
```

Description

Sets a variable to a new value. `setq` is the same as the assignment (`=`) operator. This is a syntax form.

The symbol *s_variableName* is bound to the value of *g_newValueExp*. The first argument to `setq` is not evaluated but the second one is.

Arguments

| | |
|-----------------------|---|
| <i>s_variableName</i> | Variable to be bound. |
| <i>g_newValueExp</i> | Expression to be evaluated and bound to <i>s_variableName</i> . |

Value Returned

| | |
|-----------------|---|
| <i>g_result</i> | Evaluated result of <i>g_newValueExp</i> is returned. |
|-----------------|---|

Examples

Assigns the value 5 to the variable `x`.

```
x = 5  
=> 5
```

Assigns the value 5 to the variable `x`.

```
setq( x 5 )  
=> 5
```

Assigns the symbol `a` to the variable `y`.

Cadence SKILL Language Reference

Data Operator Functions

y = 'a
=> a

Related Topics

set

setSG

```
setSG(  
    g_obj  
    g_value  
    S_prop  
)  
=>g_propValue
```

Description

Evaluates and then sets the value for the specified attribute or property. It is a lambda implementation of `setSGq()`.

Arguments

| | |
|----------------|---|
| <i>g_obj</i> | Specifies the name of an object |
| <i>g_value</i> | Specifies the value you want to set |
| <i>S_prop</i> | Specifies the name of the attribute or property for which you want to set the value |

Value Returned

| | |
|--------------------|-------------------------------|
| <i>g_propValue</i> | The set value of the property |
|--------------------|-------------------------------|

Examples

In the following example, `setSG()` evaluates the `tbl_list` argument and then sets its value.

```
tbl_list = list( (Table 'a nil)  
                Table( 'b nil)  
                Table( 'c nil))  
setSG( tbl_list 41 'x)  
=> '(41 41 41)
```

Related Topics

[set](#)

[setq](#)

symbolp

```
symbolp(  
    g_value  
)  
=> t / nil
```

Description

Checks if an object is a symbol.

The suffix `p` is usually added to the name of a function to indicate that it is a predicate function.

Arguments

| | |
|----------------|----------------|
| <i>g_value</i> | A data object. |
|----------------|----------------|

Value Returned

| | |
|------------------|------------------------------------|
| <code>t</code> | If <i>g_value</i> is a symbol. |
| <code>nil</code> | If <i>g_value</i> is not a symbol. |

Examples

```
symbolp( 'foo)  
=> t  
  
symbolp( "foo")  
=> nil  
  
symbolp( concat("foo"))  
=> t
```

Related Topics

[concat](#)

[stringp](#)

symeval

```
symeval(  
    s_symbol  
    [ e_environment ]  
)  
=> g_result
```

Description

Returns the value of the named variable.

`symeval` is slightly more efficient than `eval` and can be used in place of `eval` when you are sure that the argument being evaluated is indeed a variable name.

Arguments

| | |
|----------------------|--|
| <i>s_symbol</i> | Name of the variable. |
| <i>e_environment</i> | If this argument is given, SKILL++ semantics is assumed. The variable name will be looked up within the given (lexical) environment. |

Value Returned

| | |
|-----------------|------------------------------|
| <i>g_result</i> | Value of the named variable. |
|-----------------|------------------------------|

Examples

```
x = 5  
symeval( 'x )  
=> 5  
symeval( 'y )  
=> unbound ;Assumes y is unbound.
```

Related Topics

[eval](#)

symstrp

```
symstrp(  
    g_value  
)  
=> t / nil
```

Description

Checks if an object is either a symbol or a string.

The suffix *p* is usually added to the name of a function to indicate that it is a predicate function.

Arguments

| | |
|----------------|----------------|
| <i>g_value</i> | A data object. |
|----------------|----------------|

Value Returned

| | |
|------------|---|
| <i>t</i> | If <i>g_value</i> is either a symbol or a string. |
| <i>nil</i> | If <i>g_value</i> is neither a symbol nor a string. |

Examples

```
symstrp( "foo" )  
=> t  
symstrp( 'foo )  
=> t  
symstrp( 3 )  
=> nil
```

Related Topics

[stringp](#)

[symbolp](#)

Cadence SKILL Language Reference

Data Operator Functions

Type Conversion Functions

Before you can compare an integer to a floating-point number, you must convert both numbers to the same type. The type conversion functions helps in converting both numbers to the same type (that is, `integer` or `float`).

Any two numbers can only be equal if they are of the same type (either `integer` or `float`) and have identical values. Two floating-point numbers can appear the same when printed while differing internally in their least significant bits.

The following is a list of type conversion functions.

[charToInt](#)

[intToChar](#)

[listToVector](#)

[stringToFunction](#)

[stringToSymbol](#)

[stringToTime](#)

[symbolToString](#)

[tableToList](#)

[timeToString](#)

[timeToTm](#)

[tmToTime](#)

[vectorToList](#)

charToInt

```
charToInt (  
    s_char  
)  
=> x_ascii
```

Description

Returns the ASCII code of the first character of the given symbol. In SKILL, a single character symbol can be used as a *character* value.

Arguments

| | |
|---------------|-----------|
| <i>s_char</i> | A symbol. |
|---------------|-----------|

Value Returned

| | |
|----------------|--|
| <i>x_ascii</i> | The ASCII code of the (first) character of the given symbol. |
|----------------|--|

Examples

```
charToInt('B)  
=> 66  
  
charToInt('Before)  
=> 66
```

Related Topics

Type Conversion Functions

intToChar

intToChar

```
intToChar(  
    x_ascii  
)  
=> s_char
```

Description

Returns the single-character symbol whose ASCII code is the given integer value.

Arguments

| | |
|----------------|-------------|
| <i>x_ascii</i> | ASCII code. |
|----------------|-------------|

Value Returned

| | |
|---------------|---|
| <i>s_char</i> | Symbol of single-character whose ASCII code is <i>x_ascii</i> . |
|---------------|---|

Examples

```
intToChar( 66)  
=> B
```

Related Topics

[Type Conversion Functions](#)

[charToInt](#)

listToVector

```
listToVector(  
    l_list  
)  
=> a_vectorArray
```

Description

Returns a vector (array) filled with the elements from the given list. A vector is represented by an array.

Arguments

| | |
|---------------|--|
| <i>l_list</i> | A list whose elements will be stored in consecutive entries in the vector. |
|---------------|--|

Value Returned

| | |
|----------------------|--|
| <i>a_vectorArray</i> | Vector filled with the elements from the given list. |
|----------------------|--|

Examples

```
V = listToVector( '( 1 2 3 ) )  
=> array[3]:1954920  
V[0]  
=> 1  
V[1]  
=> 2  
V[2]  
=> 3  
V[3]  
*Error* arrayref: array index out of bounds - V[3]
```

Related Topics

Type Conversion Functions

vectorToList

stringToFunction

```
stringToFunction(  
    t_string  
    [ s_langMode ]  
)  
=> u_function
```

Description

Wraps and converts a string of SKILL code into a parameterless SKILL function.

Parses the given string argument and wraps the result with a parameterless `lambda`, then compiles the entire form into a function object. The returned function can later be *applied* with better performance than direct evaluation using `evalstring`.

Arguments

| | |
|-------------------------|---|
| <code>t_string</code> | String representing some SKILL code. |
| <code>s_langMode</code> | Must be a symbol. |
| Valid values | 'ils: Treats the string as SKILL++ code. 'il: Treats the string as SKILL code. |

Value Returned

| | |
|-------------------------|--|
| <code>u_function</code> | Parameterless function equivalent to evaluating the string (<code>lambda() t_string</code>). |
|-------------------------|--|

Examples

```
f = stringToFunction("1+2")  
=> funobj:0x220038  
apply(f nil)  
=> 3
```

Related Topics

Type Conversion Functions

stringToSymbol

Cadence SKILL Language Reference

Type Conversion Functions

stringToTime

stringToSymbol

```
stringToSymbol(  
    t_string  
)  
=> s_symbolName
```

Description

Converts a string to a symbol of the same name.

Arguments

| | |
|-----------------|--------------------------------|
| <i>t_string</i> | String to convert to a symbol. |
|-----------------|--------------------------------|

Value Returned

| | |
|---------------------|------------------------------|
| <i>s_symbolName</i> | Symbol for the given string. |
|---------------------|------------------------------|

Examples

```
y = stringToSymbol( "test")  
=> test  
sprintf(nil "%L" y)  
=> "test"
```

Related Topics

Type Conversion Functions

stringToFunction

stringToTime

symbolToString

stringToTime

```
stringToTime(  
    t_time  
)  
=> x_time
```

Description

Given a date and time string, returns an integer time value representation. The time argument must be in the format as returned by the `timeToString` function, such as: June 28 16:57:06 2022.

All time conversion functions assume local time, not GMT time.

Arguments

| | |
|---------------|--|
| <i>t_time</i> | String indicating a time and date in this format: "June 28 16:57:06 2022". This is the same format as returned by <code>timeToString</code> or <code>getCurrentTime</code> . |
|---------------|--|

Value Returned

| | |
|---------------|---------------------|
| <i>x_time</i> | Integer time value. |
|---------------|---------------------|

Examples

```
fileTimeModified( "~/cshrc" )  
=> 793561559  
timeToString(793561559)  
=> "June 23 09:45:59 2022"  
stringToTime("June 23 09:45:59 2022")  
=> 793561559
```

Related Topics

[Type Conversion Functions](#)

[timeToString](#)

symbolToString

```
symbolToString(  
    s_symbolName  
)  
=> t_string
```

Description

Converts a symbol to a string of the same name. This function is the same as `get_pname`.

Arguments

| | |
|---------------------|--------------------|
| <i>s_symbolName</i> | Symbol to convert. |
|---------------------|--------------------|

Value Returned

| | |
|-----------------|--|
| <i>t_string</i> | String with the same name as the input symbol. |
|-----------------|--|

Examples

```
y = symbolToString( 'test2')  
=> "test2"  
  
sprintf(nil "%L" y)  
=> "\"test2\""
```

Related Topics

Type Conversion Functions

stringToSymbol

tableToList

```
tableToList(  
    o_table  
)  
=> l_assoc_list
```

Description

Converts the contents of an association table to an association list. Use this function interactively to look at the contents of a table.

This function eliminates the efficiency that you gain from referencing data in an association table. Do not use this function for processing data in an association table. Instead, use this function interactively to look at the contents of a table.

Arguments

| | |
|----------------|------------------------------------|
| <i>o_table</i> | Association table to be converted. |
|----------------|------------------------------------|

Value Returned

| | |
|---------------------|---|
| <i>l_assoc_list</i> | Association list containing key/value pairs from the association table. |
|---------------------|---|

Examples

```
myTable = makeTable( "table" 0)  
=> table:table  
myTable[ "first"] = 1  
=> 1  
myTable[ 'two] = 2  
=> 2  
tableToList(myTable)  
=> ((two 2) ("first" 1))
```

Related Topics

Type Conversion Functions

vectorToList

timeToString

```
timeToString(  
    x_time  
)  
=> t_time / nil
```

Description

Takes an integer UNIX time value, returns a formatted string that the value denotes. The string is always in a form like: Dec 28 16:57:06 2021.

Arguments

| | |
|---------------|---------------------|
| <i>x_time</i> | Integer time value. |
|---------------|---------------------|

Value Returned

| | |
|---------------|-------------------------------------|
| <i>t_time</i> | Formatted string the value denotes. |
| <i>nil</i> | If a negative argument is passed. |

Examples

```
valTime=fileTimeModified( "~/ .cshrc" )  
timeToString(valTime)  
=> "Feb 23 09:45:59 2022"  
timeToString(-valTime)  
=> nil
```

Related Topics

Type Conversion Functions

timeToTm

stringToTime

timeToTm

```
timeToTm(  
    x_time  
)  
=> r_tm
```

Description

Given an integer time value, returns a `tm` structure.

`r_tm` is a defstruct similar to POSIX's `tm` struct:

```
struct tm {  
int      tm_sec;      /* seconds after the minute: [0, 61] */  
int      tm_min;      /* minutes after the hour: [0, 59] */  
int      tm_hour;     /* hours after midnight: [0, 23] */  
int      tm_mday;     /* day of the month: [1, 31] */  
int      tm_mon;      /* month of the year: [0, 11] */  
int      tm_year;     /* year since 1900 */  
int      tm_wday;     /* days since Sunday: [0, 6] */  
int      tm_yday;     /* days since January: [0, 365] */  
int      tm_isdst;    /* daylight saving time flag: <0,0,>0*/  
};
```

- Use `x->??` to get all its fields.
- Use `x->tm_sec` and so forth to access individual fields.

All time conversion functions assume local time, not GMT time.

Arguments

| | |
|---------------------|---------------------|
| <code>x_time</code> | Integer time value. |
|---------------------|---------------------|

Value Returned

| | |
|-------------------|--|
| <code>r_tm</code> | A defstruct similar to POSIX's <code>tm</code> struct. |
|-------------------|--|

Examples

```
fileTimeModified( "~/cshrc" )  
=> 793561559  
  
timeToString(793561559)  
=> "Feb 23 09:45:59 2022"  
  
x = timeToTm(793561559)  
=>array[11]:1702872
```

Cadence SKILL Language Reference

Type Conversion Functions

```
x->??  
(tm_sec 59 tm_min 45 tm_hour  
 9 tm_mday 23 tm_mon 1  
  tm_year 22 tm_wday 4 tm_yday  
 53 tm_isdst 0  
)  
x->tm_mon  
=>1
```

Related Topics

Type Conversion Functions

tmToTime

tmToTime

```
tmToTime (
    r_tm
)
=> x_time
```

Description

Given a `tm` structure, returns the integer value of the time it represents.

`r_tm` is a defstruct similar to POSIX's `tm` struct:

```
struct tm {
int      tm_sec;          /* seconds after the minute: [0, 61] */
int      tm_min;          /* minutes after the hour: [0, 59] */
int      tm_hour;         /* hours after midnight: [0, 23] */
int      tm_mday;         /* day of the month: [1, 31] */
int      tm_mon;          /* month of the year: [0, 11] */
int      tm_year;         /* year since 1900 */
int      tm_wday;         /* days since Sunday: [0, 6] */
int      tm_yday;         /* days since January: [0, 365] */
int      tm_isdst;        /* daylight saving time flag: <0,0,>0 */
};
```

- Use `x->??` to get all its fields.
- Use `x->tm_sec` and so forth to access individual fields.

All time conversion functions assume local time, not GMT time.

Arguments

| | |
|-------------------|--|
| <code>r_tm</code> | A defstruct similar to POSIX's <code>tm</code> struct. |
|-------------------|--|

Value Returned

| | |
|---------------------|---------------------|
| <code>x_time</code> | Integer time value. |
|---------------------|---------------------|

Examples

```
fileTimeModified( "~/cshrc" )
=> 793561559

timeToString(793561559)
=> "Feb 23 09:45:59 2022"

x = timeToTm(793561559)
=>array[11]:1702872
```


Cadence SKILL Language Reference

Type Conversion Functions

```
x->??  
(tm_sec 59 tm_min 45 tm_hour  
 9 tm_mday 23 tm_mon 1  
  tm_year 22 tm_wday 4 tm_yday  
 53 tm_isdst 0  
)  
tmToTime(x)  
=> 793561559
```

Related Topics

Type Conversion Functions

timeToTm

vectorToList

```
vectorToList(  
    a_vectorArray  
)  
=> l_list
```

Description

Returns a list containing the elements of an array.

Arguments

a_vectorArray Vector to be converted.

Value Returned

l_list List constructed from the given vector.

Examples

```
vectorToList( vector( 1 2 3 ) )  
=> ( 1 2 3 )  
vectorToList( Vector( 3 "Hi" ) )  
=> (3 "Hi")
```

Related Topics

Type Conversion Functions

listToVector

String Functions

A *string* is a specialized one-dimensional array whose elements are characters.

The string functions listed in this topic are patterned after functions of the same name in the C run-time library. Strings can be compared, taken apart, or concatenated.

| | | |
|----------------------------|------------------------------|-------------------------------|
| <u>blankstrp</u> | <u>buildString</u> | <u>getchar</u> |
| <u>index</u> | <u>lowerCase</u> | <u>lsprintf</u> |
| <u>nindex</u> | <u>outstringp</u> | <u>parseString</u> |
| <u>pcreCompile</u> | <u>pcreExecute</u> | <u>pcreGenCompileOptBits</u> |
| <u>pcreGenExecOptBits</u> | <u>pcreGetRecursionLimit</u> | <u>pcreListCompileOptBits</u> |
| <u>pcreListExecOptBits</u> | <u>pcreMatchAssocList</u> | <u>pcreMatchList</u> |
| <u>pcreMatchp</u> | <u>pcreObjectp</u> | <u>pcrePrintLastMatchErr</u> |
| <u>pcreReplace</u> | <u>pcreSetRecursionLimit</u> | <u>pcreSubpatCount</u> |
| <u>pcreSubstitute</u> | <u>readstring</u> | <u>rexCompile</u> |
| <u>rexExecute</u> | <u>rexMagic</u> | <u>rexMatchAssocList</u> |
| <u>rexMatchList</u> | <u>rexMatchp</u> | <u>rexReplace</u> |
| <u>rexSubstitute</u> | <u>rindex</u> | <u>sprintf</u> |
| <u>strcat</u> | <u>strcmp</u> | <u>stringp</u> |
| <u>strlen</u> | <u>strncat</u> | <u>strncmp</u> |
| <u>strpbrk</u> | <u>substring</u> | <u>upperCase</u> |

blankstrp

```
blankstrp(  
    t_string  
)  
=> t / nil
```

Description

Checks if the given string is empty or has blank space characters only and returns `true`. If there are non-space characters `blankstrp` returns `nil`.

Arguments

| | |
|-----------------|-----------|
| <i>t_string</i> | A string. |
|-----------------|-----------|

Value Returned

| | |
|------------------|--|
| <code>t</code> | If <i>t_string</i> is blank or is an empty string. |
| <code>nil</code> | If there are non-space characters. |

Examples

```
blankstrp( "")  
=> t  
  
blankstrp( " ")  
=> t  
  
blankstrp( "a string")  
=> nil
```

Related Topics

[String Functions](#)

buildString

```
buildString(  
    l_strings  
    [ S_glueCharacters ]  
)  
=> t_string
```

Description

Concatenates a list of strings with specified separation characters.

Arguments

| | |
|-------------------------|--|
| <i>l_strings</i> | List of strings. A null string is permitted. |
| <i>S_glueCharacters</i> | Separation characters you use within the strings. A null string is permitted. If this argument is omitted, the default single space is used. |

Value Returned

| | |
|-----------------|--|
| <i>t_string</i> | Strings concatenated with <i>t_glueCharacters</i> . Signals an error if <i>l_strings</i> is not a list of strings. |
|-----------------|--|

Examples

```
buildString( '("test" "il") ".")  
=> "test.il"  
buildString( '("usr" "mnt") "/" )  
=> "usr/mnt"  
buildString( '("a" "b" "c") )  
=> "a b c"  
buildString( '("a" "b" "c") "" )  
=> "abc"  
buildString( '("A" "B") "and" )  
=> "AandB"
```

Related Topics

String Functions

Cadence SKILL Language Reference

String Functions

parseString

getchar

```
getchar(  
    S_arg  
    x_index  
)  
=> s_char / nil
```

Description

Returns an indexed character of a string or the print name if the string is a symbol. Unlike the C library, the `getc` and `getchar` SKILL functions are totally unrelated.

Arguments

| | |
|----------------|--|
| <i>S_arg</i> | Character string or symbol. |
| <i>x_index</i> | Number corresponding to an indexed point in <i>S_arg</i> . |

Value Returned

| | |
|---------------|--|
| <i>s_char</i> | Single character symbol corresponding to the character in <i>S_arg</i> indexed by <i>x_index</i> . |
| nil | If <i>x_index</i> is less than 1 or greater than the length of the string. |

Examples

```
getchar("abc" 2)  
=> b  
getchar("abc" 4)  
=> nil
```

Related Topics

[String Functions](#)

[nindex](#)

[parseString](#)

[strlen](#)

Cadence SKILL Language Reference

String Functions

substring

index

```
index(  
    t_string1  
    S_string2  
)  
=> t_result / nil
```

Description

Returns a string consisting of the remainder of *string1* beginning with the first occurrence of *string2*.

Arguments

| | |
|------------------|---|
| <i>t_string1</i> | String to search for the first occurrence of <i>S_string2</i> . |
| <i>S_string2</i> | String to search for in <i>t_string1</i> . |

Value Returned

| | |
|-----------------|---|
| <i>t_result</i> | If <i>S_string2</i> is found in <i>t_string1</i> , returns a string equal to the remainder of <i>t_string1</i> that begins with the first character of <i>S_string2</i> . |
| nil | If <i>S_string2</i> is not found. |

Examples

```
index( "abc" 'b )  
=> "bc"  
index( "abcdabce" "dab" )  
=> "dabce"  
index( "abc" "cba" )  
=> nil  
index( "dandelion" "d")  
=> "dandelion"
```

Related Topics

[String Functions](#)

Cadence SKILL Language Reference

String Functions

getchar

lowerCase

```
lowerCase(  
    S_string  
)  
=> t_result
```

Description

Returns a string that is a copy of the given argument with uppercase alphabetic characters replaced by their lowercase equivalents.

If the parameter is a symbol, the name of the symbol is used.

Arguments

| | |
|-----------------|-------------------------|
| <i>S_string</i> | Input string or symbol. |
|-----------------|-------------------------|

Value Returned

| | |
|-----------------|---|
| <i>t_result</i> | Copy of <i>S_string</i> in lowercase letters. |
|-----------------|---|

Examples

```
lowerCase("Hello World!")  
=> "hello world!"
```

Related Topics

[String Functions](#)

[upperCase](#)

lsprintf

```
lsprintf(  
    t_formatString  
    [ g_arg1 ... ]  
)  
=> t_string
```

Description

Returns a string according to the provided format. `lsprintf` is a lambda version of the `sprintf` function that can be used as an argument with `apply` or `funcall`.

Refer to the Common Output Format Specifications table of the `fprintf` function. If `nil` is specified as the first argument, no assignment is made, but the formatted string is returned.

Arguments

| | |
|-----------------------|--|
| <i>t_formatString</i> | Specifies the format string |
| <i>g_arg1</i> | Specifies the arguments following the format string that are printed corresponding to their format specifications. |

Value Returned

| | |
|-----------------|------------------------------|
| <i>t_string</i> | Returns the formatted string |
|-----------------|------------------------------|

Examples

```
let( (format( "%d %d %s %L\n")  
      printf_style_args( (list 42 41 "hello" (list "world"))))  
      apply('lsprintf format printf_style_args))  
=>"42 41 hello (\nworld\n)\n"
```

Related Topics

[String Functions](#)

[sprintf](#)

nindex

```
nindex(  
    t_string1  
    S_string2 )  
=> x_result / nil
```

Description

Finds the symbol or string, *S_string2*, in *t_string1* and returns the character index, starting from one, of the first point at which the *S_string2* matches part of *t_string1*.

Arguments

| | |
|------------------|--|
| <i>t_string1</i> | String you want to search for <i>S_string2</i> . |
| <i>S_string2</i> | String you want to find occurrences of in <i>t_string1</i> . |

Value Returned

| | |
|-----------------|--|
| <i>x_result</i> | Index corresponding to the point at which <i>S_string2</i> matches part of <i>t_string1</i> . The index starts from one. |
| nil | No character match. |

Examples

```
nindex( "abc" 'b )  
=> 2  
nindex( "abcdabce" "dab" )  
=> 4  
nindex( "abc" "cba" )  
=> nil
```

Related Topics

[String Functions](#)

[getchar](#)

[substring](#)

outstringp

```
outstringp(  
    g_port  
)  
=> t / nil
```

Description

Checks whether the specified value is an outstring port.

Arguments

| | |
|---------------|--------------------------|
| <i>g_port</i> | The value to be checked. |
|---------------|--------------------------|

Value Returned

| | |
|-----|--|
| t | If the given value is an outstring port. |
| nil | If the given value is not an outstring port. |

Examples

```
p = outstring()  
outstringp(p)  
=> t
```

Related Topics

[String Functions](#)

[parseString](#)

parseString

```
parseString(  
    S_string  
    [ S_breakCharacters ]  
    [ g_insertEmptyString ]  
)  
=> l_strings
```

Description

Breaks a string into a list of substrings with break characters.

Returns the contents of *S_string* broken up into a list of words. If the optional second argument, *S_breakCharacters*, is not specified, the white space characters, `\t\r\n\v`, are used as the default. If the third optional argument *g_insertEmptyString* is provided, an empty string is inserted under the following three conditions:

- when *S_breakCharacters* is the first letter in the string.
- when *S_breakCharacters* is the last letter in the string.
- when *S_breakCharacters* is after another *S_breakCharacters*.

A sequence of break characters in *S_string* is treated as a single break character. By this rule, two spaces or even a tab followed by a space is the same as a single space. If this rule were not imposed, successive break characters would cause null strings to be inserted into the output list.

If *S_breakCharacters* is a null string, *S_string* is broken up into characters. You can think of this as inserting a null break character after each character in *S_string*.

No special significance is given to punctuation characters, so the “words” returned by `parseString` might not be grammatically correct.

Arguments

| | |
|---------------------------------------|--|
| <i>S_string</i> | String to be parsed. |
| <i>S_breakCharacter</i> <i>s</i> | List of individual break characters. |
| <i>g_insertEmptyStr</i> <i>ing</i> | Generates the list of strings to include empty string when set to <code>t</code> . The default value is <code>nil</code> . |

Cadence SKILL Language Reference

String Functions

Value Returned

l_strings List of strings parsed from *S_string*.

Examples

Space is the default break character.

```
parseString( "Now is the time" )  
=> ("Now" "is" "the" "time")
```

e is the break character.

```
parseString( "prepend" "e" )  
=> ("pr" "p" "nd" )
```

A sequence of break characters in *S_string* is treated as a single break character.

```
parseString( "feed" "e")  
=> ("f" "d")
```

Both . and / are break characters.

```
parseString( "~/exp/test.il" ". /")  
=> ("~" "exp" "test" "il")
```

The single space between c and d contributes " " in the return result.

```
parseString( "abc de" "")  
=> ("a" "b" "c" " " "d" "e")
```

Splits the string at each occurrence of the delimiter character "-".

```
parseString( "-abc-def--ghi-" "-")  
=> ("abc" "def" "ghi")
```

Inserts an empty string at each occurrence of the delimiter character "-".

```
parseString( "-abc-def--ghi-" "- " t )  
=> (" " "abc" "def" " " "ghi" " ")
```

```
parseString "-abc"  
=> (" " "abc")
```

```
parseString "abc-"  
=> ("abc" " ")
```

```
parseString "abc--xyz"  
=> ("abc" " " "xyz")
```

The above result can be used with `buildString()` to reconstruct the original string or replacing the delimiter character.

```
buildString( parseString( string delimiter t) delimiter)
```


Cadence SKILL Language Reference

String Functions

Related Topics

[String Functions](#)

[buildString](#)

[linereadstring](#)

[strcat](#)

[strlen](#)

[stringp](#)

pcreCompile

```
pcreCompile(  
    t_pattern  
    [ x_options ]  
)  
=> o_comPatObj / nil
```

Description

Compiles a regular expression string pattern (*t_pattern*) into an internal representation that you can use in a pcreExecute function call. The compilation method is PCRE/Perl-compatible. You can use a second (optional) argument to specify independent option bits for controlling pattern compilation. You can set and unset the `PCRE_CASELESS`, `PCRE_MULTILINE`, `PCRE_DOTALL`, and `PCRE_EXTENDED` independent option bits from within the pattern. The content of the options argument specifies the initial setting at the start of compilation. You can set the `PCRE_ANCHORED` option at matching time and at compile time.

Note: PCRE stands for Perl Compatible Regular Expressions. The PCRE library contains functions that implement Perl-compatible regular expression pattern matching. You can visit <http://www.pcre.org> for more information.

Arguments

| | |
|------------------|--|
| <i>t_pattern</i> | String containing regular expression string to be compiled. |
| <i>x_options</i> | Optional) Independent option bits that affect the compilation. You can specify zero or more of these options symbolically using the <u>pcreGenCompileOptBits</u> SKILL function. |

Valid Values:

`PCRE_CASELESS / 0x00000001`

Equivalent to setting `?caseLess t` using the pcreGenCompileOptBits SKILL function.

`PCRE_MULTILINE / 0x00000002`

Equivalent to setting `?multiLine t` using the pcreGenCompileOptBits SKILL function.

`PCRE_DOTALL / 0x00000004`

Cadence SKILL Language Reference

String Functions

Equivalent to setting `?dotAll t` using the `pcreGenCompileOptBits` SKILL function.

PCRE_EXTENDED / 0x00000008

Equivalent to setting `?extended t` using the `pcreGenCompileOptBits` SKILL function.

PCRE_ANCHORED / 0x00000010

Equivalent to setting `?anchored t` using the `pcreGenCompileOptBits` SKILL function.

PCRE_DOLLAR_ENDONLY / 0x00000020

Equivalent to setting `?dollar_endonly t` using the `pcreGenCompileOptBits` SKILL function.

PCRE_UNGREEDY / 0x00000200

Equivalent to setting `?ungreedy t` using the `pcreGenCompileOptBits` SKILL function.

PCRE_NO_AUTO_CAPTURE / 0x00001000

Equivalent to setting `?no_auto_capture t` using the `pcreGenCompileOptBits` SKILL function.

PCRE_FIRSTLINE / 0x00040000

Equivalent to setting `?firstline t` using the `pcreGenCompileOptBits` SKILL function.

Cadence SKILL Language Reference

String Functions

Value Returned

| | |
|--------------------------|---|
| <code>o_comPatObj</code> | Data object containing the compiled pattern. |
| <code>nil</code> | Pattern compilation failed. An error message indicating the cause of the failure appears. |

Examples

```
comPat1 = pcreCompile( "\\Qabc\\$xyz\\E" )
=> pcreobj@0x27d0fc
pcreExecute( comPat1 "abc\\$xyz" )
=> t

comPat2 = pcreCompile( "sam|Bill|jack|alan|bob" )
=> pcreobj@0x27d108
pcreExecute( comPat2 "alan" )
=> t

comPat3 = pcreCompile( "z{1,5}" )
=> pcreobj@0x27d120
pcreExecute( comPat3 "zzzzz" )
=> t

comPat4 = pcreCompile( "/\\*..*?\\*/" )
=> pcreobj@0x27d12c
pcreExecute( comPat4 "/* first command */ not comment /* second comment */" )
=> t

comPat5 = pcreCompile( "[a-z][0-9a-z]*" pcreGenCompileOptBits(?caseLess t) )
=> pcreobj@0x27d138
pcreExecute( "AB12cd" )
=> t

comPat6 = pcreCompile( "[a-z" )
=> *Error* pcreCompile: compilation failed at offset 4: missing terminating ] for
character class
nil
```

Related Topics

String Functions

pcreExecute

pcreGenCompileOptBits

pcreExecute

```
pcreExecute(  
    o_comPatObj  
    S_subject  
    [ x_options ]  
)  
=> t / nil
```

Description

Matches the subject string or symbol (*S_subject*) against a previously compiled pattern set up by the last pcreCompile call (*o_comPatObj*). The matching algorithm is PCRE/Perl-compatible. You can use a third (optional) argument to specify independent option bits for controlling pattern matching. You can use this function in conjunction with pcreCompile to match several subject strings or symbols against a single pattern.

Arguments

| | |
|--------------------|---|
| <i>o_comPatObj</i> | Data object containing the compiled pattern returned from a previous <u>pcreCompile</u> call. |
| <i>S_subject</i> | Subject string or symbol to be matched. If it is a symbol, its print name is used. |
| <i>x_options</i> | (Optional) Independent option bits that affect pattern matching. You can specify zero or more of these options symbolically using the <u>pcreGenExecOptBits</u> SKILL function. |

Valid Values:

| | |
|---------------|--|
| PCRE_ANCHORED | Equivalent to setting <code>?anchored t</code> using the <u>pcreGenExecOptBits</u> SKILL function. |
| PCRE_NOTBOL | Equivalent to setting <code>?notbol t</code> using the <u>pcreGenExecOptBits</u> SKILL function. |
| PCRE_NOTEOL | Equivalent to setting <code>?noteol t</code> using the <u>pcreGenExecOptBits</u> SKILL function. |
| PCRE_NOTEMPTY | Equivalent to setting <code>?notempty t</code> using the <u>pcreGenExecOptBits</u> SKILL function. |
| PCRE_PARTIAL | Equivalent to setting <code>?partial t</code> using the <u>pcreGenExecOptBits</u> SKILL function. |

Cadence SKILL Language Reference

String Functions

Value Returned

| | |
|------------------|--|
| <code>t</code> | A match is found. |
| <code>nil</code> | No match. You can see the error message associated with this matching failure by calling <code>pcrPrintLastMatchErr</code> . |

Examples

```
comPat1 = pcreCompile( "[12[:^digit:]]" )
=> pcreobj@0x27d150
pcrExecute( comPat1 "abc" )
=> t

comPat2 = pcreCompile( "((?i)ab)c" )
=> pcreobj@0x27d15c
pcrExecute( comPat2 "aBc" )
=> t

comPat3 = pcreCompile( "\\d{3}" )
=> pcreobj@0x27d168
pcrExecute( comPat3 "789" )
=> t

comPat4 = pcreCompile( "(\\D+|<\\d+>)*[!?!]" )
=> pcreobj@0x27d174
pcrExecute( comPat4 "Hello World!" )
=> t

comPat5 = pcreCompile( "^\\d?\\d(jan|feb|mar|apr|may|jun)\\d\\d$/ " )
=> pcreobj@0x27d180
pcrExecute( comPat5 "25jun3" ) => nil
pcrExecute( comPat5 "25jun3" pcrGenExecOptBits(?anchored t) )
=> nil
pcrExecute( comPat5 "25jun3" pcrGenExecOptBits(?partial t) )
=> t
```

Related Topics

String Functions

[pcrCompile](#)

[pcrExecute](#)

[pcrGenExecOptBits](#)

pcreGenCompileOptBits

```
pcreGenCompileOptBits(  
    [ ?caseLess    g_setCaseLessp ]  
    [ ?multiLine   g_setMultiLinep ]  
    [ ?dotAll      g_setDotAllp ]  
    [ ?extended    g_setExtendedp ]  
    [ ?anchored    g_setAnchoredp ]  
    [ ?dollar_endonly g_setDollarEndonlyp ]  
    [ ?ungreedy    g_setUngreedy ]  
    [ ?no_auto_capture g_setNoAutoCapturep ]  
    [ ?firstline   g_setFirstlinep ]  
)  
=> x_resultOptBits
```

Description

Generates bitwise inclusive OR—`bor()`—of zero or more independent option bits that affect compilation so that you can specify them symbolically in the `pcreCompile` function. If you call `pcreGenCompileOptBits` with no arguments, the function returns a zero (options have their default settings).

Arguments

`?caseLess g_setCaseLessp`

When not `nil`, letters in the pattern match both upper and lower case letters. Setting this bit is equivalent to using Perl's `/i` option. You can change this setting within a pattern using `(?i)..`

`?multiLine g_setMultiLinep`

When not `nil`, each newline in the subject string defines a line of characters for which the start-of-line metacharacter (`^`) matches at the start of the line and the end-of-line metacharacter (`$`) matches at the end of the line.

By default, PCRE treats the subject string as a single line of characters, even if it contains newlines, such that the start-of-line metacharacter (`^`) matches only at the start of the string and the end-of-line metacharacter (`$`) matches only at the end of the string, or before a terminating newline (unless `PCRE_DOLLAR_ENDONLY` is set).

`?dotAll g_setDotAllp`

Cadence SKILL Language Reference

String Functions

When not `nil`, a dot metacharater in the pattern matches all characters, including newlines. Without it, newlines are excluded.

Setting this bit is equivalent to using Perl's `/s` option. You can change this setting within a pattern using `(?s)`. A negative class such as `[^a]` always matches a newline character, independent of whether this bit is set or not.

`?extended g_setExtendedp`

When not `nil`, PCRE ignores whitespace data characters in the pattern except when they are escaped or inside a character class.

Whitespace does not include the VT character (code 11).

PCRE also ignores characters between an unescaped `#` outside a character class and the next newline character, inclusive.

Setting this bit is equivalent to using Perl's `/x` option. You can change this setting within a pattern using `(?x)`.

You can use this setting to include comments (data characters only) inside complicated patterns.

You may not use whitespace characters in special character sequences in a pattern, such as `(?(` which introduces a conditional subpattern.

`?anchored g_setAnchoredp`

When not `nil`, PCRE constrains the match to the first matching point in the subject string. You can achieve this same effect using appropriate constructs in the pattern itself.

`?dollar_endonly g_setDollarEndonlyp`

When not `nil`, a dollar metacharacter in the pattern matches at the end of the subject string only. Without this option, a dollar metacharacter also matches immediately before the final character if it is a newline (but not before any other newlines). PCRE ignores this setting if you specify `PCRE_MULTILINE`.

`?ungreedy g_setUngreedy`

Cadence SKILL Language Reference

String Functions

When not `nil`, PCRE inverts the greed of quantifiers so that they are not greedy by default. You can force a quantifier to become greedy by putting `?` after it. You can change this setting within a pattern using `(?U)`.

`?no_auto_capture` *`g_setNoAutoCapturep`*

When not `nil`, If you set this bit, you are disabling the use of numbered capturing parentheses in a pattern. Any opening parenthesis that is not followed by `?` behaves as if it were followed by `?:` but you can still use named parentheses for capturing (and they acquire numbers in the usual way).

`?firstline` *`g_setFirstlinep`*

When not `nil`, PCRE requires an unanchored pattern to match before or at the first newline character in the subject string; the matched text may continue over the newline.

Value Returned

`x_resultOptBits` Bitwise inclusive OR—`bor()`—of zero or more independent option bits that affect pattern compilation.

Examples

```
comPat1 = pcreCompile( "^abc$"
pcreGenCompileOptBits(?dollar_endonly t ?multiline t) )
=> pcreobj@0x27d060
pcreExecute( comPat1 "abc\ndef" )
=> t

pcreMatchAssocList( "[a-z][0-9]*$"
'((abc "ascii") ("123" "number") ("yy\na123" "alphanum") (a12z "ana"))
pcreGenCompileOptBits(?multiline t) pcreGenExecOptBits( ?notbol t) )
=> (("yy\na123" "alphanum"))
```

Related Topics

String Functions

[pcreCompile](#)

[pcreExecute](#)

[pcreGenExecOptBits](#)

Cadence SKILL Language Reference

String Functions

pcrMatchAssocList

pcreGenExecOptBits

```
pcreGenExecOptBits(  
    [ ?anchored g_setAnchoredp ]  
    [ ?notbol   g_setNotbolp ]  
    [ ?noteol   g_setNoteolp ]  
    [ ?notempty g_setNotemptyp ]  
    [ ?partial  g_setPartialp ]  
)  
=> x_resultOptBits
```

Description

Generates bitwise inclusive OR—`bor()`—of zero or more independent option bits that affect pattern matching so that you can specify them symbolically in the `pcreExecute` function. If you call `pcreGenExecOptBits` with no arguments, the function returns a zero (options have their default settings).

Arguments

`?anchored g_setAnchoredp`

When not `nil`, PCRE constrains the match to the first matching point in the `pcreExecute` function.

If you compiled a pattern using the `PCRE_ANCHORED` option, or if the pattern was anchored by virtue of its contents, then it must also be anchored at matching time.

`?notbol g_setNotbolp`

When not `nil`, the first character of the subject string is not the beginning of a line such that the circumflex metacharacter `^` does not match before it. If you enable this option without setting the `PCRE_MULTILINE` option (at compile time), the circumflex metacharacter never results in a match.

This option affects the behavior of `^` only; it does not affect the behavior of `\A`.

`?noteol g_setNoteolp`

Cadence SKILL Language Reference

String Functions

When not `nil`, the end of the subject string is not the end of a line such that the dollar sign metacharacter `$` does not match it nor does it match a newline character immediately before it (except if you have set the `PCRE_MULTILINE` option). If you enable this option without setting the `PCRE_MULTILINE` option (at compile time), the dollar sign metacharacter never results in a match.

This option affects the behavior of `$` only; it does not affect the behavior of `\Z` or `\z`.

`?notempty g_setNotempty`

When not `nil`, an empty string is not a valid match. PCRE attempts to match any alternatives in the pattern. If all the alternatives match the empty string, the entire match fails. For example, if you do not set this option, when PCRE applies the following sequence to a string that does not begin with `a` or `b`, it matches the empty string at the start of the subject:

`a?b?`

If you set this option, an empty string is not a valid match; PCRE searches further into the string for occurrences of `a` or `b`.

`?partial g_setPartialp`

When not `nil`, the function returns `PCRE_ERROR_PARTIAL` instead of `PCRE_ERROR_NOMATCH` in the case of a partial match. A partial match occurs when PCRE encounters the end of a subject string before it can match the complete pattern. You may not use this option with all patterns. The following restrictions apply:

You may not specify quantified atom matches to search for repeated single characters or repeated single metasequences where the maximum quantity is greater than one. However, you may specify quantifiers with any values after parentheses. For example:

Use `(a){2,4}` instead of `a{2,4}`.

Use `(\d)+` instead of `\d+`.

Cadence SKILL Language Reference

String Functions

Value Returned

x_resultOptBits Bitwise inclusive OR— `bor()` —of zero or more independent option bits that affect pattern matching.

Examples

```
comPat = pcreCompile( "^\\d?\\d(jan | feb | mar | apr | may | jun)\\d\\d$/" )
=> pcreobj@0x27d0d8

pcreExecute( comPat "25jun3" pcreGenExecOptBits(?partial t) )
=> t

pcreMatchAssocList("^([a-z][0-9]*)$"
'((abc "ascii") ("123" "number") ("yy\\na123" "alphanum") (a12z "ana")))
pcreGenCompileOptBits(?multiLine t) pcreGenExecOptBits( ?notbol t) )
=> (("yy\\na123" "alphanum"))
```

Related Topics

String Functions

pcreCompile

pcreExecute

pcreGenCompileOptBits

pcreMatchAssocList

pcreGetRecursionLimit

```
pcreGetRecursionLimit()  
=> x_value
```

Description

Returns the PCRE maximum recursion depth (stack depth) that is set by the `pcreSetRecursionLimit()` function. The default value is 10000000.

Arguments

None

Value Returned

| | |
|----------------|--|
| <i>x_value</i> | Maximum recursion depth for the PCRE match algorithms. |
|----------------|--|

Examples

```
pcreGetRecursionLimit()  
=> 10000000
```

Related Topics

[String Functions](#)

[pcreSetRecursionLimit](#)

pcreListCompileOptBits

```
pcreListCompileOptBits()  
=> t
```

Description

Displays information about the options used with `pcreGenCompileOptBits`. See the description of `pcreGenCompileOptBits` for more information.

Arguments

None

Value Returned

| | |
|----------------|--|
| <code>t</code> | Information about the options used with <code>pcreGenCompileOptBits</code> . |
|----------------|--|

Related Topics

[String Functions](#)

[pcreGenCompileOptBits](#)

pcreListExecOptBits

```
pcreListExecOptBits()  
=> t
```

Description

Displays information about the options used with `pcreGenExecOptBits`.

Arguments

None

Value Returned

`t` Returns `t`.

Related Topics

[String Functions](#)

[pcreGenExecOptBits](#)

pcreMatchAssocList

```
pcreMatchAssocList(  
    g_pattern  
    l_subjects  
    [ x_compOptBits ]  
    [ x_execOptBits ]  
)  
=> l_results / nil / error message(s)
```

Description

Matches the keys of an association list of subjects (strings or symbols) against a regular expression pattern (*g_pattern*) and returns an association list of those elements that match. The keys are the first elements of each key/value pair in the association list. You can use optional arguments to specify independent option bits for controlling pattern compiling and matching. The compiling and matching algorithms are PCRE/Perl-compatible.

The specified regular expression pattern overwrites the previously-compiled pattern and is used for subsequent matching until you provide a new pattern. The function reports any errors in the given pattern.

You can set and unset the `PCRE_CASELESS`, `PCRE_MULTILINE`, `PCRE_DOTALL`, and `PCRE_EXTENDED` independent option bits from within the pattern. The content of the options argument specifies the initial setting at the start of compilation. You can set the `PCRE_ANCHORED` option at matching time and at compile time.

Note: If `pcreObject` is specified as the *g_pattern*, `pcreMatchAssocList` skips pattern compilation and ignores *x_compOptBits*.

Arguments

| | |
|----------------------|---|
| <i>g_pattern</i> | String containing regular expression string to be compiled or a <code>pcreObject</code> . |
| <i>l_subjects</i> | Association list whose keys are strings or symbols. |
| <i>x_compOptBits</i> | (Optional) Independent option bits that affect the compilation. Valid values for this argument are the same as those for the <i>x_options</i> argument to the <code>pcreCompile</code> SKILL function. |
| <i>x_execOptBits</i> | (Optional) Independent option bits that affect pattern matching. Valid values for this argument are the same as those for the <i>x_options</i> argument to the <code>pcreExecute</code> SKILL function. |

Cadence SKILL Language Reference

String Functions

Value Returned

| | |
|-------------------------------|--|
| <code>l_results</code> | Association list of elements from the subject association list whose keys match the pattern. |
| <code>nil</code> | No keys in the subject association list match the pattern. |
| <code>error message(s)</code> | Zero or more error messages that appear if the function fails for any reason, if the subject association list is not valid, or if the pattern compilation fails (indicating the cause of the failure). |

Examples

```
pcreMatchAssocList( "[a-z][0-9]*$"
'((abc "ascii") ("123" "number") (a123 "alphanum")
(a12z "ana")) )
=> ((a123 "alphanum"))

pcreMatchAssocList("[a-z][0-9]*$"
'((abc "ascii") ("123" "number") ("yy\al23" "alphanum") (a12z "ana")))
pcreGenCompileOptBits(?multiline t) pcreGenExecOptBits( ?notbol t) )
=> ("yy\al23" "alphanum"))

pcreMatchAssocList( "box[0-9]*" '(square circle "cell9" "123") ) =>
*Error* pcreMatchAssocList: element in the list given as argument #2 is not a valid
association because its car() (taken as a key) is not either a symbol or a string
- square
```

Related Topics

String Functions

[pcreCompile](#)

[pcreExecute](#)

[pcreGenCompileOptBits](#)

[pcreGenExecOptBits](#)

pcreMatchList

```
pcreMatchList(  
    g_pattern  
    l_subjects  
    [ x_compOptBits ]  
    [ x_execOptBits ]  
)  
=> l_results / nil / error message(s)
```

Description

Matches a list of subjects (strings or symbols) against a regular expression pattern (*g_pattern*) and returns a list of those elements that match. You can use optional arguments to specify independent option bits for controlling pattern compiling and matching. The compiling and matching algorithms are PCRE/Perl-compatible.

The specified regular expression pattern overwrites the previously-compiled pattern and is used for subsequent matching until you provide a new pattern. The function reports any errors in the given pattern.

You can set and unset the PCRE_CASELESS, PCRE_MULTILINE, PCRE_DOTALL, and PCRE_EXTENDED independent option bits from within the pattern. The content of the options argument specifies the initial setting at the start of compilation. You can set the PCRE_ANCHORED option at matching time and at compile time.

Note: If *pcreObject* is specified as the *g_pattern*, *pcreMatchList* skips pattern compilation and ignores *x_compOptBits*.

Arguments

| | |
|----------------------|--|
| <i>g_pattern</i> | String containing regular expression string to be compiled or a <i>pcreObject</i> . |
| <i>l_subjects</i> | List of subject strings or symbols to be matched against the regular expression string. If it is a symbol, its print name is used. |
| <i>x_compOptBits</i> | (Optional) Independent option bits that affect the compilation. Valid values for this argument are the same as those for the <i>x_options</i> argument to the pcreCompile SKILL function. |
| <i>x_execOptBits</i> | (Optional) Independent option bits that affect pattern matching. Valid values for this argument are the same as those for the <i>x_options</i> argument to the pcreExecute SKILL function. |

Cadence SKILL Language Reference

String Functions

Value Returned

| | |
|-------------------------------|--|
| <code>l_results</code> | List of strings, symbols, or PCRE objects from the subject list that match the pattern. |
| <code>nil</code> | No matches or match failure. |
| <code>error message(s)</code> | Zero or more error messages that appear if the function fails for any reason, if the subject list is not valid, or if the pattern compilation fails (indicating the cause of the failure). |

Examples

```
pcreMatchList( "[a-z][0-9]*" ' (a01 x02 "003" aa01 "abc") )
=> (a01 x02 aa01 "abc")

pcreMatchList( "[a-z][0-9][0-9]*" ' (a001 b002 "003" aa01 "abc") )
=> (a001 b002)

pcreMatchList( "box[0-9]*" ' (square circle "cell9" "123") )
=> nil

pcreMatchList( "[a-z][0-9][0-9]*" ' ("12\ na001" b002)
pcreGenCompileOptBits(?multiLine t) pcreGenExecOptBits( ?notbol t) )
=> ("12\ na001")

pcreMatchList( "[a-z][0-9]*" ' (abc 123) )
=>
*Error* pcreMatchList: element in the list given as argument #2 must be either a
symbol or a string - 123

pcreMatchList( "[a-z][0-9]*$" ' ((abc "ascii") (a123 "alphanum")) )
=>
*Error* pcreMatchList: element in the list given as argument #2 must be either a
symbol or a string - (abc "ascii")
```

Related Topics

String Functions

pcreCompile

pcreExecute

pcreGenCompileOptBits

pcreGenExecOptBits

pcreMatchp

```
pcreMatchp(  
    g_pattern  
    S_subject  
    [ x_compOptBits ]  
    [ x_execOptBits ]  
)  
=> t / nil
```

Description

Checks to see whether the subject string or symbol (*S_subject*) matches the specified regular expression pattern (*g_pattern*). You can use optional arguments to specify independent option bits for controlling pattern compiling and matching. The compiling and matching algorithms are PCRE/Perl-compatible. For greater efficiency when matching a number of subjects against a single pattern, you should use [pcreCompile](#) and [pcreExecute](#).

The specified regular expression pattern overwrites the previously-compiled pattern and is used for subsequent matching until you provide a new pattern. The function reports any errors in the given pattern.

You can set and unset the PCRE_CASELESS, PCRE_MULTILINE, PCRE_DOTALL, and PCRE_EXTENDED independent option bits from within the pattern. The content of the options argument specifies the initial setting at the start of compilation. You can set the PCRE_ANCHORED option at matching time and at compile time.

Note: If *pcreObject* is specified as the *g_pattern*, *pcreMatchp* skips pattern compilation and ignores *x_compOptBits*.

Arguments

| | |
|----------------------|--|
| <i>g_pattern</i> | String containing regular expression string to be compiled or a <i>pcreObject</i> . |
| <i>S_subject</i> | Subject string or symbol to be matched. If it is a symbol, its print name is used. |
| <i>x_compOptBits</i> | (Optional) Independent option bits that affect the compilation. Valid values for this argument are the same as those for the <i>x_options</i> argument to the pcreCompile SKILL function. |
| <i>x_execOptBits</i> | (Optional) Independent option bits that affect pattern matching. Valid values for this argument are the same as those for the <i>x_options</i> argument to the pcreExecute SKILL function. |

Cadence SKILL Language Reference

String Functions

Value Returned

| | |
|------------------|--|
| <code>t</code> | A match is found. A message appears if you have any errors in the regular expression pattern. |
| <code>nil</code> | No match. An error message indicating the cause of the matching failure appears. |

Examples

```
pcreMatchp( "[0-9]*[.][0-9][0-9]*" "100.001" )
=> t

pcreMatchp( "[0-9]*[.][0-9]+" ".001" )
=> t

pcreMatchp( "[0-9]*[.][0-9]+" "." )
=> nil

pcreMatchp( "[0-9" "100" )
=>
*Error* pcreCompile: compilation failed at offset 4: missing terminating ] for
character class nil

pcreMatchp( "((?i)rah)\\s+\\1" "rah rah" )
=> t

pcreMatchp( "^[0-9]+" "abc\\n123\\nefg"
pcreGenCompileOptBits(?multiLine t) pcreGenExecOptBits( ?notbol t) )
=> t
```

Related Topics

String Functions

pcreCompile

pcreExecute

pcreGenCompileOptBits

pcreGenExecOptBits

pcreObjectp

```
pcreObjectp(  
    g_arg  
)  
=> t / nil
```

Description

Checks to see whether the given argument is a `pcreObject` or not.

Arguments

| | |
|--------------|------------------------|
| <i>g_arg</i> | A value to be checked. |
|--------------|------------------------|

Value Returned

| | |
|------------|---|
| <i>t</i> | <i>g_arg</i> is a <code>pcreObject</code> . |
| <i>nil</i> | <i>g_arg</i> is not a <code>pcreObject</code> . |

Examples

```
a = pcreCompile("abc[0-9]+")  
=> pcreobj@0x83b8018  
(pcreObjectp a)  
=> t  
(pcreObjectp 9)  
=> nil
```

Related Topics

[String Functions](#)

[pcreCompile](#)

pcrPrintLastError

```
pcrPrintLastError(  
    o_patMatchObj  
)  
=> t / nil
```

Description

Prints the error message associated with the last failed matching operation (that is, when pcrExecute returns `nil`).

Argument

| | |
|----------------------|---|
| <i>o_patMatchObj</i> | Data object containing information from a previously failed pattern compilation/matching operation. |
|----------------------|---|

Value Returned

| | |
|------------------|--|
| <code>t</code> | Prints the error message associated with the last failed matching operation and returns <code>t</code> . |
| <code>nil</code> | No previously failed matching operation. |

Examples

```
comPat = pcrCompile( "[0-9]*[.][0-9]+" )  
=> pcreobj@0x27d060  
pcrExecute( comPat "123" )  
=> nil  
pcrPrintLastError( comPat )  
=> The subject string did not match the compiled pattern.  
pcrExecute( comPat "123" pcrGenCompileOptBits(?caseLess t) )  
=> nil  
pcrPrintLastError( comPat )  
=> An unrecognized bit was set in the options argument.
```

Related Topics

String Functions

pcrCompile

Cadence SKILL Language Reference

String Functions

pcrExecute

pcrGenCompileOptBits

pcrGenExecOptBits

pcreReplace

```
pcreReplace(  
    o_comPatObj  
    t_source  
    t_replacement  
    x_index  
    [ x_options ] )  
=> t_result / t_source
```

Description

Replaces one or all occurrences of a previously-compiled regular expression in the given source string with the specified replacement string. The integer index indicates which of the matching substrings to replace. If the index is less than or equal to zero, the function applies the replacement string to all matching substrings. You can use an optional argument to specify independent option bits for controlling pattern matching. The matching algorithm is PCRE/Perl-compatible.

Arguments

| | |
|----------------------|--|
| <i>o_comPatObj</i> | Data object containing the compiled pattern returned from a previous pcreCompile call. |
| <i>t_source</i> | Source string to be matched and replaced. |
| <i>t_replacement</i> | Replacement string. You can use pattern tags in this string (see pcreSubstitute). |
| <i>x_index</i> | Integer index indicating which of the matching substrings to replace. If the index is less than or equal to zero, the function applies the replacement string to all matching substrings. |
| <i>x_options</i> | (Optional) Independent option bits that affect pattern matching. Valid values for this argument are the same as those for the <i>x_options</i> argument to the pcreExecute SKILL function. |

Value Returned

| | |
|-----------------|---|
| <i>t_result</i> | Copy of the source string with the specified replacement (determined by the integer index). |
| <i>t_source</i> | Original source string if no match was found. |

Cadence SKILL Language Reference

String Functions

Examples

```
comPat1 = pcreCompile( "[0-9]+" )
=> pcreobj@0x27d258

pcreReplace( comPat1 "abc-123-xyz-890-wuv" "(" 0 )
=> "abc-(*)-xyz-(*)-wuv"

pcreReplace( comPat1 "abc-123-xyz-890-wuv" "(" 1 )
=> "abc-(*)-xyz-890-wuv"

pcreReplace( comPat1 "abc-123-xyz-890-wuv" "(" 2 )
=> "abc-123-xyz-(*)-wuv"

pcreReplace( comPat1 "abc-123-xyz-890-wuv" "(" 3 )
=> "abc-123-xyz-890-wuv"

comPat2 = pcreCompile( "xyz" ) => pcreobj@0x27d264
pcreReplace( comPat2 "xyzzxyzz" "xy" 0 )
=> "xyzyxyz"
```

Related Topics

String Functions

pcreCompile

pcreSetRecursionLimit

```
pcreSetRecursionLimit(  
    x_maxDepth  
)  
=> t
```

Description

Sets the maximum recursion depth for SKILL/PCRE match algorithms. The maximum recursion depth needs to be set for systems that have a low stack depth, in order to prevent crashes while using SKILL PCRE functions.

Arguments

| | |
|-------------------|--|
| <i>x_maxDepth</i> | Maximum recursion depth for the PCRE match algorithms. |
|-------------------|--|

Value Returned

| | |
|---|---|
| t | The maximum recursion depth for the PCRE match algorithms is set. |
|---|---|

Examples

```
pcreSetRecursionLimit(1000)  
=> t  
  
pt = pcreCompile("sam | Bill| jack | alan| bob")  
=> pcreobj@0x1df55020  
  
pcreExecute(pt "myString")  
=> nil
```

Related Topics

[String Functions](#)

[pcreGetRecursionLimit](#)

pcreSubpatCount

```
pcreSubpatCount(  
    o_pcreObj  
)  
=> x_count
```

Description

Counts the subpatterns in a PCRE pattern.

Argument

| | |
|------------------|---|
| <i>o_pcreObj</i> | A PCRE compile object, produced by the <code>pcreCompile</code> function. |
|------------------|---|

Value Returned

| | |
|----------------|---|
| <i>x_count</i> | The number of subpatterns in a PCRE pattern. If there are no subpatterns in the PCRE pattern, it returns 0. <i>x_count</i> is a fixnum value. |
|----------------|---|

Examples

```
p1 = pcreCompile("(a)(b)(c)(d)") ;compile a pcre with 4 subpatterns  
pcreSubpatCount(p1)  
=> 4
```

Related Topics

[String Functions](#)

[substring](#)

pcreSubstitute

```
pcreSubstitute(  
    [o_pcreObject]  
    t_string  
)  
=> t_result / nil
```

Description

If `o_pcreObject` is not provided, `pcreSubstitute` copies the input string and substitutes all pattern tags in it using the corresponding matched strings from the last `pcreExecute/pcreMatch*` operation.

If `o_pcreObject` is provided, `pcreSubstitute` copies the input string and substitutes all pattern tags in it using the corresponding matched strings from the last `pcreExecute` operation that used the given `o_pcreObject`.

Pattern tags are of the form `\n`, where `n` is 0-9. `\0` (or `&`) refers to the string that matched the entire regular expression; `\k` refers to the string that matched the pattern wrapped by the k^{th} `backslash (. . . \)` in the regular expression.

If `o_pcreObject` is provided, pattern tag can also have the next form `\{x_num\}`, where `x_num` is a positive integer. This refers to the string that matches the pattern by the `x_num`th `backslash (. . . \)` in the regular expression which has been compiled to `o_pcreObject`. The matched string will be taken from the last string which was matched by `pcreExecute` using `o_pcreObject`.

Argument

| | |
|---------------------------|---|
| <code>o_pcreObject</code> | An object that was used in <code>pcreExecute</code> . |
| <code>t_string</code> | Argument string to which the function applies the substitution. |

Value Returned

| | |
|-----------------------|--|
| <code>t_result</code> | Copy of the argument with the specified substitutions. |
| <code>nil</code> | The last string matching operation failed (none of the pattern tags are meaningful). |

Cadence SKILL Language Reference

String Functions

Examples

```
comPat = pcreCompile( "[a-z]+\.\.\1" ) => pcreobj@0x27d048
pcreExecute( comPat "abc.bc" )
=> t
pcreSubstitute( "*\0*" )
=> "*bc.bc*"
pcreSubstitute( "The matched string is: \1" )
=> "The matched string is: bc"

r = pcreCompile("x[0-9]")
=> pcreobj@0x81ca018
pcreExecute(r "x1")
=> t
str1 = "\\0fff\\1ffff\\2fffff"
"\\0fff\\1ffff\\2fffff"
pcreSubstitute(str1)
=> "x1ffffffffffffff"

pcre = pcreCompile("(a)(b+)([as]+)(q)(w)(r*)(t)(u)(i)(h)(k)(b).*)"
=> pcreobj@0x83bb018
pcre1 = pcreCompile("0x([0-9]+)")
=> pcreobj@0x83bb034
pcreExecute(pcre "abbbasasssqwtuihkbdddd")
=> t
pcreExecute(pcre1 "0x333")
=> t
(for i 0 12
  str = (if i < 10 (sprintf nil "\\%d" i) (sprintf nil "\\{%d}" i))
  (printf "pcreSubstitute(pcre '%s') == '%L'\n" str pcreSubstitute(pcre str))
)
pcreSubstitute(pcre '\0') == "abbbasasssqwtuihkbdddd"
pcreSubstitute(pcre '\1') == "a"
pcreSubstitute(pcre '\2') == "bbb"
pcreSubstitute(pcre '\3') == "asasss"
pcreSubstitute(pcre '\4') == "q"
pcreSubstitute(pcre '\5') == "w"
pcreSubstitute(pcre '\6') == ""
pcreSubstitute(pcre '\7') == "t"
pcreSubstitute(pcre '\8') == "u"
pcreSubstitute(pcre '\9') == "i"
pcreSubstitute(pcre '\{10}') == "h"
pcreSubstitute(pcre '\{11}') == "k"
pcreSubstitute(pcre '\{12}') == "b"
t
```

Cadence SKILL Language Reference

String Functions

```
pcreSubstitute("the last pcreExecute was called - &")  
=>"the last pcreExecute was called - 0x333"
```

Related Topics

[String Functions](#)

[pcreCompile](#)

[pcreExecute](#)

readstring

```
readstring(  
    t_string  
)  
=> g_result / nil
```

Description

Returns the first expression in a string. Subsequent expressions in the string are ignored. The expression is not processed in any way.

Arguments

| | |
|-----------------|-----------------|
| <i>t_string</i> | String to read. |
|-----------------|-----------------|

Value Returned

| | |
|-----------------|--|
| <i>g_result</i> | The object read in. |
| nil | When the port is at the end of the string. |

Examples

The following example shows normal operation.

```
readstring("fun( 1 2 3 ) fun( 4 5 )") => ( fun 1 2 3 )
```

The following example shows the error message if the string contains a syntax error.

```
readstring("fun(" )  
fun(  
^  
SYNTAX ERROR found at line 1 column 4 of file *string*  
*Error* lineread/read: syntax error encountered in input  
*WARNING* (include/load): expression was improperly terminated.
```

The following example illustrates that `readstring` applied to the print representation of an expression, returns the expression.

```
EXPRESSION = 'list( 1 2 )'  
=> list(1 2)  
EXPRESSION == readstring( sprintf( nil "%L" EXPRESSION ))  
=> t
```

Cadence SKILL Language Reference

String Functions

Related Topics

String Functions

linereadstring

rexCompile

```
rexCompile(  
    t_pattern  
)  
=> t / nil
```

Description

Compiles a regular expression string pattern into an internal representation to be used by succeeding calls to `rexExecute`.

This allows you to compile the pattern expression once using `rexCompile` and then match a number of targets using `rexExecute`; this gives better performance than using `rexMatchp` each time.

Note: `rexCompile` does not support the extended regular expression syntax. To parse such regular expressions, you can use the `pcre` (Perl Compatible Regular Expressions) functions (such as `pcreCompile`) instead.

Arguments

| | |
|------------------|------------------------------------|
| <i>t_pattern</i> | Regular expression string pattern. |
|------------------|------------------------------------|

Value Returned

| | |
|------------|--|
| <i>t</i> | The given argument is a legal regular expression string. |
| <i>nil</i> | Signals an error if the given pattern is ill-formed or not a legal expression. |

Examples

```
rexCompile("^ [a-zA-Z]+")  
=> t  
rexCompile("\\ ([a-z]+\\)\\.\\1")  
=> t  
rexCompile("^\\ ([a-z]*\\)\\1$")  
=> t  
rexCompile("[ab")  
=> *Error* rexCompile: Missing ] - "[ab"
```

Cadence SKILL Language Reference

String Functions

Pattern Matching of Regular Expressions

In many applications, you need to match strings or symbols against a pattern. SKILL provides a number of pattern matching functions that are built on a few primitive C library routines with a corresponding SKILL interface.

A pattern used in the pattern matching functions is a string indicating a regular expression. Here is a brief summary of the rules for constructing regular expressions in SKILL:

Rules for Constructing Regular Expressions

| Synopsis | Meaning |
|----------------------------|---|
| <code>c</code> | Any ordinary character (not a special character listed below) matches itself. |
| <code>.</code> | A dot matches any character. |
| <code>\</code> | A backslash when followed by a special character matches that character literally. When followed by one of <code><</code> , <code>></code> , <code>(</code> , <code>)</code> , and <code>1,...,9</code> , it has a special meaning as described below. |
| <code>[c...]</code> | A nonempty string of characters enclosed in square brackets (called a set) matches one of the characters in the set. If the first character in the set is <code>^</code> , it matches a character not in the set. A shorthand S-E is used to specify a set of characters S up to E, inclusive. The special characters <code>]</code> and <code>-</code> have no special meaning if they appear as the first character in a set. |
| <code>*</code> | A regular expression of any of the forms above, followed by the closure character <code>*</code> matches zero or more occurrences of that form. |
| <code>+</code> | Similar to <code>*</code> , except it matches one or more times. |
| <code>\(...\)</code> | A regular expression wrapped as <code>\(form \)</code> matches whatever <code>form</code> matches, but saves the string matched in a numbered register (starting from one, can be up to nine) for later reference. |
| <code>\n</code> | A backslash followed by a digit <code>n</code> matches the contents of the <code>n</code> th register from the current regular expression. |
| <code>\<...\></code> | A regular expression starting with a <code>\<</code> and/or ending with a <code>\></code> restricts the pattern matching to the beginning and/or the end of a word. A word defined to be a character string can consist of letters, digits, and underscores. |
| <code>rs</code> | A composite regular expression <code>rs</code> matches the longest match of <code>r</code> followed by a match for <code>s</code> . |
| <code>^, \$</code> | A <code>^</code> at the beginning of a regular expression matches the beginning of a string. A <code>\$</code> at the end matches the end of a string. Used elsewhere in the pattern, <code>^</code> and <code>\$</code> are treated as ordinary characters. |

How Pattern Matching Works

The mechanism for pattern matching

- Compiles a pattern into a form and saves the form internally.
- Uses that internal form in every subsequent matching against the targets until the next pattern is supplied.

The `rexCompile` function does the first part of the task, that is, the compilation of a pattern. The `rexExecute` function takes care of the second part, that is, matching a target against the previously compiled pattern. Sometimes this two-step interface is too low-level and awkward to use, so functions for higher-level abstraction (such as `rexMatchp`) are also provided in SKILL.

Avoiding Null and Backslash Problems

- A null string ("") is interpreted as no pattern being supplied, which means the previously compiled pattern is still used. If there was no previous pattern, an error is signaled.
- To put a backslash character (\) into a pattern string, you need an extra backslash (\) to escape the backslash character itself.

For example, to match a file name with dotted extension `.il`, the pattern `"^[a-zA-Z]+\.\.il$"` can be used, but `"^[a-zA-Z]\.\.il$"` gives a syntax error. However, if the pattern string is read in from an input function such as `gets` that does not interpret backslash characters specifically, you should not add an extra backslash to enter a backslash character.

Related Topics

[String Functions](#)

[rexExecute](#)

[rexMatchp](#)

[rexSubstitute](#)

[pcreCompile](#)

rexExecute

```
rexExecute(  
    S_target  
)  
=> t / nil
```

Description

Matches a string or symbol against the previously compiled pattern set up by the last `rexCompile` call.

This function is used in conjunction with `rexCompile` for matching multiple targets against a single pattern.

Note: Calls to `rexMatchp` reset the pattern set up by `rexCompile`. If any calls to `rexMatchP` have been made, `rexExecute` will not match the pattern set by `rexCompile`.

Arguments

| | |
|-----------------|---|
| <i>S_target</i> | String or symbol to be matched. If a symbol is given, its print name is used. |
|-----------------|---|

Value Returned

| | |
|-----|-----------------------|
| t | A match is found. |
| nil | A match is not found. |

Examples

```
rexCompile("^ [a-zA-Z] [a-zA-Z0-9]*")  
=> t  
rexExecute('Cell123)  
=> t  
rexExecute("123 cells")  
=> nil
```

Target does not begin with a-z/A-Z

```
rexCompile("\\ ([a-z]+)\\.\\.\\.\\1")  
=> t  
rexExecute("abc.bc")
```

Cadence SKILL Language Reference

String Functions

```
=> t  
rexExecute("abc.ab")  
=> nil
```

Related Topics

[String Functions](#)

[rexCompile](#)

[rexMatchp](#)

[rexSubstitute](#)

[pcreCompile](#)

rexMagic

```
rexMagic(  
    [ g_state ]  
)  
=> t / nil
```

Description

Turns on or off the special interpretation associated with the meta-characters in regular expressions.

By default the meta-characters (^, \$, *, +, \, [,], etc.) in a regular expression are interpreted specially. However, this “magic” can be explicitly turned off and on programmatically by this function. If no argument is given, the current setting is returned. Users of `vi` will recognize this as equivalent to the `set magic/set nomagic` commands.

Arguments

| | |
|----------------|---|
| <i>g_state</i> | <code>nil</code> turns off the magic of the meta-characters. Anything else turns on the magic interpretation. |
|----------------|---|

Value Returned

| | |
|------------------|----------------------|
| <code>t</code> | The current setting. |
| <code>nil</code> | The given argument. |

Examples

```
rexCompile( "^ [0-9]+ " )  
=> t  
rexExecute( "123abc" )  
=> t  
rexSubstitute( "got: \\0")  
=> "got: 123"  
rexMagic( nil )  
=> nil  
rexCompile( "^ [0-9]+ " )  
=> t      recompile w/o magic  
rexExecute( "123abc" )  
=> nil  
rexExecute( "***^ [0-9]+!***")  
=> t
```


Cadence SKILL Language Reference

String Functions

```
rexSubstitute( "got: \\0")  
=> "got: \\0"  
  
rexMagic( t )  
=> t  
  
rexSubstitute( "got: \\0")  
=> "got: ^[0-9]+"  
rexMagic(nil) ;; switch off  
rexSubstitute("[&]")  
=> "[&]"
```

Related Topics

[String Functions](#)

[rexCompile](#)

[rexSubstitute](#)

[rexReplace](#)

rexMatchAssocList

```
rexMatchAssocList(  
    t_pattern  
    l_targets  
)  
=> l_results / nil
```

Description

Returns a new association list created out of those elements of the given association list whose key matches a regular expression pattern. The supplied regular expression pattern overwrites the previously compiled pattern and is used for subsequent matching until the next new pattern is provided.

l_targets is an association list, that is, each element on *l_targets* is a list with its *car* taken as a key (either a string or a symbol). This function matches the keys against *t_pattern*, selects the elements on *l_targets* whose keys match the pattern, and returns a new association list out of those elements.

Arguments

| | |
|------------------|---|
| <i>t_pattern</i> | Regular expression pattern. |
| <i>l_targets</i> | Association list whose keys are strings and/or symbols. |

Value Returned

| | |
|------------------|---|
| <i>l_results</i> | New association list of elements that are in <i>l_targets</i> and whose keys match <i>t_pattern</i> . |
| <i>nil</i> | If no match is found. Signals an error if the given pattern is ill-formed. |

Examples

```
rexMatchAssocList("^([a-z][0-9]*)$"  
    '((abc "ascii") ("123" "number") (a123 "alphanum")  
      (a12z "ana")))  
=> ((a123 "alphanum"))
```

Cadence SKILL Language Reference

String Functions

Related Topics

[String Functions](#)

[rexCompile](#)

[rexExecute](#)

[rexMatchp](#)

[rexMatchList](#)

rexMatchList

```
rexMatchList(  
    t_pattern  
    l_targets  
)  
=> l_results / nil
```

Description

Creates a new list of those strings or symbols in the given list that match a regular expression pattern. The supplied regular expression pattern overwrites the previously compiled pattern and is used for subsequent matching until the next new pattern is provided.

Arguments

| | |
|------------------|---|
| <i>t_pattern</i> | Regular expression pattern. |
| <i>l_targets</i> | List of strings and/or symbols to be matched against the pattern. |

Value Returned

| | |
|------------------|---|
| <i>l_results</i> | List of strings (or symbols) that are on <i>l_targets</i> and found to match <i>t_pattern</i> . |
| <i>nil</i> | If no match is found. Signals an error if the given pattern is ill-formed. |

Examples

```
rexMatchList("^ [a-z] [0-9]*" ' (a01 x02 "003" aa01 "abc"))  
=> (a01 x02 aa01 "abc")  
  
rexMatchList("^ [a-z] [0-9] [0-9]*" ' (a001 b002 "003" aa01 "abc"))  
=> (a001 b002)  
  
rexMatchList("box[0-9]*" ' (square circle "cell9" "123"))  
=> nil
```

Related Topics

String Functions

rexCompile

Cadence SKILL Language Reference

String Functions

rexMatchp

rexExecute

rexMatchAssocList

rexMatchp

```
rexMatchp(  
    t_pattern  
    S_target  
)  
=> t / nil
```

Description

Checks to see if a string or symbol matches a given regular expression pattern. The supplied regular expression pattern overwrites the previously compiled pattern and is used for subsequent matching until the next new pattern is provided.

This function matches *S_target* against the regular expression *t_pattern* and returns *t* if a match is found, *nil* otherwise. An error is signaled if the given pattern is ill-formed. For greater efficiency when matching a number of targets against a single pattern, use the `rexCompile` and `rexExecute` functions.

Arguments

| | |
|------------------|---|
| <i>t_pattern</i> | Regular expression pattern. |
| <i>S_target</i> | String or symbol to be matched against the pattern. |

Value Returned

| | |
|----------|--|
| <i>t</i> | A match is found. Signals an error if the given pattern is ill-formed. |
|----------|--|

Examples

```
rexMatchp("[0-9]*[.][0-9][0-9]*" "100.001")  
=> t  
rexMatchp("[0-9]*[.][0-9]+" ".001")  
=> t  
rexMatchp("[0-9]*[.][0-9]+" ".")  
=> nil  
rexMatchp("[0-9]*[.][0-9][0-9]*" "10.")  
=> nil  
rexMatchp("[0-9" "100")  
*Error* rexMatchp: Missing ] - "[0-9"
```

Cadence SKILL Language Reference

String Functions

Related Topics

String Functions

rexCompile

rexExecute

rexReplace

```
rexReplace(  
    t_source  
    t_replacement  
    x_index  
)  
=> t_result
```

Description

Returns a copy of the source string in which the specified substring instances that match the last compiled regular expression are replaced with the given string.

Scans the source string *t_source* to find all substring(s) that match the last regular expression compiled and replaces one or all of them by the replacement string *t_replacement*. The argument *x_index* tells which occurrence of the matched substring is to be replaced. If it's 0 or negative, all the matched substrings will be replaced. Otherwise only the *x_index* occurrence is replaced. Returns the source string if the specified match is not found.

Arguments

| | |
|----------------------|--|
| <i>t_source</i> | Source string to be matched and replaced. |
| <i>t_replacement</i> | Replacement string to be used. Pattern tags can be used in this string (see rexSubstitute). |
| <i>x_index</i> | Specifies which of the matching substrings to replace. Do a global replace if it's ≤ 0 . |

Value Returned

| | |
|-----------------|---|
| <i>t_result</i> | Copy of the source string with specified replacement or the original source string if no match was found. |
|-----------------|---|

Examples

```
rexCompile( "[0-9]+" )  
=> t  
rexReplace( "abc-123-xyz-890-wuv" "(*)" 1)  
=> "abc-(*)-xyz-890-wuv"  
rexReplace( "abc-123-xyz-890-wuv" "(*)" 2)  
=> "abc-123-xyz-(*)-wuv"
```


Cadence SKILL Language Reference

String Functions

```
rexReplace( "abc-123-xyz-890-wuv" "(*)" 3)
=> "abc-123-xyz-890-wuv"

rexReplace( "abc-123-xyz-890-wuv" "(*)" 0)
=> "abc-(*)-xyz-(*)-wuv"
rexCompile( "xyz" )
=> t

rexReplace( "xyzzxyzz" "xy" 0)
=> "xyzyxyz" ; no rescanning!

rexCompile("^teststr")
rexReplace("teststr_a" "bb" 0)
=> "bb_a"

rexReplace("teststr_a" "bb&" 0)
=> "b teststr_a"

rexReplace("teststr_a" "[&]" 0)
=> "[teststr]_a"
```

Related Topics

String Functions

rexCompile

rexMatchp

rexSubstitute

rexExecute

rexSubstitute

```
rexSubstitute(  
    t_string  
)  
=> t_result / nil
```

Description

Substitutes the pattern tags in the argument string with previously matched (sub)strings.

Copies the argument string and substitutes all pattern tags in it by their corresponding matched strings in the last string matching operation. The tags are in the form of '*n*', where *n* is 0-9. '*\0*' (or '*&*') refers to the string that matched the entire regular expression and '*\k*' refers to the string that matched the pattern wrapped by the *k*'th '*\(...\)*' in the regular expression.

Arguments

| | |
|-----------------|------------------------------------|
| <i>t_string</i> | Argument string to be substituted. |
|-----------------|------------------------------------|

Value Returned

| | |
|-----------------|--|
| <i>t_result</i> | Copy of the argument with all the tags in it being substituted by the corresponding strings. |
| <i>nil</i> | The last string matching operation failed (and none of the pattern tags are meaningful). |

Examples

```
rexCompile( "[a-z]+\\[([0-9]+\)\]" )  
=> t  
rexExecute( "abc123" )  
=> t  
rexSubstitute( "*\0*" )  
=> "*abc123*"  
rexSubstitute( "The matched number is: \1" )  
  
=> "The matched number is: 123"  
rexExecute( "123456" )  
=> nil ; match failed  
rexSubstitute( "-\0-" )
```

Cadence SKILL Language Reference

String Functions

```
=> nil  
  
rexCompile("^teststr")  
=> t  
s="teststr_1"  
rexExecute(s)  
rexSubstitute("&")  
=> "teststr"  
rexSubstitute("[&]")  
=> "[teststr]"
```

Related Topics

String Functions

rexCompile

rexMatchp

rexReplace

rindex

```
rindex(  
    t_string1  
    S_string2  
)  
=> t_result / nil
```

Description

Returns a string consisting of the remainder of *string1* beginning with the last occurrence of *string2*.

Compares two strings. Similar to `index` except that it looks for the last (that is, rightmost) occurrence of the symbol or string *S_string2* in string *t_string* instead of the first occurrence.

Arguments

| | |
|------------------|--|
| <i>t_string1</i> | String to search for the last occurrence of <i>S_string2</i> . |
| <i>S_string2</i> | String or symbol to search for. |

Value Returned

| | |
|------------------|--|
| <i>t_result</i> | Remainder of <i>t_string1</i> starting with last match of <i>S_string2</i> . |
| <code>nil</code> | There is no match. |

Examples

```
rindex( "dandelion" "d")  
=> "delion"
```

Related Topics

[String Functions](#)

[nindex](#)

sprintf

```
sprintf(  
    {s_Var | nil }  
    t_formatString  
    [ g_arg1 ... ]  
)  
=> t_string
```

Description

Formats the output and assigns the resultant string to the variable given as the first argument.

Note: `sprintf` is a syntax form and should not be used as an argument to `apply` or `eval`.

If `nil` is specified as the first argument, no assignment is made, but the formatted string is returned.

Arguments

| | |
|-----------------------|---|
| <i>s_Var</i> | Variable name. |
| <code>nil</code> | <code>nil</code> if no variable name. |
| <i>t_formatString</i> | Format string. |
| <i>g_arg1</i> | Arguments following the format string are printed according to their corresponding format specifications. |

Value Returned

| | |
|-----------------|--------------------------|
| <i>t_string</i> | Formatted output string. |
|-----------------|--------------------------|

Examples

```
sprintf(s "Memorize %s number %d!" "transaction" 5)  
=> "Memorize transaction number 5!"  
  
s  
=> "Memorize transaction number 5!"  
  
p = outfile(sprintf(nil "test%d.out" 10))  
=> port:"test10.out"
```

Related Topics

[String Functions](#)

[Common Output Format Specifications](#)

strcat

```
strcat(  
    S_string1  
    [ S_string2 ... ]  
)  
=> t_result
```

Description

Takes input strings or symbols and concatenates them.

Arguments

S_string1 S_string2 ...

One or more input strings or symbols.

Value Returned

t_result

New string containing the contents of all input strings or symbols *S_string1*, *S_string2*, ..., concatenated together. The input arguments are left unchanged.

Examples

```
strcat( 'ab "xyz" )  
=> "abxyz"  
strcat( "l" "ab" "ef" )  
=> "labef"
```

Related Topics

[String Functions](#)

[buildString](#)

[concat](#)

[strncat](#)

[strcmp](#)

Cadence SKILL Language Reference

String Functions

strncmp

substring

strcmp

```
strcmp(  
    t_string1  
    t_string2  
)  
=> 1 / 0 / -1
```

Description

Compares two argument strings alphabetically.

Compares the two argument strings *t_string1* and *t_string2* and returns an integer greater than, equal to, or less than zero depending on whether *t_string1* is alphabetically greater, equal to, or less than *t_string2*. To test if the contents of two strings are the same, use the `equal` function.

Arguments

| | |
|------------------|-------------------------------|
| <i>t_string1</i> | First string to be compared. |
| <i>t_string2</i> | Second string to be compared. |

Value Returned

| | |
|----|--|
| 1 | <i>t_string1</i> is alphabetically greater than <i>t_string2</i> . |
| 0 | <i>t_string1</i> is alphabetically equal to <i>t_string2</i> . |
| -1 | <i>t_string1</i> is alphabetically less than <i>t_string2</i> . |

Examples

```
strcmp( "abc" "abb" )  
=> 1  
strcmp( "abc" "abc")  
=> 0  
strcmp( "abc" "abd")  
=> -1
```

Related Topics

String Functions

Cadence SKILL Language Reference

String Functions

strncmp

stringp

```
stringp(  
    g_value  
)  
=> t / nil
```

Description

Checks if an object is a string.

The suffix `p` is usually added to the name of a function to indicate that it is a predicate function.

Arguments

| | |
|----------------|----------------|
| <i>g_value</i> | A data object. |
|----------------|----------------|

Value Returned

| | |
|------------------|----------------------------------|
| <code>t</code> | <i>g_value</i> is a string. |
| <code>nil</code> | <i>g_value</i> is not a string.. |

Examples

```
stringp( 93)  
=> nil  
stringp( "93")  
=> t
```

Related Topics

[String Functions](#)

[listp](#)

[symbolp](#)

strlen

```
strlen(  
    t_string  
)  
=> x_length
```

Description

Returns the number of characters in a string.

Arguments

| | |
|-----------------|-----------------------------------|
| <i>t_string</i> | String length you want to obtain. |
|-----------------|-----------------------------------|

Value Returned

| | |
|-----------------|-----------------------------|
| <i>x_length</i> | Length of <i>t_string</i> . |
|-----------------|-----------------------------|

Examples

```
strlen( "abc" )  
=> 3  
strlen( "\\007" )  
=> 1 ; Backslash notation used.
```

Related Topics

[String Functions](#)

[parseString](#)

[substring](#)

[strcat](#)

[strcmp](#)

[strncmp](#)

[stringp](#)

strncat

```
strncat(  
    t_string1  
    t_string2  
    x_max  
)  
=> t_result
```

Description

Creates a new string by appending a maximum number of characters from *t_string2* to *t_string1*.

Concatenates input strings. Similar to *strcat* except that at most *x_max* characters from *t_string2* are appended to the contents of *t_string1* to create the new string. *t_string1* and *t_string2* are left unchanged.

Arguments

| | |
|------------------|---|
| <i>t_string1</i> | First string included in the new string. |
| <i>t_string2</i> | Second string whose characters are appended to <i>t_string1</i> . |
| <i>x_max</i> | Maximum number of characters from <i>t_string2</i> that you want to append to the end of <i>t_string1</i> . |

Value Returned

| | |
|-----------------|---|
| <i>t_result</i> | The new string; <i>t_string1</i> and <i>t_string2</i> are left unchanged. |
|-----------------|---|

Examples

```
strncat( "abcd" "efghi" 2)  
=> "abcdef"  
strncat( "abcd" "efghijk" 5)  
=> "abcdefghi"
```

Related Topics

[String Functions](#)

Cadence SKILL Language Reference

String Functions

parseString

substring

strcat

strcmp

strncmp

substring

stringp

strncmp

```
strncmp(  
    t_string1  
    t_string2  
    x_max  
)  
=> 1 / 0 / -1
```

Description

Compares two argument strings alphabetically only up to a maximum number of characters.

Similar to `strcmp` except that only up to *x_max* characters are compared. To test if the contents of two strings are the same, use the `equal` function.

Arguments

| | |
|------------------|--|
| <i>t_string1</i> | First string to be compared. |
| <i>t_string2</i> | Second string to be compared. |
| <i>x_max</i> | Maximum number of characters in both strings to be compared. |

Value Returned

For the first specified number of characters:

| | |
|----|--|
| 1 | <i>t_string1</i> is alphabetically greater than <i>t_string2</i> |
| 0 | <i>t_string1</i> is alphabetically equal to <i>t_string2</i> . |
| -1 | <i>t_string1</i> is alphabetically less than <i>t_string2</i> . |

Examples

```
strncmp( "abc" "ab" 3)  
=> 1  
strncmp( "abc" "de" 4)  
=> -1  
strncmp( "abc" "ab" 2)  
=> 0
```

Cadence SKILL Language Reference

String Functions

Related Topics

String Functions

strcmp

strpbrk

```
strpbrk(  
    t_str1  
    t_str2  
)  
=> t_subStr / nil
```

Description

Returns a substring of the first occurrence in *t_str1* of any character from the string pointed to by *t_str2*

Arguments

| | |
|---------------|--|
| <i>t_str1</i> | Specifies the string that you need to scan |
| <i>t_str2</i> | Specifies the pattern that you need to match |

Value Returned

| | |
|-----------------|---|
| <i>t_substr</i> | Returns a substring of the first occurrence of any character specified in <i>t_str2</i> |
| <i>nil</i> | Returns <i>nil</i> if no occurrence of any character from <i>t_str2</i> is found in <i>t_str1</i> |

Examples

```
s="world"  
strpbrk(s "o")  
=> "orld"  
strpbrk(s "sssssl")  
=>"ld"  
strpbrk(s "ss")  
=> nil  
strpbrk("WORLD" "world")  
=> nil  
strpbrk("WORLD" " ")  
=> nil
```

Cadence SKILL Language Reference

String Functions

Related Topics

[String Functions](#)

[strcat](#)

[strcmp](#)

substring

```
substring(  
    S_string  
    x_index  
    [ x_length ]  
)  
=> t_result / nil
```

Description

Creates a new substring from an input string, starting at an index point and continuing for a given length.

Creates a new substring from *S_string* with a starting point determined by *x_index* and length determined by an optional third argument *x_length*.

- If *S_string* is a symbol, the substring is taken from its print name.
- If *x_length* is not given, then all of the characters from *x_index* to the end of the string are returned.
- If *x_index* is negative the substring begins at the indexed character from the end of the string.
- If *x_index* is out of bounds (that is, its absolute value is greater than the length of *S_string*), nil is returned.

Arguments

| | |
|-----------------|--|
| <i>S_string</i> | A string. |
| <i>x_index</i> | Starting point for returning a new string. Cannot be zero. |
| <i>x_length</i> | Length of string to be returned. |

Value Returned

| | |
|-----------------|--|
| <i>t_result</i> | Substring of <i>S_string</i> starting at the character indexed by <i>x_index</i> , with a maximum of <i>x_length</i> characters. |
| nil | If <i>x_index</i> is out of bounds. |

Cadence SKILL Language Reference

String Functions

Examples

```
substring("abcdef" 2 4)
=> "bcde"
substring("abcdef" 4 2)
=> "de"
substring("abcdef" -4 2)
=> "cd"
```

Related Topics

[String Functions](#)

[parseString](#)

Cadence SKILL Language Reference

String Functions

upperCase

```
upperCase(  
    S_string  
)  
=> t_result
```

Description

Returns a string that is a copy of the given argument with the lowercase alphabetic characters replaced by their uppercase equivalents.

If the parameter is a symbol, the name of the symbol is used.

Arguments

| | |
|-----------------|-------------------------|
| <i>S_string</i> | Input string or symbol. |
|-----------------|-------------------------|

Value Returned

| | |
|-----------------|---|
| <i>t_result</i> | Copy of <i>S_string</i> in uppercase letters. |
|-----------------|---|

Examples

```
upperCase("Hello world!")  
=> "HELLO WORLD!"
```

Related Topics

[String Functions](#)

[lowerCase](#)

Cadence SKILL Language Reference

String Functions

Arithmetic Functions

All arithmetic operators are translated into calls to predefined SKILL functions. The following table lists the arithmetic functions.

| | | |
|-------------------|--------------------|-------------------------|
| <u>abs</u> | <u>add1</u> | <u>atof</u> |
| <u>atoi</u> | <u>ceiling</u> | <u>defMathConstants</u> |
| <u>difference</u> | <u>evenp</u> | <u>exp</u> |
| <u>expt</u> | <u>fix</u> | <u>fixp</u> |
| <u>fix2</u> | <u>float</u> | <u>floatp</u> |
| <u>floor</u> | <u>int</u> | <u>isInfinity</u> |
| <u>isNaN</u> | <u>leftshift</u> | <u>log</u> |
| <u>log10</u> | <u>max</u> | <u>min</u> |
| <u>minus</u> | <u>minusp</u> | <u>mod</u> |
| <u>modf</u> | <u>modulo</u> | <u>nearlyEqual</u> |
| <u>negativep</u> | <u>oddp</u> | <u>onep</u> |
| <u>plus</u> | <u>plusp</u> | <u>quotient</u> |
| <u>random</u> | <u>realp</u> | <u>remainder</u> |
| <u>rightshift</u> | <u>round</u> | <u>round2</u> |
| <u>sort</u> | <u>sortcar</u> | <u>sqrt</u> |
| <u>srandom</u> | <u>sub1</u> | <u>times</u> |
| <u>truncate</u> | <u>xdifference</u> | <u>xplus</u> |
| <u>xquotient</u> | <u>xtimes</u> | <u>zerop</u> |
| <u>zxt</u> | | |

abs

```
abs (  
    n_number  
)  
=> n_result
```

Description

Returns the absolute value of a floating-point number or integer.

Arguments

| | |
|-----------------|-----------------------------------|
| <i>n_number</i> | Floating-point number or integer. |
|-----------------|-----------------------------------|

Value Returned

| | |
|-----------------|-------------------------------------|
| <i>n_result</i> | Absolute value of <i>n_number</i> . |
|-----------------|-------------------------------------|

Examples

```
abs ( -209.625)  
=> 209.625  
  
abs ( -23)  
=> 23
```

Related Topics

[min](#)

[Arithmetic Functions](#)

add1

```
add1(  
    n_number  
)  
=> n_result
```

Description

Adds one to a floating-point number or integer.

Arguments

| | |
|-----------------|--|
| <i>n_number</i> | Floating-point number or integer to increase by one. |
|-----------------|--|

Value Returned

| | |
|-----------------|---------------------------|
| <i>n_result</i> | <i>n_number</i> plus one. |
|-----------------|---------------------------|

Examples

```
add1( 59 )  
=> 60
```

Related Topics

[sub1](#)

[Arithmetic Functions](#)

atof

```
atof(  
    t_string [t]  
)  
=> f_result / nil
```

Description

Converts a string into a floating-point number. Returns `nil` if the given string does not denote a number.

The `atof` function calls the C library function `strtod` to convert a string into a floating-point number. It returns `nil` if *t_string* does not represent a number.

Arguments

| | |
|-----------------|---|
| <i>t_string</i> | A string. |
| <i>t</i> | If <i>t_string</i> includes any non-numerical characters, this argument enforces that <code>nil</code> is returned. |

Value Returned

| | |
|------------------|---|
| <i>f_result</i> | The floating-point value represented by <i>t_string</i> . |
| <code>nil</code> | If <i>t_string</i> includes any non-numerical characters. |

Examples

```
atof("123")  
=> 123.0  
atof("abc")  
=> nil  
atof("123.456")  
=> 123.456  
atof("123abc")  
=> 123.0  
atof("12.01.01")  
=> 12.01  
atof("12.01.01" t)  
=> nil
```

Related Topics

[atoi](#)

[Arithmetic Functions](#)

atoi

```
atoi(  
    t_string [t]  
)  
=> x_result / nil
```

Description

Converts a string into an integer. Returns `nil` if the given string does not denote an integer.

The `atoi` function calls the C library function `strtol` to convert a string into an integer. It returns `nil` if *t_string* does not represent an integer.

Arguments

| | |
|-----------------|---|
| <i>t_string</i> | A string. |
| <i>t</i> | If <i>t_string</i> includes any non-numeric characters, this argument enforces that <code>nil</code> is returned. |

Value Returned

| | |
|------------------|---|
| <i>x_result</i> | The integer value represented by <i>t_string</i> . |
| <code>nil</code> | If <i>t_string</i> includes any non-numeric characters. |

Examples

```
atoi("123")  
=> 123  
atoi("abc")  
=> nil  
atoi("123.456")  
=> 123  
atoi("123abc")  
=> 123  
atoi("12.01.01")  
=> 12.01  
atoi("12.01.01" t)  
=> nil
```

Related Topics

[atof](#)

[Arithmetic Functions](#)

ceiling

```
ceiling(  
    n_number  
)  
=> x_integer
```

Description

Returns the smallest integer not smaller than the given argument.

Arguments

| | |
|-----------------|-------------|
| <i>n_number</i> | Any number. |
|-----------------|-------------|

Value Returned

| | |
|------------------|---|
| <i>x_integer</i> | Smallest integer not smaller than <i>n_number</i> . |
|------------------|---|

Examples

```
(ceiling -4.3)  
=> -4  
(ceiling 3.5)  
=> 4
```

Related Topics

[floor](#)

[round](#)

[truncate](#)

[Arithmetic Functions](#)

defMathConstants

```
defMathConstants(  
    s_id  
)  
=> s_id
```

Description

Associates a set of predefined math constants as properties of the given symbol.

Arguments

s_id The properties to be associated with the symbol are listed as name/value pairs.

The names are explained in the following table.

| Name | Meaning |
|-----------|---|
| E | The base of natural logarithm. (<i>e</i>) |
| LOG2E | The base-2 logarithm of <i>e</i> $\log_2 e$ |
| LOG10E | The base-10 logarithm of <i>e</i> $\log_{10} e$ |
| LN2 | The natural logarithm of 2. $\log_e 2$ |
| LN10 | The natural logarithm of 10. $\log_e 10$ |
| PI | The ratio of the circumference of a circle to its diameter. (π) |
| PI_OVER_2 | $\pi / 2$ $\frac{\pi}{2}$ |

Cadence SKILL Language Reference

Arithmetic Functions

| Name | Meaning |
|-----------------|--|
| PI_OVER_4 | $\pi / 4$ $\frac{\pi}{4}$ |
| ONE_OVER_PI | $1/\pi$ $\frac{1}{\pi}$ |
| TWO_OVER_PI | $2/\pi$ $\frac{2}{\pi}$ |
| TWO_OVER_SQRTPI | $\frac{2}{\sqrt{\pi}}$ |
| SQRT_TWO | The square root of 2. $\sqrt{2}$ |
| SQRT_POINT_FIVE | The square root of 1/2. $\sqrt{\frac{1}{2}}$ |
| INT_MAX | The maximum value of a SKILL integer. |
| INT_MIN | The minimum value of a SKILL integer is -2147483648. The minimum literal value which may appear in a program is -2147483647. |
| DBL_MAX | The maximum value of a SKILL double. |
| DBL_MIN | The minimum value of a SKILL double. |
| SHRT_MAX | The maximum value of a SKILL "short" integer. |
| SHRT_MIN | The minimum value of a SKILL "short" integer. |

Cadence SKILL Language Reference

Arithmetic Functions

Value Returned

s_id The symbol ID.

Examples

```
defMathConstants('m)
=> m

m.?? => (
SQRT_POINT_FIVE 0.7071068
SQRT_TWO 1.414214
TWO_OVER_SQRTPI 1.128379
TWO_OVER_PI 0.6366198
ONE_OVER_PI 0.3183099
PI_OVER_4 0.7853982
PI_OVER_2 1.570796
PI 3.141593
LN10 2.302585
LN2 0.6931472
LOG10E 0.4342945
LOG2E 1.442695
E 2.718282
DBL_MIN 2.225074e-308
DBL_MAX 1.797693e+308
INT_MIN -2147483648
INT_MAX 2147483647
SHRT_MIN -32768
SHRT_MAX 32767)

m.SQRT_POINT_FIVE
=> 0.7071068

m.INT_MIN
=> -2147483648

m.PI
=> 3.141593

printf("%.17f\n" m.PI)
=> 3.14159265358979312
```

Related Topics

[printf](#)

[getqq](#)

[plist](#)

[setplist](#)

[Arithmetic Functions](#)

difference

```
difference(  
    n_op1  
    n_op2  
    [ n_op3 ... ]  
)  
=> n_result
```

Description

Returns the result of subtracting one or more operands from the first operand. Prefix form of the – arithmetic operator.

Arguments

| | |
|--------------|--|
| <i>n_op1</i> | Number from which the others are to be subtracted. |
| <i>n_op2</i> | Number to subtract. |
| <i>n_op3</i> | Optional additional numbers to subtract. |

Value Returned

| | |
|-----------------|--------------------------|
| <i>n_result</i> | Result of the operation. |
|-----------------|--------------------------|

Examples

```
difference(5 4 3 2 1)  
=> -5  
difference(-12 13)  
=> -25  
difference(12.2 -13)  
=> 25.2
```

Related Topics

[xdifference](#)

[Arithmetic Functions](#)

evenp

```
evenp(  
    g_general  
)  
=> t / nil
```

Description

Checks if a number is an even integer.

Arguments

| | |
|------------------|------------------|
| <i>g_general</i> | Number to check. |
|------------------|------------------|

Value Returned

| | |
|-----|---|
| t | If <i>g_general</i> is an even integer. |
| nil | If <i>g_general</i> is not an even integer. |

Examples

```
evenp( 59 )  
=> nil  
evenp( 60 )  
=> t  
evenp( 2.0 )  
=> nil ; Number is even, but not an integer.
```

Related Topics

[minusp](#)

[oddp](#)

[onep](#)

[plusp](#)

[zerop](#)

Arithmetic Functions

exp

```
exp(  
    n_number  
)  
=> f_result
```

Description

Raises *e* to a given power.

Arguments

| | |
|-----------------|-----------------------------|
| <i>n_number</i> | Power to raise <i>e</i> to. |
|-----------------|-----------------------------|

Value Returned

| | |
|-----------------|--|
| <i>f_result</i> | Value of <i>e</i> raised to the <i>n_number</i> th power. |
|-----------------|--|

Examples

```
exp( 1 )  
=> 2.718282  
  
exp( 3.0 )  
=> 20.08554
```

Related Topics

[asin](#)

[atan](#)

[cos](#)

[log](#)

[sin](#)

[Arithmetic Functions](#)

expt

```
expt (
    n_base
    n_power
)
=> n_result
```

Description

Returns the result of raising a base number to a power. Prefix form of the ** exponentiation operator.

Arguments

| | |
|----------------|--------------------------------------|
| <i>n_base</i> | Number to be raised to a power. |
| <i>n_power</i> | Power to which the number is raised. |

Value Returned

| | |
|-----------------|---|
| <i>n_result</i> | Result of the operation. If <code>expt(0,0)</code> is specified, the value returned is 1.0, indicating no error. |
|-----------------|---|

Examples

```
expt (2 3)
=> 8

expt (-2 3)
=> -8

expt (3.3 2)
=> 10.89
```

Related Topics

[exp](#)

[Arithmetic Functions](#)

Cadence SKILL Language Reference

Arithmetic Functions

fix

```
fix(  
    n_arg  
)  
=> x_result
```

Description

Returns the largest integer not larger than the given argument.

If the given floating point argument *n_arg* is greater than the maximum integer value `INT_MAX`, a warning message displays and the `INT_MAX` value is returned. Similarly, if the floating point argument *n_arg* is less than the minimum integer value `INT_MIN`, a warning message displays and the `INT_MIN` value is returned. This function is equivalent to `floor`.

Arguments

| | |
|--------------|-------------|
| <i>n_arg</i> | Any number. |
|--------------|-------------|

Value Returned

| | |
|-----------------|---|
| <i>x_result</i> | The largest integer not greater than <i>n_arg</i> . If an integer is given as an argument, it returns the argument. |
|-----------------|---|

Examples

```
fix(1.9)  
=> 1  
  
fix(-5.6)  
=> -6  
  
fix(100)  
=> 100  
  
fix(4.1 * 100)  
=> 409  
  
fix(1.111111e10)  
*WARNING* (fix): Input value 11111110000.000000 is out of range. Using the maximum  
integer value allowed (2147483647) instead. Check your code to ensure that all input  
values and calculations have been correctly specified.  
=>2147483647  
  
fix(-1.1234e20)  
*WARNING* (fix): Input value -11234000000000000000.000000 is out of range. Using  
the minimum integer value allowed (-2147483648) instead. Check your code to ensure  
that all input values and calculations have been correctly specified.  
=>-2147483648
```

Related Topics

Type Conversion Functions (fix and float)

ceiling

fixp

floor

round

Arithmetic Functions

fixp

```
fixp(  
    g_value  
)  
=> t / nil
```

Description

Checks whether the specified object is an integer, that is, a fixed number.

The suffix `p` is usually added to the name of a function to indicate that it is a predicate function. This function is equivalent to `integerp`.

Arguments

| | |
|----------------|-------------------|
| <i>g_value</i> | Any SKILL object. |
|----------------|-------------------|

Value Returned

| | |
|------------|---|
| <i>t</i> | If <i>g_value</i> is an integer, a data type whose internal name is <code>fixnum</code> . |
| <i>nil</i> | If <i>g_value</i> is not an integer. |

Examples

```
fixp(3)  
=> t  
  
fixp(3.0)  
=> nil
```

Related Topics

[fix](#)

[fixp](#)

[floatp](#)

[round](#)

[integerp](#)

Cadence SKILL Language Reference

Arithmetic Functions

Arithmetic Functions

fix2

```
fix2(  
    n_value  
)  
=> x_result / nil
```

Description

This function is a version of the `fix` function that works for rounding issue in floating-point calculations. The function returns the largest integer not larger than the given argument.

Arguments

| | |
|----------------|-------------|
| <i>n_value</i> | Any number. |
|----------------|-------------|

Value Returned

| | |
|-----------------|---|
| <i>x_result</i> | Returns the largest integer not larger than the given argument. |
| <i>nil</i> | If <i>n_value</i> is not an integer. |

Examples

```
fix2(4.1 * 100)  
=> 410
```

Related Topics

[fix](#)

[float](#)

[floatp](#)

[integerp](#)

[“Comparing Floating-Point Numbers](#)

[Arithmetic Functions](#)

float

```
float(  
    n_arg  
)  
=> f_result
```

Description

Converts a number into its equivalent floating-point number.

Arguments

| | |
|--------------|---|
| <i>n_arg</i> | Integer to be converted to floating-point. If you give a floating-point number as an argument, it returns the argument unchanged. |
|--------------|---|

Value Returned

| | |
|-----------------|--------------------------|
| <i>f_result</i> | A floating-point number. |
|-----------------|--------------------------|

Examples

```
float(3)  
=> 3.0  
float(1.2)  
=> 1.2
```

Related Topics

[fix](#)

[fixp](#)

[floatp](#)

[Arithmetic Functions](#)

floatp

```
floatp(  
    g_value  
)  
=> t / nil
```

Description

Checks whether the specified object is a floating-point number. Same as `realp`.

The suffix `p` is usually added to the name of a function to indicate that it is a predicate function.

Arguments

| | |
|----------------|-------------------|
| <i>g_value</i> | Any SKILL object. |
|----------------|-------------------|

Value Returned

| | |
|------------------|--|
| <code>t</code> | If <i>g_value</i> is a floating-point number, a data type whose internal name is <code>flonum</code> . |
| <code>nil</code> | If <i>g_value</i> is not a floating-point number. |

Examples

```
floatp(3)  
=> nil  
floatp(3.0)  
=> t
```

Related Topics

[fix](#)

[fixp](#)

[floatp](#)

[realp](#)

[Arithmetic Functions](#)

floor

```
floor(  
    n_number  
)  
=> x_integer
```

Description

Returns the largest integer not larger than the given argument.

Arguments

| | |
|-----------------|-------------|
| <i>n_number</i> | Any number. |
|-----------------|-------------|

Value Returned

| | |
|------------------|---|
| <i>x_integer</i> | Largest integer not larger than <i>n_number</i> . |
|------------------|---|

Examples

```
(floor -4.3)  
=> -5  
(floor 3.5)  
=> 3
```

Related Topics

[ceiling](#)

[fix](#)

[round](#)

[truncate](#)

[Arithmetic Functions](#)

int

```
int(  
    g_value  
)  
=> x_result
```

Description

Rounds off the number value to the nearest integer. The `int` function works as an overloadable arithmetic operator adopted from DFII to the SKILL Core language. The argument (*g_value*) is specified on the number class (numberp arguments).

Arguments

| | |
|----------------|---|
| <i>g_value</i> | Specifies the number value you want to round off. |
|----------------|---|

Value Returned

| | |
|-----------------|---------------------|
| <i>x_result</i> | The nearest integer |
|-----------------|---------------------|

Examples

```
int(2.7)  
=>2  
int(.7)  
=>0
```

Related Topics

[Arithmetic Functions](#)

isInfinity

```
isInfinity(  
    f_flownum  
)  
=> t / nil
```

Description

Checks whether the given flownum argument represents infinity (positive or negative).

Arguments

| | |
|------------------|--------------------------|
| <i>f_flownum</i> | A floating-point number. |
|------------------|--------------------------|

Value Returned

| | |
|-----|---|
| t | If <i>f_flownum</i> is infinity (positive or negative). |
| nil | If <i>f_flownum</i> is not infinity (positive or negative). |

Examples

```
plus_inf = 2.0 * 1e999  
isInfinity (plus_inf)  
=> t  
  
isInfinity (987.65)  
=> nil
```

Related Topics

[Arithmetic Functions](#)

isNaN

```
isNan(  
    f_flownum  
)  
=> t / nil
```

Description

Checks whether the given flownum argument represents NaN (not-a-number). Else, it returns nil.

Arguments

| | |
|------------------|--------------------------|
| <i>f_flownum</i> | A floating-point number. |
|------------------|--------------------------|

Value Returned

| | |
|-----|---|
| t | If <i>f_flownum</i> is NaN. |
| nil | If <i>f_flownum</i> is a floating-point number. |

Examples

```
nan = 0.0 * 2.0 * 1e999  
isNan (nan)  
=> t  
  
isNan (123.456)  
=> nil
```

Related Topics

Arithmetic Functions

leftshift

```
leftshift(  
    x_val  
    x_num  
)  
=> x_result
```

Description

Returns the integer result of shifting a value a specified number of bits to the left. Prefix form of the << arithmetic operator. `leftshift` is logical (that is, vacated bits are 0-filled).

Arguments

| | |
|--------------|---|
| <i>x_val</i> | Value to be shifted. |
| <i>x_num</i> | Number of bits <i>x_val</i> is shifted. |

Value Returned

| | |
|-----------------|--------------------------|
| <i>x_result</i> | Result of the operation. |
|-----------------|--------------------------|

Examples

```
leftshift(7 2)  
=> 28  
  
leftshift(10 1)  
=> 20
```

Related Topics

[rightshift](#)

[Arithmetic Functions](#)

log

```
log (
    n_number
)
=> f_result
```

Description

Returns the natural logarithm of a floating-point number or integer.

Arguments

| | |
|-----------------|-----------------------------------|
| <i>n_number</i> | Floating-point number or integer. |
|-----------------|-----------------------------------|

Value Returned

| | |
|-----------------|--|
| <i>f_result</i> | Natural logarithm of the value passed in. If the value of <i>n_number</i> is not a positive number, an error is signaled. |
|-----------------|--|

Examples

```
log ( 3.0 )
=> 1.098612
```

Related Topics

[exp](#)

[sqrt](#)

[Arithmetic Functions](#)

log10

```
log10(  
    n_number  
)  
=> f_result
```

Description

Returns the base 10 logarithm of a floating-point number or integer.

Arguments

| | |
|-----------------|-----------------------------------|
| <i>n_number</i> | Floating-point number or integer. |
|-----------------|-----------------------------------|

Value Returned

| | |
|-----------------|---|
| <i>f_result</i> | Base 10 logarithm of the value passed in. |
|-----------------|---|

Examples

```
log10( 10.0 )  
=> 1.0  
  
log10( -20.0 )  
=> complex(1.30103, 1.36438)
```

Related Topics

[log](#)

[sqrt](#)

[Arithmetic Functions](#)

Cadence SKILL Language Reference

Arithmetic Functions

max

```
max (
    n_num1 [ n_num2 ... ]
)
=> n_result
```

Description

Returns the maximum of the values passed in. This function requires at least one argument.

Arguments

| | |
|---------------|-----------------------------|
| <i>n_num1</i> | First value to check. |
| <i>n_num2</i> | Additional values to check. |

Value Returned

| | |
|-----------------|----------------------------------|
| <i>n_result</i> | Maximum of the values passed in. |
|-----------------|----------------------------------|

Examples

```
max (6)
=> 6

max (3 2 1)
=> 3

max (-3 -2 -1)
=> -1
```

Related Topics

[abs](#)

[min](#)

[numberp](#)

[Arithmetic Functions](#)

min

```
min(  
    n_num1 [ n_num2 ... ]  
)  
=> n_result
```

Description

Returns the minimum of the values passed in. This function requires at least one argument.

Arguments

| | |
|---------------|-----------------------------|
| <i>n_num1</i> | First value to check. |
| <i>n_num2</i> | Additional values to check. |

Value Returned

| | |
|-----------------|----------------------------------|
| <i>n_result</i> | Minimum of the values passed in. |
|-----------------|----------------------------------|

Examples

```
min(3)  
=> 3  
  
min(1 2 3)  
=> 1  
  
min(-1 -2.0 -3)  
=> -3.0
```

Related Topics

[abs](#)

[max](#)

[numberp](#)

[Arithmetic Functions](#)

minus

```
minus(  
    n_op  
)  
=> n_result
```

Description

Returns the negative of a number. Prefix form of the – unary operator.

Arguments

| | |
|-------------|-----------|
| <i>n_op</i> | A number. |
|-------------|-----------|

Value Returned

| | |
|-----------------|-------------------------|
| <i>n_result</i> | Negative of the number. |
|-----------------|-------------------------|

Examples

```
minus( 10 )  
=> -10  
  
minus( -1.0 )  
=> 1.0  
  
minus( -0 )  
=> 0
```

Related Topics

[Arithmetic Functions](#)

minusp

```
minusp(  
    g_general  
)  
=> t / nil
```

Description

Checks if a value is a negative number. Same as `negativep`.

Arguments

| | |
|------------------|------------------|
| <i>g_general</i> | Number to check. |
|------------------|------------------|

Value Returned

| | |
|-----|---|
| t | If <i>g_general</i> is a negative number. |
| nil | If <i>g_general</i> is not a negative number. |

Examples

```
minusp( 3 )  
=> nil  
minusp( -3 )  
=> t
```

Related Topics

[evenp](#)

[negativep](#)

[numberp](#)

[oddp](#)

[onep](#)

[plusp](#)

[zerop](#)

mod

```
mod(  
    x_integer1  
    x_integer2  
)  
=> x_result
```

Description

Returns the integer remainder of dividing two integers. The remainder is either zero or has the sign of the dividend.

This function is equivalent to `remainder`.

Arguments

| | |
|-------------------|-----------|
| <i>x_integer1</i> | Dividend. |
| <i>x_integer2</i> | Divisor. |

Value Returned

| | |
|-----------------|--|
| <i>x_result</i> | Integer remainder of the division. The sign is determined by the dividend. |
|-----------------|--|

Examples

```
mod(4 3)  
=> 1
```

Related Topics

[modf](#)

[modulo](#)

modf

```
modf (  
    f_flonum1  
    f_flonum2  
)  
=> f_result
```

Description

Returns the floating-point remainder of the division of *f_flonum1* by *f_flonum2*.

Arguments

| | |
|------------------|-------------------------------------|
| <i>f_flonum1</i> | A floating-point number (Dividend). |
| <i>f_flonum2</i> | A floating-point number (Divisor). |

Value Returned

| | |
|-----------------|--|
| <i>f_result</i> | Floating-point remainder of the division. The sign is determined by the dividend. |
|-----------------|--|

Examples

```
;; Sign is determined by the dividend  
modf(-10.1 10.0)  
=> -0.1  
modf(10.1 -10.0)  
=> 0.1
```

Related Topics

[mod](#)

[modulo](#)

modulo

```
modulo(  
    x_integer1  
    x_integer2  
)  
=> x_integer
```

Description

Returns the remainder of dividing two integers. The remainder always has the sign of the divisor.

The `remainder (mod)` and `modulo` functions differ on negative arguments. The `remainder` is either zero or has the sign of the dividend if you use the `remainder` function. With `modulo` the return value always has the sign of the divisor.

Arguments

| | |
|-------------------|-----------|
| <i>x_integer1</i> | Dividend. |
| <i>x_integer2</i> | Divisor. |

Value Returned

| | |
|------------------|---|
| <i>x_integer</i> | The remainder of the division. The sign is determined by the divisor. |
|------------------|---|

Examples

```
modulo( 13 4)  
=> 1  
remainder( 13 4)  
=> 1
```

```
modulo( -13 4)  
=> 3  
remainder( -13 4)  
=> -1
```

```
modulo( 13 -4)  
=> -3  
remainder( 13 -4)  
=> 1
```

Cadence SKILL Language Reference

Arithmetic Functions

```
modulo( -13 -4)  
=> -1  
remainder( -13 -4)  
=> -1
```

Related Topics

[mod](#)

[modf](#)

[remainder](#)

nearlyEqual

```
nearlyEqual(  
    n_val1 n_val2  
    [ f_relTolerance [ f_absTolerance ] ]  
)  
=> t / nil
```

Description

Checks whether one value (*n_val1*) is approximately equal to another value (*n_val2*).

Arguments

| | |
|-----------------------------|--|
| <i>n_val1</i> <i>n_val2</i> | The values that need to be checked. |
| <i>f_relTolerance</i> | The relative tolerance or the amount of error allowed, relative to the larger absolute value of <i>n_val1</i> or <i>n_val2</i> . It must be greater than 0. The default tolerance is 1e-9, which ensures that the two values are the same within about 9 decimal digits. To set a tolerance of 5%, for example, the pass tolerance must be equal to 0.05. |
| <i>f_absTolerance</i> | The minimum absolute tolerance level that can be used for comparisons near zero. |

Value Returned

| | |
|-----|--|
| t | <i>n_val1</i> is nearly equal to <i>n_val2</i> . |
| nil | <i>n_val1</i> is not equal to <i>n_val2</i> . |

Examples

```
;; nearlyEqual check at 0.1% relative tolerance  
relativeTolerance = 0.001  
Val1 = 17.00  
Val2 = 17.01  
nearlyEqual(val1 val2 relativeTolerance)  
=> t  
nearlyEqual(val2 val1 relativeTolerance)  
=> t
```

[illegible]eqequaleqv

negativep

```
negativep(  
    n_num  
)  
=> t / nil
```

Description

Checks whether the specified value is a negative number. Same as `minusp`.

Arguments

| | |
|--------------|------------------|
| <i>n_num</i> | Number to check. |
|--------------|------------------|

Value Returned

| | |
|------------------|--|
| <code>t</code> | <i>n_num</i> is a negative number. |
| <code>nil</code> | <i>n_num</i> is not a negative number. |

Examples

```
negativep( 3 )  
=> nil  
negativep( -3 )  
=> t
```

Related Topics

[evenp](#)

[minusp](#)

[numberp](#)

[oddp](#)

[onep](#)

[plusp](#)

[zerop](#)

oddp

```
oddp(  
    g_value  
)  
=> t / nil
```

Description

Checks whether an object is an odd integer. `oddp` is a predicate function.

Arguments

| | |
|----------------|------------------------------------|
| <i>g_value</i> | A SKILL object that is an integer. |
|----------------|------------------------------------|

Value Returned

| | |
|------------------|--|
| <code>t</code> | If <i>g_value</i> is an odd integer. |
| <code>nil</code> | If <i>g_value</i> is not an odd integer. |

Examples

```
oddp( 7 )  
=> t  
  
oddp( 8 )  
=> nil
```

Related Topics

[evenp](#)

[fixp](#)

[integerp](#)

[minusp](#)

[onep](#)

[plusp](#)

[zerop](#)

onep

```
onep(  
    g_value  
)  
=> t / nil
```

Description

Checks whether the given object is equal to one. `onep` is a predicate function.

Arguments

| | |
|----------------|--|
| <i>g_value</i> | A SKILL object that is either a floating-point number or an integer. |
|----------------|--|

Value Returned

| | |
|-----|--|
| t | If <i>g_value</i> is equal to one. |
| nil | If <i>g_value</i> is not equal to one. |

Examples

```
onep( 1 )  
=> t  
  
onep( 7 )  
=> nil  
  
onep( 1.0 )  
=> t
```

Related Topics

[evenp](#)

[minusp](#)

[numberp](#)

[plusp](#)

[zerop](#)

plus

```
plus(  
    n_op1  
    n_op2  
    [ n_op3 ... ]  
)  
=> n_result
```

Description

Returns the result of adding one or more operands to the first operand. Prefix form of the + arithmetic operator.

Arguments

| | |
|--------------|--|
| <i>n_op1</i> | First number to be added. |
| <i>n_op2</i> | Second number to be added. |
| <i>n_op3</i> | Optional additional numbers to be added. |

Value Returned

| | |
|-----------------|---------------------|
| <i>n_result</i> | Sum of the numbers. |
|-----------------|---------------------|

Examples

```
plus(5 4 3 2 1)  
=> 15  
  
plus(-12 -13)  
=> -25  
  
plus(12.2 13.3)  
=> 25.5
```

Related Topics

[xplus](#)

plusp

```
plusp(  
    g_value  
)  
=> t / nil
```

Description

Checks whether the given object is a positive number.

`plusp` is a predicate function.

Arguments

| | |
|----------------|--|
| <i>g_value</i> | A SKILL object that is either a floating-point number or an integer. |
|----------------|--|

Value Returned

| | |
|------------------|---|
| <code>t</code> | If <i>g_value</i> is a positive number. |
| <code>nil</code> | If <i>g_value</i> is not a positive number. |

Examples

```
plusp( -209.623472)  
=> nil  
  
plusp( 209.623472)  
=> t
```

Related Topics

[evenp](#)

[minusp](#)

[oddp](#)

[onep](#)

[zerop](#)

quotient

```
quotient(  
    n_op1  
    n_op2  
    [ n_op3 ... ]  
)  
=> n_result
```

Description

Returns the result of dividing the first operand by one or more operands. Prefix form of the / arithmetic operator.

Arguments

| | |
|--------------|--|
| <i>n_op1</i> | Dividend. |
| <i>n_op2</i> | Divisor. |
| <i>n_op3</i> | Optional additional divisors for multiple divisions. |

Value Returned

| | |
|-----------------|--------------------------|
| <i>n_result</i> | Result of the operation. |
|-----------------|--------------------------|

Examples

```
quotient(5 4 3 2 1)  
=> 0  
  
quotient(-10 -2)  
=> 5  
  
quotient(10.8 -2.2)  
=> -4.909091
```

Related Topics

[xquotient](#)

random

```
random(  
    [ x_number ]  
)  
=> x_result
```

Description

Returns a random integer between zero and a given number minus one.

If you call `random` with no arguments, it returns an integer that has all of its bits randomly set.

Arguments

| | |
|-----------------|-------------|
| <i>x_number</i> | An integer. |
|-----------------|-------------|

Value Returned

| | |
|-----------------|--|
| <i>x_result</i> | Random integer between zero and <i>x_number</i> minus one. |
|-----------------|--|

Examples

```
random( 93 )  
=> 26  
random()  
=> 2078917053
```

Related Topics

[srandom](#)

realp

```
realp(  
    g_obj  
)  
=> t / nil
```

Description

Checks whether the specified value is a real number. Same as `floatp`.

Arguments

| | |
|--------------|-------------------|
| <i>g_obj</i> | Any SKILL object. |
|--------------|-------------------|

Value Returned

| | |
|-----|--------------------------------|
| t | Argument is a real number. |
| nil | Argument is not a real number. |

Examples

```
realp( 2789987)  
=> nil  
  
realp( 2789.987)  
=> t
```

Related Topics

[floatp](#)

[integerp](#)

[fixp](#)

remainder

```
remainder(  
    x_integer1  
    x_integer2  
)  
=> x_integer
```

Description

Returns the remainder of dividing two integers. The remainder is either zero or has the sign of the dividend. Same as `mod`.

The `remainder` and `modulo` functions differ on negative arguments. The remainder is either zero or has the sign of the dividend if you use the `remainder` function. With `modulo` the return value always has the sign of the divisor.

Arguments

| | |
|-------------------|-----------|
| <i>x_integer1</i> | Dividend. |
| <i>x_integer2</i> | Divisor. |

Value Returned

| | |
|------------------|--|
| <i>x_integer</i> | Remainder of dividing <i>x_integer1</i> by <i>x_integer2</i> . The sign is determined by the sign of <i>x_integer1</i> . |
|------------------|--|

Examples

```
modulo( 13 4)  
=> 1  
remainder( 13 4)  
=> 1  
  
modulo( -13 4)  
=> 3  
remainder( -13 4)  
=> -1  
  
modulo( 13 -4)  
=> -3  
remainder( 13 -4)  
=> 1  
  
modulo( -13 -4)  
=> -1  
remainder( -13 -4)  
=> -1
```

Related Topics

modulo

rightshift

```
rightshift(  
    x_val  
    x_num  
)  
=> x_result
```

Description

Returns the integer result of shifting a value a specified number of bits to the right. Prefix form of the >> arithmetic operator. `rightshift` is logical (that is, vacated bits are 0-filled).

Arguments

| | |
|--------------|---|
| <i>x_val</i> | Value to be shifted. |
| <i>x_num</i> | Number of bits <i>x_val</i> is shifted. |

Value Returned

| | |
|-----------------|--------------------------|
| <i>x_result</i> | Result of the operation. |
|-----------------|--------------------------|

Examples

```
rightshift(7 2)  
=> 1  
rightshift(10 1)  
=> 5
```

Related Topics

[leftshift](#)

round

```
round(  
    n_arg  
)  
=> x_result
```

Description

Rounds a floating-point number to its closest integer value. If the given floating point argument *n_arg* is greater than the maximum integer value `INT_MAX`, a warning message displays and the `INT_MAX` value is returned. Similarly, if the floating point argument *n_arg* is less than the minimum integer value `INT_MIN`, a warning message displays and the `INT_MIN` value is returned.

Arguments

| | |
|--------------|------------------------|
| <i>n_arg</i> | Floating-point number. |
|--------------|------------------------|

Value Returned

| | |
|-----------------|--|
| <i>x_result</i> | Integer whose value is closest to <i>n_arg</i> . |
|-----------------|--|

Examples

```
round(1.5)  
=> 2  
round(-1.49)  
=> -1  
round(1.49)  
=> 1  
  
round(1.111111e10)  
=>2147483647  
round(-1.1234e20)  
=>-2147483648
```

Related Topics

[fix](#)

[float](#)

round2

```
round2(  
    n_arg  
)  
=> x_result
```

Description

This function is a version of the `round` function that rounds the result in floating-point calculations to its closest integer value.

Arguments

| | |
|--------------|--------------------------|
| <i>n_arg</i> | A floating-point number. |
|--------------|--------------------------|

Value Returned

| | |
|-----------------|--|
| <i>x_result</i> | Integer whose value is closest to <i>n_arg</i> . |
|-----------------|--|

Examples

```
val=-0.2865  
round(val/0.001)*0.001  
=> -0.286  
round2(val/0.001)*0.001  
=> -0.287
```

Related Topics

Type Conversion Functions (fix and float)

sort

```
sort(  
    l_data  
    u_comparefn  
)  
=> l_result
```

Description

Sorts a list according to the specified comparison function. By default, the sort function uses `alphalessp`, which defaults to an alphabetical sort when `u_comparefn` is `nil`. This function does not create a new list. It returns the altered input list. This is a destructive operation. The `l_data` list is modified in place and no new storage is allocated. Pointers previously pointing to `l_data` may not be pointing at the head of the sorted list.

Sorts the list `l_data` according to the sort function `u_comparefn`. `u_comparefn(g_x g_y)` returns non-`nil` if `g_x` can precede `g_y` in sorted order, `nil` if `g_y` must precede `g_x`. If `u_comparefn` is `nil`, alphabetical order is used. The algorithm currently implemented in `sort` is based on recursive merge sort.



Caution

The `l_data` list is modified in place and no new storage is allocated. Pointers previously pointing to `l_data` may not be pointing at the head of the sorted list.

Arguments

| | |
|--------------------------|---|
| <code>l_data</code> | List of objects to be sorted. |
| <code>u_comparefn</code> | Comparison function to determine which of any two elements should come first. |

Value Returned

| | |
|-----------------------|--|
| <code>l_result</code> | <code>l_data</code> sorted by the comparison function <code>u_comparefn</code> . |
|-----------------------|--|

Examples

```
a = list( 3 -1 8 2 )  
sort( a lambda((x y) lessp( x y))) => (-1 2 3 8)
```

Cadence SKILL Language Reference

Arithmetic Functions

The following examples demonstrate the use of second argument as `nil`. In this case, `sort` would expect the data to be sorted as either a list of symbol or strings.

```
y = '(c a d b)
(sort y nil)
=> (a b c d)

y
=> (c d) ;no longer points to head of list
y = '(c a d b)
y = (sort y nil)
=> (a b c d)

y
=> (a b c d) ;reassignment points y to sorted list.
```

The following example demonstrates how to use a non-trivial sort function.

```
cells=list("b" "a" "d" "c")
data=makeTable("Data" -1)
data["a"]=0
data["b"]=1
data["c"]=2
data["d"]=3
cells=sort(cells lambda((x y) lessp(data[x] data[y])))
=> ("a" "b" "c" "d")
```

Related Topics

[lessp](#)

[sortcar](#)

sortcar

```
sortcar(  
    l_data  
    u_comparefn  
)  
=> l_result
```

Description

Similar to `sort` except that only the `car` of each element in a list is used for comparison by the sort function. This function does not create a new list. It returns the altered input list.

This function also sorts `l_data` based on the function `u_comparefn`.



The `l_data` list is modified in place and no new storage is allocated. Pointers previously pointing to `l_data` might not be pointing at the head of the sorted list.

Arguments

| | |
|--------------------------|---|
| <code>l_data</code> | List of objects to be sorted. |
| <code>u_comparefn</code> | Comparison function to determine which of any two elements should come first. |

Value Returned

| | |
|-----------------------|--|
| <code>l_result</code> | <code>l_data</code> sorted by the comparison function <code>u_comparefn</code> . |
|-----------------------|--|

Examples

```
sortcar( '((4 four) (3 three) (2 two)) 'lessp )  
=> ((2 two) (3 three) (4 four))  
  
sortcar( '((d 4) (b 2) (c 3) (a 1)) nil )  
=> ((a 1) (b 2) (c 3) (d 4))  
  
myList = list(' (2 two) ' (4 four) ' (1 one) ' (3 three))  
newList = sortcar( copy(myList) 'lessp )  
newList = ((1 one) (2 two) (3 three) (4 four))  
myList = ((2 two) (4 four) (1 one) (3 three)) ;; not changed !!
```

Related Topics

sort

Cadence SKILL Language Reference

Arithmetic Functions

sqrt

```
sqrt(  
    n_number  
)  
=> f_result
```

Description

Returns the square root of a floating-point number or integer.

Arguments

| | |
|-----------------|-----------------------------------|
| <i>n_number</i> | Floating-point number or integer. |
|-----------------|-----------------------------------|

Value Returned

| | |
|-----------------|---|
| <i>f_result</i> | Square root of the value passed in. If the value of <i>n_number</i> is not a positive number, an error is signaled. |
|-----------------|---|

Examples

```
sqrt( 49 )  
=> 7.0  
  
sqrt( 43942 )  
=> 209.6235
```

srandom

```
srandom(  
    x_number  
)  
=> t
```

Description

Sets the seed of the random number generator to a given number.

Arguments

| | |
|-----------------|-------------|
| <i>x_number</i> | An integer. |
|-----------------|-------------|

Value Returned

| | |
|---|---------|
| t | Always. |
|---|---------|

Examples

```
srandom( 89 )  
=> t
```

Related Topics

[random](#)

sub1

```
sub1(  
    n_number  
)  
=> n_result
```

Description

Subtracts one from a floating-point number or integer.

Arguments

| | |
|-----------------|-----------------------------------|
| <i>n_number</i> | Floating-point number or integer. |
|-----------------|-----------------------------------|

Value Returned

| | |
|-----------------|----------------------------|
| <i>n_result</i> | <i>n_number</i> minus one. |
|-----------------|----------------------------|

Examples

```
sub1( 59 )  
=> 58  
sub1(-59.0)  
=> -60.0  
sub1(59.0)  
=> 58.0
```

Related Topics

[add1](#)

times

```
times(  
    n_op1  
    n_op2  
    [ n_op3 ... ]  
)  
=> n_result
```

Description

Returns the result of multiplying the first operand by one or more operands. Prefix form of the * arithmetic operator.

Arguments

| | |
|--------------|--|
| <i>n_op1</i> | First operand to be multiplied. |
| <i>n_op2</i> | Second operand to be multiplied. |
| <i>n_op3</i> | Optional additional operands to be multiplied. |

Value Returned

| | |
|-----------------|-------------------------------|
| <i>n_result</i> | Result of the multiplication. |
|-----------------|-------------------------------|

Examples

```
times(5 4 3 2 1)  
=> 120  
  
times(-12 -13)  
=> 156  
  
times(12.2 -13.3)  
=> -162.26
```

Related Topics

[xtimes](#)

truncate

```
truncate(  
    n_number  
)  
=> x_integer
```

Description

Truncates a given number to an integer.

Arguments

n_number Any SKILL number.

Value Returned

x_integer *n_number* truncated to an integer.

Examples

```
truncate( 1234.567)  
=> 1234  
round( 1234.567)  
=> 1235  
truncate( -1.7)  
=> -1
```

Related Topics

[ceiling](#)

[floor](#)

[round](#)

xdifference

```
xdifference(  
    x_op1  
    x_op2  
    [ x_opt3 ]  
)  
=> x_result
```

Description

Returns the integer result of subtracting one or more operands from the first operand. `xdifference` is an integer-only arithmetic function while `difference` can handle integers and floating-point numbers. `xdifference` runs slightly faster than `difference` in integer arithmetic calculation.

Arguments

| | |
|---------------------|---|
| <code>x_op1</code> | Operand from which one or more operands are subtracted. |
| <code>x_op2</code> | Operand to be subtracted. |
| <code>x_opt3</code> | Optional additional operands to be subtracted. |

Value Returned

| | |
|-----------------------|----------------------------|
| <code>x_result</code> | Result of the subtraction. |
|-----------------------|----------------------------|

Examples

```
xdifference(12 13)  
=> -1  
xdifference(-12 13)  
=> -25
```

Related Topics

[difference](#)

xplus

```
xplus(  
    x_op1  
    x_op2  
    [ x_opt3 ]  
)  
=> x_result
```

Description

Returns the integer result of adding one or more operands to the first operand. `xplus` is an integer-only arithmetic function while `plus` can handle integers and floating-point numbers. `xplus` runs slightly faster than `plus` in integer arithmetic calculation.

Arguments

| | |
|---------------------|---|
| <code>x_op1</code> | First operand to be added. |
| <code>x_op2</code> | Second operand to be added. |
| <code>x_opt3</code> | Optional additional operands to be added. |

Value Returned

| | |
|-----------------------|-------------------------|
| <code>x_result</code> | Result of the addition. |
|-----------------------|-------------------------|

Examples

```
xplus(12 13)  
=> 25  
  
xplus(-12 -13)  
=> -25
```

Related Topics

[plus](#)

xquotient

```
xquotient(  
    x_op1  
    x_op2  
    [ x_opt3 ]  
)  
=> x_result
```

Description

Returns the integer result of dividing the first operand by one or more operands. `xquotient` is an integer-only arithmetic function while `quotient` can handle integers and floating-point numbers. `xquotient` runs slightly faster than `quotient` in integer arithmetic calculation.

Arguments

| | |
|---------------------|-------------------------------|
| <code>x_op1</code> | Dividend. |
| <code>x_op2</code> | Divisor. |
| <code>x_opt3</code> | Optional additional divisors. |

Value Returned

| | |
|-----------------------|-------------------------|
| <code>x_result</code> | Result of the division. |
|-----------------------|-------------------------|

Examples

```
xquotient(10 2)  
=> 5  
  
xquotient(-10 -2)  
=> 5
```

Related Topics

[quotient](#)

xtimes

```
xtimes(  
    x_op1  
    x_op2  
    [ x_opt3 ]  
)  
=> x_result
```

Description

Returns the integer result of multiplying the first operand by one or more operands. `xtimes` is an integer-only arithmetic function while `times` can handle integers and floating-point numbers. `xtimes` runs slightly faster than `times` in integer arithmetic calculation.

Arguments

| | |
|---------------|--|
| <i>x_op1</i> | First operand to be multiplied. |
| <i>x_op2</i> | Second operand to be multiplied. |
| <i>x_opt3</i> | Optional additional operands to be multiplied. |

Value Returned

| | |
|-----------------|-------------------------------|
| <i>x_result</i> | Result of the multiplication. |
|-----------------|-------------------------------|

Examples

```
xtimes(12 13)  
=> 156  
  
xtimes(-12 -13)  
=> 156
```

zerop

```
zerop(  
    g_value  
)  
=> t / nil
```

Description

Checks whether the specified object is equal to zero. `zerop` is a predicate function.

Arguments

| | |
|----------------|--|
| <i>g_value</i> | A SKILL object that is either a floating-point number or an integer. |
|----------------|--|

Value Returned

| | |
|------------------|---|
| <code>t</code> | If <i>g_value</i> is equal to zero. |
| <code>nil</code> | If <i>g_value</i> is not equal to zero. |

Examples

```
zerop( 0 )  
=> t  
  
zerop( 7 )  
=> nil
```

Related Topics

[evenp](#)

[minusp](#)

[oddp](#)

[onep](#)

[plusp](#)

zxt

```
zxt(  
    x_number  
    x_bits  
)  
=> x_result
```

Description

Zero-extends the number represented by the rightmost specified number of bits in the given integer.

Zero-extends the rightmost *x_bits* bits of *x_number*. Executes faster than doing *x_number*<*x_bits* - 1:0>.

Arguments

| | |
|-----------------|-----------------|
| <i>x_number</i> | An integer. |
| <i>x_bits</i> | Number of bits. |

Value Returned

| | |
|-----------------|---|
| <i>x_result</i> | <i>x_number</i> with the rightmost <i>x_bits</i> zero-extended. |
|-----------------|---|

Examples

```
zxt( 8 3 )  
=> 0  
  
zxt( 10 2 )  
=> 2
```

Cadence SKILL Language Reference

Arithmetic Functions

Bitwise Operator Functions

The `bnot`, `band`, `band`, `bxor`, `bxnor`, `bor`, and `bnor` operators all perform bitwise logical operations on their integer arguments.

The following is a list of bitwise operator functions.

| | | |
|----------------------------------|-----------------------------------|-------------------------------|
| <u><code>band</code></u> | <u><code>bitfield</code></u> | <u><code>bitfield1</code></u> |
| <u><code>band</code></u> | <u><code>bnor</code></u> | <u><code>bnot</code></u> |
| <u><code>bor</code></u> | <u><code>bxnor</code></u> | <u><code>bxor</code></u> |
| <u><code>setqbitfield</code></u> | <u><code>setqbitfield1</code></u> | |

band

```
band(  
    x_op1  
    x_op2  
    [ x_op3 ... ]  
)  
=> x_result
```

Description

Returns the integer result of the Boolean AND operation on each parallel pair of bits in each operand. Prefix form of the & bitwise operator.

Arguments

| | |
|--------------|---|
| <i>x_op1</i> | Operand to be evaluated. |
| <i>x_op2</i> | Operand to be evaluated. |
| <i>x_op3</i> | Optional additional operands to be evaluated. |

Value Returned

| | |
|-----------------|--------------------------|
| <i>x_result</i> | Result of the operation. |
|-----------------|--------------------------|

Examples

```
band(12 13)  
=> 12  
band(1 2 3 4 5)  
=> 0
```

Related Topics

[bnot](#)

[bnot](#)

bitfield

```
bitfield(  
    x_val  
    x_msb  
    x_lsb  
)  
=> x_result
```

Description

Returns the value of a specified set of bits of a specified integer. Prefix form of the < : > operator.

Arguments

| | |
|--------------|---|
| <i>x_val</i> | Integer for which you want to extract the value of a specified set of bits. |
| <i>x_msb</i> | Leftmost bit of the set of bits to be extracted. |
| <i>x_lsb</i> | Rightmost bit of the set of bits to be extracted. |

Value Returned

| | |
|-----------------|---------------------------|
| <i>x_result</i> | Value of the set of bits. |
|-----------------|---------------------------|

Examples

```
x = 0b1011  
bitfield(x 2 0)  
=> 3  
bitfield(x 3 0)  
=> 11
```

Related Topics

[setqbitfield1](#)

bitfield1

```
bitfield1(  
    x_val  
    x_bitPosition  
)  
=> x_result
```

Description

Returns the value of a specified bit of a specified integer. Prefix form of the <> operator.

Arguments

| | |
|----------------------|---|
| <i>x_val</i> | Integer for which you want to extract the value of a specified bit. |
| <i>x_bitPosition</i> | Position of the bit whose value you want to extract. |

Value Returned

| | |
|-----------------|------------------------|
| <i>x_result</i> | Value of a single bit. |
|-----------------|------------------------|

Examples

```
x = 0b1001  
bitfield1(x 0)  
=> 1  
bitfield1(x 3)  
=> 1
```

Related Topics

[bitfield](#)

[setqbitfield1](#)

Cadence SKILL Language Reference

Bitwise Operator Functions

bnand

```
bnand(  
    x_op1  
    x_op2  
    [ x_op3 ... ]  
)  
=> x_result
```

Description

Returns the integer result of the Boolean NAND operation on each parallel pair of bits in each operand. Prefix form of the ~& bitwise operator.

Arguments

| | |
|--------------|---|
| <i>x_op1</i> | Operand to be evaluated. |
| <i>x_op2</i> | Operand to be evaluated. |
| <i>x_op3</i> | Optional additional operands to be evaluated. |

Value Returned

| | |
|-----------------|--------------------------|
| <i>x_result</i> | Result of the operation. |
|-----------------|--------------------------|

Examples

```
bnand(12 13)  
=> -13  
bnand(1 2 3 4 5)  
=> -1
```

Related Topics

[band](#)

[bnor](#)

[bnot](#)

bnor

```
bnor(  
    x_op1  
    x_op2  
    [ x_op3 ... ]  
)  
=> x_result
```

Description

Returns the integer result of the Boolean NOR operation on each parallel pair of bits in each operand. Prefix form of the ~| bitwise operator.

Arguments

| | |
|--------------|---|
| <i>x_op1</i> | Operand to be evaluated. |
| <i>x_op2</i> | Operand to be evaluated. |
| <i>x_op3</i> | Optional additional operands to be evaluated. |

Value Returned

| | |
|-----------------|--------------------------|
| <i>x_result</i> | Result of the operation. |
|-----------------|--------------------------|

Examples

```
bnor(12 13)  
=> -14  
bnor(1 2 3 4 5)  
=> -8
```

Related Topics

[band](#)

[bnot](#)

bnot

```
bnot (  
    x_op  
)  
=> x_result
```

Description

Returns the integer result of the Boolean NOT operation on each parallel pair of bits in each operand. Prefix form of the ~ (one's complement) unary operator.

Arguments

| | |
|-------------|--------------------------|
| <i>x_op</i> | Operand to be evaluated. |
|-------------|--------------------------|

Value Returned

| | |
|-----------------|--------------------------|
| <i>x_result</i> | Result of the operation. |
|-----------------|--------------------------|

Examples

```
bnot (12)  
=> -13  
bnot (-12)  
=> 11
```

Related Topics

[band](#)

[bnor](#)

bor

```
bor(  
    x_op1  
    x_op2  
    [ x_op3 ... ]  
)  
=> x_result
```

Description

Returns the integer result of the Boolean OR operation on each parallel pair of bits in each operand. Prefix form of the | bitwise operator.

Arguments

| | |
|--------------|---|
| <i>x_op1</i> | Operand to be evaluated. |
| <i>x_op2</i> | Operand to be evaluated. |
| <i>x_op3</i> | Optional additional operands to be evaluated. |

Value Returned

| | |
|-----------------|--------------------------|
| <i>x_result</i> | Result of the operation. |
|-----------------|--------------------------|

Examples

```
bor(12 13)  
=> 13  
bor(1 2 3 4 5)  
=> 7
```

Related Topics

[band](#)

[bnot](#)

[bnot](#)

bxnor

```
bxnor(  
    x_op1  
    x_op2  
    [ x_op3 ... ]  
)  
=> x_result
```

Description

Returns the integer result of the Boolean XNOR operation on each parallel pair of bits in each operand. Prefix form of the \sim^{\wedge} bitwise operator.

Arguments

| | |
|--------------|---|
| <i>x_op1</i> | Operand to be evaluated. |
| <i>x_op2</i> | Operand to be evaluated. |
| <i>x_op3</i> | Optional additional operands to be evaluated. |

Value Returned

| | |
|-----------------|--------------------------|
| <i>x_result</i> | Result of the operation. |
|-----------------|--------------------------|

Examples

```
bxnor(12 13)  
=> -2  
bxnor(1 2 3 4 5)  
=> -2
```

Related Topics

[band](#)

[bnor](#)

[bnot](#)

bxor

```
bxor(  
    x_op1  
    x_op2  
    [ x_op3 ... ]  
)  
=> x_result
```

Description

Returns the integer result of the Boolean XOR operation on each parallel pair of bits in each operand. Prefix form of the ^ bitwise operator.

Arguments

| | |
|--------------|---|
| <i>x_op1</i> | Operand to be evaluated. |
| <i>x_op2</i> | Operand to be evaluated. |
| <i>x_op3</i> | Optional additional operands to be evaluated. |

Value Returned

| | |
|-----------------|--------------------------|
| <i>x_result</i> | Result of the operation. |
|-----------------|--------------------------|

Examples

```
bxor(12 13)  
=> 1  
bxor(1 2 3 4 5)  
=> 1
```

Related Topics

[band](#)

[bnor](#)

[bnot](#)

setqbitfield

```
setqbitfield(  
    s_var  
    x_val  
    x_msb  
    x_lsb  
)  
=> x_result
```

Description

Sets a value into a set of bits in the bit field specified by the variable *s_var*, stores the new value back into the variable, and then returns the new value. Prefix form of the < : >= operator.

Arguments

| | |
|--------------|---|
| <i>s_var</i> | Variable representing the bit field whose value is to be changed. |
| <i>x_val</i> | New value of the bit. |
| <i>x_msb</i> | Leftmost bit of the set of bits whose value is to be changed. |
| <i>x_lsb</i> | Rightmost bit of the set of bits whose value is to be changed. |

Value Returned

| | |
|-----------------|-----------------------------|
| <i>x_result</i> | New value of <i>s_var</i> . |
|-----------------|-----------------------------|

Examples

```
x = 0  
setqbitfield(x 0b1001 3 0)  
=> 9  
x => 9  
setqbitfield(x 1 2 1)  
=> 11  
x => 11  
setqbitfield(x 0 3 2)  
=> 3  
x => 3
```

Related Topics

[bitfield](#)

Cadence SKILL Language Reference

Bitwise Operator Functions

setqbitfield1

setqbitfield1

```
setqbitfield1(  
    s_var  
    x_val  
    x_bitPosition  
)  
=> x_result
```

Description

Sets a value into a single bit in the bit field specified by the variable *s_var*, stores the new value back into the variable, and then returns the new value. Prefix form of the <>= operator.

Arguments

| | |
|----------------------|---|
| <i>s_var</i> | Variable representing the bit field whose value is to be changed. |
| <i>x_val</i> | New value of the bit. |
| <i>x_bitPosition</i> | Position of the bit whose value you are changing. |

Value Returned

| | |
|-----------------|-----------------------------|
| <i>x_result</i> | New value of <i>s_var</i> . |
|-----------------|-----------------------------|

Examples

```
x = 0b1001  
setqbitfield1(x 1 1)  
=> 11  
x => 11  
setqbitfield1(x 1 2)  
=> 15  
x => 15
```

Related Topics

[bitfield](#)

Cadence SKILL Language Reference

Bitwise Operator Functions

Trigonometric Functions

The following is a list of trigonometric related SKILL functions.

acos

asin

atan

atan2

cos

sin

tan

Cadence SKILL Language Reference

Trigonometric Functions

acos

```
acos(  
    n_number  
)  
=> f_result
```

Description

Returns the arc cosine of a floating-point number or integer.

Arguments

| | |
|-----------------|-----------------------------------|
| <i>n_number</i> | Floating-point number or integer. |
|-----------------|-----------------------------------|

Value Returned

| | |
|-----------------|---------------------------------|
| <i>f_result</i> | Arc cosine of <i>n_number</i> . |
|-----------------|---------------------------------|

Examples

```
acos(0.3)  
=> 1.266104
```

Related Topics

[Trigonometric Functions](#)

[cos](#)

asin

```
asin(  
    n_number  
)  
=> f_result
```

Description

Returns the arc sine of a floating-point number or integer.

Arguments

| | |
|-----------------|-----------------------------------|
| <i>n_number</i> | Floating-point number or integer. |
|-----------------|-----------------------------------|

Value Returned

| | |
|-----------------|----------------------------------|
| <i>f_result</i> | Arc sine of the value passed in. |
|-----------------|----------------------------------|

Examples

```
asin(0.3)  
=> 0.3046927
```

Related Topics

[Trigonometric Functions](#)

[sin](#)

atan

```
atan(  
    n_number  
)  
=> f_result
```

Description

Returns the arc tangent of a floating-point number or integer.

Arguments

| | |
|-----------------|-----------------------------------|
| <i>n_number</i> | Floating-point number or integer. |
|-----------------|-----------------------------------|

Value Returned

| | |
|-----------------|----------------------------------|
| <i>f_result</i> | Arc tangent of <i>n_number</i> . |
|-----------------|----------------------------------|

Examples

```
atan(0.3)  
=> 0.2914568
```

Related Topics

Trigonometric Functions

atan2

Cadence SKILL Language Reference

Trigonometric Functions

atan2

```
atan2(  
    n_y  
    n_x  
)  
=> f_result
```

Description

Computes the principal value of the arc tangent of n_y/n_x , using the signs of both arguments to determine the quadrant of the return value.

Arguments

| | |
|------------|---|
| <i>n_y</i> | Vertical coordinate value. |
| <i>n_x</i> | Horizontal coordinate value. |
| | n_y/n_x is the tangent of the required angle. |

Value Returned

| | |
|-----------------|---|
| <i>f_result</i> | Arc tangent of y/x in the range $[-\pi, \pi]$ radians. If both arguments are 0.0, 0.0 is returned. If x or y is NaN, NaN is returned. In IEEE754 mode, <code>atan2()</code> handles the following exceptional arguments according to ANSI/IEEE Std 754-1985: <code>atan2(+0, x)</code> returns +0 for $x > 0$ or $x = +0$ <code>atan2(+0, x)</code> returns $+\pi$ for $x < 0$ or $x = -0$ <code>atan2(y, +0)</code> returns $\pi/2$ for $y > 0$ <code>atan2(y, +0)</code> returns $-\pi/2$ for $y < 0$ <code>atan2(+y, Inf)</code> returns +0 for finite $y > 0$ <code>atan2(+Inf, x)</code> returns $+\pi/2$ for finite x <code>atan2(+y, -Inf)</code> returns $+\pi$ for finite $y > 0$ <code>atan2(+Inf, Inf)</code> returns $+\pi/4$ <code>atan2(+Inf, -Inf)</code> returns $+3\pi/4$ |
|-----------------|---|

Examples

```
atan2(1 1)  
=> 0.7853982  
atan2(0 0)
```

Cadence SKILL Language Reference

Trigonometric Functions

=> 0.0

Related Topics

Trigonometric Functions

atan

Cadence SKILL Language Reference

Trigonometric Functions

COS

```
cos (  
    n_number  
)  
=> f_result
```

Description

Returns the cosine of a floating-point number or integer.

Arguments

| | |
|-----------------|-----------------------------------|
| <i>n_number</i> | Floating-point number or integer. |
|-----------------|-----------------------------------|

Value Returned

| | |
|-----------------|-----------------------------|
| <i>f_result</i> | Cosine of <i>n_number</i> . |
|-----------------|-----------------------------|

Examples

```
cos (0.3)  
=> 0.9553365  
cos (3.14/2)  
=> 0.0007963
```

Related Topics

[Trigonometric Functions](#)

[acos](#)

sin

```
sin(  
    n_number  
)  
=> f_result
```

Description

Returns the sine of a floating-point number or integer.

Arguments

| | |
|-----------------|-----------------------------------|
| <i>n_number</i> | Floating-point number or integer. |
|-----------------|-----------------------------------|

Value Returned

| | |
|-----------------|---------------------------|
| <i>f_result</i> | Sine of <i>n_number</i> . |
|-----------------|---------------------------|

Examples

```
sin(3.14/2)  
=> 0.9999997  
sin(3.14159/2)  
=> 1.0
```

Floating point results from evaluating the same expressions may be machine dependent.

Related Topics

Trigonometric Functions

asin

tan

```
tan(  
    n_number  
)  
=> f_result
```

Description

Returns the tangent of a floating-point number or integer.

Arguments

| | |
|-----------------|-----------------------------------|
| <i>n_number</i> | Floating-point number or integer. |
|-----------------|-----------------------------------|

Value Returned

| | |
|-----------------|------------------------------|
| <i>f_result</i> | Tangent of <i>n_number</i> . |
|-----------------|------------------------------|

Examples

```
tan( 3.0 )  
=> -0.1425465
```

Related Topics

[Trigonometric Functions](#)

[atan](#)

Cadence SKILL Language Reference

Trigonometric Functions

Logical and Relational Functions

This topic lists the SKILL functions related to logical and relational operations.

| | | |
|-------------------|---------------------------|--------------------|
| <u>alphalessp</u> | <u>and</u> | <u>compareTime</u> |
| <u>eq</u> | <u>equal</u> | <u>eqv</u> |
| <u>geqp</u> | <u>greaterp</u> | <u>leqp</u> |
| <u>lessp</u> | <u>member, memq, memv</u> | <u>neq</u> |
| <u>nequal</u> | <u>null</u> | <u>numberp</u> |
| <u>or</u> | <u>sxtd</u> | |

alphalessp

```
alphalessp(  
    S_arg1  
    S_arg2  
)  
=> t / nil
```

Description

Compares two string or symbol names alphabetically.

This function returns `t` if the first argument is alphabetically less than the second argument. If `S_arg` is a symbol, then its name is its print name. If `S_arg` is a string, then its name is the string itself.

Arguments

| | |
|---------------------|---------------------------------|
| <code>S_arg1</code> | First name you want to compare. |
| <code>S_arg2</code> | Name to compare against. |

Value Returned

| | |
|------------------|--|
| <code>t</code> | If <code>S_arg1</code> is alphabetically less than the name of <code>S_arg2</code> . |
| <code>nil</code> | In all other cases. |

Examples

```
alphalessp( "name" "name1" )  
=> t  
alphalessp( "third" "fourth" )  
=> nil  
alphalessp('a 'ab)  
=> t
```

Related Topics

[Logical and Relational Functions](#)

[strcmp](#)

Cadence SKILL Language Reference

Logical and Relational Functions

strncmp

and

```
and(  
    g_arg1  
    g_arg2  
    [ g_arg3... ]  
)  
=> nil / g_val
```

Description

Evaluates from left to right its arguments to see if the result is `nil`. As soon as an argument evaluates to `nil`, and returns `nil` without evaluating the rest of the arguments. Otherwise, and evaluates the next argument. If all arguments except for the last evaluate to non-`nil`, and returns the value of the last argument as the result of the function call. Prefix form of the `&&` binary operator.

Arguments

| | |
|---------------|-------------------|
| <i>g_arg1</i> | Any SKILL object. |
| <i>g_arg2</i> | Any SKILL object. |
| <i>g_arg3</i> | Any SKILL object. |

Value Returned

| | |
|------------------|---|
| <code>nil</code> | If an argument evaluates to <code>nil</code> . |
| <i>g_val</i> | Value of the last argument if all the preceding arguments evaluate to non- <code>nil</code> . |

Examples

```
and(nil t)  
=> nil  
  
and(t nil)  
=> nil  
  
and(18 12)  
=> 12
```

Related Topics

[Logical and Relational Functions](#)

Cadence SKILL Language Reference

Logical and Relational Functions

band

bband

bnor

bnot

bor

bxnor

bxor

compareTime

```
compareTime(  
    t_time1  
    t_time2  
)  
=> x_difference
```

Description

Compares two string arguments, representing a clock-calendar time.

Arguments

| | |
|----------------|---|
| <i>t_time1</i> | First string in the <i>month day hour:minute:second year</i> format. |
| <i>t_time2</i> | Second string in the <i>month day hour:minute:second year</i> format. |

Value Returned

| | |
|---------------------|---|
| <i>x_difference</i> | An integer representing a time that is later than (positive), equal to (zero), or earlier than (negative) the second argument. The units are seconds. |
|---------------------|---|

Examples

In the following example, 687,777 seconds have occurred between the two dates given. For a positive number of seconds, the most recent date needs to be given as the first argument.

```
compareTime("Apr 8 4:21:39 1991" "Apr 16 3:24:36 1991")  
=> -687777.
```

In the following example, 600 seconds (10 minutes) have occurred between the two dates.

```
compareTime("Apr 16 3:24:36 1991" "Apr 16 3:14:36 1991")  
=> 600
```

Related Topics

[Logical and Relational Functions](#)

[getCurrentTime](#)

eq

```
eq(  
    g_arg1  
    g_arg2  
)  
=> t / nil
```

Description

Checks addresses when testing for equality.

Returns `t` if *g_arg1* and *g_arg2* are the same (that is, are at the same address in memory). The `eq` function runs considerably faster than `equal` but should only be used for testing equality of symbols, shared lists, or small numeric values (in the range of -256 to +256). Using `eq` on types other than symbols, lists, or small numeric values will give unpredictable results and should be avoided.

For testing equality of numbers, strings, and lists in general, the `equal` function and not the `eq` function should be used. You can test for equality between symbols using `eq` more efficiently than using the `==` operator, which is the same as the `equal` function. If one argument of the `eq` function is a string, SKILL Lint prints an error suggesting that the `eqv` or `equal` function be used instead.

Arguments

| | |
|---------------|---|
| <i>g_arg1</i> | Any SKILL object. <i>g_arg1</i> is compared with <i>g_arg2</i> to see if they point to the same object. |
| <i>g_arg2</i> | Any SKILL object. |

Value Returned

| | |
|------------------|-------------------------------------|
| <code>t</code> | Both arguments are the same object. |
| <code>nil</code> | The two objects are not identical. |

Examples

```
x = 'dog  
eq( x 'dog )  
=> t  
  
eq( x 'cat )  
=> nil
```

Cadence SKILL Language Reference

Logical and Relational Functions

```
y = 'dog  
eq( x y )  
=> t
```

Related Topics

Logical and Relational Functions

equal

equal

```
equal(  
    g_arg1  
    g_arg2  
)  
=> t / nil
```

Description

Checks contents of strings and lists when testing for equality.

Checks if two arguments are equal or if they are logically equivalent, for example, *g_arg1* and *g_arg2* are equal if they are both lists/strings and their contents are the same. This test is slower than using *eq* but works for comparing objects other than symbols.

- If the arguments are the same object in virtual memory (that is, they are *eq*), *equal* returns *t*.
- If the arguments are the same type and their contents are equal (for example, strings with identical character sequence), *equal* returns *t*.
- If the arguments are a mixture of fixnums and flonums, *equal* returns *t* if the numbers are identical (for example, 1.0 and 1).

Arguments

| | |
|---------------|---|
| <i>g_arg1</i> | Any SKILL object. <i>g_arg1</i> and <i>g_arg2</i> are tested to see if they are logically equivalent. |
| <i>g_arg2</i> | Any SKILL object. |

Value Returned

| | |
|------------|---|
| <i>t</i> | If <i>g_arg1</i> and <i>g_arg2</i> are equal. |
| <i>nil</i> | If <i>g_arg1</i> and <i>g_arg2</i> are not equal. |

Examples

```
x = 'cat  
equal( x 'cat )  
=> t  
  
x == 'dog  
=> nil      ; == is the same as equal.
```

Cadence SKILL Language Reference

Logical and Relational Functions

```
x = "world"
equal( x "world" )
=> t

x = '(a b c)
equal( x '(a b c))
=> t

equal(2 2.0)
=> t
```

Related Topics

Logical and Relational Functions

eq

Cadence SKILL Language Reference

Logical and Relational Functions

eqv

```
eqv(  
    g_general1  
    g_general2  
)  
=> t / nil
```

Description

Tests for the equality between two strings or two numbers of the same type (for example, both numbers are integers). Except for numbers, `eqv` is like `eq`.

Arguments

| | |
|-------------------|--------------------------|
| <i>g_general1</i> | The first SKILL object. |
| <i>g_general2</i> | The second SKILL object. |

Value Returned

| | |
|------------|--|
| <i>t</i> | <i>g_general1</i> and <i>g_general2</i> represent the same string or the same number. |
| <i>nil</i> | <i>g_general1</i> and <i>g_general2</i> does not represent the same string or the same number. |

Examples

```
(eqv 1.5 1.5)  
=> t  
(equal 1.5 1.5)  
=> t  
(eq 1.5 1.5)  
=> nil  
(eqv (list 1 2) (list 1 2))  
=> nil  
s1="world"  
s2="world"  
eqv(s1 s2)  
=> t
```

Related Topics

Logical and Relational Functions

eq

equal

geqp

```
geqp (  
    n_num1  
    n_num2  
)  
=> t / nil
```

Description

This predicate function checks if the first argument is greater than or equal to the second argument. Prefix form of the `>=` operator.

Arguments

| | |
|---------------|--|
| <i>n_num1</i> | Number to be checked. |
| <i>n_num2</i> | Number against which <i>n_num1</i> is checked. |

Value Returned

| | |
|-----|---|
| t | <i>n_num1</i> is greater than or equal to <i>n_num2</i> . |
| nil | <i>n_num1</i> is less than <i>n_num2</i> . |

Examples

```
geqp(2 2)  
=> t  
geqp(-2 2)  
=> nil  
geqp(3 2.2)  
=> t
```

Related Topics

[Logical and Relational Functions](#)

[greaterp](#)

[leqp](#)

Cadence SKILL Language Reference

Logical and Relational Functions

lessp

greaterp

```
greaterp(  
    n_num1  
    n_num2  
)  
=> t / nil
```

Description

This predicate function checks if the first argument is greater than the second argument. Prefix form of the > operator.

Arguments

| | |
|---------------|--|
| <i>n_num1</i> | Number to be checked. |
| <i>n_num2</i> | Number against which <i>n_num1</i> is checked. |

Value Returned

| | |
|-----|--|
| t | <i>n_num1</i> is greater than <i>n_num2</i> . |
| nil | <i>n_num1</i> is less than or equal to <i>n_num2</i> . |

Examples

```
greaterp(2 2)  
=> nil  
greaterp(-2 2)  
=> nil  
greaterp(3 2.2)  
=> t
```

Related Topics

[Logical and Relational Functions](#)

[geqp](#)

[leqp](#)

Cadence SKILL Language Reference

Logical and Relational Functions

lessp

leqp

```
leqp(  
    n_num1  
    n_num2  
)  
=> t / nil
```

Description

This predicate function checks if the first argument is less than or equal to the second argument. Prefix form of the `<=` operator.

Arguments

| | |
|---------------|--|
| <i>n_num1</i> | Number to be checked. |
| <i>n_num2</i> | Number against which <i>n_num1</i> is checked. |

Value Returned

| | |
|-----|--|
| t | <i>n_num1</i> is less than or equal to <i>n_num2</i> . |
| nil | <i>n_num1</i> is greater than <i>n_num2</i> . |

Examples

```
leqp(2 2)  
=> t  
leqp(-2 2)  
=> t  
leqp(3 2.2)  
=> nil
```

Related Topics

[Logical and Relational Functions](#)

[geqp](#)

[greaterp](#)

Cadence SKILL Language Reference

Logical and Relational Functions

lessp

lessp

```
lessp(  
    n_num1  
    n_num2  
)  
=> t / nil
```

Description

This predicate function checks if the first argument is less than the second argument. Prefix form of the < operator.

Arguments

| | |
|---------------|--|
| <i>n_num1</i> | Number to be checked. |
| <i>n_num2</i> | Number against which <i>n_num1</i> is checked. |

Value Returned

| | |
|------------|---|
| <i>t</i> | <i>n_num1 is less than n_num2.</i> |
| <i>nil</i> | <i>n_num1 is greater than or equal to n_num2.</i> |

Examples

```
lessp(2 2)  
=> nil  
lessp(-2 2)  
=> t  
lessp(3 2.2)  
=> nil
```

Related Topics

[Logical and Relational Functions](#)

[geqp](#)

[greaterp](#)

Cadence SKILL Language Reference

Logical and Relational Functions

leqp

member, memq, memv

```
member (
    g_obj
    g_arg
)
=> l_sublist / t / nil
```

Description

Returns the largest sublist of *l_list* whose first element is *g_obj* or checks whether the key *g_obj* exists in the association table. For comparison, *member* uses the *equal* function, *memq* uses the *eq* function, and *memv* uses *eqv*.

memq should only be used when comparing symbols and lists. See *eq* for restrictions on when *eq* based comparisons can be used.

It is faster to convert a string to a symbol using *concat* in conjunction with *memq* than using *member*, which performs a comparison using *equal* which is slower, especially for large lists. These functions return a non-*nil* value if the first argument matches a member of the list passed in as the second argument.

Arguments

| | |
|--------------|---|
| <i>g_obj</i> | Element to be searched for in <i>l_list</i> or key to be searched in the association table. |
| <i>g_arg</i> | A list or an association table. |

Value Returned

| | |
|------------------|---|
| <i>l_sublist</i> | The part of <i>l_list</i> or association table beginning with the first match of <i>g_obj</i> . |
| <i>t</i> | The key <i>g_obj</i> exists in the association table. |
| <i>nil</i> | The key <i>g_obj</i> does not exist in the association table. |

Examples

```
x = "c"
=> "c"

member( x '("a" "b" "c" "d"))
=> ("c" "d")
```

Cadence SKILL Language Reference

Logical and Relational Functions

```
memq('c '(a b c d c d))  
=> (c d c d)  
  
memq( concat( x ) '(a b c d ))  
=> (c d)  
  
memv( 1.5 '(a 1.0 1.5 "1.5"))  
=> (1.5 "1.5")
```

```
tb = makeTable("myTable")  
tb[0]= 1  
tb["skill"] = 2  
member("skill" tb)  
=> t
```

Related Topics

Logical and Relational Functions

eq

equal

eqv

concat

Cadence SKILL Language Reference

Logical and Relational Functions

neq

```
neq(  
    g_arg1  
    g_arg2  
)  
=> t / nil
```

Description

Checks if two arguments are *not* identical using the *eq* function and returns *t* if they are not. That is, *g_arg1* and *g_arg2* are tested to see if they are at the same address in memory.

Arguments

| | |
|---------------|-------------------|
| <i>g_arg1</i> | Any SKILL object. |
| <i>g_arg2</i> | Any SKILL object. |

Value Returned

| | |
|------------|--|
| <i>t</i> | If <i>g_arg1</i> and <i>g_arg2</i> are not eq. |
| <i>nil</i> | If <i>g_arg1</i> and <i>g_arg2</i> are eq. |

Examples

```
a = 'dog  
=> dog  
neq( a 'dog )  
=> nil  
neq( a 'cat )  
=> t  
z = '(1 2 3)  
=> (1 2 3)  
neq(z z)  
=> nil  
neq('(1 2 3) z)  
=> t
```

Cadence SKILL Language Reference

Logical and Relational Functions

Related Topics

Logical and Relational Functions

eq

equal

eqv

nequal

nequal

```
nequal(  
    g_arg1  
    g_arg2  
)  
=> t / nil
```

Description

Checks if two arguments are *not* logically equivalent using the `equal` function and returns `t` if they are not.

`g_arg1` and `g_arg2` are only equal if they are either `eqv` or they are both lists/strings and their contents are the same.

Arguments

| | |
|---------------------|-------------------|
| <code>g_arg1</code> | Any SKILL object. |
| <code>g_arg2</code> | Any SKILL object. |

Value Returned

| | |
|------------------|---|
| <code>t</code> | If <code>g_arg1</code> and <code>g_arg2</code> are not equal. |
| <code>nil</code> | If <code>g_arg1</code> and <code>g_arg2</code> are equal. |

Examples

```
x = "cow"  
=> "cow"  
nequal( x "cow" )  
=> nil  
nequal( x "dog" )  
=> t  
z = '(1 2 3)  
=> (1 2 3)  
nequal(z z)  
=> nil  
nequal('(1 2 3) z)  
=> nil
```

Related Topics

Logical and Relational Functions

neq

equal

null

```
null(  
    g_value  
)  
=> t / nil
```

Description

Checks if an object is equal to `nil`.

`null` is a type predicate function.

Arguments

| | |
|----------------|----------------|
| <i>g_value</i> | A data object. |
|----------------|----------------|

Value Returned

| | |
|------------------|--|
| <code>t</code> | If <i>g_value</i> is equal to <code>nil</code> . |
| <code>nil</code> | If <i>g_value</i> is not equal to <code>nil</code> . |

Examples

```
null( 3 )  
=> nil  
null('() )  
=> t  
null( nil )  
=> t
```

Related Topics

[equal](#)

numberp

```
numberp(  
    g_value  
)  
=> t / nil
```

Description

Checks if a data object is a number, that is, either an integer or floating-point number.

The suffix `p` is usually added to the name of a function to indicate that it is a predicate function.

Arguments

| | |
|----------------|----------------|
| <i>g_value</i> | A data object. |
|----------------|----------------|

Value Returned

| | |
|------------------|----------------------------------|
| <code>t</code> | The data object is a number. |
| <code>nil</code> | The data object is not a number. |

Examples

```
numberp( 3 )  
=> t  
numberp('isASymbol)  
=> nil  
numberp( 3.5)  
=> t
```

Related Topics

[Logical and Relational Functions](#)

[null](#)

or

```
or(  
    g_arg1  
    g_arg2  
    [ g_arg3... ]  
)  
=> nil / g_val
```

Description

Evaluates from left to right its arguments to see if the result is non-`nil`. As soon as an argument evaluates to non-`nil`, `or` returns that value without evaluating the rest of the arguments. If all arguments except the last evaluate to `nil`, `or` returns the value of the last argument as the result of the function call. Prefix form of the `||` binary operator.

Arguments

| | |
|---------------------|--|
| <code>g_arg1</code> | First argument to be evaluated. |
| <code>g_arg2</code> | Second argument to be evaluated. |
| <code>g_arg3</code> | Optional additional arguments to be evaluated. |

Value Returned

| | |
|--------------------|---|
| <code>nil</code> | All arguments evaluate to <code>nil</code> . |
| <code>g_val</code> | Value of the argument that evaluates to non- <code>nil</code> , or the value of the last argument if all the preceding arguments evaluate to <code>nil</code> . |

Examples

```
or(t nil)  
=> t  
or(nil t)  
=> t  
or(18 12)  
=> 18
```

Related Topics

[Logical and Relational Functions](#)

and

sxtd

```
sxtd(  
    x_number  
    x_bits  
)  
=> x_result
```

Description

Sign-extends the number represented by the rightmost specified number of bits in the given integer.

Sign-extends the rightmost *x_bits* bits of *x_number*. That is, sign-extends the bit field *x_number*<*x_bits* - 1:0> with *x_number*<*x_bits* - 1> as the sign bit.

Arguments

| | |
|-----------------|-----------------|
| <i>x_number</i> | An integer. |
| <i>x_bits</i> | Number of bits. |

Value Returned

| | |
|-----------------|---|
| <i>x_result</i> | <i>x_number</i> with the rightmost <i>x_bits</i> sign-extended. |
|-----------------|---|

Examples

```
sxtd( 7 4 )  
=> 7  
sxtd( 8 4 )  
=> -8  
sxtd( 5 2 )  
=> 5
```

Related Topics

[Logical and Relational Functions](#)

[zxtd](#)

Cadence SKILL Language Reference

Logical and Relational Functions

Flow Control Functions

This topic lists the SKILL functions related to flow control operations.

| | | |
|---------------------|----------------------|--------------------|
| <u>case</u> | <u>caseq</u> | <u>catch</u> |
| <u>cond</u> | <u>decode</u> | <u>do</u> |
| <u>exists</u> | <u>existss</u> | <u>for</u> |
| <u>fors</u> | <u>forall</u> | <u>foralls</u> |
| <u>foreach</u> | <u>foreachs</u> | <u>if</u> |
| <u>go</u> | <u>map</u> | <u>mapc</u> |
| <u>mapcan</u> | <u>mapcar</u> | <u>mapcon</u> |
| <u>mapinto</u> | <u>maplist</u> | <u>not</u> |
| <u>regExitAfter</u> | <u>regExitBefore</u> | <u>remExitProc</u> |
| <u>return</u> | <u>setof</u> | <u>setofs</u> |
| <u>throw</u> | <u>unless</u> | <u>when</u> |
| <u>while</u> | | |

case

```
case (
    g_keyForm
    l_clause1
    [ l_clause2 ... ]
)
=> g_result / nil
```

Description

Branches to one of the clauses depending on the value of the given expression. `case()` evaluates *g_keyForm* and matches the resulting value sequentially against the clauses until it finds a match. Once a match is found it stops searching the clauses, evaluates the forms in the matching clause, and returns the resulting value. This is a syntax function.

Each *l_clause* is in turn a list of the form (*g_keys* *g_expr1* [*g_expr2* ...]) in which the first element, that is *g_keys*, is either an atom (that is, a scalar) of any data type or a list of keys (to be compared with the given expression). When using a list of keys, specify it as a list of one or more lists to distinguish it from a list of scalar keys. If any of the keys matches the value from *g_keyForm*, that clause is selected. Keys are always treated as constants and are never evaluated.

The symbol `⊔` has special meaning as a key in that it matches anything. It acts as a catch-all and should be handled last to serve as a default case when no other match is found. To match the value `⊔`, use a list of `⊔` as the key.

Arguments

g_keyForm

An expression whose value is evaluated and tested for equality against the keys in each clause.

A match occurs when either the selector is equal to the key or the selector is equal to one of the elements in the list of keys. If a match is found, the expressions in that clause and that clause only (that is, the first match) are executed. The value of `case` is then the value of the last expression evaluated (that is, the last expression in the clause selected). If there is no match, `case` returns `nil`.

Cadence SKILL Language Reference

Flow Control Functions

| | |
|------------------|---|
| <i>l_clause1</i> | An expression whose first element is an atom or list of atoms to be compared against the value of <i>g_keyForm</i> . The remainder of the <i>l_clause</i> is evaluated if a match is found. Do not put quotes or use the <code>list()</code> function when specifying the lists in a clause. |
| <i>l_clause2</i> | Zero or more clauses of the same form as <i>l_clause1</i> . |

Value Returned

| | |
|------------------|---|
| <i>g_resultb</i> | The value of the last expression evaluated in the matched clause, or <code>nil</code> if there is no match. |
| <code>nil</code> | If there is no match. |

Examples

```
nameofmonth = "February"
month = case( nameofmonth
              ("January" 1)
              ("February" 2)
              (t 'Other))
=> 2
```

```
listofnums = list(2 4 6)
case( listofnums
      (( (1 2 3) ) 'onetwothree)
      (( (1 3 5)
          (7 9 11) ) 'odd)
      (( (2 4 6)
          (8 10 12) ) 'even)
      (t 'unknown))
=> even
```

```
case( myBool
      (nil 'never) ; this will never match, it is a list of no keys
      (( nil ) nil) ; matches nil
      (( t ) t) ; matches t
      (t (error "Expected t or nil")))
)
```

Cadence SKILL Language Reference

Flow Control Functions

```
shapeType="line"
rectCount=0
labelOrLineCount=0
miscount=0
case( shapeType
("rect" ++rectCount println( "Shape is a rectangle" ))
(( "label" "line" ) ++labelOrLineCount println( "Shape is a line or a label" ))
(t ++miscount println( "Shape is miscellaneous" ))
) ; case
=> Shape is a line or a label
```

```
procedure(migrateShape(shape "d")
  case(list(shape->layerName shape->purpose)
    (((("POLY" "test1"))
      shape->layerName = "CPO"
      shape->purpose = "drawing"
    )
    (((("Oxide" "drawing") ("abcd" "efgh"))
      println(shape->layerName)
    )
    (((("M1" "net"))
      shape->purpose = "label"
    )
    (((("M2" "net"))
      shape->purpose = "label"
    )
    (((("M3" "net"))
      shape->purpose = "label"
    )
    (((("M4" "net"))
      shape->purpose = "label"
    )
    )
  ) ;
```

Related Topics

Flow Control Functions

eq

equal

caseq

```
caseq(  
    g_keyForm  
    l_clause1  
    [ l_clause2 ... ]  
)  
=> g_result / nil
```

Description

Works like the `case()` function, but uses `eq()` to find a matching clause instead of the `equal()` function. The keys used with `caseq()` should therefore not be strings or lists. In case you want to use a string value or a list, SKILL recommends using the `case()` function. See [eq](#) for details on the difference between the `eq()` and `equal()` functions.

Arguments

| | |
|------------------|---|
| <i>g_keyForm</i> | <p>An expression whose value is evaluated and tested for equality against the comparators in each clause. A match occurs when either the selector is equal to the comparator or the selector is equal to one of the elements in the list given as the comparator.</p> <p>If a match is found, the expressions in that clause and that clause only (that is, the first match) are executed. The value of case is then the value of the last expression evaluated (that is, the last expression in the clause selected).</p> <p>If there is no match, case returns nil.</p> |
| <i>l_clause1</i> | <p>An expression whose first element is an atom or list of atoms to be compared against the value of <i>g_keyForm</i>. The remainder of the <i>l_clause</i> is evaluated if a match is found.</p> |
| <i>l_clause2</i> | <p>Zero or more clauses of the same form as <i>l_clause1</i>.</p> |

Value Returned

| | |
|-----------------|--|
| <i>g_result</i> | <p>The value of the last expression evaluated in the matched clause, or <code>nil</code> if there is no match.</p> |
| <i>nil</i> | <p>If there is no match.</p> |

Cadence SKILL Language Reference

Flow Control Functions

Examples

```
caseq(value
((nil) printf("Failed.\n"))
(indeterminate printf("Indeterminate.\n"))
((t) printf("Succeeded.\n"))
(t printf("Default.\n"))
))
```

Related Topics

[Flow Control Functions](#)

catch

```
catch(  
    s_tag  
    g_form  
)  
=> g_result
```

Description

Establishes a control transfer or a return point for the `throw` and `err` functions. The return point is identified with a *s_tag*. So, when a particular tag/exception is caught, `catch` evaluates *g_form*. If the forms execute normally (without error), the value of the last body form is returned from the `catch`. There can also be nested `catch` blocks and *s_tag* can be `t` (the value `t` the `catch` function catch any condition thrown by `throw`).

Arguments

| | |
|---------------|---|
| <i>s_tag</i> | Identifies the return point for the <code>throw</code> and <code>err</code> functions |
| <i>g_form</i> | Specifies the forms that are evaluated |

Value Returned

| | |
|-----------------|---|
| <i>g_result</i> | The value of the last form if the forms exit normally, otherwise, returns the values that are thrown if a <code>throw</code> or <code>err</code> occurs |
|-----------------|---|

Examples

The following example describes a nested `catch`. The tag, `'wrongPlat`, is caught by the default handler `catch(t . . .)`.

```
catch(t  
    catch('issue1  
        printf("Hello ")  
        catch('issue2  
            when(cdsPlat() == "lnx86"  
                throw('wrongPlat printf("\n") nil); no exception is thrown on  
non-lnx86 platforms  
            )  
            printf("world\n")  
        )  
    )  
)
```

Cadence SKILL Language Reference

Flow Control Functions

```
Hello  
=> nil
```

Related Topics

[Flow Control Functions](#)

cond

```
cond(  
    l_clause1 ...  
)  
=> g_result
```

Description

Examines conditional clauses from left to right until either a clause is satisfied or there are no more clauses remaining. This is a syntax function.

`cond` clauses can have one of the following forms:

- (*g_condition g_expr1* ...) where *g_condition* is any expression
- (*g_condition*)
- Alternate clause, "`=> clause`" where *g_condition* => *u_expression*
- Else clause of the form (*else g_expr* ...), where the condition is replaced by the symbol `else`. This form is applicable only in SKILL++/Scheme mode.

Each clause is considered in succession. If *g_condition* evaluates to non-`nil` then processing stops and the value of the clause is used for the whole `cond` form. If one or more *g_expr* forms are given, they are evaluated in order and the value of the final *g_expr* is used as the value of the whole `cond` form. If no *g_expr* forms are given, the value of *g_condition* is used.

If the clause uses the alternate clause form, "`=> clause`", *u_expression* must evaluate to a function, which is called with the value of *g_condition* as a single argument. The value returned by this function is used as the value of the whole `cond` form.

If an `else` clause is encountered, its *g_expr* forms are evaluated unconditionally and the value of the final *g_expr* is used as the value of the whole `cond` form.

Arguments

l_clause1

Each clause should be of the form (*g_condition g_expr1* ...) where if *g_condition* evaluates to non-`nil` then all the succeeding expressions are evaluated.

Cadence SKILL Language Reference

Flow Control Functions

Value Returned

g_result Value of the last expression of the satisfied clause, or `nil` if no clause is satisfied.

Examples

```
procedure( test(x)
  cond((null x) (println "Arg is null"))
      ((numberp x) (println "Arg is a number"))
      ((stringp x) (println "Arg is a string"))
      (t (println "Arg is an unknown type"))))
```

```
test( nil )
=> nil; Prints "Arg is null".

test( 5 )
=> nil; Prints "Arg is a number".

test( 'sym )
=> nil; Prints "Arg is an unknown type".
```

Related Topics

[Flow Control Functions](#)

decode

```
decode (  
    g_keyForm  
    l_clause1  
    [ l_clause2 ... ]  
)  
=> g_result / nil
```

Description

Branches to one of the clauses depending on the value of the given expression. `decode()` evaluates *g_keyForm* and matches the resulting value sequentially against the clauses until it finds a match. Once a match is found it stops searching the clauses, evaluates the forms in the matching clause, and returns the resulting value.

Arguments

| | |
|------------------|---|
| <i>g_keyForm</i> | An expression whose value is evaluated and tested for equality against the key in each clause. A match occurs when either the selector is equal to the key. If a match is found, the expressions in that clause and that clause only (that is, the first match) are executed. |
| <i>l_clause1</i> | A list of the form (<i>g_keys</i> <i>g_expr1</i> [<i>g_expr2</i> ...]) in which the first element, that is <i>g_keys</i> , is an atom (that is, a scalar) of any data type. If any of the keys matches the value from <i>g_keyForm</i> , the clause that contains it is selected. Keys are always treated as constants and are never evaluated. |
| <i>l_clause2</i> | Any other clauses in the same form as <i>l_clause1</i> . |

Value Returned

| | |
|-----------------|---|
| <i>g_result</i> | The value of the last expression evaluated in the matched clause. |
| <i>nil</i> | If there is no match. |

Examples

```
v = "test"  
decode (v  
        (1 nil)
```

Cadence SKILL Language Reference

Flow Control Functions

```
        ("test" printf("test found\n"))  
        (2 t)  
        (t nil)  
    )
```

=> 2

Related Topics

Flow Control Functions

case

caseq

do

```
do (
  (
    (
      s_var1
      g_initExp1
      [ g_stepExp1 ]
    )
    (
      s_var2
      g_initExp2
      [ g_stepExp2 ]
    ) ...
  )
  (
    g_terminationExp
    g_terminationExp1 ...
  )
  g_loopExp1
  g_loopExp2 ...
)
=> g_value
```

Description

Iteratively executes one or more expressions. Used in SKILL++ mode only.

Use `do` to iteratively execute one or more expressions. The `do` expression provides a `do-while` facility allowing multiple loop variables with arbitrary variable initializations and step expressions. You can declare

- One or more loop variables, specifying for each variable both its initial value and how it gets updated each time around the loop.
- A termination condition which is evaluated before the body expressions are executed.
- One or more termination expressions to be evaluated upon termination to determine a return value.

A do Expression Evaluates in Two Phases

■ Initialization phase

The initialization expressions *g_initExp1*, *g_initExp2*, ... are evaluated in an unspecified order and the results bound to the local variables *var1*, *var2*, ...

■ Iteration phase

Cadence SKILL Language Reference

Flow Control Functions

This phase is a sequence of steps, informally described as going around the loop zero or more times with the exit determined by the termination condition.

More formally stated:

1. Each iteration begins by evaluating the termination condition.

If the termination condition evaluates to a non-`nil` value, the `do` expression exits with a return value computed as follows:

2. The termination expressions *terminationExp1*, *terminationExp2*, ... are evaluated in order. The value of the last termination condition is returned as the value of the `do` expression.

Otherwise, the `do` expression continues with the next iteration as follows.

3. The loop body expressions *g_loopExp1*, *g_loopExp2*, ... are evaluated in order.
4. The step expressions *g_stepExp1*, *g_stepExp2*, ..., if given, are evaluated in an unspecified order.
5. The local variables *var1*, *var2*, ... are bound to the above results. Reiterate from step one.

Value Returned

g_result The value of the expression executed.

Examples

By definition, the sum of the integers *1*, ..., *N* is the *Nth* triangular number. The following example finds the first triangular number greater than a given limit.

```
procedure( trTriangularNumber( limit )
do(
  (
    ( i 0 i+1 )      ;;; start loop variables
    ( sum 0 )        ;;; no step expression
                    ;;; same as ( sum 0 sum )
  )                ;;; end loop variables
  ( sum > limit      ;;; test
    sum              ;;; return result
  )
  sum = sum+i        ;;; body
)                    ; do
)                    ; procedure

trTriangularNumber( 4 )
=> 6
```


Cadence SKILL Language Reference

Flow Control Functions

```
trTriangularNumber( 5 )  
=> 6  
trTriangularNumber( 6 )  
=> 10
```

Related Topics

Flow Control Functions

while

exists

```
exists(  
    s_formalVar  
    l_valueList  
    g_predicateExpr  
)  
=> g_result  
  
exists(  
    s_key  
    o_table  
    g_predicateExpr  
)  
=> t / nil
```

Description

Returns the first tail of *l_valueList* whose *car* satisfies a predicate expression. Also verifies whether an entry in an association table satisfies a predicate expression. This is a syntax form.

This process continues to apply the *cdr* function successively through *l_valueList* until it finds a list element that causes *g_predicateExpr* to evaluate to non-nil. It then returns the tail that contains that list element as its first element.

This function can also be used to verify whether an entry in an association table satisfies *g_predicateExpr*.

Arguments

| | |
|------------------------|--|
| <i>s_formalVar</i> | Local variable that is usually referenced in <i>g_predicateExpr</i> . |
| <i>l_valueList</i> | List of elements that are bound to <i>s_formalVar</i> , one at a time. |
| <i>g_predicateExpr</i> | SKILL expression that usually uses the value of <i>s_formalVar</i> . |
| <i>s_key</i> | Key portion of an association table entry. |
| <i>o_table</i> | Association table containing the entries to be processed. |

Value Returned

| | |
|-----------------|--|
| <i>g_result</i> | First tail of <i>l_valueList</i> whose <i>car</i> satisfies <i>g_predicateExpr</i> . |
|-----------------|--|

Cadence SKILL Language Reference

Flow Control Functions

| | |
|------------------|--|
| <code>nil</code> | If none of the elements in <i>l_valueList</i> can satisfy it. |
| <code>t</code> | Entry in an association table satisfies <i>g_predicateExpr</i> . |

Examples

Tests an association table and verifies the existence of an entry where both the key and its corresponding value are of type string.

```
exists( x '(1 2 3 4) (x > 1) )  
=> (2 3 4)  
exists( x '(1 2 3 4) (x > 4) )  
=> nil
```

```
exists( key myTable (and (stringp key)  
                        (stringp myTable[key])))  
=> t
```

Related Topics

Flow Control Functions

[car](#)

[cdr](#)

existss

```
existss(  
    s_formalVar  
    l_valueList  
    g_predicateExpr  
)  
=> g_result  
  
existss(  
    s_key  
    o_table  
    g_predicateExpr  
)  
=> t / nil
```

Description

Returns the first tail of *l_valueList* whose *car* satisfies a predicate expression. Also verifies whether an entry in an association table satisfies a predicate expression. In the SKILL++ mode, this function always locally wraps the loop or iterator local variable (*s_formalVar*) in a `let` block while compiling the code. Local wrapping preserves the lexical scope of the loop variable. This function may work slower than its non-wrapped counterpart `exists`. This is a syntax form.

This process continues to apply the `cdr` function successively through *l_valueList* until it finds a list element that causes *g_predicateExpr* to evaluate to non-`nil`. It then returns the tail that contains that list element as its first element.

This function can also be used to verify whether an entry in an association table satisfies *g_predicateExpr*.

Arguments

| | |
|------------------------|--|
| <i>s_formalVar</i> | Local variable that is usually referenced in <i>g_predicateExpr</i> . |
| <i>l_valueList</i> | List of elements that are bound to <i>s_formalVar</i> , one at a time. |
| <i>g_predicateExpr</i> | SKILL expression that usually uses the value of <i>s_formalVar</i> . |
| <i>s_key</i> | Key portion of an association table entry. |
| <i>o_table</i> | Association table containing the entries to be processed. |

Cadence SKILL Language Reference

Flow Control Functions

Value Returned

| | |
|-----------------|--|
| <i>g_result</i> | First tail of <i>l_valueList</i> whose <i>car</i> satisfies <i>g_predicateExpr</i> . |
| <i>nil</i> | If none of the elements in <i>l_valueList</i> can satisfy it. |
| <i>t</i> | Entry in an association table satisfies <i>g_predicateExpr</i> . |

Examples

```
(defun test_exists (x)
  existss( x (list x x+1 x+9) println(x))
  println(x)
)
test_exists(9)

=> 9
10
18
9
nil
```

Also, see the example for the [foreachs](#) function.

Related Topics

[Flow Control Functions](#)

[car](#)

[cdr](#)

[exists](#)

for

```
for(  
    s_loopVar  
    x_initialValue  
    x_finalValue  
    g_expr1  
    [ g_expr2 ... ]  
)  
=> t
```

Description

Evaluates the sequence *g_expr1*, *g_expr2* ... for each loop variable value, beginning with *x_initialValue* and ending with *x_finalValue*. This is a syntax form.

First evaluates the initial and final values, which set the initial value and final limit for the local loop variable named *s_loopVar*. Both *x_initialValue* and *x_finalValue* must be integer expressions. During each iteration, the sequence of expressions *g_expr1*, *g_expr2* ... is evaluated and the loop variable is then incremented by one. If the loop variable is still less than or equal to the final limit, another iteration is performed. The loop terminates when the loop variable reaches a value greater than the limit. The maximum value for the loop variable is INT_MAX-1. The loop variable must not be changed inside the loop. It is local to the `for` loop and would not retain any meaningful value upon exit from the `for` loop.

Arguments

| | |
|-----------------------|---|
| <i>s_loopVar</i> | Name of the local loop variable that must not be changed inside the loop. |
| <i>x_initialValue</i> | Integer expression setting the initial value for the local loop variable. |
| <i>x_finalValue</i> | Integer expression giving final limit value for the loop. |
| <i>g_expr1</i> | Expression to evaluate inside loop. |
| <i>g_expr2</i> | Additional expression(s) to evaluate inside loop. |

Value Returned

| | |
|----------|--|
| <i>t</i> | This construct always returns <i>t</i> . |
|----------|--|

Examples

The following example prints 10 numbers and returns `t`.

```
sum = 0
for( i 1 10
    sum = sum + i
    printf("%d\n" sum))
=> t
```

Related Topics

[Flow Control Functions](#)

[foreach](#)

fors

```
fors(  
    s_loopVar  
    x_initialValue  
    x_finalValue  
    g_expr1  
    [ g_expr2 ... ]  
)  
=> t
```

Description

Evaluates the sequence *g_expr1*, *g_expr2* ... for each loop variable value, beginning with *x_initialValue* and ending with *x_finalValue*. In the SKILL++ mode, this function always locally wraps the loop or iterator local variable (*s_loopVar*) in a `let()` block while compiling the code. Local wrapping preserves the lexical scope of the loop variable. This function may work slower than its non-wrapped counterpart `for`. This is a syntax form.

First evaluates the initial and final values, which set the initial value and final limit for the local loop variable named *s_loopVar*. Both *x_initialValue* and *x_finalValue* must be integer expressions. During each iteration, the sequence of expressions *g_expr1*, *g_expr2* ... is evaluated and the loop variable is then incremented by one. If the loop variable is still less than or equal to the final limit, another iteration is performed. The loop terminates when the loop variable reaches a value greater than the limit. The maximum value for the loop variable is `INT_MAX-1`. The loop variable must not be changed inside the loop. It is local to the `for` loop and would not retain any meaningful value upon exit from the `for` loop.

Arguments

| | |
|-----------------------|--|
| <i>s_loopVar</i> | Name of the local loop variable that must not be changed inside the loop |
| <i>x_initialValue</i> | Integer expression setting the initial value for the local loop variable |
| <i>x_finalValue</i> | Integer expression giving final limit value for the loop |
| <i>g_expr1</i> | Expression to evaluate inside loop |
| <i>g_expr2</i> | Additional expression(s) to evaluate inside loop |

Value Returned

`t` This construct always returns `t`

Examples

```
(defun test_for (x)
  fors( x x+1 x+9 println(x))
  println(x)
)
test_for(9)
=> 10
11
12
13
14
15
16
17
18
9
nil
```

Also, see the example for the [`foreachs`](#) function.

Related Topics

[Flow Control Functions](#)

forall

```
forall(  
    s_formalVar  
    l_valueList  
    g_predicateExpr  
)  
=> t / nil  
forall(  
    s_key  
    o_table  
    g_predicateExpr  
)  
=> t / nil
```

Description

Checks if *g_predicateExpr* evaluates to non-nil for every element in *l_valueList*. This is a syntax form.

Verifies that an expression remains true for every element in a list. The `forall` function can also be used to verify that an expression remains true for every key/value pair in an association table. The syntax for association table processing is provided in the second syntax statement.

Arguments

| | |
|------------------------|--|
| <i>s_formalVar</i> | Local variable usually referenced in <i>g_predicateExpr</i> . |
| <i>l_valueList</i> | List of elements that are bound to <i>s_formalVar</i> one at a time. |
| <i>g_predicateExpr</i> | A SKILL expression that usually uses the value of <i>s_formalVar</i> . |
| <i>s_key</i> | Key portion of the table entry. |
| <i>o_table</i> | Association table containing the entries to be processed. |

Value Returned

| | |
|------------|--|
| <i>t</i> | If <i>g_predicateExpr</i> evaluates to non-nil for every element in <i>l_valueList</i> or for every key in an association table. |
| <i>nil</i> | If <i>g_predicateExpr</i> evaluates to nil for every element in <i>l_valueList</i> or for every key in an association table. |

Examples

Returns `t` if each key and its value in the association table are of the type string.

```
forall( x '(1 2 3 4) (x > 0) )  
=> t
```

```
forall( x '(1 2 3 4) (x < 4) )  
=> nil
```

```
forall(key myTable (and (stringp key) (stringp myTable[key])))  
=> t
```

Related Topics

[Flow Control Functions](#)

forall

```
forall(  
    s_formalVar  
    l_valueList  
    g_predicateExpr  
)  
=> t / nil  
forall(  
    s_key  
    o_table  
    g_predicateExpr  
)  
=> t / nil
```

Description

Checks if *g_predicateExpr* evaluates to non-nil for every element in *l_valueList*. In the SKILL++ mode, this function always locally wraps the loop or iterator local variable (*s_formalVar*) in a `let` block while compiling the code. Local wrapping preserves the lexical scope of the loop variable. This function may work slower than its non-wrapped counterpart `forall`. This is a syntax form.

Verifies that an expression remains true for every element in a list. The `forall` function can also be used to verify that an expression remains true for every key/value pair in an association table. The syntax for association table processing is provided in the second syntax statement.

Arguments

| | |
|------------------------|--|
| <i>s_formalVar</i> | Local variable usually referenced in <i>g_predicateExpr</i> . |
| <i>l_valueList</i> | List of elements that are bound to <i>s_formalVar</i> one at a time. |
| <i>g_predicateExpr</i> | A SKILL expression that usually uses the value of <i>s_formalVar</i> . |
| <i>s_key</i> | Key portion of the table entry. |
| <i>o_table</i> | Association table containing the entries to be processed. |

Value Returned

| | |
|----------|--|
| <i>t</i> | If <i>g_predicateExpr</i> evaluates to non-nil for every element in <i>l_valueList</i> or for every key in an association table. |
|----------|--|

Cadence SKILL Language Reference

Flow Control Functions

`nil` If *g_predicateExpr* evaluates to `nil` for every element in *l_valueList* or for every key in an association table.

Examples

```
(defun test_forall (x)
  forall (x (list x x+1 x+9) println(x))
  println(x)
)
test_forall(9)
=> 9
9
nil
```

Also, see the example for the [foreachs](#) function.

Related Topics

[Flow Control Functions](#)

foreach

```
foreach(  
    s_formalVar  
    g_exprList  
    g_expr1  
    [ g_expr2 ... ]  
)  
=> l_valueList / l_result  
  
foreach(  
    (  
        s_formalVar1...  
        s_formalVarN  
    )  
    g_exprList1...  
    g_exprListN  
    g_expr1  
    [ g_expr2 ... ]  
)  
=> l_valueList / l_result  
  
foreach(  
    s_formalVar  
    g_exprTable  
    g_expr1  
    [ g_expr2 ... ]  
)  
=> o_valueTable / l_result
```

Description

Evaluates one or more expressions for each element of a list of values. This is a syntax form.

```
foreach( [s_mappingFunction] s_formalVar g_exprList g_expr1 [ g_expr2 ... ] )  
=> l_valueList / l_result
```

The first syntax form evaluates *g_exprList*, which returns a list *l_valueList*. It then assigns the first element from *l_valueList* to the formal variable *s_formalVar* and executes the expressions *g_expr1*, *g_expr2* ... in sequence. The function then assigns the second element from *l_valueList* and repeats the process until *l_valueList* is exhausted.

```
foreach( [s_mappingFunction] (s_formalVar1...s_formalVarN) g_exprList1...  
g_exprListN g_expr1 [ g_expr2 ... ] )  
=> l_valueList / l_result
```

The second syntax form of `foreach` can iterate over multiple lists to perform vector operations. Instead of a single formal variable, the first argument is a list of formal variables

followed by a corresponding number of expressions for value lists and the expressions to be evaluated.

```
foreach( [s_mappingFunction] s_formalVar g_exprTable g_expr1 [ g_expr2 ... ])  
=> o_valueTable / l_result
```

The third syntax form of `foreach` can be used to process the elements of an association table. In this case, `s_formalVar` is assigned each key of the association table one by one, and the body expressions are evaluated each iteration. The syntax for association table processing is provided in this syntax statement.

Arguments

| | |
|---|---|
| <code>s_formalVar</code> | Name of the variable. |
| <code>s_mappingFunction</code> | One of <code>map</code> , <code>mapc</code> , <code>mapcan</code> , <code>mapcar</code> , <code>mapcon</code> , or <code>maplist</code> . |
| <code>g_exprList</code> | Expression whose value is a list of elements to assign to the formal variable <code>s_formalVar</code> . |
| <code>g_expr1</code> , <code>g_expr2</code> | Expressions to execute. |
| <code>g_exprTable</code> | Association table whose elements are to be processed. |

Value Returned

| | |
|---------------------------|---|
| <code>l_valueList</code> | Value of the second argument, <code>g_exprList</code> . |
| <code>l_result</code> | Return value of the <code>s_mappingFunction</code> if that is used. It is not necessarily the result of the last expression evaluated (it depends on the mapping function). |
| <code>o_valueTable</code> | Value of <code>g_exprTable</code> . |

Examples

```
foreach( x '(1 2 3 4) println(x))  
1           ; Prints the numbers 1 through 4.  
2  
3  
4  
=> (1 2 3 4) ; Returns the second argument to foreach.
```

The next example shows `foreach` accessing an association table and printing each key and its associated data.

```
foreach(key myTable printf("%L : %L\n" key myTable[key]))
```

Cadence SKILL Language Reference

Flow Control Functions

The following is an example with more than one loop variable:

```
(foreach (x y) '(1 2 3) '(4 5 6) (println x+y))  
5  
7  
9  
=> (1 2 3)
```

Errors and Warnings

The error messages from `foreach` might at times appear cryptic because some `foreach` forms get expanded to call the mapping functions `mapc`, `mapcar`, `mapcan`, and so forth.

Advanced Usage

The `foreach` function typically expands to call `mapc`; however, you can also request that a specific mapping function be applied by giving the name of the mapping function as the first argument to `foreach`. Thus, `foreach` can be used as an extremely powerful tool to construct new lists.

Mapping functions are not accepted when this form is applied to association tables.

```
foreach( mapcar x '(1 2 3) (x >1))=> (nil t t)  
foreach( mapcan x '(1 2 3) if((x > 1) ncons(x))) => (2 3)  
foreach( maplist x '(1 2 3) length(x)) => (3 2 1)
```

Related Topics

[Flow Control Functions](#)

foreachs

```
foreachs(  
    s_formalVar  
    g_exprList  
    g_expr1  
    [ g_expr2 ... ]  
)  
=> l_valueList / l_result  
  
foreachs(  
    (  
        s_formalVar1...  
        s_formalVarN  
    )  
    g_exprList1...  
    g_exprListN  
    g_expr1  
    [ g_expr2 ... ]  
)  
=> l_valueList / l_result  
  
foreachs(  
    s_formalVar  
    g_exprTable  
    g_expr1  
    [ g_expr2 ... ]  
)  
=> o_valueTable / l_result
```

Description

Evaluates one or more expressions for each element of a list of values. In the SKILL++ mode, this function always locally wraps the loop or iterator local variable, *s_formalVar*, in a `let` block while compiling the code. Local wrapping preserves the lexical scope of the loop variable. This function may work slower than its non-wrapped counterpart `foreach`. This is a syntax form.

The first form shown in the syntax above evaluates *g_exprList*, which returns a list *l_valueList*. It then assigns the first element from *l_valueList* to the formal variable *s_formalVar* and executes the expressions *g_expr1*, *g_expr2* ... in sequence. The function then assigns the second element from *l_valueList* and repeats the process until *l_valueList* is exhausted.

The second form shown in the syntax above can iterate over multiple lists to perform vector operations. Instead of a single formal variable, the first argument is a list of formal variables

Cadence SKILL Language Reference

Flow Control Functions

followed by a corresponding number of expressions for value lists and the expressions to be evaluated.

The third form shown in the syntax above can be used to process the elements of an association table. In this case, *s_formalVar* is assigned each key of the association table one by one, and the body expressions are evaluated each iteration. The syntax for association table processing is provided in this syntax statement.

Arguments

| | |
|--------------------------|--|
| <i>s_formalVar</i> | Name of the local loop variable that must not be changed inside the loop |
| <i>s_mappingFunction</i> | One of map, mapc, mapcan, mapcar, or maplist |
| <i>g_exprList</i> | Expression whose value is a list of elements to assign to the formal variable <i>s_formalVar</i> |
| <i>g_expr1, g_expr2</i> | Expressions to execute |
| <i>g_exprTable</i> | Association table whose elements are to be processed |

Value Returned

| | |
|---------------------|---|
| <i>l_valueList</i> | Value of the second argument, <i>g_exprList</i> |
| <i>l_result</i> | The result of the last expression evaluated |
| <i>o_valueTable</i> | Value of <i>g_exprTable</i> |

Examples

If the loop variable of a foreach is also defined in the surrounding lexical scope, and then a function declared in that lexical scope is called within the foreach, it will access the loop variable rather than the same variable from the surrounding scope. For example:

```
procedure (LoopScopingIssue(x)
  procedure (printArg())
    printf("printArg: x is %L\n" x)
  )
  foreach(x '(1 2 3 4 5)
    printf("local loop: x is %L\n" x)
    printArg()
  )
)
```

Cadence SKILL Language Reference

Flow Control Functions

)

LoopScopingIssue(10) will output:

```
local loop: x is 1
printArg: x is 1
local loop: x is 2
printArg: x is 2
local loop: x is 3
printArg: x is 3
local loop: x is 4
printArg: x is 4
local loop: x is 5
printArg: x is 5
```

If the lexical scope is fully honored, you expect the call to `printArg()` to print the value of `x` passed into `LoopScopingIssue`.

If instead you use `foreachs`:

```
procedure(LoopScopingIssue(x)
  procedure(printArg()
    printf("printArg: x is %L\n" x)
  )
  foreachs(x ' (1 2 3 4 5)
    printf("local loop: x is %L\n" x)
    printArg()
  )
)
```

then `LoopScopingIssue(10)` will output:

```
local loop: x is 1
printArg: x is 10
local loop: x is 2
printArg: x is 10
local loop: x is 3
printArg: x is 10
local loop: x is 4
printArg: x is 10
local loop: x is 5
printArg: x is 10
```

Related Topics

Flow Control Functions

if

```
if(  
    g_condition  
    g_thenExpression  
    [ g_elseExpression ]  
)  
=> g_result  
  
if(  
    g_condition  
    then g_thenExpr1 ...  
    [ else g_elseExpr1 ... ]  
)  
=> g_result
```

Description

Selectively evaluates two groups of one or more expressions. This is a syntax form.

```
if( g_condition g_thenExpression [ g_elseExpression ] )  
=> g_result
```

The `if` form evaluates *g_condition*, typically a relational expression, and executes *g_thenExpression* if the condition is true (that is, its value is non-`nil`); otherwise, *g_elseExpression* is executed. The value returned by `if` is the value of the corresponding expression evaluated. The `if` form can therefore be used to evaluate expressions conditionally.

```
if( g_condition then g_thenExpr1 ... [ else g_elseExpr1 ... ] )  
=> g_result
```

The second form of `if` uses the keywords `then` and `else` to group sequences of expressions for conditional execution. If the condition is true, the sequence of expressions between `then` and `else` (or the end of the `if` form) is evaluated, with the value of the last expression evaluated returned as the value of the form. If the condition is `nil` instead, the sequence of expressions following the `else` keyword (if any) is evaluated instead. Again, the value of the last expression evaluated is returned as the value of the form.

Arguments

| | |
|-------------------------|-----------------------|
| <i>g_condition</i> | Any SKILL expression. |
| <i>g_thenExpression</i> | Any SKILL expression. |
| <i>g_elseExpression</i> | Any SKILL expression. |

Value Returned

g_result The value of *g_thenExpression* if *g_condition* has a non-nil value. The value of *g_elseExpression* is returned if the above condition is not true.

Examples

```
x = 2
if( (x > 5) 1 0)
=> 0                               ; Returns 0 because x is less than 5.

a = "polygon"
if( (a == "polygon") print(a) )

"polygon"                          ; Prints the string polygon.
=> nil                             ; Returns the result of print.

x = 5
if( x "non-nil" "nil" )
=> "non-nil"                       ; Returns "non-nil" because x was not
                                   ; nil. If x was nil then "nil" would be
                                   ; returned.

x = 7
if( (x > 5) then 1 else 0)
=> 1                               ; Returns 1 because x is greater than 5.

if( (x > 5)
    then println("x is greater than 5")
      x + 1
    else print("x is less ")
      x - 1)

x is greater than 5                ; Printed if x was 7.
=> 8                              ; Returned 8 if x was 7.
```

Related Topics

Flow Control Functions

cond

foreach

unless

while

go

```
go (
    s_label
)
```

Description

Transfers control to the statement following the label argument. This is a syntax form.

The `go` statement is only meaningful when it is used inside a `prog` statement. Control can be transferred to any labeled statement inside any `progs` that contain the `go` statement, but cannot be transferred to labeled statements in a `prog` that is not active at the time the `go` statement is executed. Usually, using `go` is considered poor programming style when higher level control structures such as `foreach` and `while` can be used.

Arguments

| | |
|----------------------|--|
| <code>s_label</code> | Label you want to transfer control to inside a <code>prog</code> . |
|----------------------|--|

Value Returned

None

Examples

The following example demonstrates how to use the `go` function form in a simple loop structure.

```
procedure( testGo( data )
    prog( ()
        start
            print( car( data ))
            data = cdr( data )
            if( data go( start )) ; go statement to jump to start.
        )
    )
testGo( '(a b c))
abc ; Prints the variable data.
=> nil ; Returns nil.
```

Related Topics

Flow Control Functions

Cadence SKILL Language Reference

Flow Control Functions

foreach

return

while

map

```
map (
  u_func
  l_arg1
  [ l_arg2 ... ]
)
=> l_arg1
```

Description

Applies the given function to successive *sublists* of the argument lists and returns the first argument list. All of the lists should have the same length. This function is not the same as the standard Scheme `map` function. To get the behavior of the standard Scheme `map` function, use `mapcar` instead. This function is usually used for its side effects, not its return value (see `mapc`).

Note: This function is not the same as the standard Scheme `map` function. To get the behavior of the standard Scheme `map` function, use `mapcar` instead.

Arguments

| | |
|---------------|---|
| <i>u_func</i> | Function to apply to successive sublists. Must be a function that accepts lists as arguments. |
| <i>l_arg1</i> | Argument list. |
| <i>l_arg2</i> | Additional argument lists, which must be the same length as <i>l_arg1</i> . |

Value Returned

| | |
|---------------|--------------------------|
| <i>l_arg1</i> | The first argument list. |
|---------------|--------------------------|

Examples

No interesting side effect.

```
map( 'list ' (1 2 3) ' (9 8 7) )
=> (1 2 3)
```

Prints three lists as a side effect and returns the list (1 2 3).

Cadence SKILL Language Reference

Flow Control Functions

```
map( '(lambda (x y) (print (append x y))) '(1 2 3) '(9 8 7) )  
(1 2 3 9 8 7) (2 3 8 7) (3 7)  
=> (1 2 3)
```

Related Topics

Flow Control Functions

[apply](#)

[foreach](#)

[mapc](#)

[mapcar](#)

[mapcan](#)

[maplist](#)

mapc

```
mapc (
    u_func
    l_arg1
    [ l_arg2 ... ]
)
=> l_arg1
```

Description

Applies a function to successive *elements* of the argument lists and returns the first argument list. All of the lists should have the same length. `mapc` returns `l_arg1`.

`mapc` is primarily used with a `u_func` that has side effects, because the values returned by the `u_func` are not preserved. `u_func` must be an object acceptable as the first argument to apply and it must accept as many arguments as there are lists. It is first passed the `car` of all the lists given as arguments. The elements are passed in the order in which the lists are specified. The second elements are passed to `u_func`, and so on until the last element.

Arguments

| | |
|---------------------|---|
| <code>u_func</code> | Function to apply to argument lists. |
| <code>l_arg1</code> | Argument list. |
| <code>l_arg2</code> | Additional argument lists, which must be the same length as <code>l_arg1</code> . |

Value Returned

| | |
|---------------------|--------------------------|
| <code>l_arg1</code> | The first argument list. |
|---------------------|--------------------------|

Examples

Prints three lists as a side effect and returns the list (1 2 3).

```
mapc( 'list '(1 2 3) '(9 8 7) ) => (1 2 3)
mapc( '(lambda (x y) (print (list x y))) '(1 2 3) '(9 8 7) )
(1 9) (2 8) (3 7)
=> (1 2 3)
```

Cadence SKILL Language Reference

Flow Control Functions

Related Topics

[Flow Control Functions](#)

[foreach](#)

[map](#)

[mapcar](#)

[mapcan](#)

[maplist](#)

mapcan

```
mapcan(  
    u_func  
    l_arg1  
    [ l_arg2 ... ]  
)  
=> l_result
```

Description

Applies a function to successive *elements* of the argument lists and returns the result of appending these intermediate results. All of the lists should have the same length.

Specifically, a function is applied to the *car* of all the argument lists, passed in the same order as the argument lists. The second elements are processed next, continuing until the last element is processed. The result of each call to *u_func* must be a list. These lists are destructively modified and concatenated so that the resulting list of all the concatenations is the result of *mapcan*. The argument *u_func* must accept as many arguments as there are lists.

Arguments

| | |
|---------------|---|
| <i>u_func</i> | Function to apply to argument lists. |
| <i>l_arg1</i> | Argument list. |
| <i>l_arg2</i> | Additional argument lists, which must be the same length as <i>l_arg1</i> . |

Value Returned

| | |
|-----------------|--|
| <i>l_result</i> | List consisting of the concatenated results. |
|-----------------|--|

Examples

```
mapcan( 'list '(1 2 3) '(a b c) )  
=> (1 a 2 b 3 c)  
  
mapcan( (lambda (n) (and (plusp n) (list n))) '(1 -2 3 -4 5))  
=> (1 3 5)
```

Cadence SKILL Language Reference

Flow Control Functions

Related Topics

Flow Control Functions

map

mapc

mapcar

mapcan

maplist

nconc

mapcar

```
mapcar(  
    u_func  
    l_arg1  
    [ l_arg2 ... ]  
)  
=> l_result
```

Description

Applies a function to successive *elements* of the argument lists and returns the list of the corresponding results.

The values returned from successive calls to *u_func* are put into a list using the `list` function. If the argument lists are of different lengths, the `mapcar` function iterates till the end of the shortest list.

Arguments

| | |
|---------------|---|
| <i>u_func</i> | Function to be applied to argument lists. The result of each call to <i>u_func</i> can be of any data type. |
| <i>l_arg1</i> | Argument list. |
| <i>l_arg2</i> | Additional argument lists. |

Value Returned

| | |
|-----------------|--|
| <i>l_result</i> | A list of results from applying <i>u_func</i> to successive elements of the argument list. |
|-----------------|--|

Examples

```
mapcar( 'plus ' (1 2 3) '(9 8 7) )  
=> (10 10 10)  
  
mapcar( 'plus ' (1 2 3 4) '(4 5) '(1 2 3 4 5 6) '(1 2 3))  
=> (7 11)  
  
mapcar( 'list '(a b c) '(1 2 3) '(x y z) )  
=> ((a 1 x) (b 2 y) (c 3 z))  
  
mapcar( lambda( (x) plus( x 1 )) '(2 4 6) )  
=> (3 5 7)
```

Cadence SKILL Language Reference

Flow Control Functions

Related Topics

Flow Control Functions

map

mapc

mapcan

mapcon

maplist

nconc

mapcon

```
mapcon(  
    u_func  
    l_arg1  
    [ l_arg2 ]  
)  
=> l_result
```

Description

Applies the function *u_func* to successive sublists of the lists and returns a concatenated list.

Arguments

| | |
|---------------|--|
| <i>u_func</i> | Specifies the function to be applied to the given list. Must accept lists as arguments. The result of calling <i>u_func</i> can be of any data type. |
| <i>l_arg1</i> | Specifies the argument list to be processed |
| <i>l_arg2</i> | Additional argument lists, which must be the same length as <i>l_arg1</i> |

Value Returned

| | |
|-----------------|---|
| <i>l_result</i> | Returns a concatenated list that results from calling the <i>u_func</i> on the cons cells of the given list |
|-----------------|---|

Examples

```
mapcon((lambda (x)  
  (printf "x = %L\n" x)  
  (list (car x) (add1 (car x))))) '(1 2 3 4)); lambda: (u_func) with one argument  
x = (1 2 3 4)  
x = (2 3 4)  
x = (3 4)  
x = (4)  
result: (1 2 2 3 3 4 4 5)  
mapcon((lambda (x y) (printf "x = %L y = %L\n" x y)  
  (list (car x) (add1 (car y)))))  
  '(1 2 3 4)
```


Cadence SKILL Language Reference

Flow Control Functions

```
'(4 3 2 1)
) ; lambda: (u_func) is with 2 arguments
x = (1 2 3 4) y = (4 3 2 1)
x = (2 3 4) y = (3 2 1)
x = (3 4) y = (2 1)
x = (4) y = (1)
result : (1 5 2 4 3 3 4 2)
```

Related Topics

Flow Control Functions

map

mapc

mapcan

maplist

nconc

mapinto

```
mapinto(  
    l_resultSequence  
    g_function  
    ({l_sequences}*)  
)  
=> l_resultSequence
```

Description

Applies *g_function* to the elements of *l_sequences* and destructively modifies the *l_resultSequence*. The first argument is a sequence that receives the results of the mapping. If *l_resultSequence* and the other argument sequences are not all of the same length, the mapping stops when the shortest of *l_resultSequence* or *l_sequences* is exhausted.

If *l_resultSequence* is longer than *l_sequences*, extra elements at the end of *l_resultSequence* are unchanged.

Note: If you specify `nil` as the *l_resultSequence*, no mapping is performed since `nil` is a sequence of length zero.

Arguments

| | |
|-------------------------|--|
| <i>l_resultSequence</i> | A sequence that receives the results of the mapping. |
| <i>g_function</i> | Function (symbol or funobj) that takes as many arguments as there are sequences. |
| <i>l_sequences</i> | Several lists. Each element of these lists is used as an argument of <i>g_function</i> . |

Value Returned

l_resultSequence Updated first argument list.

Examples

```
mapinto ('(1 2 3 4) 'plus )  
=>(1 2 3 4)  
mapinto (' (1 2 3 4) 'plus ())  
=>(1 2 3 4)
```

Cadence SKILL Language Reference

Flow Control Functions

```
a = '(1 2 3 4 5)
mapinto ( a 'plus '(1 1 1) '(1 1))
=>(2 2 3 4 5)
```

Related Topics

[Flow Control Functions](#)

maplist

```
maplist(  
    u_func  
    l_arg1  
    [ l_arg2 ... ]  
)  
=> l_result
```

Description

Applies a function to successive *sublists* of the argument lists and returns a list of the corresponding results. All of the lists should have the same length.

The returned values of the successive function calls are concatenated using the function `list`.

Arguments

| | |
|---------------|--|
| <i>u_func</i> | Function to be applied to argument lists. Must accept lists as arguments. The result of calling <i>u_func</i> can be of any data type. |
| <i>l_arg1</i> | Argument list. |
| <i>l_arg2</i> | Additional argument lists, which must be the same length as <i>l_arg1</i> . |

Value Returned

| | |
|-----------------|--|
| <i>l_result</i> | A list of the results returned from calling <i>u_func</i> on successive sublists of the argument list. |
|-----------------|--|

Examples

```
maplist( 'length ' (1 2 3) )  
=> (3 2 1)  
  
maplist( 'list '(a b c) '(1 2 3) )  
=> (((a b c) (1 2 3)) ((b c) (2 3)) ((c) (3)))
```

Related Topics

[Flow Control Functions](#)

Cadence SKILL Language Reference

Flow Control Functions

map

mapc

mapcan

mapcar

nconc

not

```
not(  
    g_obj  
)  
=> t / nil
```

Description

Same as the `!` operator. Returns `t` if the object is `nil`, and returns `nil` otherwise.

Arguments

| | |
|--------------|-------------------|
| <i>g_obj</i> | Any SKILL object. |
|--------------|-------------------|

Value Returned

| | |
|------------------|---|
| <code>t</code> | If <i>g_obj</i> is <code>nil</code> . |
| <code>nil</code> | If <i>g_obj</i> is not <code>nil</code> . |

Examples

```
(not nil)  
=> t  
(not 123)  
=> nil  
(not t)  
=> nil
```

Related Topics

[Flow Control Functions](#)

[null](#)

regExitAfter

```
regExitAfter(  
    s_name  
)  
=> t / nil
```

Description

Registers the action to be taken after the `exit` function has performed its bookkeeping tasks but before it returns control to the operating system.

Arguments

| | |
|---------------|---|
| <i>s_name</i> | Name of the function that is to be added to the head of the list of functions to be performed after the <code>exit</code> function. |
|---------------|---|

Value Returned

| | |
|------------------|---|
| <code>t</code> | The function is added to the list of functions. |
| <code>nil</code> | The function is not added to the list of functions. |

Examples

```
procedure( foo( @rest args)  
    println( "After proc being executed"))  
regExitAfter( 'foo)  
=> t
```

Related Topics

[Flow Control Functions](#)

[clearExitProcs](#)

[exit](#)

[regExitBefore](#)

[remExitProc](#)

regExitBefore

```
regExitBefore(  
    s_name  
)  
=> t
```

Description

Registers the action to be taken before the `exit` function is executed. If the function registered returns the `ignoreExit` symbol, the exit is aborted.

Arguments

| | |
|---------------|---|
| <i>s_name</i> | Name of the function that is to be added to the head of the list of functions to be executed before the <code>exit</code> function. |
|---------------|---|

Value Returned

| | |
|----------|---|
| <i>t</i> | The function registered returns the <code>ignoreExit</code> symbol and aborts exit. |
|----------|---|

Examples

```
procedure( foo() println( "Aborting exit") 'ignoreExit)  
=> foo  
regExitBefore('foo)  
=> t  
exit                                ;Does not exit.  
"Aborting exit"  
  
procedure( foo() println( "Exiting"))  
=> foo  
exit                                ;Exits program.  
"Exiting"
```

Related Topics

[Flow Control Functions](#)

[clearExitProcs](#)

[exit](#)

Cadence SKILL Language Reference

Flow Control Functions

regExitBefore

remExitProc

remExitProc

```
remExitProc(  
    s_name  
)  
=> t
```

Description

Removes a registered exit procedure.

When SKILL exits, the function is not called.

The exit procedure must have been previously registered with the `regExitBefore` or `regExitAfter` function.

Arguments

| | |
|---------------|--|
| <i>s_name</i> | Name of the registered exit procedure to be removed. |
|---------------|--|

Value Returned

| | |
|---|---|
| t | The registered exit procedure is removed. |
|---|---|

Examples

```
remExitProc('endProc)  
=> t
```

Related Topics

[Flow Control Functions](#)

[exit](#)

[regExitBefore](#)

[regExitAfter](#)

return

```
return(  
    [ g_result ]  
)  
=> g_result / nil
```

Description

Forces the enclosing `prog` to exit and returns the given value. The `return` statement has meaning only when used inside a `prog` statement.

Both `go` and `return` are not purely functional in the sense that they transfer control in a non-standard way. That is, they don't return to their caller.

Arguments

g_result Any SKILL object.

Value Returned

The enclosing `prog` statement exits with the value given to `return` as the `prog`'s value. If `return` is called with no arguments, `nil` is returned as the enclosing `prog`'s value.

Examples

```
procedure( summation(l)  
    prog( (sum temp)  
        sum = 0  
        temp = l  
        while( temp  
            if( null(car(temp))  
            then  
                return(sum)  
            else  
                sum = sum + car(temp)  
                temp = cdr(temp)  
            )  
        )  
    )  
)
```

Returns the summation of previous numbers if a `nil` is encountered.

```
summation( '(1 2 3 nil 4))  
=> 6                                      ; 1+2+3  
  
summation( '(1 2 3 4))  
=> nil                                   ; prog returns nil if no explicit return)
```

Related Topics

Flow Control Functions

nlambda

go

setof

```
setof(  
    s_formalVar  
    l_valueList  
    g_predicateExpression  
)  
=> l_result  
  
setof(  
    ( s_formalVar1... s_formalVarN )  
    l_valueList1 ... l_valueListN  
    g_predicateExpression  
)  
=> l_valueList / l_result  
  
setof(  
    s_formalVar  
    o_table  
    g_predicateExpression  
)  
=> l_result
```

Description

Returns a new list containing only those elements in a list or the keys in an association table that satisfy an expression. This is a syntax form.

The `setof` form can also be used to identify all keys in an association table that satisfy the specified expression.

Arguments

s_formalVar

s_formalVar1...*s_formalVarN*

Local variable that is usually referenced in
g_predicateExpression.

l_valueList

l_valueList1...*l_valueListN*

List of elements that are bound to *s_formalVar* one at a time.

g_predicateExpression

SKILL expression that usually uses the value of *s_formalVar*.

Cadence SKILL Language Reference

Flow Control Functions

o_table Association table whose keys are bound to *s_formalVar* one at time.

Value Returned

l_result New list containing only those elements in *l_valueList* that satisfy *g_predicateExpression*, or list of all keys that satisfy the specified expression.

Examples

```
setof( x '(1 2 3 4) (x > 2) )
=> (3 4)
setof( x '(1 2 3 4) (x < 3) )
=> (1 2)
setof( (x y) '(1 2 3) '(4 5 6) oddp(x) && evenp(y) )
=> (1 3)
myTable = makeTable("atable" 0)
=> table:atable
myTable["a"]="first"
=> "first"
myTable["b"]=2
=> 2
setof(key myTable (and (stringp key) (stringp myTable[key])))
=> ("a")
```

Related Topics

Flow Control Functions

setofs

```
setofs(  
    s_formalVar  
    l_valueList  
    g_predicateExpression  
)  
=> l_result  
  
setofs(  
    ( s_formalVar1... s_formalVarN )  
    l_valueList1 ... l_valueListN  
    g_predicateExpression  
)  
=> l_valueList / l_result  
  
setofs(  
    s_formalVar  
    o_table  
    g_predicateExpression  
)  
=> l_result
```

Description

Returns a new list containing only those elements in a list or the keys in an association table that satisfy an expression. In the SKILL++ mode, this function always locally wraps the loop or iterator local variable (*s_formalVar*) in a `let` block while compiling the code. Local wrapping preserves the lexical scope of the loop variable. This function may work slower than its non-wrapped counterpart `setof`. This is a syntax form.

The `setof` form can also be used to identify all keys in an association table that satisfy the specified expression.

Arguments

s_formalVar

s_formalVar1...*s_formalVarN*

Local variable that is usually referenced in
g_predicateExpression.

l_valueList

l_valueList1...*l_valueListN*

List of elements that are bound to *s_formalVar* one at a time.

Cadence SKILL Language Reference

Flow Control Functions

g_predicateExpression

SKILL expression that usually uses the value of *s_formalVar*.

o_table

Association table whose keys are bound to *s_formalVar* one at time.

Value Returned

l_result

New list containing only those elements in *l_valueList* that satisfy *g_predicateExpression*, or list of all keys that satisfy the specified expression.

Examples

```
procedure (SetofScopingIssue (x)
  procedure (checkValue (candidate)
    candidate==x
  )
  setof(x ' (1 2 3 4 5)
    checkValue(x)
  )
)
```

```
SetofScopingIssue(3) => (1 2 3 4 5)
```

Whereas using `setofs`:

```
procedure (SetofScopingIssue (x)
  procedure (checkValue (candidate)
    candidate==x
  )
  setofs(x ' (1 2 3 4 5)
    checkValue(x)
  )
)
```

```
SetofScopingIssue(3) => (3)
```

Related Topics

[Flow Control Functions](#)

throw

```
throw(  
    s_tag  
    g_value  
)  
=>
```

Description

Transfers the control back to the return point established in a catch block. The argument value is used as the value to be passed. The `throw` function should always be used inside `catch(. . . g_form . . .)`.

Arguments

| | |
|----------------|---|
| <i>s_tag</i> | Specifies the return point in a catch block |
| <i>g_value</i> | Evaluates forms and saves the results. If the form produces multiple values, then all the values are saved. The saved results are returned as the value or values of catch. |

Value Returned

Transfers the control back to the return point in a catch block

Examples

```
catch( 'problem  
    begin(  
        throw( 'problem  
                let( nil  
                    printf( "Caught %L\n" 1) 1  
                )  
            )  
        2  
    )  
)  
Caught 1 ; message is printed . . .  
=> 1 ; value returned by throw()
```

unless

```
unless(  
    g_condition  
    g_expr1 ...  
)  
=> g_result / nil
```

Description

Evaluates a condition. If the result is true (non-`nil`), it returns `nil`; otherwise evaluates the body expressions in sequence and returns the value of the last expression. This is a syntax form.

The semantics of this function can be read literally as "unless the condition is true, evaluate the body expressions in sequence".

Arguments

| | |
|--------------------|-----------------------|
| <i>g_condition</i> | Any SKILL expression. |
| <i>g_expr1</i> | Any SKILL expression. |

Value Returned

| | |
|------------------|---|
| <i>g_result</i> | Value of the last expression of the sequence <i>g_expr1</i> if <i>g_condition</i> evaluates to <code>nil</code> . |
| <code>nil</code> | If <i>g_condition</i> evaluates to non- <code>nil</code> . |

Examples

```
x = -123  
unless( x >= 0 println("x is negative") -x)  
=> 123 ;Prints "x is negative" as side effect.  
unless( x < 0 println("x is positive") x)  
=> nil
```

Related Topics

Flow Control Functions

cond

Cadence SKILL Language Reference

Flow Control Functions

if

when

when

```
when(  
    g_condition  
    g_expr1 ...  
)  
=> g_result / nil
```

Description

Evaluates a condition. If the result is non-`nil`, evaluates the sequence of expressions and returns the value of the last expression. This is a syntax form.

If the result of evaluating *g_condition* is `nil`, `when` returns `nil`.

Arguments

| | |
|--------------------|-----------------------|
| <i>g_condition</i> | Any SKILL expression. |
| <i>g_expr1</i> | Any SKILL expression. |

Value Returned

| | |
|------------------|--|
| <i>g_result</i> | Value of the last expression of the sequence <i>g_expr1</i> if <i>g_condition</i> evaluates to non- <code>nil</code> . |
| <code>nil</code> | If the <i>g_condition</i> expression evaluates to <code>nil</code> . |

Examples

```
x = -123  
when( x < 0  
    println("x is negative")  
    -x)  
=> 123 ;Prints "x is negative" as side effect.  
when( x >= 0  
    println("x is positive")  
    x)  
=> nil
```

Related Topics

[Flow Control Functions](#)

Cadence SKILL Language Reference

Flow Control Functions

cond

if

unless

while

```
while(  
    g_condition  
    g_expr1 ...  
)  
=> t
```

Description

Repeatedly evaluates a condition and sequence of expressions until the condition evaluates to false. This is a syntax form.

Repeatedly evaluates *g_condition* and the sequence of expressions *g_expr1* ... if the condition is true. This process is repeated until *g_condition* evaluates to false (*nil*). Because this form always returns *t*, it is principally used for its side-effects.

Arguments

| | |
|--------------------|-----------------------|
| <i>g_condition</i> | Any SKILL expression. |
| <i>g_expr1</i> | Any SKILL expression. |

Value Returned

| | |
|----------|---------------------------|
| <i>t</i> | Always returns <i>t</i> . |
|----------|---------------------------|

Examples

The following example, prints the digits 0 through 10.

```
i = 0  
while( (i <= 10) printf("%d\n" i++) )  
=> t
```

Related Topics

[Flow Control Functions](#)

[foreach](#)

Input Output Functions

This topic lists the SKILL functions related to input and output operations.

| | | |
|--|---|---|
| <u>close</u> | <u>compress</u> | <u>display</u> |
| <u>drain</u> | <u>ed</u> | <u>edi</u> |
| <u>edit</u> | <u>edl</u> | <u>encrypt</u> |
| <u>expandMacroDeep</u> | <u>fileLength</u> | <u>fileSeek</u> |
| <u>fileTell</u> | <u>fileTimeModified</u> | <u>fprintf</u> |
| <u>fscanf, scanf, sscanf</u> | <u>get_filename</u> | <u>getc</u> |
| <u>getDirFiles</u> | <u>getOutstring</u> | <u>gets</u> |
| <u>include</u> | <u>infile</u> | <u>info</u> |
| <u>inportp</u> | <u>instring</u> | <u>isExecutable</u> |
| <u>isFile</u> | <u>isFileEncrypted</u> | <u>isFileName</u> |
| <u>IsLargeFile</u> | <u>isLink</u> | <u>isPortAtEOF</u> |
| <u>isReadable</u> | <u>isWritable</u> | <u>lineread</u> |
| <u>linereadstring</u> | <u>load</u> | <u>loadi</u> |
| <u>loadPort</u> | <u>loadstring</u> | <u>makeTempFileName</u> |
| <u>newline</u> | <u>numOpenFiles</u> | <u>openportp</u> |
| <u>outfile</u> | <u>outportp</u> | <u>outstring</u> |
| <u>portp</u> | <u>pprint</u> | <u>print</u> |
| <u>printf</u> | <u>printlev</u> | <u>println</u> |
| <u>putc</u> | <u>read</u> | <u>readTable</u> |
| <u>renameFile</u> | <u>simplifyFilename</u> | <u>simplifyFilenameUnique</u> |
| <u>truename</u> | <u>which</u> | <u>write</u> |

writeTable

close

```
close(  
    p_port  
)  
=> t
```

Description

Drains, closes, and frees a port. When a file is closed, it frees the FILE* associated with *p_port*. Do not use this function on *piport*, *poport*, *stdin*, *stdout*, and *stderr*.

Arguments

| | |
|---------------|------------------------|
| <i>p_port</i> | Name of port to close. |
|---------------|------------------------|

Value Returned

| | |
|---|----------------------------------|
| t | The port is closed successfully. |
|---|----------------------------------|

Examples

```
p = outfile("~/test/myFile")  
=> port:"~/test/myFile"  
close(p)  
=> t
```

Related Topics

outfile

infile

drain

compress

```
compress(  
    t_sourceFile  
    t_destFile  
)  
=> t / error message
```

Description

Reduces the size of a SKILL file, which must be SKILL source code, and places the output into another file.

Compression renders the data less readable because indentation and comments are lost. The command sets the switch `fullPrecision` to `t` to retain floating point number precision while saving the file. It is not the same as encrypting the file because the representation of `t_destFile` is still in ASCII format. This process does not remove the source file.

Arguments

| | |
|---------------------------|--------------------------------|
| <code>t_sourceFile</code> | Name of the SKILL source file. |
| <code>t_destFile</code> | Name of the destination file. |

Value Returned

| | |
|----------------------------|--|
| <code>t</code> | Function executes successfully. |
| <code>error message</code> | Signals an error if problems are encountered compressing the file. |

Examples

```
compress( "triad.il" "triad_cmp.il")  
=> t
```

Related Topics

[encrypt](#)

display

```
display(  
    g_obj  
    [ p_port ]  
)  
=> t / nil
```

Description

Writes a representation of an object to the given port.

Strings that appear in the written representation are not enclosed in double quotes, and no characters are escaped within those strings.

Arguments

| | |
|---------------|---|
| <i>g_obj</i> | Any SKILL object. |
| <i>p_port</i> | Optional output port. <code>poport</code> is the default. |

Value Returned

| | |
|------------|---|
| <i>t</i> | Usually ignored. Function is for side effects only. |
| <i>nil</i> | Usually ignored. Function is for side effects only. |

Examples

The side effect is to display `Hello!` to `poport`.

```
(display "Hello!")  
=> t
```

Related Topics

[drain](#)

[print](#)

[write](#)

drain

```
drain(  
    [ p_outputPort ]  
)  
=> t / nil
```

Description

Writes out all characters that are in the output buffer of a port.

Analogous to `fflush` in C (plus `fsync` if the port is a file). Not all systems guarantee that the disk is updated on each write. As a result, it is possible for a set of seemingly successful writes to fail when the port is closed.

To protect your data, call `drain` after a logical set of writes to a file port. It is not recommended that you call `drain` after every write however, because this could impact your program's performance.

Arguments

| | |
|---------------------|--|
| <i>p_outputPort</i> | Port to flush output from. If no argument is given this function does nothing. |
|---------------------|--|

Value Returned

| | |
|------------|--|
| <i>t</i> | If all buffered data was successfully written out. |
| <i>nil</i> | There was a problem writing out the data, and some or all of it was not successfully written out. Signals an error if the port to be drained is an input port or has been closed. |

Examples

```
drain()  
=> t  
  
drain(poport)  
=> t  
  
myPort = outfile("/tmp/myfile")  
=> port:"/tmp/myfile"  
  
for(i 0 15 fprintf(myPort "Test output%d\n" i))  
=> t
```

Cadence SKILL Language Reference

Input Output Functions

```
system( "ls -l /tmp/myfile")
--rw-r--r-- 1 root 0 Aug12 14:44 /tmp/myFile
fileLength( "/tmp/myfile")
=> 0

drain(myPort)
=> t

fileLength( "/tmp/myfile" )
=> 230

close(myPort)
=> t

drain(myPort)
=> *Error* drain: cannot send output to a closed port - port:
    "/tmp/myfile"

drain(piport)
=> *Error* drain: cannot send output to an input port -
    port:"*stdin*"

drain(poport)
=> t

defun(handleWriteError (x)
  printf("WARNING - %L write unsuccessful\n" x) nil)
=> handleWriteError

myPort=outfile("/tmp/myfile")
=> port:"/tmp/myfile"

for(i 0 15 fprintf(myPort "%d\n" (2*i)))
=> t

if(!drain(myPort) handleWriteError(myPort) t)
=> t
```

Related Topics

[outfile](#)

[close](#)

Cadence SKILL Language Reference

Input Output Functions

ed

```
ed(  
    [ t_fileName ]  
)  
=> t / nil
```

Description

Edits the named file.

Arguments

| | |
|-------------------|--|
| <i>t_fileName</i> | File to edit. If no argument is given, defaults to the previously edited file, or <code>temp.il</code> , if there is no previous file. |
|-------------------|--|

Value Returned

| | |
|------------|---|
| <i>t</i> | The operation was successfully completed. |
| <i>nil</i> | The file does not exist or there is an error condition. |

Related Topics

[edi](#)

[edl](#)

[edit](#)

Cadence SKILL Language Reference

Input Output Functions

edi

```
edi(  
    [ t_fileName ]  
)  
=> t / nil
```

Description

Edits the named file, then includes the file into SKILL.

Arguments

| | |
|-------------------|--|
| <i>t_fileName</i> | File to edit. If no argument is given, defaults to the previously edited file, or <code>temp.il</code> , if there is no previous file. |
|-------------------|--|

Value Returned

| | |
|------------|---|
| <i>t</i> | The operation was successfully completed. |
| <i>nil</i> | The file does not exist or there is an error condition. |

Examples

```
edi( "~/myFile.il" )
```

Related Topics

[ed](#)

[edl](#)

[edit](#)

edit

```
edit(  
    S_object  
    [ g_loadFlag ]  
)  
=> x_childId
```

Description

Edits a file, function, or variable. This function only works if you are in graphical mode. This is an `nlambda` function.

`edit` brings up an editor window in a separate process and thus doesn't lock up the CIW. If the object being edited is a function that was loaded after debug mode was turned on, then `edit` opens up the file that contains the function. If the editor is `vi` or `emacs` it jumps to the start of the function. If `g_loadFlag` is `t` the file is loaded into SKILL when the editor is exited. Be sure the `editor` variable is set up properly if you are using an editor other than `vi` or `emacs`.

Arguments

| | |
|-------------------|---|
| <i>S_object</i> | If you are editing a file, the object you are editing must be a string. If you are editing a function or variable, it must be an unquoted symbol. |
| <i>g_loadFlag</i> | Determines whether to load the file after the editor window is exited. Valid values: <code>t</code> or <code>nil</code> Default: <code>nil</code> . |

Value Returned

| | |
|------------------|---|
| <i>x_childId</i> | Integer identifying the process spawned for the editor. |
|------------------|---|

Examples

Edits the `.cdsinit` file in your home directory.

```
edit( "~/cdsinit" )
```

Edits the `myFun` function.

Cadence SKILL Language Reference

Input Output Functions

```
edit ( myFun )
```

Edits the `myVar` variable and loads in the new value when the editor window is closed.

```
edit ( myVar )
```

Related Topics

[ed](#)

[edl](#)

[edi](#)

[isFile](#)

Cadence SKILL Language Reference

Input Output Functions

edl

```
edl(  
    [ t_fileName ]  
)  
=> t / nil
```

Description

Edits the named file, then loads the file into SKILL.

Arguments

| | |
|-------------------|--|
| <i>t_fileName</i> | File to edit. If no argument is given, defaults to the previously edited file, or <code>temp.il</code> , if there is no previous file. |
|-------------------|--|

Value Returned

| | |
|------------|---|
| <i>t</i> | The operation was successfully completed. |
| <i>nil</i> | The file does not exist or there is an error condition. |

Examples

```
edl( "/tmp/demo.il" )
```

Related Topics

[ed](#)

[edi](#)

[edit](#)

encrypt

```
encrypt(  
    t_sourceFile  
    t_destFile  
    [ t_password ]  
)  
=> t
```

Description

Encrypts a SKILL file and places the output into another file.

If a password is supplied, the same password must be given to the command used to reload the encrypted file.

Arguments

| | |
|---------------------|---|
| <i>t_sourceFile</i> | Name of the SKILL file you are encrypting. |
| <i>t_destFile</i> | Destination file you want the encrypted file to be placed in. |
| <i>t_password</i> | Optional password; you are asked for it before you can reload the encrypted file. |

Value Returned

| | |
|----------|--|
| <i>t</i> | When the file has been encrypted and placed in <i>t_destFile</i> . Signals an error if you fail to name a destination file or give the name of a file already present. |
|----------|--|

Examples

Encrypts the `triadb` file into the `myPlace` file with `option` as the password. Returns `t` if successful.

```
encrypt("triadb" "myPlace" "option")  
=> t  
  
encrypt("file.il" "file.ile") ; SKILL file  
encrypt("file_sc.ils" "file_sc.ilse") ; SCHEME file
```

Cadence SKILL Language Reference

Input Output Functions

Related Topics

[compress](#)

[load](#)

expandMacroDeep

```
expandMacroDeep(  
    g_form  
)  
=> g_expandedForm
```

Description

This function recursively expands all macros specified in *g_form*.

Arguments

| | |
|---------------|--------------------------------|
| <i>g_form</i> | Form that can be a macro call. |
|---------------|--------------------------------|

Value Returned

| | |
|-----------------------|---|
| <i>g_expandedForm</i> | Expanded form or the original form if the given argument is not a macro call. |
|-----------------------|---|

Examples

```
expandMacroDeep(myFunction(1 2))
```

fileLength

```
fileLength(  
    S_name  
)  
=> x_size / 0
```

Description

Determines the number of bytes in a file.

A directory is viewed just as a file in this case. Uses the current SKILL path if a relative path is given. A path that is anchored to the current directory, for example, `./`, `../`, or `../..`, and so on, is not considered as a relative path.

Arguments

| | |
|---------------|--|
| <i>S_name</i> | Name of the file you want the size of. |
|---------------|--|

Value Returned

| | |
|---------------|--|
| <i>x_size</i> | Number of bytes in the <i>S_name</i> file. |
| 0 | The file exists but is empty. Signals an error if the named file does not exist. |

Examples

Return value is system-dependent.

```
fileLength("/tmp")  
=> 1024
```

Assuming the named file exists and is 32157 bytes long.

```
fileLength("~/test/out.1")  
=> 32157
```

Related Topics

[isFile](#)

[isFileName](#)

fileSeek

```
fileSeek(  
    p_port  
    x_offset  
    x_whence  
)  
=> t / nil
```

Description

Sets the position for the next operation to be performed on the file opened on a port. The position is specified in bytes.

Arguments

| | |
|-----------------|--|
| <i>p_port</i> | Port associated with the file. |
| <i>x_offset</i> | Number of bytes to move forward (or backward with negative argument). |
| <i>x_whence</i> | Valid Values: <ul style="list-style-type: none">0 Offset from the beginning of the file.1 Offset from current position of file pointer.2 Offset from the end of the file. |

Value Returned

| | |
|------------|--|
| <i>t</i> | The operation was successfully completed. |
| <i>nil</i> | The file does not exist or the position given is out of range for an input file. |

Examples

Let the file `test.data` contain the single line of text:

```
0123456789 test xyz  
p = infile("test.data")  
=> port:"test.data"  
fileTell(p)  
=> 0
```

Cadence SKILL Language Reference

Input Output Functions

```
for(i 1 10 getc(p))
=> t    ; Skip first 10 characters

fileTell(p)
=> 10

fscanf(p "%s" s)
=> 1    ; s = "test" now

fileTell(p)
=> 15

fileSeek(p 0 0)
=> t

fscanf(p "%d" x)
=> 1    ; x = 123456789 now

fileSeek(p 6 1)
=> t

fscanf(p "%s" s)
=> 1    ; s = "xyz" now
```

Related Topics

[fileTell](#)

[isFile](#)

[isFileName](#)

fileTell

```
fileTell(  
    p_port  
)  
=> x_offset
```

Description

Returns the current offset in bytes for the file opened on a port.

Arguments

| | |
|---------------|--------------------------------|
| <i>p_port</i> | Port associated with the file. |
|---------------|--------------------------------|

Value Returned

| | |
|-----------------|---|
| <i>x_offset</i> | Current offset (from the beginning of the file) in bytes for the file opened on <i>p_port</i> . |
|-----------------|---|

Examples

Let the file `test.data` contain the single line of text:

```
0123456789 test xyz  
p = infile("test.data")  
=> port:"test.data"  
fileTell(p)  
=> 0  
for(i 1 10 getc(p))  
=> t      ; Skip first 10 characters  
fileTell(p)  
=> 10  
fscanf(p "%s" s)  
=> 1      ; s = "test" now  
fileTell(p)  
=> 15
```

Related Topics

[infile](#)

[isFile](#)

[fileSeek](#)

Cadence SKILL Language Reference

Input Output Functions

outfile

fileTimeModified

```
fileTimeModified(  
    t_filename  
)  
=> x_time / nil
```

Description

Gets the time a given file was last modified.

The return value is an internal, numeric, representation of the time the named file was last modified (for example, the number of seconds from January 1, 1970). The number, which is system-dependent, is derived from the underlying operating system. It can be affected by system environment variables and local machine setting based on the timezone. For more information on time-related settings, refer to the documentation of the operating system.

The return value is an internal, numeric, representation of the time the named file was last modified (for example, the number of seconds from January 1, 1970). The number, which is system-dependent, is derived from the underlying operating system.

Arguments

| | |
|-------------------|-----------------|
| <i>t_filename</i> | Name of a file. |
|-------------------|-----------------|

Value Returned

| | |
|---------------|---|
| <i>x_time</i> | Last time <i>t_filename</i> was modified. |
| <i>nil</i> | No file with the given name was found. |

Examples

```
fileTimeModified( "~/ .cshrc" )  
=> 787435470
```

Related Topics

[getCurrentTime](#)

fprintf

```
fprintf(  
    p_port  
    t_formatString  
    [ g_arg1 ... ]  
)  
=> t
```

Description

Writes formatted output to a port.

The `fprintf` function writes formatted output to the port given as the first argument. The optional arguments following the format string are printed according to their corresponding format specifications.

`printf` is identical to `fprintf` except that it does not take the `p_port` argument and the output is written to `poport`.

Output is right justified within a field by default unless an optional minus sign “-” immediately follows the % character, which will then be left justified. To print a percent sign, you must use two percent signs in succession. You must explicitly put `\n` in your format string to print a newline character and `\t` for a tab.

Common Output Format Specifications

| Format Specification | Type(s) of Argument | Prints |
|--|----------------------------|--|
| %d | fixnum | Integer in decimal radix |
| %o | fixnum | Integer in octal |
| %x | fixnum | Integer in hexadecimal |
| %f | flonum | Floating-point number in the style [-]ddd.ddd |
| %e | flonum | Floating-point number in the style [-]d.ddde[-]ddd |
| %g | flonum | Floating-point number in style f or e, whichever gives full precision in minimum space |
| Note: Qualifying %g with width may cause imprecise results to be printed. | | |

Cadence SKILL Language Reference

Input Output Functions

Common Output Format Specifications

| Format Specification | Type(s) of Argument | Prints |
|----------------------|---------------------|---|
| %s | string, symbol | Prints out a string (without quotes) or the print name of a symbol |
| %c | string, symbol | The first character |
| %n | fixnum, flonum | Number |
| %P | list | Point |
| %B | list | Box |
| %N | any | Prints an object in the old style, that is, does not call the <code>printself</code> function |
| %L | list | Default format for the data type Print behavior depends on the value of the <code>printpretty</code> variable: If <code>printpretty</code> is <code>nil</code> , this behaves like %N If <code>printpretty</code> is <code>non-nil</code> (default), %L uses <code>printself</code> for standard objects |
| %A | any | Prints any type of object using the <code>printself</code> representation |

The `t_formatString` argument is a conversion control string containing directives listed in the table above. The %L, %P, and %B directives ignore the width and precision fields.

```
%[-][width][.precision]conversion_code
[-]           = left justify
[width]       = minimum number of character positions
[.precision]  = number of characters to be printed
conversion_code
```

Cadence SKILL Language Reference

Input Output Functions

Arguments

| | |
|-----------------------|---|
| <i>p_port</i> | Output port to write to. |
| <i>t_formatString</i> | Characters to be printed verbatim, intermixed with format specifications prefixed by the % sign. |
| <i>g_arg1</i> | The arguments following the format string are printed according to their corresponding format specifications. |

Value Returned

| | |
|----------|--|
| <i>t</i> | Prints the formatted output and returns <i>t</i> . |
|----------|--|

Examples

```
p = outfile("power.out")
=> port:"power.out"
for(i 0 15 fprintf(p "%20d %-20d\n" 2**i 3**i))
=> t
close( p)
```

At this point the `power.out` file has the following contents.

```
1 1
2 3
4 9
8 27
16 81
32 243
64 729
128 2187
256 6561
512 19683
1024 59049
2048 177147
4096 531441
8192 1594323
16384 4782969
32768 14348907
```

The following example shows the use of %A, which calls the `printself` method.

```
defmethod(printself ((obj fixnum))
```

Cadence SKILL Language Reference

Input Output Functions

```
sprintf(nil "FIXNUM{%d}" obj));; Defines the printself method
printf("Print control A returns: %A\n" 42);; %A calls the printself method
=> Print control A returns: FIXNUM{42}
```

The following example shows the use of %L, which calls `printself` only for standard objects.

```
defmethod(printself ((obj fixnum))
  sprintf(nil "FIXNUM{%d}" obj));; Defines the printself method
  printf("Print control L returns: %L\n" 42)
=> Print control L returns: 42
```

The following example shows the use of %L, %A, and %N print controls with `printf` when printing standard objects. %A prints the same result as %L and %N does not call the `printself` method.

```
defclass(A () ());; Defines a class A
defmethod(printself ((obj A));; Defines the printself method
  sprintf(nil "OBJ_A{%L}" obj))
  printf("Print control L returns: %L\n" Instance('A))
  printf("Print control A returns: %A\n" Instance('A))
  printf("Print control N returns: %N\n" Instance('A))
=> Print control L returns: OBJ_A{stdobj@0x83bf024}
Print control A returns: OBJ_A{stdobj@0x83bf024}
Print control N returns: stdobj@0x83bf03c
```

Related Topics

[close](#)

[fscanf, scanf, sscanf](#)

[outfile](#)

[printf](#)

fscanf, scanf, sscanf

```
fscanf(  
    p_inputPort  
    t_formatString  
    [ s_var1 ... ]  
)  
=> x_items / nil  
  
scanf(  
    t_formatString  
    [ s_var1 ... ]  
)  
=> x_items / nil  
  
sscanf(  
    t_sourceString  
    t_formatString  
    [ s_var1 ... ]  
)  
=> x_items / nil
```

Description

The main difference between these functions is the source of input. `fscanf` reads input from a port according to format specifications and returns the number of items read in. `scanf` takes its input from `piport` implicitly. `scanf` only works in standalone SKILL when the `piport` is not the CIW. `sscanf` reads its input from a string instead of a port. Another difference is that whereas `sscanf` supports the width while reading floating-point numbers from the input string, `fscanf` and `scanf` do not.

The results are stored into corresponding variables in the call. The `fscanf` function can be considered the inverse function of the `fprintf` output function. The `fscanf` function returns the number of input items it successfully matched with its format string. It returns `nil` if it encounters an end of file.

The maximum size of any input string being read as a string variable for `fscanf` is currently limited to 8K. Also, the function `lineread` is a faster alternative to `fscanf` for reading SKILL objects.

If an error is found while scanning for input, only those variables read before the error will be assigned.

Cadence SKILL Language Reference

Input Output Functions

The common input formats accepted by `fscanf` are summarized below.

Common Input Format Specifications

| Format Specification | Type(s) of Argument | Scans for |
|----------------------|---------------------|---|
| <code>%d</code> | fixnum | An integer |
| <code>%f</code> | flonum | A floating-point number |
| <code>%s</code> | string | A string (delimited by spaces) in the input |

Arguments

| | |
|-----------------------------|---|
| <code>p_inputPort</code> | Input port <code>fscanf</code> reads from. The input port cannot be the CIW for <code>fscanf</code> . |
| <code>t_sourceString</code> | Input string for <code>sscanf</code> . |
| <code>t_formatString</code> | Format string to match against in the reading. |
| <code>s_var1</code> | Name of variable to store results of read. |

Value Returned

| | |
|----------------------|---|
| <code>x_items</code> | The number of input items it successfully read in. As a side-effect, the items read in are assigned to the corresponding variables specified in the call. |
| <code>nil</code> | It encounters an end of file. |

Examples

Scans for an integer and a floating-point number from the input port `p` and stores the values read in the variables `i` and `d`, respectively.

```
fscanf( p "%d %f" i d )
```

Assume a file `testcase` with one line:

```
hello 2 3 world
x = infile("testcase")
=> port:"testcase"
fscanf( x "%s %d %d %s" a b c d )
=> 4
```


Cadence SKILL Language Reference

Input Output Functions

```
(list a b c d)
=> ("hello" 2 3 "world")
```

Scans the given floating point number as `val1` (1.23) and `val2` (4) and returns the resulting number as 2 because two values were read.

```
s = "1.234"
sscanf(s "%4f%d" val1 val2)
```

Related Topics

[fprintf](#)

[lineread](#)

get_filename

```
get_filename(  
    p_port  
)  
=> s_result
```

Description

Returns the file name of a port.

Arguments

| | |
|---------------|----------------|
| <i>p_port</i> | A port object. |
|---------------|----------------|

Value Returned

| | |
|-----------------|----------------------------|
| <i>x_result</i> | The file name of the port. |
|-----------------|----------------------------|

Examples

```
aPort  
=> port:"inFile"  
get_filename( aPort )  
=> "inFile"
```

getc

```
getc(  
    [ p_inputPort ]  
)  
=> s_char
```

Description

Reads and returns a single character from an input port. Unlike the C library, the `getc` and `getchar` SKILL functions are totally unrelated.

The input port arguments for both `gets` and `getc` are optional. If the port is not given, the functions take their input from `piport`.

Arguments

| | |
|--------------------|--|
| <i>p_inputPort</i> | Input port; if not given, function defaults to <code>piport</code> . |
|--------------------|--|

Value Returned

| | |
|---------------|---|
| <i>s_char</i> | Single character from the input port in symbol form. If the character returned is a non-printable character, its octal value is stored as a symbol. |
|---------------|---|

Examples

In the following assume the file `test1.data` has its first line read as:

```
#This is the data for test1  
p = infile("test1.data")  
=> port:"test1.data"  
getc(p)  
=> \#  
getc(p)  
=> T  
getc(p)  
=> h
```

Related Topics

[gets](#)

Cadence SKILL Language Reference

Input Output Functions

getDirFiles

```
getDirFiles(  
    S_name  
)  
=> l_strings
```

Description

Returns a list of the names of all files and directories, including . and . . , in a directory.

Uses the current SKILL path for relative paths. A path that is anchored to the current directory, for example, ./, ../, or ../../.., and so on, is not considered as a relative path.

Arguments

| | |
|---------------|--|
| <i>S_name</i> | Name of the directory in either string or symbol form. |
|---------------|--|

Value Returned

| | |
|------------------|--|
| <i>l_strings</i> | List of names of all files and directories in a given directory name (including . and . .). |
| | Signals an error if the directory does not exist or is inaccessible. |

Examples

```
getDirFiles(car(getInstallPath()))  
=> ( "." ".." "bin" "cdsuser" "etc" "group" "include" "lib" "pvt" "samples" "share"  
    "test" "tools" "man" "local" )
```

Related Topics

[gets](#)

[getSkillPath](#)

getOutstring

```
getOutstring(  
    s_port)  
=> t_string / nil
```

Description

Retrieves the content of the outstring port (while it is open).

Arguments

| | |
|---------------|---|
| <i>s_port</i> | Specifies the outstring port from which the content needs to be retrieved |
|---------------|---|

Value Returned

| | |
|-----------------|--|
| <i>t_string</i> | The string read from the outstring port. |
| nil | The string cannot be read from the outstring port. |

Examples

```
s = outstring()  
= >port:"*string*"   
fprintf(s "Quick brown")  
getOutstring(s)  
=>"Quick brown"  
fprintf(s " fox jumps")  
getOutstring(s)  
=> "Quick brown fox jumps"  
fprintf(s " over the lazy dog")  
getOutstring(s)  
=> "Quick brown fox jumps over the lazy dog"  
close(s)  
getOutstring(s)  
=> nil
```

Cadence SKILL Language Reference

Input Output Functions

gets

```
gets(  
    g_variableName  
    [ p_inputPort ]  
)  
=> t_string / nil
```

Description

Reads a line from the input port and stores the line as a string in the variable. This is a macro.

The string is also returned as the value of `gets`. The terminating newline character of the line becomes the last character in the string.

Arguments

| | |
|-----------------------|--|
| <i>s_variableName</i> | Variable to store input string in. You can also specify <code>nil</code> instead of a variable name. |
| <i>p_inputPort</i> | Name of input port; <code>piport</code> is used if none is given. |

Value Returned

| | |
|------------------|---|
| <i>t_string</i> | Returns the input string when successful. |
| <code>nil</code> | When EOF is reached. <i>s_variableName</i> stores the last value returned (that is, <code>nil</code>). |

Examples

Assume the `test1.data` file has the following first two lines:

```
#This is the data for test1  
0001 1100 1011 0111  
  
p = infile("test1.data")      => port:"test1.data"  
gets(s p)                    => "#This is the data for test1\n"  
gets(s p)  
=> "0001 1100 1011 0111\n"  
s  
=> "0001 1100 1011 0111\n"  
  
var = gets(nil port) -- read into var from port  
var = gets(nil) -- read into var from <stdin>
```

Cadence SKILL Language Reference

Input Output Functions

Related Topics

[getc](#)

[getchar](#)

[infile](#)

Cadence SKILL Language Reference

Input Output Functions

include

```
include(  
    t_file)  
=> t / error
```

Description

Loads the file with name *t_file* in SKILL regardless of any errors in the file.

Arguments

| | |
|---------------|---|
| <i>t_file</i> | Name of the file you want to load; it should be a string value. |
|---------------|---|

Value Returned

| | |
|-------|---|
| t | The file loads successfully. |
| error | The file specified as <i>t_file</i> does not exist. |

Examples

```
include("./test.il")  
t  
include("")  
*WARNING* open : empty file name  
*Error* include: can't access file - ""
```


Cadence SKILL Language Reference

Input Output Functions

infile

```
infile(  
    S_fileName  
)  
=> p_inport / nil
```

Description

Opens an input port ready to read a file. Always remember to close the port when you are done.

The file name can be specified with either an absolute path or a relative path. In the latter case, current SKILL path is used if it's not `nil`. A path that is anchored to the current directory, for example, `./`, `../`, or `../..`, and so on, is not considered as a relative path.

Note: Always remember to close the port when you are done.

Arguments

| | |
|-------------------|---|
| <i>S_fileName</i> | Name of the file to be read; it can be either a string or a symbol. |
|-------------------|---|

Value Returned

| | |
|-----------------|--|
| <i>p_inport</i> | Port opened for reading the named file. |
| <i>nil</i> | The file does not exist or cannot be opened for reading. |

Examples

If such a file exists and is readable.

```
in = infile("~/test/input.il")  
=> port:"~/test/input.il"
```

If `myFile` does not exist according to the current setting of the SKILL path or exists but is not readable.

```
infile("myFile")  
=> nil  
close(in)  
=> t
```

Cadence SKILL Language Reference

Input Output Functions

Related Topics

[close](#)

[isFileName](#)

[isReadable](#)

[outfile](#)

[portp](#)

Cadence SKILL Language Reference

Input Output Functions

info

```
info(  
    t_formatString  
    [ g_args1... ]  
)  
=> nil
```

Description

Prints the formatted output to poport according to the specification.

Arguments

| | |
|-----------------------|--|
| <i>r_formatString</i> | Format specification string. |
| <i>g_args</i> | Arguments following the format string. |

Value Returned

| | |
|------------|--------------------------------------|
| <i>nil</i> | Prints the argument value to poport. |
|------------|--------------------------------------|

Examples

```
info("Hello Skill") ; prints "Hello Skill"  
Hello Skill  
nil
```

```
info("value = %d" 42) ; prints value = 42  
value = 42  
nil
```

inportp

```
inportp(  
    g_obj  
)  
=> t / nil
```

Description

Checks if an object is an input port.

Note: An input port may be closed, so if `inportp` returns `t`, that does not guarantee a successful read from the port.

Arguments

| | |
|--------------|-------------------|
| <i>g_obj</i> | Any SKILL object. |
|--------------|-------------------|

Value Returned

| | |
|------------------|--|
| <code>t</code> | The given object is an input port. |
| <code>nil</code> | The given object is not an input port. |

Examples

```
(inportp piport)  
=> t  
(inportp poport)  
=> nil  
(inportp 123)  
=> nil
```

Related Topics

[outportp](#)

instring

```
instring(  
    t_string  
)  
=> p_port
```

Description

Opens a string for reading, just as infile would open a file.

An input port that can be used to read the string is returned. *Always remember to close the port when you are done.*

Arguments

| | |
|-----------------|----------------------------------|
| <i>t_string</i> | Input string opened for reading. |
|-----------------|----------------------------------|

Value Returned

| | |
|---------------|----------------------------|
| <i>p_port</i> | Port for the input string. |
|---------------|----------------------------|

Examples

```
s = "Hello World!"  
=> "Hello World!"  
p = instring(s)  
=> port:"*string*"  
fscanf(p "%s %s" a b)  
=> 2  
a  
=> "Hello"  
b  
=> "World!"  
close(p) => t
```

Related Topics

[gets](#)

[infile](#)

isExecutable

```
isExecutable(  
    S_name  
    [ tl_path ]  
)  
=> t / nil
```

Description

Checks if you have permission to execute a file or search a directory.

A directory is executable if it allows you to name that directory as part of your path in searching files. It uses the current SKILL path for relative paths. A path that is anchored to the current directory, for example, `./`, `../`, or `../..`, and so on, is not considered as a relative path.

Arguments

| | |
|----------------|--|
| <i>S_name</i> | Name of the file or directory you want to check for execution/search permission. |
| <i>tl_path</i> | List of paths that overrides the SKILL path. |

Value Returned

| | |
|------------|---|
| <i>t</i> | If you have permission to execute the file or search the directory specified by <i>S_name</i> . |
| <i>nil</i> | The directory does not exist or you do not have the required permissions. |

Examples

```
isExecutable("/bin/ls")  
=> t  
  
isExecutable("/usr/tmp")  
=> t
```

The following example returns *nil* if `attachFiles` does not exist or is non-executable.

```
isExecutable("attachFiles")  
=> nil
```

Cadence SKILL Language Reference

Input Output Functions

Related Topics

[isFile](#)

[isReadable](#)

[isWritable](#)

isFile

```
isFile(  
    S_name  
    [ tl_path ]  
)  
=> t / nil
```

Description

Checks if a file exists and that it is not a directory.

Identical to `isFileName`, except that directories are not viewed as (regular) files. Uses the current SKILL path for relative paths. A path that is anchored to the current directory, for example, `./`, `../`, or `../..../`, and so on, is not considered as a relative path.

Arguments

| | |
|----------------|--|
| <i>S_name</i> | Path you want to check. |
| <i>tl_path</i> | List of paths that overrides the SKILL path. |

Value Returned

| | |
|-----|--|
| t | The <i>S_name</i> file exists. |
| nil | The <i>S_name</i> file does not exist. |

Examples

Assumes `DACLib` is a directory and `triadc` is a file in the current working directory and the SKILL path is `nil`. A directory is not viewed as a file in this se.

```
isFile( "DACLib")  
=> nil  
  
isFile( "triadc")  
=> t  
isFile( ".cshrc" list( "." "~" ) )  
=> t
```

Related Topics

[isFileName](#)

Cadence SKILL Language Reference

Input Output Functions

getSkillPath

isFileEncrypted

```
isFileEncrypted(  
    S_name  
)  
=> t / nil
```

Description

Checks if a file exists and is encrypted.

Similar to `isFile`, except that it returns `t` only if the file exists and is encrypted. Uses the current SKILL path for relative paths. A path that is anchored to the current directory, for example, `./`, `../`, or `../..../`, and so on, is not considered as a relative path.

Arguments

| | |
|---------------|-------------------------|
| <i>S_name</i> | File you want to check. |
|---------------|-------------------------|

Value Returned

| | |
|------------------|--|
| <code>t</code> | The <i>S_name</i> file exists and is encrypted. |
| <code>nil</code> | The <i>S_name</i> file does not exist or is not encrypted. |

Examples

```
isFileEncrypted( "~/testfns.il")  
=> nil  
  
encrypt( "~/testfns.il" "~/testfns.ile")  
isFileEncrypted( "~/testfns.ile")  
=> t
```

Related Topics

[getSkillPath](#)

[isFile](#)

isFileName

```
isFileName(  
    S_name  
    [ tl_path ]  
)  
=> t / nil
```

Description

Checks if a file or directory exists.

The file name can be specified with either an absolute path or a relative path. In the latter case, current SKILL path is used if it's not `nil`. Only the presence or absence of the name is checked. If found, the name can belong to either a file or a directory. `isFileName` differs from `isFile` in this regard. A path that is anchored to the current directory, for example, `./`, `../`, or `../..`, and so on, is not considered as a relative path.

Arguments

| | |
|----------------|---|
| <i>S_name</i> | Path you want to check. |
| <i>tl_path</i> | List of paths to override the SKILL path. |

Value Returned

| | |
|------------------|--|
| <code>t</code> | The <i>S_name</i> path exists. |
| <code>nil</code> | The <i>S_name</i> path does not exist. |

Examples

Suppose `DACLib` is a directory and `triadc` is a file in the current working directory and the SKILL path is `nil`.

```
isFileName("DACLib")  
=> t
```

A directory is just a special kind of file.

```
isFileName("triadc")  
=> t
```

Result if `triad1` does not exist in current working directory.

```
isFileName("triad1")  
=> nil
```

Cadence SKILL Language Reference

Input Output Functions

```
isFileName( ".cshrc" list( "." "~" ) )  
=> t
```

Related Topics

[isFile](#)

[getSkillPath](#)

IsLargeFile

```
isLargeFile(  
    S_name  
    [ tl_path ]  
)  
=> t / nil
```

Description

Checks if a file is a large file (with size greater than 2GB).

The file name can be specified with either an absolute path or a relative path. In the latter case, the current SKILL path is searched if it's not nil. A path that is anchored to the current directory, for example, `./`, `../`, or `../..`, and so on, is not considered as a relative path.

The SKILL path can be overridden by specifying *tl_path*.

Arguments

| | |
|----------------|---|
| <i>S_name</i> | Name of the file you want to check. |
| <i>tl_path</i> | List of paths to override the SKILL path. |

Value Returned

| | |
|------------|--|
| <i>t</i> | The <i>S_name</i> file has a size greater than 2GB. |
| <i>nil</i> | The <i>S_name</i> file has a size less than or equal to 2GB. |

Examples

```
fileLength( "largeFile" )  
=> 3072000000  
isLargeFile( "largeFile" )  
=> t
```

Related Topics

[fileLength](#)

[isFile](#)

Cadence SKILL Language Reference

Input Output Functions

isFileName

isLink

```
isLink(  
    S_name  
    [ tl_path ]  
)  
=> t / nil
```

Description

Checks if a path exists and if it is a symbolic link.

When *S_name* is a relative path, the current SKILL path is used if it's non-`nil`. A path that is anchored to the current directory, for example, `./`, `../`, or `../..`, and so on, is not considered as a relative path.

Arguments

| | |
|----------------|---|
| <i>S_name</i> | Path you want to check. |
| <i>tl_path</i> | List of paths that override the SKILL path. |

Value Returned

| | |
|------------------|---|
| <code>t</code> | The name exists and it is a symbolic link. |
| <code>nil</code> | The name exists and is not a symbolic name or if <i>S_name</i> does not exist at all. |

Examples

```
isLink("/usr/bin")  
=> nil  
  
isLink("/usr/spool")  
=> t ;Assuming it's a link to /var/spool
```

Related Topics

[isFile](#)

isPortAtEOF

```
isPortAtEOF(  
    p_port  
)  
=> t / nil
```

Description

Takes an input port and returns *t* if end-of-file (EOF) has previously been detected while reading the input port; it returns *nil* otherwise.

Arguments

| | |
|---------------|---|
| <i>p_port</i> | Input port. This must be open, otherwise the function will return an error. |
|---------------|---|

Value Returned

| | |
|------------|---|
| <i>t</i> | End-of-file (EOF) has previously been detected while reading the input port <i>p_port</i> . |
| <i>nil</i> | End-of-file (EOF) has not been reached yet. |

Examples

```
port = infile("input_file")  
while(! isPortAtEOF(port)  
    printf("%L\n" read(port))  
)  
close(port)
```


isReadable

```
isReadable(  
    S_name  
    [ tl_path ]  
)  
=> t / nil
```

Description

Checks if you have permission to read a file or list a directory. Uses the current SKILL path for relative paths. A path that is anchored to the current directory, for example, `./`, `../`, or `../..`, and so on, is not considered as a relative path.

Arguments

| | |
|----------------|--|
| <i>S_name</i> | Name of a file or directory you want to know your access permissions on. |
| <i>tl_path</i> | List of paths to override the SKILL path. |

Value Returned

| | |
|------------|--|
| <i>t</i> | If <i>S_name</i> exists and you have permission to read it (for files) or list the contents (for directories). |
| <i>nil</i> | The file does not exist or does exist, but you do not have permission to read it. |

Examples

Result if current working directory is readable.

```
isReadable("./")  
=> t
```

Result if `"~/DACLib"` is not readable or does not exist.

```
isReadable("~/DACLib")  
=> nil
```

Related Topics

[infile](#)

Cadence SKILL Language Reference

Input Output Functions

isExecutable

isFile

isWritable

isWritable

```
isWritable(  
    S_name  
    [ tl_path ]  
)  
=> t / nil
```

Description

Checks if you have permission to write to a file or update a directory. Uses the current SKILL path for relative paths. A path that is anchored to the current directory, for example, `./`, `../`, or `../..`, and so on, is not considered as a relative path.

Arguments

| | |
|----------------|--|
| <i>S_name</i> | Name of a file or directory you want to find out your write permission on. |
| <i>tl_path</i> | List of paths to search that overrides the SKILL path. |

Value Returned

| | |
|-----|---|
| t | If <i>S_name</i> exists and you have permission to write or update it. |
| nil | The file does not exist or does exist, but you do not have permission to read it. |

Examples

```
isWritable("/tmp")  
=> t
```

Result if `out.1` does not exist or there is no write permission to it.

```
isWritable("~/test/out.1")  
=> nil
```

Related Topics

[isFile](#)

[isExecutable](#)

Cadence SKILL Language Reference

Input Output Functions

isReadable

lineread

```
lineread(  
    [ p_inputPort ]  
)  
=> t / nil / l_results
```

Description

Parses the next line in the input port into a list that you can further manipulate. It is used by the interpreter's top level to read in all input and understands SKILL and SKILL++ syntax.

Only one line of input is read in unless there are still open parentheses pending at the end of the first line, or binary *infix* operators whose right-hand argument has not yet been supplied, in which case additional input lines are read until all open parentheses have been closed and all binary *infix* operators satisfied. The symbol *t* is returned if *lineread* reads a blank input line and *nil* is returned at the end of the input file.

Arguments

| | |
|--------------------|--|
| <i>p_inputPort</i> | Input port. The default is <i>piport</i> . |
|--------------------|--|

Value Returned

| | |
|------------------|--|
| <i>t</i> | If the next line read in is blank. |
| <i>nil</i> | If the input port is at the end of file. |
| <i>l_results</i> | A list of the objects read in from the next (logical) input line |

Examples

```
lineread(piport)      ; Reads in the next input expression  
f 1 2 +               ; First input line of the file being read  
3                     ; Second input line  
=> (f 1 (2 + 3))  
  
lineread(piport)      ; Another input line of the file  
f(a b c)              ; Returns a list of input objects  
=> ((f a b c))
```

Related Topics

[gets](#)

Cadence SKILL Language Reference

Input Output Functions

infile

linereadstring

linereadstring

```
linereadstring(  
    t_string  
)  
=> g_value / nil
```

Description

Executes `lineread` on a string and returns the first form read in. Anything after the first form is ignored.

Arguments

| | |
|-----------------|---------------|
| <i>t_string</i> | Input string. |
|-----------------|---------------|

Value Returned

| | |
|------------------|---|
| <i>g_value</i> | The first form (line) read in from the argument string. |
| <code>nil</code> | No form is read (that is, the argument string is all spaces). |

Examples

```
linereadstring "abc"  
=> (abc)  
linereadstring "f a b c"  
=> (f a b c)  
linereadstring "x + y"  
=> ((x + y))
```

In the following example, only the first form is read in.

```
linereadstring "f a b c\n g 1 2 3"  
=> (f a b c)
```

Related Topics

[evalstring](#)

[gets](#)

[instring](#)

[lineread](#)

load

```
load(  
    t_fileName  
    [ t_password ]  
)  
=> t
```

Description

Opens a file, repeatedly calls `lineread` to read in the file, immediately evaluating each form after it is read in. Uses the file extension to determine the language mode (`.il/.ile` for SKILL and `.ils/.ilse` for SKILL++) for processing the language expressions contained in the file. By default, the loaded code is evaluated in dynamic scoping. However, if the extension is `.ils/.ilse`, lexical scoping is used. For a SKILL++ file, the loaded code is always evaluated in the top level environment.

It closes the file when end of file is reached. Unless errors are discovered, the file is read in quietly. If `load` is interrupted by pressing `Control-c`, the function skips the rest of the file being loaded.

SKILL has an autoload feature that allows applications to load functions into SKILL on demand. If a function being executed is undefined, SKILL checks to see if the name of the function (a symbol) has a property called `autoload` attached to it. If the property exists, its value, which must be either a string or an expression that evaluates to a string, is used as the name of a file to be loaded. The file should contain a definition for the function that triggered the autoload. Execution proceeds normally after the function is defined.

Arguments

t_fileName

File to be loaded. Uses the file name extension to determine the language mode to use.

The valid values are:

- `'ils/'ilse`, which indicates that the file contains SKILL++ code.
- `'il/'ils`, which indicates that the file contains SKILL code.

t_password

Password, if *t_fileName* is an encrypted file.

Cadence SKILL Language Reference

Input Output Functions

Value Returned

t The file is successfully loaded.

Examples

```
load( "testfns.il")           ; Load file testfns.il
fn.autoload = "myfunc.il"     ; Declares an autoload property.
fn(1)
```

`fn` is undefined at this point, so this call triggers an autoload of `myfunc.il`, which contains the definition of `fn`. The function call `fn(1)` is then successfully performed.

```
fn(2)           ; fn is now defined and executes normally.
```

You might have an application partitioned into two files. Assume that `UtilsA.il` contains classic SKILL code and `UtilsB.ils` contains SKILL/SKILL++ code. The following example loads both files appropriately.

```
procedure( trLoadSystem()
  load( "UtilsA.il" )      ;;; SKILL code
  load( "UtilsB.ils" )     ;;; SKILL++ code
)                          ; procedure
```

Related Topics

[include](#)

[loadi](#)

[lineread](#)

loadi

```
loadi(  
    t_fileName  
    [ t_password ]  
)  
=> t
```

Description

Identical to `load`, except that `loadi` ignores errors encountered during the load, prints an error message, and then continues loading.

Opens the named file, repeatedly calls `lineread` to read in the file, immediately evaluates each form after it is read in, then closes the file when end of file is reached. Unlike `load`, `loadi` ignores errors encountered during the load. Rather than stopping, `loadi` causes an error message to be printed and then continues to end of file. Otherwise, `loadi` is the same as `load`.

Arguments

| | |
|-------------------------|--|
| <code>t_fileName</code> | File to be loaded, with the proper extension to specify the language mode. |
| <code>t_password</code> | Password, if <code>t_fileName</code> is an encrypted file. |

Value Returned

| | |
|----------------|---------------------|
| <code>t</code> | The file is loaded. |
|----------------|---------------------|

Examples

Loads the `testfns.il` file.

```
loadi( "testfns.il" )
```

Loads the `test.il` file from the `tmp` directory.

```
loadi( "/tmp/test.il")
```

Related Topics

[encrypt](#)

Cadence SKILL Language Reference

Input Output Functions

include

load

lineread

Cadence SKILL Language Reference

Input Output Functions

loadPort

```
loadPort (
    p_port
    [?langMode g_langMode]
    [?password g_password]
    [?ignoreErrors g_ignoreErrors])
)
=> t
```

Description

Loads a SKILL file from *p_port*.

Arguments

| | |
|-----------------------------|--|
| <i>p_port</i> | An input (SKILL) port. |
| <i>?langMode g_langMode</i> | Specifies the language mode to use regardless of the original file extension Valid values: 'ils: Loads the file in SKILL++ mode 'il: Loads the file in SKILL mode Default value: 'il |

| | |
|-----------------------------|------------------------------------|
| <i>?password g_password</i> | Password, if the file is encrypted |
|-----------------------------|------------------------------------|

| | |
|-------------------------------------|--|
| <i>?ignoreErrors g_ignoreErrors</i> | If specified, ignores errors during load |
|-------------------------------------|--|

Value Returned

| | |
|----------|---------------------------|
| <i>t</i> | Always returns <i>t</i> . |
|----------|---------------------------|

Cadence SKILL Language Reference

Input Output Functions

Examples

```
loadPort( myPort ?langMode `ils )
```

Related Topics

[load](#)

[loadi](#)

loadstring

```
loadstring(  
    t_string  
    [ s_langMode ]  
)  
=> t
```

Description

Opens a string for reading, then parses and executes expressions stored in the string, just as `load` does in loading a file.

Note: `loadstring` is different from `evalstring` in two ways: (1) it uses `lineread` mode, and (2) it always returns `t` if it evaluates successfully.

Arguments

| | |
|-------------------|--|
| <i>t_string</i> | Input string to be evaluated. |
| <i>s_langMode</i> | File to be loaded. Uses the file name extension to determine the language mode to use. The valid values are: <ul style="list-style-type: none">■ <code>'ils</code>, which indicates that the file contains SKILL++ code.■ <code>'il</code>, which indicates that the file contains SKILL code. |

Value Returned

| | |
|----------|---|
| <i>t</i> | When <i>t_string</i> has been successfully read in and evaluated. Signals an error if <i>t_string</i> is not a string, or contains ill-formed SKILL expressions. |
|----------|---|

Examples

```
loadstring "1+2"  
=> t  
loadstring "procedure( f(y) x=x+y )"  
=> t  
loadstring "x=10\n f 20\n f 30"  
=> t  
x  
=> 60
```

Cadence SKILL Language Reference

Input Output Functions

Related Topics

[evalstring](#)

[instring](#)

[load](#)

[gets](#)

makeTempFileName

```
makeTempFileName (  
    S_nameTemplate  
)  
=> t_name
```

Description

Appends a string suffix to the last component of a path template so that the resulting composite string does not duplicate any existing file name.

That is, it checks that such named file does not exist. SKILL path is not used in this checking.

The last component of the resultant path is guaranteed to be no more than 14 characters. If the original template has a long last component it is truncated from the end if needed. Also, any trailing X's (uppercase only) are removed from the template before the new string suffix is appended. You are encouraged to follow the convention of placing temporary files in the /tmp directory on your system.

Arguments

S_nameTemplate Template file name as a string or a symbol.

Value Returned

t_name Path that can be used to create a file or directory.

Examples

In the following example, trailing X's (uppercase only) are removed.

```
d = makeTempFileName("/tmp/testXXXX")  
=> "/tmp/testa00324"
```

In the following example, the name is used this time.

```
createDir(d)  
=> t
```

A new name is returned this time.

```
makeTempFileName("/tmp/test")  
=> "/tmp/testb00324"
```


Related Topics

[Input Output Functions](#)

newline

```
newline(  
    [ p_outputPort ]  
)  
=> nil
```

Description

Prints a newline (`\n`) character and then flushes the output port.

Arguments

| | |
|---------------------|--|
| <i>p_outputPort</i> | Output port. Defaults to <code>poport</code> , the standard output port. |
|---------------------|--|

Value Returned

| | |
|------------------|--|
| <code>nil</code> | Prints a newline and then returns <code>nil</code> . |
|------------------|--|

Examples

```
print("Hello") newline() print("World!")  
"Hello"  
"World!"  
=> nil
```

Related Topics

[drain](#)

[fprintf](#)

[outfile](#)

numOpenFiles

```
numOpenFiles (
    )
=> ( x_current x_maximum )
```

Description

Returns the number of files now open and the maximum number of files that a process can open. The numbers are returned as a two-element list.

Arguments

None

Value Returned

| | |
|------------------|--|
| <i>x_current</i> | Number of files that are currently open. |
| <i>x_maximum</i> | Maximum number of files that a process can open. This is usually platform-dependent. |

Examples

Result is system-dependent.

```
numOpenFiles()          => (6 64)
```

One more file is opened.

```
f = infile("/dev/null")  => port:"/dev/null"
numOpenFiles()          => (7 64)
```

Related Topics

[close](#)

[infile](#)

[outfile](#)

openportp

```
openportp(  
    g_obj  
)  
=> t / nil
```

Description

Checks if the given argument is a port object and it is open (for input or output), *nil* otherwise.

Arguments

| | |
|--------------|-------------------|
| <i>g_obj</i> | Any SKILL object. |
|--------------|-------------------|

Value Returned

| | |
|------------|--|
| <i>t</i> | If <i>g_obj</i> is a port and it is open for input or output. |
| <i>nil</i> | If <i>g_obj</i> is not a port and it is not open for input or output.. |

Examples

```
(portp ip = (infile "inFile"))  
=> t  
(portp op = (outfile "outFile"))  
=> t  
(openportp ip)  
=> t  
(openportp op)  
=> t  
(close ip)  
=> t  
(openportp ip)  
=> nil  
(close op)  
=> t  
(openportp op)  
=> nil
```

Related Topics

[Input Output Functions](#)

outfile

```
outfile(  
    S_fileName  
    [ t_mode ]  
    [ g_openHiddenFile ]  
)  
=> p_outport / nil
```

Description

Opens an output port ready to write to a file.

The file can be specified with either an absolute path or a relative path. If a relative path is given and the current SKILL path setting is not `nil`, all directory paths from SKILL path are checked in order, for that file. A path that is anchored to the current directory, for example, `./`, `../`, or `../..`, and so on, is not considered as a relative path. If found, the system overwrites the first updatable file in the list. If no updatable file is found, it places a new file of that name in the first writable directory.

If the optional *g_openHiddenFile* argument (which is intended to be used on Windows only) is specified, the system will be forced to open a Windows hidden file. The *g_openHiddenFile* must be used for opening existing Windows hidden files only. If the named Windows hidden file does not exist (including the current SKILL path), `outfile` will fail. In addition, the *t_mode* option must also be specified (to either `w` or `a` only) if *g_openHiddenFile* is given.

Arguments

| | |
|-------------------------|--|
| <i>S_fileName</i> | Name of the file to open or create. |
| <i>t_mode</i> | If the mode string <i>t_mode</i> is specified, the file is opened in the mode requested. If <i>t_mode</i> is <code>a</code> , an existing file is opened in append mode. If it is <code>w</code> , a new file is created for writing (any existing file is overwritten). The default is <code>w</code> . |
| <i>g_openHiddenFile</i> | If specified to non-nil, the named Windows hidden file is forced to open. This argument must be used for Windows hidden files only. |

Value Returned

| | |
|------------------|--|
| <i>p_outport</i> | An output port ready to write to the specified file. |
|------------------|--|

Cadence SKILL Language Reference

Input Output Functions

`nil`

If the named file cannot be opened for writing or the named Windows hidden file does not exist (including the current SKILL path).

An error is signaled if an illegal mode string is supplied.

Examples

```
p = outfile("/tmp/out.il" "w")
=> port:"/tmp/out.il"
outfile("/bin/ls")
=> nil
```

To force opening a Windows hidden file `t_mode` must also be specified.

```
outfile( "aHiddenFile" "w" t)
```

Related Topics

[close](#)

[drain](#)

[getSkillPath](#)

[infile](#)

outportp

```
outportp(  
    g_obj  
)  
=> t / nil
```

Description

Checks if an object is an output port.

Note: An output port may be closed, so if `outportp` returns `t`, that does not guarantee a successful write to the port.

Arguments

| | |
|--------------|-------------------|
| <i>g_obj</i> | Any SKILL object. |
|--------------|-------------------|

Value Returned

| | |
|------------------|---|
| <code>t</code> | The given object is an output port. |
| <code>nil</code> | The given object is not an output port. |

Examples

```
(outportp poport)  
=> t  
(outportp piport)  
=> nil  
(outportp 123)  
=> nil
```

Related Topics

[inportp](#)

outstring

```
outstring(  
    )  
=> p_openedPort / nil
```

Description

Takes no arguments and returns an opened output port for strings (or an output). After a port is opened, it can be used with functions, such as `fprintf`, `println`, and `close` that write to an output port. You need to use the `getOutstring` function to retrieve the content of output port (while it is open).

You can use the `close` function to close the output port.

Arguments

None

Value Returned

| | |
|---------------------------|---------------------------|
| <code>p_openedPort</code> | The opened output port |
| <code>nil</code> | The port cannot be opened |

Examples

```
s = outstring() ; string port opened for output  
=> port:s  
fprintf(s "the value is %d" 1) ; fprintf into string  
getOutstring(s)  
=> the value is 1  
close(s)  
getOutstring(s)  
=> nil
```

Related Topics

[Input Output Functions](#)

portp

```
portp(  
    g_value  
)  
=> t / nil
```

Description

Checks if an object is an input or output port.

The suffix *p* is usually added to the name of a function to indicate that it is a predicate function.

Arguments

| | |
|----------------|----------------|
| <i>g_value</i> | A data object. |
|----------------|----------------|

Value Returned

| | |
|------------|--|
| <i>t</i> | If <i>g_value</i> is an input or output port, whose type name is <i>port</i> . |
| <i>nil</i> | If <i>g_value</i> is not an input or output port. |

Examples

```
portp( piport )  
=> t  
portp( 3.0 )  
=> nil
```

Related Topics

[infile](#)

[outfile](#)

pprint

```
pprint(  
    g_value  
    [ p_outputPort ]  
)  
=> nil
```

Description

Identical to `print` except that it pretty prints the value whenever possible.

The `pprint` function is useful, for example, when printing out a long list where `print` prints the list on one (possibly huge) line but `pprint` limits the output on a single line and produces a multiple line printout if necessary. This output is much more readable.

`pprint` does not work the same as the `pp` function. `pp` is an `nlambda` and only takes a function name whereas `pprint` is a `lambda` and takes an arbitrary SKILL object.

Arguments

| | |
|---------------------------|---|
| <code>g_value</code> | Any SKILL value to be printed. |
| <code>p_outputPort</code> | Output port to print to. Default is <code>poport</code> . |

Value Returned

| | |
|------------------|--|
| <code>nil</code> | Prints the argument value (to the given port). |
|------------------|--|

Examples

```
pprint '(1 2 3 4 5 6 7 8 9 0 a b c d e f g h i j k)  
(1 2 3 4 5  
  6 7 8 9 0  
  a b c d e  
  f g h i j  
  k  
)  
=> nil
```

Related Topics

[print](#)

print

```
print(  
    g_value  
    [ p_outputPort ]  
)  
=> nil
```

Description

Prints a SKILL object using the default format for the data type of the value.

For example, strings are enclosed in double quotes. Same as `println`, except no newline character is printed.

Arguments

| | |
|---------------------|--|
| <i>g_value</i> | Any SKILL object. |
| <i>p_outputPort</i> | Output port to print to. Default is <code>oport</code> . |

Value Returned

| | |
|------------------|---|
| <code>nil</code> | Always returns <code>nil</code> after printing out the object supplied. |
|------------------|---|

Examples

```
print("hello")  
"hello"  
=> nil
```

Related Topics

[pprint](#)

[println](#)

[printlev](#)

printf

```
printf(  
    t_formatString  
    [ g_arg1 ... ]  
)  
=> t
```

Description

Writes formatted output to `poport`.

The optional arguments following the format string are printed according to their corresponding format specifications.

`printf` is identical to `fprintf` except that it does not take the `p_port` argument and the output is written to `poport`.

Arguments

| | |
|-----------------------|---|
| <i>t_formatString</i> | Characters to be printed verbatim, intermixed with format specifications prefixed by the % sign. |
| <i>g_arg1</i> | Arguments following the format string are printed according to their corresponding format specifications. |

Value Returned

| | |
|----------|--|
| <i>t</i> | Prints the formatted output and returns <i>t</i> . |
|----------|--|

Examples

```
x = 197.9687 => 197.9687  
printf("The test measures %10.2f.\n" x)
```

Prints the following line to `poport` and returns *t*.

```
The test measures          197.97.  
=> t
```

Related Topics

Common Output Format Specifications

Cadence SKILL Language Reference

Input Output Functions

fprintf

println

printlev

```
printlev(  
    g_value  
    x_level  
    x_length  
    [ p_outputPort ]  
)  
=> nil
```

Description

Prints a list with a limited number of elements and levels of nesting.

Lists are normally printed in their entirety no matter how many elements they have or how deeply nested they are. Applications have the option, however, of setting upper limits on the number of elements and the levels of nesting shown when printing lists. These limits are sometimes necessary to control the volume of interactive output because the SKILL top-level automatically prints the results of expression evaluation. Limits can also protect against the infinite looping on circular lists possibly created by programming mistakes.

Two integer variables, print length and print level (specified by *x_length* and *x_level*), control the maximum number of elements and the levels of nesting that are printed. List elements beyond the maximum specified by print length are abbreviated as “. . .” and lists nested deeper than the maximum level specified by print level are abbreviated as &. Both print length and print level are initialized to *nil* (meaning no limits are imposed) by SKILL, but each application is free to set its own limits.

The *printlev* function is identical to *print* except that it takes two additional arguments specifying the maximum level and length to be used in printing the expression.

Arguments

| | |
|---------------------|---|
| <i>g_value</i> | Any SKILL value. |
| <i>x_level</i> | Specifies the level of nesting that you want to print; lists nested deeper than the maximum level specified are abbreviated as “&”. |
| <i>x_length</i> | Specifies the length (or maximum number of elements) you want to print. List elements beyond the maximum specified here are abbreviated as “. . .”. |
| <i>p_outputPort</i> | Output port. Default is <i>poport</i> . |

Cadence SKILL Language Reference

Input Output Functions

Value Returned

`nil` Prints the argument value and then returns `nil`.

Examples

```
List = '(1 2 (3 (4 (5))) 6)
=> '(1 2 (3 (4 (5))) 6)
printlev(List 100 2)
(1 2 ...)
=> nil

printlev(List 3 100)
(1 2 (3 (4 &)) 6)
=> nil

printlev(List 3 3 p)      ; Assumes port p exists.
(1 2 (3 (4 &)) ...)      ; Prints to port p.
=> nil
```

Related Topics

[list](#)

[print](#)

println

```
println(  
    g_value  
    [ p_outputPort ]  
)  
=> nil
```

Description

Prints a SKILL object using the default format for the data type of the value, then prints a newline character.

A newline character is automatically printed after printing *g_value*. `println` flushes the output port after printing each newline character.

Arguments

| | |
|---------------------|--|
| <i>g_value</i> | Any SKILL value. |
| <i>p_outputPort</i> | Port to be used for output. The default is <code>poport</code> . |

Value Returned

| | |
|------------------|--|
| <code>nil</code> | Prints the given object and returns <code>nil</code> . |
|------------------|--|

Examples

```
for( i 1 3 println( "hello" ))      ;Prints hello three times.  
"hello"  
"hello"  
"hello"  
=> t                                ;for always returns t
```

Related Topics

[drain](#)

[print](#)

[newline](#)

Cadence SKILL Language Reference

Input Output Functions

putc

```
putc(  
    x_symbol  
    p_port  
)  
=> s_symbol
```

Description

Puts the *x_symbol* to *p_port* (to complement getc function)

Arguments

| | |
|-----------------|----------------|
| <i>x_symbol</i> | Symbol number |
| <i>p_port</i> | An output port |

Value Returned

| | |
|-----------------|-------------------------|
| <i>s_symbol</i> | The symbol that was put |
|-----------------|-------------------------|

Examples

```
putc(1 poport)  
=> \001
```

Related Topics

[Input Output Functions](#)

read

```
read(  
    [ p_inputPort ]  
)  
=> g_result / nil / t
```

Description

Parses and returns the next expression from an input port.

Returns the next expression regardless of how many lines the expression takes up - even if there are other expressions on the same line. If the next line is empty, returns `t`. If the port is positioned at end of file, then it returns `nil`.

Arguments

| | |
|--------------------|--|
| <i>p_inputPort</i> | Input port. Default is <code>piport</code> . |
|--------------------|--|

Values Returned

| | |
|------------------|--------------------------------------|
| <i>g_result</i> | The object read in. |
| <code>nil</code> | When the port is at the end of file. |
| <code>t</code> | If an empty line is encountered. |

Examples

Suppose the file `SkillSyntaxFile.il` contains the following expressions. A blank line follows the second expression:

```
define( x 1 )  
define( y 2 )  
procedure( add( x y ) x+y )  
  
myPort = infile( "SkillSyntaxFile.il" )  
=> port:SkillSyntaxFile.il"  
read( myPort )  
=> define(x 1)  
read( myPort )  
=> define(y 2)  
read( myPort )  
=> t  
read( myPort )  
=> procedure((add x y) (x + y) )  
read( myPort )
```

Cadence SKILL Language Reference

Input Output Functions

```
=> nil  
close( myPort )  
=> t
```

Related Topics

[lineread](#)

readTable

```
readTable(  
    S_fileName  
    o_table  
)  
=> t / nil
```

Description

Reads and appends the contents of a file to an existing association table.

Prerequisites

The file submitted must have been created with the `writeTable` function so that the contents are in a usable format.

Arguments

| | |
|-------------------|--|
| <i>S_fileName</i> | File name (either a string or symbol) from which to read the data. |
| <i>o_table</i> | Association table to which the file contents are appended. |

Value Returned

| | |
|------------|------------------------------------|
| <i>t</i> | The data is read and appended. |
| <i>nil</i> | The data is not read and appended. |

Examples

```
myTable = makeTable("table1")  
=> table:table1  
myTable2 = makeTable("table2")  
=> table:table2  
myTable["three"] = 3  
=> 3  
writeTable("table.out" myTable)  
=> t  
readTable("table.out" myTable2)  
=> t
```

Related Topics

[makeTempFileName](#)

[writeTable](#)

renameFile

```
renameFile(  
    S_old  
    S_new  
)  
=> t / nil
```

Description:

The `renameFile()` function changes the name of a file or directory. The `S_old` argument points to the pathname of the file or directory to be renamed. The `S_new` argument points to the new pathname of the file or directory. If the SKILL path is nil, `renameFile()` would search the current directory. Otherwise, the SKILL path would be searched first for `S_old`. A path that is anchored to the current directory, for example, `./`, `../`, or `../..`, and so on, is not considered as a relative path.

Arguments:

| | |
|--------------------|--|
| <code>S_old</code> | Points to the pathname of the file or directory to be renamed. |
| <code>S_new</code> | Points to the new pathname of the file or directory. |

Value Returned

| | |
|------------------|---|
| <code>t</code> | File or directory is successfully re-named. |
| <code>nil</code> | If <code>S_old</code> path does not exist. |

Note: If you do not have sufficient privileges to rename a file or directory, the `renameFile()` function throws an error (neither returns `t` nor `nil`). You can use the `errset()` function to handle such exceptional situations. For more information on the `errset()` function, see [The errset Function](#) in the *Cadence SKILL Language User Guide*.

Example

```
renameFile( "/usr/oldname" "/usr/newName" )  
=> t  
  
renameFile( "/usr/old" "/usr/new" )  
=> nil ;if old does not exist.  
  
renameFile( "old" "new" ) ;if old is a file while new is a directory  
*Error* renameFile: is a directory  
renameFile( "/usr/old" "/usr/new" ) ; if you do not have permissions to rename old
```

Cadence SKILL Language Reference

Input Output Functions

```
*Error* renameFile: permission denied
```

Related Topics

[Input Output Functions](#)

simplifyFilename

```
simplifyFilename(  
    t_name  
    [ g_dontResolveLinks ]  
)  
=> t_result
```

Description

Expands the name of a file to its full path.

Returns the fully expanded name of the file *t_name*. Tilde expansion is performed, “.” and “..” are compressed, and redundant slashes are removed. By default, symbolic links are also resolved, unless the second (optional) argument *g_notResolveLinks* is specified to non-nil.

If *t_name* is not absolute, the current working directory is prefixed to the returned file name.

Arguments

| | |
|---------------------------|---|
| <i>t_name</i> | File to be fully expanded. |
| <i>g_dontResolveLinks</i> | If specified to non-nil, symbolic links are not resolved. |

Value Returned

| | |
|-----------------|----------------------------------|
| <i>t_result</i> | Fully expanded name of the file. |
|-----------------|----------------------------------|

Examples

Assumes the user’s home directory is `/usr/mnt/user`.

```
simplifyFilename("~/test")  
=> "/usr/mnt/user/test"
```

Assumes `/tmp/fileName` is a symbolic link of `/tmp/fileName.real`.

```
simplifyFilename("/tmp/fileName" t)  
=> "/tmp/fileName"
```


Cadence SKILL Language Reference

Input Output Functions

Related Topics

Input Output Functions

isFileName

simplifyFilenameUnique

```
simplifyFilenameUnique(  
    t_path  
)  
=> t_fullPath / error message
```

Description

Returns the full path for the given *t_path* without links and a trailing slash / at the end of the result string. The function returns an error if the given *t_path* is incorrect.

Arguments

| | |
|---------------|------------------------------|
| <i>t_path</i> | Path to a directory or file. |
|---------------|------------------------------|

Value Returned

| | |
|-------------------|--|
| <i>t_fullPath</i> | Full path for the given <i>t_path</i> without links and a trailing slash / at the end. |
|-------------------|--|

Examples

;The example below illustrates the difference between the simplifyFilename and simplifyFilenameUnique functions

```
simplifyFilename(".////")  
=> "/home/user1/"  
  
simplifyFilenameUnique(".////")  
=> "/home/user1"
```

Related Topics

[Input Output Functions](#)

truename

```
truename(  
    t_string  
)  
=> t_truename
```

Description

Tries to find the specified file (*t_string*) and returns the full path to the file.

It uses the current SKILL path for relative paths. A path that is anchored to the current directory, for example, ./, ../, or ../../., and so on, is not considered as a relative path.

Arguments

| | |
|-----------------|------------------------------------|
| <i>t_string</i> | A string specifying the file name. |
|-----------------|------------------------------------|

Value Returned

| | |
|-------------------|--|
| <i>t_truename</i> | The truename or full path of the specified file. |
|-------------------|--|

Examples

```
getSkillPath()  
=> (". " "~")  
  
setSkillPath(append1(getSkillPath() "~/skill"))  
=> nil  
  
getSkillPath()  
=> (". " "~" "~/skill")  
  
getWorkingDir()  
=> "/home/skillproj/work"  
  
truename("./runtest")  
=> "/home/skillproj/work/runtest"  
  
truename("mycode.il")  
=> "/home/skillproj/skill/mycode.il"  
  
truename(".cshrc")  
=> "/home/skillproj/.cshrc"  
  
truename("~/old/code.il")  
=> nil ; this file/directory does not exist
```

Related Topics

Input Output Functions

which

which

```
which(  
    t_fileName  
)  
=> t_fullPath / nil
```

Description

Returns the absolute path of the given context file, or regular file or directory.

The main usage of this function is to load prerequisite context files.

If *t_fileName* identifies a context file (that is with the `.cxt` extension), it looks under the standard contexts location (associated with the application in which this function is called), as well as common Cadence contexts directory, `your_install_path/tools/dfII/etc/context`, and user contexts location, `your_install_path/tools/dfII/local/context`, for the presence of the context file.

If *t_fileName* identifies a regular file or directory, the current SKILL path is searched. A path that is anchored to the current directory, for example, `./`, `../`, or `../..`, and so on, is not considered as a relative path.

Note: *t_fileName* should be a simple file or directory name, and should not contain directory separators.

Arguments

| | |
|-------------------|--|
| <i>t_fileName</i> | Name of a context file, or a regular file or directory that you want to get the absolute path. |
|-------------------|--|

Value Returned

| | |
|-------------------|--|
| <i>t_fullPath</i> | The absolute path of <i>t_fileName</i> . |
| <i>nil</i> | If <i>t_fileName</i> is not found. |

Examples

Loading a prerequisite context file:

```
loadContext( which( "myPrereq.cxt" ) )  
=> t
```

Cadence SKILL Language Reference

Input Output Functions

Get the absolute path of a file:

```
which( ".cdsinit" )  
=> "/usr/deeptik/.cdsinit"
```

Related Topics

[Input Output Functions](#)

[truename](#)

Cadence SKILL Language Reference

Input Output Functions

write

```
write(  
    g_value  
    [ p_outputPort ]  
)  
=> nil
```

Description

Prints a SKILL object using the default format for the data type of the value.

For example, strings are enclosed in ". Same as `print`.

Arguments

| | |
|---------------------|---|
| <i>g_value</i> | Any SKILL object. |
| <i>p_outputPort</i> | Output port to print to. Default is <code>poport</code> . |

Value Returned

| | |
|------------------|--|
| <code>nil</code> | Always returns <code>nil</code> , after it prints out the object supplied to it. |
|------------------|--|

Examples

```
for( i 1 3 write( "hello" ))      ;Prints hello three times.  
"hello""hello""hello"  
=> t
```

Related Topics

Input Output Functions

display

pprint

print

println

printlev

writeTable

```
writeTable(  
    S_fileName  
    o_table  
)  
=> t / nil
```

Description

Writes the contents of an association table to a file with one key/value pair per line.

Note: This function is for writing basic SKILL data types that are stored in an association table. The function cannot write database objects or other user-defined types that might be stored in association tables.

Arguments

| | |
|-------------------|---|
| <i>S_fileName</i> | Name of the print file (either a string or symbol) to which the table contents are to be written. |
| <i>o_table</i> | Association table from which the data is accessed. |

Value Returned

| | |
|-----|--|
| t | If the data is successfully written to the file. |
| nil | Unable to write the data to the file. |

Examples

```
writeTable("inventory" myTable)  
=> t  
writeTable(noFile myTable)  
=> nil
```

Related Topics

[Input Output Functions](#)

[makeTempFileName](#)

[readTable](#)

Core Functions

This topic provides a list of SKILL functions related to core operations.

| | | |
|-----------------------|--------------------------|--------------------------|
| <u>arglist</u> | <u>assert</u> | <u>atom</u> |
| <u>bcdp</u> | <u>booleanp</u> | <u>boundp</u> |
| <u>describe</u> | <u>fdoc</u> | <u>gc</u> |
| <u>gensym</u> | <u>getMuffleWarnings</u> | <u>getSkillVersion</u> |
| <u>get_pname</u> | <u>get_string</u> | <u>getVersion</u> |
| <u>getWarn</u> | <u>help</u> | <u>inScheme</u> |
| <u>inSkill</u> | <u>isVarImported</u> | <u>makeSymbol</u> |
| <u>measureTime</u> | <u>muffleWarnings</u> | <u>needNCells</u> |
| <u>restoreFloat</u> | <u>saveFloat</u> | <u>schemeTopLevelEnv</u> |
| <u>setPrompts</u> | <u>sstatus</u> | <u>status</u> |
| <u>theEnvironment</u> | <u>unbindVar</u> | |

arglist

```
arglist(  
    g_function  
)  
=> l_argumentList
```

Description

Returns the number and types of arguments expected for a function. Also checks if the specified function is a binary object,

This function is useful for determining how many arguments a function takes and what they are.

If the function is read-protected, the arguments are still returned. If the function is a primitive (binary), the argument list is based on the type template for the function specified. If the function is defined in SKILL, the argument list in the function definition is returned.

Arguments

| | |
|-------------------|---|
| <i>g_function</i> | Name of the function or the symbol whose argument list you want to see. |
|-------------------|---|

Value Returned

| | |
|-----------------------|---|
| <i>l_argumentList</i> | Number and types of arguments for <i>g_function</i> . |
|-----------------------|---|

Examples

The first argument of `rexMatchp` must be a string and the second must be a string or symbol.

```
arglist('rexMatchp)  
=> ( t_string S_stringSymbol "tS")
```

Related Topics

[Core Functions](#)

assert

```
assert(  
    g_expression  
    [ t_formatString  
      [ g_arg1 ] ... ] )  
)  
=> nil
```

Description

Enables you to insert assertions into the SKILL code, either at the top-level or within a function. It evaluates the expression (*g_expression*) and returns `nil` if the expression value is non-nil. Otherwise, throws an error and returns the unevaluated expression.

Arguments

| | |
|-----------------------|---|
| <i>g_expression</i> | A generic expression. |
| <i>t_formatString</i> | Characters to be printed verbatim, intermixed with format specifications prefixed by the % sign. |
| <i>g_arg1</i> | The arguments following the format string are printed according to their corresponding format specifications. |

Value Returned

| | |
|------------------|--------------------------|
| <code>nil</code> | Assertion is successful. |
|------------------|--------------------------|

Examples

```
assert(1 == 1)  
=> nil  
  
assert( 1==2 )  
=> *ERROR* ASSERT FAILED: (1 == 2)  
  
assert( 1==2 "Assertion failed." )  
=> *ERROR* Assertion failed.  
  
a = 1  
b = 2  
assert( a==b "Assertion failed. %d is not equal to %d" a b )
```

Cadence SKILL Language Reference

Core Functions

=> ***ERROR*** Assertion failed. 1 is not equal to 2.

Related Topics

Core Functions

atom

```
atom(  
    g_arg  
)  
=> t / nil
```

Description

Checks if an object is an atom.

Atoms are all SKILL objects except non-empty lists. The special symbol `nil` is both an atom and a list.

Arguments

| | |
|--------------|-------------------|
| <i>g_arg</i> | Any SKILL object. |
|--------------|-------------------|

Value Returned

| | |
|------------------|---------------------------------|
| <code>t</code> | If <i>g_arg</i> is an atom. |
| <code>nil</code> | If <i>g_arg</i> is not an atom. |

Examples

```
atom( 'hello )  
=> t  
  
x = '(a b c)  
atom( x )  
=> nil  
  
atom( nil )  
=> t
```

Related Topics

Core Functions

bcdp

```
bcdp(  
    g_value  
)  
=> t / nil
```

Description

Checks if an object is a binary primitive function.

The suffix *p* is usually added to the name of a function to indicate that it is a predicate function.

Arguments

| | |
|----------------|------------------|
| <i>g_value</i> | Object to check. |
|----------------|------------------|

Value Returned

| | |
|------------|---|
| <i>t</i> | If <i>g_value</i> is a binary function. |
| <i>nil</i> | If <i>g_value</i> is not a binary function. |

Examples

```
bcdp(getd('plus))  
=> t  
bcdp('plus)  
=> nil
```

Related Topics

[Core Functions](#)

booleanp

```
booleanp(  
    g_obj  
)  
=> t / nil
```

Description

Checks if an object is a boolean. Returns `t` if the object is `t` or `nil`. Returns `nil` otherwise.

Arguments

| | |
|--------------|-------------------|
| <i>g_obj</i> | Any SKILL object. |
|--------------|-------------------|

Value Returned

| | |
|------------------|--|
| <code>t</code> | If <i>g_obj</i> is either <code>t</code> or <code>nil</code> . |
| <code>nil</code> | If <i>g_obj</i> is not a boolean. |

Examples

```
(booleanp 0 )  
=> nil  
(booleanp nil)  
=> t  
(booleanp t)  
=> t
```

Related Topics

Core Functions

boundp

```
boundp(  
    s_arg  
    [ e_environment ]  
)  
=> t / nil
```

Description

Checks if the variable named by a symbol is bound, that is, has been assigned a value. The single argument form of `boundp` only works in SKILL mode.

Remember that a variable can be set to the special symbol `unbound`.

The `boundp()` function does not check the current language mode. If single argument is specified, SKILL semantics are used, whereas if two arguments are specified, SKILL++ semantics are used.

Arguments

| | |
|----------------------|--|
| <i>s_arg</i> | Symbol to be tested to see if it is bound. |
| <i>e_environment</i> | If this argument is given, SKILL++ semantics are used. The symbol will be searched for within the given (lexical) environment. |

Value Returned

| | |
|------------|---|
| <i>t</i> | If the symbol <i>s_arg</i> has been assigned a value. |
| <i>nil</i> | If the symbol <i>s_arg</i> has not been assigned a value. |

Examples

```
x = 5           ; Binds x to the value 5.  
y = 'unbound    ; Unbind y  
  
boundp( 'x )  
=> t  
  
boundp( 'y )  
=> nil  
  
y = 'x           ; Bind y to the constant x.  
boundp( y )
```


Cadence SKILL Language Reference

Core Functions

```
=> t           ; Returns t because y evaluates to x,  
                ; which is bound.
```

Related Topics

Core Functions

describe

```
describe(  
    [ s_symbol ]  
)  
=> t
```

Description

Prints information about the symbol *s_symbol*. If the symbol has a function definition, information on the argument list and other available details will be printed. If the symbol has a variable definition, information about its value and function will be printed. If the function is called without any arguments, the help message will be printed.

Arguments

| | |
|-----------------|--|
| <i>s_symbol</i> | SKILL symbol to print information for. |
|-----------------|--|

Value Returned

| | |
|---|--|
| t | Information about the symbol is printed. |
|---|--|

Examples

```
describe('append)  
Symbol append has a function definition.  
Its argument list is (g_general g_general "gg")  
This is a built-in function.  
=> t
```

Related Topics

[Core Functions](#)

fdoc

```
fdoc(  
    s_function  
)  
=> t_doc / nil
```

Description

Returns the documentation string for the function bound to the symbol *s_function*. SKILL switch `saveInlineDoc` must be set to save and retrieve the doc string.

Arguments

| | |
|-------------------|---------------------------------------|
| <i>s_function</i> | A symbol for the SKILL function name. |
|-------------------|---------------------------------------|

Value Returned

| | |
|--------------|--|
| <i>t_doc</i> | Documentation string is available. |
| <i>nil</i> | Inline documentation is not available. |

Examples

```
sstatus(saveInlineDoc t) ;; enable inline documentation in compile time  
defun(myFun (a b)  
    "documentation for myFun: return sum a and b"  
    a + b  
    )  
fdoc('myFun)  
=> "documentation for myFun: return sum a and b"=
```

Related Topics

[Core Functions](#)

gc

```
gc (
    [ t_string ]
)
=> nil
```

Description

Forces a garbage collection. This function is also called by the system.

Garbage collection (*gc*) refers to the process in which SKILL locates storage cells that are no longer needed (thus the term garbage) and recycles them by putting them back on the free storage list. Garbage collection is also called by the system. Garbage collection is transparent to SKILL users and to users of applications built on top of SKILL.

You can turn on the printing of garbage collection messages by setting the *_gcprint* variable to *t* (that is, *_gcprint=t*). Garbage collection can be turned off at any time by setting the *gcdisable* variable to *t*. To enable garbage collection again, you can restore *gcdisable* to its previous value. You can force a garbage collection at any time by calling the *gc* function.

Note: Because some applications turn off garbage collection during their execution, you should be careful about enabling it. Corrupted data can result.

Arguments

| | |
|-----------------|---|
| <i>t_string</i> | File into which additional information is dumped. |
|-----------------|---|

Value Returned

| | |
|------------|-----------------------------|
| <i>nil</i> | Always returns <i>nil</i> . |
|------------|-----------------------------|

Examples

```
gc ( )
=> nil
```

Related Topics

[Core Functions](#)

Cadence SKILL Language Reference

Core Functions

gcsummary

gensym

```
gensym(  
    [ S_arg ]  
)  
=> s_result
```

Description

Returns a new symbol based on the input argument.

The new symbol's print name is the result of concatenating the printed representation of the argument, or "G" if no argument is given, and the printed (decimal) representation of a number. The returned new symbol is unique in the sense that it does not exist at the time this function is called.

Arguments

| | |
|--------------|---|
| <i>S_arg</i> | String or symbol to be concatenated into a new symbol. If not supplied, the default value is G. |
|--------------|---|

Value Returned

| | |
|-----------------|--------------------|
| <i>s_result</i> | New unique symbol. |
|-----------------|--------------------|

Examples

```
gensym()  
=> G5  
gensym("test")  
=> test6  
test7 = 10  
=> 10      ;test7 exists now.  
gensym('test')  
=> test8    ;test7 is skipped.  
gensym() == gensym()  
=> nil      ;Always returns nil.
```

Related Topics

Core Functions

getMuffleWarnings

```
getMuffleWarnings(  
    )  
=> l_list
```

Description

Returns a list of warnings that were called and suppressed by the preceding `muffleWarnings` command.

Arguments

None

Value Returned

l_list List of warnings or `nil`, if no warnings were called.

Examples

Results pertain to the preceding `muffleWarnings` command.

```
muffleWarnings(  
    warn("A first warning 1 level")  
    warn("A second warning 1 level")  
    muffleWarnings(  
        warn("A first warning 2 level")  
        warn("A second warning 2 level")  
        2+2  
    )  
=> 4  
  
getMuffleWarnings()  
=> ("A first warning 2 level" "A second warning 2 level")  
1+2  
)  
=> 3  
  
getMuffleWarnings()  
=> ("A first warning 1 level" "A second warning 1 level")
```

Related Topics

Core Functions

muffleWarnings

getSkillVersion

```
getSkillVersion(  
    [ g_printSubVersion ]  
)  
=> t_version
```

Description

Returns the major version if the argument is left `blank`; otherwise, returns the current subversion (or tarkit version) of SKILL that is running in the build

Arguments

g_printSubVersion

(Optional) Specify a flag to print the current subversion (or tarkit version) of SKILL running in the build

Value Returned

t_version

If the argument flag is left `blank`, returns the major version of SKILL running in the build. If the argument flag is specified, returns the current subversion (tarkit version) of SKILL running in the build

Examples

```
getSkillVersion()  
=> "SKILL04.20"  
  
getSkillVersion(t)  
"@(#)$CDS:    il skillSrc33.12-d009 08/31/11 14:50 fwinteg sjfdl803 $"
```

Related Topics

Core Functions

get_pname

```
get_pname(  
    s_arg  
)  
=> t_result
```

Description

Returns the print name of a symbol as a string.

This function is useful for converting symbols to strings. If you just want to print the name of a symbol, you do *not* need to use this function. This function is equivalent to `symbolToString`.

Arguments

| | |
|--------------|-----------|
| <i>s_arg</i> | A symbol. |
|--------------|-----------|

Value Returned

| | |
|-----------------|---------------------------|
| <i>t_result</i> | Print name of the symbol. |
|-----------------|---------------------------|

Examples

```
get_pname( 'a )  
=> "a"  
get_pname(concat("Cell_" 123))  
=> "Cell_123"
```

Related Topics

[Core Functions](#)

[get_string](#)

get_string

```
get_string(  
    S_arg  
)  
=> t_result
```

Description

Converts the argument to a string if it is a symbol. Otherwise it returns the string itself.

Arguments

| | |
|--------------|-------------------|
| <i>S_arg</i> | String or symbol. |
|--------------|-------------------|

Value Returned

| | |
|-----------------|--|
| <i>t_result</i> | If the argument is a string, returns the argument itself. If the argument is a symbol, returns the print name as a string. |
|-----------------|--|

Examples

```
get_string('xyz')  
=> "xyz"  
get_string("xyz")  
=> "xyz"
```

Related Topics

Core Functions

get_pname

getVersion

```
getVersion(  
    [ g_opt ]  
)  
=> t_[sub]version
```

Description

Returns the version number of the Cadence software you are currently using. If you specify the optional argument *g_opt*, as *t* (or a non-nil value), the subversion number of the Cadence software currently used is returned. By default, the full version number, including the hotfix version, of the Cadence software currently used is returned.

Use the SKILL system structure to determine the bitType (32bit / 64bit) of the current Virtuoso session:

```
system.LP64  
=> nil ;; 32bit  
=> t   ;; 64bit
```

or

```
system.system.ILP32  
=> nil ;; 64bit  
=> t   ;; 32bit
```

These `system.??` properties are initialized at startup.

Arguments

| | |
|--------------|--|
| <i>g_opt</i> | If the optional argument, <i>g_opt</i> , is specified as <i>t</i> (or a non-nil value), the subversion number of the Cadence software currently used is returned. By default, the full version number, including the hotfix version, of the Cadence software currently used is returned. |
|--------------|--|

Value Returned

| | |
|-----------------------|---|
| <i>t_[sub]version</i> | String identifying the version/subversion of the program you are running. |
|-----------------------|---|

Cadence SKILL Language Reference

Core Functions

Examples

```
getVersion()  
=> "@(#) $CDS: virtuoso version [Version] [DateStamp] [BuildHost] $"  
getVersion(nil)  
=> "@(#) $CDS: virtuoso version [Version] [DateStamp] [BuildHost] $"  
getVersion( 'subVer )  
=> "sub-version [SubVersion]"  
getVersion(t)  
=> "sub-version [SubVersion] "  
getVersion("subversion")  
=> "sub-version [SubVersion] "
```

Related Topics

Core Functions

dbGetVersion

getWarn

```
getWarn(  
    )  
=> t_warning
```

Description

Returns the buffered warning if it has not already been printed.

Arguments

None

Value Returned

| | |
|------------------|---|
| <i>t_warning</i> | The warning message that would have been printed if it had not been intercepted by the call to <code>getWarn</code> . |
|------------------|---|

Examples

```
procedure( testWarn( @key ( getLastWarn nil ) )  
    warn("This is warning %d\n" 1 ) ;;; print previous warning  
    warn("This is warning %d\n" 2 ) ;;; and buffer new one.  
    warn("This is warning %d\n" 3 )  
    when( getLastWarn  
        thrownAwayWarn = getWarn( ) ;;; throw away last warning  
        nil ;;; return nil  
    ) ; when  
    ) ; procedure
```

The `testWarn` function intercepts the last warning message and stores it in a global variable if `t` is passed in, and lets the system print all the warnings if `nil` is given as an argument. Use of the `getWarn()` function makes it possible to throw away a warning message, if desired.

```
testWarn( ?getLastWarn t)  
=> nil  
*WARNING* This is warning 1  
*WARNING* This is warning 2
```

Returns `nil`. The system prints the first two warnings and the third is intercepted and stored in global variable `thrownAwayWarn`.

```
testWarn( ?getLastWarn nil)  
=> nil  
*WARNING* This is warning 1  
*WARNING* This is warning 2  
*WARNING* This is warning 3
```

Cadence SKILL Language Reference

Core Functions

Returns `nil`. The system prints all the queued warnings.

The return value may be interleaved with the warning message output. The following example shows how the output can appear in the CIW.

```
testWarn( ?getLastWarn t)
*WARNING* This is warning 1
*WARNING* This is warning 2
=> nil

testWarn( ?getLastWarn nil)
*WARNING* This is warning 1
*WARNING* This is warning 2
=> nil
*WARNING* This is warning 3
```

Related Topics

Core Functions

help

```
help(  
    [ S_name ]  
)  
=> t / nil
```

Description

Retrieves and prints the cdsFinder documentation strings for the given function name (a symbol). If the given name is a string, it is interpreted as a regular expression, and the entire cdsFinder database is searched for functions whose name or documentation string contains or matches the given string. Help is an `nlambda` function.

Arguments

| | |
|---------------|---------------------|
| <i>S_name</i> | Name to search for. |
|---------------|---------------------|

Value Returned

| | |
|------------|--|
| <i>t</i> | The given function name is found in the cdsFinder. |
| <i>nil</i> | No match is found for <i>S_name</i> . |

Examples

```
help nonexistent  
=> nil  
help scanf
```

Prints the following and returns *t*.

```
fscanf( p_inputPort t_formatString [s_var1 ...] )  
scanf( t_formatString [s_var1 ...] )  
sscanf( t_sourceString t_formatString [s_var1 ...] )
```

The only difference between these functions is the source of input. *fscanf* reads input from a port according to format specifications and returns the number of items read in. *scanf* takes its input from piport implicitly. *scanf* only works in standalone SKILL when the piport is not the CIW. *sscanf* reads its input from a string instead of a port.

```
=> t  
help println
```

Cadence SKILL Language Reference

Core Functions

Prints the following and returns t.

```
println( g_value [p_outputPort] )  
=> nil
```

Prints a SKILL object using the default format for the data type of the value, then prints a newline character.

```
=> t  
help "read"
```

Prints the following and returns t.

```
fscanf, scanf, sscanf, getWarn, infile, instring, ipcReadProcess,  
ipcWaitForProcess, isReadable, lineread, linereadstring, load, loadstring,  
outfile, pp, putpropq, putpropqq, read, readTable, readstring  
=> t  
help "match nowhere"  
=> nil
```

Related Topics

Core Functions

inScheme

```
inScheme (  
    g_form  
)  
=> g_result
```

Description

Evaluates a form as top-level SKILL++ code, disregarding the surrounding evaluation context.

Arguments

| | |
|---------------|---|
| <i>g_form</i> | Form to be evaluated as top-level SKILL++ code. |
|---------------|---|

Value Returned

| | |
|-----------------|---------------------------|
| <i>g_result</i> | Result of the evaluation. |
|-----------------|---------------------------|

Examples

Defines a SKILL++ global variable, even if this code appears inside a SKILL file.

```
(inScheme  
    (define myVar 100))  
=> myVar
```

Related Topics

[Core Functions](#)

[inSkill](#)

inSkill

```
inSkill(  
    g_form  
)  
=> g_result
```

Description

Evaluates a form as top-level SKILL code, disregarding the surrounding evaluation context.

Arguments

| | |
|---------------|---|
| <i>g_form</i> | Form to be evaluated as top-level SKILL code. |
|---------------|---|

Value Returned

| | |
|-----------------|---------------------------|
| <i>g_result</i> | Result of the evaluation. |
|-----------------|---------------------------|

Examples

Sets a SKILL global variable, even if this code appears inside a SKILL++ file.

```
(inSkill  
    skillVar = 100)  
=> 100
```

Related Topics

[Core Functions](#)

isVarImported

```
isVarImported(  
    s_var  
)  
=> t / nil
```

Description

Checks if the specified variable was imported into SKILL++ or not.

Arguments

| | |
|--------------|-----------------------------|
| <i>s_var</i> | The variable to be checked. |
|--------------|-----------------------------|

Value Returned

| | |
|-----|--|
| t | The specified variable <i>s_var</i> was imported into SKILL++. |
| nil | If the given variable is not imported. |

Examples

```
isVarImported('myvar)  
=> nil
```

Related Topics

[Core Functions](#)

makeSymbol

```
makeSymbol(  
    S_createSymbol  
    [ t_namespaceArg ]  
)  
=> s_result
```

Description

Creates a symbol corresponding to the specified symbol or character string. You can optionally specify the namespace name (*t_namespace*) in which you want to create the symbol.

The function `gensym()` also creates symbols. However, the symbol names are determined internally (and are therefore unique) whereas in the case of `makeSymbol()` the symbol name depends upon the string passed as a parameter to the function.

Arguments

| | |
|-----------------------|---|
| <i>S_createSymbol</i> | Specifies the value for which a corresponding symbol needs to be created. |
| <i>t_namespaceArg</i> | Specifies the name of the namespace in which you want to create the symbol. |

Value Returned

| | |
|-----------------|---|
| <i>s_result</i> | A symbol corresponding to the specified string value. |
|-----------------|---|

Examples

The following example creates a symbol corresponding to the specified string value, `myString`.

```
makeSymbol("myString")  
=> myString
```

The following example uses an increment counter (`count`) to create unique symbols (`myString1`, `myString2`, and so on)

```
count=0  
makeSymbol(strcat("myString" sprintf(nil "%L" ++count)))
```

Cadence SKILL Language Reference

Core Functions

The following example creates a symbol, `myString`, in the namespace, `newNamespace`.

```
makeNamespace("newNamespace")  
makeSymbol("myString" "newNamespace")  
=> newNamespace::myString
```

Related Topics

Core Functions

measureTime

```
measureTime(  
    g_expression ...  
)  
=> l_result
```

Description

Measures the time needed to evaluate an expression and returns a list with performance data (*n_utime*, *n_stime*, *n_clockTime*, and *x_pageFaults*) for the executed expressions. This is a syntax form.

- *n_utime*: The amount of user CPU time, in seconds, spent on the execution of expressions (counted with `getrusage()`).
- *n_stime*: The amount of system CPU time, in seconds, spent on the execution of expressions (counted with `getrusage()`).
- *n_clockTime*: The clock time used on execution of the expressions (in seconds) (counted with `gettimeofday()`). This function assumes that the executed expressions do not alter `gettimeofday()` result.
- *x_pageFaults*: The number of page faults that occurred during the execution of the expressions (counted with `gettimeofday()`).

Arguments

g_expression Expression(s) to be evaluated and timed.

Value Returned

l_result A list with performance data (*n_utime*, *n_stime*, *n_clockTime*, and *x_pageFaults*) for the executed expressions.

Examples

```
myList = nil                              ; Initializes the variable myList.  
measureTime( for( i 1 10000 myList = cons(i myList) ) )  
=> (0.4 0.05 0.4465 0)
```

Result indicates that it took .4 seconds and 0 page faults to build a list from 1 to 10,000 using `cons`.

Cadence SKILL Language Reference

Core Functions

```
myList = nil ; Initializes the variable myList.
measureTime( for( i 1 1000 myList = append1(myList i) ) )
=> (5.04 0.03 5.06 0)
```

Result indicates that it took 5 seconds and 0 page faults to build a list from 1 to 1000 using `append1`.

```
tab = makeTable("testTable" 'unbound 5000)
=> table:testTable

result = measureTime(for(i 0 10000 tab[i] = t))
=> (0.003 0.0 0.002537012 0)
```

Related Topics

Core Functions

muffleWarnings

```
muffleWarnings(  
    g_expr1 ...  
)  
=> g_general
```

Description

Returns the result of the last expression evaluated. If the last expression evaluated calls the `warn` function (either SKILL `warn()` or C-level `ilWarn*`), the related message is not printed out.

To get the list of muffled warning messages, use the `getMuffleWarnings` function immediately after a `muffleWarnings` command.

Arguments

| | |
|----------------|--------------------------------|
| <i>g_expr1</i> | Expression(s) to be evaluated. |
|----------------|--------------------------------|

Value Returned

| | |
|------------------|--|
| <i>g_general</i> | Result of the last expression evaluated. |
|------------------|--|

Examples

Result indicates 3 as the value evaluated from the last expression. The muffled warning messages are listed as a result of the `getMuffleWarnings` function.

```
muffleWarnings(  
    warn("A warning")  
    warn("A second warning")  
    1+2  
)  
=> 3  
  
getMuffleWarnings()  
=> ("A warning" "A second warning")
```

Related Topics

[Core Functions](#)

[getMuffleWarnings](#)

needNCells

```
needNCells(  
    {s_cellType | S_userType}  
    x_cellCount  
)  
=> t / nil
```

Description

Ensures that there is enough memory available for the specified number of SKILL objects (cells).

If necessary, more memory is allocated. The name of the user type can be passed in as a string or a symbol, however internal types like `list` or `fixnum` must be passed in as symbols.

Arguments

| | |
|--------------------|-----------------------------------|
| <i>s_cellType</i> | Objects of type <i>cellType</i> . |
| <i>S_userType</i> | Objects of type <i>userType</i> . |
| <i>x_cellCount</i> | Number of objects. |

Value Returned

| | |
|------------|---------------------------------|
| <i>t</i> | Enough memory is available. |
| <i>nil</i> | Enough memory is not available. |

Examples

Guarantees there will always be 1000 list cells available in the system.

```
needNCells( 'list 1000 )  
=> t
```

Related Topics

Core Functions

restoreFloat

```
restoreFloat(  
    t_string  
)  
=> f_number
```

Description

Restores a floating point number (*f_number*) from its serialized string (*t_string*) representation. *t_string* should be created by `saveFloat()`.

Arguments

| | |
|-----------------|--|
| <i>t_string</i> | A serialized float created by <code>ilSaveFloat()</code> . |
|-----------------|--|

Value Returned

| | |
|-----------------|-------------------------------------|
| <i>f_number</i> | The restored floating point number. |
|-----------------|-------------------------------------|

Examples

```
str = saveFloat(1.4106)  
=> "float:3ff6a09e667f3bcd@3ff691d14e3bcd36"  
restoreFloat(str) == 1.4106
```

Related Topics

Core Functions

saveFloat

```
saveFloat(  
    f_number  
)  
=> t_string
```

Description

Serializes the given floating point number (*f_number*) to string (*t_string*).

Arguments

| | |
|-----------------|--|
| <i>f_number</i> | The floating point number that needs to be serialized. |
|-----------------|--|

Value Returned

| | |
|-----------------|--|
| <i>t_string</i> | The string representation of <i>f_number</i> . |
|-----------------|--|

Examples

```
str = saveFloat(1.4106)  
=> "float:3ff6a09e667f3bcd@3ff691d14e3bcd36"
```

Related Topics

[Core Functions](#)

schemeTopLevelEnv

```
schemeTopLevelEnv(  
  )  
=> e_envobj
```

Description

Returns the top level SKILL++ environment as an environment object.

Arguments

None

Value Returned

| | |
|-----------------|---|
| <i>e_envobj</i> | The top level SKILL++ environment object. |
|-----------------|---|

Examples

```
schemeTopLevelEnv()  
=> envobj:0x1ad018
```

Related Topics

[Core Functions](#)

setPrompts

```
setPrompts(  
    s_prompt1  
    s_prompt2  
)  
=> t / nil
```

Description

Sets the prompt text string for the CIW. The first prompt is used to indicate the topmost top-level. The second prompt is used whenever a nested top-level is entered.

The text string for *s_prompt2* should always be the `%d` format string, which behaves the same as the `printf()` format string, such that the nesting level of a nested top-level will be shown as it deepens.

Changing prompts in some applications can seriously interfere with their functioning. Therefore, be careful using this function.

Arguments

| | |
|------------------|---------------------|
| <i>s_prompt1</i> | Prompt text string. |
| <i>s_prompt2</i> | Prompt text string. |

Value Returned

| | |
|-----|---|
| t | The prompt has been set. |
| nil | Issues an error message if the prompt is not changed. |

Examples

```
setPrompts("~> " "<%d>> ")  
t  
~> toplevel( 'ils )  
ILS-<2>> toplevel( 'ils )  
ILS-<3>>
```

Sets the topmost top-level to `~>` and the nested top-level to `<%d>>` :

```
setPrompts("~> " "<%s>> ")  
*Error* setPrompts: setPrompts expected %d not %s in prompt --  
<%s>>
```

%s is an illegal format string.

Related Topics

Core Functions

Cadence SKILL Language Reference

Core Functions

sstatus

```
sstatus(  
    s_name  
    g_switchValue  
)  
=> g_switchValue
```

Description

Sets the internal system variable named to a given value. This is a syntax form.

The internal variables are typically Boolean switches that accept only the Boolean values of `t` and `nil`. Efficiency and security are the reasons why these system variables are stored as internal variables that can only be set by `sstatus`, rather than as SKILL variables you can set directly.

Internal System Variables

| Name | Meaning | Default |
|------------------|---|------------------|
| autoReload | If <code>t</code> , the debugger will try to auto-reload a file that is not loaded under <code>debugMode</code> when the user tries to single-step into the code defined by that file. This might not work correctly for SKILL++ functions defined using assignment. | <code>nil</code> |
| classAuxAutoLoad | If <code>t</code> , the SKILL++ code that accesses classes located in SKILL context files auto-loads the context (if this context has not already been loaded). | <code>nil</code> |
| debugMacro | If <code>t</code> , the IL compiler sets <code>lineNumber</code> on the expanded macro code to <code>lineNumber</code> of the original form. | <code>nil</code> |
| debugMode | If <code>t</code> , provides more information for debugging SKILL programs. Allows you to redefine write-protected SKILL functions. | <code>nil</code> |
| echoInput | If <code>t</code> , each user input in CIW is repeated in the output port. | <code>nil</code> |
| errsetTrace | If <code>t</code> , prints errors and stacktrace information that is normally suppressed by <code>errset</code> . | <code>nil</code> |

Cadence SKILL Language Reference

Core Functions

| | | |
|----------------------------------|--|------------------|
| <code>floatPrecisionChars</code> | <p>Rounds off the value to the specified number of digits. For example, if set to 10, the value has 10-digit accuracy.</p> <p>If <code>fullPrecision</code> is set to <code>t</code>, it is also considered and the value then has 17-digit accuracy.</p> <p>If <code>fullPrecision</code> is set to <code>nil</code>, the value still has 10-digit accuracy.</p> | 7 |
| <code>forceWarnings</code> | If <code>t</code> , all warnings are flushed immediately, even if <code>getWarn()</code> is used or the warning is stored in a temporary buffer to be printed later in the CIW. | <code>nil</code> |
| <code>fullPrecision</code> | If <code>t</code> , unformatted print functions (<code>print</code> , <code>println</code> , <code>printlev</code>) print floating point numbers in full precision (usually 16 digits); otherwise, the default is about 7 digits of precision. | <code>nil</code> |
| <code>integermode</code> | If <code>t</code> , the parser translates all arithmetic operators into calls to functions that operate only on <code>fixnums</code> . This results in small execution time savings, particularly for compute-intensive tasks whose inner loops are dominated by integer arithmetic calculations. | <code>nil</code> |
| <code>keepNLInString</code> | <p>When set to <code>nil</code>, newline characters in strings are replaced with spaces. When set to <code>t</code>, the newline characters are retained as they are.</p> <p>This option is applicable only if <code>status(multilineString)</code> is <code>t</code> and the parsed string is inside a SKILL expression.</p> | <code>nil</code> |
| <code>keepSrcInfo</code> | If <code>t</code> , the source information (file/line information) is added to <code>funobject</code> during compilation. | <code>nil</code> |
| <code>lazyComp</code> | <p>It is an auxiliary switch used by the V-code compiler.</p> <p>If <code>t</code>, tells V-code compiler to generate code (compile function) when it is called for the first time. That is, not to compile function after it is entered by the user (or loaded from a file) until it is called.</p> <p>If set to <code>nil</code>, enables the eager mode, where each function is compiled immediately after it is entered.</p> | <code>t</code> |

Cadence SKILL Language Reference

Core Functions

| | | |
|--------------------------------|---|------------------|
| <code>mergemode</code> | If <code>t</code> , arithmetic expressions are merged by the parser, whenever possible, into a minimum number of function calls and therefore run somewhat faster because most of the arithmetic functions, such as <code>plus</code> , <code>difference</code> , <code>times</code> , and <code>quotient</code> , can accept a variable number of arguments. | <code>t</code> |
| <code>multilineString</code> | If <code>t</code> , allows SKILL strings inside double quotes to be spanned on several lines. | <code>t</code> |
| <code>optimizeNestedLet</code> | If <code>t</code> , instructs the SKILL compiler to parse the code for <code>let</code> constructions (defining local variables and local functions) and expand/remove them by moving their local variables to the top-level function's local variables section. | <code>nil</code> |
| <code>optimizeTailCall</code> | <p>If <code>t</code>, enables the tail call recursion, which prevents runtime stack overflow when a function is called recursively.</p> <p>This works only in Scheme mode (<code>toplevel 'ils</code>).</p> | <code>nil</code> |
| <code>printinfix</code> | Printing of arithmetic expressions and function calls in <code>infix</code> notation is turned off (on) if the second argument is <code>nil</code> (<code>t</code>). | <code>t</code> |
| <code>profCount</code> | If <code>t</code> , the SKILL Profiler provides the number of times a SKILL function is called (as an additional column in the table view of the profiler's result). | <code>nil</code> |
| <code>saveInlineDoc</code> | If <code>t</code> , when a SKILL function has inline documentation, allows the documentation string to be stored in the function symbol property. | <code>t</code> |
| <code>savePcreData</code> | When set to <code>t</code> , all <code>pcre</code> compiled objects are saved to context. After the context is loaded these objects are restored. | <code>nil</code> |
| | Note: <code>savePcreData</code> can cause context incompatibility with previous versions of SKILL. | |

Cadence SKILL Language Reference

Core Functions

| | | |
|------------------|--|----------|
| scopedMacros | <p>Identifies the scope of the macros and controls how the macros are expanded when processing the Scheme function body.</p> <p>If this switch is set to <code>t</code>, the scope is checked before expanding <code>MACRO/ALIAS: FUN(ARGS)</code>. If the function is found in local scope (in Scheme environment), the <code>MACRO/ALIAS</code> is not expanded to prevent it from calling a <code>GLOBAL</code> function.</p> | nil |
| showStepResult | If <code>t</code> , prints the expression evaluation results performed by the step command in CIW. If the SKILL IDE is also running, a new assistant window is displayed, which also displays the expression evaluation results. | nil |
| sourceTracing | <p>If <code>t</code>, the debugger will try to print the corresponding source location at stop/breakpoints (as well as in stack tracing).</p> <p>A file must be loaded in when <code>debugMode</code> is set to <code>t</code> to get its source line numbers. The source forms printed are truncated to fit on one line.</p> | nil |
| stacktrace | Prints stack frames every time an error occurs. Toggle on or off with <code>t</code> or <code>nil</code> , or set the number of frames to display. | 0 |
| stacktraceDump | Prints the local variables when an error occurs if <code>sstatus(stacktrace t)</code> is set. Toggle on/off with <code>t</code> / <code>nil</code> . | nil |
| stackTraceFormat | <p>Controls the stacktrace output format. It can have one of three values:</p> <ul style="list-style-type: none"> ■ <code>fullStack</code> prints the complete set of SKILL stack frames. ■ <code>onlyCall</code> suppresses the printing of non-function frames in the output. ■ <code>onlyTop</code> suppresses the printing of non-function frames except for the topmost function frame. | fullStac |

Cadence SKILL Language Reference

Core Functions

| | | |
|-------------------------------|--|--------------------|
| <code>traceArgs</code> | <p>If not set to <code>nil</code>, the system will save the evaluated arguments of function calls, which can then be displayed in the stacktrace.</p> <p>Setting <code>debugMode</code> or tracing functions (using <code>tracef</code>) will no longer turn on <code>traceArgs</code> automatically. The default behavior is to turn off this switch because it is expensive to retain the evaluated arguments.</p> <p>Note: Turning on this switch could slow down the execution speed significantly.</p> | <code>nil</code> |
| <code>traceTEnable</code> | Allows the use of <code>t</code> as an argument to the <code>trace</code> , <code>tracev</code> , and <code>tracep</code> functions. | <code>. nil</code> |
| <code>traceIndent</code> | If <code>t</code> , prints the trace with many ' ', as in the earlier trace style. To print the trace in the new ' [%level ' construction, use the default value (<code>nil</code>). | <code>nil</code> |
| <code>verboseLoad</code> | If <code>t</code> , prints the complete path of the loaded file in the CIW in debug mode. | <code>nil</code> |
| <code>verboseNamespace</code> | If <code>t</code> , enables the printing of warnings related to SKILL namespaces. | <code>nil</code> |
| <code>writeProtect</code> | <p>When on, all functions being defined have their write protection set to <code>t</code> so they cannot be redefined.</p> <p>When off, all functions being defined for the first time are not write-protected and thus can be redefined. When developing SKILL code, be sure this switch is set to off.</p> | <code>nil</code> |

Arguments

| | |
|----------------------------|--|
| <code>s_name</code> | Name of internal system variable. |
| <code>g_switchValue</code> | New value for internal system variable, usually <code>t</code> or <code>nil</code> . |

Value Returned

| | |
|----------------------------|---|
| <code>g_switchValue</code> | The second argument to <code>sstatus</code> . |
|----------------------------|---|

Examples

Turns on debug mode.

```
sstatus( debugMode t )  
=> t
```

Turns on integer mode.

```
sstatus( integermode t )  
=> t
```

Prints the local variables when an error occurs.

```
sstatus( stacktraceDump t )  
=> t
```

Prints the first six stack frames every time an error occurs.

```
sstatus( stacktrace 6 )  
=> 6
```

```
defun factorial (n) (if (n== 0) 1 (n*factorial(n-1))  
=>factorial
```

(trace factorial); value of the `traceIndent` variable is `nil`, which is the default value

```
=>(factorial)
```

```
(factorial 10)  
|[1]factorial(10)  
|[2]factorial(9)  
|[3]factorial(8)  
|[4]factorial(7)  
|[5]factorial(6)  
|[6]factorial(5)  
|[7]factorial(4)  
|[8]factorial(3)  
|[9]factorial(2)  
|[10]factorial(1)  
|[11]factorial(0)  
|[11]factorial --> 1  
|[10]factorial --> 1  
|[9]factorial --> 2  
|[8]factorial --> 6  
|[7]factorial --> 24
```

Cadence SKILL Language Reference

Core Functions

```
|[6]factorial --> 120
|[5]factorial --> 720
|[4]factorial --> 5040
|[3]factorial --> 40320
|[2]factorial --> 362880
|[1]factorial --> 3628800
3628800
```

```
(sstatus traceIndent t)
t
(factorial 10)
|factorial(10)
||factorial(9)
|||factorial(8)
||||factorial(7)
|||||factorial(6)
||||||factorial(5)
|||||||factorial(4)
|||||||factorial(3)
|||||||factorial(2)
|||||||factorial(1)
|||||||factorial(0)
|||||||factorial --> 1
|||||||factorial --> 1
|||||||factorial --> 2
|||||||factorial --> 6
|||||||factorial --> 24
|||||||factorial --> 120
|||||||factorial --> 720
|||||||factorial --> 5040
|||||||factorial --> 40320
|||||||factorial --> 362880
|||||||factorial --> 3628800
3628800
```

Related Topics

Core Functions

status

```
status(  
    s_name  
)  
=> g_switchValue
```

Description

Returns the value of the internal system variable named. This `nlambda` function also works in SKILL++ mode.

See the `sstatus` function for a list of the Internal System Variables.

Arguments

| | |
|---------------|-----------------------------------|
| <i>s_name</i> | Name of internal system variable. |
|---------------|-----------------------------------|

Value Returned

| | |
|----------------------|---|
| <i>g_switchValue</i> | Status of the internal system variable, usually either <code>t</code> or <code>nil</code> . |
|----------------------|---|

Examples

Checks the status of `debugMode` and returns `t` if `debugMode` is on.

```
status( debugMode )  
=> t
```

The `status` function gets a switch. The `sstatus` function sets a switch.

```
status debugMode      ; read the current value of the switch  
=> nil  
  
sstatus debugMode t ; set the value of the switch to new value  
=> t  
  
status debugMode  
=> t
```

Related Topics

Core Functions

sstatus

theEnvironment

```
theEnvironment(  
    [ u_funobj ]  
)  
=> e_environment / nil
```

Description

(SKILL++ mode only) Returns the top level environment if called from a SKILL++ top-level. Returns the enclosing lexical environment if called within a SKILL++ function. Returns the associated environment if passed a SKILL++ function object. Otherwise returns `nil`.

- In SKILL++, there is a unique top-level environment that implicitly encloses all other local environments. If you do not pass the optional argument, when you call `theEnvironment` from a SKILL++ top-level, `theEnvironment` returns this environment. The `schemeTopLevelEnv` function also returns this environment.
- If you call `theEnvironment` from within a SKILL++ function and if you do not pass the optional argument, `theEnvironment` returns the enclosing lexical environment.
- If you are in debug mode, you can pass a closure to `theEnvironment`. A *closure* is another term for a function object returned by evaluating a SKILL++ `lambda` expression which abstractly, consists of two parts:
 - ❑ The code for the `lambda` expression.
 - ❑ The environment in which the free variables in the body are bound when the `lambda` expression is evaluated.
- If you call `theEnvironment` from a SKILL function and do not pass a *closure*, then `theEnvironment` function returns `nil`.

Arguments

| | |
|------------------------------|---|
| <code><i>u_funobj</i></code> | Optional argument. Should be a SKILL++ closure. |
|------------------------------|---|

Value Returned

| | |
|-----------------------------------|--|
| <code><i>nil</i></code> | Returned when called from a SKILL function and you do not pass a SKILL++ closure as the optional argument. |
| <code><i>e_environment</i></code> | Either the top-level environment, or the enclosing environment, or the closure's environment. |

Examples

Returns the environment that the `let` expression establishes. The value of `z` is an environment in which `x` is bound to 3. Each time you execute the above expression, it returns a different environment object, as you can tell by observing the print representation.

```
Z = let( ( x )
        x = 3
        theEnvironment()
      ) ; let
=> envobj:0x1e0060
```

Uses `theEnvironment` to illustrate that the variable initialization expressions in a `let` expression refer to the enclosing environment.

```
Z = let( (( x theEnvironment() ))
        x
      )
=> envobj:0x2fc018
eq( schemeTopLevelEnv() Z ) => t
```

Uses `theEnvironment` to illustrate that the variable initialization expressions in a `letrec` expression refers to the `letrec`'s environment.

```
V = letrec( (( x theEnvironment() ))
            x
          )
=> envobj:0x33506c
eq( schemeTopLevelEnv() V ) => nil
eq( V~>x V ) => t
```

Returns the environment that the nested `let` expressions establish. Notice that assigning it to the top-level variable `W` makes it persistent.

```
W = let( (( r 3 ) ( y 4 ))
        let( (( z 5 ) ( v 6 ))
              theEnvironment()
            ) ; let
        ) ; let
=> envobj:0x456030c
W~>r => 3
W~>z => 5
W~>?? => ((z(5) (v 6)) ((r 3) y(4)))
```

Returns a function object which, in turn, returns its local environment.

```
Q = letrec(
  ( ;; begin locals
    ( X 6 )
    ( self
      lambda( ( )
        theEnvironment()
      ) ; lambda
    ) ; self
  ) ;; end of locals
  self
) ; letrec
=> funobj:0x1e38b8
```


Cadence SKILL Language Reference

Core Functions

```
Q() => envobj:0x1e00e4  
theEnvironment( Q ) => envobj:0x1e00e4 ;in debug mode only
```

Related Topics

Core Functions

unbindVar

```
unbindVar(  
    s_varName  
)  
=> t
```

Description

Resets a SKILL or Scheme variable so that its value becomes unbound.

Arguments

| | |
|------------------|-------------------------|
| <i>s_varName</i> | The name of a variable. |
|------------------|-------------------------|

Value Returned

| | |
|---|------------------------------------|
| t | The variable is not bound anymore. |
|---|------------------------------------|

Examples

```
myVar = 42  
unbindVar(myVar)  
boundp('myVar)  
=> nil ; this variable is not bound anymore
```

Related Topics

[Core Functions](#)

Function and Program Structure

This topic lists the SKILL functions related to function and program structure operations.

| | | |
|--|--|---|
| <u>addDefstructClass</u> | <u>alias</u> | <u>apply</u> |
| <u>argc</u> | <u>argv</u> | <u>begin</u> |
| <u>clearExitProcs</u> | <u>declareLambda</u> | <u>declareNLambda</u> |
| <u>declareSQNLambda</u> | <u>defdynamic</u> | <u>defglobalfun</u> |
| <u>define</u> | <u>define_syntax</u> | <u>defmacro</u> |
| <u>defsetf</u> | <u>defun</u> | <u>defUserInitProc</u> |
| <u>destructuringBind</u> | <u>dynamic</u> | <u>dynamicLet</u> |
| <u>err</u> | <u>error</u> | <u>errset</u> |
| <u>errsetstring</u> | <u>eval</u> | <u>fboundp</u> |
| <u>flet</u> | <u>funcall</u> | <u>getd</u> |
| <u>getFnWriteProtect</u> | <u>getFunType</u> | <u>getVarWriteProtect</u> |
| <u>globalProc</u> | <u>isCallable</u> | <u>isMacro</u> |
| <u>labels</u> | <u>lambda</u> | <u>let</u> |
| <u>letrec</u> | <u>letseq</u> | <u>mprocedure</u> |
| <u>nlambda</u> | <u>nprocedure</u> | <u>procedure</u> |
| <u>procedurep</u> | <u>prog</u> | <u>prog1</u> |
| <u>prog2</u> | <u>progn</u> | <u>putd</u> |
| <u>setf_dynamic</u> | <u>setFnWriteProtect</u> | <u>setVarWriteProtect</u> |
| <u>unalias</u> | <u>unwindProtect</u> | <u>warn</u> |

addDefstructClass

```
addDefstructClass(  
    s_name  
)  
=> u_classObject
```

Description

Creates a class for the `defstruct`.

By default, an instance of a `defstruct` does not have a class. You cannot use `Instance` to instantiate this class. Use the instantiation function created by `defstruct`.

Using `addDefstructClass` to create a class for a `defstruct` allows you to define methods for a `defstruct`.

Arguments

| | |
|---------------|--|
| <i>s_name</i> | The name of the <code>defstruct</code> . |
|---------------|--|

Value Returned

| | |
|----------------------|-------------------|
| <i>u_classObject</i> | The class object. |
|----------------------|-------------------|

Examples

```
defstruct( card rank suit )  
=> t  
  
x = _card( ?rank 8 ?suit "spades" )  
=> array[4]:3897312  
type( x )  
=> card  
findClass( 'card' )  
=> nil  
classOf( x )  
=> nil  
addDefstructClass( card )  
=> funobj:0x1c98f8  
className( classOf( x ) )  
=> card
```

Related Topics

Function and Program Structure

Cadence SKILL Language Reference

Function and Program Structure

Instance

alias

```
alias(  
    s_aliasName  
    s_functionName  
)  
=> s_aliasName
```

Description

Defines a symbol as an alias for a function. This is an `nlambda` function.

Defines the *s_aliasName* symbol as an alias for the *s_functionName* function, which must already have been defined. The `alias` function does not evaluate its arguments. Use the `alias` function only to speed up interactive command entry and never in programs.

Arguments

| | |
|-----------------------|---|
| <i>s_aliasName</i> | Symbol name of the alias. |
| <i>s_functionName</i> | Name of the function you are creating an alias for. |

Value Returned

| | |
|--------------------|--------------------|
| <i>s_aliasName</i> | Name of the alias. |
|--------------------|--------------------|

Examples

Aliases `path` to the `getSkillPath` function.

```
alias path getSkillPath  
=> path
```

Aliases `e` to the `edit` function.

```
alias e edit  
=> e
```

Related Topics

[Function and Program Structure](#)

apply

```
apply(  
    slu_func  
    [g_arg ...]  
    l_args  
)  
=> g_result
```

Description

Applies the given function to the given argument list.

`apply` takes two or more arguments. The first argument must be the name of a function, or a function object, or a list containing a `lambda`/`nlambda`/`macro` expression. The remainder of the arguments are used to construct the list of arguments passed to the function specified by the first argument; the `g_arg` arguments are individual arguments, which are prepended to the `l_args` argument to create a combined list of arguments.

Note: The last argument to `apply` must always be a list.

The argument list `l_args` is bound to the formal arguments of `slu_func` according to the type of function. For `lambda` functions the length of `l_args` should match the number of formal arguments, unless keywords or optional arguments exist. For `nlambda` and `macro` functions, `l_args` is bound directly to the single formal parameter of the function.

Note: If `slu_func` is a macro, `apply` evaluates it only once, that is, it expands it and returns the expanded form, but does not evaluate the expanded form again (as `eval` does).

Arguments

| | |
|-----------------|--|
| <i>slu_func</i> | Name of the function. |
| <i>g_arg</i> | Optional arguments that are prepended to <i>l_args</i> to create a combined list of arguments. |
| <i>l_args</i> | Argument list to apply to the function. |

Value Returned

| | |
|-----------------|---|
| <i>g_result</i> | The result of applying the function to the given arguments. |
|-----------------|---|

Cadence SKILL Language Reference

Function and Program Structure

Examples

```
apply('plus (list 1 2) )      ; Apply plus to its arguments.
=> 3

procedure( sumTail(l) apply( 'plus cdr(l)))
=> sumTail                    ;Define a procedure
sumTail( '(1 2 3))
=> 5

apply('plus list(1 2 3 4))    ; adds 1, 2, 3 and 4
=> 10

apply('plus 1 2 list(3 4))    ; adds 1, 2, 3 and 4.
=> 10
```

Related Topics

[Function and Program Structure](#)

argc

```
argc(  
    )  
=> n / 0 / -1 / -2
```

Description

Returns the number of arguments passed to a SKILL script. Used to enhance the SKILL script environment. This function works only for scripting with SKILL standalone executable (skill).

Arguments

None

Value Returned

| | |
|----------|--|
| <i>n</i> | <i>n</i> arguments were passed (<i>n</i> is an integer). |
| 0 | No arguments were passed, but <code>argv(0)</code> has a value. |
| -1 | Argument list is <code>nil</code> (no arguments passed, and <code>argv(0)</code> is <code>nil</code>). This can occur when using SKILL interactively. |
| -2 | Error caused by a problem with the argument list property. |

Examples

Assume that arguments passed to a SKILL script file are ("my.il" "1st" "2nd" "3rd"):

```
argc() => 3
```

An example using a SKILL executable:

```
$ skill -V  
  @(#) $CDS: skill version 07.02 09/19/2007 09:08 (cat61lnx) $  
$ cat /tmp/foo.il  
  (printf "argc is %d, argv[0] is %s, argv is %L\n" (argc) (argv 0) (argv))  
$ skill /tmp/foo.il -someArg -someArg2  
  argc is 2, argv[0] is /tmp/foo.il, argv is ("-someArg" "-someArg2")
```

Cadence SKILL Language Reference

Function and Program Structure

Related Topics

Function and Program Structure

argv

argv

```
argv(  
    [ x_int ]  
)  
=> g_result
```

Description

Returns the arguments passed to a SKILL script. Used to enhance the SKILL script environment. This function works only for scripting with SKILL standalone executable (skill).

Arguments

x_int It must be a positive integer.

Value Returned

g_result The return value depends on the arguments passed.

- `argv()` - List of all arguments (list of strings or `nil`).
- `argv(0)` - Name of the calling script.
- `argv(n)` - *n*th argument as a string or `nil` if there is no *n*th argument.

Examples

Assume that arguments passed to a SKILL script file are (`"my.il"` `"1st"` `"2nd"` `"3rd"`):

```
argv()  
=> ("1st" "2nd" "3rd")  
argv(0)  
=> "my.il"  
argv(1)  
=> "1st"  
argv(4)  
=> nil
```

An example using a SKILL executable:

```
$ skill -V  
@(#) $CDS: skill version 07.02 09/19/2007 09:08 (cat61lnx) $  
$ cat /tmp/foo.il
```

Cadence SKILL Language Reference

Function and Program Structure

```
(printf "argc is %d, argv[0] is %s, argv is %L\n" (argc) (argv 0) (argv))  
$ skill /tmp/foo.il -someArg -someArg2  
argc is 2, argv[0] is /tmp/foo.il, argv is ("-someArg" "-someArg2")
```

Related Topics

[Function and Program Structure](#)

begin

```
SKILL mode
  begin(
    g_exp1
    [ g_exp2 ...
      g_expN ]
  )
=> g_result
SKILL++ mode
begin(
  def1
  [ def2 ...
    defN ]
)
=> g_result
```

Description

In the SKILL mode, `begin` is a syntax form used to group a sequence of expressions. Evaluates expressions from left to right and returns the value of the last expression. Equivalent to `progn`. This expression type is used to sequence side effects such as input and output. Whereas, in the SKILL++ mode, `begin` is a syntax form used to group either a sequence of expressions or a sequence of definitions.

```
begin( exp1 [exp2 ... expN] )
```

The expressions are evaluated sequentially from left to right, and the value of the last expression is returned. This expression type is used to sequence side effects such as input and output.

```
begin( [def1 def2 ... defN] )
```

This form is treated as though the set of definitions is given directly in the enclosing context. It is most commonly found in macro definitions.

Arguments

g_exp1, *g_exp2*, *g_expN*

Arbitrary expressions.

Value Returned

g_result

Value of the last expression, *g_expN*.

Cadence SKILL Language Reference

Function and Program Structure

Examples

The following example describes the begin function in the SKILL mode.

```
begin( x = 1 y = 2 z = 3 )  
=> 3
```

The following example describes the begin function in the SKILL++ mode.

```
begin( x = 1 y = 2 z = 3 )  
=> 3  
begin( define( x 1 ) define( y 2 ) define( z 3 ) )  
=> z
```

Related Topics

[Function and Program Structure](#)

[progn](#)

clearExitProcs

```
clearExitProcs(  
    [ g_tcovItem ]  
)  
=> t
```

Description

Removes all registered exit procedures. When the optional argument *g_tcovItem* is set to *t*, it removes all exit procedures except those needed for the `ilTCov` reports.

Arguments

| | |
|-------------------|---|
| <i>g_tcovItem</i> | Optional argument, which when set to <i>t</i> does not clear the <i>tCov</i> exit hook. |
|-------------------|---|

Value Returned

| | |
|----------|---|
| <i>t</i> | Registered exit procedures are removed. |
|----------|---|

Examples

```
clearExitProcs( )  
=> t
```

Related Topics

[Function and Program Structure](#)

declareLambda

```
declareLambda (  
    s_name1 ... s_nameN  
)  
=> s_nameN
```

Description

Tells the evaluator that certain (forward referenced) functions are of `lambda` type (as opposed to `nlambda` or `macro`).

Declares *s_name1* ... *s_nameN* as procedures (`lambdas`) to be defined later. This is much like C's "extern" declarations. Because the calling sequence for `nlambdas` is different from that of `lambdas`, the evaluator needs to know the function type in order to generate more efficient code. Without the declarations, the evaluator can still handle things properly, but with some performance penalty. The result of evaluating this form is the last name given (in addition to the side-effects to the evaluator).

This (and `declareNLambda`) form has effect only on undefined function names, otherwise it is ignored. Also, when the definition is provided later, if it is of a different function type (for example, declared as `lambda` but defined as `nlambda`) a warning will be given and the definition is used regardless of the declaration. In this case (definition is inconsistent with declaration), if there is any code already loaded that made forward references to these names, that part of code should be reloaded in order to use the correct calling sequence.

Arguments

s_name1 One or more function names.

Value Returned

s_nameN The last name in the arguments.

Examples

```
declareLambda(fun1 fun2 fun3)  
=> fun3
```

Related Topics

[Function and Program Structure](#)

declareNLambda

```
declareNLambda (
    s_name1 ... s_nameN
)
=> s_nameN
```

Description

Tells the evaluator that certain (forward referenced) functions are of `nlambda` type (as opposed to `lambdas` or `macros`).

Declares `s_name1 ... s_nameN` as `nprocedures` (`nlambdas`) to be defined later. This is much like C's "extern" declarations. Because the calling sequence for `nlambdas` is different from that of `lambdas`, the evaluator needs to know the function type in order to generate more efficient code. Without the declarations, the evaluator can still handle things properly, but with some performance penalty. The result of evaluating this form is the last name given (in addition to the side-effects to the evaluator).

Arguments

| | |
|----------------------|-----------------------------|
| <code>s_name1</code> | One or more function names. |
|----------------------|-----------------------------|

Value Returned

| | |
|----------------------|---------------------------------|
| <code>s_nameN</code> | The last name in the arguments. |
|----------------------|---------------------------------|

Examples

```
declareNLambda(nfun1 nfun2 nfun3)
=> nfun3
```

Related Topics

[Function and Program Structure](#)

declareSQNLambda

```
declareSQNLambda (
    s_functionName ...
)
=> nil
```

Description

Declares the given `nlambda` functions to be *solely-quoting nlambda*s.

This is an `nlambda` function. The named functions are defined as `nlambda`s only to save typing the explicit quotes to the arguments.

The compiler has been instructed to allow the calling of these kinds of `nlambda`s from SKILL++ code without giving a warning message.

All the debugging commands have been declared as `SQNLambda`s already.

Arguments

s_functionName Function to be declared as a *solely-quoting nlambda*.

Value Returned

`nil` This function is for side-effects only.

Examples

```
declareSQNLambda ( step next stepout )
=> nil
```

Related Topics

[Function and Program Structure](#)

defdynamic

```
defdynamic(  
    s_varName  
    g_Value  
    [ t_docString ]  
)  
=> g_value
```

Description

This syntax form sets the dynamic variable *s_varName* to *g_value*. In SKILL, this function works as a `defvar`. In Scheme, *g_value* is evaluated in the current lexical scope.

Arguments

| | |
|--------------------|---|
| <i>s_varName</i> | Name of the dynamic variable. |
| <i>g_Value</i> | New value of the dynamic variable. |
| <i>t_docString</i> | A documentation string (currently ignored). |

Value Returned

| | |
|----------------|--------------------------------|
| <i>g_value</i> | Value of the dynamic variable. |
|----------------|--------------------------------|

Examples

```
kx  
=> *Error* eval: unbound variable - kx  
(inScheme x = 0 (defdynamic kx x "test") kx)  
=> *Error* eval: unbound variable - kx  
kx  
=> 0
```

Related Topics

[Function and Program Structure](#)

defglobalfun

```
defglobalfun(  
    s_funcName  
    ( l_formalArglist )  
    g_expr1 ...  
)  
=> s_funcName
```

Description

Defines a global function with the name and formal argument list you specify.

The functions that you define using `defglobalfun` are defined within a lexical scope, but are globally accessible.

For `defglobalfun` there must be white space between *s_funcName* and the open parenthesis. Expressions within the function can reference any variable on the formal argument list or any global variable defined outside the function. If necessary, local variables can be declared using the `let` function.

Arguments

| | |
|------------------------|---|
| <i>s_funcName</i> | Name of the function you are defining. |
| <i>l_formalArglist</i> | Formal argument list. |
| <i>g_expr1</i> | Expression or expressions to be evaluated when <i>s_funcName</i> is called. |

Value Returned

| | |
|-------------------|---|
| <i>s_funcName</i> | The name of the function being defined. |
|-------------------|---|

Examples

Define two global functions, `test_set` and `test_get` using `defglobalfun` and that reference a lexical variable *secret_val*:

```
toplevel 'ils  
ILS-<2> (let ((secret_val 1))  
  (defglobalfun test_set (x) secret_val = x)  
  (globalProc test_get() secret_val)  
)
```

Cadence SKILL Language Reference

Function and Program Structure

```
ILS-<2> test_get ()  
=> 1  
  
ILS-<2> test_set (2)  
=> 2  
  
ILS-<2> test_get ()  
=> 2
```

Related Topics

[Function and Program Structure](#)

define

```
define(  
    s_var  
    g_expression  
)  
=> s_var  
  
define(  
    (  
        s_var  
        [ s_formalVar1 ... ]  
    )  
    g_body ...  
)  
=> s_var
```

Description

(SKILL++ mode only) Is a syntax form used to provide a definition for a global or local variable. The `define` syntax form has two variations.

Definitions are allowed only at the top-level of a program and at the beginning or within the body of following syntax forms: `define` (another call to `define`), `lambda`, `let`, `letrec`, `defun`, and `letseq`. If occurring within a body, the `define`'s variable is local to the body.

■ Top Level Definitions

A definition occurring at the top level is equivalent to an assignment statement to a global variable.

■ Internal Definitions

A definition that occurs within the body of a syntax form establishes a local variable whose scope is the body.

■ **define(s_var g_expression)**

This is the primary variation. The other variation can be rewritten in this form. The expression is evaluated in enclosing lexical environment and the result is assigned or bound to the variable.

■ **define((s_var [s_formalVar1 ...]) g_body)**

In this variation, body is a sequence of one or more expressions optionally preceded by one or more nested definitions. This form is equivalent to the following `define`

```
define( s_var  
    lambda(( [sformalVar1 ...] ) g_body ...)
```

Examples

■ First variation

```
define( x 3 )
=> x
define( addTwoNumbers lambda( ( x y ) x+y ) )
=> addTwoNumbers
```

■ Second variation

```
define( ( addTwoNumbers x y ) x+y )
=> addTwoNumbers
```

■ Local definition using second variation

```
let( (( x 3 ))
      define( ( add y ) x+y ) ; define
      add( 5 )
    )
    ; let
=> 8
```

Defines a local function `add`, then invokes it.

```
let( ()
      define( ( f n )
                if( n > 0 then n*f(n-1) else 1 ) ; if
              ) ; define
      f( 5 )
    )
    ; let
=> 120
```

Declares a single recursive local function `f` that computes the factorial of its argument. The `let` expression returns the factorial of 5.

Related Topics

Function and Program Structure

[let](#)

[letrec](#)

[letseq](#)

define_syntax

```
define_syntax(  
    s_name  
    g_expander ...  
)  
=> s_name
```

Description

Creates a syntax rule using the `syntax_rule` expander form.

Arguments

| | |
|-------------------|---|
| <i>s_name</i> | Name of the syntax rule. |
| <i>g_expander</i> | Expander form, which can be of the form <code>(syntax_rules (...))</code> . |

Value Returned

| | |
|---------------|--|
| <i>s_name</i> | A macro expression, which evaluates to a single argument procedure that performs the specified syntactic transformation. |
|---------------|--|

Examples

```
(define_syntax incf  
  (syntax_rules ()  
    ((location) (setf location (add1 location)))  
    ((location amount) (setf location (plus location amount)))))  
=> incf  
x=3 => 3  
(incf x) => 4  
x => 4  
(incf x 3) => 7  
x => 7  
x='(1 2 3) => (1 2 3)  
(incf (cadr x)) => 3  
x => (1 3 3)  
(incf (car x) 5) => 6  
x => (6 3 3)
```

Related Topics

[Function and Program Structure](#)

defmacro

```
defmacro (
    s_macroName
    ( l_formalArglist )
    g_expr1 ...
)
=> s_macroName
```

Description

Defines a macro which can take a list of formal arguments including @optional, @key, and @rest (instead of the more restrictive format as required by using mprocedure).

The arguments will be matched against the formals before evaluating the body.

Arguments

| | |
|------------------------|--|
| <i>s_macroName</i> | Name of the macro you are defining. |
| <i>l_formalArglist</i> | Formal argument list. |
| <i>g_expr1</i> | Expression or expressions to be evaluated. |

Value Returned

| | |
|--------------------|--------------------------------------|
| <i>s_macroName</i> | The name of the macro being defined. |
|--------------------|--------------------------------------|

Examples

```
defmacro ( whenNot (cond @rest body)
    `(if ! ,cond then ,@body) )
=> whenNot

expandMacro ( '(whenNot x > y z = f(y) x*z) )
=> if(!(x > y) then (z = (f y)) (x * z))

whenNot(1 > 2 "hello" 1+2)
=> 3
```

Related Topics

[Function and Program Structure](#)

defsetf

```
defsetf(  
    s_accessFn  
    s_updateFn  
)  
=> setf_<s_accessFn>
```

Description

`defsetf` is a macro that allows you to specify an update function to use when `setf()` is called with a place using a given access function. It creates a macro with the prefix `setf_` which is used by `setf` to update a value at the place given by `s_accessFn()`.

Arguments

| | |
|-------------------|--|
| <i>s_accessFn</i> | The access function name which <code>setf</code> is expected to handle. |
| <i>s_updateFn</i> | The name of a function or macro which replaces the value at the place accessed by <code>s_accessFn</code> . The function or macro must accept the same number of arguments as <code>s_accessFn</code> plus one additional argument containing the new value. |

Value Returned

setf_<s_accessFn>

A macro which is used in `setf`.

Examples

```
; a personal CAR function to distinguish from the built-in car  
defun(CAR (x) car(x))  
; update function which replaces the car of the list with a new value  
defun(SETCAR (x new)  
    car(rplaca(x new))  
)  
defsetf(CAR SETCAR)  
  
test_ls='(1 2 3 4 5 6)  
; use := operator which is equivalent to setf()
```

Cadence SKILL Language Reference

Function and Program Structure

```
CAR(test_ls) := 10
assert(test_ls == '(10 2 3 4 5 6))
```

Related Topics

[Function and Program Structure](#)

defun

```
defun (
    s_funcName
    ( l_formalArglist )
    g_expr1 ...
)
=> s_funcName
```

Description

Defines a function with the name and formal argument list you specify. This is a syntax form.

The body of the procedure is a list of expressions to be evaluated one after another when *s_funcName* is called. There must be no white space between `defun` and the open parenthesis that follows.

However, for `defun` there must be white space between *s_funcName* and the open parenthesis. This is the only difference between the `defun` and `procedure` forms. `defun` has been provided principally so that you can your code appear more like other LISP dialects.

Expressions within a function can reference any variable on the formal argument list or any global variable defined outside the function. If necessary, local variables can be declared using the `let` function.

Arguments

| | |
|------------------------|---|
| <i>s_funcName</i> | Name of the function you are defining. |
| <i>l_formalArglist</i> | Formal argument list. |
| <i>g_expr1</i> | Expression or expressions to be evaluated when <i>s_funcName</i> is called. |

Several parameters provide flexibility in procedure argument lists. These parameters are referred to as @ (“at” sign) options. The parameters are `@rest`, `@optional`, `@key`, and `@aux`. See [procedure](#) for a detailed description of these argument list parameters.

Value Returned

| | |
|-------------------|---|
| <i>s_funcName</i> | The name of the function being defined. |
|-------------------|---|

Cadence SKILL Language Reference

Function and Program Structure

Examples

```
procedure( cube(x) x**3 )      ; Defines a function to compute the
=> cube                        ; cube of a number using procedure.
```

```
cube( 3 )
=> 27
```

```
defun( cube (x) x**3 )        ; Defines a function to compute the
=> cube                        ; cube of a number using defun.
```

The following function computes the factorial of its positive integer argument by recursively calling itself.

```
procedure( factorial(x)
  if( (x == 0) then 1
    else x * factorial(x - 1))
=> factorial
```

```
defun( factorial (x)
  if( (x == 0) then 1
    else x * factorial( x - 1))
=> factorial
```

```
factorial( 6 )
=> 720
```

Related Topics

[Function and Program Structure](#)

[let](#)

defUserInitProc

```
defUserInitProc(  
    t_contextName  
    u_func  
    [ autoInit ]  
)  
=> ( t_contextName s_procName )
```

Description

Registers a user-defined function that the system calls immediately after autoloading a context.

Lets you customize existing Cadence contexts. In the general case, most Cadence-supplied contexts have internally defined an initialization function through the `defInitProc` function. This function defines a second initialization function, called after the internal initialization function, thereby allowing you to customize on top of Cadence supplied contexts. This is best done in the `.cdsinit` file.

Arguments

| | |
|----------------------|--|
| <i>t_contextName</i> | Name of context file to load. |
| <i>u_func</i> | Function to be called when context file is loaded. |
| <i>[autoInit]</i> | |

Value Returned

```
((t_contextName s_procName))
```

Always returns an association list when set up. The function is not called at this point, but is called when the *t_contextName* context is loaded.

Examples

```
defUserInitProc( "myContext" 'initMyContext)  
=> ( ("myContext" initMyContext))
```

Cadence SKILL Language Reference

Function and Program Structure

Related Topics

Function and Program Structure

defInitProc

callInitProc

destructuringBind

```
destructuringBind(  
    l_variables  
    l_expression  
    [ g_body ]  
)  
=> g_result
```

Description

Enables you to bind value to variables in a list. The list of values is obtained by evaluating the *l_expression*. The `destructuringBind` macro then evaluates the *g_body* form.

`destructuringBind` does not check the correctness of *l_variables*.

Arguments

| | |
|---------------------|---|
| <i>l_variables</i> | A simple or a complex list. A complex list is a list that can include other lists. You can also use <code>@optional</code> , <code>@key</code> , and <code>@rest</code> in this list as a procedure or a function's argument list. |
| <i>l_expression</i> | An expression that is evaluated and its result is assigned or bound to the corresponding variable in <i>l_variables</i> . |
| <i>g_body</i> | A sequence of one or more expressions. |

Value Returned

| | |
|-----------------|--|
| <i>g_result</i> | The evaluated result of the last expression in <i>g_body</i> . |
|-----------------|--|

Examples

■ Simple case:

```
(destructuringBind (a b) '(1 2) a+b )  
=> 3
```

■ Complex case: assume `myBBox()` returns `((0 0) (5 5))`

```
(destructuringBind (p1 p2) myBBox()  
printf( "%L and %L points of a bounding box" p1 p2))  
(0 0) and (5 5) points of a bounding box
```


Cadence SKILL Language Reference

Function and Program Structure

```
=> t
(destructuringBind ((x1 y1) (x2 y2)) myBBox()
printf( "(%L %L) and (%L %L) points of a bounding box" x1 y1 x2 y2))
(0 0) and (5 5) points of a bounding box
=> t
```

■ Optional case

```
(destructuringBind (a b @optional (c 1)) '(1 2 5)
printf("a=%L b=%L c=%L\n" a b c) a+b )
a=1 b=2 c=5
=> 3
```

■ Keyword case: assume myKeys() returns (100 ?key1 "Hello" ?key2 "World")

```
(destructuringBind (v1 @key key1 key2) myKeys()
printf( "Position value %L and key values %L %L" v1 k1 k2))
Position value 100 and key values "Hello" "World"
=> t
```

Related Topics

Function and Program Structure

dynamic

```
dynamic(  
    s_varName  
)  
=> g_value / error
```

Description

This syntax form returns the value of the dynamic variable *s_varName*. If *s_varName* is not a dynamic variable, it returns an error.

Arguments

| | |
|------------------|-------------------------------|
| <i>s_varName</i> | Name of the dynamic variable. |
|------------------|-------------------------------|

Value Returned

| | |
|----------------|--|
| <i>g_value</i> | Value of the dynamic variable <i>s_varName</i> . |
|----------------|--|

Examples

```
kx  
=> *Error* toplevel: undefined variable - kx  
(inScheme x = 9 (setf (dynamic kx) x))  
9=>  
kx  
=>9
```

Related Topics

[Function and Program Structure](#)

dynamicLet

```
dynamicLet (  
  (  
    [(s_var1 g_init1)  
     (s_var2 g_init2)  
     ...]  
  )  
=> g_result
```

Description

Evaluates the init forms (*g_init1*, *g_init2*, ...) in the current lexical environment, and then binds the variables (*s_var1*, *s_var2*, ...) in parallel. The variables are bound as SKILL dynamic variables for the duration of the body forms.

In SKILL, this syntax form is compiled as a `let()`.

Arguments

| | |
|------------------|--|
| <i>s_varName</i> | Name of a dynamically scoped local variable. |
|------------------|--|

Value Returned

| | |
|-----------------|---|
| <i>g_result</i> | The result of the last executed expression in the body. |
|-----------------|---|

Examples

```
(dynamicLet ((X 21))  
  (let ((a 100)  
        b)  
    (dynamicLet ((X a)  
                  (Y (progn b=12  
                           13)))  
      (printf "(inSkill X) == %L\n" (inSkill X))  
      (printf "a == %L\n" a)  
      (assert (inSkill X) == a)  
      (assert (inSkill X) == 100)  
      (assert (inSkill Y) == 13)  
      (assert a == 100)  
      (assert b == 12)))  
    (assert (inSkill X) == 21))  
  (inSkill X) == 100  
  a == 100  
  nil
```

Cadence SKILL Language Reference

Function and Program Structure

```
(inScheme (dynamicLet ((X 21))
  (let ((a 100)
        b)
    (dynamicLet ((X a)
                  (Y (progn b=12
                             13)))
      (printf "(inSkill X) == %L\n" (inSkill X))
      (printf "a == %L\n" a)
      (assert (inSkill X) == a)
      (assert (inSkill X) == 100)
      (assert (inSkill Y) == 13)
      (assert a == 100)
      (assert b == 12)))
    (assert (inSkill X) == 21))
)

(inSkill X) == 100
a == 100
nil
```

Related Topics

Function and Program Structure

err

```
err(  
    [ g_value ]  
)  
=> none
```

Description

Causes an error.

If this error is caught by an `errset`, `nil` is returned by that `errset`. However, if the optional *g_value* argument is given then *g_value* is returned from the `errset` and can be used to identify which `err` signaled the error. The `err` function never returns a value.

Arguments

| | |
|----------------|--|
| <i>g_value</i> | SKILL object that becomes the return value for <code>errset</code> . |
|----------------|--|

Value Returned

Never returns a value.

Examples

```
errset( err( 'ErrorType))  
=> (ErrorType)  
errset.errset  
=> nil  
  
procedure( test( x )  
    if( (equal errset( foo( x )) 'throw))  
        then println( "Throw caught" )  
        else if( errset.errset println( "Error: divide by  
zero"))))=> test  
  
procedure( foo( x )  
    if( (equal (4 / x) 1)  
        then err( 'throw )  
        else println( x ))=> foo  
  
test( 4 ) => nil          ; Prints Throw caught  
test( 2 ) => nil          ; Prints 2  
test( 0 ) => nil          ; Prints Error: divide by zero
```

Cadence SKILL Language Reference

Function and Program Structure

Related Topics

Function and Program Structure

error

error

```
error(  
    t_formatString  
    [ g_arg1 ... ]  
)  
  
error  
    [ S_message1  
      [ S_message2 ] ... ]  
)  
=> none
```

Description

Prints error messages and calls `err`.

Prints the `S_message1` and `S_message2` error messages if they are given and then calls `err`, causing an error. The first argument can be a format string, which causes the rest of the arguments to be printed in that format.

Arguments

| | |
|-----------------------------|---|
| <code>t_formatString</code> | Characters to be printed verbatim, intermixed with format specifications prefixed by the % sign. |
| <code>g_arg1</code> | The arguments following the format string are printed according to their corresponding format specifications. |
| <code>S_message1</code> | Message string or symbol. |
| <code>S_message2</code> | More message strings or symbols. More than two arguments should be given only if the first argument is a format string. |

Value Returned

Prints the `S_message1` and `S_message2` error messages if they are given and then calls `err`, causing an error. `error` never returns.

Examples

Prints `*Error* myFunc: Bad List`

```
error( "myFunc" "Bad List")
```

Cadence SKILL Language Reference

Function and Program Structure

Prints **Error** bad args - name 100 (1 2 3)
`error("bad args - %s %d %L" "name" 100 '(1 2 3))`

Prints out **Error** test and returns nil.

`errset(error("test") t) => nil`

Related Topics

[Function and Program Structure](#)

errset

```
errset(  
    g_expr  
    [ g_errprint ]  
)  
=> l_result / nil
```

Description

Encapsulates the execution of an expression in an environment safe from the error mechanism. This is a syntax form.

If an error occurs in the evaluation of the given expression, control always returns to the command following the `errset` instead of returning to the nearest toplevel. If `g_errprint` is non-`nil`, error messages are issued; otherwise they are suppressed. In either case, information about the error is placed in the `errset` property of the `errset` symbol. Programs can therefore access this information with the `errset.errset` construct after determining that `errset` returned `nil`.

Arguments

| | |
|-------------------|---|
| <i>g_expr</i> | Expression to be evaluated; while evaluating it, any errors cause immediate return from the <code>errset</code> . |
| <i>g_errprint</i> | Flag to control the printout of error messages. If <code>t</code> then prints the error message encountered in <code>errset</code> , defaults to <code>nil</code> . |

Value Returned

| | |
|------------------|---|
| <i>l_result</i> | List with value from successful evaluation of <i>g_expr</i> . |
| <code>nil</code> | An error occurred. |

Examples

```
errset(1+2)  
=> (3)  
errset.errset  
=> nil  
errset(sqrt('x'))  
=> nil
```

Because `sqrt` requires a numerical argument.

Cadence SKILL Language Reference

Function and Program Structure

```
errset.errset  
=> ("sqrt" 0 t nil ("*Error* sqrt: can't handle sqrt(x)...))
```

When working in the CIW, to ensure that the `errset.errset` variable is not modified internally in the Virtuoso Studio design environment, do not separate `errset` and `errset.errset`. For example, use this construct:

```
errset(sqrt('x)), errset.errset  
=> ("sqrt" 0 t nil ("*Error* sqrt: cannot handle sqrt(x)"))
```

Related Topics

Function and Program Structure

error

errsetstring

```
errsetstring(  
    t_string  
    [ g_errprint ]  
    [ s_langMode ]  
)  
=> l_value / nil
```

Description

Reads and evaluates an expression stored in a string. Same as `evalstring` except that it calls `errset` to catch any errors that might occur during the parsing and evaluation.

If an error has occurred, `nil` is returned, otherwise a list containing the value of the evaluation is returned. Should an error occur, it is stored in `errset.errset`. If `errprint` is non-`nil`, error messages are printed out; otherwise they are suppressed.

Arguments

| | |
|-------------------|---|
| <i>t_string</i> | String to be evaluated. |
| <i>g_errprint</i> | Flag for controlling the printout of error messages. If <code>t</code> , then prints the error message encountered in <code>errset</code> . Defaults to <code>nil</code> . |
| <i>s_langMode</i> | Symbol to determine the language mode to use. The valid values are: <ul style="list-style-type: none">■ <code>'ils</code>, which indicates that the given string is evaluated in SKILL++ mode.■ <code>'il</code>, which indicates that the given string is evaluated in SKILL code. This is the default mode. |

Value Returned

| | |
|----------------|---|
| <i>l_value</i> | List with the value from successful evaluation of <i>t_string</i> . |
| <i>nil</i> | An error occurs. |

Examples

```
errsetstring("1+2")  
=> (3)
```

Cadence SKILL Language Reference

Function and Program Structure

```
errsetstring("1+'a")  
=> nil
```

Returns *nil* because an error occurred.

```
errsetstring("1+'a" t)  
=> nil  
Prints out error message  
=>*Error* plus: can't handle (1+a)...
```

Related Topics

[Function and Program Structure](#)

[error](#)

[evalstring](#)

eval

```
eval(  
    g_expression  
    [ e_environment ]  
)  
=> g_result
```

Description

Evaluates an argument and returns its value. If an environment argument is given, *g_expression* is treated as SKILL++ code, and the expression is evaluated in the given (lexical) environment. Otherwise *g_expression* is treated as SKILL code.

This function gives you control over evaluation. If the optional second argument is not supplied, it takes *g_expression* as SKILL code. If an environment argument is given, it treats *g_expression* as SKILL++ code, and evaluates it in the given (lexical) environment.

For SKILL++'s `eval`, if the given environment is not the top-level one, the effect is like evaluating *g_expression* within a `let` construct for the bindings in the given environment, with the following exception:

If *g_expression* is a definitional form (such as `(define ...)`), it is treated as a global definition instead of local one. Therefore any variables defined will still exist after executing the `eval` form.

Arguments

| | |
|----------------------|--|
| <i>g_expression</i> | Any SKILL expression. |
| <i>e_environment</i> | If this argument is given, SKILL++ semantics is assumed. The forms entered will be evaluated within the given (lexical) environment. |

Value Returned

| | |
|-----------------|--|
| <i>g_result</i> | Result of evaluating <i>g_expression</i> . |
|-----------------|--|

Examples

Evaluates the expression `plus(2 3)`.

```
eval( 'plus( 2 3 ) )    => 5
```

Cadence SKILL Language Reference

Function and Program Structure

Evaluates the symbol `x` and returns the value of symbol `x`.

```
x = 5                => 5
eval( 'x ' )         => 5
```

Evaluates the expression `max(2 1)`.

```
eval( list( 'max 2 1 ' ) ) => 2
```

Related Topics

[Function and Program Structure](#)

[evalstring](#)

evalstring

```
evalstring(  
    t_string  
    [ s_langMode ]  
)  
=> g_value / nil
```

Description

Reads and evaluates an expression stored in a string.

The resulting value is returned. Notice that `evalstring` does not allow the outermost set of parentheses to be omitted from the evaluated expression, as in `load` or in the top level.

Arguments

| | |
|-------------------|---|
| <i>t_string</i> | String containing the SKILL expression to be evaluated. |
| <i>s_langMode</i> | Symbol to determine the language mode to use. The valid values are: <ul style="list-style-type: none">■ <code>'ils</code>, which indicates that the given string is evaluated in SKILL++ mode.■ <code>'il</code>, which indicates that the given string is evaluated in SKILL code. This is the default mode. |

Value Returned

| | |
|----------------|--|
| <i>g_value</i> | The value of the argument expression after evaluation. |
| <i>nil</i> | No form is read. |

Examples

The `1+2` infix notation is the same as `(plus 1 2)`.

```
evalstring("1+2")  
=> 3
```

The following example signals that `car` is an unbound variable.

```
evalstring("cons('a '(b c))")  
=> (a b c)
```

Cadence SKILL Language Reference

Function and Program Structure

```
car '(1 2 3)
=> 1
evalstring("car '(1 2 3)")
```

Related Topics

[Function and Program Structure](#)

expandMacro

```
expandMacro(  
    g_form  
)  
=> g_expandedForm
```

Description

Expands one level of macro call for a form.

Checks if the given form *g_form* is a macro call and returns the expanded form if it is. Otherwise it returns the original argument. The macro expansion is done only once (one level). That is, if the expanded form is another macro call, it is not further expanded (unless another `expandMacro` is called with the expanded form as its argument).

Arguments

| | |
|---------------|--------------------------------|
| <i>g_form</i> | Form that can be a macro call. |
|---------------|--------------------------------|

Value Returned

| | |
|-----------------------|---|
| <i>g_expandedForm</i> | Expanded form or the original form if the given argument is not a macro call. |
|-----------------------|---|

Examples

```
mprocedure( testMsg(args)  
    `(printf "test %s -- %L\n" , (cadr args)progn(,@(cddr args))) )  
=> testMsg  
  
expandMacro( '(testMsg "alpha1" y = f(x) g(y 100)) )  
=> printf("test %s -- %L\n" "alpha1"  
    progn((y = (f x)) (g y 100)))
```

Related Topics

[Function and Program Structure](#)

[defmacro](#)

fboundp

```
fboundp(  
    s_functionName  
)  
=> g_definition / nil
```

Description

Returns the function binding, if defined, for a specified function name.

The function examines only the current function binding and does not check for any potential definitions from autoloading. `fboundp` can be considered as an alias to `getd`.

Arguments

| | |
|-----------------------|-------------------------------------|
| <i>s_functionName</i> | Name to check for function binding. |
|-----------------------|-------------------------------------|

Value Returned

| | |
|---------------------|---|
| <i>g_definition</i> | If the function is defined in SKILL, returns the function object that the procedure function associates with a symbol. If the function is primitive, the binary definition is printed. |
| nil | No function definition exists for the specified function name. |

Examples

```
fboundp( 'xyz )  
=> nil ;assuming there is no function named xyz  
  
fboundp( 'defstruct )  
=> funobj:0x261108 ;a non-nil result  
  
fboundp( 'cadr )  
=> lambda:cadr  
  
fboundp( 1 )  
=> nil
```

Related Topics

[Function and Program Structure](#)

flet

```
flet(  
    l_bindings  
    [g_body]  
)  
=> g_result
```

Description

Enables you to define local functions with LET semantics.

The names of functions defined by `flet` retain their local definitions only within the body of `flet`. Also, the function definition bindings are visible only in the body of `flet`. This helps in defining a local version of function which in turn calls the global version of the function with the same name but with different arguments.

`flet` can only be used in Scheme mode.

Arguments

| | |
|-------------------|---|
| <i>l_bindings</i> | A list of variables or a list of the form (<i>s_variable</i> <i>g_value</i>). |
| <i>g_body</i> | A sequence of one or more expressions. |

Value Returned

| | |
|-----------------|-----------------------|
| <i>g_result</i> | Result of evaluation. |
|-----------------|-----------------------|

Examples

```
(flet ((foo (x) (list x))) (foo 1))  
=> (1)
```

Related Topics

[Function and Program Structure](#)

funcall

```
funcall(  
    slu_func  
    [ arg ... ]  
)  
=> g_result
```

Description

Applies the given function to the given arguments.

The first argument to `funcall` must be either the name of a function or a `lambda/nlambda/macro` expression or a function object. The rest of the arguments are to be passed to the function.

The arguments `arg ...` are bound to the formal arguments of `slu_func` according to the type of function. For `lambda` functions the length of `arg` should match the number of formal arguments, unless keywords or optional arguments exist. For `nlambda` and `macro` functions, `arg` are bound directly to the single formal parameter of the function.

If `slu_func` is a macro, `funcall` evaluates it only once, that is, it expands it and returns the expanded form, but does not evaluate the expanded form again (as `eval` does).

Arguments

| | |
|-----------------|---|
| <i>slu_func</i> | Name of the function. |
| <i>arg</i> | Arguments to be passed to the function. |

Value Returned

| | |
|-----------------|---|
| <i>g_result</i> | The result of applying the function to the given arguments. |
|-----------------|---|

Examples

```
funcall( 'plus 1 2 )           ; Apply plus to its arguments.  
=> 3  
  
procedure( sum3(x y z) funcall( 'plus x y z)  
=> sum3                       ; Define a procedure  
sum3(1 2 3)  
=> 6
```

Cadence SKILL Language Reference

Function and Program Structure

Related Topics

Function and Program Structure

getd

```
getd(  
    s_functionName  
)  
=> g_definition / nil
```

Description

Returns the function binding for a function name.

In Scheme mode, function bindings are treated as regular value bindings. Therefore, `getd()` returns any value bound to the symbol.

Arguments

| | |
|-----------------------|-----------------------|
| <i>s_functionName</i> | Name of the function. |
|-----------------------|-----------------------|

Value Returned

| | |
|---------------------|---|
| <i>g_definition</i> | If the function is defined in SKILL, returns the function object that the procedure function associates with a symbol. If the function is primitive, the binary definition is printed. |
| nil | No function definition exists. |

Examples

The function is primitive.

```
getd( 'alias )  
=> nlambda:alias
```

The function is written in SKILL.

```
getd( 'edit )  
=> funobj:0x24b478
```

Related Topics

[Function and Program Structure](#)

getFnWriteProtect

```
getFnWriteProtect(  
    s_name  
)  
=> t / nil
```

Description

Checks if the given function is write-protected. The value is `t` if *s_name* is write-protected. Else, it is `nil`.

Arguments

| | |
|---------------|-----------------------|
| <i>s_name</i> | Name of the function. |
|---------------|-----------------------|

Value Returned

| | |
|------------------|--|
| <code>t</code> | The function is write protected. |
| <code>nil</code> | The function is not write protected. It signals an error if the function is not defined. |

Examples

```
getFnWriteProtect( 'strlen )  
=> t
```

Related Topics

[Function and Program Structure](#)

getFunType

```
getFunType (
    u_functionObject
)
=> s_functionObject_type
```

Description

Returns a symbol denoting the function type for a given function object. Possible function types include `lambda`, `nlambda`, `macro`, `syntax`, or `primop`.

Arguments

u_functionObject A function object.

Value Returned

s_functionObject_type

Possible return values include `lambda`, `nlambda`, `macro`, `syntax`, or `primop`.

Examples

```
getFunType( getd( 'sin ))
=> lambda
getFunType( lambda( (x y) x+y ))
=> lambda
getFunType( getd( 'breakpt ))
=> nlambda
getFunType( getd( 'if ))
=> syntax
getFunType( getd( 'plus ))
=> primop
```

Related Topics

[Function and Program Structure](#)

[defmacro](#)

getVarWriteProtect

```
getVarWriteProtect(  
    s_name  
)  
=> t / nil
```

Description

(SKILL mode only) Checks if a variable is write-protected. Does not work in SKILL++ mode. In SKILL++ mode, use `getFnWriteProtect` instead.

Arguments

| | |
|---------------|--------------------------------|
| <i>s_name</i> | Name of the variable to check. |
|---------------|--------------------------------|

Value Returned

| | |
|-----|--------------------------------------|
| t | The variable is write-protected. |
| nil | The variable is not write-protected. |

Examples

Returns `nil` if the variable `x` is not write protected.

```
x = 5  
getVarWriteProtect( 'x )  
=> nil
```

Related Topics

[Function and Program Structure](#)

globalProc

```
globalProc(  
    s_funcName(  
        l_formalArglist  
    )  
    g_expr1 ...  
)  
=> s_funcName
```

Description

Defines a global function using a formal argument list. The functions that you define using `globalProc` are defined within a lexical scope, but are globally accessible.

The body of `globalProc` is a list of expressions to be evaluated one after another when *s_funcName* is called. There must be no white space between `globalProc` and the open parenthesis that follows, nor between *s_funcName* and the open parenthesis of *l_formalArglist*. However, for `defglobalfun` there must be white space between *s_funcName* and the open parenthesis. This is the only difference between the two functions.

Expressions within a function can reference any variable on the formal argument list or any global variable defined outside the function. If necessary, local variables can be declared using the `let` or `prog` functions.

Arguments

| | |
|------------------------|---|
| <i>s_funcName</i> | Name of the function you are defining. |
| <i>l_formalArglist</i> | Formal argument list. |
| <i>g_expr1</i> | Expression or expressions to be evaluated when <i>s_funcName</i> is called. |

Value Returned

| | |
|-------------------|-------------------------------------|
| <i>s_funcName</i> | Name of the function being defined. |
|-------------------|-------------------------------------|

Examples

Define two global functions, `test_set` and `test_get` using `globalProc` that reference a lexical variable *secret_val*:

Cadence SKILL Language Reference

Function and Program Structure

```
toplevel 'ils
ILS-<2> (let ((secret_val 1))
  (defglobalfun test_set (x) secret_val = x)
  (globalProc test_get() secret_val)
)
ILS-<2> test_get()
=> 1

ILS-<2> test_set(2)
=> 2

ILS-<2> test_get()
=> 2
```

Related Topics

[Function and Program Structure](#)

isCallable

```
isCallable(  
    s_function  
)  
=> t / nil
```

Description

Checks if a function is defined or is autoloadable from a context.

Arguments

| | |
|-------------------|---------------------|
| <i>s_function</i> | Name of a function. |
|-------------------|---------------------|

Value Returned

| | |
|-----|---|
| t | The specified function is defined or is autoloadable. |
| nil | The specified function is not defined or is not autoloadable. |

Examples

```
isCallable( 'car)  
=> t  
  
procedure( myFunction( x ) x+1)  
isCallable('myFunction)  
=> t
```

Related Topics

[Function and Program Structure](#)

isMacro

```
isMacro(  
    s_symbolName  
)  
=> t / nil
```

Description

Checks if the given symbol denotes a macro.

Arguments

| | |
|---------------------|------------------|
| <i>s_symbolName</i> | Symbol to check. |
|---------------------|------------------|

Value Returned

| | |
|-----|---|
| t | The given symbol denotes a macro. |
| nil | The given symbol does not denote a macro. |

Examples

```
(isMacro 'plus)  
=> nil  
(isMacro 'defmacro)  
=> t
```

Related Topics

[Function and Program Structure](#)

[defmacro](#)

labels

```
labels(  
    l_bindings  
    [ g_body ]  
)  
=> g_result
```

Description

Enables you to define local functions with LET semantics.

`labels` is similar to the `flet` function except that in `labels`, the scope of name bindings for the functions defined by `labels` encompasses the function body as well as the function definitions themselves.

`labels` can only be used in Scheme mode.

Arguments

| | |
|-------------------|---|
| <i>l_bindings</i> | A list of variables or a list of the form (<i>s_variable</i> <i>g_value</i>). |
| <i>g_body</i> | A sequence of one or more expressions. |

Value Returned

| | |
|-----------------|-----------------------|
| <i>g_result</i> | Result of evaluation. |
|-----------------|-----------------------|

Examples

```
(labels ((sum (x)  
          (if (plusp x)  
              x + (sum (sub1 x))  
              0)))  
  (sum 10))  
=> 55
```

Related Topics

[Function and Program Structure](#)

lambda

```
lambda (
  ( s_formalArgument )
  g_expr1 ...
)
=> U_result
```

Description

Defines a function without a name. This is a syntax form.

The keywords `lambda` and `nlambda` allow functions to be defined without having names. This is useful for writing temporary or local functions. In all other respects `lambda` is identical to the `procedure` form.

Arguments

| | |
|-------------------------|---|
| <i>s_formalArgument</i> | Formal argument for the function definition. |
| <i>g_expr1</i> | SKILL expression to be evaluated when the function is called. |

Value Returned

| | |
|-----------------|--------------------|
| <i>U_result</i> | A function object. |
|-----------------|--------------------|

Examples

```
(lambda ( (x y) x + y ) 5 6)
=> 11
```

Related Topics

[Function and Program Structure](#)

let

```
SKILL mode
let(
  l_bindings
  g_expr1 ...
)
=> g_result
SKILL++ mode
let(
  [ s_var ]
  (
    ( s_var1 s_initExp1 )
    ( s_var2 s_initExp2 )
    ...
  )
  body
)
=> g_result
```

Description

In the SKILL mode, this function provides a faster alternative to `prog` for binding local variables only. This is a `syntax` form. In the SKILL++ mode, this function declares a lexical scope. This includes a collection of local variables, as well as body expressions to be evaluated. This becomes a named `let` if the optional `s_var` is given.

The SKILL mode argument `l_bindings` is either a list of variables or a list of the form `(s_variable g_value)`. The bindings list is followed by one or more forms to be evaluated. The result of the `let` form is the value of the last `g_expr`.

`let` is preferable to `prog` in all circumstances where a single exit point is acceptable, and where the `go` and `label` constructs are not required.

Whereas, the functions, `let`, `letseq`, and `letrec` give SKILL++ a block structure. The syntax of the three constructs is similar, but they differ in the regions they establish for their variable bindings.

- In a `let` expression, the initial values are computed before any of the variables become bound.
- In a `letseq` expression, the bindings and evaluations are performed sequentially.
- In a `letrec` expression, all the bindings are in effect while their initial values are being computed, thus allowing mutually recursive definitions.

Cadence SKILL Language Reference

Function and Program Structure

Use the `let` form to declare a collection of local variables. You can provide an initialization expression for each variable. The order of evaluation of the initialization expressions is unspecified. Each variable has the body of the `let` expression as its lexical scope. This means that the initialization expressions should not cross-references to the other local variables.

In SKILL++ mode, local defines can appear at the beginning of the body of a `let`, `letseq`, or `letrec` form.

Arguments

| | |
|-------------------|---|
| <i>l_bindings</i> | (SKILL mode) Local variable bindings, can either be bound to a value or <code>nil</code> (the default). |
| <i>g_expr1</i> | (SKILL mode) Any number of expressions. |
| <i>s_var</i> | (SKILL++ mode) When the optional <i>s_var</i> is given, this becomes a named <code>let</code> . A named <code>let</code> is just like an ordinary <code>let</code> except that <i>s_var</i> is bound within the body to a function whose formal arguments are the bound variables and whose body is <i>body</i> . |
| <i>s_var1</i> | (SKILL++ mode) Name of local variable. The variables are bound to fresh locations holding the result of evaluating the corresponding <i>initExp</i> . |
| <i>s_initExp</i> | (SKILL++ mode) Expression evaluated for the initial value. The <i>initExps</i> are evaluated in the current environment (in some unspecified order). |
| <i>body</i> | (SKILL++ mode) A sequence of one or more expressions. The expressions in (<i>body</i>) are evaluated sequentially in the extended environment. Each local variable binding has <i>body</i> as its scope. |

Value Returned

| | |
|-----------------|--|
| <i>g_result</i> | The result of the last expression evaluated. |
|-----------------|--|

Examples

The following example describes the use of the `let` function in the SKILL mode.

```
x = 5
let( ((x '(a b c)) y)
      println( y )           ; Prints nil.
```

Cadence SKILL Language Reference

Function and Program Structure

```
x)
=> (a b c) ; Returns the value of x.

procedure( test( x y )
  let( ((x 6) (z "return string"))
    if( (equal x y)
      then z
      else nil)))
test( 8 6 ) ; Call function test.
=> "return string" ; z is returned because 6 == 6.
```

The following example describes the use of the `let` function in the SKILL++ mode.

```
let( ( ( x 2 ) ( y 3 ) )
  x*y
)
=> 6

let( ( ( x 2 ) ( y 3 ) )
  let( (( z 4 ))
    x + y + z
  ) ; let
) ; let
=> 9

let( ( ( x 2 ) ( y 3 ) )
  let( (( x 7 ) ( foo lambda( ( z ) x + y + z ) ) )
    foo( 5 )
  ) ; let
) ; let
=> 10 ;not 15

let( ((x 2) (y 3))
  define( f(z) x*z+y)
  f(5)
)
=> 13
```

Related Topics

[Function and Program Structure](#)

[letrec](#)

[letseq](#)

letrec

```
letrec (
    (
        ( s_var1 s_initExp1 )
        ( s_var2 s_initExp2 )
        ...
    )
    body
)
=> g_result
```

Description

(SKILL++ mode) A `letrec` expression can be used *in SKILL++ mode only*. All the bindings are in effect while their initial values are being computed, thus allowing mutually recursive definitions. Use `letrec` to declare recursive local functions.

Recursive `let` form. Each binding of a variable has the entire `letrec` expression as its scope, making it possible to define mutually recursive procedures.

Use `letrec` when you want to declare recursive local functions. Each initialization expression can refer to the other local variables being declared, with the following restriction: each initialization expression must be executable without accessing any of those variables.

For example, a `lambda` expression satisfies this restriction because its body gets executed only when called, not when it's defined.

Arguments

| | |
|-------------------|--|
| <i>s_var</i> | Name of a local variable. The variables are bound to fresh locations holding undefined values. Each variable is assigned to the result of the corresponding <i>initExp</i> . |
| <i>s_initExp1</i> | Expressions evaluated for the initial value. The <i>initExps</i> are evaluated in the resulting environment (in some unspecified order). |
| <i>body</i> | A sequence of one or more expressions. The expressions in <i>body</i> are evaluated sequentially in the extended environment. |

Value Returned

| | |
|-----------------|---|
| <i>g_result</i> | Value of the last expression of <i>body</i> . |
|-----------------|---|

Examples

The following example declares a single recursive local function. The local function `f` computes the factorial of its argument. The `letrec` expression returns the factorial of 5.

```
letrec(
  ( ;; variable list
    ( f
      lambda( ( n )
        if( n > 0 then n*f(n-1) else 1
        ) ; if
      ) ; lambda
    ) ; f
  ) ; variable list
  f( 5 )
) ; letrec
=> 120
```

Related Topics

[Function and Program Structure](#)

letseq

```
letseq(  
    (  
        ( s_var1 initExp1 )  
        ( s_var2 initExp2 )  
        ...  
    )  
    body  
)  
=> g_result
```

Description

A `letseq` expression can be used in both SKILL and SKILL++ modes. The bindings and evaluations are performed sequentially.

Use `letseq` to control the order of evaluation of the initialization expressions. `letseq` is similar to `let`, but the bindings are performed sequentially from left to right, and the scope of a binding indicated by (*var1* *initExp1*) is that part of the `letseq` expression to the right of the binding. Thus the second binding is done in an environment in which the first binding is visible, and so on.

This form is equivalent to a corresponding sequence of nested `let` expressions. It is also equivalent to `let*` is the standard Scheme syntax. This function is equivalent of `let*()` but it is strongly recommended using this function over `let*()`.

Arguments

| | |
|----------------|---|
| <i>s_var</i> | Name of a local variable. Each variable is assigned to the result of the corresponding <i>initExp</i> . |
| <i>initExp</i> | Expressions evaluated for the initial value. The <i>initExps</i> are evaluated sequentially in the environments that result from previous bindings. |
| <i>body</i> | A sequence of one or more expressions. |

Value Returned

| | |
|-----------------|---|
| <i>g_result</i> | Value of the last expression of <i>body</i> . |
|-----------------|---|

Cadence SKILL Language Reference

Function and Program Structure

Examples

```
letseq( ( ( x 1 ) ( y x+1 ) )
        y
      ) ; letseq
=> 2
```

The example above is a more convenient equivalent to the code below in which you control the sequence explicitly by the nesting.

```
let( ( ( x 1 ) )
      let( ( ( y x+1 ) )
            y
          )
    )
```

Related Topics

[Function and Program Structure](#)

mprocedure

```
mprocedure (  
    s_macroName (  
        s_formalArgument  
    )  
    g_expr1 ...  
)  
=> s_funcName
```

Description

Defines a macro with the given name that takes a single formal argument. This is a `syntax` form.

The body of the macro is a list of expressions to be evaluated one after another. The value of the last expression evaluated is considered the result of `macro` expansion and is evaluated again to get the value of the macro call.

When a `macro` is called, *s_formalArgument* is bound to the entire macro call form, that is, a list with the name of the macro as its first element followed by the unevaluated arguments to the macro call.

Macros in SKILL are completely general in that a `macro` body can call any other function to build an expression that is to be evaluated again.

Note: A macro call within a function definition is expanded only once, when the function is compiled. For this reason, be cautious when defining macros. `sure` they are purely functional, that is, side-effects free. You can use `expandMacro` to verify the correct behavior of a macro definition.

Arguments

| | |
|-------------------------|--|
| <i>s_macroName</i> | Name of the macro function. |
| <i>s_formalArgument</i> | Formal arguments for the macro definition. |
| <i>g_expr1</i> | A SKILL expression. |

Value Returned

| | |
|-------------------|----------------------------|
| <i>s_funcName</i> | Name of the macro defined. |
|-------------------|----------------------------|

Cadence SKILL Language Reference

Function and Program Structure

Examples

```
mprocedure ( whenNot (callForm)
              `(if !, (cadr callForm) then ,@(caddr callForm)))
=> whenNot

expandMacro ( '(whenNot x>y z=f(y) x*z))
=> if (! (x>y) then (z=f(y)) (x*z))

whenNot (1>2 "Good")
=> "Good"
```

Related Topics

[Function and Program Structure](#)

[defmacro](#)

nlambda

```
nlambda (
  (
    s_formalArgument
  )
  g_expr1 ...
)
=> u_result
```

Description

(SKILL mode only) Allows `nlambda` functions to be defined without having names. In all other respects, `nlambda` is identical to `nprocedure`. This is a syntax form that is not supported in SKILL++ mode.

Allowing `nlambda` functions to be defined without having names is useful for writing temporary or local functions. In all other respects `nlambda` is identical to `nprocedure`.

An `nlambda` function should be declared to have a single formal argument. When evaluating an `nlambda` function, SKILL collects all the argument expressions unevaluated into a list and binds that list to the single formal argument. The body of the `nlambda` can selectively evaluate the elements of the argument list.

In general, it is preferable to use `lambda` instead of `nlambda` because `lambda` is more efficient. In most cases, `nlambdas` can be easily replaced by macros (and perhaps helper functions).

Arguments

| | |
|-------------------------|--|
| <i>s_formalArgument</i> | Formal argument for the function definition. |
| <i>g_expr1</i> | SKILL expressions to be evaluated when the function is called. |

Value Returned

| | |
|-----------------|--------------------|
| <i>u_result</i> | A function object. |
|-----------------|--------------------|

Examples

```
putd( 'foo nlambda( (x) println( x )))
=> funobj:0x309128
```

Cadence SKILL Language Reference

Function and Program Structure

```
apply( nlambda((y) foreach(x y printf(x))) '("Hello" "World\n"))
HelloWorld
=> ("Hello" "World\n")
```

Related Topics

Function and Program Structure

nprocedure

```
nprocedure (  
    s_funcName (  
        s_formalArgument  
    )  
    g_expr1 ...  
)  
=> s_funcName
```

Description

(SKILL mode only) Defines an `nlambda` function with a function name and a single formal argument. This is a syntax form that is not supported in SKILL++ mode.

The body of the procedure is a list of expressions to be evaluated one after another. The value of the last expression evaluated is returned as the value of the function. There must be no white space separating the *s_funcName* and the open parenthesis of the list containing *s_formalArgument*.

An `nlambda` function defined by `nprocedure` differs from a `lambda` function defined by `procedure` in that an `nlambda` function does not evaluate its arguments; it binds the whole argument list to its single formal argument. `lambda` functions, on the other hand, evaluate each argument in the argument list and bind them one by one to each formal argument on the formal argument list. It is recommended that `procedure` be used over `nprocedure` whenever possible, in part because `procedure` is faster and also offers better type checking.

In general, it is preferable to use `lambda` instead of `nlambda` because `lambda` is more efficient.

Arguments

| | |
|-------------------------|--|
| <i>s_funcName</i> | Name of newly defined function. |
| <i>s_formalArgument</i> | Formal argument for the function definition. |
| <i>g_expr1</i> | SKILL expressions to be evaluated when the function is called. |

Value Returned

| | |
|-------------------|---|
| <i>s_funcName</i> | Returns the name of the function defined. |
|-------------------|---|

Examples

Defines a `lambda` function.

```
procedure( printarg(x) println(x))  
=> printarg
```

Defines an `nlambda` function.

```
nprocedure( nprintarg(x) println(x))  
=> nprintarg
```

Calls a `lambda` function. Prints the value 20. `println` returns `nil`. `y = 10`

```
=> 10  
printarg(y * 2)  
20  
=> nil
```

Calls an `nlambda` function. Prints a list of the unevaluated arguments. `println` returns `nil`.

```
nprintarg(y * 2)  
((y * 2))  
=> nil
```

Related Topics

[Function and Program Structure](#)

procedure

```
procedure (  
    s_funcName (  
        l_formalArglist  
    )  
    g_expr1 ...  
)  
=> s_funcName
```

Description

Defines a function using a formal argument list. The body of the procedure is a list of expressions to evaluate.

The body of the procedure is a list of expressions to be evaluated one after another when *s_funcName* is called. There must be no white space between `procedure` and the open parenthesis that follows, nor between *s_funcName* and the open parenthesis of *l_formalArglist*. However, for `defun` there must be white space between *s_funcName* and the open parenthesis. This is the only difference between the two functions. `defun` has been provided principally so that you can your code appear more like other LISP dialects.

The last argument in *l_formalArglist* can be a string denoting type-checking characters, specified using the argument type template.

Expressions within a function can reference any variable on the formal argument list or any global variable defined outside the function. If necessary, local variables can be declared using the `let` or `prog` functions.

Arguments

| | |
|------------------------|---|
| <i>s_funcName</i> | Name of the function you are defining. |
| <i>l_formalArglist</i> | Formal argument list. |
| <i>g_expr1</i> | Expression or expressions to be evaluated when <i>s_funcName</i> is called. |

Value Returned

| | |
|-------------------|-------------------------------------|
| <i>s_funcName</i> | Name of the function being defined. |
|-------------------|-------------------------------------|

Cadence SKILL Language Reference

Function and Program Structure

Examples

```
procedure( cube(x) x**3 )      ; Defines a function to compute the
=> cube                        ; cube of a number using procedure.

cube( 3 ) => 27

defun( cube (x) x**3 )        ; Defines a function to compute the
=> cube                        ; cube of a number using defun.
```

The following function computes the factorial of its positive integer argument by recursively calling itself.

```
procedure( factorial(x)
  if( (x == 0) then 1
    else x * factorial(x - 1)))
=> factorial

defun( factorial (x)
  if( (x == 0) then 1
    else x * factorial( x - 1)))
=> factorial

factorial( 6 )
=> 720
```

ARGUMENT LIST PARAMETERS

Several parameters provide flexibility in procedure argument lists. These parameters are referred to as @ (“at”) options. The parameters are @rest, @optional, @key, and @aux.

@rest Option

The @rest option allows an arbitrary number of arguments to be passed into a function. Let’s say you need a function that takes any number of arguments and returns a list of them in reverse order. Using the @rest option simplifies this task.

Note: The name of the parameter following @rest is changeable. The r has been used for convenience.

```
procedure( myReverse( @rest r )
  reverse( r ))
=> myReverse

myReverse( 'a 'b 'c )
=> (c b a)
```

@optional Option

The @optional option gives you another way to specify a flexible number of arguments. With @optional, each argument on the argument list is matched up with an argument on the formal argument list. If you place @optional in the argument list of a procedure definition, any argument following it is considered optional.

Cadence SKILL Language Reference

Function and Program Structure

You can provide any optional argument with a default value. Specify the default value using a default form. The default form is a two-member list. The first member of this list is the optional argument's name. The second member is the default value.

The default value is assigned only if no value is assigned when the function is called. If the procedure does not specify a default value for a given argument, `nil` is assigned.

The following is an outline of a procedure that builds a box of a certain length and width.

```
procedure (buildbox (length width @optional (xcoord 0)
                  (ycoord 0) color)
  .
  .
)
```

Both *length* and *width* must be specified when this function is called. However, the color and the coordinates of the box are declared as optional parameters. If only two parameters are specified, the optional parameters are given their default values. For *xcoord* and *ycoord*, those values are 0. Since no value is specified for *color*, *color*'s default value is `nil`.

Examine the following calls to `buildbox` and their return values:

```
buildbox(1 2); Builds a box of length 1, width 2
              ; at the coordinates (0,0) with the default color nil
buildbox(3 4 5.5 10.5); Builds a box of length 3, width 4
              ; at coordinates (5.5,10.5) with the default color nil
buildbox(3 4 5 5 'red); Builds a box of length 3, width 4
              ; at coordinates (5,5) with the default color red.
```

As illustrated in the above examples, `@optional` relies on order to determine what arguments are assigned to each formal argument. When relying on order is too lengthy or inconvenient, another “at” sign parameter, `@key`, provides an alternative.

@key Option

`@key` and `@optional` are mutually exclusive; they cannot appear in the same argument list. The `@key` option lets you specify the expected arguments in any order.

For example, examine the following function:

```
procedure (setTerm (@key (deviceType 'unknown)
                     (baudRate 9600)
                     keyClick )
  .
  .
)
```

If you call `setTerm` without arguments (that is, `setTerm()`), `deviceType` is set to `unknown`, `baudRate` to 9600, and `keyClick` to `nil`. Default forms work the same as they do

Cadence SKILL Language Reference

Function and Program Structure

for @optional. To specify a keyword for an argument (for example, deviceType, baudRate, and keyClick in the above function), precede the keyword with a question mark (?).

To set the baudRate to 4800 and the keyClick to ON, the call is:

```
setTerm(?baudRate 4800 ?keyClick 'ON)
; This sets baudRate and keyClick. Because nothing
; was specified for deviceType, it is set to its default,
; unknown.
setTerm(?keyClick 'ON ?baudRate 4800) ; Does
; the same as above.
```

In summary, there are two standard forms that procedure argument lists follow:

```
procedure(functionname([var1 var2 ...]
    [@optional opt1 opt2 ...]
    [@rest r])
    .
    .
)
procedure(functionname([var1 var2 ...]
    [@key key1 key2 ...]
    [@rest r])
    .
    .
)
```

Related Topics

[Function and Program Structure](#)

[Type Checking](#)

[defun](#)

[let](#)

procedurep

```
procedurep(  
    g_obj  
)  
=> t / nil
```

Description

Checks if an object is a procedure, or function, object.

A procedure may be a function object defined in SKILL or SKILL++, or system primitives. Symbols are not considered procedures even though they may have function bindings.

Arguments

| | |
|--------------|-------------------|
| <i>g_obj</i> | Any SKILL object. |
|--------------|-------------------|

Value Returned

| | |
|-----|---|
| t | The argument is a procedure, function, or object. |
| nil | The argument is not a procedure, function, or object. |

Examples

```
(procedurep 123 )  
=> nil  
  
(procedurep (getd 'plus))  
=> t  
  
(procedurep 'plus)  
=> nil
```

Related Topics

[Function and Program Structure](#)

[defun](#)

prog

```
prog(  
    l_localVariables  
    [  
        [ s_label ]  
        g_expr1  
    ] ...  
)  
=> g_result / nil
```

Description

Allows for local variable bindings and permits abrupt exits on control jumps. This is a syntax form.

The first argument to `prog` is a list of variables declared to be local within the context of the `prog`. The expressions following the `prog` are executed sequentially unless one of the control transfer statements such as `go` or `return` is encountered. A `prog` evaluates to the value of `nil` if no `return` statement is executed and control simply “falls through” the `prog` after the last expression is executed. If a `return` is executed within a `prog`, the `prog` immediately returns with the value of the argument given to the `return` statement.

Any statement in a `prog` can be preceded by a symbol that serves as a label for the statement. Unless multiple return points are necessary or you are using the `go` function, a faster construct for binding local variables, `let`, should be used over `prog`.

Arguments

| | |
|-------------------------|---|
| <i>l_localVariables</i> | List of variables local to <code>prog</code> . |
| <i>s_label</i> | Labels a statement inside a <code>prog</code> ; labels can be defined only for statements at the top level. Statements nested inside another statement cannot be labeled unless the surrounding statement is itself a <code>prog</code> . |
| <i>g_expr1</i> | Any SKILL expression to be evaluated inside the <code>prog</code> . |

Value Returned

| | |
|-----------------|--|
| <i>g_result</i> | Value of the <code>return</code> statement if one is used. |
| <i>nil</i> | Otherwise always returns <code>nil</code> . |

Cadence SKILL Language Reference

Function and Program Structure

Examples

```
x = "hello"
=> "hello"

prog( (x y)                ; Declares local variables x and y.
      x = 5                ; Initialize x to 5.
      y = 10               ; Initialize y to 10.
      return( x + y )
)
=> 15

x
=> "hello"                  ; The global x keeps its original value.
```

Related Topics

Function and Program Structure

let

progn

prog1

```
prog1(  
    g_expr1  
    [ g_expr2 ... ]  
)  
=> g_result
```

Description

Evaluates expressions from left to right and returns the value of the *first* expression. This is a syntax form.

Arguments

| | |
|----------------|-----------------------|
| <i>g_expr1</i> | Any SKILL expression. |
| <i>g_expr2</i> | Any SKILL expression. |

Value Returned

| | |
|-----------------|---|
| <i>g_result</i> | Value of the first expression, <i>g_expr1</i> . |
|-----------------|---|

Examples

The following example returns the value of the first expression.

```
prog1(  
    x = 5  
    y = 7 )  
=> 5
```

Related Topics

[Function and Program Structure](#)

[prog2](#)

[progn](#)

prog2

```
prog2(  
    g_expr1  
    g_expr2  
    [ g_expr3... ]  
)  
=> g_result
```

Description

Evaluates expressions from left to right and returns the value of the *second* expression. This is a syntax form.

Arguments

| | |
|----------------|-------------------------------|
| <i>g_expr1</i> | First SKILL expression. |
| <i>g_expr2</i> | Second SKILL expression. |
| <i>g_expr3</i> | Additional SKILL expressions. |

Value Returned

| | |
|-----------------|--|
| <i>g_result</i> | Value of the second expression, <i>g_expr2</i> . |
|-----------------|--|

Examples

The following example returns the value of the second expression.

```
prog2(  
    x = 4  
    p = 12  
    x = 6 )  
=> 12
```

Related Topics

[Function and Program Structure](#)

[prog1](#)

[progn](#)

progn

```
progn(  
    g_expr1 ...  
)  
=> g_result
```

Description

Evaluates expressions from left to right and returns the value of the last expression. This is a syntax form.

`progn` is useful for grouping a sequence of expressions into a single expression. As a shorthand notation for `progn`, use braces (`{ }`) to group multiple expressions into a single expression.

Arguments

g_expr1 Any SKILL expression.

Value Returned

g_result Value of the last expression evaluated.

Examples

```
progn(  
    println("expr 1")  
    println("expr 2") )  
"expr 1"  
"expr 2"  
=> nil
```

The value of `println` is `nil`. The following example uses braces.

```
{    println("expr 1")  
    println("expr 2")  
    2 + 3}  
"expr 1"  
"expr 2"  
5
```

Related Topics

[Function and Program Structure](#)

Cadence SKILL Language Reference

Function and Program Structure

let

prog1

prog2

putd

```
putd(  
    s_functionName  
    u_functionDef  
)  
=> u_functionDef
```

Description

Assigns a new function binding, which must be a function, a `lambda` expression, or `nil`, to a function name. If you just want to define a function, use `procedure` or `defun`.

Assigns the function definition of *u_functionDef* to *s_functionName*. This is different from `alias`, which does a macro expansion when evaluated. You can undefine a function name by setting its function binding to `nil`. A function name can be write-protected by the system to protect you from unintentional name collisions, in which case you cannot change the function binding of that function name using `putd`.

If you just want to define a function, use `procedure` or `defun`.

Arguments

| | |
|-----------------------|--|
| <i>s_functionName</i> | Name of the function. |
| <i>u_functionDef</i> | New function binding, which must be a binary function, a <code>lambda</code> expression, or <code>nil</code> . |

Value Returned

| | |
|----------------------|---|
| <i>u_functionDef</i> | Function definition, which is either a binary function or a SKILL expression. |
|----------------------|---|

Examples

Assigns the function `mySqrt` the same definition as `sqrt`.

```
putd( 'mySqrt getd( 'sqrt ))  
=> lambda:sqrt
```

Assigns the symbol `newFn` a function definition that prints the string `This is a new function` when called.

Cadence SKILL Language Reference

Function and Program Structure

```
putd( 'newFn lambda( () println( "This is a new function" )) )  
=> funobj:0x3cf088
```

Related Topics

Function and Program Structure

setf_dynamic

```
setf_dynamic(  
    g_value  
    s_name  
)  
=> g_value
```

Description

Evaluates *g_value* in the current lexical scope and updates the SKILL variable named *s_name*.

Arguments

| | |
|----------------|---|
| <i>g_value</i> | New value of dynamic variable <i>s_name</i> . |
| <i>s_name</i> | Name of the dynamic variable. |

Value Returned

| | |
|----------------|------------------------------------|
| <i>g_value</i> | New value of the dynamic variable. |
|----------------|------------------------------------|

Examples

```
kx  
=>0  
(inScheme x = 9 (setf (dynamic kx) x))  
=>9  
kx  
=>9
```

Related Topics

[Function and Program Structure](#)

setFnWriteProtect

```
setFnWriteProtect(  
    s_name  
)  
=> t / nil
```

Description

Prevents a named function from being redefined.

If *s_name* has a function value, it can no longer be changed. If it does not have a function value but does have an autoload property, the autoload is still allowed. This is treated as a special case so that all the desired functions can be write-protected first and autoloaded as needed.

Arguments

| | |
|---------------|-----------------------|
| <i>s_name</i> | Name of the function. |
|---------------|-----------------------|

Value Returned

| | |
|-----|---|
| t | The function is now write protected. |
| nil | If the function is already write protected. |

Examples

Define a function and set its write protection so it cannot be redefined.

```
procedure( test() println( "Called function test" ))  
setFnWriteProtect( 'test ) => t  
procedure( test() println( "Redefine function test" ))  
*Error* def: function name already in use and cannot be  
    redefined - test  
setFnWriteProtect( 'plus ) => nil
```

Returns *nil* because the *plus* function is already write protected.

Related Topics

[Function and Program Structure](#)

setVarWriteProtect

```
setVarWriteProtect(  
    s_name  
)  
=> t / nil
```

Description

(SKILL mode only) Sets the write-protection on a variable to prevent its value from being updated. Does not work in SKILL++ mode.

Use this function in SKILL mode only when the variable and its contents are to remain constant.

- If the variable has a value, it can no longer be changed.
- If the variable does not have a value, it cannot be used.
- If the variable holds a list or other data structure as its value, it is assumed that the contents will not be changed. If you try to update the contents, the behavior is unspecified.

In SKILL++ mode, use `setFnWriteProtect` instead.

Arguments

| | |
|---------------|---|
| <i>s_name</i> | Name of variable to be write-protected. |
|---------------|---|

Value Returned

| | |
|-----|---------------------------------------|
| t | Variable is write protected. |
| nil | Variable was already write protected. |

Examples

```
y = 5 ; Initialize the variable y.  
setVarWriteProtect( 'y )=> t ; Set y to be write protected.  
setVarWriteProtect( 'y )=> nil ; Already write protected.  
y = 10 ; y is write protected.  
*Error* setq: Variable is protected and cannot be  
          assigned to - y
```

Cadence SKILL Language Reference

Function and Program Structure

Related Topics

Function and Program Structure

unalias

```
unalias(  
    s_aliasName1 ...  
)  
=> l_result
```

Description

Undefines the aliases specified in an argument list and returns a list containing the aliases undefined by the call. This is `nlambda` function also works in SKILL++ mode.

Use alias for interactive command entry only and never in programs.

Arguments

| | |
|---------------------|---------------------------|
| <i>s_aliasName1</i> | Symbol name of the alias. |
|---------------------|---------------------------|

Value Returned

| | |
|-----------------|------------------------------|
| <i>l_result</i> | List of the aliases removed. |
|-----------------|------------------------------|

Examples

Aliases `path` to the `getSkillPath` function.

```
alias path getSkillPath  
=> path
```

Removes `path` as an alias.

```
unalias path  
=> (path)
```

Related Topics

[Function and Program Structure](#)

unwindProtect

```
unwindProtect (
    [ g_protectedForm ]
    [ g_cleanupForm ]
)
=> g_result
```

Description

Evaluates the *g_protectedForm* expression and then executes the SKILL *g_cleanupForm* expression. Even if the evaluation of *g_protectedForm* is interrupted or encounters an error, the *g_cleanupForm* expression is still executed. You can therefore use *g_cleanupForm* to close open file handles, reset variables, and restore the state to a known value.

If an error occurs within *g_protectedForm*, the program would normally stop after executing *g_cleanupForm*. To force continued execution despite the error, wrap `unwindProtect` with a suitable function to catch errors, such as `errset`. Even if the error is caught using `errset`, *g_cleanupForm* will still be executed.

To include more than a single expression, group expressions by using functions such as `progn`, `let`, or `prog`.

Arguments

| | |
|------------------------|---------------------------------------|
| <i>g_protectedForm</i> | Name of the function to be evaluated. |
| <i>g_cleanupForm</i> | Any valid SKILL expression. |

Value Returned

| | |
|-----------------|-------------------------------------|
| <i>g_result</i> | Result of the expression evaluated. |
|-----------------|-------------------------------------|

Examples

```
unwindProtect(undefFun() printf("cleanup form called here\n"))
```

The outputs are as follows:

```
*Error* eval: undefined function - undefFun
cleanup form called here
unwindProtect (
    {
```

Cadence SKILL Language Reference

Function and Program Structure

```
    printf("first statement\n")
    1/0
    printf("second statement\n")
}
printf("cleanup form called here\n")
)
```

The outputs are as follows:

```
first statement
*Error* quotient: Attempted to divide by zero
cleanup form called here
errset(
    unwindProtect(
    {
        printf("first statement\n")
        1/0
        printf("second statement\n")
    }
    printf("cleanup form called here\n")
)
)
    printf("program continued after error\n")
```

The outputs are as follows:

```
first statement
cleanup form called here
program continued after error
```

Related Topics

Function and Program Structure

warn

```
warn(  
    t_formatString  
    [ g_arg1 ... ]  
)  
=> nil
```

Description

Buffers a warning message with given arguments inserted using the same format specification as `sprintf`, `printf`, and `fprintf`.

After a function returns to the top level, the buffered warning message is printed in the Command Interpreter Window. Arguments to `warn` use the same format specification as `sprintf`, `printf`, and `fprintf`.

This function is useful for printing SKILL warning messages in a consistent format. You can also suppress a message with a subsequent call to `getWarn`.

Arguments

| | |
|-----------------------|---|
| <i>t_formatString</i> | Characters to print verbatim in the warning message with format specifications prefixed by the percent (%) sign. |
| <i>g_arg1 ...</i> | Optional arguments following the format string, which are printed according to their corresponding format specifications. |

Value Returned

| | |
|------------------|-----------------------------------|
| <code>nil</code> | Always returns <code>nil</code> . |
|------------------|-----------------------------------|

Examples

```
arg1 = 'fail  
warn( "setSkillPath: first argument must be a string or list of strings - %s\n"  
    arg1)  
=> nil
```

```
*WARNING* setSkillPath: first argument must be a string or list of strings - fail
```

Cadence SKILL Language Reference

Function and Program Structure

Related Topics

Function and Program Structure

Environment Functions

Various SKILL functions are available to interact with and query the system environment. The following is a list of environment functions.

[cdsGetInstPath](#)

[cdsGetToolsPath](#)

[cdsPlat](#)

[changeWorkingDir](#)

[cputime](#)

[createDir](#)

[createDirHier](#)

[csh](#)

[deleteDir](#)

[deleteFile](#)

[exit](#)

[getCurrentTime](#)

[getInstallPath](#)

[getLogin](#)

[getPrompts](#)

[getShellEnvVar](#)

[getSkillPath](#)

[getTempDir](#)

[getWorkingDir](#)

[isDir](#)

[prependInstallPath](#)

[setShellEnvVar](#)

[setSkillPath](#)

[sh, shell](#)

[system](#)

[unsetShellEnvVar](#)

[vi, vii, vil](#)

cdsGetInstPath

```
cdsGetInstPath(  
    [ t_name ]  
)  
=> t_string
```

Description

Returns the absolute path of the Cadence installation directory as a string.

`cdsGetInstPath` is for the cds root hierarchy and is meant to be used by all Virtuoso and non-Virtuoso applications.

Arguments

| | |
|---------------|--|
| <i>t_name</i> | The optional argument <i>t_name</i> is appended to the end of the cds root path with a directory separator if necessary. |
|---------------|--|

Value Returned

| | |
|-----------------|------------------------------------|
| <i>t_string</i> | The installation path as a string. |
|-----------------|------------------------------------|

Examples

```
cdsGetInstPath()  
=> "/cds/99.02/latest.il"  
cdsGetInstPath("tools")  
=> "/cds/99.02/latest.il/tools"
```

Related Topics

[Environment Functions](#)

[cdsGetToolsPath](#)

[getSkillPath](#)

cdsGetToolsPath

```
cdsGetToolsPath(  
    [ t_subDirPath ]  
)  
=> t_cdsToolsPath
```

Description

Returns the absolute path of the Cadence installation `tools` directory as a string after resolving the `tools` directory appropriately. This function is provided for multiple platform support mainly to simplify access to a common Cadence installation hierarchy for all Unix platforms.

Arguments

| | |
|---------------------|---|
| <i>t_subDirPath</i> | The optional argument <i>t_subDirPath</i> is appended to the end of the Cadence installation <code>tools</code> directory path with a directory separator if necessary. |
|---------------------|---|

Value Returned

| | |
|-----------------------|---|
| <i>t_cdsToolsPath</i> | The absolute path of the Cadence installation <code>tools</code> directory as a string. |
|-----------------------|---|

Examples

```
cdsGetToolsPath()  
=> "/cds/latest/latest.il/tools"  
cdsGetToolsPath("")  
=> "/cds/latest/latest.il/tools/"  
cdsGetToolsPath("bin")  
=> "/cds/latest/latest.il/tools/bin"
```

Related Topics

[Environment Functions](#)

[getSkillPath](#)

cdsPlat

```
cdsPlat()  
=> t_plat
```

Description

Returns the platform for the Cadence software that is currently running. The possible values are: sun4v, sol86, hppa, ibmrs, wint, lnx86, or lni64.

Arguments

None

Value Returned

t_plat The platform upon which the Cadence software is running. One of the following strings:

Examples

```
system("uname")  
=> SunOS  
    0  
cdsPlat()  
=> "sun4v"
```

Related Topics

[Environment Functions](#)

[cdsGetToolsPath](#)

[cdsGetInstPath](#)

changeWorkingDir

```
changeWorkingDir(  
    [ S_name ]  
)  
=> t
```

Description

Changes the working directory to the specified working directory.

Different error messages are printed if the operation fails because the directory does not exist or you do not have search (execute) permission.

Use this function with care: if “.” is either part of the SKILL path or the libraryPath. Changing the working directory can affect the visibility of SKILL files or design data.

Arguments

| | |
|---------------|---|
| <i>S_name</i> | Name of the working directory you want to use. Can be specified with either a relative or absolute path. If you specify a relative path, the shell environment is used to search for the directory, not the SKILL path. |
|---------------|---|

Value Returned

| | |
|---|--|
| t | The function executes successfully. Prints an error message if the directory you tried to change to does not exist. Prints a permission denied message if you do not have search permission. |
|---|--|

Examples

Assume, there is a directory /usr5/design/cpu with appropriate permission and there is no test directory under /usr5/design/cpu.

```
changeWorkingDir( "/usr5/design/cpu")  
=> t
```

The following example signals an error about a non-existent directory.

```
changeWorkingDir( "test")
```

Related Topics

Environment Functions

cdsPlat

createDir

cputime

```
cputime(  
    )  
=> x_result
```

Description

Returns the total amount of CPU time (user and system) used in units of 60ths of a second.

Arguments

None

Value Returned

| | |
|-----------------|--------------------------------|
| <i>x_result</i> | CPU time in 60ths of a second. |
|-----------------|--------------------------------|

Examples

```
cputime()  
=> 8  
  
integerp( cputime() )  
=> t  
  
floatp( cputime() )  
=> nil
```

Related Topics

Environment Functions

cdsPlat

csh

createDir

```
createDir(  
    S_name  
)  
=> t / nil
```

Description

Creates a directory.

The directory name can be specified with either an absolute or relative path; the SKILL path is used in the latter case. A path that is anchored to the current directory, for example, `./`, `../`, or `../..`, and so on is not considered as a relative path.

Arguments

| | |
|---------------|---|
| <i>S_name</i> | Name of the directory you are creating. |
|---------------|---|

Value Returned

| | |
|------------|--|
| <i>t</i> | The directory is created. |
| <i>nil</i> | The directory is not created because it already exists. Also, if the directory cannot be created because you do not have permission to update the parent directory, or a parent directory does not exist, an error is signaled. |

Examples

```
createDir("/usr/tmp/test")  
=> t  
  
createDir("/usr/tmp/test")  
=> nil ;Directory already exists.
```

Related Topics

[Environment Functions](#)

[changeWorkingDir](#)

[createDir](#)

createDirHier

```
createDirHier(  
    t_pathName  
)  
=> t / nil
```

Description

Creates all directories specified in the given SKILL path that do not already exist

The permissions associated with new directories are subject to the file creation mask on systems supporting that concept. If the directory with the specified name already exists, `nil` is returned. The directory names in the given SKILL path can be specified with either absolute or relative; the SKILL path is used in the latter case.

A path that is anchored to the current directory, for example, `./`, `../`, or `../..`, etc., is not considered as a relative path.

Arguments

| | |
|-------------------|--|
| <i>t_pathName</i> | Specifies a (hierarchical) SKILL path consisting of all the directories that need to be created. |
|-------------------|--|

Value Returned

| | |
|------------|--|
| <i>t</i> | All the directories specified in the given SKILL path are created |
| <i>nil</i> | A directory with the same name already exists or an incorrect SKILL path is specified If the directory cannot be created because you do not have permission to update the parent directory, or a parent directory does not exist, an error is signaled. |

Examples

The following example creates the directories `/dir1/dir2/` as specified in the given SKILL path.

```
createDirHier("./dir1/dir2")
```

Related Topics

Cadence SKILL Language Reference

Environment Functions

Environment Functions

createDir

csch

```
csch(  
    [ t_command ]  
)  
=> t / nil
```

Description

Starts the UNIX C-shell as a process to execute a command string.

Identical to the `sh` function, but invokes the C-shell (`csch`) rather than the Bourne-shell (`sh`).

Arguments

| | |
|------------------|----------------------------|
| <i>t_command</i> | Command string to execute. |
|------------------|----------------------------|

Value Returned

| | |
|------------|--|
| <i>t</i> | The exit status of executing the given shell command is 0. |
| <i>nil</i> | The exit status of executing the given shell command is not 0. |

Examples

The following example creates a sub-directory called `tmp` in your home directory.

```
csch( "mkdir ~/tmp" )  
=> t
```

Related Topics

Environment Functions

sh, shell

deleteDir

```
deleteDir(  
    S_name  
)  
=> t / nil
```

Description

Deletes the specified directory. The directory name can be specified with either an absolute or relative path; the SKILL path is used in the latter case. A path that is anchored to the current directory, for example, `./`, `../`, or `../..`, and so on, is not considered as a relative path.

Arguments

| | |
|---------------|----------------------------------|
| <i>S_name</i> | Name of the directory to delete. |
|---------------|----------------------------------|

Value Returned

| | |
|------------------|--|
| <code>t</code> | The directory is successfully deleted. |
| <code>nil</code> | The directory does not exist. |
| | Reports an error if you do not have permission to delete a directory or the directory you want to delete is not empty. |

Examples

Reports an error about permission violation.

```
createDir("/usr/tmp/test")  
=> t  
deleteDir("/usr/tmp/test")  
=> t  
deleteDir("/usr/bin")
```

Assuming there are some files in `~`, reports an error that the directory is not empty.

```
deleteDir("~/")
```

Related Topics

[Environment Functions](#)

Cadence SKILL Language Reference

Environment Functions

createDir

deleteFile

deleteFile

```
deleteFile(  
    S_name  
)  
=> t / nil
```

Description

Deletes a file. The file name can be specified with either an absolute or relative path; the SKILL path is used in the latter case. If a symbolic link is passed in as the argument, it is the link itself, not the file or directory referenced by the link, that gets removed. A path that is anchored to the current directory, for example, `./`, `../`, or `../..`, and so on, is not considered as a relative path.

Arguments

| | |
|---------------|----------------------------------|
| <i>S_name</i> | Name of file you want to delete. |
|---------------|----------------------------------|

Value Returned

| | |
|-----|---|
| t | File is successfully deleted. |
| nil | File does not exist or signals an error if you do not have permission to delete a file. |

Examples

In the following example, the named file exists and is deleted.

```
deleteFile("~/test/out.1") => t
```

In the following example, the named file does not exist.

```
deleteFile("~/test/out.2") => nil
```

When you do not have write permission for `/bin`, an error is printed about permission violation in CIW.

```
deleteFile("/bin/ls")
```

Related Topics

Environment Functions

Cadence SKILL Language Reference

Environment Functions

deleteDir

exit

```
exit(  
    [ x_status ]  
)  
=> nil
```

Description

Causes SKILL to exit with a given process status (defaults to 0), whether in interactive or batch mode.

Use `exit` functions to customize the behavior of an exit call. Sometimes you might like to do certain cleanup actions before exiting SKILL. You can do this by registering `exit-before` and/or `exit-after` functions.

An `exit-before` function is called before `exit` does anything, and an `exit-after` function is called after `exit` has performed its bookkeeping tasks and just before it returns control to the operating system. The user-defined exit functions do not take any arguments.

To give you even more control, an `exit-before` function can return the atom `ignoreExit` to abort the exit call totally. When `exit` is called, first all the registered `exit-before` functions are called in the reverse order of registration. If any of them returns the special atom `ignoreExit`, the exit request is aborted and it returns `nil` to the caller.

After the `exit-before` functions are called:

1. Some bookkeeping tasks are called.
2. All the registered `exit-after` functions are called in the reverse order of their registration.
3. Finally the process exits to the operating system.

For compatibility with earlier versions of SKILL, you can still define the functions named `exitbefore` and `exitafter` as one of the exit functions. They are treated as the first registered exit functions (the last to be called). To avoid confusing the system setup, do not use these names for other purposes.

Arguments

| | |
|------------------------------|-------------------------------------|
| <code><i>x_status</i></code> | Process exit status; defaults to 0. |
|------------------------------|-------------------------------------|

Value Returned

`nil` The exit request is aborted. Otherwise there is no return value because the process exits.

Examples

In the following example, depending on the result from calling `closeMyDataBase`, the system either exits the application (after asking for confirmation if running in graphic mode) or aborts the exit and returns `nil`.

```
(defun myExitBefore ()
  (if (closeMyDataBase)
      t                ; if OK in closeMyDataBase then exit
      'ignoreExit))   ; otherwise we want to abort exit
regExitBefore('myExitBefore)
=> t                  ; exit function is registered
exit()
```

Related Topics

[Environment Functions](#)

[csh](#)

getCurrentTime

```
getCurrentTime(  
    )  
    => t_timeString
```

Description

Returns a string representation of the current time.

Arguments

None

Value Returned

| | |
|---------------------|---|
| <i>t_timeString</i> | Current time in the form of a string. The format of the string is month day hour:minute:second year. |
|---------------------|---|

Examples

The format used in the following example is also used by the `compareTime` function.

```
getCurrentTime( )=> "June 10 18:15:18 2022"
```

Related Topics

Environment Functions

`cputime`

getInstallPath

```
getInstallPath(  
    )  
=> l_string
```

Description

Returns the absolute path of the Cadence DFII installation directory where the DFII products are installed on your system as a list of a single string.

Arguments

None

Value Returned

l_string Returns the installation path as a list of a single string.

Examples

```
getInstallPath()  
=> ("/usr5/cds/5.0")
```

Related Topics

Environment Functions

getSkillPath

getLogin

```
getLogin(  
    )  
=> t_loginName
```

Description

Returns the login name of the current user as a string.

Arguments

None

Value Returned

| | |
|--------------------|--|
| <i>t_loginName</i> | Returns the user's login name as a string. |
|--------------------|--|

Examples

```
getLogin  
=> "john"
```

Related Topics

Environment Functions

getInstallPath

getPrompts

```
getPrompts(  
    )  
=> l_strings
```

Description

Returns the current values of the first level and second level prompt text strings, respectively.

The first prompt text string is the first level prompt that represents the topmost top-level prompt, while the second one indicates the second level prompt which is used whenever a nested top-level is entered.

Arguments

None

Value Returned

l_strings

The current values of the first level and second level prompt text strings. The result is a list where the first element is the first level prompt and the second element is the second level prompt specified by `setPrompts`.

Examples

Default prompts for the SKILL interpreter and CIW, respectively.

```
skill> getPrompts()  
("> " "<%d> ")  
CIW> getPrompts()  
("> " "> ")
```

Related Topics

[Environment Functions](#)

[getLogin](#)

getShellEnvVar

```
getShellEnvVar(  
    t_UnixShellVariableName  
)  
=> t_value / nil
```

Description

Returns the value of a UNIX environment variable, if it has been set. This function expands the environment variable name specified in the argument.

Arguments

| | |
|--------------------------------------|--|
| <code>t_UnixShellVariableName</code> | Name of the UNIX shell environment variable. |
|--------------------------------------|--|

Value Returned

| | |
|----------------------|---|
| <code>t_value</code> | Value of named UNIX environment variable. |
| <code>nil</code> | No environment variable with the given name has been set. |

Examples

Returns the current value of the `SHELL` environment variable.

```
getShellEnvVar("SHELL")  
=> "/bin/csh"  
  
setShellEnvVar("ITER" "1")  
=> t  
  
setShellEnvVar("EDITOR_COPY_$ITER" "$EDITOR")  
=> t  
  
getShellEnvVar("EDITOR_COPY_$ITER")  
=> "gedit"  
  
unsetShellEnvVar("EDITOR_COPY_$ITER")  
=> t  
  
getShellEnvVar("EDITOR_COPY_$ITER")  
=> nil
```

Related Topics

Environment Functions

Cadence SKILL Language Reference

Environment Functions

sh, shell

setShellEnvVar

unsetShellEnvVar

getSkillPath

```
getSkillPath(  
    )  
=> l_strings / nil
```

Description

Returns the current SKILL path. The SKILL path is used in resolving relative paths for some SKILL functions.

Arguments

None

Value Returned

| | |
|------------------|--|
| <i>l_strings</i> | Directory paths from the current SKILL path setting. The result is a list where each element is a path component as specified by <code>setSkillPath</code> . |
| <i>nil</i> | The last call to <code>setSkillPath</code> gave <i>nil</i> as its argument. |

Examples

```
setSkillPath('("." "~" "~/cpu/test1"))  
=> ("~/cpu/test1")  
getSkillPath()  
=> (("." "~" "~/cpu/test1"))
```

The example below shows how to add a directory to the beginning of your search path (assuming a directory “~/lib”).

```
setSkillPath(cons("~/lib" getSkillPath()))  
=> ("~/lib" "~/cpu/test1")  
getSkillPath()  
=> ("~/lib" (("." "~" "~/cpu/test1")))
```

Related Topics

[Environment Functions](#)

[/O and File Handling](#)

getTempDir

```
getTempDir(  
    )  
=> t_TempDir
```

Description

Returns the system temp directory as a string.

Arguments

None

Value Returned

| | |
|------------------|--|
| <i>t_TempDir</i> | The name of your current temp directory. |
|------------------|--|

Examples

```
getTempDir()  
=> "/tmp"
```

Related Topics

[Environment Functions](#)

[getWorkingDir](#)

getWorkingDir

```
getWorkingDir(  
    )  
=> t_currentDir
```

Description

Returns the current working directory as a string.

The result is put into a `~/prefixed` form if possible by testing for commonality with the current user's home directory. For example, `~/test` would be returned in preference to `/usr/mnt/user1/test`, assuming that the home directory for `user1` is `/usr/mnt/user1` and the current working directory is `/usr1/mnt/user1/test`.

Ensure that the logged-in user has execute permissions for the directory.

Arguments

None

Value Returned

| | |
|---------------------|---|
| <i>t_currentDir</i> | The name of your current working directory. |
|---------------------|---|

Examples

```
getWorkingDir()  
=> "~/project/cpu/layout"
```

Related Topics

[Environment Functions](#)

[getTempDir](#)

isDir

```
isDir(  
    S_name  
    [ tl_path ]  
)  
=> t / nil
```

Description

Checks if a path exists and if it is a directory name.

When *S_name* is a relative path, the current SKILL path is used if it's non-`nil`. A path that is anchored to the current directory, for example, `./`, `../`, or `../..../`, and so on, is not considered as a relative path.

Arguments

| | |
|----------------|--|
| <i>S_name</i> | Path you want to check. |
| <i>tl_path</i> | List of paths that overrides the SKILL path. |

Value Returned

| | |
|------------------|--|
| <code>t</code> | The name exists and it is the name of a directory. |
| <code>nil</code> | The name exists and is not the name of a directory or <i>S_name</i> does not exist at all. |

Examples

Assumes `DACLib` is a directory and `triadc` is a file under the current working directory and the SKILL path is `nil`.

```
isDir("DACLib")  
=> t  
  
isDir("triadc")  
=> nil
```

The following example returns `nil` if `test` does not exist.

```
isDir("test")  
=> nil
```

Related Topics

Environment Functions

getSkillPath

prependInstallPath

```
prependInstallPath(  
    S_name  
)  
=> t_string
```

Description

Prepends the Cadence DFII installation path to a file or directory and returns the resulting path as a string.

Possibly adds a slash (/) separator if needed. The typical use of this function is to compute one member of a list passed to `setSkillPath`.

Arguments

| | |
|---------------|--|
| <i>S_name</i> | File or directory name to append to the installation path. If a symbol is given, its print name is used. |
|---------------|--|

Value Returned

| | |
|-----------------|---|
| <i>t_string</i> | String formed by prepending the installation path to the argument path. |
|-----------------|---|

Examples

```
getInstallPath()  
=> ("/usr5/cds/4.2")
```

Assume this is your install path.

```
prependInstallPath( "etc/context" )  
=> "/usr5/cds/4.2/etc/context"
```

A slash (/) is added.

```
prependInstallPath( "/bin" )  
=> "/usr5/cds/4.2/bin"  
  
setSkillPath( list( "." prependInstallPath("bin")  
                  prependInstallPath("etc/context")) )  
=> nil  
  
getSkillPath()  
=> ( "." "/usr5/cds/4.2/bin" "/usr5/cds/4.2/etc/context" )
```

Cadence SKILL Language Reference

Environment Functions

Related Topics

Environment Functions

getSkillPath

setShellEnvVar

```
setShellEnvVar(  
    t_varName_or_nameValuePair  
    [ t_varValue ]  
)  
=> t / nil
```

Description

Sets or updates the value of the UNIX environment variable. This function expands the environment variable name specified in the argument.

Arguments

| | |
|-----------------------------------|--|
| <i>t_varName_or_nameValuePair</i> | Environment variable name or assignment expression (<name>=<value>) |
| <i>t_varValue</i> | Value of the environment variable |

Value Returned

| | |
|------------|---|
| <i>t</i> | The shell environment variable is set. |
| <i>nil</i> | The shell environment variable cannot be set. |

Examples

Sets the parent working directory to the /tmp directory.

```
setShellEnvVar("PWD=/tmp")  
=> t
```

Gets the parent working directory.

```
getShellEnvVar("PWD")  
=> "/tmp"
```

Sets the Test directory to the /tmp directory.

```
setShellEnvVar("TEST=/tmp")  
=> t
```

Sets the Test directory to the home directory.

Cadence SKILL Language Reference

Environment Functions

```
setShellEnvVar("TEST" "/home")
=> t
```

Returns nil, as an equal to sign is required to set the value.

```
setShellEnvVar("TEST")
=> nil
```

WARNING setShellEnvVar: must have an equal sign to set a value - "TEST"

Returns nil, as the argument does not have a variable name.

```
setShellEnvVar("/tmp")
=> nil
```

WARNING setShellEnvVar: the argument should include a variable name - "/tmp"

Returns nil, as the argument has a space before the equal to sign.

```
setShellEnvVar("TEST = /tmp")
=> nil
```

WARNING setShellEnvVar: must not have a space before the equal sign - "TEST = /tmp"

```
setShellEnvVar("ITER" "1")
=> t

setShellEnvVar("EDITOR_COPY_$ITER" "$EDITOR")
=> t

getShellEnvVar("EDITOR_COPY_$ITER")
=> "gedit"
```

Related Topics

Environment Functions

sh, shell

setSkillPath

```
setSkillPath(  
    {tl_paths | nil }  
)  
=> l_strings / nil
```

Description

Sets the internal SKILL path used by some file-related functions in resolving relative path names.

You can specify the directory paths either in a single string, separated by spaces, or as a list of strings. The system tests the validity of each directory path as it puts the input into standard form. If all directory paths exist, it returns `nil`.

If any path does not exist, a list is returned in which each element is an invalid path. Also:

- The directories on the SKILL path are always searched for in the order you specified in *tl_paths*.
- Even if a path does not exist (and hence appears in the returned list) it remains on the new SKILL path.

The use of the SKILL path in other file-related functions can be effectively disabled by calling `setSkillPath` with `nil` as the argument.

Arguments

| | |
|------------------|--|
| <i>tl_paths</i> | Directory paths specified either in a single string or in a list of strings. |
| <code>nil</code> | Turns off the use of the SKILL path. |

Value Returned

| | |
|------------------|---|
| <i>l_strings</i> | List of directory paths that appear in the <i>tl_paths</i> argument but do not exist. |
| <code>nil</code> | If all directory paths exist. |

Cadence SKILL Language Reference

Environment Functions

Examples

```
setSkillPath('("." "~" "~/cpu/test1"))  
=> nil ; If "~/cpu/test1" exists.  
=> ("~/cpu/test1") ; If "~/cpu/test1" does not exist.
```

The same task can be done with the following call that puts all paths in one string.

```
setSkillPath(". ~ ~/cpu/test1")
```

Related Topics

Environment Functions

getSkillPath

sh, shell

```
sh(  
    [ t_command ]  
)  
=> t / nil  
  
shell(  
    [ t_command ]  
)  
=> t / nil
```

Description

Starts the UNIX Bourne shell `sh` as a child process to execute a command string.

If the `sh` function is called with no arguments, an interactive UNIX shell is invoked that prompts you for UNIX command input (available only in nongraphic applications).

Arguments

| | |
|------------------|-----------------|
| <i>t_command</i> | Command string. |
|------------------|-----------------|

Value Returned

| | |
|------------|--|
| <i>t</i> | The exit status of executing the given shell command is 0. |
| <i>nil</i> | The exit status of executing the given shell command is not 0. |

Examples

Removes the `junk` file from the `/tmp` directory and returns `t` if it is removed successfully.

```
shell("rm /tmp/junk")
```

Related Topics

[Environment Functions](#)

[setShellEnvVar](#)

system

```
system(  
    t_command  
)  
=> x_result
```

Description

Spawns a separate UNIX process to execute a command.

Arguments

| | |
|------------------|---------------------|
| <i>t_command</i> | Command to execute. |
|------------------|---------------------|

Value Returned

| | |
|-----------------|---|
| <i>x_result</i> | The return code caused by executing the given UNIX command. |
|-----------------|---|

Examples

The output of the `system()` command is redirected to a UNIX terminal window

```
system( "date" )  
Tue Aug 22 16:24:33 IST 2017  
0  
system( "daa" )  
sh: daa: not found  
1
```

Related Topics

[Environment Functions](#)

[sh, shell](#)

unsetShellEnvVar

```
unsetShellEnvVar(  
    t_envVarName  
)  
=> t / nil
```

Description

Removes an environment variable from the environment of the calling process. This function expands the environment variable name specified in the argument. If the environment variable (*t_envVarName*) does not exist in the current environment, the environment is left unchanged.

Arguments

| | |
|---------------------|--|
| <i>t_envVarName</i> | A string representing the environment variable name. |
|---------------------|--|

Value Returned

| | |
|------------|---|
| <i>t</i> | The environment variable is successfully removed. |
| <i>nil</i> | The environment variable does not exist or there is an error condition. |

Examples

```
setShellEnvVar("test=testValue")  
=> t  
getShellEnvVar("test")  
=> "testValue"  
unsetShellEnvVar("test")  
=> t  
getShellEnvVar("test")  
=> nil  
setShellEnvVar("ITER" "1")  
=> t  
setShellEnvVar("EDITOR_COPY_$ITER" "$EDITOR")  
=> t  
getShellEnvVar("EDITOR_COPY_$ITER")  
=> "gedit"  
unsetShellEnvVar("EDITOR_COPY_$ITER")  
=> t
```

Cadence SKILL Language Reference

Environment Functions

```
getShellEnvVar("EDITOR_COPY_$ITER")  
=> nil
```

Related Topics

Environment Functions

setShellEnvVar

vi, vii, vil

```
vi(  
    [ S_fileName ]  
)  
=> t / nil  
vii  
    [ S_fileName ]  
)  
=> t / nil  
viii  
    [ S_fileName ]  
)  
=> t / nil
```

Description

Edits a file using the `vi` editor. This is an `nlambda` function. Edits the named file using the `vi` editor, and optionally includes (`vii`) or loads (`vil`) the file into SKILL after exiting the editor. These functions are just variants of `ed`, `edi`, and `edl` with explicit request for using the `vi` editor.

Arguments

| | |
|-------------------|--|
| <i>S_fileName</i> | File to edit. If no argument is given, defaults to the previously edited file, or <code>temp.il</code> , if there is no previous file. |
|-------------------|--|

Value Returned

| | |
|------------------|--|
| <code>t</code> | The operation was successfully completed. |
| <code>nil</code> | The file does not exit or there is an error condition. |

Examples

```
vil( "test.il" )  
vi()
```

Related Topics

[Environment Functions](#)

[deleteFile](#)

Cadence SKILL Language Reference

Environment Functions

Namespace Functions

SKILL provides several namespace functions that you can use. For example, you can use namespace functions to create a new namespace, associate symbols with the new or an existing namespace, add or remove symbols to and from a namespace, and also use shadow functions to resolve any name conflicts between symbols within a namespace.

The following is a list of namespace functions.

[makeNamespace](#)

[findNamespace](#)

[useNamespace](#)

[unuseNamespace](#)

[importSymbol](#)

[findSymbol](#)

[addToExportList](#)

[getSymbolNamespace](#)

[removeFromExportList](#)

[addToNamespace](#)

[shadow](#)

[shadowImport](#)

[removeShadowImport](#)

[unimportSymbol](#)

makeNamespace

```
makeNamespace (  
    t_name  
)  
=> o_namespace / nil
```

Description

Creates a SKILL namespace with the given *t_name*. A namespace or its parts can be saved in a context and loaded with the context.

Arguments

| | |
|---------------|-------------------------|
| <i>t_name</i> | Name for the namespace. |
|---------------|-------------------------|

Value Returned

| | |
|--------------------|--|
| <i>o_namespace</i> | The namespace object when successfully created. |
| nil | The namespace is not created or a namespace with the same name already exists. |

Examples

```
makeNamespace ("METHODS")  
=> ns@METHODS
```

Related Topics

[Namespace Functions](#)

findNamespace

```
findNamespace(  
    t_name  
)  
=> o_namespace / nil
```

Description

Returns the namespace object with the specified name.

Arguments

| | |
|---------------|---|
| <i>t_name</i> | Specify the name for which you want to retrieve the namespace object. |
|---------------|---|

Value Returned

| | |
|--------------------|---|
| <i>o_namespace</i> | The namespace object. |
| <i>nil</i> | No namespace object exists with the given name. |

Examples

```
findNamespace("A")  
=> ns@A
```

Related Topics

[Namespace Functions](#)

useNamespace

```
useNamespace(  
    t_namespace  
)  
=> t / nil
```

Description

Sets the given namespace for use and imports its symbols into the current namespace.

Arguments

| | |
|--------------------|---|
| <i>t_namespace</i> | Specify the name of the namespace that you want to use. |
|--------------------|---|

Value Returned

| | |
|------------|--|
| <i>t</i> | The given namespace is successfully set for use. |
| <i>nil</i> | The given namespace is not set or an error occurred. |

Examples

```
useNamespace("METHODS")  
=> t
```

Related Topics

[Namespace Functions](#)

unuseNamespace

```
unuseNamespace(  
    t_namespace  
)  
=> t / nil
```

Description

Unsets the specified namespace.

Arguments

| | |
|--------------------|---|
| <i>t_namespace</i> | Specify the name of the namespace that you want to unset. |
|--------------------|---|

Value Returned

| | |
|------------|--|
| <i>t</i> | The specified namespace is successfully unset for use. |
| <i>nil</i> | The specified namespace cannot be unset. |

Examples

```
unuseNamespace("METHODS")  
=> t
```

Related Topics

[Namespace Functions](#)

importSymbol

```
importSymbol(  
    l_symbolList  
    [ t_namespace ]  
)  
=> t / nil
```

Description

Imports symbols into the given namespace. By default, this function imports into the `IL` (or default) namespace.

Arguments

| | |
|---------------------|--|
| <i>l_symbolList</i> | Specify a list of symbols that you want to import into the default namespace. |
| <i>t_namespace</i> | (Optional). Specifies the name of the namespace into which you want to import the given symbols. |

Value Returned

| | |
|----------|--|
| <i>t</i> | The symbols are successfully imported into the namespace (given or default). |
|----------|--|

Examples

```
importSymbol(' (A::level A::value) )  
=> t
```

Related Topics

[Namespace Functions](#)

findSymbol

```
findSymbol(  
    t_name  
    [ ?namespace t_namespace ]  
)  
=> s_symbolName / nil
```

Description

Searches for a symbol that is specified as a string in the given namespace and returns its corresponding SKILL symbol.

Arguments

| | |
|--------------------|--|
| <i>t_name</i> | A string value to specify the name of the symbol you want to search for. |
| <i>t_namespace</i> | (Optional) The namespace in which you want to search for the symbol. |

Value Returned

| | |
|---------------------|---|
| <i>s_symbolName</i> | The name of the symbol. |
| <i>nil</i> | No such symbol exists in the namespace. |

Examples

```
(Namespace "my")  
ns@my  
'my::aaa  
my::aaa  
(findSymbol "aaa" ?namespace "my")  
my::aaa  
(findSymbol "bbb" ?namespace "my")  
nil
```

Related Topics

[Namespace Functions](#)

addToExportList

```
addToExportList(  
    l_symbols  
)  
=> t
```

Description

Adds the specified symbols to the namespace export list. This function does not throw any errors if a symbol is already exported. You can export any symbol from your namespace.

Arguments

| | |
|------------------|--|
| <i>l_symbols</i> | Specify the symbols that you want to add to the namespace export list. |
|------------------|--|

Value Returned

| | |
|---|--|
| t | The specified symbols are successfully added to the namespace export list. |
|---|--|

Examples

```
(addToExportList '(newNameSpace::aaa newNameSpace::bbb))  
=> t  
(useNamespace "newNameSpace")  
=> t  
(getSymbolNamespace 'aaa)  
=> ns@newNameSpace
```

Related Topics

[Namespace Functions](#)

getSymbolNamespace

```
getSymbolNamespace(  
    s_name  
)  
=> o_namespace
```

Description

Returns the namespace where the symbol is created.

Arguments

| | |
|---------------|--|
| <i>s_name</i> | Specifies the name of the symbol for which you want to retrieve the namespace where the symbol is created. |
|---------------|--|

Values Returned

| | |
|--------------------|--|
| <i>o_namespace</i> | The namespace where the specified symbol is created. |
|--------------------|--|

Examples

```
getSymbolNamespace('car')  
=> ns@IL
```

Related Topics

[Namespace Functions](#)

removeFromExportList

```
removeFromExportList(  
    l_symbolList  
)  
=> t
```

Description

Removes symbols referenced in *l_symbolList* from the export list of its namespace. This function will not throw an error, if some of the symbols are not exported. If a symbol from *l_symbolList* was imported by `useNamespace` it will not be removed by `unuseNamespace`.

Arguments

| | |
|---------------------|---|
| <i>l_symbolList</i> | Specifies the symbols that you want to remove from the export list of your namespace. |
|---------------------|---|

Value Returned

| | |
|---|--|
| t | The referenced symbols are successfully removed. |
|---|--|

Examples

```
(removeFromExportList '(jane::aaa))  
=> t  
(useNamespace "jane")  
=> t  
(getSymbolNamespace 'aaa)  
=> nil
```

Related Topics

[Namespace Functions](#)

[useNamespace](#)

[unuseNamespace](#)

addToNamespace

```
addToNamespace (
    t_namespaceName
    l_symbolList
)
=> t
```

Description

Adds and imports the given list of symbol names to the export list of the namespace *t_namespaceName*.

Arguments

| | |
|------------------------|---|
| <i>t_namespaceName</i> | Specify the name of the namespace to which you want to add the given list of symbols. |
| <i>l_symbolList</i> | Specifies the symbols that you want to add to the export list of the specified namespace. |

Value Returned

| | |
|---|---|
| t | The list of symbols are successfully added. |
|---|---|

Examples

```
(addToNamespace "A" '("a" "b" "c"))
=> t
(getSymbolNamespace 'a)
=> ns@A
```

Related Topics

[Namespace Functions](#)

shadow

```
shadow(  
    l_symbols  
    [ t_namespace ]  
)  
=> t
```

Description

Adds symbols *s_symbol* to the shadow list of the default namespace. The symbols which are added to the shadow list are not overridden by import.

Arguments

| | |
|--------------------|---|
| <i>l_symbols</i> | Specify a list of symbols to be protected in the default namespace. |
| <i>t_namespace</i> | (Optional) Specify the namespace in which these symbols should be protected. The default value is the "IL" namespace. |

Value Returned

| | |
|---|--|
| t | Indicates that the symbol was added to the shadow list of the current namespace. |
|---|--|

Examples

```
addToExportList(' (p1:::x p1:::y p1:::z))  
=> t  
addToExportList(' (p2:::x p2:::y p2:::z))  
=> t  
useNamespace("p1")  
=> t  
useNamespace("p2")  
*error* useNamespace symbol name conflict - p2:::x p2:::y p2:::z  
unuseNamespace("p1")  
shadow(shadow('p1:::x p1:::y p1:::z))  
=> t  
useNamespace("p2")  
=> t
```

Related Topics

[Namespace Functions](#)

shadowImport

```
shadowImport (
    l_symbols
    [ t_namespace ]
)
=> t
```

Description

Adds symbols to the namespace shadow list. By default, all warnings related to namespaces are suppressed in the `shadowImport` function.

Arguments

| | |
|--------------------|---|
| <i>l_symbols</i> | Specify the list of symbols that you want to add to the shadow list. |
| <i>t_namespace</i> | (Optional) Specify the namespace of the shadow list to which you want to add the symbols. If you do not provide a namespace, the symbols are added to the shadow list of the default namespace, <code>IL</code> . |

Value Returned

| | |
|----------|--|
| <i>t</i> | The symbols are successfully added to the namespace shadow list. |
|----------|--|

Examples

```
shadowImport ('(methods::drawPolygon)')
=> t
```

Related Topics

[Namespace Functions](#)

removeShadowImport

```
shadowImport (
    l_symbols
    [ t_namespace ]
)
=> t
```

Description

Removes the specified symbols from the namespace shadow list.

Arguments

| | |
|--------------------|--|
| <i>l_symbols</i> | Specify the list of symbols that you want to remove from the shadow list. |
| <i>t_namespace</i> | (Optional) Specify the namespace of the shadow list from which you want to remove the symbols. If you do not provide a namespace, the symbols are removed from the shadow list of the default namespace, <code>IL</code> . |

Value Returned

| | |
|----------|--|
| <i>t</i> | The symbols are successfully removed from the namespace shadow list. |
|----------|--|

Example

```
removeShadowImport ('drawPolygon')
=> t
```

Related Topics

[Namespace Functions](#)

unimportSymbol

```
unimportSymbol(  
    l_symbolList  
    [ t_namespace ]  
)  
=> t
```

Description

Unimports symbols from the given namespace. By default, this function unimports from the `IL` (or default) namespace.

Arguments

| | |
|---------------------|--|
| <i>l_symbolList</i> | Specify a list of symbols that you want to unimport from the default namespace. |
| <i>t_namespace</i> | (Optional). Specifies the name of the namespace from which you want to unimport the given symbols. |

Values Returned

| | |
|----------|---|
| <i>t</i> | Unimports symbols from the default namespace. |
|----------|---|

Examples

```
unimportSymbol(' (A::level A::value) )  
=> t
```

Related Topics

[Namespace Functions](#)

Scheme/SKILL++ Equivalents Tables

The purpose of this topic is to help users familiar with Scheme to get a jump start with SKILL++. All of Scheme’s special (syntax) forms and functions are listed along with their SKILL++ equivalents.

The tables, which are divided into expressions, lexical structure, and functions, use these terms:

| | |
|-------------|---|
| Same | Insicates that the Scheme functionality is provided with the same name (syntax) and same behavior in SKILL++. |
| Supported | <p>Indicates that the Scheme functionality is provided, but it is implemented under a different name and/or is used somewhat differently. For example,</p> <p>(1) In SKILL++, the Scheme function <code>-vector</code> becomes <code>Vector</code>.</p> <p>(2) The global variable <code>piport</code> is used in place of the Scheme function <code>current-input-port</code>.</p> |
| Infix only | Means that the specific Scheme functionality is provided, but the given name can only be used as an infix operator in SKILL++. There is usually an equivalent function with a different name to which this infix operator can be mapped. |
| Unsupported | Means that this Scheme functionality is not yet provided in current SKILL++. |

Related Topics

[Lexical Structure](#)

[Expressions](#)

[Functions](#)

Lexical Structure

The following table describes the Scheme/SKILL++ equivalent lexical structures.

| Scheme | SKILL++ | Comment |
|--|--------------|--|
| Boolean literals <code>#t</code> , <code>#f</code> | Supported. | Use <code>t</code> for <code>#t</code> , <code>nil</code> for <code>#f</code> . |
| Character literals <code>#\...</code> | Unsupported. | Character type not supported. |
| Simple numeric literals such as integers & floats | Supported. | Use <code>0...</code> , <code>0x...</code> , and <code>0b...</code> for <code>#o...</code> , <code>#x...</code> , and <code>#b...</code> (octal/hex/binary integers). |
| String literals <code>"..."</code> | Same. | |
| Vector literals <code>#(...)</code> | Same. | |
| case-insensitive symbols | Unsupported. | Symbols in SKILL++ are always case- sensitive. |
| <code>nil</code> as a symbol | Unsupported. | In SKILL++, just as in SKILL, <code>nil</code> is not a symbol. |
| Special symbol constituent characters such as <code>!</code> , <code>\$</code> , <code>%</code> , <code>&</code> , <code>*</code> , <code>/</code> , <code><</code> , <code>=</code> , and so forth. | Unsupported. | Some of these are used for (infix) operators in SKILL++, others are illegal characters. <code>?</code> is used for keyword prefix. |
| <code>'</code> (single quote) | Same. | Shorthand for <code>quote</code> . |
| <code>`</code> (back quote) | Same. | Shorthand for <code>quasiquote</code> in Scheme and for <code>_backquote</code> in SKILL++. |
| <code>,</code> (comma) | Same. | Shorthand for <code>unquote</code> in Scheme and for <code>_comma</code> in SKILL++. |
| <code>,@</code> | Same. | Shorthand for <code>unquote-splicing</code> in Scheme and for <code>_commaAt</code> in SKILL++. |

Related Topics

[Scheme/SKILL++ Equivalents Tables](#)

Cadence SKILL Language Reference

Scheme/SKILL++ Equivalents Tables

Expressions

Functions

Expressions

The following table describes the Scheme/SKILL++ equivalent expressions.

| Scheme | SKILL++ | Comment |
|--|--------------|--|
| (improper lists), such as (d d) | Unsupported. | SKILL++ lists must end with <code>nil</code> . |
| (procedure calls), such as (f e ...) | Same. | Can be written as <code>f(e ...)</code> in SKILL++ if <code>f</code> is a symbol (variable). |
| (and e ...) | Same. | |
| (begin e ...) | Same. | Equivalent to <code>progn</code> in SKILL++. |
| (case ((d ...) e ...) ... [(else e ...)]) | Same. | |
| (cond (e ...) ... [(else e ...)]) | Same. | |
| (define x e) (define (x v ...) body) | Same. | One can also use SKILL's <code>procedure</code> syntax to define functions in SKILL++. |
| (do ((v e [e]) ...) (e ...) e ...) | Same. | |
| (if e1 e2 e3) | Same. | SKILL++ allows extended <code>if</code> syntax (with <code>then</code> and <code>else</code> keywords) as in SKILL. |
| (lambda (x ...) body) | Same. | Improper variable list such as (x y) can't be used as formals in SKILL++. Use SKILL style <code>@rest</code> , <code>@optional</code> instead. |
| (let [x] ((v e) ...) body) | Same. | |
| (let* ((v e) ...) body) | Supported. | Use <code>letseq</code> instead of <code>let*</code> in SKILL++. |
| (letrec ((v e) ...) body) | Same. | |

Cadence SKILL Language Reference

Scheme/SKILL++ Equivalents Tables

| Scheme | SKILL++ | Comment |
|------------|------------|---|
| (or e ...) | Same. | |
| (set! x e) | Supported. | Use <code>setq</code> or the infix <code>=</code> operator. |

Related Topics

[Scheme/SKILL++ Equivalents Tables](#)

[Lexical Structure](#)

[Functions](#)

Functions

The following table describes the Scheme/SKILL++ equivalent functions.

| Scheme | SKILL++ | Comment |
|---|--------------|---|
| <code>+</code> , <code>-</code> , <code>*</code> , <code>/</code> | Infix only. | Equivalent to functions <code>plus</code> , <code>difference</code> , <code>times</code> , and <code>quotient</code> in SKILL++. |
| <code><</code> , <code><=</code> , <code>></code> , <code>>=</code> | Infix only. | Equivalent to functions <code>lessp</code> , <code>leqp</code> , <code>greaterp</code> , and <code>geqp</code> in SKILL++. |
| <code>=</code> | Supported. | Used as the infix assignment operator in SKILL++. For equality, use the infix operator <code>==</code> or function <code>equal</code> . |
| <code>abs</code> | Same. | |
| <code>acos</code> | Same. | |
| <code>angle</code> | Unsupported. | |
| <code>append</code> | Same. | Takes two arguments only. |
| <code>apply</code> | Same. | |
| <code>asin</code> | Same. | |
| <code>assoc</code> | Same. | |
| <code>assq</code> | Same. | |

Cadence SKILL Language Reference

Scheme/SKILL++ Equivalents Tables

| Scheme | SKILL++ | Comment |
|--------------------------------|--------------|--|
| assv | Same. | |
| atan | Same. | In SKILL++, <code>atan</code> takes one argument only; <code>atan2</code> takes two arguments. |
| boolean? | Supported. | Use <code>booleanp</code> . |
| car, cdr, caar, ..., cddddr | Same. | |
| call-with-current-continuation | Unsupported. | |
| call-with-input-file | Unsupported. | |
| call-with-output-file | Unsupported. | |
| ceiling | Same. | |
| char->integer | Unsupported. | True character type is not supported in SKILL++. However, single-character symbols can be used to simulate it. The function <code>charToInt</code> has the same effect on symbols. |
| char-alphabetic? | Unsupported. | Character type not supported. |
| char-ci<=? | Unsupported. | Character type not supported. |
| char-ci<? | Unsupported. | Character type not supported. |
| char-ci=? | Unsupported. | Character type not supported. |
| char-ci>=? | Unsupported. | Character type not supported. |
| char-ci>? | Unsupported. | Character type not supported. |
| char-downcase | Unsupported. | Character type not supported. |
| char-lower-case? | Unsupported. | Character type not supported. |
| char-numeric? | Unsupported. | Character type not supported. |
| char-upcase | Unsupported. | Character type not supported. |
| char-upper-case? | Unsupported. | Character type not supported. |
| char-whitespace? | Unsupported. | Character type not supported. |
| char<=? | Unsupported. | Character type not supported. |
| char<? | Unsupported. | Character type not supported. |

Cadence SKILL Language Reference

Scheme/SKILL++ Equivalents Tables

| Scheme | SKILL++ | Comment |
|---------------------|--------------|---|
| char=? | Unsupported. | Character type not supported. |
| char>=? | Unsupported. | Character type not supported. |
| char>? | Unsupported. | Character type not supported. |
| char? | Unsupported. | Character type not supported. |
| close-input-port | Supported. | Use <code>close</code> . |
| close-output-port | Supported. | Use <code>close</code> . |
| complex? | Unsupported. | |
| cons | Same. | The second argument must be a list. |
| cos | Same. | |
| current-input-port | Supported. | Use the <code>piport</code> global variable. |
| current-output-port | Supported. | Use the <code>poport</code> global variable. |
| denominator | Unsupported. | |
| display | Same. | |
| eof-object? | Unsupported. | SKILL++ reader returns <code>nil</code> on EOF. |
| eq? | Supported. | Use <code>eq</code> . |
| equal? | Supported. | Use <code>equal</code> . |
| eqv? | Supported. | Use <code>eqv</code> . |
| even? | Supported. | Use <code>evenp</code> . |
| exact->inexact | Unsupported. | |
| exact? | Unsupported. | |
| exp | Same. | |
| expt | Same. | |
| floor | Same. | Use <code>fix</code> or <code>floor</code> . |
| for-each | Supported. | Use <code>mapc</code> . |
| gcd | Unsupported. | |
| imag-part | Unsupported. | |
| inexact->exact | Unsupported. | |

Cadence SKILL Language Reference

Scheme/SKILL++ Equivalents Tables

| Scheme | SKILL++ | Comment |
|---------------|--------------|--|
| inexact? | Unsupported. | |
| input-port? | Supported. | Use <code>inportp</code> . |
| integer->char | Unsupported. | Character type not supported. Use <code>intToChar</code> for the same effect on symbols. |
| integer? | Supported. | Use <code>fixp</code> or <code>integerp</code> . |
| lcm | Unsupported. | |
| length | Same. | Works for both lists and vectors. |
| list | Same. | |
| list->vector | Supported. | Use <code>listToVector</code> . |
| list-ref | Supported. | Use <code>nth</code> . |
| list? | Supported. | Use <code>listp</code> . |
| log | Same. | |
| magnitude | Unsupported. | |
| -polar | Unsupported. | |
| -rectangular | Unsupported. | |
| -string | Unsupported. | |
| -vector | Supported. | Use <code>Vector</code> . |
| map | Supported. | Use <code>mapcar</code> instead. <code>map</code> in SKILL++ behaves differently from <code>map</code> in standard Scheme. |
| max | Same. | |
| member | Same. | |
| memq | Same. | |
| memv | Same. | |
| min | Same. | |
| modulo | Same. | <code>modulo</code> differs from <code>mod</code> in SKILL++, which is the same as <code>remainder</code> . |
| negative? | Supported. | Use <code>minusp</code> or <code>negativep</code> . |

Cadence SKILL Language Reference

Scheme/SKILL++ Equivalents Tables

| Scheme | SKILL++ | Comment |
|------------------|--------------|---|
| newline | Same. | |
| not | Same. | New for SKILL++. Same as ! operator. |
| null? | Supported. | Use <code>null</code> . |
| number->string | Supported. | Use <code>sprintf</code> . |
| number? | Supported. | Use <code>numberp</code> . |
| numerator | Unsupported. | |
| odd? | Supported. | Use <code>oddp</code> . |
| open-input-file | Supported. | Use <code>infile</code> . |
| open-output-file | Supported. | Use <code>outfile</code> . |
| output-port? | Supported. | Use <code>outportp</code> . |
| pair? | Supported. | Use <code>dtpr</code> or <code>pairp</code> . |
| peek-char | Unsupported. | |
| positive? | Supported. | Use <code>plusp</code> . |
| procedure? | Supported. | Use <code>procedurep</code> . |
| quotient | Same. | |
| rational? | Unsupported. | |
| rationalize | Unsupported. | |
| read | Supported. | Or use <code>lineread</code> . Returns <code>nil</code> on EOF. |
| read-char | Unsupported. | Character type not supported. Use <code>getc</code> for similar effect. |
| real-part | Unsupported. | |
| real? | Supported. | Use <code>floatp</code> or <code>realp</code> . |
| remainder | Same. | Use <code>mod</code> or <code>remainder</code> . |
| reverse | Same. | |
| round | Same. | |
| set-car! | Supported. | Use <code>rplaca</code> or <code>setcar</code> . |
| set-cdr! | Supported. | Use <code>rplacd</code> or <code>setcdr</code> . |

Cadence SKILL Language Reference

Scheme/SKILL++ Equivalents Tables

| Scheme | SKILL++ | Comment |
|----------------|--------------|--|
| sin | Same. | |
| sqrt | Same. | |
| string | Unsupported. | |
| string->number | Supported. | Use <code>readstring</code> . |
| string->symbol | Supported. | Use <code>concat</code> or <code>stringToSymbol</code> . |
| string-append | Supported. | Use <code>strcat</code> . |
| string-ci<=? | Unsupported. | |
| string-ci<? | Unsupported. | |
| string-ci>? | Unsupported. | |
| string-length | Supported. | Use <code>strlen</code> . |
| string-ref | Unsupported. | Use <code>getchar</code> for similar effect. |
| string-set! | Unsupported. | Strings in SKILL++ are immutable. |
| string<? | Supported. | Use <code>alphalessp</code> or <code>strcmp</code> . |
| string=? | Supported. | Use <code>alphalessp</code> or <code>strcmp</code> . |
| string>=? | Supported. | Use <code>alphalessp</code> or <code>strcmp</code> . |
| string>? | Supported. | Use <code>alphalessp</code> or <code>strcmp</code> . |
| string? | Supported. | Use <code>stringp</code> . |
| substring | Supported. | Argument values differ. SKILL++ uses index and length. Scheme standard uses start and end (index). |
| symbol->string | Supported. | Use <code>get_pname</code> or <code>symbolToString</code> . |
| symbol? | Supported. | Use <code>symbolp</code> . |
| tan | Same. | |
| truncate | Same. | |
| vector | Same. | |
| vector-length | Supported. | Use <code>length</code> . |
| vector->list | Supported. | Use <code>vectorToList</code> . |

Cadence SKILL Language Reference

Scheme/SKILL++ Equivalents Tables

| Scheme | SKILL++ | Comment |
|-------------|--------------|--|
| vector-ref | Supported. | Use <code>arrayref</code> or the <code>a[i]</code> syntax. |
| vector-set! | Supported. | Use <code>setarray</code> or the <code>a[i] = v</code> syntax. |
| vector? | Supported. | Use <code>arrayp</code> or <code>vectorp</code> . |
| write | Same. | |
| write-char | Unsupported. | |
| zero? | Supported. | Use <code>zerop</code> . |

Related Topics

[Scheme/SKILL++ Equivalents Tables](#)

[Lexical Structure](#)

[Expressions](#)

Mapping Symbols to Values

There are many objects in SKILL that map symbols to values. The `get` function tries to work for all of them. Of course this over-intelligence causes confusion in cases such as hash tables.

Reader-Writer Correspondence

The functions come in reader/writer pairs as given below. The functions (`get`, `getq`, `getqq`) in the left-hand column, read from a given object. The functions (`putprop`, `putpropq`, `putpropqq`) in the right-hand column, write to (or modify) a given object.

```
get    <--> putprop
getq   <--> putpropq
getqq  <--> putpropqq
```

Using the Infix Operator

The `get` and `putprop` functions have no corresponding infix operators. The infix operators for the other four functions are as given in the following table:

| Examples | | | | |
|-----------|----------------|------------|---------------------------|-------------------|
| Function | Infix Operator | LHS or RHS | Function Call | Infix Operator |
| getq | -> | LHS | getq(obj prop) | obj->prop |
| putpropq | -> = | RHS | putpropq(obj value prop) | obj->prop = value |
| getqq | . | LHS | getqq(obj prop) | obj.prop |
| putpropqq | . = | RHS | putpropqq(obj value prop) | obj.prop = value |

Evaluating Arguments

The functions differ about which of their arguments are taken as literals or are evaluated. The following table describes the arguments that are evaluated for each of the four functions:

| Function Call Using Infix Operator | Function Call Using the Syntax | Arguments Evaluated |
|--|--|---|
| - | <code>get(obj prop)</code> | <code>obj</code> , <code>prop</code> |
| - | <code>putprop(obj value prop)</code> | <code>obj</code> , <code>value</code> , <code>prop</code> |
| <code>obj->prop</code> | <code>getq(obj prop)</code> | <code>obj</code> |
| <code>obj->prop=value</code> | <code>putpropq(obj value prop)</code> | <code>obj</code> , <code>value</code> |
| <code>obj.prop</code> | <code>getqq(obj prop)</code> | |
| <code>obj.prop=value</code> | <code>putpropqq(obj value prop)</code> | <code>value</code> |

The following are equivalent:

```

getq(obj prop) <--> get(obj 'prop)
getqq(obj prop) <--> get('obj 'prop) <--> getq('obj prop)

putpropq(obj value prop) <--> putprop(obj value 'prop)
putpropqq(obj value prop) <--> putprop('obj value 'prop) <-->
putpropq('obj value prop)

```

Except for the quoting semantics, all the functions behave the same. They retrieve the value associated with a symbol in a specified object. If a string is given rather than a symbol as the property name, the effect is as if the function were called with the symbol that has the print-name.

The following are equivalent:

```

get(obj 'prop) <--> get(obj "prop")
getq(obj prop) <--> getq(obj "prop")
getqq(obj prop) <--> getqq(obj "prop")
putprop(obj value 'prop) <--> putprop(obj value "prop")
putpropq(obj value prop) <--> putpropq(obj value "prop")
putpropqq(obj value prop) <--> putpropqq(obj value "prop")

```

Working with Lists

If the given object is a list, `get`, `getq`, `putprop`, and `putpropq` assume it is a DPL and consequently read or modify the named field of the DPL.

Working with Symbols

If the given object is a symbol, `get`, `getq`, `putprop`, and `putpropq` read or modify the symbol's property list.

Working with Hash Tables

For the cases of hash tables (returned by `Instance`) the functions `arrayref` and `setarray` can be used instead. There are also `[]` and `[] =` infix operators which obey the following equivalence:

```
hash->prop  
hash['prop']  
getq(hash prop)  
get(hash 'prop)  
get(hash "prop")  
getq(hash "prop")  
arrayref(hash 'prop)
```

And, the following are equivalent:

```
hash->prop = value  
hash['prop'] = value  
putpropq(hash value prop)  
putpropq(hash value "prop")  
putprop(hash value 'prop)  
putprop(hash value "prop")  
setarray(hash 'prop value)
```

Cadence SKILL Language Reference

Mapping Symbols to Values

Working with SKILL++

For the cases of SKILL++ instances of `standardObject` (returned by `Table`), the functions `slotValue` and `setSlotValue` can be used in accordance to the equivalence sets specified below.

The following are equivalent:

```
self->slot  
getq(self slot)  
get(self 'slot)  
slotValue(self 'slot)
```

And, the following are equivalent:

```
self->slot = value  
putprop(self value 'slot)  
putprop(self value "slot")  
putpropq(self value slot)  
putpropq(self value "slot")  
setSlotValue(self 'slot value)
```

In addition to the uses described above, applications that embed SKILL (such as Virtuoso and AllegroPCB) extend the capabilities of the `get` and `putprop` family of functions to work intuitively on their data structures, these include hi forms, menus and widgets, dbobjects, CDF objects, waveform objects, and many other types of objects.

setf Helper Functions

The following table describes expander functions that are available for the `setf_<helper>` functions. In addition to the helper functions listed in the table below, you can create your own `setf` helper functions.

| Function | Description |
|----------------------------|--|
| <code>setf_arrayref</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>arrayref</code> . |
| <code>setf_caaar</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>caar</code> . |
| <code>setf_caadr</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>caadr</code> . |
| <code>setf_caar</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>caar</code> . |
| <code>setf_cadar</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>cadar</code> . |
| <code>setf_caddr</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>caddr</code> . |
| <code>setf_cadr</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>cadr</code> . |
| <code>setf_car</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>car</code> . |
| <code>set_cdaar</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>cdaar</code> . |
| <code>setf_cdadr</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>cdadr</code> . |
| <code>setf_cdar</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>cdar</code> . |

Cadence SKILL Language Reference

setf Helper Functions

| | |
|----------------------------------|---|
| <code>setf_cddar</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>cddar</code> . |
| <code>setf_cdddr</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>cdddr</code> . |
| <code>setf_cddr</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>cddr</code> . |
| <code>setf_cdr</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>cdr</code> . |
| <code>setf_get</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>get</code> . |
| <code>setf_getSG</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>getSG</code> . |
| <code>setf_getSGq</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>getSGq</code> . |
| <code>setf_getShellEnvVar</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>getShellEnvVar</code> . |
| <code>setf_getd</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>getd</code> . |
| <code>setf_getq</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>getq</code> . |
| <code>setf_getqq</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>getqq</code> . For example, <code>(setf mysymbol.myprop 42)</code> sets <code>mysymbol.myprop</code> to value 42. |
| <code>setf_last</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>last</code> . |
| <code>setf_leftEdge</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>leftEdge</code> . |
| <code>setf_lowerLeft</code> | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <code>lowerLeft</code> . |

Cadence SKILL Language Reference

setf Helper Functions

| | |
|-----------------|--|
| setf_nth | <p>Returns the result of the corresponding <code>setf</code> operation to support <code>setf(nth(...) ...)</code> expressions. In the function, replace <i>helper</i> with <i>nth</i>.</p> <p>For example:</p> <pre>myList = '(1 2 3 4); A user-defined list setf(nth(2 myList) 0); Set the 2nd element (zero-based) of myList myList is now modified: (1 2 0 4) setf(nthelem(1 myList) 6); set the 1st element of myList (assuming one-based index) myList is now modified: (6 2 0 4)</pre> |
| setf_nthcdr | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <i>nthcdr</i> . |
| setf_nthcdr | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <i>nthcdr</i> . |
| setf_nthelem | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <i>nthelem</i> . |
| setf_rightEdge | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <i>rightEdge</i> . |
| setf_slotValue | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <i>slotValue</i> . |
| setf_topEdge | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <i>topEdge</i> . |
| setf_bottomEdge | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <i>bottomEdge</i> . |
| setf_upperRight | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <i>upperRight</i> . |
| setf_xCoord | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <i>xCoord</i> . |
| setf_yCoord | Returns the result of the corresponding <code>setf</code> operation. In the function, replace <i>helper</i> with <i>yCoord</i> . |

Related Topics

[setf](#)

Cadence SKILL Language Reference

setf Helper Functions

setf <helper>

Type Introspection Functions

Type introspection is the ability of a function to determine the type or property of an object at runtime. The following table describes the type introspection functions that are available in SKILL.

| Function | Description |
|----------------------------|---|
| <u>dtpr</u> | Checks if an object is a non-empty list. |
| <u>listp</u> | Checks if an object is a list. |
| <u>pairp</u> | Checks if an object is a <code>cons</code> object, that is, a non-empty list. |
| <u>arrayp</u> | Checks if an object is an array. |
| <u>defstructp</u> | Checks if an object is an instance of a particular <code>defstruct</code> . |
| <u>tablep</u> | Checks if an object is an association table. |
| <u>type</u> , <u>typep</u> | Returns a symbol whose name denotes the type of a SKILL object. The functions <code>type</code> and <code>typep</code> are identical. |
| <u>vectorp</u> | Checks if an object is a vector. Behaves the same as <code>arrayp</code> . |
| <u>integerp</u> | Checks if an object is an integer. This function is the same as <code>fixp</code> . |
| <u>otherp</u> | Checks if an object is a user type object, such as an association table or a window. |
| <u>symbolp</u> | Checks if an object is a symbol. |
| <u>symstrp</u> | Checks if an object is either a symbol or a string. |
| <u>outstringp</u> | Checks whether the specified value is an outstring port. |
| <u>pcrObjectp</u> | Checks to see whether the given argument is a <code>pcrObject</code> or not. |
| <u>stringp</u> | Checks if an object is a string. |
| <u>evenp</u> | Checks if a number is an even integer. |

Cadence SKILL Language Reference

Type Introspection Functions

| Function | Description |
|---------------------------|--|
| <u>oddp</u> | Checks if an object is an odd integer. |
| <u>floatp</u> | Checks if an object is a floating-point number. Same as <u>realp</u> . |
| <u>fixp</u> | Checks if an object is an integer, that is, a fixed number. |
| <u>minusp</u> | Checks if a value is a negative number. Same as <u>negativep</u> . |
| <u>plusp</u> | Checks if the given object is equal to one. |
| <u>onep</u> | Checks if the given object is equal to one. |
| <u>realp</u> | Checks if a value is a real number. Same as <u>floatp</u> . |
| <u>zerop</u> | Checks if an object is equal to zero. |
| <u>numberp</u> | Checks if a data object is a number, that is, either an integer or floating-point number. |
| <u>inportp</u> | Checks if an object is an input port. |
| <u>outportp</u> | Checks if an object is an output port. |
| <u>openportp</u> | Checks if the given argument is a port object and it is open (for input or output), <u>nil</u> otherwise. |
| <u>portp</u> | Checks if an object is an input or output port. |
| <u>bcdp</u> | Checks if an object is a binary primitive function. |
| <u>booleanp</u> | Checks if an object is a boolean. |
| <u>getFunType</u> | Returns a symbol denoting the function type for a given function object. |
| <u>isMacro</u> | Checks if the given symbol denotes a macro. |
| <u>isCallable</u> | Checks if a function is defined or is autoloadable from a context. |
| <u>boundp</u> | Checks if the variable named by a symbol is bound, that is, has been assigned a value. The single argument form of <u>boundp</u> only works in SKILL mode. |
| <u>fboundp</u> | Checks if the given name has a function binding. |
| <u>getFnWriteProtect</u> | Checks if the given function is write-protected. |
| <u>getVarWriteProtect</u> | Checks if a variable is write-protected. |

Cadence SKILL Language Reference

Type Introspection Functions

| Function | Description |
|----------------------|--|
| <u>isVarImported</u> | Checks if the specified variable was imported into SKILL++ or not. |
| <u>fdoc</u> | Returns the documentation string for the function bound to the symbol <i>s_function</i> . SKILL switch <code>saveInlineDoc</code> must be set to save and retrieve the doc string. |
| <u>procedurep</u> | Checks if an object is a procedure, or function, object. |

Cadence SKILL Language Reference

Type Introspection Functions

The Standalone skill Program

The standalone `skill` application offers an interactive environment for users to execute SKILL functions.

This application supports only the SKILL functions documented in the current reference. It does not include Cadence Virtuoso application components or support related application-specific SKILL functions.

Syntax

The syntax for running `skill` is as follows:

```
skill [<options>] [<IL file(s)...>]
```

| | |
|-------------------|--|
| <i>options</i> | <p>One or more of these options can be used, separated by spaces.</p> <ul style="list-style-type: none">■ <code>-c</code>: read SKILL functions from a string.■ <code>-e</code>: abort when a file with an error is encountered.■ <code>-f</code>: ignore the <code>.ilinit</code> file.■ <code>-i</code>: switch to interactive mode, instead of exiting, after a specified IL file is loaded. |
| <i>IL file(s)</i> | <p>When <code>skill</code> is invoked with one or more IL files, the files are loaded in the order in which they are specified and the application exits after loading the last file.</p> <p>When <code>skill</code> is invoked without any IL file, an interactive prompt is displayed at which the use can enter SKILL functions.</p> |

When no options or IL files are specified, the skill program is started in interactive mode where an input prompt is displayed for the user to type in commands or operations.

Examples

Runs `skill` in interactive mode from the shell prompt. If the user types in `4*10`, the value returned is 40. The `exit` command closes the program and returns the user to the shell prompt:

```
sh> skill
> 4*10
40
> exit
sh>
```

Runs `skill` by reading SKILL functions from a string:

```
skill -c "144 / 12"
=> 12
```

Runs `skill` in interactive mode after the specified IL file is loaded:

```
skill -i new.il
```

Runs `skill` in interactive mode with a prompt at which the user can enter SKILL functions:

```
skill -I new.il
```

Runs `skill` by reading SKILL functions from the specified IL files in the order in which they are specified:

```
skill new.il new1.il
```

Use skill as a Script

The `skill` application can also be used as a script similar to `sh` or `Perl`.

The first line of the script must have a command to invoke the 'skill' application. Arguments used in the script are treated as strings, as in the case of other scripting languages. The script must include the `exit()` call to terminate the script. If it is not included, `skill` treats the arguments as IL files and will attempt to load them.

A sample script follows:

```
#!/cdsHier/tools/dfII/bin/skill
printf("Hello world\n")
when( argc() == 2
    printf("Arguments: %s %s\n",argv(1) argv(2))
    printf("Types: %s %s\n",type(argv(1)),type(argv(2)))
)
exit(0)
```

Before running the script, ensure that the script file has permissions set as follows:

```
chmod + x
```

Related Topics

[Scheme/SKILL++ Equivalents Tables](#)

Identifiers Used to Denote Data Types

Data type identifiers are used to indicate the type of value required by an API argument. These data types are denoted by a single letter that is prefixed to the argument label and is separated from the argument by an underscore; for example, *t* is the data type in *t_viewName*. Data types and underscores are used only as identifiers; they must not be typed when specifying the argument in a function.

| Prefix | Internal Name | Data Type |
|---------------|----------------------|---|
| <i>a</i> | array | array |
| <i>A</i> | amsobject | AMS object |
| <i>b</i> | ddUserType | DDPI object |
| <i>B</i> | ddCatUserType | DDPI category object |
| <i>C</i> | opfcontext | OPF context |
| <i>d</i> | dbobject | Cadence database object (CDBA) |
| <i>e</i> | envobj | environment |
| <i>f</i> | flonum | floating-point number |
| <i>F</i> | opffile | OPF file ID |
| <i>g</i> | general | any data type |
| <i>G</i> | gdmSpecIIUserType | generic design management (GDM) spec object |
| <i>h</i> | hdbobject | hierarchical database configuration object |
| <i>I</i> | dbgenobject | CDB generator object |
| <i>K</i> | mapiobject | MAPI object |
| <i>l</i> | list | linked list |
| <i>L</i> | tc | Technology file time stamp |
| <i>m</i> | nmpIIUserType | nmpII user type |
| <i>M</i> | cdsEvalObject | cdsEvalObject |
| <i>n</i> | number | integer or floating-point number |

Cadence SKILL Language Reference

The Standalone skill Program

| Prefix | Internal Name | Data Type |
|--------------|---------------------|--|
| <i>o</i> | userType | user-defined type (other) |
| <i>p</i> | port | I/O port |
| <i>pkx</i> | package | package |
| <i>q</i> | gdmSpecListUserType | gdm spec list |
| <i>r</i> | defstruct | defstruct |
| <i>R</i> | rodObj | relative object design (ROD) object |
| <i>s</i> | symbol | symbol |
| <i>S</i> | stringSymbol | symbol or character string |
| <i>t</i> | string | character string (text) |
| <i>T</i> | txobject | transient object |
| <i>u</i> | function | function object, either the name of a function (symbol) or a lambda function body (list) |
| <i>U</i> | funobj | function object |
| <i>v</i> | hdbpath | hdbpath |
| <i>w</i> | wtype | window type |
| <i>sw</i> | swtype | subtype session window |
| <i>dW</i> | dwtype | subtype dockable window |
| <i>x</i> | integer | integer number |
| <i>y</i> | binary | binary function |
| <i>&</i> | pointer | pointer type |