

RootPay — UPI Intent API

Authentication, Create UPI Intent, Status Check & S2S Webhook Response

Base URL: `https://api.templamart.com` | Version: 1.0 | Date: March 2026

1. Authentication (Login)

POST `/api/v1/auth/login`

Authenticate with username/email and password. Returns a JWT Bearer token.

Request

Content-Type: `application/x-www-form-urlencoded`

Field	Type		Description
username	string	Required	Username or email
password	string	Required	Account password

cURL

```
curl -X POST https://api.templamart.com/api/v1/auth/login \
-H "Content-Type: application/x-www-form-urlencoded" \
-d "username=seller@example.com" \
-d "password=your_password"
```

Response (200)

```
{
  "access_token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...",
  "token_type": "bearer",
  "role": 2,
  "isKYCVerified": true
}
```

Field	Type	Description
access_token	string	JWT token — use as <code>Authorization: Bearer {token}</code>
token_type	string	Always "bearer"
role	int	User role (1=Buyer, 2=Seller, 3=Admin)
isKYCVerified	boolean	KYC verification status

Token Expiry: Access token expires after **180 minutes (3 hours)**. After expiry, login again to get a new token.

2. Create UPI Intent

POST `/api/v1/payments/async/create-upi-intent`

Creates a UPI intent payment and returns a `upi://pay?...` URL. Open this URL on mobile to launch UPI apps (GPay, PhonePe, Paytm, BHIM, etc.) for direct payment.

Headers

```
Authorization: Bearer <access_token>
Content-Type: application/json
```

Request Body

Field	Type		Description
amount	float	Required	Amount in INR
merchantOrderId	string	Required	Your unique order ID (must not already exist)
channel	string	Optional	Default: "web"
purpose	string	Optional	Default: "Online Payment"
customer.buyer_name	string	Required	Customer full name
customer.email	email	Required	Customer email address
customer.phone	string	Required	Phone number (10-15 digits)
customer.address1	string	Optional	Address line 1
customer.address2	string	Optional	Address line 2
fingerprint	string	Required	32-character lowercase hexadecimal device fingerprint
userAgent	string	Required	Browser / device user-agent string

cURL

```
curl -X POST https://api.templamart.com/api/v1/payments/async/create-upi-intent \
-H "Authorization: Bearer eyJhbGci..." \
-H "Content-Type: application/json" \
-d '{
  "amount": 800.00,
  "merchantOrderId": "UPI-20260326-001",
  "customer": {
    "buyer_name": "Jane Doe",
    "email": "jane@example.com",
    "phone": "9876543210"
  },
  "fingerprint": "3f9c2a8e7d1b4c0a9e5521b6f4a8d2c9",
  "userAgent": "Mozilla/5.0 (Linux; Android 13) Chrome/123.0"
}'
```

Response (200)

```
{
  "status": "pending",
  "grd_id": "UPI-20260326-001",
  "amount": 800.0,
  "intent_url": "upi://pay?pa=merchant@bank&pn=ROOTPAY&am=800.00&cu=INR&...",
  "order_id": "GW2690365670372QR11017",
  "order_token": null,
  "expires_in": 1200,
  "gateway_used": "JioPay_UPI_QR",
  "attempt_number": 1,
  "processing_time_ms": 920.1
}
```

Field	Type	Description
status	string	"pending" — awaiting UPI payment
grd_id	string	Your merchantOrderId echoed back
amount	float	Payment amount in INR
intent_url	string	UPI intent URL — open on mobile to launch UPI app
order_id	string null	Gateway order reference
order_token	string null	Gateway token
expires_in	int	URL validity in seconds (1200 = 20 minutes)
gateway_used	string	Gateway that processed the request
attempt_number	int	Gateway attempt (1 = primary, 2 = fallback)

processing_time_ms	float	Server processing time in milliseconds
--------------------	-------	--

Mobile Integration: On Android/iOS, open the `intent_url` using the system intent handler. The device will show a UPI app picker (GPay, PhonePe, Paytm, etc.). After payment, the webhook callback notifies your server.

3. Check Payment Status

GET `/api/v1/payments/async/status/{merchant_order_id}`

Returns the current payment status and all gateway attempt logs for the given order.

cURL

```
curl -X GET https://api.templamart.com/api/v1/payments/async/status/UPI-20260326-001 \
-H "Authorization: Bearer eyJhbGci..."
```

Response (200)

```
{
  "order_id": "UPI-20260326-001",
  "status": "success",
  "amount": 800.0,
  "payment_url": "upi://pay?pa=merchant@bank&pn=ROOTPAY&am=800.00&cu=INR&...",
  "gateway_attempts": [
    {
      "gateway": "JioPay_UPI_QR",
      "attempt": 1,
      "status": "success",
      "payment_url": "upi://pay?...",
      "error": null,
      "timestamp": "2026-03-26T15:30:00"
    }
  ],
  "total_attempts": 1
}
```

Field	Type	Description
order_id	string	Your merchantOrderId
status	string	"pending", "success", or "failed"
amount	float	Payment amount
payment_url	string null	UPI intent URL (if available)

gateway_attempts	array	List of gateway attempt logs
total_attempts	int	Total number of gateway attempts

4. S2S Webhook Response (Server-to-Server Callback)

After UPI payment completion, the gateway sends a server-to-server (S2S) callback to your configured webhook URL with the payment result. Below is the JSON your server will receive:

Success Response

```
{
  "merchantOrderId": "UPI-20260326-001",
  "status": "success",
  "amount": "800.00",
  "transactionId": "4000406366135",
  "paymentMode": "UPI",
  "paymentId": "201339259844",
  "paymentInstrument": "9876543210@upi",
  "paymentDateTime": "20260326153500",
  "customerEmail": "jane@example.com",
  "customerPhone": "9876543210",
  "responseCode": "0000",
  "responseDescription": "Transaction successful"
}
```

Failed Response

```
{
  "merchantOrderId": "UPI-20260326-001",
  "status": "failed",
  "amount": "800.00",
  "transactionId": "",
  "paymentMode": "UPI",
  "responseCode": "R9999",
  "responseDescription": "Transaction failed"
}
```

S2S Response Fields

Field	Type	Description
merchantOrderId	string	Your order ID (matches create-upi-intent request)
status	string	"success" or "failed"

amount	string	Amount paid
transactionId	string	Gateway transaction ID
paymentMode	string	"UPI"
paymentId	string	Payment reference ID
paymentInstrument	string	UPI VPA used for payment
paymentDateTime	string	Payment timestamp (YYYYMMDDHHmmss)
customerEmail	string	Customer email
customerPhone	string	Customer phone
responseCode	string	"0000" = success, any other = failed
responseDescription	string	Human-readable status description

Important: Always verify the payment status using the **Status Check API** (Section 3) after receiving the S2S callback. Do not rely solely on the webhook — treat it as a notification.

5. Error Codes

HTTP	Meaning
400	Bad Request — missing or invalid fields
401	Unauthorized — invalid or expired token
404	Not Found — no matching product or order
409	Conflict — merchantOrderId already exists
502	Bad Gateway — payment gateway failed
500	Internal Server Error

All errors return: `{ "detail": "Error description" }`