

Templamart Payment API

API Documentation v1.0

Base URL:	https://api.templamart.com
API Version:	v1
Authentication:	Bearer Token (OAuth2)
Documentation Date:	February 04, 2026

Table of Contents

- 1. Introduction
- 2. Authentication
- 3. API Endpoints
 - 3.1 Login
 - 3.2 Get Ticket Sizes
 - 3.3 Create Payment
- 4. Webhooks
- 5. Error Handling
- 6. Code Examples

1. Introduction

The Templamart Payment API provides a secure and efficient way to integrate payment processing capabilities into your applications. This RESTful API supports various payment methods and channels including web, Android, iOS, and direct API integrations.

Key Features:

- OAuth2 authentication for secure access
- Dynamic ticket size management
- Multi-channel payment support (web, Android, iOS, API)
- Real-time webhook notifications
- Comprehensive error handling

2. Authentication

The API uses OAuth2 password grant flow for authentication. All authenticated endpoints require a Bearer token in the Authorization header.

Important: Only users with role=2 can access payment-related endpoints.

3. API Endpoints

3.1 Login

Endpoint:

POST /api/v1/auth/login

Description:

Authenticates a user and returns an access token for subsequent API requests.

Headers:

Header	Value	Required
Content-Type	application/x-www-form-urlencoded	Yes

Request Parameters:

Parameter	Type	Required	Description
username	string	Yes	User's username
password	string	Yes	User's password

Example Request:

```
POST /api/v1/auth/login Content-Type: application/x-www-form-urlencoded
username=templamart_demo&password;=Mart@1234
```

Example Response (200 OK):

```
{ "access_token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...", "token_type":
"bearer", "expires_in": 3600, "user": { "username": "templamart_demo",
"role": 2 } }
```

3.2 Get Ticket Sizes

Endpoint:

```
GET /api/v1/payments/async/ticket-sizes
```

Description:

Retrieves the list of available payment amounts (ticket sizes) that can be used for creating payments. This endpoint requires authentication with a user having role=2.

Note: This endpoint requires role=2 access.

Headers:

Header	Value	Required
Authorization	Bearer {access_token}	Yes

Example Request:

```
GET /api/v1/payments/async/ticket-sizes Authorization: Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...
```

Example Response (200 OK):

```
{ "ticket_sizes": [50.0, 100.0, 150.0, 200.0, 300.0, 500.0] }
```

3.3 Create Payment

Endpoint:

```
POST /api/v1/payments/async/create-payment
```

Description:

Creates a new payment order and returns a payment link for the customer to complete the transaction. The payment amount should be one of the values returned by the ticket-sizes endpoint.

Headers:

Header	Value	Required
Authorization	Bearer {access_token}	Yes
Content-Type	application/json	Yes

Request Body Parameters:

Parameter	Type	Required	Description
amount	float	Yes	Payment amount (must match ticket size)
merchantOrderId	string	Yes	Unique merchant order identifier
channel	string	Yes	Payment channel: web, android, ios, api
purpose	string	Yes	Purpose of payment
customer	object	Yes	Customer information object

Customer Object:

Field	Type	Required	Description
buyer_name	string	Yes	Customer's full name
email	string	Yes	Customer's email address

phone	string	Yes	Customer's phone number
address1	string	Yes	Primary address
address2	string	No	Secondary address / Apartment details

Example Request:

```
{ "amount": 300.0, "merchantOrderId": "ORD-A1B2C3D4E5F6", "channel": "web",
  "purpose": "Online Payment", "customer": { "buyer_name": "raju", "email":
  "raju@gmail.com", "phone": "9876543210", "address1": "221B Baker Street,
  London", "address2": "Apartment 2, Near the Museum" } }
```

Example Response (200 OK):

```
{ "orderId": "OM02511231443339109649852V", "merchantOrderId":
  "ORD-A1B2C3D4E5F6", "payment_link": "https://pay.templamart.com/...",
  "amount": 300.0, "state": "PENDING", "expireAt": 1763890413904 }
```

4. Webhooks

Templamart sends webhook notifications to your configured endpoint when payment events occur. This allows you to receive real-time updates about payment status changes.

Payment Completed Event

Event Type:

```
pg.order.completed
```

Description:

Sent when a payment is successfully completed. Contains comprehensive transaction details including UPI information, payment modes, and instrument details.

Webhook Payload Fields:

Field	Type	Description
type	string	Event type identifier
event	string	Event name (e.g., pg.order.completed)
payload.state	string	Payment state (e.g., COMPLETED)
payload.amount	number	Payment amount in smallest currency unit
payload.orderId	string	System-generated order ID
payload.merchantOrderId	string	Your merchant order ID
payload.merchantId	string	Merchant identifier
payload.paymentDetails	array	Array of payment detail objects

Example Webhook Payload:

```
{ "type": "PG_ORDER_COMPLETED", "event": "pg.order.completed", "payload": {  
  "state": "COMPLETED", "amount": 50000, "orderId":
```

```
"OM02511231443339109649852V", "expireAt": 1763890413904, "feeAmount": 0,
"merchantId": "AHGONLINE", "payableAmount": 50000, "merchantOrderId":
"GRP7398287584889143296", "paymentDetails": [ { "state": "COMPLETED",
"amount": 50000, "feeAmount": 0, "timestamp": 1763889213990, "paymentMode":
"UPI_QR", "payableAmount": 50000, "transactionId":
"OM2511231443339269649768V", "rail": { "type": "UPI", "vpa":
"70XXXXXX17@axl", "utr": "736258989655", "upiTransactionId":
"AXLa3015f4718594e2490f6ac55c47705d2" }, "instrument": { "type": "ACCOUNT",
"ifsc": "MAHB0000501", "bankId": "MAHB", "accountType": "SAVINGS",
"maskedAccountNumber": "XXXXXXX5571" } } ] } }
```

Best Practices: Always verify webhook signatures and implement idempotent processing to handle duplicate notifications.

5. Error Handling

The API uses standard HTTP status codes to indicate the success or failure of requests. All error responses include a JSON body with additional details.

HTTP Status Codes

Code	Status	Description
200	OK	Request successful
400	Bad Request	Invalid request parameters
401	Unauthorized	Missing or invalid authentication token
403	Forbidden	Insufficient permissions (e.g., role != 2)
404	Not Found	Resource not found or invalid amount
500	Internal Server Error	Server-side error occurred

Example Error Response:

```
{ "detail": "Invalid amount. Amount must be one of the available ticket sizes.", "status": 404, "error": "Not Found" }
```

6. Code Examples

6.1 Python Example

```
import requests import uuid BASE_URL = "https://api.templamart.com" # 1. Login def login(username, password): response = requests.post(f"{BASE_URL}/api/v1/auth/login", data={"username": username, "password": password}, headers={"Content-Type": "application/x-www-form-urlencoded"}) return response.json()["access_token"] # 2. Get available prices def get_ticket_sizes(token): response = requests.get(f"{BASE_URL}/api/v1/payments/async/ticket-sizes", headers={"Authorization": f"Bearer {token}"}) return response.json()["ticket_sizes"] # 3. Create payment def create_payment(token, amount): payload = { "amount": amount, "merchantOrderId": f"ORD-{uuid.uuid4().hex[:12].upper()}", "channel": "web", "purpose": "Online Payment", "customer": { "buyer_name": "John Doe", "email": "john@example.com", "phone": "9876543210", "address1": "123 Main St, City", "address2": "Apt 4B" } } response = requests.post(f"{BASE_URL}/api/v1/payments/async/create-payment", headers={"Authorization": f"Bearer {token}", "Content-Type": "application/json"}, json=payload) return response.json() # Usage token = login("your_username", "your_password") prices = get_ticket_sizes(token) result = create_payment(token, prices[0]) print(f"Payment Link: {result['payment_link']}")
```

6.2 cURL Example

```
# Login curl -X POST https://api.templamart.com/api/v1/auth/login \ -H "Content-Type: application/x-www-form-urlencoded" \ -d "username=your_username&password=your_password" # Get ticket sizes curl -X GET https://api.templamart.com/api/v1/payments/async/ticket-sizes \ -H "Authorization: Bearer YOUR_ACCESS_TOKEN" # Create payment curl -X POST https://api.templamart.com/api/v1/payments/async/create-payment \ -H "Authorization: Bearer YOUR_ACCESS_TOKEN" \ -H "Content-Type: application/json" \ -d '{ "amount": 300.0, "merchantOrderId": "ORD-UNIQUE123", "channel": "web", "purpose": "Online Payment", "customer": { "buyer_name": "John Doe", "email": "john@example.com", "phone": "9876543210", "address1": "123 Main St", "address2": "Apt 4B" } }'
```

Support and Contact

For technical support, API access requests, or additional information, please contact the Templamart development team:

Support Email:	support@templamart.com
Documentation:	https://docs.templamart.com
API Status:	https://status.templamart.com

Document generated on February 04, 2026 at 11:59 AM