

The capacity of a LLM-enabled system to perceive its environment,
maintain internal state, and autonomously choose actions that
causally influence the external world.

See also: (AI Agents that Matter; Kaplan & Strub et al, 2024), (AI; Russell & Norvig, 1995), (Intelligent Agents; Wooldridge & Jennings, 2000)


What is an *agent*?

What is an *agent*?

The capacity of a LLM-enabled system to perceive its environment, maintain internal state, and autonomously choose actions that causally influence the external world.


What is an *agent*?

The capacity of a LLM-enabled system to **perceive its environment**, maintain internal state, and autonomously choose actions that causally influence the external world.



```
54 54 /// A transport implementation
55 55 #[derive(Clone)]
56 56 pub struct Transport {
57 57     addr: SocketAddr,
58 58     tls_enabled: bool,
59 59 }
60 60
61 61 impl Transport {
62 62     pub async fn new(config: TransportConfig) -> Result<Self, Box<dyn std::error::Er
63 63     Ok(Self {
64 64         addr: config.addr,
65 65         tls_enabled: config.tls_config.is_some(),
66 66     })
67 67 }
68 68
69 69 pub fn local_addr(&self) -> Result<SocketAddr, Box<dyn std::error::Error> {
70 70     Ok(self.addr)
71 71 }
72 72
73 73 pub async fn accept(&self) -> Result<Stream, Box<dyn std::error::Error> {
74 74     Ok(Stream::new())
75 75 }
76 76 }
77 77
78 78 /// A transport stream
79 79 pub struct Stream {}
80 80
81 81 impl Stream {
82 82     pub(crate) fn new() -> Self {
83 83         Self {}
84 84     }
85 85
86 86     pub async fn read(&mut self, _buf: &mut [u8]) -> std::io::Result<usize> {
87 87         Ok(0)
88 88     }
89 89 }
```

Cursor



NVIDIA

See also: (AI Agents that Matter; Kapoor & Stroebl et al., 2024), (AI; Russell & Norvig, 1995), (Intelligent Agents; Wooldridge & Jennings, 2009).