Jaime Bruno Cirne de Oliveira

NECTA: Neural Connectivity Time-resolved Analysis

Natal – Rio Grande do Norte, Brazil

2026

Jaime Bruno Cirne de Oliveira

NECTA: Neural Connectivity Time-resolved Analysis

Thesis presented to the Graduate Program in Bioinformatics at the Federal University of Rio Grande do Norte in partial fulfillment of the requirements for obtaining the degree of Doctor in Bioinformatic

Advisor: Prof. Dr^{a}. Kerstin Erika Schmidt

Natal – Rio Grande do Norte, Brazil

2026

Jaime Bruno Cirne de Oliveira

NECTA: Neural Connectivity Time-resolved Analysis

Thesis presented to the Graduate Program in Bioinformatics at the Federal University of Rio Grande do Norte in partial fulfillment of the requirements for obtaining the degree of Doctor in Bioinformatic

Advisor: Prof. Drª. Kerstin Erika Schmidt

Natal – Rio Grande do Norte, Brazil, x June 2026, Defense Committee:

Prof. Drª Kerstin Erika Schmidt - Advisor
UFRN

Prof. Dr. -
UFRN

Prof. Dr. -
Empresa ou instituição

Natal – Rio Grande do Norte, Brazil
2026

ACKNOWLEDGEMENTS

Escreva aqui seus agradecimentos.

"It pays to keep an open mind, but not so open your brains fall out."
(Carl Sagan)

RESUMO

A análise tradicional da conectividade funcional do cérebro frequentemente colapsa a dimensão temporal, gerando grafos estáticos que mascaram a evolução dinâmica das redes neurais, o chamado "Dinoma" (Dynome). Além disso, a extração de redes resolvidas no tempo a partir de dados de eletrofisiologia de alta densidade (LFP) esbarra no fenômeno físico da condução de volume e no gargalo computacional associado ao processamento estocástico de Big Data. Esta tese de qualificação apresenta o NECTA (Neural Connectivity Time-resolved Analysis), um framework computacional interativo de alto desempenho projetado para a exploração metodológica do mesoconectoma dinâmico. O NECTA emprega uma arquitetura paralela baseada em Dask e armazenamento otimizado nativo de nuvem em Zarr para orquestrar simulações estocásticas em larga escala, fatiamento de tensores multidimensionais e modelos nulos topológicos, superando de maneira linear as limitações críticas de memória RAM (Out-Of-Memory) de fluxos analíticos tradicionais. O framework mitiga ativamente os artefatos de condução volumétrica (zero-phase lag) através de processamentos no sinal analítico de Hilbert, utilizando estimadores complexos baseados em fase, como o Índice de Atraso de Fase Ponderado (wPLI) e a Coerência Imaginária (iCoh). Para inferência causal estrita, implementou-se a Coerência Direcionada Parcial (PDC) em um módulo auto-otimizado dinamicamente pelo Critério de Informação Bayesiana (BIC), controlando penalizações de complexidade em regressões autorregressivas vetoriais (MVAR). O sistema foi validado in silico (contra ruído sintético e condução modelada) e aplicado empiricamente a um dataset de 48 canais do córtex visual primário felino (Área 17, Área 18 e Zona de Transição), registrado sob anestesia geral e paralisia (isolando oscilações intrínsecas de modulações cognitivas atencionais). Os resultados in vivo demonstraram que o córtex visual exibe intensas e ativas flutuações topológicas de alta frequência, atingindo picos transientes de eficiência de "Mundo Pequeno" (Small-Worldness) precisamente coordenados durante a estimulação visual por grades em movimento. A análise direcional na banda Low Gamma (30-59 Hz) estabeleceu a Área 17 como um nó Fonte (Driver) persistente e a Área 18 como um Sumidouro (Sink) estável, enquanto a Zona de Transição atuou como um robusto modulador dinâmico do fluxo inter-hemisférico, alternando sua direcionalidade causal sob estimulação. O NECTA democratiza análises avançadas em neuroinformática, entregando um ecossistema interativo (Dash/Cytoscape) reprodutível focado em Open Science que habilita a tradução ágil e sistêmica de sinais eletrofisiológicos brutos em descobertas conectômicas cronológicas.

Palavras-chaves: Conectividade Funcional Dinâmica; Eletrofisiologia; Computação de Alto Desempenho; Coerência Direcionada Parcial; Córtex Visual.

ABSTRACT

Traditional analysis of brain functional connectivity often collapses the temporal dimension, generating static graphs that obscure the dynamic evolution of neural networks, known as the "Dynome". Furthermore, extracting time-resolved networks from high-density electrophysiology (LFP) is heavily hindered by the physical phenomenon of volume conduction and the computational bottleneck associated with stochastic Big Data processing. This qualifying thesis presents NECTA (Neural Connectivity Time-resolved Analysis), an interactive high-performance computational framework designed to explore the dynamic mesoconnectome. NECTA employs a Dask-based parallel architecture and cloud-native Zarr-optimized storage to orchestrate large-scale stochastic simulations, multidimensional tensor slicing, and topological null models, linearly overcoming the critical RAM (Out-Of-Memory) limitations of traditional analytical pipelines. The framework actively mitigates volume conduction artifacts (zero-phase lag) through Hilbert analytical signal processing, utilizing phase-based complex estimators such as the Weighted Phase Lag Index (wPLI) and Imaginary Coherence (iCoh). For strict causal inference, Partial Directed Coherence (PDC) was implemented within a module dynamically auto-optimized by the Bayesian Information Criterion (BIC), controlling complexity penalties in multivariate autoregressive regressions (MVAR). The system was validated in silico (against synthetic noise and modeled conduction) and empirically applied to a 48-channel dataset from the feline primary visual cortex (Area 17, Area 18, and the Transition Zone), recorded under general anesthesia and paralysis (isolating intrinsic oscillations from top-down cognitive modulations). In vivo results demonstrated that the visual cortex exhibits intense and active high-frequency topological fluctuations, reaching transient peaks in Small-Worldness efficiency precisely coordinated during visual stimulation by moving gratings. Directed analysis in the Low Gamma band (30-59 Hz) established Area 17 as a persistent Driver node (Source) and Area 18 as a stable Sink, while the Transition Zone acted as a robust dynamic modulator of interhemispheric flow, alternating its causal directionality upon stimulation. NECTA democratizes advanced neuroinformatics analyses, delivering a reproducible, Open Science-oriented interactive ecosystem (Dash/Cytoscape) that enables the agile and systemic translation of raw electrophysiological signals into chronological connectomic discoveries.

Keywords: Dynamic Functional Connectivity; Electrophysiology; High-Performance Computing; Partial Directed Coherence; Visual Cortex.

LIST OF FIGURES

Figure 1 – Mapping directly to the anatomically separated electrode matrixes . . . 14
Figure 2 – Esquematização dos gargalos metodológicos 17
Figure 3 – Arquitetura Distribuída e Orientada a Nuvens 21
Figure 4 – Mapeamento Evolutivo de Net Flow 27

LIST OF TABLES

Table 1 – Methodological Rationale for Connectivity Estimator Selection in NECTA. 23

LIST OF ABBREVIATIONS AND ACRONYMS

HTML	*HyperText Markup Language*
JSON	*JavaScript Object Notation*
REST	*Representational State Transfer*

LIST OF SYMBOLS

Γ	Letra grega Gama
Λ	Lambda
ζ	Letra grega minúscula zeta
$\in$	Pertence

CONTENTS

1 INTRODUCTION 14
1.1 The Primary Visual Cortex and the Limits of Static Topologies . . . 14
1.2 The Paradigm Shift to the "Dynome" 15
1.3 Rhythmic Oscillations, Predictive Coding, and Gamma Synchronization 15
1.4 The Methodological Bottleneck in Electrophysiology 15

2 WORKING HYPOTHESIS AND OBJECTIVES 18
2.1 Working Hypothesis 18
2.2 General Objective 18
2.3 Specific Objectives 19

3 MATERIALS AND METHODS 20
3.1 Animal Preparation and Data Acquisition 20
3.2 Data Ingestion Architecture (The Isaac Pipeline) 20
3.3 Distributed Pre-Computation Engine (HPC) 20
3.4 Spectral Connectivity and Phase Analysis 21
3.5 Directed Functional Connectivity (PDC) 22
3.6 In Silico Validation: Ground Truth Modeling and Stress Testing . . 22
3.7 Graph Theory, Statistical Validation, and Open Science 23
3.8 Interactive Visualization Dashboard 24

4 RESULTS 25
4.1 In Silico Ground Truth Extraction and Hardware Benchmarking . . . 25
4.2 Baseline Characterization and the Static Backbone 25
4.3 Hierarchical Information Flow (Directed Connectivity) 25
4.4 Dynamic Topology and Temporal Integration 26
4.5 The "Dynome" Evolution and Modulatory Nodes 26

5 DISCUSSION 28
5.1 From Static Maps to the Visual Dynome 28
5.2 Isolating Intrinsic Dynamics in the Anesthetized State 28
5.3 Mitigating Electrophysiological Confounders 29
5.4 Gamma Synchronization, Predictive Coding, and Callosal Modulation 29
5.5 Overcoming the Computational Scale and Open Science 30

6 CONCLUSÃO 31

BIBLIOGRAPHY **32**

1 INTRODUCTION

1.1 The Primary Visual Cortex and the Limits of Static Topologies

The primary visual cortex has long served as the canonical model for understanding cortical microcircuitry, sensory processing, and the brain's **neural networks**. Historically, the architectural and functional parcellation of visual areas—such as Area 17 (A17), Area 18 (A18), and their Transition Zone (TZ) in the feline model—has been extensively mapped using single-unit recordings and static receptive field analyses (Wunderle et al., 2013; Schmidt et al., 2023). These classical approaches have established the foundational **static connectome**—a rigid, structural blueprint of the visual system detailing how intra- and inter-hemispheric neural networks form clustered functional communities. However,



Figure 1 – **Mapping directly to the anatomically separated electrode matrixes | (Coherence (Low Gamma)) | Density: 15%: Coherence clusters**

relying exclusively on these stationary statistical relationships collapses the true, living matrix of cortical connections. Averaging neural interactions over long temporal windows (e.g., minutes of recording) treats the neural network as a fixed roadmap, inevitably obscuring sub-second synaptic recruitment and leading to a severe loss of organic causality resolution. Cognitive processes, particularly visual feature binding, do not operate in a stationary state; they evolve dynamically and transiently as stimuli move across and between receptive fields. Consequently, **static topologies**—while accurately describing the anatomical constraints and the baseline connectome of neural communication—completely mask the rapid, transient fluctuations in functional integration that are the actual hallmark of active sensory processing.

1.2 The Paradigm Shift to the "Dynome"

To overcome the limitations of static connectomics, the neuroscientific community has begun shifting its focus toward the exploration of the "Dynome"—the millisecond-scale evolution of functional networks and their temporal dynamics (KOPELL et al., 2014). Capturing the Dynome requires shifting the analytical framework from time-averaged correlations to time-resolved state transitions, often achieved through sliding-window approaches (ALLEN et al., 2014). By dissecting the continuous data stream into granular temporal epochs, it becomes possible to observe how network metrics, such as *Small-Worldness* and modularity, adapt and evolve. This time-varying perspective provides a much more accurate representation of the brain's real-time functional state, revealing that macroscopic efficiency is not fixed but reacts continuously to ongoing sensory integration.

1.3 Rhythmic Oscillations, Predictive Coding, and Gamma Synchronization

At the mesoscopic scale, rhythmic neural oscillations—specifically in the Gamma frequency band (30–90 Hz)—act as a fundamental mechanism for cortical communication and information routing. Under the predictive coding framework, the synchronized engagement of neuronal populations in the gamma band provides a fast transmission channel for feedforward visual processing, carrying sensory "prediction errors" from primary areas (A17) to higher-order regions (A18) (VEZOLI et al., 2021). Furthermore, the Transition Zone (TZ) acts not merely as a geographic boundary, but as a highly specialized region densely innervated by transcallosal projections, facilitating massive interhemispheric coordination essential for integrating visual stimuli across the vertical meridian (SCHMIDT et al., 2023). Thus, mapping the directionality of gamma synchronization across A17, TZ, and A18 is crucial for deciphering the causal architecture and dynamic modulation of the visual cortex.

1.4 The Methodological Bottleneck in Electrophysiology

Despite the theoretical necessity of time-resolved, directed connectivity analysis, extracting these networks from dense multi-electrode arrays poses severe methodological and computational challenges. The primary analytical bottleneck in Local Field Potential (LFP) analysis is *volume conduction*—the instantaneous spread of electrical fields through cortical tissue. This phenomenon causes multiple electrodes to record a single biological source simultaneously, generating spurious zero-phase lag correlations that heavily contaminate graph topologies with false-positive edges (BASTOS; SCHOFFELEN, 2015).

Furthermore, the transition to high-density electrophysiology (e.g., 32-64 channel matrices) creates a "Big Data" computational crisis. Calculating dynamic, non-linear connectivity metrics (such as Partial Directed Coherence or phase-based indices), generating hundreds of surrogate networks for statistical validation, and tracking graph properties over moving time windows inevitably lead to combinatorial explosions. Traditional, single-threaded analytical scripts are inherently incapable of managing such stochastic, multidimensional loads, often resulting in Out-of-Memory (OOM) failures or prohibitive processing times.

Consequently, there is a critical need for a modern, high-performance computing (HPC) framework capable of mitigating volume conduction artifacts through advanced phase-based estimators while leveraging distributed parallel processing to interactively render the mesoscopic Dynome.



Figure 2 – **Esquematização dos principais gargalos metodológicos em conectômica eletrofisiológica e suas respectivas resoluções no framework proposto. (Painel A)** Representação biofísica da Condução de Volume: as linhas de campo elétrico de um único dipolo profundo atingem instantaneamente múltiplos microeletrodos, criando anomalias de *zero-lag* e gerando matrizes topológicas falsamente densas. À direita, a resolução analítica utilizando índices de fase complexa (wPLI/iCoh), que filtra os artefatos e recupera um grafo esparso e fidedigno. **(Painel B)** Representação abstrata do colapso temporal: o cálculo de correlações através de janelas demasiadamente longas funde diferentes estados cerebrais transitórios, resultando numa rede artificial estática. Em contraste, a exploração focada no "Dinoma" preserva a flexibilidade sequencial e as rápidas reorganizações dos engramas funcionais de integração.

2 WORKING HYPOTHESIS AND OBJECTIVES

2.1 Working Hypothesis

Traditional analyses of multichannel electrophysiological data often collapse the temporal dimension, yielding static graphs that obscure the transient coordination of neural ensembles. Furthermore, attempts to extract time-resolved networks are frequently confounded by volume conduction and crippled by the computational intractability of massive stochastic testing.

We hypothesize that integrating phase-based, zero-lag immune connectivity estimators (e.g., Imaginary Coherence and Weighted Phase Lag Index) with dynamically optimized causal models (Partial Directed Coherence) will overcome the artifactual bottlenecks of volume conduction. Critically, to address the profound combinatorial explosion inherent in time-varying analyses, the deployment of a highly scalable, parallel computing architecture—specifically the Dask/Xarray ecosystem—is posited not merely as a software enhancement, but as an indispensable mathematical requirement for the system's survival. The "Big Data" processing scale is a forced consequence of the successive combinatorial routines required for Monte-Carlo simulations, phase-randomized surrogate permutations, and structural null models applied to adaptive topological thresholding over continuous, non-linear dynamic windows.

By deploying this integrated HPC framework, it will be possible to decode the "Dynome" of the primary visual cortex. We expect to reveal that the anatomical structural backbone (Areas 17, 18, and the Transition Zone) supports highly flexible, time-varying topological reorganizations—such as transient peaks in Small-Worldness—that align exactly with the active phases of sensory feature binding.

2.2 General Objective

The primary objective of this thesis is to develop, validate, and empirically apply **NECTA (Neural Electrophysiological Connectivity Time-resolved Analysis)**. This open-source, high-performance computational framework is specifically designed to meet the rigorous statistical and computational survival requirements necessary for the interactive exploration of dynamic mesoconnectomes from raw, high-density electrophysiological recordings.

2.3 Specific Objectives

To achieve the general goal, the project is subdivided into the following specific aims:

1. **Data Ingestion and Standardization:** To develop a robust pipeline (the *Isaac* ecosystem) capable of converting dispersed legacy electrophysiological binaries (e.g., SPASS format) into standardized, cloud-native, n-dimensional tensors (Zarr/Xarray) using lazy-loading mechanisms.

2. **High-Performance Computation Engine:** To architect a distributed pre-computation backend using Dask, capable of orchestrating parallel pipelines for spectral connectivity, phase-based metrics, and graph topology across multiple frequency bands and sliding time windows.

3. **Advanced Causal Inference:** To implement a self-optimizing Partial Directed Coherence (PDC) module that automatically selects the optimal Multivariate Autoregressive (MVAR) model order via the Bayesian Information Criterion (BIC), thereby preventing overfitting and ensuring rigorous information flow directionality.

4. **Statistical Rigor and Null Modeling:** To embed strict statistical validation protocols, including False Discovery Rate (FDR) corrections applied to phase-randomized surrogate data, and topological null models (Erdös-Rényi and Configuration Models) to validate graph communities.

5. **Interactive Visual Analytics:** To construct a reactive, component-based frontend (using Dash and Cytoscape) that translates multidimensional connectivity arrays into an interactive chronologic connectome, allowing frame-by-frame topological inspection.

6. **Empirical Validation *In Vivo*:** To apply the NECTA framework to an empirical dataset (‘c1608a01‘) obtained from the feline visual cortex (A17/TZ/A18) to characterize the hierarchical directionality of gamma-band synchronization and the temporal evolution of network efficiency during visual stimulation.

3 MATERIALS AND METHODS

3.1 Animal Preparation and Data Acquisition

The empirical validation of the framework utilized the ‘c1608a01‘ dataset (WUNDERLE; ERIKSSON; SCHMIDT, 2013). Multichannel electrophysiological recordings (Local Field Potentials and multi-unit spikes) were obtained from the primary visual cortex of an adult cat. To isolate intrinsic cortical network dynamics from confounding behavioral variables (e.g., saccadic eye movements or fluctuations in conscious attention), the animal was maintained under general anesthesia and paralysis. High-density matrix electrodes (32–64 channels) were implanted spanning Area 17 (A17), the A17/18 Transition Zone (TZ), and Area 18 (A18).

3.2 Data Ingestion Architecture (The Isaac Pipeline)

To process the high-density recordings, the *VisionICeIO* (Isaac) pipeline was developed to act as a bridge between legacy proprietary formats (e.g., SPASS binaries) and modern data structures.

- **Tensor Standardization:** Dispersed binaries containing spike times, waveforms, and continuous LFP traces were parsed and merged into regularized multidimensional arrays. Ragged arrays (e.g., varying spike counts per trial) were standardized using ‘NaN‘ padding.

Zarr and Xarray Encapsulation: *The output is structured as a cloud-native ‘Zarr‘ store. By encapsulating the data within an ‘xarray.Dataset‘, the framework leverages* lazy loading*, allowing the frontend to read metadata trees without exhausting system RAM.

3.3 Distributed Pre-Computation Engine (HPC)

Analyzing dynamic connectivity across continuous recordings poses a severe combinatorial challenge. NECTA addresses this through a distributed pre-computation engine orchestrated by **Dask**.

- **Task Graphs:** Computations are divided into discrete, independent tasks (e.g., computing coherence for a specific frequency band and time window) and mapped across a cluster of worker nodes.

- **Fingerprinting and Cache Versioning:** To ensure data integrity, the orchestrator implements a cryptographic fingerprinting mechanism. Any modification to analytical parameters (e.g., altering variance thresholds or VAR criteria) alters the global hash, safely invalidating obsolete ‘Zarr‘ caches.



Figure 3 – **Topologia de Sistemas e Fluxo de Processamento de Dados da Plataforma NECTA.** O diagrama rastreia as engrenagens de abstração metodológica: a leitura de pacotes brutos desestruturados provenientes de matrizes LFP (binários legados SPASS), seguida pela ingestão assíncrona e conversão modular em *Datacubes* fragmentados via Xarray/Zarr. Através de uso semântico e *lazy loading*, os cálculos são submetidos a particionamento em Grafos de Tarefas (*Task Graphs*) no orquestrador Dask, que aloca nós de processamento (*Workers*) independentes sob seu agendador estocástico. Finalmente, os dados processados fluem por um barramento de serialização até a exportação interativa de estado em um pacote web reativo renderizado via JavaScript (Cytoscape/Dash).

3.4 Spectral Connectivity and Phase Analysis

To mitigate the artifacts of volume conduction inherent to LFP recordings, NECTA expands upon classical Magnitude Squared Coherence by employing phase-based estimators.

- **Analytical Signal Extraction:** Raw LFP signals are processed using the Hilbert Transform to yield the analytical signal, granting instantaneous access to both phase $\phi(t)$ and amplitude $A(t)$.
- **Imaginary Coherence (iCoh) & Weighted Phase Lag Index (wPLI):** The framework computes 'iCoh' to strictly isolate interactions with non-zero phase delays. Furthermore, 'wPLI' is calculated by weighting the phase differences by the magnitude of the imaginary component of the cross-spectrum, providing a highly robust metric against uncorrelated noise and instantaneous spatial spread.

3.5 Directed Functional Connectivity (PDC)

To infer causal interactions and hierarchical information flow, NECTA implements an advanced Partial Directed Coherence (PDC) pipeline.

1. **Stationarity Filtering:** LFP windows exceeding a predefined variance threshold are identified as artifacts and discarded, preserving the assumptions of autoregressive modeling.
2. **Automated Order Selection:** Instead of imposing a static model order, the Dask workers dynamically fit Multivariate Autoregressive (MVAR) models using Ordinary Least Squares (OLS). The algorithm iterates through orders (up to `max_order=20`) and selects the optimal p that minimizes the Bayesian Information Criterion (BIC), balancing model fit against parametric complexity.
3. **Frequency Transformation:** Autoregressive coefficients A_r are transformed into the frequency domain $A(f)$ using Fast Fourier Transforms accelerated via 'Numba' (FastMath), yielding the normalized PDC matrices.

Table 1: Methodological Rationale for Connectivity Estimator Selection in NECTA

3.6 In Silico Validation: Ground Truth Modeling and Stress Testing

To irrefutably prove the causal extraction capabilities of NECTA, the platform was subjected to *in silico* validation using controlled synthetic matrices.

- **Neural Mass Models (Ground Truth):** Theoretical multivariate LFP arrays were generated utilizing coupled Neural Mass Models with pre-programmed structural connections, known delays, and specific oscillatory gamma bursts (30-90Hz), establishing an exact biological ground truth.

Table 1: Methodological Rationale for Connectivity Estimator Selection in NECTA			
Algorithm Family	**Examples**	**Vulnerability to Volume Conduction**	**Directionality**
Traditional Parametric Time-Domain	Pearson Correlation	**Severe:** Highly contaminated by instantaneous topological artifacts.	Non-Directed
Mixed Spectral Synchrony	PLV, Magnitude Coherence	**High:** Latent topological interference in mixed phase-magnitude domains.	Non-Directed
Instantaneous Phase-Lag Delay Modeling	wPLI, iCoh	**Low:** Extreme robustness via strict subtraction of zero-lag real projections.	Non-Directed
Multivariate Regressive Causal Modeling	PDC, DTF	**Moderate to Low:** Shielded by dynamic order selection (BIC) and surrogate thresholding.	**Causal (Driver/Sink)**

Table 1 – Methodological Rationale for Connectivity Estimator Selection in NECTA.

Noise Induction and Volume Conduction: *These synthetic matrices were progressively corrupted. The* Signal-to-Noise Ratio (SNR)* was degraded using pink and white noise, and severe instantaneous spatial mixing was modeled to emulate electrical cross-talk (Volume Conduction) in real biological tissue. The NECTA extraction pipeline (wPLI and BIC-optimized PDC) was applied blindly. Evaluation using Receiver Operating Characteristic (ROC) and Area Under the Curve (AUC) metrics confirmed the platform's capacity to filter noise and retrieve the underlying ground truth causal graphs reliably.

Furthermore, an exhaustive hardware **Stress Test (Benchmarking)** evaluated the Dask orchestrator. The computational scale of processing multivariate combinatorics (FDR surrogate validations and MVAR scaling) was timed systematically across 1, 2, 4, 8, and 16 active worker threads. These benchmarks proved the exponential operational efficiency of NECTA's chunked Zarr loading compared to traditional monolithic Python pipelines (e.g., MNE), effectively overcoming the Out-Of-Memory (OOM) limits of big-data electrophysiology.

3.7 Graph Theory, Statistical Validation, and Open Science

A crucial aspect of NECTA is its rigorous statistical and topological validation.

- **Surrogate Data & FDR Correction:** For connectivity edges, significance is

established by generating 100 phase-randomized surrogate datasets. Edge-wise p-values are subjected to False Discovery Rate (FDR) correction (Benjamini-Hochberg, $\alpha = 0.05$).

- **Topological Null Models:** Macro-topology is validated against Erdös-Rényi and Configuration Models to ensure detected communities preserve empirical degree distributions.
- **Open Science and Reproducibility:** Complying with open-source global standards, the NECTA framework ensures transparency. All algorithms, Dask partition logs, and dependencies are containerized, version-controlled, and openly hosted on digital repositories (GitHub/CodeMeta), allowing independent researchers to audit, reproduce, and expand the methodological codebase.

3.8 Interactive Visualization Dashboard

The final tier of NECTA is a Single Page Application (SPA) built with ‘Dash‘ and ‘Cytoscape‘. The interface performs on-the-fly slicing of the pre-computed ‘Zarr‘ cache using ‘xarray.sel()‘. Changes in the global state trigger instantaneous callbacks that serialize exact data slices into JSON, seamlessly re-rendering complex Connectome Matrices, Temporal Integration scatter plots, and anatomical Information Flow graphs.

4 RESULTS

4.1 In Silico Ground Truth Extraction and Hardware Benchmarking

Prior to empirical applications, the NECTA mathematical modules were tested *in silico* against synthetic data matrices. By feeding the architecture with pre-programmed neural mass signals embedded in progressive layers of Pink/White noise and modeled electrical spatial leakage (simulated Volume Conduction), the 'wPLI' and dynamically optimized PDC estimators consistently filtered the spurious zero-phase interactions. Analyzing the Receiver Operating Characteristic (ROC) outputs confirmed high precision in extracting the embedded causal ground-truth graphs, despite severe Signal-to-Noise (SNR) corruption.

Concurrently, hardware stress testing evaluated the distributed execution of these complex tasks. The monolithic extraction of MVAR matrices combined with phase-randomized surrogate networks (e.g., iterating through multiple frequency bands) resulted in deterministic Out-of-Memory (OOM) failures or intractable execution times when running sequentially. However, by deploying NECTA's Dask-driven orchestrator, linear scalability was achieved across active worker threads (1, 2, 4, 8, 16), effectively accelerating combinatorial FDR validation and dynamically preventing memory exhaustion by leveraging chunked Zarr abstractions.

4.2 Baseline Characterization and the Static Backbone

To establish a baseline structural framework, static functional connectivity was evaluated across the entire recording session. Applying Magnitude Coherence in the Low Gamma band (30–59 Hz) with a proportional density threshold of 15

4.3 Hierarchical Information Flow (Directed Connectivity)

To decode the causal relationships within this structural backbone, Partial Directed Coherence (PDC) was applied using the BIC-optimized MVAR models. The static PDC analysis in the Low Gamma band revealed a highly asymmetrical and hierarchical information flow across the visual cortex. By calculating the Net Flow for each region, A17 emerged as the dominant persistent *Driver* (Source) of the network (+1.10 net flow). In contrast, A18 functioned as the primary *Receiver* (Sink) (-1.36 net flow). These results establish a clear directional pathway extending from A17 through the TZ and terminating

in A18 (A17 → TZ → A18), consistent with canonical feedforward processing hierarchies.

4.4 Dynamic Topology and Temporal Integration

The core capability of NECTA lies in capturing the "Dynome"—the transition from static networks to chronological connectomes. Connectivity was recalculated using a sliding-window approach ($W = 500$ ms, 50

The dynamic analysis revealed that the network's topological efficiency is not static but responds organically to visual processing phases. The network achieved its absolute peak in *Small-Worldness* specifically during the moving grating stimulus phase. This transient optimization was driven primarily by a rapid surge in local clustering, indicating that the anesthetized cortical network actively reorganizes into a highly efficient state to process dynamic visual inputs.

4.5 The "Dynome" Evolution and Modulatory Nodes

Extracting frame-by-frame snapshots (Connectome Filmstrip) of the dynamic Low Gamma Coherence network illustrated a stable rhythmic organization over time. The hubs located in A17 and the TZ maintained cohesive clustering. Crucially, evaluating the *Net Flow Evolution* uncovered a complex temporal interplay obscured by static analysis. While A17 consistently acted as a "Volatile Source" and A18 as a "Stable Sink", the Transition Zone (TZ) exhibited unique behavior. The TZ functioned as a *Dynamic Modulator*, actively switching its directional role (from sink to source, or vice versa) precisely at the onset of visual stimulation. This highlights the framework's capacity to dissect the mesoconnectome chronologically, revealing dynamic hierarchical relays that coordinate sensory integration across the interhemispheric boundary.



Figure 4 – **Mapeamento Evolutivo Topológico do Net-Flow de Informação (Banda Baixa-Gama).** Proporções de entrada (*in-degree*) menos saída (*out-degree*). **(A)** Durante o período basal, a rede opera numa hierarquia visual preditiva estrita, onde a Área 17 (A17) é o polo motriz primário e a Área 18 (A18) o sumidouro passivo, com a Zona de Transição (TZ) em estado neutro. **(B)** No exato momento do estímulo (inserção do *grating* móvel), a topologia sofre uma remodelação ativa. A TZ reverte a sua polaridade passiva e adota dinâmicas de modulação aguda, alterando drasticamente os *edge weights* (espessura das setas) e provando que a flexibilidade mesoscópica reage transitoriamente à entrada do estímulo periférico.

5 DISCUSSION

5.1 From Static Maps to the Visual Dynome

Historically, the functional organization of the primary visual system has been delineated through the static mapping of receptive fields and anatomical inter-hemispheric tracing (Wunderle et al., 2013; Schmidt et al., 2023). While these classical methods successfully outline the spatial constraints and functional columns of the cortex, they inherently capture only a time-averaged "structural backbone." Cognitive processing and the integration of moving stimuli, however, depend on millisecond-scale state transitions within neural ensembles—a temporal dimension defined as the *Dynome* (KOPELL et al., 2014).

The application of the NECTA framework to the ‘c1608a01‘ dataset provides empirical proof of this dynamic nature. By utilizing a continuous sliding-window approach, we demonstrated that the visual cortex undergoes rapid, stimulus-locked topological reorganizations. The observation that the network reaches transient peaks in *Small-Worldness* precisely during the moving grating stimulus demonstrates that macroscopic network efficiency is an active, responsive property rather than a fixed anatomical trait.

5.2 Isolating Intrinsic Dynamics in the Anesthetized State

A critical strength of our biological validation lies in the physiological state of the animal model. The recordings were obtained under general anesthesia and complete paralysis. Far from being a limitation, this state is analytically profound. It systematically suppresses top-down cognitive and attentional modulations, behavioral volition, and saccadic eye movements. Therefore, the dynamic topological reorganizations and the causal directionality shifts extracted by NECTA—such as the transient peaks in network clustering—cannot be dismissed as mere artifacts of cognitive states or conscious attentional engagement. Instead, the framework successfully unveils the intrinsic, low-level reflexive plasticity inherent to local synaptic loops and dense transcallosal pathways interlinking A17, A18, and the TZ. Revealing this level of structural fluidity without massive executive-level interference highlights NECTA’s power as a tool for decoding primary mesoscopic coding.

5.3 Mitigating Electrophysiological Confounders

A profound challenge in high-density LFP connectomics is the pervasive artifact of volume conduction, wherein a single electrical source is instantaneously registered by multiple neighboring electrodes (BASTOS; SCHOFFELEN, 2015). If unaccounted for, this phenomenon generates spurious zero-phase lag correlations, heavily biasing the resulting graph topology with false-positive edges.

NECTA addresses this methodological bottleneck architecturally. By employing the Hilbert Transform to extract analytical signals, the framework calculates phase-based indices such as the Weighted Phase Lag Index ($wPLI$) and Imaginary Coherence ($iCoh$), which are mathematically immune to instantaneous spatial spread. This algorithmic refinement ensures that the dynamic topologies extracted reflect true underlying physiological synchronization rather than electrical crosstalk.

5.4 Gamma Synchronization, Predictive Coding, and Callosal Modulation

Previous work from our group has established the cardinal role of gamma-band synchronization in functional routing and cohesion within the retinogeniculate and cortical pathways of the cat (NEUENSCHWANDER et al., 2023). NECTA extends this foundation by mapping the causal directionality of these high-frequency rhythms.

By applying Partial Directed Coherence (PDC) optimized dynamically via the Bayesian Information Criterion (BIC), we eliminated the bias of static model-order selection (which often leads to overfitting when estimating temporal shifts, unlike AIC). The resulting hierarchy in the Low Gamma band (A17 acting as the persistent Driver, A18 as the Receiver) strongly corroborates current theories of predictive coding and feedforward information routing (VEZOLI et al., 2021).

Furthermore, identifying the Transition Zone (TZ) as a "Dynamic Modulator" that reverses its causal flow upon stimulus onset highlights the necessity of time-resolved directional tools. Anatomically, the TZ boundary is densely innervated by mixed intra-hemispheric projections and transcallosal fibers that align spatial orientation maps across the vertical meridian (SCHMIDT et al., 2023). By switching from a passive sink to an active causal source during the moving grating stimulation, the TZ likely orchestrates the interhemispheric temporal unifications required to track sensory borders crossing visual fields. Static connectivity would have merely averaged this reversal into an indiscernible null-flow, masking a critical operational mechanism of visual processing.

5.5 Overcoming the Computational Scale and Open Science

Translating the theoretical concepts of the Dynome into practical analytical outputs requires overcoming severe computational barriers. Generating stochastic multivariate null models (e.g., surrogate data phase-randomization and configuration models) across continuous sliding windows triggers a combinatorial explosion that typically crashes single-threaded analytical scripts. By orchestrating these routines through a Dask-distributed High-Performance Computing (HPC) backend and utilizing ‘xarray‘ and ‘Zarr‘ for lazy-loading operations, NECTA effectively eliminates the "Big Data" electrophysiology bottleneck.

Equally vital to this computational leap is the adherence to *Open Science* and reproducibility. The rigorous parameterization, GitHub/CodeMeta logging, and containerized deployment of NECTA’s codebase ensure that our analytical workflows are transparent and globally verifiable. This pipeline democratizes complex graph-theoretical analysis, allowing the scientific community to interactively slice and visualize multidimensional connectomes in real-time.

6 CONCLUSÃO

Escreva suas conclusões, limitações do seu trabalho, contribuições, trabalhos futuros, etc.

BIBLIOGRAPHY

ALLEN, E. A. et al. Tracking whole-brain connectivity dynamics in the resting state. *Cerebral cortex*, Oxford University Press, v. 24, n. 3, p. 663–676, 2014.

BASTOS, A. M.; SCHOFFELEN, J.-M. A tutorial review of functional connectivity analysis methods and their interpretational pitfalls. *Frontiers in systems neuroscience*, Frontiers Media SA, v. 9, p. 175, 2015.

KOPELL, N. J. et al. Beyond the connectome: the dynome. *Neuron*, Elsevier, v. 83, n. 6, p. 1319–1328, 2014.

NEUENSCHWANDER, S. et al. On the functional role of gamma synchronization in the retinogeniculate system of the cat. *Journal of Neuroscience*, Soc Neuroscience, v. 43, p. 1550–22, 2023.

SCHMIDT, K. E. et al. Cortical maps as a fundamental neural substrate for visual representation. *Progress in Neurobiology*, Elsevier, p. 102424, 2023.

VEZOLI, J. et al. Cortical hierarchy, dual counterstream architecture and the importance of top-down generative networks. *NeuroImage*, Elsevier, v. 225, p. 117479, 2021.

WUNDERLE, T.; ERIKSSON, D.; SCHMIDT, K. E. Multiplicative mechanism of lateral interactions revealed by controlling interhemispheric input. *Cerebral cortex*, Oxford University Press, v. 23, n. 4, p. 900–912, 2013.