



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE

Angular Testing

3 - Asynchrony and Mocking

Asynchrony



Potential Problems

- Expects not running
- Timeouts
- Cryptic error messages



Native Approaches

- done callback
- return Promise
- return `expect().resolves`
- `async/await`



done

```
it("should test with done", (done) => {
```

```
  let a = 1;
```

```
  Promise.resolve()
```

```
    .then(() => {
```

```
      a++;
```

```
      expect(a).toBe(1);
```

```
    })
```

```
    .then(done, done);
```

```
});
```



return the Promise

```
it("should return the promise", () => {
```

```
  let a = 1;
```

```
  return Promise.resolve().then(() => {
```

```
    a++;
```

```
    expect(a).toBe(2);
```

```
  });
```

```
});
```



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE

return expect().resolves

```
it("should test with expect.resolves", () => {
```

```
  let a = 1;
```

```
  const promise = Promise.resolve().then(() => a + 1);
```

```
  return expect(promise).resolves.toBe(2);
```

```
});
```



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE

Use async/await

```
it("should test with done", async () => {
```

```
  let a = 1;
```

```
  await Promise.resolve().then(() => {
```

```
    a++;
```

```
  });
```

```
  expect(a).toBe(2);
```

```
});
```



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE

Angular-based Approaches

- **waitForAsync**: automatic done callback
- **fakeAsync**: transforms async to sync task
 - flushMicrotasks: run all microtasks
 - tick: move forward in time
 - flush: run all asynchronous tasks (skips periodic timers)



waitForAsync: Automatic done callback

```
test('async', waitForAsync(() => {  
  expect.hasAssertions();  
  let a = 1;  
  Promise.resolve().then(() => {  
    a++;  
    expect(a).toBe(2);  
  });  
  
  window.setTimeout(() => {  
    a++;  
    expect(a).toBe(3);  
  }, 1000);  
}))  
);
```



fakeAsync: Turn asynchrony into synchrony

```
test("microtasks", fakeAsync(() => {  
  let a = 1;  
  
  Promise.resolve().then(() => (a = 2));  
  
  expect(a).toBe(1);  
  
  flushMicrotasks();  
  
  expect(a).toBe(2);  
}));
```



fakeAsync

```
test("immediate macrotasks", fakeAsync(() => {  
  let a = 1;  
  window.setTimeout(() => (a = 2));  
  expect(a).toBe(1);  
  
  tick();  
  expect(a).toBe(2);  
}));
```



fakeAsync

```
test("delayed macrotasks", fakeAsync(() => {  
  let a = 1;  
  window.setTimeout(() => (a = 2), 2000);  
  expect(a).toBe(1);  
  
  tick(2000);  
  expect(a).toBe(2);  
}), 1000);
```



fakeAsync

```
test("delayed macrotasks", fakeAsync(() => {  
  let a = 1;  
  window.setTimeout(() => (a = 2), 2000);  
  expect(a).toBe(1);  
  
  flush();  
  expect(a).toBe(2);  
}), 1000);
```




Why fakeAsync over waitForAsync?

1. Run unreachable asynchronous tasks
2. Assertion at the end (AAA pattern)
3. No remaining macrotasks as "implicit" assertion




Mocking (Test Doubles)



ANGULAR
ARCHITECTS
INSIDE KNOWLEDGE

Stub



Mock



Two Types (Academic)

1. Stub: Replaces a dependency
 - a. When dependency returns a value
 - b. e.g. HTTP Request
 - c. Is enough in most cases
 - d. Test doesn't verify the stub is called
2. Mock: Verifies a call to a dependency
 - a. A "side-effect only" dependency
 - b. Usage has to be verified
 - c. e.g. SnackBar, Router navigation
 - d. Test verifies the mock is called



```
export class ValidAddressLookuper {  
  constructor(  
    private addresses: () => AddressSource[],  
    private addressValidator: AddressValidatorService  
  ) {}  
  
  lookup(query: string): boolean {  
    return this.addresses()  
      .filter((addressSource) => this.addressValidator.isValidAddress(addressSource))  
      .some((address) => address.value.startsWith(query));  
  }  
}
```



Stub

```
it('should stub validator', () => {  
  const validator = { isValidAddress: () => true };  
  const lookuper = new ValidAddressLookuper(  
    () => [  
      {  
        value: 'Domgasse 5',  
        expiryDate: new Date(2000, 0, 1)  
      }  
    ],  
    validator as AddressValidatorService  
  );  
  
  expect(lookuper.lookup('Domgasse 5')).toBe(true);  
});
```




Mocking Functions

return value

arguments of functions

```
const validatorFn = jest.fn<boolean, [AddressSource]>(  
  (addressSource) => true  
)  
);
```

optional implementation



Mock

```
it('should mock validator', () => {  
  const validator = { isValidAddress: jest.fn<boolean, [AddressSource]>(() => true) };  
  const lookuper = new ValidAddressLookuper(  
    () => [  
      {  
        value: 'Domgasse 5',  
        expiryDate: new Date(2000, 0, 1)  
      }  
    ],  
    validator as AddressValidatorService  
  );  
  
  expect(lookuper.lookup('Domgasse 5')).toBe(true);  
});
```



Mock

```
it('should mock validator', () => {  
  const validator = { isValidAddress: jest.fn<boolean, [AddressSource]>(() => true) };  
  const lookuper = new ValidAddressLookuper(  
    () => [  
      {  
        value: 'Domgasse 5',  
        expiryDate: new Date(2000, 0, 1)  
      }  
    ],  
    validator as AddressValidatorService  
  );  
  
  lookuper.lookup('Domgasse 5')  
  
expect(lookuper.lookup('Domgasse 5')).toBe(true);  
});
```



Mock

```
it('should mock validator', () => {  
  const validator = { isValidAddress: jest.fn(() => true) };  
  const lookuper = new ValidAddressLookuper(  
    () => [  
      {  
        value: 'Domgasse 5',  
        expiryDate: new Date(2000, 0, 1)  
      }  
    ],  
    validator as AddressValidatorService  
  );  
  
  lookuper.lookup('Domgasse 5')  
  
  expect(validator.isValidAddress).toBeCalled();  
});
```



Mock

```
it('should mock validator', () => {  
  const validator = { isValidAddress: jest.fn(() => true) };  
  const lookuper = new ValidAddressLookuper(  
    () => [  
      {  
        value: 'Domgasse 5',  
        expiryDate: new Date(2000, 0, 1)  
      }  
    ],  
    validator as AddressValidatorService  
  );  
  
  lookuper.lookup('Domgasse 5')  
  
  expect(validator.isValidAddress).toBeCalledWith({  
    value: 'Domgasse 5',  
    expiryDate: new Date(2000, 0, 1)  
  });  
});
```



Mock



```
it('should mock validator', () => {  
  const validator = { isValidAddress: jest.fn<boolean, [AddressSource]>(() => true) };  
  const lookuper = new ValidAddressLookuper(  
    () => [  
      {  
        value: 'Domgasse 5',  
        expiryDate: new Date(2000, 0, 1)  
      }  
    ],  
    validator as AddressValidatorService  
  );  
  
  lookuper.lookup('Domgasse 5')  
  
  expect(validator.isValidAddress.mock.calls[0][0].value).toBe('Domgasse 5');  
});
```



Spying

```
it('should check with spied validator', () => {  
  const addressValidator = new AddressValidator();  
  const validatorSpy = jest.spyOn(addressValidator, 'isValidAddress');  
  const addresses = ['Domgasse 15, 1010 Wien'];  
  const lookuper = new AddressLookuper(() => addresses, addressValidator);  
  
  lookuper.lookup('Domgasse 15');  
  
  expect(validatorSpy).toHaveBeenCalledWith('Domgasse 15, 1010 Wien');  
});
```





Spy = Mocking in Jasmine

- Can be wrapped around a function or property
- Saves history of calls along their arguments
- Returns undefined by default
- Allows to replace implementation (fake) dynamically



Spy Strategy - Behaviours

`spy.and.`

- **stub**: default
- `callThrough`: uses original implementation
- `fake`: uses alternative implementation
- `returnValue` / `returnValues`: value or list of values to be returned



Factory methods

- `spyOn`
 - requires an object
 - attaches spy on one method
- `jasmine.createSpy`
 - used when dealing with functions
- `jasmine.createSpyObj`
 - creates an object with multiple spied functions



Spy in Action

```
it('should mock with spyOn', () => {  
  const validator = { isValid: (query) => query === 'Domgasse 5' };  
  const spy = spyOn(validator, 'isValid');  
  
  expect(validator.isValid('Domgasse 5')).toBeUndefined();  
  expect(spy).toHaveBeenCalledWith('Domgasse 5');  
  
  spy.and.callThrough();  
  expect(validator.isValid('Domgasse 5')).toBeTrue();  
  
  spy.and.callFake((query) => query === 'Domgasse 15');  
  expect(validator.isValid('Domgasse 15')).toBeTrue();  
  expect(validator.isValid('Domgasse 5')).toBeFalse();  
  
  spy.and.returnValue(true);  
  expect(validator.isValid('unknown')).toBeTrue();  
});
```



inject() & TestBed

- `inject()` as successor to constructor-based DI
- `inject()` cannot be mocked
- `TestBed.inject(Class)` lets Angular instantiate Class
- `TestBed.configureTestingModule(`

```
    {providers: [  
      {provide: Class, useValue: mock}  
    ]}  
  )
```

- Overrides default services
- Is not typesafe



Lab Time

