



| | | | |
|-----------------------------------|------------------------------------|---------------|-----------|
| Confidentiality Class | External Confidentiality Label | Document Type | Page |
| Ericsson Internal | | User Guide | 1 (24) |
| Prepared By (Subject Responsible) | Approved By (Document Responsible) | Checked | |
| EJAITUR Jaime Tur | | | |
| Document Number | Revision | Date | Reference |
| 0.7.3 | 0.7.3 | 2026-02-16 | |

SSB Retuning Automations - User Guide



| | | | |
|-----------------------------------|------------------------------------|---------------|-----------|
| Confidentiality Class | External Confidentiality Label | Document Type | Page |
| Ericsson Internal | | User Guide | 2 (24) |
| Prepared By (Subject Responsible) | Approved By (Document Responsible) | Checked | |
| EJAITUR Jaime Tur | | | |
| Document Number | Revision | Date | Reference |
| 0.7.3 | 0.7.3 | 2026-02-16 | |



Contents

| | | |
|----------|---|-----------|
| 1 | Tool overview | 4 |
| 2 | Repository technical architecture..... | 5 |
| 2.1 | Main files..... | 5 |
| 2.1.1 | Orchestration core..... | 5 |
| 2.1.2 | Main modules files | 5 |
| 2.1.3 | Common layer and utilities | 5 |
| 3 | Inputs, outputs, and content per module..... | 6 |
| 3.1 | Module 0 — Update Network Frequencies | 6 |
| 3.1.1 | Input | 6 |
| 3.1.2 | Process..... | 6 |
| 3.1.3 | Output..... | 6 |
| 3.1.4 | Detailed implementation notes | 6 |
| 3.1.5 | Impact on GUI and Web Interface | 6 |
| 3.2 | Module 1 — Configuration Audit & Logs Parser | 7 |
| 3.2.1 | Inputs | 7 |
| 3.2.2 | Process..... | 7 |
| 3.2.3 | Outputs | 7 |
| 3.2.4 | Main semantic content | 8 |
| 3.3 | Module 2 — Consistency Check (Pre/Post) | 8 |
| 3.3.1 | Inputs | 8 |
| 3.3.2 | Process..... | 8 |
| 3.3.3 | Outputs | 9 |
| 3.4 | Module 3 — Consistency Check Bulk | 9 |
| 3.4.1 | Inputs | 9 |
| 3.4.2 | Process..... | 9 |
| 3.4.3 | Outputs | 9 |
| 3.5 | Module 4 — Final Clean-Up..... | 10 |
| 3.5.1 | Inputs | 10 |
| 3.5.2 | Process..... | 10 |
| 3.5.3 | Outputs | 10 |
| 4 | Configuration Audit module in detail | 11 |
| 4.1 | SummaryAudit checks philosophy..... | 11 |
| 4.2 | Operational meaning of SummaryAudit rows | 11 |
| 4.3 | SummaryAudit checks catalog | 11 |
| 4.3.1 | MeContext Audit..... | 11 |
| 4.3.2 | NR Frequency Audit / NR Frequency Inconsistencies | 11 |
| 4.3.3 | LTE Frequency Audit / LTE Frequency Inconsistencies | 12 |
| 4.3.4 | ENDC Audit / ENDC Inconsistencies..... | 12 |
| 4.3.5 | Cardinalities Audit / Inconsistencies | 13 |
| 4.3.6 | Profiles Audit (if enabled)..... | 13 |

| | | | |
|-----------------------------------|------------------------------------|---------------|-----------|
| Confidentiality Class | External Confidentiality Label | Document Type | Page |
| Ericsson Internal | | User Guide | 3 (24) |
| Prepared By (Subject Responsible) | Approved By (Document Responsible) | Checked | |
| EJAITUR Jaime Tur | | | |
| Document Number | Revision | Date | Reference |
| 0.7.3 | 0.7.3 | 2026-02-16 | |



| | | |
|-----------|---|-----------|
| 4.4 | Detailed check execution order and gating rules..... | 13 |
| 4.5 | Additional columns injected into parsed MO sheets..... | 14 |
| 4.5.1 | "MeContext" enrichment (main planning helper) | 14 |
| 4.5.2 | "NRCellRelation" and "GUtranCellRelation" enrichment | 15 |
| 4.5.3 | "ExternalNRCellCU" and "ExternalGUtranCell" enrichment | 15 |
| 4.5.4 | "TermPointToGNodeB" / "TermPointToGNB" enrichment..... | 15 |
| 4.6 | Key SummaryAudit checks by source table (implementation-level) | 15 |
| 5 | Consistency Check module in detail | 18 |
| 5.1 | Filtering by non-retuned nodes | 18 |
| 5.2 | How it detects parameter discrepancies..... | 18 |
| 5.3 | How it detects frequency discrepancies..... | 18 |
| 5.4 | How it detects neighbor discrepancies..... | 18 |
| 5.5 | Content of each ConsistencyChecks output sheet..... | 19 |
| 6 | Input requirements and operational best practices | 20 |
| 7 | Execution Modes and Versioning | 21 |
| 8 | Known limitations and considerations..... | 22 |
| 9 | Quick module reference | 23 |
| 10 | Additional documentation recommendations (detected gaps) | 24 |

Document Title: *SSB Retuning Automations - User Guide*

Document Name (type of document): *USER GUIDE*

Document No (decimal class): *198 17-<product number> Uen*

(do this after the document is imported into EriDoc using **Assign Document Number** function).

| | | | |
|-----------------------------------|------------------------------------|---------------|-----------|
| Confidentiality Class | External Confidentiality Label | Document Type | Page |
| Ericsson Internal | | User Guide | 4 (24) |
| Prepared By (Subject Responsible) | Approved By (Document Responsible) | Checked | |
| EJAITUR Jaime Tur | | | |
| Document Number | Revision | Date | Reference |
| 0.7.3 | 0.7.3 | 2026-02-16 | |



Technical User Guide — SSB Retuning Automations

1 Tool overview

SSB Retuning Automations is an automation platform for SSB retuning projects that can run in GUI or CLI mode or through a Web Interface (using a server/client infrastructure) and orchestrates five functional modules:

- **Module 0:** Update Network Frequencies.
- **Module 1:** Configuration Audit & Logs Parser.
- **Module 2:** Consistency Check (manual Pre/Post).
- **Module 3:** Consistency Check Bulk (automatic Pre/Post detection by market).
- **Module 4:** Final Clean-Up.

The main execution lives in "src/SSB_RetuningAutomations.py", where CLI arguments, GUI, configuration persistence, input resolution (folders/ZIP), per-module execution, and artifact versioning are managed.

| | | | |
|-----------------------------------|------------------------------------|---------------|-----------|
| Confidentiality Class | External Confidentiality Label | Document Type | Page |
| Ericsson Internal | | User Guide | 5 (24) |
| Prepared By (Subject Responsible) | Approved By (Document Responsible) | Checked | |
| EJAITUR Jaime Tur | | | |
| Document Number | Revision | Date | Reference |
| 0.7.3 | 0.7.3 | 2026-02-16 | |



2 Repository technical architecture

2.1 Main files

2.1.1 Orchestration core

- "src/SSB_RetuningAutomations.py": entry point, CLI/GUI parsing, module routing, batch/bulk execution, and versioning.

2.1.2 Main modules files

- "src/modules/ConfigurationAudit/ConfigurationAudit.py": log parsing and audit workbook construction (Excel + PPT).
- "src/modules/ConfigurationAudit/ca_summary_excel.py": assembly of "SummaryAudit" and discrepancy dataframes.
- "src/modules/ConsistencyChecks/ConsistencyChecks.py": PRE/POST loading, relation comparison, discrepancies, and output export.
- "src/modules/ProfilesAudit/ProfilesAudit.py": profiles audit (integrated into module 1).
- "src/modules/CleanUp/FinalCleanUp.py": final clean-up (base implementation for extension).

2.1.3 Common layer and utilities

- "src/modules/Common/*.py": correction command logic and shared functions.
- "src/utls/*.py": IO, parsing, frequency handling, Excel, pivots, sorting, infrastructure, and timing.

| | | | |
|-----------------------------------|------------------------------------|---------------|-----------|
| Confidentiality Class | External Confidentiality Label | Document Type | Page |
| Ericsson Internal | | User Guide | 6 (24) |
| Prepared By (Subject Responsible) | Approved By (Document Responsible) | Checked | |
| EJAITUR Jaime Tur | | | |
| Document Number | Revision | Date | Reference |
| 0.7.3 | 0.7.3 | 2026-02-16 | |



3 Inputs, outputs, and content per module

3.1 Module 0 — Update Network Frequencies

3.1.1 Input

- Input folder (may contain subfolders/ZIPs already supported by the IO layer).
- Logs with an "NRFrequency" table and the "arfcnValueNRDI" column.

3.1.2 Process

1. Scan logs and detects "NRFrequency" blocks.
2. Extracts numeric values from "arfcnValueNRDI".
3. Removes duplicates and sorts frequencies.
4. Updates the persisted "Network frequencies" configuration for GUI/CLI.

3.1.3 Output

- Does not generate Excel/PPT.
- Updates the persisted network frequency value used for filtering and selection in later runs.

3.1.4 Detailed implementation notes

- The module reuses the same input resolver used by the other modules ("ensure_logs_available"), so it can consume either plain folders or folders containing ZIPs without changing operator workflow.
- It scans **all** detected logs, slices each "SubNetwork" block, and processes only blocks where MO name is exactly "NRFrequency".
- Inside each "NRFrequency" block, it reads "arfcnValueNRDI", keeps only strictly numeric values, deduplicates, and sorts numerically.
- The resulting list is persisted to "config.cfg" in "network_frequencies" and also loaded in-memory into the "NETWORK_FREQUENCIES" global list.
- In practice, this module should be executed after collecting representative logs from the network and then only when new frequencies are introduced. For stable markets, running it once is usually enough.

3.1.5 Impact on GUI and Web Interface

- **Desktop GUI:** when launching in GUI mode (no CLI args), the app loads "network_frequencies" from "config.cfg" and uses that list as the selectable values shown to users.

| | | | |
|-----------------------------------|------------------------------------|---------------|-----------|
| Confidentiality Class | External Confidentiality Label | Document Type | Page |
| Ericsson Internal | | User Guide | 7 (24) |
| Prepared By (Subject Responsible) | Approved By (Document Responsible) | Checked | |
| EJAITUR Jaime Tur | | | |
| Document Number | Revision | Date | Reference |
| 0.7.3 | 0.7.3 | 2026-02-16 | |



- **Web Interface:** the backend endpoint loading defaults first tries persisted "network_frequencies"; if empty, it falls back to parsing the hardcoded defaults from "SSB_RetuningAutomations.py".
- This means Module 0 is the canonical mechanism to keep both interfaces aligned with real network frequency inventory.

3.2 Module 1 — Configuration Audit & Logs Parser

3.2.1 Inputs

- Input folder with logs (".log", ".logs", ".txt") or ZIPs resolvable by utilities.
- Frequency parameters:
 - "n77_ssb_pre"
 - "n77_ssb_post"
 - "n77b_ssb"
- allowed SSB/ARFCN lists pre/post.
- Flags:
 - "profiles_audit"
 - "frequency_audit"
 - "export_correction_cmd"
 - "fast_excel_export".

3.2.2 Process

1. Parses files and extracts MO tables by "SubNetwork" blocks.
2. Generates one sheet per detected table.
3. Builds "SummaryAudit" + pivots/auxiliary summaries.
4. Runs profiles audit if enabled.
5. Exports CA correction commands if requested.
6. Generates the summary PPT.

3.2.3 Outputs

- Folder "ConfigurationAudit_<timestamp>_v<version>/".
- Excel file "ConfigurationAudit_<timestamp>_v<version>.xlsx":

| | | | |
|-----------------------------------|------------------------------------|---------------|-----------|
| Confidentiality Class | External Confidentiality Label | Document Type | Page |
| Ericsson Internal | | User Guide | 8 (24) |
| Prepared By (Subject Responsible) | Approved By (Document Responsible) | Checked | |
| EJAITUR Jaime Tur | | | |
| Document Number | Revision | Date | Reference |
| 0.7.3 | 0.7.3 | 2026-02-16 | |



- Sheets for each parsed MO table.
- "SummaryAudit".
- NR/LTE parameter discrepancy sheets.
- Summary/pivot sheets by frequencies and relations.
- PPT file "ConfigurationAudit_<timestamp>_v<version>.pptx".
- Optional folder "Correction_Cmd_CA/" with AMOS commands.

3.2.4 Main semantic content

- **SummaryAudit** contains rows with:
- "Category", "SubCategory", "Metric", "Value", "ExtraInfo",
- and execution context fields (stage, module, etc. depending on the flow).
- "Value" usually represents a count of impacted nodes/cells/relations.
- "ExtraInfo" contains the NodeId list or a compact discrepancy detail.

3.3 Module 2 — Consistency Check (Pre/Post)

3.3.1 Inputs

- "input_pre" and "input_post" (or equivalent resolved structure).
- Frequencies "n77_ssb_pre" and "n77_ssb_post".
- Optional reference to PRE and POST "ConfigurationAudit" to enrich target classification.
- Optional list of frequency filters ("cc_freq_filters").

3.3.2 Process

1. Loads relation tables ("GUtranCellRelation", "NRCellRelation").
2. Normalizes columns/keys and selects the most recent snapshots by date.
3. Detect:

- new relations,
- missing relations,
- parameter discrepancies,
- frequency discrepancies,

| | | | |
|-----------------------------------|------------------------------------|---------------|-----------|
| Confidentiality Class | External Confidentiality Label | Document Type | Page |
| Ericsson Internal | | User Guide | 9 (24) |
| Prepared By (Subject Responsible) | Approved By (Document Responsible) | Checked | |
| EJAITUR Jaime Tur | | | |
| Document Number | Revision | Date | Reference |
| 0.7.3 | 0.7.3 | 2026-02-16 | |



- summary by PRE/POST frequency pair.

4. Classify destination targets as "SSB-Pre", "SSB-Post" or "Unknown".

5. Exports detailed Excel outputs and correction commands.

3.3.3 Outputs

- "CellRelation_<timestamp>_v<version>.xlsx" (end-to-end relations view).
- "ConsistencyChecks_CellRelation_<timestamp>_v<version>.xlsx" with:
 - "Summary"
 - "SummaryAuditComparisson" (if there is PRE/POST SummaryAudit)
 - "Summary_CellRelation"
 - GU blocks: "GU_relations", "GU_param_disc", "GU_freq_disc", "GU_freq_disc_unknown", "GU_missing", "GU_new"
 - NR blocks: "NR_relations", "NR_param_disc", "NR_freq_disc", "NR_freq_disc_unknown", "NR_missing", "NR_new"
 - optional "GU_all", "NR_all".
 - "Correction_Cmd_CC/" with commands per type (new/missing/discrepancies).

3.4 Module 3 — Consistency Check Bulk

3.4.1 Inputs

- Root folder with subfolders like "yyyymmdd_hhmm_step0" (optionally nested by market).

3.4.2 Process

1. Detects PRE/POST candidates by the most appropriate date/time.
2. Excludes folders using a blacklist ("ignore", "old", "bad", "partial", "incomplete", "discard", etc.).
3. Runs Module 2 for each detected market.

3.4.3 Outputs

- Same output structure as module 2, per market.
- Traceability file "FoldersCompared.txt".

| | | | |
|-----------------------------------|------------------------------------|---------------|-----------|
| Confidentiality Class | External Confidentiality Label | Document Type | Page |
| Ericsson Internal | | User Guide | 10 (24) |
| Prepared By (Subject Responsible) | Approved By (Document Responsible) | Checked | |
| EJAITUR Jaime Tur | | | |
| Document Number | Revision | Date | Reference |
| 0.7.3 | 0.7.3 | 2026-02-16 | |



3.5 Module 4 — Final Clean-Up

3.5.1 Inputs

- Final retune working folder.

3.5.2 Process

- Executes final cleanup policies (structure prepared to expand rules).

3.5.3 Outputs

- Versioned cleanup directory according to the active implementation.

| | | | |
|-----------------------------------|------------------------------------|---------------|-----------|
| Confidentiality Class | External Confidentiality Label | Document Type | Page |
| Ericsson Internal | | User Guide | 11 (24) |
| Prepared By (Subject Responsible) | Approved By (Document Responsible) | Checked | |
| EJAITUR Jaime Tur | | | |
| Document Number | Revision | Date | Reference |
| 0.7.3 | 0.7.3 | 2026-02-16 | |



4 Configuration Audit module in detail

4.1 SummaryAudit checks philosophy

SummaryAudit sheet contains a high-level checks table by categories. The flow:

1. Excludes "UNSYNCHRONIZED" nodes based on "MeContext".
2. Evaluates NR, LTE, ENDC, Externals, TermPoints, cardinalities, and profiles.
3. Records each check as a row ("Category/SubCategory/Metric/Value/ExtraInfo").

4.2 Operational meaning of SummaryAudit rows

- **Category:** audited technical domain (NR/LTE/ENDC/MeContext/etc.).
- **SubCategory:** type of analysis (Audit/Inconsistencies/Profiles).
- **Metric:** specific rule evaluated.
- **Value:**
 - Integer: number of affected nodes/relations/cells.
 - "N/A": not evaluable due to missing columns.
 - Text: captured status or error.
 - **ExtraInfo:** list of nodes or bounded detail for troubleshooting.

4.3 SummaryAudit checks catalog

4.3.1 MeContext Audit

- total unique nodes and unsynchronized node exclusion.
- "UNSYNCHRONIZED" nodes (excluded from the rest of the audits).

4.3.2 NR Frequency Audit / NR Frequency Inconsistencies

Source tables: "NRCellIDU", "NRFrequency", "NRFreqRelation", "NRSectorCarrier", "NRCellRelation", "ExternalNRCellICU", "TermPointToGNodeB", "TermPointToGNB".

Main checks:

- Detection of NR nodes with N77 SSB (band 646600–660000).
- Classification of NR nodes as LowMidBand / mmWave / mixed.
- Nodes whose N77 SSBs are fully within allowed PRE or POST lists.

| | | | |
|-----------------------------------|------------------------------------|---------------|-----------|
| Confidentiality Class | External Confidentiality Label | Document Type | Page |
| Ericsson Internal | | User Guide | 12 (24) |
| Prepared By (Subject Responsible) | Approved By (Document Responsible) | Checked | |
| EJAITUR Jaime Tur | | | |
| Document Number | Revision | Date | Reference |
| 0.7.3 | 0.7.3 | 2026-02-16 | |



- Nodes with N77 SSB outside allowed lists.
- Old/new SSB presence per node (only old, only new, both).
- Nodes with NRFreqRelationId in an unexpected format (auto-created outside convention).
- NR relations to old/new SSB.
- NR externals and termpoints pointing to old/new/unknown.

Typical triggering:

- Each check is enabled if the table and minimum required columns exist.
- If columns are missing, a "N/A" status row is added.
- If the table is empty or not found, an informative row "Table not found or empty" is added.

Interpretation:

- "Value > 0" in inconsistencies indicates a real deviation that requires investigation.
- "ExtraInfo" typically lists affected nodes for operational targeting.

4.3.3 LTE Frequency Audit / LTE Frequency Inconsistencies

Source tables: "GUtranSyncSignalFrequency", "GUtranFreqRelation", "GUtranCellRelation", "ExternalGUtranCell", "TermPointToENodeB".

Main checks:

- LTE nodes with old/new SSB.
- Nodes with both old/new or old without new.
- SSB outside the expected pre/post set.
- LTE relations to old/new and parameter discrepancies per cell relation.
- LTE externals OUT_OF_SERVICE for old/new.

4.3.4 ENDC Audit / ENDC Inconsistencies

Source tables: "EndcDistrProfile", "FreqPrioNR".

Main checks:

| | | | |
|-----------------------------------|------------------------------------|---------------|-----------|
| Confidentiality Class | External Confidentiality Label | Document Type | Page |
| Ericsson Internal | | User Guide | 13 (24) |
| Prepared By (Subject Responsible) | Approved By (Document Responsible) | Checked | |
| EJAITUR Jaime Tur | | | |
| Document Number | Revision | Date | Reference |
| 0.7.3 | 0.7.3 | 2026-02-16 | |



- "gUtranFreqRef" and "mandatoryGUtranFreqRef" with old/new + N77B combinations.
- Nodes that do not contain the expected frequency combination.
- In "FreqPrioNR": old without new, both present, and parameter mismatch per cell.

4.3.5 Cardinalities Audit / Inconsistencies

Cardinality checks per relation table (per node and/or per cell) to detect overprovisioning or gaps versus expected limits.

4.3.6 Profiles Audit (if enabled)

- Compares PRE/POST profiles by supported profile MO.
- Detects parameter discrepancies between old/new variants.
- Adds results to SummaryAudit and auxiliary detail sheets.

4.4 Detailed check execution order and gating rules

1. MeContext pre-processing

- Computes total nodes and "UNSYNCHRONIZED" nodes.
- Builds an exclusion list and filters all other MO dataframes by "NodeId" before running any other checks.

2. Node scoping for Pre/Post interpretation

- "NRCellIDU" checks run first because they generate the rows used to infer node scope (Pre-retune vs Post-retune).
- This scope is reused by relation/externals/termpoint checks to classify targets ("SSB-Pre", "SSB-Post", "Unknown").

3. Per-table processors

- NR processors: "NRFrequency", "NRFreqRelation", "NRSectorCarrier", "NRCellRelation".
- LTE processors: "GUtranSyncSignalFrequency", "GUtranFreqRelation", "GUtranCellRelation".
- Externals/Termpoints: "ExternalNRCellCU", "ExternalGUtranCell", "TermPointToGNodeB", "TermPointToGNB", "TermPointToENodeB".
- ENDC/Cardinality/Profile processors follow and append their own rows.

4. Resilience model

| | | | |
|-----------------------------------|------------------------------------|---------------|-----------|
| Confidentiality Class | External Confidentiality Label | Document Type | Page |
| Ericsson Internal | | User Guide | 14 (24) |
| Prepared By (Subject Responsible) | Approved By (Document Responsible) | Checked | |
| EJAITUR Jaime Tur | | | |
| Document Number | Revision | Date | Reference |
| 0.7.3 | 0.7.3 | 2026-02-16 | |



- If a table is missing/empty: emits "Table not found or empty" metric rows.
- If required columns are missing: emits "N/A" rows.
- If exceptions occur: emits "ERROR: ..." rows without aborting the full SummaryAudit generation.

4.5 Additional columns injected into parsed MO sheets

Besides SummaryAudit, Module 1 enriches several raw MO sheets with operational columns for execution/cleanup.

4.5.1 "MeContext" enrichment (main planning helper)

Additional columns are computed per "NodeId" by aggregating NR/LTE relation tables:

- Topology and inventory:
 - "mmWave Cells", "LowMidBand Cells", "N77 Cells"
 - "N77A old SSB cells", "N77A new SSB cells"
- Relation counters:
 - "NRFreqRelation to old N77A SSB", "NRFreqRelation to new N77A SSB"
 - "GUtranFreqRelation to old N77A SSB", "GUtranFreqRelation to new N77A SSB"
- Priority snapshots (unique consolidated values):
 - "NRFreqRelation to old N77A SSB cellReselPrio"
 - "NRFreqRelation to new N77A SSB cellReselPrio"
 - "GUtranFreqRelation to old N77A SSB cellReselPrio"
 - "GUtranFreqRelation to new N77A SSB cellReselPrio"
 - "GUtranFreqRelation to old N77A SSB EndcPrio"
 - "GUtranFreqRelation to new N77A SSB EndcPrio"
- Workflow recommendation fields:
 - "Step1", "Step2b", "Step2ac", "Next Step", "EndcPrio Next Step"

| | | | |
|-----------------------------------|------------------------------------|---------------|-----------|
| Confidentiality Class | External Confidentiality Label | Document Type | Page |
| Ericsson Internal | | User Guide | 15 (24) |
| Prepared By (Subject Responsible) | Approved By (Document Responsible) | Checked | |
| EJAITUR Jaime Tur | | | |
| Document Number | Revision | Date | Reference |
| 0.7.3 | 0.7.3 | 2026-02-16 | |



Operational interpretation:

- "Step1" focuses on old/new relation parity and reselection-priority convergence.
- "Step2b" focuses on old/new N77A cell presence.
- "Step2ac" focuses on ENDC priority transition validation.
- "Next Step" concatenates pending actions to provide a single execution hint per node.

4.5.2 "NRCellRelation" and "GUtranCellRelation" enrichment

Both relation tables are normalized with helper columns used for discrepancy targeting and command generation:

- "Frequency" extracted from relation references.
- External endpoint decomposition fields (function/cell identifiers parsed from references).
- "GNodeB_SSB_Target" classification ("SSB-Pre"/"SSB-Post"/"Unknown").
- "Correction_Cmd" prebuilt command text for the rows considered actionable.

4.5.3 "ExternalNRCellCU" and "ExternalGUtranCell" enrichment

- Adds "Frequency", "Termpoint", "TermpointStatus", "TermpointConsolidatedStatus".
- Adds "GNodeB_SSB_Target" and "Correction_Cmd" for retune remediation flows.
- For LTE externals, service state ("OUT_OF_SERVICE") is also reflected in SummaryAudit checks.

4.5.4 "TermPointToGNodeB" / "TermPointToGNB" enrichment

- Adds consolidated termpoint health/status fields and "SSB needs update" boolean.
- Adds "GNodeB_SSB_Target" and generated "Correction_Cmd" when target and frequency logic indicates migration to post-retune SSB.

4.6 Key SummaryAudit checks by source table (implementation-level)

Below is the practical checklist implemented by the processors:

- **NRCellIDU:**
- Node classification LowMidBand/mmWave/mixed.
- N77-in-band detection.

| | | | |
|-----------------------------------|------------------------------------|---------------|-----------|
| Confidentiality Class | External Confidentiality Label | Document Type | Page |
| Ericsson Internal | | User Guide | 16 (24) |
| Prepared By (Subject Responsible) | Approved By (Document Responsible) | Checked | |
| EJAITUR Jaime Tur | | | |
| Document Number | Revision | Date | Reference |
| 0.7.3 | 0.7.3 | 2026-02-16 | |



- Allowed pre/post SSB-list compliance and out-of-list inconsistencies.
- **NRFrequency:**
 - old/new/both/old-without-new presence by node.
 - values outside expected old/new sets.
- **NRFreqRelation:**
 - old/new/both/old-without-new relation presence.
 - naming-convention checks for auto-created relation IDs.
 - cell-level old-vs-new parameter mismatch detection.
 - profile reference transition checks (old profile clones vs expected post clone).
- **NRSectorCarrier:**
 - allowed ARFCN list compliance (pre/post).
 - out-of-list inconsistencies.
- **NRCellRelation:**
 - relation counts to old/new targets.
 - extraction/parsing consistency from "nRFreqRelationRef".
- **GUtranSyncSignalFrequency:**
 - old/new/both/old-without-new LTE presence by node.
 - out-of-set inconsistencies.
- **GUtranFreqRelation:**
 - old/new/both/old-without-new checks.
 - naming convention validation ("<ssb>-30-20-0-1" style).
 - old/new cell-level parameter and ENDC priority checks.
- **GUtranCellRelation:**
 - relation counts to old/new LTE targets.

| | | | |
|-----------------------------------|------------------------------------|---------------|-----------|
| Confidentiality Class | External Confidentiality Label | Document Type | Page |
| Ericsson Internal | | User Guide | 17 (24) |
| Prepared By (Subject Responsible) | Approved By (Document Responsible) | Checked | |
| EJAITUR Jaime Tur | | | |
| Document Number | Revision | Date | Reference |
| 0.7.3 | 0.7.3 | 2026-02-16 | |



- **ExternalNRCellICU / ExternalGUTranCell:**
- old/new external references counts.
- target classification and termpoint correlation.
- **TermPoint tables:**
- locked/disabled/unhealthy transport endpoint detection.
- alignment with external-cell update needs.
- **EndcDistrProfile / FreqPrioNR:**
- expected old/new + N77B combinations.
- unexpected combinations and param discrepancies.
- **Cardinality checks:**
- hard-limit and threshold checks per node/cell relation families.
- explicit inconsistency rows when limits are reached/exceeded.

| | | | |
|-----------------------------------|------------------------------------|---------------|-----------|
| Confidentiality Class | External Confidentiality Label | Document Type | Page |
| Ericsson Internal | | User Guide | 18 (24) |
| Prepared By (Subject Responsible) | Approved By (Document Responsible) | Checked | |
| EJAITUR Jaime Tur | | | |
| Document Number | Revision | Date | Reference |
| 0.7.3 | 0.7.3 | 2026-02-16 | |



5 Consistency Check module in detail

5.1 Filtering by non-retuned nodes

If a POST SummaryAudit exists, the module obtains PRE/POST node lists and can exclude discrepancies whose target points to nodes that did not complete retune, reducing operational noise.

5.2 How it detects parameter discrepancies

1. Selects common PRE and POST relations by composite key:
 - GU: typically "NodeId", "EUTranCellFDDId", "GUtranCellRelationId".
 - NR: typically "NodeId", "NRCellCUId", "NRCellRelationId".
2. Excludes control columns (keys, frequency, Pre/Post, Date).
3. Compares value-by-value across shared columns.
4. Sets "ParamDiff=True" if at least one column differs.
5. In GU it ignores "timeOfCreation" and "mobilityStatusNR" to avoid false positives.

5.3 How it detects frequency discrepancies

1. Extracts base frequency from relation references ("extract_gu_freq_base" / "extract_nr_freq_base").
2. Discrepancy rule:
 - if PRE had "freq_before" or "freq_after", and POST does **not** end up in "freq_after", it marks "FreqDiff=True".
3. Classifies the discrepancy as:
 - "FreqDiff_SSBPost" (target identified as SSB-Post),
 - "FreqDiff_Unknown" (cannot be associated to a known target).

5.4 How it detects neighbor discrepancies

They are split into three groups:

- **New relations:** keys present in POST and absent in PRE.
- **Missing relations:** keys present in PRE and absent in POST.
- **Discrepancies:** same key in PRE/POST but with parametric or frequency differences.

| | | | |
|-----------------------------------|------------------------------------|---------------|-----------|
| Confidentiality Class | External Confidentiality Label | Document Type | Page |
| Ericsson Internal | | User Guide | 19 (24) |
| Prepared By (Subject Responsible) | Approved By (Document Responsible) | Checked | |
| EJAITUR Jaime Tur | | | |
| Document Number | Revision | Date | Reference |
| 0.7.3 | 0.7.3 | 2026-02-16 | |



5.5 Content of each ConsistencyChecks output sheet

- **Summary:** KPIs per table (PRE/POST volume, discrepancies, new/missing, source files).
- **SummaryAuditComparisson:** diff of SummaryAudit PRE vs POST metrics (without "ExtraInfo" to keep the comparison clean).
- **Summary_CellRelation:** KPI per "Freq_Pre/Freq_Post" pair and per technology.
- **GU_relations / NR_relations:** relation universe enriched with target classification and command snippets.
- **GU_param_disc / NR_param_disc:** common relations with param differences.
- **GU_freq_disc / NR_freq_disc:** frequency discrepancies to SSB-Post targets.
- **GU_freq_disc_unknown / NR_freq_disc_unknown:** discrepancies with non-classifiable targets.
- **GU_missing / NR_missing:** relations removed versus PRE.
- **GU_new / NR_new:** relations added in POST.
- **GU_all / NR_all:** optional consolidated dump for extended analysis.

| | | | |
|-----------------------------------|------------------------------------|---------------|-----------|
| Confidentiality Class | External Confidentiality Label | Document Type | Page |
| Ericsson Internal | | User Guide | 20 (24) |
| Prepared By (Subject Responsible) | Approved By (Document Responsible) | Checked | |
| EJAITUR Jaime Tur | | | |
| Document Number | Revision | Date | Reference |
| 0.7.3 | 0.7.3 | 2026-02-16 | |



6 Input requirements and operational best practices

- Keep market log exports in a consistent structure (especially for bulk).
- Validate that PRE/POST have the same table granularity and consistent naming.
- Validate frequency inputs ("n77_ssb_pre", "n77_ssb_post", "n77b_ssb") before batch execution.
- Correctly configure allowed SSB/ARFCN lists to minimize false positives.
- Run **Configuration Audit** before Consistency Checks whenever possible.
- Use Bulk mode only with a controlled folder naming convention.
- Review "Summary" and "Summary_CellRelation" first, then then deep-dive into detail sheets (ConfigurationAudit) and discrepancy tabs (ConsistencyCheck).
- Consume "Correction_Cmd_CA" and "Correction_Cmd_CC" as a remediation proposal, not as blind execution.

| | | | |
|-----------------------------------|------------------------------------|---------------|-----------|
| Confidentiality Class | External Confidentiality Label | Document Type | Page |
| Ericsson Internal | | User Guide | 21 (24) |
| Prepared By (Subject Responsible) | Approved By (Document Responsible) | | Checked |
| EJAITUR Jaime Tur | | | |
| Document Number | Revision | Date | Reference |
| 0.7.3 | 0.7.3 | 2026-02-16 | |



7 Execution Modes and Versioning

- **GUI mode:** run without CLI arguments.
- **CLI mode:** run with explicit module and options.
- **Web Interface:** the tool can be run in a server/client infrastructure, accessing the server through a Web Interface where you can upload your inputs, enqueue different tasks and export the results when finish..

All Generated artifacts include a versioned suffix: "<timestamp>_v<TOOL_VERSION>".

This guarantees traceability and avoids collisions between runs.

| | | | |
|-----------------------------------|------------------------------------|---------------|-----------|
| Confidentiality Class | External Confidentiality Label | Document Type | Page |
| Ericsson Internal | | User Guide | 22 (24) |
| Prepared By (Subject Responsible) | Approved By (Document Responsible) | Checked | |
| EJAITUR Jaime Tur | | | |
| Document Number | Revision | Date | Reference |
| 0.7.3 | 0.7.3 | 2026-02-16 | |



8 Known limitations and considerations

- The engine depends on log quality and structure: missing columns downgrade checks to "N/A".
- Some rules depend on naming conventions in references (NR/GU relation refs).
- The Final Clean-Up module is prepared to extend operation-specific policies.

| | | | |
|-----------------------------------|------------------------------------|---------------|-----------|
| Confidentiality Class | External Confidentiality Label | Document Type | Page |
| Ericsson Internal | | User Guide | 23 (24) |
| Prepared By (Subject Responsible) | Approved By (Document Responsible) | Checked | |
| EJAITUR Jaime Tur | | | |
| Document Number | Revision | Date | Reference |
| 0.7.3 | 0.7.3 | 2026-02-16 | |



9 Quick module reference

| Module | Main input | Main output | Goal |
|------------------------------|--------------------------|-----------------------------|----------------------------------|
| 0 Update Network Frequencies | Logs folder | Persisted config | Update network frequency list |
| 1 Configuration Audit | Logs/ZIP folder | Excel + PPT + CA commands | Audit configuration and profiles |
| 2 Consistency Check | PRE and POST folders | 2 Excel + CC commands | Compare pre/post relations |
| 3 Consistency Check (Bulk) | Multi-market root folder | Module 2 outputs per market | Run bulk comparison |
| 4 Final Clean-Up | Final folder | Clean-up folder | Operational final clean-up |

| | | | |
|-----------------------------------|------------------------------------|---------------|-----------|
| Confidentiality Class | External Confidentiality Label | Document Type | Page |
| Ericsson Internal | | User Guide | 24 (24) |
| Prepared By (Subject Responsible) | Approved By (Document Responsible) | Checked | |
| EJAITUR Jaime Tur | | | |
| Document Number | Revision | Date | Reference |
| 0.7.3 | 0.7.3 | 2026-02-16 | |



10

Additional documentation recommendations (detected gaps)

To keep the guide aligned with the real behavior, these areas are also important to document in future iterations:

- Explicit mapping of each "SummaryAudit" metric to its correction-command export sheet/folder.
- Full decision table for "Step1/Step2b/Step2ac" outcomes and expected operator actions.
- Cardinality thresholds per MO (including rationale and vendor constraints).
- Frequency-audit feature toggle behavior ("frequency_audit") and which checks are suppressed when disabled.
- Detailed limitations of reference parsing when vendor naming conventions are not respected.